Detecting Incorrect Visual Demonstrations for Improved Policy Learning

Abstract: Learning tasks only from raw video demonstrations is the current state of the art in robotics visual imitation learning research. The implicit assumption here is that all video demonstrations show an optimal/near-optimal way of performing the task. What if that is not true? What if one or more videos show a wrong way of executing the task? A task policy learned from such incorrect demonstrations can be potentially unsafe for robots and humans. It is therefore important to analyze the video demonstrations for correctness before handing them over to the policy learning algorithm. This is a challenging task, especially due to the very large state space. This paper proposes a framework to autonomously detect incorrect video demonstrations of sequential tasks consisting of several sub-tasks. We analyze the demonstration pool to identify video(s) for which task-features follow a 'disruptive' sequence. We analyze entropy to measure this disruption and – through solving a *minmax* problem – assign poor weights to incorrect videos. We evaluated the framework with two real-world video datasets: our custom-designed *Tea-Making with a YuMi robot* [1] and the publicly available *50-Salads* [2]. Experimental results show the effectiveness of the proposed framework in detecting incorrect video demonstrations even when they make up 40% of the demonstration set. We also show that various state-of-the-art imitation learning algorithms learn a better policy when incorrect demonstrations are discarded from the training pool.

Keywords: Imitation Learning, Visual Demonstrations, Incorrect Demonstrations

1 Introduction

Visual imitation learning (VIL) [1, 2, 3, 4] – where tasks are learned from raw video demonstrations– is probably the most feasible way for lay users to teach robots new skills in natural settings. VIL however is challenging, especially due to very high dimensional state space. VIL algorithms are generally evaluated in controlled laboratory settings [4, 5, 6, 7, 8, 9] or simulated environments [10, 11, 12, 13, 14], where the assumption that all video demonstrations are optimal/ near-optimal is possible to maintain. In reality, lay users will make inadvertent errors while demonstrating a task due to reasons including fatigue, presence of distractions, and lack of knowledge on robot learning mechanism. For example, it is not unusual to forget to turn-off the oven once or twice – e.g., because the phone rang – out of the ten times a user was showing the robot how to make a cup of tea. Unless a robotics expert carefully curates the videos, a policy learning algorithm can learn a potentially unsafe tea-making policy – that it is ok to keep the oven on – from these video demonstrations. It is therefore important to automatically analyze video demonstrations for correctness before policy learning takes place. This paper proposes a framework for detecting **incorrect video demonstrations** [3]. Many real-world tasks that a service robot is expected to learn from humans are multi-step sequential tasks, e.g. following a recipe for cooking, tea-making, preparing a dinner table, etc. The proposed framework therefore deals only with videos of sequential tasks.

The state-of-the-art approaches for detecting incorrect demonstrations – almost all of which involve non-visual demonstrations – is learning weights to assign importance to different demonstrations.

---

[1]Dataset is available upon request and will be public after acceptance.

[2]https://cvip.computing.dundee.ac.uk/datasets/foodpreparation/50salads/

[3]We define incorrect demonstrations as the ones that do not follow the standard task definition and are structurally wrong. For example, in the context of a *tea-making* task, an incorrect demonstration would be the one where the demonstrator did not add water or tea-bag to the cup.

Existing algorithms however come with restrictive assumptions – such as, expert-labeling of incorrect demonstrations [15, 16, 17], using a simulator to generate more data for training [18, 19, 20, 21] – which nullify the core appeal of VIL that a lay user's only responsibility is to show how to do the task, preferably a handful of times; the onus is on the algorithms to learn an accurate policy without demanding more data. We bridge this gap by proposing a framework for autonomous detection of incorrect video demonstration [3] which does not have any restrictive assumptions.

The proposed framework leverages two simple facts: 1) spatio-temporal features are better representatives of dynamic human activities than spatial-only visual features and 2) individual steps of a multi-step task – hereafter referred as sub-tasks – typically maintain some internal structures among themselves, violation of which is an indication of incorrect demonstration [3]. Accordingly, the intuition behind the proposed framework is to identify groups of spatio-temporal features as the representatives of different sub-tasks (Sections 3.1 and 3.2) and analyze the internal consistency of these features overall videos in the demonstration pool (Section 3.3). Evaluation of the proposed framework on two real-world datasets – publicly available *50-salad* [22] and our custom-designed *tea-making with YuMi robot* – shows promising results on detecting incorrect demonstrations even when they constitute 40% of the entire demonstration pool. We also show that various state-of-the-art IL algorithms learn better policies when incorrect demonstrations are automatically removed using the proposed framework than IL algorithms that learns from sub-optimal/incorrect demonstrations.

2 Related Work

The current imitation learning literature does not explicitly discuss the issue of incorrect demonstrations and how they may affect the learned policy. However, there exists a handful of work that offers mechanisms to differentiate optimal, sub-optimal, and noisy demonstrations during the learning process. This section discusses these methods.

The 2IWIL framework [15] requires an expert to label a fraction of the demonstrations as optimal/non-optimal using confidence score. A semi-supervised classifier is then trained to predict the confidence score of any unlabeled demonstration. Finally, these scores are used by a weighted GAIL framework while learning the task policy. To avoid error accumulation in such a two-step learning process, IC-GAIL [15] trains a single framework for generating the confidence score and learning the policy in an end-to-end fashion. The WGAIL [18] introduces a method of assigning weights to imperfect demonstrations in GAIL [23] without imposing extensive prior information. The success of WGAIL [18] however is limited to simulated environments.

The works that are conceptually closest to our proposed work are R-MaxEnt [24], BCND [25], and DEMO-DICE [26]. R-MaxEnt [24] jointly learns weights for different demonstrations and a task policy. The method however requires carefully-crafted task features, which are only achievable through hand-picking, and therefore has been evaluated for tasks with small state space. BCND [25] learns ensemble policies with a weighted BC objective function where the expert demonstrations are sampled from a noisy expert policy. The weights are generated from the policy learned in a previous internal iteration. DEMO-DICE [26] learns from different level of optimality in the demonstrations but through a much robust convex optimization problem. None of these three approaches however discuss how they can be scaled up for large state space, i.e. visual imitation learning.

Several IL algorithms are capable of detecting demonstrations corrupted by a limited amount of random noise [16, 19, 26]. Demonstrations with artificially injected random noise are far more trivial to process than incorrect demonstrations provided by humans in real world [3]. Additionally, some of these works [16, 19] requires simulators to generate additional data.

A number of inverse reinforcement learning-based IL algorithms [17, 27] use "failed" demonstration, along with optimal ones, for policy learning. However, they assume that these failed demonstrations are labeled *a priori* by an expert.

All algorithms discussed above are designed to work with non-visual demonstrations and can not be scaled-up to deal with extremely large state space (of video demonstrations). None of these methods can detect incorrect demonstrations without prior labeling of training data or access to more data (through a simulator). Furthermore, all existing work on sub-optimal demonstrations deal with continuous control tasks – e.g. Manipulation, Ant, HalfCheetah, etc. – Where a single incorrect action (e.g. a wrong joint-angle) may or may not cause the algorithm to eventually learn a completely incorrect policy. In case of multi-step sequential tasks, however, a single incorrect action can lead to an incorrect policy – e.g. not turning off the oven or not adding a tea-bag while making a cup of tea. Our proposed work fills up this void in visual imitation learning research.

Figure 1: The proposed framework has two steps: the first step (green shaded box, Sections 3.1 and 3.2) takes as an input n raw videos and does sub-task segmentation, generating q segments each with T frames. A features generator extracts f spatio-temporal visual features from each segment, creating a $q \times f$ matrix for each video. The second step (red shaded box, Section 3.3) concatenates all these features and uses them to solve a *minmax* problem which generates n weights, one for each input video.

3 Proposed Framework

The propose framework identifies incorrect demonstrations of a multi-step sequential task through analyzing the sub-task-representative spatio-temporal features. We leverage the concept of feature expectation matching [28, 29, 30] along with the principle of maximum entropy [31, 32] to learn a stochastic model of the sub-task sequence and generate weights for different demonstrations. Entropy analysis enables us to identify the most consistent group of demonstrations – in terms of sub-task features sequences – and assign higher weights to this group. Note that, multi-step sequential tasks can often be executed in multiple ways – such as making tea with or without milk/sugar – all of which are considered as correct. The proposed model is capable of distinguishing such cases from the case of incorrect demonstrations [3] through generating a distinct weight distribution.

Fig. 1 shows an overview of the proposed framework. The input is a set of n raw video demonstrations and the output is a n-dimensional vector representing the weight of each demonstration. The framework calculates these weights in a two-step process. At the first step (green shaded box in Fig. 1) each video is segmented into sub-tasks using any off-the-shelf video segmentation algorithm, e.g. [33] (Section 3.1). Our custom-designed algorithm then extracts spatio-temporal visual features from each sub-task video segments (Section 3.2). These features are representatives of various sub-tasks and are passed to the second step of the framework. During the second step (red shaded box in Fig. 1) these representative features are used to learn a stochastic model of the sub-task sequence which in-turn generates weights for different video demonstrations (Section 3.3).

3.1 Sub-task Segmentation

A video segmentation algorithm is used to segment each video in the demonstration set $\mathcal{D}$ into q sub-tasks and generate the start- and end-frame for each sub-task. Here, q is a hyper-parameter which does not require fine-tuning as we do not need very accurate sub-task segmentation. For multi-step tasks such as *tea-making* or *meal-preparation*, any value between 10 to 20 is reasonable for q. We employed the semi-supervised MS-TCN++ [33] for this purpose and have used the code available at [4]. MS-TCN++ leverages temporal convolution for temporal action segmentation and requires some labeled data for training. MS-TCN++ uses a multi-stage architecture for the temporal action segmentation task. Each stage

Figure 2: Sub-task segmentation results. Top row: Sample frames from one video from the *50-salad* dataset representing the start of different sub-tasks. Middle row: The ground truth (GT) time-line for each sub-task in this video (colors representing different sub-tasks). Bottom row: Segmentation generated by MS-TCN++.

features a set of dilated temporal convolutions to generate an initial prediction that is refined by the next one. MS-TCN++ requires some training data with the ground truth frame labels. Fig. 2 shows the segmentation of a video from the *50-salad* dataset into $q = 17$ sub-tasks (each sub-task coded with different colors). Note that the only purpose of this segmentation is assigning a consistent label to the set of task-relevant features that will be extracted from the sub-task videos (Section 3.2). The proposed framework is tolerant to typical errors in the existing video segmentation algorithms.

[4]The code is available in https://github.com/sj-li/MS-TCN2

3.2 Learning Task-relevant Features

The hallmark of most multi-step sequential tasks is their high-level temporal structure. For example, in the context of a *tea-making* task, *stirring the cup* happens **after** *milk or sugar is added* etc. We employ our own feature generator [5] that can identify and rank a subset of visual features from a video based on their temporal significance. We briefly discuss this feature identification process in this section.

The feature generation happens in three steps: 1) a set of spatial features are extracted from the training videos through any pre-trained convolutional neural networks (CNN) such as VGG-16 [34]. These features, by construction, are not sensitive to temporal content of the video. 2) Extracted spatial features alongside with their automatically extracted time stamp (i.e. when a feature started and stopped appearing in the video) are used to create a graph of temporal relationships among spatial features. This graphical structure – that we name interval temporal relationship (ITR) graph – is used to train a graph convolution network (GCN)[35] which learns the discriminatory temporal features present in the ITR graph. c) These temporally sensitive features are ranked, based on their contribution in classifying the activity in the video, using erasure ranking [36]. Only a set of high-ranked features are used for further analysis. More details are in appendix B.

In summary, each video in the demonstration set $\mathcal{D}$ is automatically segmented into q sub-task segments. For each video segment, a set of ranked features $\{s_j\}_{j=1}^q$ is extracted, $s = \{f_n\}_{n=1}^N$, N: the number of features from each segment. These sets, along with the sub-task labels $\{t_j\}_{j=1}^q$, are passed to the next step.

3.3 Incorrect Demonstration Detection

We aim to learn a stochastic model $p(t|s)$ that can infer the next sub-task $t \in \mathcal{T}$ given the current state $s \in \mathcal{S}$ and leverage this model to determine a weight $w \in [0,1]^D$ for each video in the demonstration set $\mathcal{D}$.

To derive the model $p(t|s)$ and the weights w we leverage the principle of maximum entropy (ME) [31, 32] which is proven to choose the most uniform model among a set of constrained models. We use the concept of feature expectation matching (FEM) [28, 29, 30] – a widely popular approach in IL [28, 29, 30] – to define a set of constraints to be observed by $p(t|s)$. In the context of incorrect demonstration detection, the goal is to match the expected value of each feature $\mathbb{E}_{\tilde{p}}[f_i]$ that we identify from the demonstration videos through the feature generator (discussed in Section 3.2) with the calculated expected value $\mathbb{E}_p[f_i]$ generated by the learned model $p(t|s)$. This model $p(t|s)$ will represent the sub-task sequences in the demonstration videos in the most unbiased manner [32].

Along with the model $p(t|s)$, we want to generate a weight w that indicates how well a specific video conform with the learned model. We achieve this by adding to the model-objective the requirement of calculating the minimum weights w that give us the model with the maximum entropy. Using this objective we are forcing the system to generate weights that indicate how consistent a video is with the majority of the videos in the training pool. Poor consistency (lower values of w) is an indication of incorrect demonstration. We start with the expected feature definition to formally derive $p(t|s)$:

$$\mathbb{E}_p[f_i] = \sum_{s \in \mathcal{S}} \sum_{t \in \mathcal{T}} \tilde{p}(s) p(t|s) f_i(s,t) \qquad \mathbb{E}_{\tilde{p}}[f_i] = \sum_{s \in \mathcal{S}} \sum_{t \in \mathcal{T}} \tilde{p}(s) \tilde{p}(t|s) f_i(s,t) \tag{1}$$

Here $\tilde{p}(s)$ is the empirical distribution of the states in $\mathcal{D}$, $\tilde{p}(t|s)$ is the empirical conditional distribution of predicting sub-task t given the state s, $f_i(s,t)$ is a feature function whose values are state features corresponding to predicted sub-tasks (Section 3.2). The optimization constraint, according to FEM, is $\mathbb{E}_p[f_i] - \mathbb{E}_{\tilde{p}}[f_i] = 0$. This formalism considers the training set $\mathcal{D}$ as one monolithic whole. Our goal however is to consider each video-demonstration separately and generate a weight $w \in [0,1]$ for each of them. We therefore redefine the distributions terms and parameterized them by demonstration d and weight w as follows:

$$\tilde{p}_w(t|s) = \frac{1}{M} \sum_{d=1}^D w_d \cdot \tilde{p}(t|s,d) \qquad , \tilde{p}_w(s) = \frac{1}{M} \sum_{d=1}^D w_d \cdot \tilde{p}(s,d)$$

Here D is the total number of demonstrations and M, which should be $\sum_{d=1}^D w_d = M$, is the minimum number of demonstrations that we can trust in a given set. Through the experimental results,

---

[5] The reference has been omitted to comply with double-blind review process.

we can see that the algorithm is not sensitive to the value of M. Usually, we can set this number to be $M = D/2$ since a dataset where more than half of the videos have incorrect demonstrations is not suitable for learning.

We define the optimization problem as shown in equation 2. Here the objective function maximizes the model entropy $H(p(t|s))$ while minimizing the demonstrations weights w. The first constraint is the FEM between the empirical expected feature values and the generated feature value after the modification with the wight parameter. The second constraint is to make sure we generate a correct probability distribution of the sub-task prediction $p(t|s)$. The last constraint is to ensure that there are at least M optimal demonstration in the dataset.

$$
\min_{w \in \mathbb{R}^D} \max_{p(t|s) \in \mathbb{R}^{S \times T}} \underbrace{- \sum_{s \in \mathcal{S}} \sum_{t \in \mathcal{T}} p(t|s) \log p(t|s) \sum_{d=1}^{D} w_d \cdot \tilde{p}(s,d)}_{H(p(t|s))}
$$

$$
\text{s. t.} \sum_{d=1}^{D} w_d \sum_{s \in \mathcal{S}} \sum_{t \in \mathcal{T}} f_i(s,t) \tilde{p}(s,d) \Big(p(t|s) - \tilde{p}(t|s,d) \Big) = 0 \tag{2}
$$

$$
\sum_{t \in \mathcal{T}} p(t|s) - 1 = 0, \quad \forall s \in \mathcal{S}, \qquad \sum_{d=1}^{D} w_d = M, \; w_d \geq 0, \; \forall d \in \mathcal{D}, \quad w_d \leq 1
$$

We use Lagrange multiplier approach to derive the dual problem – as shown in (3) – that we solve to to find the weights w[6]. The weights assigned to incorrect demonstrations are significantly lower than the correct ones. The global optimizer toolbox in Matlab is used to solve this non-convex quadratic problem.

$$
\min_{w \in \mathbb{R}^D, \lambda \in \mathbb{R}^N} \Lambda(\lambda, w) \equiv -\frac{1}{M} \sum_{d=1}^{D} w_d \Big(- \sum_{s \in \mathcal{S}} \tilde{p}(s,d) \log z_\lambda(s) + \sum_{i=1}^{N} \lambda_i \sum_{s \in \mathcal{S}} \sum_{t \in \mathcal{T}} \tilde{p}(t|s,d) f(s,t) \Big)
$$

$$
\text{s. t.} \sum_{d=1}^{D} w_d = M, \; w_d \geq 0 \; \forall d \in \mathcal{D}, \; w_d \leq 1 \tag{3}
$$

Here $z_\lambda(s) = \sum_{t \in \mathcal{T}} \exp \left(\sum_{i=1}^{N} \lambda_i f_i(s,t) \right)$ is a normalization constant, and λ is the Lagrange multiplier. A full pseudo code for the approach can be found in appendix D.

4 Experiment and Results

We conducted experiments to investigate the following: (1) can a video segmentation algorithm be used to detect incorrect video demonstrations? (Section 4.1) (2) how well the weights generated by the proposed framework can differential among optimal, sub-optimal and incorrect demonstrations (Sections 4.2 and 4.3), and (3) what generates a better policy?: learning while leveraging incorrect demonstrations vs discarding incorrect demonstrations from the training pool (Section 4.4). We used two video datasets for experiments: our custom-designed imitation learning dataset *Tea-Making with a YuMi Robot* and publicly available activity recognition dataset *50-salads* [22].

4.1 Video Segmentation Vs Incorrect Demonstration Detection

Since the proposed framework used a video segmentation algorithm which performed sub-task segmentation and thereby generated a sequence of sub-task for each video, a natural confusion may arise: can we use a clustering algorithm to analyze the sequence of sub-tasks from a demonstration pool and identify the incorrect demonstrations? We performed a series of experiments to resolve this. All video segmentation algorithms make non-zero segmentation errors and the consequence of inaccurate segmentation is detrimental in identifying incorrect demonstrations. For example, the highest reported per-frame accuracy of video-segmentation algorithm is 83% on the publicly available 50-salads dataset [33]. The sub-task segmentation accuracy – which is relevant for detecting incorrect demonstration – reduces to 70% with 30% tolerance in per-frame accuracy (i.e. we allow 30% of the frames from a sub-task to be incorrectly classified). This accuracy decreases significantly with reduced tolerance in per-frame accuracy. Table 1 summarizes the results. As an example, Fig. 2 shows the segmentation of a video

Accuracy	Tolerance
0%	5%
30%	10%
50%	20%
70%	30%

Table 1: Sub-task accuracy

---

[6] A complete derivation and implementation details can be found in the appendix A.

from the *50-salad* dataset into 17 sub-tasks (each sub-task coded with different colors) using the best-performing segmentation algorithm reported in [33]. The algorithm has generated more than four sub-tasks with false labels. There is no known way to directly use such an output sequence to distinguish between correct vs incorrect demonstration.

4.2 Analysis of Demonstration Weights: Tea-Making with YuMi Robot

4.2.1 The dataset

This custom-designed dataset has 36 videos showing three different human participants making a cup of tea – each participant performing 12 trials. The dataset was created through an IRB-approved user study. There are seven ground-truth sub-tasks in tea-making: *Turn on the oven, Add water, Add sugar, Add milk, Add tea bag, Stir, Turn off the oven*. Participants were asked to make tea while following any sequence of their choice but they must use both ingredients (i.e. milk and sugar). In majority of the resultant videos participants observed the following sequence: *Turn on the oven, Add tea bag, Add sugar, Add milk, Turn off the oven, Add water, Stir*. We consider these videos as **optimal demonstrations** and use the term **Seq_1** to denote them. Only a subset of videos show participants using the following sequence: *Turn on the oven, Add sugar, Add milk, Add tea bag, Turn off oven, Add water, Stir*. We consider these videos as **sub-optimal demonstrations** and use the term **Seq_2** to denote them. In a small subset of videos, the participants – based on our instructions – skipped one or two of the three critical sub-tasks namely, *Add tea-bag, Add hot water, Turn off the oven*. These videos are considered as **incorrect demonstrations** since they show a wrong or unsafe way of performing the tea-making task. We use the term **Seq_3** to denote them. Finally, to facilitate IL policy learning by real robots – which requires the joint angles of the robot for training – another 12 demonstrations were added to the dataset where the YuMi robot, instead of a human demonstrator, is remotely controlled to do the same tea-making task while following the same sub-task sequence as human demonstrators. All 48 videos are used for training and evaluations. A set of representative frames from three different types of video demonstrations are shown in appendix C

4.2.2 Sub-task segmentation and feature generation

Using MS-TCN++ [33] we segmented the videos into $q = 7$ sub-task segments with a per-frame accuracy of 80%. Fig. 3 shows the segmentation of a video from the *tea-making* dataset . From each segment, 64 frames were uniformly sampled. Frames were reduced to 224×224 pixels and went through background subtraction before being fed to the feature generator (Section 3.2). The dimension of the generated features was 64×32 which was further reduced to 1×32 through a *max* function over the 64 frames. Appendix B shows a visual representation of some of the features generated by the model.

Figure 3: Sub-task segmentation for a *tea-making* video. Top row: Sample frames from the input videos representing the different sub-tasks. Middle row: The ground truth sub-task segmentation (each color represents a sub-task). Bottom row: sub-task segmentation by MS-TCN++ [33]. Incorrectly added sub-tasks are in purple, green, and black).

4.2.3 Demonstration weights

The proposed framework, through equation (3), generates weights for different videos. This section discusses how these weights are used to identify optimal, sub-optimal, and incorrect demonstrations. For this, we create two demonstration sets: the first one has 6 optimal videos (**seq_1**: $d1$ to $d6$), 4 sub-optimal (**seq_2**: $d7$ to $d10$) and 2 incorrect ones ($d11$ to d_12) while the second set has 8 optimal (**seq_1**: $d1$ to $d8$) and 4 incorrect videos ($d9$ to $d12$). Fig. 4 shows the weights for different demonstrations for these two sets after normalizing them to have values between $[0, 1]$. The weights are distributed in such a way that it is trivial to pick up two thresholds to differentiate optimal, non-convention,

(a) The first set. (b) The second set.

Figure 4: Weights for two sets of videos from the *Tea-Making with a YuMi Robot* dataset. It is trivial to pick up two thresholds to differentiate optimal ('blue'), sub-optimal ('green'), and incorrect videos ('red').

and incorrect videos. There is one false positive (FP) in each of these two sets, $d3$ and $d4$. Further analysis on these two FP videos indicates two possible sources of errors: 1) the solver that solves the non-convex, non-linear optimization problem in (3) did not converge to the global minimum or (2)

the feature generator (Section 3.2) failed to identify a good set of features. Section 4.2.4 discusses the implication of generating erroneous weights.

4.2.4 Robustness of performance

We investigated the robustness of the proposed method in detecting sub-optimal and incorrect demonstrations. For this, we made a demonstration pool with 10 optimal demonstrations (**seq_1**) and one sub-optimal or incorrect demonstration (**seq_2** or **seq_3**). Keeping the number of optimal demonstrations fixed at 10, we increased the incorrect (or sub-optimal) demonstrations in the dataset until they become 44% of the dataset (i.e., 10 optimal and 8 incorrect or sub-optimal). Tables 2 and 3 show accuracy, recall, and precision in different cases. Here, a false positive (FP) indicates an optimal video demonstration inaccurately detected as incorrect (or sub-optimal) while a false negative (FN) is an incorrect (or sub-optimal) video incorrectly identified as optimal. True positive (TP) and true negative (TN) are also defined accordingly.

The proposed framework can detect sub-optimal and incorrect video demonstrations with an average accuracy of 86% and 90%, respectively. However, when detecting incorrect demonstration, the metric that carries most significance is Recall ($\frac{TP}{TP+FN}$). The proposed framework shows 100% recall, both for **Seq_2** and **Seq_3**. In other words, the framework can correctly identify every incorrect/sub-optimal demonstration in the dataset. The implication of this is significant: the framework can pass to the policy learning algorithm a train-

#Seq_1	#Seq_2	Accuracy	Recall	Precision
10	1	90	100	67
10	2	92	100	80
10	4	85	100	80
10	6	81	100	80
10	8	83	100	84
Average		86%	**100**	**78**

Table 2: Robustness with Seq_2

ing set consisting of purely optimal demonstrations and thereby learning a highly accurate policy [15, 18, 19, 37] (more discussion in Section 4.4). While the framework generates some false positive results (as shown by Precision values 78% and 83%, respectively), they do not directly jeopardize the quality of the learned policy. However, too many false positive may cause many demonstrations to be thrown away, resulting in a rapid shrinking of the demonstration pool which is undesirable for realistic applications where collecting demonstration is costly.

4.3 Analysis of Demonstration Weights: The 50-salads

4.3.1 The dataset

The *50-Salads* is a public dataset containing 50 videos of 25 actors preparing two different types of salads. The videos are recorded from an overhead camera and the average video duration is 6.4 minutes. There are 17 unique sub-tasks involved with preparing the dressing and mixing different ingredients (Cheese, cucumber, lettuce, tomato, dressing). However, the average number of sub-tasks in different videos is 20 as different actors follow different sub-task sequences to prepare the salad. Since it is not a custom-designed datasets, we had to devise a

#Seq_1	#Seq_3	Accuracy	Recall	Precision
10	1	90	100	67
10	2	92	100	80
10	4	93	100	89
10	6	88	100	86
10	8	89	100	89
Average		90%	**100**	**83**

Table 3: Robustness with Seq_3

strategy to create incorrect demonstrations. Being an activity recognition dataset, *50-salads* is a balanced dataset where half of the videos starts with sub-tasks related to *preparing dressing* and the other half with that related to *cutting and mixing different ingredients*. We used the first half of the dataset to create the incorrect demonstrations by removing all frames related to *preparing dressing*. Thus the **optimal demonstrations** are those videos where actors *cut and mix ingredients* and then *prepare the dressing* while **incorrect demonstrations** are the ones where actors miss the sub-tasks related to *preparing dressing*. Because of the limitation of the dataset, we focused only on detecting the incorrect demonstration, not the **sub-optimal** demonstrations. Fig. 2 shows example frames from the *50-salads* dataset.

4.3.2 Sub-task segmentation and feature generation

Using MS-TCN++ [33] we segmented each videos into $q = 17$ sub-task segments with a per-frame accuracy of 77% which is very close to the accuracy reported in the original paper [33]. Fig. 2 shows segmentation for an optimal demonstration where MS-TCN++ algorithm adds at least four additional sub-tasks to the ground truth. Feature generation followed the same strategy we adopted for the *Tea-making with YuMi Robot* dataset.

4.3.3 Demonstration weights

To analyze the weights of optimal vs incorrect demonstrations we created a demonstration set with 10 correct demonstrations ($d1$ *to* $d10$) and 2 incorrect ones

334 *d*11 *to d*12. Fig. 5 shows the normalized weights for different demonstrations.
335 It is trivial to pick up a thresholds to differentiate optimal and incorrect videos.
336

4.3.4 Robustness of performance

338 We evaluated the robustness of the proposed method in detecting only
339 the incorrect demonstrations in the *50-Salads* dataset. We made a demon-
340 stration pool with 10 optimal demonstrations and 1 incorrect one, and
341 gradually increased the number of incorrect demonstrations in the pool.
342 Table 4 shows accuracy, precision, and recall for different settings. From
343 Table 4, the average accuracy is 85% which is lower than that with the
344 *Tea-making with YuMi Robot* dataset. This is because *Salad-preparation*
345 is much more complex task than *Tea-making* with more than a double
346 number of sub-tasks. However, the recall performance remains 100% –
347 which means we never missed an incorrect demonstration ($FN = 0$) – a
348 desirable property for eventually learning an accurate policy. However,
349 unlike the *Tea-making with YuMi Robot* dataset, we could not empirically
350 investigate the policy accuracy for this dataset due to lack of robot joint angle data.

Figure 5: Weights for a set of videos from the *50-Salads* dataset. It is trivial to pick up a threshold to differentiate optimal ('blue'), and incorrect videos ('red').

4.4 Leveraging Vs Discarding Incorrect Demonstrations: Which Gives the Better Policy?

352 For the tea-making task, we created a demonstration set con-
353 taining varying number of incorrect demonstrations and investi-
354 gated the effect of having incorrect demonstrations on the accu-
355 racy of the learned policy. We studied three different strategies
356 for policy learning: i) we use the proposed framework to detect
357 incorrect demonstrations and discard them from the training set
358 before learning a policy using BC/BC-RNN [38, 2], ii) we use
359 BC/BC-RNN to learn a policy without discarding the incorrect
360 demonstrations iii) we use two contemporary IL approaches –
361 DEMO-DICE [26] and R-MaxEnt [24] – that leverage incor-

# Seq_1	# Seq_3	Accuracy	Recall	Precision
10	1	90	100	67
10	2	83	100	67
10	4	85	100	80
10	6	81	100	77
Average		**85**%	**100**	**73**

Table 4: Robustness with Seq_3 for the *50-Salads*

362 rect demonstrations for policy learning but assign poor weights to them in the learning process.
363 Fig. 6 shows the policy accuracy in different settings where policy-accuracy is defined as *(Number of*
364 *correctly chosen actions / Total number of executed actions until the goal is reached)* $\times 100$. When
365 incorrect demonstrations are present in the training set, Demo-Dice and R-MaxEnt learned a better
366 policy than BC/BC-RNN by assigning poor weights to incorrect videos. However, BC/BC-RNN
367 learned far better policy than Demo-Dice and R-MaxEnt when the incorrect videos were removed by
368 the proposed framework based on their poor weights. Implementation details and code links for the
369 policy learning algorithms can be found in appendix D.

5 Conclusion

371 We presented a novel approach for detecting incorrect video
372 demonstrations of any multi-stage sequential task. The pro-
373 posed method leverages entropy analysis to identify video(s) in
374 the demonstration pool that follow a disruptive task-sequence
375 and assign poor weights to them. Using two different datasets
376 we demonstrated the effectiveness of our approach. The pro-
377 posed framework can be used as a pre-processing step for any
378 visual IL algorithm to improve the accuracy of the learned
379 policy.

6 Limitations and Future Work

381 The proposed framework requires a value for q (the number
382 of sub-tasks) at the beginning of the pipeline. Techniques for
383 sub-goal identification from video – an active research area in
384 computer vision – can be employed for automatically generat-
385 ing a value for q. The proposed work is also limited in detecting
386 missing sub-tasks without providing any information about the

Figure 6: Accuracy of the tea-making task policy increases as incorrect demonstrations are removed from the training pool using the proposed framework.

387 importance of these sub-tasks. Introducing risk parameter for each sub-tasks and learning those
388 parameters from the dataset is a possible solution.

References

[1] R. Rafailov, T. Yu, A. Rajeswaran, and C. Finn. Visual adversarial imitation learning using variational models. *Advances in Neural Information Processing Systems*, 34, 2021.

[2] A. Mandlekar, D. Xu, J. Wong, S. Nasiriany, C. Wang, R. Kulkarni, L. Fei-Fei, S. Savarese, Y. Zhu, and R. Martín-Martín. What matters in learning from offline human demonstrations for robot manipulation. *arXiv preprint arXiv:2108.03298*, 2021.

[3] Y. Zhu, P. Stone, and Y. Zhu. Bottom-up skill discovery from unsegmented demonstrations for long-horizon robot manipulation. *IEEE Robotics and Automation Letters*, 2022.

[4] L. Smith, N. Dhawan, M. Zhang, P. Abbeel, and S. Levine. Avid: Learning multi-stage tasks via pixel-level translation of human videos. *arXiv preprint arXiv:1912.04443*, 2019.

[5] S. Pirk, K. Hausman, A. Toshev, and M. Khansari. Modeling long-horizon tasks as sequential interaction landscapes. *Conference on Robotic Learning*, 2020.

[6] R. Rahmatizadeh, P. Abolghasemi, L. Bölöni, and S. Levine. Vision-based multi-task manipulation for inexpensive robots using end-to-end learning from demonstration. In *2018 IEEE international conference on robotics and automation (ICRA)*, pages 3758–3765. IEEE, 2018.

[7] B. Wu, S. Nair, L. Fei-Fei, and C. Finn. Example-driven model-based reinforcement learning for solving long-horizon visuomotor tasks. *arXiv preprint arXiv:2109.10312*, 2021.

[8] M. Hussein, M. Begum, and M. Petrik. Inverse reinforcement learning of interaction dynamics from demonstrations. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 2267–2274. IEEE, 2019.

[9] S. Nair and C. Finn. Hierarchical foresight: Self-supervised learning of long-horizon tasks via visual subgoal generation. *arXiv preprint arXiv:1909.05829*, 2019.

[10] C. Lynch, M. Khansari, T. Xiao, V. Kumar, J. Tompson, S. Levine, and P. Sermanet. Learning latent plans from play. In *Conference on Robot Learning*, pages 1113–1132. PMLR, 2020.

[11] V. Tangkaratt, N. Charoenphakdee, and M. Sugiyama. Robust imitation learning from noisy demonstrations. *arXiv preprint arXiv:2010.10181*, 2020.

[12] H. Lin, B. Li, X. Zhou, J. Wang, and M. Q.-H. Meng. No need for interactions: Robust model-based imitation learning using neural ode. *arXiv preprint arXiv:2104.01390*, 2021.

[13] D. S. Brown, W. Goo, and S. Niekum. Better-than-demonstrator imitation learning via automatically-ranked demonstrations. In *Conference on robot learning*, pages 330–359. PMLR, 2020.

[14] Y. Li, J. Song, and S. Ermon. Infogail: Interpretable imitation learning from visual demonstrations. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pages 3815–3825, 2017.

[15] Y.-H. Wu, N. Charoenphakdee, H. Bao, V. Tangkaratt, and M. Sugiyama. Imitation learning from imperfect demonstration. In *International Conference on Machine Learning*, pages 6818–6827. PMLR, 2019.

[16] D. Brown, W. Goo, P. Nagarajan, and S. Niekum. Extrapolating beyond suboptimal demonstrations via inverse reinforcement learning from observations. In *International conference on machine learning*, pages 783–792. PMLR, 2019.

[17] K. Shiarlis, J. Messias, and S. Whiteson. Inverse reinforcement learning from failure. 2016.

[18] Y. Wang, C. Xu, B. Du, and H. Lee. Learning to weight imperfect demonstrations. In *International Conference on Machine Learning*, pages 10961–10970. PMLR, 2021.

[19] V. Tangkaratt, B. Han, M. E. Khan, and M. Sugiyama. Variational imitation learning with diverse-quality demonstrations. In *International Conference on Machine Learning*, pages 9407–9417. PMLR, 2020.

[20] L. Liu, Z. Tang, L. Li, and D. Luo. Robust imitation learning from corrupted demonstrations. *arXiv preprint arXiv:2201.12594*, 2022.

[21] Y. Wang, C. Xu, and B. Du. Robust adversarial imitation learning via adaptively-selected demonstrations. In *Proceedings of the Thirtieth International Joint Conference on Artificial Intelligence, IJCAI-21*, pages 3155–3161, 2021.

[22] S. Stein and S. J. McKenna. Combining embedded accelerometers with computer vision for recognizing food preparation activities. In *Proceedings of the 2013 ACM international joint conference on Pervasive and ubiquitous computing*, pages 729–738, 2013.

[23] J. Ho and S. Ermon. Generative adversarial imitation learning. In *Advances in neural information processing systems*, pages 4565–4573, 2016.

[24] M. Hussein, B. Crowe, M. Clark-Turner, P. Gesel, M. Petrik, and M. Begum. Robust behavior cloning with adversarial demonstration detection. In *2021 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 7858–7864. IEEE.

[25] F. Sasaki and R. Yamashina. Behavioral cloning from noisy demonstrations. In *International Conference on Learning Representations*, 2020.

[26] G.-H. Kim, S. Seo, J. Lee, W. Jeon, H. Hwang, H. Yang, and K.-E. Kim. Demodice: Offline imitation learning with supplementary imperfect demonstrations. In *International Conference on Learning Representations*, 2021.

[27] D. H. Grollman and A. Billard. Donut as i do: Learning from failed demonstrations. In *2011 IEEE International Conference on Robotics and Automation*, pages 3804–3809. IEEE, 2011.

[28] T. Osa, J. Pajarinen, G. Neumann, J. A. Bagnell, P. Abbeel, and J. Peters. An algorithmic perspective on imitation learning. *arXiv preprint arXiv:1811.06711*, 2018.

[29] H. Ravichandar, A. S. Polydoros, S. Chernova, and A. Billard. Recent advances in robot learning from demonstration. *Annual Review of Control, Robotics, and Autonomous Systems*, 3:297–330, 2020.

[30] B. D. Ziebart, A. L. Maas, J. A. Bagnell, and A. K. Dey. Maximum entropy inverse reinforcement learning. In *Association for the Advancement of Artificial Intelligence (AAAI)*, volume 8, pages 1433–1438. Chicago, IL, USA, 2008.

[31] S.-i. Amari. *Information geometry and its applications*, volume 194. Springer, 2016.

[32] E. T. Jaynes. Information theory and statistical mechanics. *Physical review*, 106(4):620, 1957.

[33] S.-J. Li, Y. AbuFarha, Y. Liu, M.-M. Cheng, and J. Gall. Ms-tcn++: Multi-stage temporal convolutional network for action segmentation. *IEEE transactions on pattern analysis and machine intelligence*, 2020.

[34] K. Simonyan and A. Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

[35] M. Schlichtkrull, T. N. Kipf, P. Bloem, R. Van Den Berg, I. Titov, and M. Welling. Modeling relational data with graph convolutional networks. In *European Semantic Web Conference*, pages 593–607. Springer, 2018.

[36] J. Li, W. Monroe, and D. Jurafsky. Understanding neural networks through representation erasure. *arXiv preprint arXiv:1612.08220*, 2016.

[37] J. Zheng, S. Liu, and L. M. Ni. Robust bayesian inverse reinforcement learning with sparse behavior noise. In *Twenty-Eighth AAAI Conference on Artificial Intelligence*, 2014.

[38] D. A. Pomerleau. Efficient training of artificial neural networks for autonomous navigation. *Neural computation*, 3(1):88–97, 1991.