Attribute-Based Diagnosis of LLM Alignment with Hate Speech Annotations

Abstract

Hate speech annotation is costly, subjective, and prone to annotator disagreement, making large-scale dataset construction challenging. We systematically analyze how well large language models (LLMs) align with human judgments across ten theoretically grounded subjective attributes, such as dehumanization, violence, and sentiment, evaluating both small and large variants of Llama 3.1 and Qwen 2.5. Our analysis reveals a consistent split across all models: behaviorally explicit dimensions (insult, humiliate, attack-defend) correlate strongly with human annotations, while evaluative dimensions (respect, sentiment, hate speech) are systematically inverted. Demographic persona conditioning reduces model confidence without improving alignment. Building on these insights, we propose combining attribute-level LLM predictions via a confidence-weighted Ridge regression to reconstruct continuous hate speech scores from the Measuring Hate Speech corpus, achieving R^2 of up to 0.71 and outperforming direct prompting baselines, demonstrating that structured attribute decomposition recovers a richer and more human-aligned signal than end-to-end label prediction alone.

1 Introduction

Hate speech annotation is a challenging task; determining whether a comment is hateful requires nuanced judgment, as what one person perceives as harmful, another may view as acceptable (Mostafazadeh Davani et al., 2022; Sap et al., 2022). This subjectivity manifests as systematic annotator disagreement that cannot be resolved by adjudication alone, and collecting high-quality annotations at scale remains prohibitively expensive and methodologically complex (Waseem and Hovy, 2016). These challenges have motivated a growing line of work on using LLMs as scalable substitutes for human annotators (Argyle et al., 2023; Gilardi et al., 2023; Tan et al., 2024). By prompting models to produce labels, researchers have shown promising alignment with human judgments on various tasks (Tan et al., 2024), specifically for subjective tasks (Hu and Collier, 2024; Deshpande et al., 2023). However, existing work treats annotation simulation as a single holistic prediction, a label or scalar score, offering no insight into which aspects of a subjective construct the model understands and where it diverges from human perception.

Hate speech is not a monolithic concept but a constellation of distinct behaviors and dimensions. The Measuring Hate Speech corpus (Kennedy et al., 2020) captures this complexity through ten theoretically grounded annotation attributes, including dehumanization, violence, respect, etc., each targeting a specific facet of hateful content. These attributes are combined via Item Response Theory (IRT) into a continuous hate speech score, which makes it a unique lens for studying LLM annotation simulation at the attribute level, rather than collapsing hate speech into a single judgment.

In this paper, we exploit this structure to conduct a systematic investigation of LLM-based subjective tasks annotation prediction. We prompt small and large variants of Llama 3.1 and Qwen 2.5 to rate each of the ten attributes independently, extracting both predictions and model confidence scores. This fine-grained view reveals a consistent and interpretable pattern: behaviorally explicit dimensions such as insult, humiliate, and attack_defend align strongly with human judgments across four models, while evaluative dimensions such as respect, sentiment, and hate speech itself are systematically inverted, a finding that holds regardless of model size or family. We also examine whether demographic persona conditioning improves this alignment, finding that while it reduces model confidence, it does not bring predictions closer to human labels (Hu and Collier, 2024; Sarumi et al., 2025).

Building on these insights, we ask whether fine-grained attribute predictions can be combined to

recover the continuous IRT hate speech score more effectively than direct prompting. We propose a confidence-weighted Ridge regression pipeline that aggregates attribute-level LLM predictions into a reconstructed hate speech score, and evaluate it against direct prompting baselines. Our pipeline achieves R^2 of up to 0.71 and outperforms direct prompting, demonstrating that structured attribute decomposition captures a richer and more human-aligned signal than end-to-end label prediction.

2 Related Work

A growing body of recent studies explores using LLMs to replace or augment human annotators, particularly for subjective tasks where collecting labels at scale is expensive. Calderon et al. (2025) propose a statistical framework for testing when LLMs can substitute human annotators, while Radharapu et al. (2025) show that LLMs struggle in tasks without annotator consensus. Falk and Lapesa (2025) examine the relationship between human label variation and model uncertainty in perspectivist annotation, and Chochlakis et al. (2025) warn that naive aggregation of LLM outputs can collapse meaningful variation in subjective tasks. Together, these works establish that LLM annotation simulation is promising but fundamentally limited, limitations that our work examines at the attribute level rather than the label level.

Hate speech annotation is particularly susceptible to subjectivity and cultural variation. Lee et al. (2024) show that hate speech annotations vary systematically across cultures, motivating perspectivist approaches to modeling. Alacam et al. (2025) distinguish subjectivity from uncertainty in hate speech modeling, while Lu et al. (2025) analyze LLM confidence under offensive language disagreement. Giorgi et al. (2025) compare human and persona-based LLM biases in hate speech annotation, finding that LLM biases differ systematically from human annotator biases, a direction our work extends by identifying which specific attributes align, which invert, and how this pattern holds across models. Gligorić et al. (2025) use LLM confidence to decide when human annotation is needed; we instead treat confidence as a weighting signal for attribute-based score prediction.

3 Our Approach

We use LLMs to rate each of the ten MHS attributes independently for each comment, under two condi-

tions: a *vanilla* prompt with no demographic context and a *persona* prompt conditioned on the real demographic profile of the corresponding MHS annotator. For each prediction, we extract a confidence score from token-level log probabilities and measure attribute-level alignment with human judgments via Spearman rank correlation. Building on these predictions, we construct confidence-weighted attribute features, which are passed to a Ridge regression model trained on the training set to reconstruct the continuous IRT hate speech score on the test set.

Attribute-level simulation: Let $\mathcal{A} = \{a_1, \ldots, a_{10}\}$ denote the ten MHS attributes and $\mathcal{F} = \{f_1, \ldots, f_m\}$ denote the m demographic features of each annotator (gender, age, race, religion, and political ideology). For each comment n and attribute a_i, we prompt the LLM to predict an ordinal label $S_{n,i} \in \{0, \ldots, s\}$ [1] under two conditions: In the *vanilla* condition, the model receives only the attribute definition and comment text with no demographic context: $S_{n,i} = \text{LLM}(a_i, c_n)$. In the *persona* condition, the prompt is additionally conditioned on the annotator's demographic profile $\mathbf{f}_n \in \mathcal{F}$: $S_{n,i} = \text{LLM}(a_i, c_n, \mathbf{f}_n)$.

Confidence extraction: To evaluate attribute-level alignment, we compute the Spearman rank correlation between LLM predictions $S_{n,i}$ and mean human ratings $h_{n,i}$ for each attribute a_i: $\rho_i = \text{Spearman}(S_{n,i}, h_{n,i})$, Confidence scores are extracted from token-level log probabilities, renormalized via softmax $\mathcal{V}$: $C_{n,i} = \frac{\exp(\ell_{\hat{k}})}{\sum_{k \in \mathcal{V}} \exp(\ell_k)}$, where ℓ_k is the log probability of label token k and $\hat{k} = \arg\max_{k \in \mathcal{V}} P(k \mid \text{prompt})$.

Score reconstruction: The confidence–weighted feature for each attribute is: $x_{n,i} = S_{n,i} \cdot C_{n,i}$, and the final hate speech score is predicted by a Ridge regression model trained on the training set: $\hat{y}_n = \text{Ridge}(\mathbf{x}_n)$, where $\mathbf{x}_n = (x_{n,1}, \ldots, x_{n,10})$ is the vector of weighted attribute features.

4 Experimental Details

Dataset We use the Measuring Hate Speech (MHS) corpus (Kennedy et al., 2020), a large-scale dataset of 39,565 comments annotated by 7,912 crowd-sourced annotators. MHS captures the multidimensional nature of hateful content through ten

---

[1] s represent the maximum ordinal value that varies for each attribute.

	Respect	Sentiment	Status	Hate speech	Genocide	Dehuman-ize	Attack-defend	Violence	Humiliate	Insult
Llama 70B Vanilla	-73.03	-70.47	-57.35	-48.79	54.87	59.78	61.76	64.45	66.42	69.75
Llama 70B Persona	-75.67	-72.40	-58.21	-50.01	53.79	60.27	60.99	68.68	67.43	71.65
Qwen 72B Vanilla	-74.44	-72.78	-56.11	-51.34	52.60	57.87	61.17	64.81	66.70	71.17
Qwen 72B Persona	-74.19	-71.74	-56.03	-52.27	53.31	57.77	60.82	66.83	66.69	70.68

Table 1: Spearman rank correlation ($\times 100$) between LLM attribute predictions and human ratings for large models.

ordinal attributes, each targeting a distinct facet: *hatespeech* (whether the comment contains hate speech), *attack/defend* (whether it attacks or defends a group), *genocide* (whether it calls for or justifies genocide), *violence* (whether it incites or glorifies violence), *dehumanize* (whether it dehumanizes a group), *status* (whether it degrades the status of a group), *humiliate* (whether it humiliates a group or individual), *insult* (whether it contains insults), *respect* (whether it shows respect toward a group), and *sentiment* (the overall sentiment toward the target group). The final hate speech score is derived via Item Response Theory (IRT), a psychometric framework that aggregates attribute ratings into a continuous score while accounting for annotator reliability (Sachdeva et al., 2022b).

Models We evaluate four open-source LLMs across two model families and two size regimes: Meta-Llama-3.1-70B-Instruct and Meta-Llama-3.1-8B-Instruct (Grattafiori et al., 2024), and Qwen2.5-72B-Instruct and Qwen2.5-7B-Instruct (Yang et al., 2025). Evaluating models of different sizes and families allows us to assess whether alignment patterns generalize beyond a single model or scale. Details on the models are in Appendix A.

Prompts We design two prompt variants to simulate attribute annotation. The *vanilla* prompt presents the model with the attribute definition, its ordinal scale anchors drawn from the original MHS annotation guidelines (Sachdeva et al., 2022a), and the comment text. Grounding the prompts in the original guidelines ensures a fair and consistent comparison between LLM and human judgments across all ten attributes. The *persona* prompt extends the vanilla prompt by prepending the real demographic profile of the corresponding MHS annotator. For the baseline comparison, we design four direct binary prompting variants: a zero-shot prompt with no additional context, a few-shot prompt with example annotations, a definition-based prompt providing a brief description of hate speech, and an attribute-aware prompt listing all

ten MHS attributes as considerations without decomposing them. All four ask the model to output a single hate/non-hate label and are compared against our attribute-level pipeline on binary classification performance. Additional details about the prompts can be found in Appendix B.

5 Results

We structure our results in two parts. First, we analyze attribute-level LLM-human alignment across the full dataset using Spearman's rank correlation. Second, we evaluate hate speech score reconstruction using 5-fold cross-validation on the train/test split, reporting R², F1, accuracy, precision, and recall averaged across folds.

Attribute-level Analysis Table 1 presents the Spearman rank correlations between LLM attribute predictions and human ratings across all four models and prompting conditions. A consistent pattern emerges across all settings: attributes naturally split into two clusters. Behaviorally explicit attributes, such as insult, humiliate, violence, attack_defend, dehumanize, and genocide, show strong positive correlations with human judgments (ranging from 53 to 72), indicating that LLMs reliably track human perception of concrete, observable behaviors in text. In contrast, evaluative attributes, such as respect, sentiment, status, and hate speech, are systematically inverted (ranging from -52 to -75), suggesting that LLMs apply a different judgment schema for dimensions that require holistic or contextual assessment. Results for smaller models are in Appendix C.

Figure 1 shows the relationship between average model confidence and Spearman correlation with human ratings for each attribute, across both larger models and prompting conditions. A notable pattern emerges: the attributes that align most poorly with human judgments, respect, sentiment, and hate speech cluster in the bottom-right quadrant, indicating that the model is highly confident precisely where it diverges most from human per-

Figure 1: Average model confidence versus Spearman correlation with human ratings for each attribute.

		R²	F1	Acc.	Prec.	Recall
Llama-70B	Zero-shot	–	60.30	66.64	43.95	96.02
	Few-shot	–	60.63	67.47	44.53	94.93
	Definition	–	61.61	70.79	47.15	88.88
	Attr. aware	–	60.30	66.97	44.15	95.12
	Attr. value	–	54.91	57.49	38.12	98.14
	Vanilla	70.57 ± 0.59	68.63	84.02	71.15	66.29
	Persona	70.71 ± 0.45	68.95	84.49	73.07	65.27
Qwen-72B	Zero-shot	–	70.60	70.03	54.86	99.02
	Few-shot	–	50.33	51.36	34.62	99.40
	Definition	–	69.64	69.11	54.17	97.49
	Attr. aware	–	69.45	68.26	53.42	99.26
	Attr. value	–	50.71	48.98	34.02	99.48
	Vanilla	68.85 ± 0.56	69.20	83.95	70.08	68.34
	Persona	68.65 ± 0.60	67.63	83.83	71.67	64.03

Table 2: Hate speech score reconstruction and classification results (×100).

reconstruct the continuous IRT hate speech score without access to ground-truth labels at test time.

Compared to direct prompting baselines, our pipeline consistently achieves superior accuracy (84% vs 57–70%) and competitive F1 across both models. While Qwen baselines show competitive F1, this masks extreme prediction bias — baselines achieve very high recall (up to 99%) but poor precision (as low as 34%), flagging the vast majority of comments as hate speech regardless of content. Our pipeline produces substantially more calibrated predictions, achieving a better balance between precision and recall and consequently higher accuracy and F1. Llama-3.1 outperforms Qwen-2.5 despite Qwen showing marginally stronger Spearman correlations on individual attributes in Table 1, suggesting that aggregate reconstruction quality does not directly follow from per-attribute alignment. See Appendices D and E for the ablation study and qualitative examples of model predictions.

6 Conclusion

We investigated LLM alignment with hate speech annotations at the attribute level, revealing a consistent split across four models: behaviorally explicit attributes align well with human judgments, while evaluative attributes are systematically inverted. Our confidence-weighted Ridge pipeline achieves R^2 of up to 0.71 on hate speech score prediction, demonstrating that structured attribute decomposition recovers a stronger signal than direct label prediction.

ception. While positively correlated attributes such as insult, humiliate, and violence also attract relatively high confidence, the negatively correlated attributes tend to sit at the highest confidence range (0.88–0.95), suggesting that LLMs are not only wrong on evaluative attributes but particularly certain about their wrong judgments. This pattern holds consistently across both large models. In smaller models, the confidence range is lower, and the two-cluster separation is less pronounced; confidence plots for smaller models are in Appendix C. Persona conditioning consistently shifts attribute confidence leftward across both large models without improving alignment, confirming that demographic conditioning affects model certainty but not its conceptual understanding of attributes.

Hate Score Reconstruction Table 2 presents the hate speech score reconstruction and classification results across larger models, prompting conditions, and baselines. Our confidence-weighted Ridge pipeline achieves R² values of up to 70.70 for Llama-3.1 and 68.91 for Qwen-2.5, demonstrating that attribute-level LLM predictions can reliably

Limitations

Our study focuses on the Measuring Hate Speech corpus, as it is the only dataset providing the combination of multi-attribute annotation, continuous IRT scoring, and annotator demographic profiles required by our pipeline; extending to other corpora would require comparable annotation depth. We evaluate two model families, Llama and Qwen, in two size regimes; broader coverage was constrained by computational resources, though the consistency of findings across four models suggests the patterns are not family-specific. Persona conditioning relies on demographic features available in MHS; richer annotator signals, such as annotation history or cultural context, are not provided in the dataset and cannot be incorporated.

Ethical Considerations

This work involves processing hateful content, which may pose risks to researchers and annotators involved in data collection and model evaluation. We use an existing dataset and do not collect new annotations. While our pipeline could reduce the cost of hate speech annotation, we caution against fully replacing human annotators, particularly given the systematic misalignments identified on evaluative attributes, dimensions that often capture the most nuanced and culturally grounded aspects of hate speech. Automated annotation systems should be used to assist rather than substitute human judgment in sensitive content moderation.

References

Özge Alacam, Sanne Hoeken, Andreas Säuberli, Hannes Gröner, Diego Frassinelli, Sina Zarrieß, and Barbara Plank. 2025. Disentangling subjectivity and uncertainty for hate speech annotation and modeling using gaze. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 28707–28724, Suzhou, China. Association for Computational Linguistics.

Lisa P. Argyle, Ethan C. Busby, Nancy Fulda, Joshua R. Gubler, Christopher Rytting, and David Wingate. 2023. Out of one, many: Using language models to simulate human samples. *Political Analysis*, 31(3):337–351.

Nitay Calderon, Roi Reichart, and Rotem Dror. 2025. The alternative annotator test for llm-as-a-judge: How to statistically justify replacing human annotators with llms.

Georgios Chochlakis, Alexandros Potamianos, Kristina Lerman, and Shrikanth Narayanan. 2025. Aggregation artifacts in subjective tasks collapse large language models' posteriors. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 5513–5528, Albuquerque, New Mexico. Association for Computational Linguistics.

Ameet Deshpande, Vishvak Murahari, Tanmay Rajpurohit, Ashwin Kalyan, and Karthik Narasimhan. 2023. Toxicity in chatgpt: Analyzing persona-assigned language models. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 1236–1270, Singapore. Association for Computational Linguistics.

Neele Falk and Gabriella Lapesa. 2025. Mining the uncertainty patterns of humans and models in the annotation of moral foundations and human values. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 22898–22921, Vienna, Austria. Association for Computational Linguistics.

Fabrizio Gilardi, Meysam Alizadeh, and Maël Kubli. 2023. Chatgpt outperforms crowd workers for text-annotation tasks. *Proceedings of the National Academy of Sciences*, 120(30):e2305016120.

Tommaso Giorgi, Lorenzo Cima, Tiziano Fagni, Marco Avvenuti, and Stefano Cresci. 2025. Human and llm biases in hate speech annotations: A socio-demographic analysis of annotators and targets. In *Proceedings of the International AAAI Conference on Web and Social Media*, volume 19, pages 653–670.

Kristina Gligorić, Tijana Zrnic, Cinoo Lee, Emmanuel Candès, and Dan Jurafsky. 2025. Can unconfident LLM annotations be used for confident conclusions? In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 3514–3533, Albuquerque, New Mexico. Association for Computational Linguistics.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Tiancheng Hu and Nigel Collier. 2024. Quantifying the persona effect in LLM simulations. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 10289–10307, Bangkok, Thailand. Association for Computational Linguistics.

Chris J Kennedy, Geoff Bacon, Alexander Sahn, and Claudia von Vacano. 2020. Constructing interval variables via faceted rasch measurement and multi-task deep learning: a hate speech application. *arXiv preprint arXiv:2009.10277*.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph Gonzalez, Hao Zhang, and Ion Stoica. 2023. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the 29th symposium on operating systems principles*, pages 611–626.

Nayeon Lee, Chani Jung, Junho Myung, Jiho Jin, Jose Camacho-Collados, Juho Kim, and Alice Oh. 2024. Exploring cross-cultural differences in English hate speech annotations: From dataset construction to analysis. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 4205–4224, Mexico City, Mexico. Association for Computational Linguistics.

Junyu Lu, Kai Ma, Kaichun Wang, Kelaiti Xiao, Roy Ka-Wei Lee, Bo Xu, Liang Yang, and Hongfei Lin. 2025. Is llm an overconfident judge? unveiling the capabilities of llms in detecting offensive language with annotation disagreement. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 5609–5626.

Aida Mostafazadeh Davani, Mark Díaz, and Vinodkumar Prabhakaran. 2022. Dealing with disagreements: Looking beyond the majority vote in subjective annotations. *Transactions of the Association for Computational Linguistics*, 10:92–110.

Bhaktipriya Radharapu, Manon Revel, Megan Ung, Sebastian Ruder, and Adina Williams. 2025. Arbiters of ambivalence: Challenges of using LLMs in no-consensus tasks. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 4677–4731, Vienna, Austria. Association for Computational Linguistics.

Pratik Sachdeva, Renata Barreto, Geoff Bacon, Alexander Sahn, Claudia Von Vacano, and Chris Kennedy. 2022a. The measuring hate speech corpus: Leveraging rasch measurement theory for data perspectivism. In *Proceedings of the 1st Workshop on Perspectivist Approaches to NLP@ LREC2022*, pages 83–94.

Pratik S Sachdeva, Renata Barreto, Claudia von Vacano, and Chris J Kennedy. 2022b. Assessing annotator identity sensitivity via item response theory: A case study in a hate speech corpus. In *Proceedings of the 2022 ACM conference on fairness, accountability, and transparency*, pages 1585–1603.

Maarten Sap, Swabha Swayamdipta, Laura Vianna, Xuhui Zhou, Yejin Choi, and Noah A. Smith. 2022. Annotators with attitudes: How annotator beliefs and identities bias toxic language detection. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 5884–5906, Seattle, United States. Association for Computational Linguistics.

Olufunke Sarumi, Charles Welch, Daniel Braun, and Jörg Schlötterer. 2025. The impact of annotator personas on llm behavior across the perspectivism spectrum. In *Proceedings of the 8th International Conference on Natural Language and Speech Processing (ICNLSP-2025)*, pages 121–136.

Zhen Tan, Dawei Li, Song Wang, Alimohammad Beigi, Bohan Jiang, Amrita Bhattacharjee, Mansooreh Karami, Jundong Li, Lu Cheng, and Huan Liu. 2024. Large language models for data annotation and synthesis: A survey. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 930–957.

Zeerak Waseem and Dirk Hovy. 2016. Hateful symbols or hateful people? predictive features for hate speech detection on Twitter. In *Proceedings of the NAACL Student Research Workshop*, pages 88–93, San Diego, California. Association for Computational Linguistics.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Remi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander Rush. 2020. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 38–45, Online. Association for Computational Linguistics.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. 2025. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*.

A Models

All models used in this study are loaded in quantized form and served via vLLM (Kwon et al., 2023) from HuggingFace (Wolf et al., 2020). We load them in inference mode, without training and changing their weights. To ensure deterministic and comparable outputs across runs, we set the temperature to 0.0, fix the random seed to 42, and limit generation to a single token (max_tokens=1), enabling direct extraction of token-level probabilities as confidence scores for each attribute prediction.

For the Spearman correlation analysis (Section 3), we retain the full (comment, annotator) granularity. Each LLM prediction is compared against the corresponding human annotator's label, allowing a direct per-annotator alignment measurement. For the Ridge regression (Section 3), we operate at the comment level. The IRT-derived hate speech score θ_n is computed once per comment, so predictions must also be aggregated to the

Figure 2: Ridge regression weights per attribute for two models (LLama top and Qwen bottom). Positive weights indicate hate-promoting attributes, negative weights reflect evaluative attributes inverted relative to human judgments (cf. Table 1).

comment level. Under the vanilla condition, this is straightforward. Under the persona condition, the LLM produces one prediction per (comment, annotator) pair — these are averaged across annotators before entering Ridge, ensuring a consistent unit of analysis across both conditions. After merging on `comment_id`, the regression set comprises approximately 39,500 unique comments.

Figure 2 shows the Ridge weights for each attribute across vanilla conditions for both models. Attributes with strong positive Spearman correlations in Table 1, insult, humiliate, violence, receive large positive weights, while evaluative attributes, respect, sentiment, hate speech, receive large negative weights. This direct correspondence between the alignment analysis in section 1 and the learned weights confirms that the Ridge model exploits the inversion signal from evaluative attributes rather than discarding it, turning a potential weakness into a useful predictive feature.

B Prompts

All prompts share a common structure consisting of a system prompt instructing the model to act as an expert annotator without applying safety filters, followed by a user prompt containing the attribute description with ordinal scale anchors drawn from the original MHS annotation guidelines (Sachdeva et al., 2022a), the comment text, and an instruction to output a single integer token. The per-attribute scoring rubrics used in the vanilla condition are shown in Table 4. In the vanilla condition, the system prompt provides no demographic context. In the persona condition, a demographic header (Table 3) is prepended to each per-attribute rubric. The header takes the form: *"You are a content annotator with the following characteristics: gender ..., age ... (old/young), race ..., religion ..., ideology .... Evaluate this comment from your perspective as this annotator."* Demographic fields are populated from the corresponding row of the MHS annotation file, so the model produces one prediction per (comment, annotator, attribute) triple, mirroring the granularity of the human annotation data. The rubric itself is unchanged between the two conditions, and both use identical decoding configurations, ensuring that the only difference between vanilla and persona predictions is the demographic context.

C Small Model Results

Table 5 presents the Spearman rank correlations for the two smaller models. The two-cluster pattern observed in large models is largely preserved, though with notable deviations. In Llama-3.1-8B, sentiment collapses to near zero (-1.56) under vanilla prompting and status flips to positive (+38.68), suggesting that smaller models struggle to maintain consistent evaluative judgments on these dimensions. Qwen-2.5-7B shows a more stable pattern, retaining negative correlations on all evaluative attributes, though with weaker magnitudes than its 72B counterpart. Figure 3 shows the confidence vs. correlation plots for both small models. Unlike large models where evaluative attributes cluster clearly in the bottom-right quadrant, small models show a more dispersed pattern with lower overall confidence (0.55–0.80), and the separation between behaviorally explicit and evaluative attributes is less pronounced.

Table 6 presents the hate speech score reconstruction and classification results for the two smaller models. Our confidence-weighted Ridge pipeline achieves R² of up to 62.55 for Llama-3.1-8B and 60.53 for Qwen-2.5-7B, demonstrating

Persona header

```
You are a content annotator with the following characteristics:
- Gender: {gender}
- Age: {age} ({age_category})
- Race: {race}
- Religion: {religion}
- Ideology: {ideology}
Evaluate this comment from your perspective as this annotator.
```

Table 3: Persona header prepended to each per-attribute scoring rubric (Table 4) in the persona prompting condition. Placeholders in curly braces are populated per row from the demographic fields of the corresponding MHS annotator.

Attribute	Scale	Scoring rubric
sentiment	0–4	Sentiment polarity: 0=strongly negative, 1=somewhat negative, 2=neutral, 3=somewhat positive, 4=strongly positive.
hatespeech	0–2	Presence of hate speech: 0=no, 1=unclear/neutral, 2=yes.
insult	0–4	Insult toward the group: 0=none, 1=mild, 2=neutral/unsure, 3=clear, 4=severe.
humiliate	0–4	Humiliation toward the group: 0=none, 1=mild, 2=neutral/unsure, 3=attempted humiliation, 4=degrading.
dehumanize	0–4	Dehumanization of the group: 0=strongly no, 1=no, 2=unclear/neutral, 3=yes, 4=strongly yes.
violence	0–4	Call for violence against the group: 0=strongly no, 1=no, 2=unclear/neutral, 3=yes, 4=strongly yes.
genocide	0–4	Call for deliberate large-scale killing of the group: 0=strongly no, 1=no, 2=unclear/neutral, 3=yes, 4=strongly yes.
status	0–4	Relative social status framing: 0=strongly inferior, 1=inferior, 2=equal/neutral, 3=superior, 4=strongly superior.
respect	0–4	Respect toward the group: 0=strongly disrespectful, 1=disrespectful/rude, 2=neutral, 3=respectful/polite, 4=strongly respectful.
attack_defend	0–4	Stance toward the group: 0=strongly defending, 1=defending, 2=neutral/mixed, 3=attacking, 4=strongly attacking.

Table 4: Per-attribute scoring rubrics used in the vanilla prompting condition. Each attribute is queried with a fixed prompt defining the ordinal scale. In the persona condition, the persona header in Table 3 is prepended verbatim; the rubric itself is unchanged.

that attribute-level predictions from smaller models can still recover a meaningful hate speech signal, though with a notable drop compared to their larger counterparts (70.57 and 68.85, respectively).

Compared to direct prompting baselines, the picture is more nuanced for smaller models than for large ones. While our pipeline consistently achieves superior accuracy and precision across both models, some baselines, particularly attribute-aware prompting for Llama-8B (F1: 61.99), achieve competitive or slightly higher F1 than our pipeline (56.34). This is largely driven by the same high recall/low precision pattern observed in large model baselines, where the model flags the vast majority of comments as hate speech. Our pipeline maintains substantially better precision (71.36 vs. 46.65 for Llama-8B), indicating more reliable, calibrated predictions. Notably, Llama-8B few-shot nearly collapses, achieving 99.54% recall by pre-

dicting almost everything as hate speech, suggesting that few-shot prompting is unstable for smaller models on this task.

D Ablation Study

Table 7 reports the ablation results for the hate speech score reconstruction pipeline across four formula variants, evaluated on the vanilla condition for both large models. The variants are:

- A: No Ridge, confidence + Spearman weighted sum

- B: Ridge with confidence weighting (our method)

- C: Ridge without confidence weighting

- D: No Ridge, Spearman weighted sum only

The results reveal three clear findings. First, Ridge regression is essential; formulas A and D,

		Respect	Sentiment	Status	Hate speech	Genocide	Dehumanize	Attack-defend	Violence	Humiliate	Insult
Llama-8B	Vanilla	-70.25	-1.56	38.68	-46.69	43.03	55.40	58.66	54.99	64.79	67.47
	Persona	-67.05	-43.31	4.15	-50.11	41.08	51.21	54.93	48.53	51.80	56.59
Qwen-7B	Vanilla	-66.95	-59.56	-31.57	-48.54	36.76	56.22	63.00	56.05	60.63	66.72
	Persona	-64.97	-56.66	-8.86	-50.20	41.06	55.61	59.98	53.49	60.84	65.24

Table 5: Spearman rank correlation ($\times 100$) between LLM attribute predictions and human ratings for small models, ordered from most negative to most positive.

		R^2	F1	Acc.	Prec.	Rec.
Llama-8B	Zero-shot	–	49.05	74.50	51.86	46.54
	Few-shot	–	50.19	47.88	33.55	99.54
	Definition	–	59.86	74.40	51.04	72.38
	Attr. aware	–	61.99	70.13	46.65	92.33
	Attr. value	–	60.19	68.57	45.19	90.07
	Vanilla	62.55	56.34	80.97	71.36	46.54
	Persona	61.03	60.42	80.86	66.49	55.37
Qwen-7B	Zero-shot	–	58.08	63.61	41.72	95.55
	Few-shot	–	54.38	56.69	37.65	97.84
	Definition	–	57.81	63.59	41.63	94.58
	Attr. aware	–	58.53	64.40	42.25	95.22
	Attr. value	–	50.05	47.69	33.45	99.36
	Vanilla	60.53	56.11	80.37	68.39	47.56
	Persona	57.92	54.57	79.86	67.39	45.85

Table 6: Hate speech score reconstruction and classification results ($\times 100$) for small models. R^2 is reported as mean $\pm$ std over 5 folds. Baselines are zero-shot direct prompting variants. Our pipeline consistently achieves superior accuracy and precision despite lower F1 on some baseline variants.

Figure 3: Average model confidence versus Spearman correlation with human ratings for each attribute.

which use weighted sums without Ridge, collapse to strongly negative R^2 values (as low as -13.24 for Llama and -10.15 for Qwen), confirming that a simple weighted aggregation of attribute predictions cannot recover the continuous hate speech score. Without Ridge, the inverted evaluative attributes directly subtract from the score in an uncontrolled way, producing unreliable predictions.

Second, confidence weighting improves performance; formula C, which uses Ridge without confidence weighting, achieves a lower R^2 than our method B (68.63 vs 70.57 for Llama-70B, 68.27 vs 68.85 for Qwen-72B). While the gain is modest, it is consistent across both models, supporting the intuition that a confident prediction on an attribute carries more signal than an uncertain one.

Third, Spearman pre-scaling is redundant; adding it on top of confidence weighting before Ridge produces identical results, confirming that Ridge absorbs the Spearman pre-scaling into its learned weights automatically. This simplifies the final pipeline to confidence weighting followed by Ridge regression.

E   Qualitative Examples

Table 8 presents three representative comments illustrating LLM attribute prediction behavior across the hate speech severity spectrum. The hate speech score threshold for binary classification is 0.5, following Kennedy et al. (2020); comments with a score above this threshold are classified as hate speech. In the supportive trans community comment (ground truth: -8.34), Llama correctly rates behavioral attributes such as insult, violence, and genocide as zero, but incorrectly assigns high scores to sentiment and respect, a direct manifesta-

	Formula	R^2	Pearson	Spearman
Llama-70B	A	-8.44	0.83	0.83
	B	70.57	0.84	0.83
	C	68.63	0.83	0.82
	D	-13.24	0.82	0.81
Qwen-72B	A	-7.38	0.83	0.81
	B	68.85	0.83	0.82
	C	68.27	0.83	0.81
	D	-10.15	0.82	0.81

Table 7: Ablation study comparing formula variants for hate speech score reconstruction (vanilla condition, large models only). C = confidence weighting. R^2 reported as percentage ($\times 100$).

tion of the evaluative attribute inversion identified in Table 1. In the extreme hate speech example (ground truth: 6.30), Llama correctly captures behavioral dimensions but rates sentiment and respect as zero when humans rate them at 4, causing the Ridge pipeline to severely underestimate the final score (1.875 vs 6.30). The two intermediate examples further confirm that behavioral attributes are predicted more reliably than evaluative ones, and that Ridge predictions closely track ground truth when evaluative attributes are less central to the comment's hateful content.

F Use of Artifacts

We use the Measuring Hate Speech (MHS) corpus, which is publicly available on HuggingFace under a Creative Commons Attribution 4.0 International (CC BY 4.0) license. This license permits use for research purposes. We use Meta-Llama-3.1-70B-Instruct and Meta-Llama-3.1-8B-Instruct, released under the Llama 3.1 Community License, which permits research and commercial use. We use Qwen2.5-72B-Instruct and Qwen2.5-7B-Instruct, released under the Apache 2.0 License, which permits research and commercial use. We use vLLM, released under the Apache 2.0 License, for model serving. Our experimental code will be made publicly available upon publication. The experiments were carried out on machines with NVIDIA GeForce GTX 1080 Ti GPUs. During evaluation, models were used in inference mode without any parameter updates.

G AI Usage Statement

We used AI assistance in several stages of this work. Claude (Anthropic) was used as a writing assistant to help draft, revise, and improve the clarity of the

	Human	Llama
"Fellow trans girl here! Love and support confirmed!"		
Hate Score	-8.34	-4.83
sentiment	0.00	4.00
respect	0.00	4.00
status	2.00	4.00
insult	0.00	0.00
humiliate	0.00	0.00
dehumanize	0.00	0.00
violence	0.00	0.00
genocide	0.00	0.00
attack_defend	0.25	0.00
*"They ain't got no new n***** coming out???"*		
Hate Score	-0.70	-1.03
sentiment	3.25	1.00
respect	3.25	1.00
status	2.25	1.00
insult	2.75	3.00
humiliate	2.75	3.00
dehumanize	2.25	3.00
violence	1.25	0.00
genocide	0.50	0.00
attack_defend	2.25	3.00
*"Dig burn PITS and treat them THE INVADING N**** ALL OVER EUROPE..."*		
Hate Score	6.30	1.88
sentiment	4.00	0.00
respect	4.00	0.00
status	4.00	0.00
insult	4.00	4.00
humiliate	4.00	4.00
dehumanize	4.00	4.00
violence	4.00	4.00
genocide	4.00	4.00
attack_defend	4.00	4.00

Table 8: Representative examples showing human vs Llama-70B attribute predictions and Ridge hate speech score. Evaluative attributes (sentiment, respect, status) show systematic misalignment, while behavioral attributes are predicted more reliably.

paper text. All AI-generated text was reviewed, edited, and verified by the authors. All experimental results, analyses, and scientific claims are the sole responsibility of the authors.