CAT: Collaborative Adversarial Training

Abstract

Adversarial training can improve the robustness of neural networks. Previous adversarial training methods focus on a single training strategy and do not consider the collaboration between different training strategies. In this paper, we find different adversarial training methods have distinct robustness for sample instances. For example, an instance can be correctly classified by a model trained using standard adversarial training (AT) but not by a model trained using TRADES, and vice versa. Based on this phenomenon, we propose a collaborative adversarial training framework to improve the robustness of neural networks. Specifically, we simultaneously use different adversarial training methods to train two robust models from scratch. We input the adversarial examples generated by each network to the peer network and use the peer network's logit to guide its network's training. **C**ollaborative **A**dversarial **T**raining (**CAT**) can improve both robustness and accuracy. Finally, Extensive experiments on CIFAR-10 and CIFAR-100 validated the effectiveness of our method. CAT achieved new state-of-the-art robustness without using any additional data on CIFAR-10 under the Auto-Attack benchmark[1].

1 Introduction

With the development of deep learning, Deep Neural Networks (DNNs) have been applied to various fields, such as: image classification (He et al., 2016), object detection (Redmon et al., 2016), semantic segmentation (Pal & Pal, 1993), etc. And state-of-the-art performance has been obtained. But recent research has found that DNNs are vulnerable to adversarial perturbations (Goodfellow et al., 2014). A finely crafted adversarial perturbation by a malicious agent can easily fool the neural network. This raises security concerns about the deployment of neural networks in security-critical areas such as Autonomous driving (Chen et al., 2019) and medical diagnostics (Kong et al., 2017).

To cope with the vulnerability of DNNs, different types of methods have been proposed to improve the robustness of neural networks, including adversarial training (Madry et al., 2017), defensive distillation (Papernot et al., 2016), feature denoising (Xie et al., 2019) and model pruning (Madaan et al., 2020). Among them, Adversarial Training (AT) is the most effective method to improve adversarial robustness. AT can be regarded as a type of data augmentation strategy that trains neural networks based on adversarial examples crafted from natural examples. AT is usually formulated as a min-maximization problem, where the inner maximization generates adversarial examples, while the outer minimization optimizes the parameters of the model based on the adversarial examples generated by the inner maximization process.

The previous methods have focused on how to improve the model's adversarial accuracy, focusing only on the numerical improvement, but not on the characteristics of the different methods. We ask: *Do different adversarial training methods perform the same for different sample instances?* We analyzed different adversarial training methods (taking AT (Madry et al., 2017) and TRADES (Zhang et al., 2019) as examples) and found that different methods behave differently for sample instances, as illustrated in Figure 1. Specifically, for the same adversarial example, the AT-trained network can classify correctly, while the TRADES-trained network misclassifies. Similarly, some examples can be correctly classified by the TRADES-trained network, but not by the AT-trained network. That is, although AT and TRADES have the same numerical adversarial accuracy, they behave differently for sample instances. This raises the question:

Do two networks learn better if they collaborate?

---

[1] https://github.com/fra31/auto-attack

Figure 1: Classification results of different adversarial training methods on sample instances. The first row is the classification result of the model trained by AT and the second row is the classification result of the model trained by TRADES. 1 means correct classification and 0 means incorrect classification. 10000 is the size of the CIFAR-10 test set. The third row is the result of correct classification by both AT and TRADES, and the result is shown in red. It can be seen that the models trained by different methods perform differently on sample instances.

Based on this observation, we propose a **C**ollaborative **A**dversarial **T**raining (**CAT**) framework to improve the robustness of neural networks. Our framework is shown in Figure 2. Specifically, we simultaneously train two deep neural networks separately using different adversarial training methods. At the same time, the adversarial examples generated by this network are input to the peer network to obtain the corresponding logit. Then the logit obtained by the peer network is used to guide the learning of this network together with its own adversarial training objective function. We expect to improve the robustness of the neural network by allowing peers to learn from each other in this collaborative learning way. Extensive experiments on different neural networks and different datasets demonstrate the effectiveness of our approach. CAT achieved new state-of-the-art robustness without any additional synthetic data or real data on CIFAR-10 under the Auto-Attack benchmark.

In summary our contribution is threefold as follows.

- We find that the models obtained using different adversarial training methods have different representations for individual sample instances.
- We propose a novel adversarial training framework: collaborative adversarial training. CAT simultaneously trains two neural networks from scratch using different adversarial training methods and allows them to collaborate to improve the robustness of the model.
- We have conducted extensive experiments on a variety of datasets and networks, and evaluated them on state-of-the-art attacks. We demonstrate that CAT can substantially improve the robustness of neural networks and obtain new state-of-the-art performance without any additional data.

2 RELATED WORK

2.1 ADVERSARIAL ATTACK

Since Goodfellow et al. (2014) discovered that DNNs are vulnerable to adversarial examples, a large number of works have been proposed to craft adversarial examples. Based on the accessibility to the knowledge of the target model, it can be divided into white-box attacks and black-box attacks. White-box attacks craft adversarial examples based on the knowledge of the target model, while black-box attacks are agnostic to the knowledge of the target model.

White-box Attack: Goodfellow et al. (2014) proposed FGSM to efficiently craft adversarial examples, which can be generated in just one step. Later FGSM was extended to different iterative

attack methods. I-FGSM performs FGSM iteratively with a small step size. Madry et al. (2017) proposed PGD to generate adversarial examples, which is the most efficient way of using the first-order information of the network. Dong et al. (2018) combines momentum into the iterative process to help the model escape from local optimal points. And the adversarial examples generated by this method are also more transferable. Boundary-based attacks such as deepfool (Moosavi-Dezfooli et al., 2016) and CW (Carlini & Wagner, 2017) also make the model more challenging. Recently, the ensemble approach of diverse attack methods (Auto-Attack), consisting of APGD-CE (Croce & Hein, 2020b), APGD-DLR (Croce & Hein, 2020b), FAB (Croce & Hein, 2020a) and Square Attack (Andriushchenko et al., 2020), became a benchmark for testing model robustness.

Black-box Attack: Due to the similarity of the model structure, the adversarial examples generated on the surrogate model can be transferred to fool the target model. There are many ways to explore the transferability of adversarial examples for black-box attacks. Dong et al. (2018) combines momentum with an iterative approach to obtain better transferability. Scale-invariance (Lin et al., 2019) boosts the transferability of adversarial examples by transforming the inputs on multiple scales.

2.2 Adversarial Robustness

Adversarial attacks present a significant threat to DNNs. For this reason, many methods have been proposed to defend against adversarial examples, including denoising (Xie et al., 2019), adversarial training (Madry et al., 2017) and input purification (Naseer et al., 2020). ANP (Madaan et al., 2020) finds the vulnerability of latent features and uses pruning to improve robustness. Madry uses PGD to generate adversarial examples for adversarial training, which is also the most effective way to defend against adversarial examples. A large body of work uses new regularization or objective functions to improve the effectiveness of standard adversarial training. Kannan et al. (2018) uses Adversarial logit pairing to improve robustness by encouraging the logits of normal and adversarial examples to be closer together. TRADES (Zhang et al., 2019) uses KL divergence to regularize the output of adversarial and pure examples.

2.3 Knowledge Distillation

Knowledge distillation (KD) is commonly used for model compression and was first used by hinton (Hinton et al., 2015) to distill knowledge from a well-trained teacher network to a student network. KD can significantly improve the accuracy of student models. There have been many later works to improve the effectiveness of KD (Romero et al., 2014). In recent years, KD has been extended to other areas. Goldblum et al. (2020) analyzes the application of knowledge distillation to adversarial robustness and proposes ARD to transfer knowledge from a large teacher model with better robustness to a small student model. ARD can produce a student network with better robustness than training from scratch. In this paper, we propose a more effective collaborative training framework to improve the robustness of the network.

3 Proposed Method

3.1 Motivation

We investigated the performance of the robust models obtained by different training methods on sample instances. We found that different models perform differently on sample instances: for some samples, the AT (Madry et al., 2017)-trained model correctly classifies, while the TRADES (Zhang et al., 2019)-trained model misclassifies. Similarly, for some samples, the TARDES-trained network can classify correctly, while the AT-trained network can misclassify. A straightforward conclusion can be drawn that the networks trained by different methods master different knowledge, although their accuracy values are about the same. So can we use the knowledge learned from these two networks to improve the robustness of neural networks? A simple idea is to let two networks that master different knowledge learn collaboratively. For this purpose, we propose collaborative adversarial training. CAT improves the robustness of neural networks by making the knowledge of both networks interact during the training procedure. And the framework is illustrated in Figure 2.

Figure 2: **The framework of CAT, performing adversarial training collaboratively.** Given a batch of natural samples, the two networks f and g are attacked separately to generate adversarial examples u and v. Then u and v are fed into both networks to obtain the corresponding logits. We then use the logits obtained from the peer networks to guide the learning of its network, i.e., $g_u \to f_u, f_v \to g_v$.

3.2 COLLABORATIVE ADVERSARIAL TRAINING (CAT)

We take the methods of AT and TRADES as an example to introduce collaborative adversarial training. We first briefly introduce the training objective functions of AT and TRADES and then introduce CAT in detail.

Adversarial training is defined as a min-maximization problem, and Madry et al. (2017) proposes to use PGD for adversarial training. That is, PGD is used to generate adversarial examples for the internal maximization process, while external minimization uses the internal PGD-generated adversarial examples and the ground-truth label y to optimize the model parameters. AT is formulated as:

$$\min_{\theta} \mathbb{E}_{(x,y) \in D_{data}} (\arg \max_{\delta} L(f_\theta^{AT}(x_{AT}^{adv}), y)), \quad (1)$$

$$x_{AT}^{adv} = x + \delta. \quad (2)$$

where D_{data} is the training data distribution, x and y are training data and corresponding label samples from D_{data}. f_θ is a neural network parameterized by θ. L is the standard cross-entropy loss used in image classification tasks. δ is the adversarial perturbations generated by PGD. Follwing previous study, δ is bounded by l_∞.

Neural Networks trained by AT can obtain a certain level of robustness, with compromises on the accuracy of natural samples. For this purpose, TRADES uses a new training objective function for adversarial training. Formulated as:

$$\min_{\theta'} \mathbb{E}_{(x,y) \in D_{data}} L(g_{\theta'}^{TRADES}(x), y) + \lambda D_{KL}(g_{\theta'}^{TRADES}(x), g_{\theta'}^{TRADES}(x_{TRADES}^{adv})), \quad (3)$$

where x^{adv} is the adversarial data corresponding to natural data x and y is the true label. L is the cross-entropy loss in classification task. D_{KL} is the KL divergence to pushing natural logits and adversarial logits together. λ is a trade-off parameter.

CAT expects to improve robustness by letting neural networks trained by different methods exchange knowledge information, i.e., collaborative adversarial learning. As illustrated in Figure 2. we use the logit of a peer network to guide the learning of this network. Specifically, we input the adversarial data crafted by the AT-trained network into the TRADES-trained network to get the corresponding logit. Then use the logit obtained by the TRADES-trained network to guide the training of the AT-trained network. The formulation goes to:

$$L_1 = D_{KL}(f^{AT}(x_{AT}^{adv}), \hat{g}^{TRADES}(x_{AT}^{adv})), \quad (4)$$

where D_{KL} is KL divergence used to compute the relative entropy, the same as in TRADES. f^{AT} is the network trained with AT and g^{TRADES} is the network trained with TRADES. $\hat{g}^{TRADES}(x_{AT}^{adv})$ represents that we take the logit obtained by TRADES-trained network as a constant. x_{AT}^{adv} is the adversarial data generated by f^{AT} with PGD function based on natural example x.

Similarly, to make the two networks learn collaboratively. We need to feed the adversarial samples generated by the TRADES network to the AT network to obtain the corresponding logit. And then the logit obtained by the peer network is used to guide the training of the TRADES-trained network. The loss is formulated as:

$$L_2 = D_{KL}(g^{TRADES}(x_{TRADES}^{adv}), \hat{f}^{AT}(x_{TRADES}^{adv})). \tag{5}$$

x_{TRADES}^{adv} is the adversarial example crafted by TRADES-trained network use KL divergence function. $\hat{f}^{AT}(x_{TRADES}^{adv})$ represents that we take the logit obtained by AT-trained network as a constant.

It is not enough to let the two networks learn from each other in this way. Real class labels are needed to guide them. For this purpose, we combine the respective training objective functions of the two networks and the mutual learning objective function to guide the learning of the networks together. Therefore, the training objective function for collaborative adversarial training based on AT and TRADES is:

$$L_{total} = \alpha L_{TRDES} + (1 - \alpha)L_2 + \beta L_{AT} + (1 - \beta)L_1, \tag{6}$$

where α and β is the trade-off parameter to balance the guidance of peer logit and the original training objective function. L_{TRADES} is the training objective of TRADES defined in Equation (3). And L_{AT} is the training objective of AT defined in Equation (1). The first two items in Equation (6) are used to train model g and the last two items are used to train model f, due to we take the peer logit as constant.

The decision boundaries learned by different adversarial training methods are different. Under the constraint of peer logit, i.e., Equation (4) and Equation (5), the two networks trained by different methods continuously optimize the classification decision boundaries in the process of collaborative learning. Finally, both networks learn better decision boundaries than learning alone to obtain better robustness.

Our collaborative adversarial learning is a generalized adversarial training method that can be used with any two adversarial methods. Generally, CAT can use any number of different adversarial training methods for collaborative learning. However in this paper, for computational efficiency and simplicity of implementation, we only consider collaborative learning of two different adversarial training methods.

4 EXPERIMENT RESULT

In this section, we conduct extensive experiment on popular benchmark datasets to demonstrate the effectiveness and performance of CAT. First, we briefly introduce the experiment setup and implementation details of CAT. Then, ablation study is done to choose the best hyperparameters and CAT methods. Finally, according to the best CAT methods, we report the white-box and black-box adversarial robustness on two popular benchmark datasets. All images values are scaled into [0,1], and all our experiments are run on a single NVIDIA GeForce GTX 1080Ti.

Datasets: We used two benchmark datasets, including CIFAR-10 (Krizhevsky et al., 2009) and CIFAR-100 (Krizhevsky et al., 2012). CIFAR-10 has 10 classes. For each class, there are 5000 images for training and 1000 images for test. And for CIFAR-100, there are 100 classes, and similarly for each class, there are 500 images for training and 100 images for test. Both datasets are widely used for training and testing adversarial robustness. The image size in both datasets is 32×32.

Training setup: Our overall training parameters refer to Madaan et al. (2020). Specifically, we use SGD (momentum 0.9, batch size 128) to train ResNet18 for 200 epochs on the CIFAR-10 dataset with weight decay 5e-4 and initial learning rate 0.1 which is divided by 10 at 100-th and 150-th epoch, respectively. RandomCrop and RandomHorizontalFlip are used as data augmentation. For the internal maximization process, we use PGD_{10} adversarial attack to solve, with random start, step size 2.0/255 and perturbation size 8.0/255. We use $\lambda = 100$ in all experiments. The experimental

Figure 3: Adversarial robustness using different hyperparameters under the trades-at for collaborative adversarial training framework. From left to right, the results of Clean acc, FGSM acc, PGD acc, and AA acc are shown. model f and model g represent the results of using TRADES and AT in the CAT training framework, respectively.

Table 1: The white-box robustness results (accuracy (%)) of different CAT methods on CIFAR-10. We report the results of best checkpoint and last checkpoint. The best results are marked using **boldface**. Two ResNet-18 networks are used in our CAT framework.

Method	Best Checkpoint					Last Checkpoint				
	Clean	FGSM	PGD_{20}	CW_∞	AA	Clean	FGSM	PGD_{20}	CW_∞	AA
$CAT_{AT-TRADES}$	83.74	59.69	54.44	52.60	50.52	84.45	**60.03**	**53.01**	**52.01**	49.30
	83.55	59.78	**54.52**	52.58	50.86	84.12	59.69	52.82	51.88	49.39
CAT_{AT-ALP}	84.66	59.94	53.11	51.90	49.74	84.71	59.84	50.77	50.53	47.80
	85.21	**60.21**	53.02	52.13	49.96	**85.27**	59.75	51.10	50.69	47.91
$CAT_{TRADES-ALP}$	83.91	59.76	54.44	52.56	**51.02**	84.67	59.85	52.51	51.43	49.31
	84.75	59.76	54.17	**52.72**	50.85	**85.27**	59.82	52.56	51.83	**49.64**

parameters of ResNet18 in CIFAR-100, WideResNet-34-10 in CIFAR-10 and CIFAR-100 are the same as described above.

Evaluation setup: We report the clean accuracy on natural examples and the adversarial accuracy on adversarial examples. For adversarial accuracy, we report both white-box and black-box. We follow the widely used protocols in the adversarial research field. For the white-box attack, we consider three basic attack methods: FGSM (Goodfellow et al., 2014), PGD (Madry et al., 2017), and CW_∞ (Carlini & Wagner, 2017) optimized by PGD_{20}, and a stronger ensemble attack method named AutoAttack (AA) (Croce & Hein, 2020b). For the black-box attacks, we consider both transfer-based attacks and query-based attacks.

Due to the fact that CAT uses two methods for collaborative training, we report the results for both networks. For example, the method of collaborative adversarial training using TRADES and ALP can be denoted as $CAT_{TRADES-ALP}$.

4.1 ABLATION STUDY

4.1.1 HYPERPARAMETER:

CAT improves adversarial robustness through the learning of collaboration, which requires both the knowledge of peer networks and the guidance of the ground truth label. The balance of original methods and the collaborative is a trade-off by a hyperparameter α and β. For simplicity, we set α equals β in our experiment. We execute collaborative training by TRADES and AT as the base method and experiment with different trades-off parameters. We test various α value varying from 1/50 to 1/5. The experiment results are illustrated in Figure 3. From the figure we can conclude that if α is too high, i.e., little knowledge is drawn from the peer network, the effect is about the same as training with AT and trades alone. If α is too low, i.e., overly focused on the knowledge from the

peer network, The network is also not very robust. Since Auto-Attack is currently the most powerful integrated attack method, we choose hyperparameter α and β based primarily on the robustness of the network against AA. In the following experiments, we set $\alpha = \beta = 1/20.0$ by default.

4.1.2 DIFFERENT CAT METHODS:

As described in Section 3.2, any two adversarial training methods can be incorporated into the CAT framework and learned collaboratively. Considering that different adversarial training methods have distinct properties, the performance of different CAT methods may also vary. For this reason, we consider three collaborative adversarial training methods, AT-TRADES, AT-ALP, and TRADES-ALP, respectively. Table 1 shows the performance of the different CAT methods. All CAT training methods obtained good robustness against four attack methods. We again mainly consider the performance of auto-attack and choose TRADES-ALP as the base method for our CAT.

4.2 ADVERSARIAL ROBUSTNESS

4.2.1 WHITE-BOX ROBUSTNESS

For FGSM, PGD, CW_{∞}, AA, the attack perturbations are all 8.0/255 and the step size for PGD, CW_{∞} are 2/25, with 20 iterations. According to the way of reporting in previous papers, we report both the best checkpoint and the last checkpoint of the training phase. The best checkpoint result of the training phase is selected based on the model's PGD defense results for the test dataset (attack step size 2.0/255, iteration number 10, perturbation size 8.0/255).

Table 2 shows the adversarial accuracy of the networks trained by different methods on two datasets CIFAR-10 and CIFAR-100 against the four attacks. We also report the accuracy of the model for natural examples. From the table, we can obtain the following conclusions: (1) our method obtains good robustness against all four attacks on both datasets. For example, for the strongest AA attack method, CAT can obtain 2% improvement. (2) our method obtains high adversarial robustness while ensuring accuracy for natural examples. Although there is still a big gap compared to 94.65 of the standard training strategy, there is a nearly 1% improvement in the accuracy of the natural examples compared to the other three methods. (3) The robustness of both networks is significantly improved in the CAT training framework. The robustness of both networks is higher than separately trained ones. (4) The difference in accuracy between the two networks trained in the CAT framework is smaller than separately trained ones, which demonstrates that the two networks do well in collaborative learning. For example, for the CIFAR-10 dataset, the difference in robustness between the two networks of TRADES-ALP against AA in the CAT training framework is 0.17%, while the difference is 0.73% under separate training. The same conclusion can be drawn from CIFAR-100 datasets.

4.2.2 BLACK-BOX ROBUSTNESS

For black-box attacks, we consider both transfer-based attacks and query-based attacks. For the transfer-based attack, we use the standard adversarial training of ResNet-34 as the surrogate model, trained with the same parameters as described in Section 4. First, we perform the attack on the surrogate model to generate adversarial examples and then transfer the adversarial examples to the target network to get the robustness of the target network. Here, we consider four attacks: FGSM, PGD_{20}, PGD_{40}, and CW_{∞}, with the same attack parameters as Section 4.2.1. For query-based attacks, we consider Square attack, which is an efficient black-box query-based attack method. Table Table 3 shows the results, and our method CAT achieves the best performance.

4.3 COMPARISION TO SOTA

We use two WideResNet-34-10 (Zagoruyko & Komodakis, 2016) networks for collaborative adversarial training, one using the TRADES (Zhang et al., 2019) training method and the other using the ALP (Kannan et al., 2018) training method. Table 4 shows the accuracy of the different methods for natural examples and the robustness against Auto-Attack. For some methods, we also report the results of WideResNet-34-20. All results are from the original paper. From the table we can conclude that the robustness of both networks trained with CAT outperforms the previous methods, demonstrating the state-of-the-art performance obtained by our CAT.

Table 2: The white-box robustness results (accuracy $(\%)$) of CAT on CIFAR-10 and CIFAR-100. We report the results of best checkpoint and last checkpoint. The best results are marked using **boldface**. Two ResNet-18 networks are used in our CAT framework. TRA-ALP is short for TRADES-ALP due to the limitation.

| Dataset | Method | Best Checkpoint | | | | | Last Checkpoint | | | | |
		Clean	FGSM	PGD_{20}	CW_∞	AA	Clean	FGSM	PGD_{20}	CW_∞	AA
CIFAR-10	Natural	**94.65**	19.26	0.0	0.0	0.0	**94.65**	19.26	0.0	0.0	0.0
	AT	82.82	57.57	51.76	50.05	47.55	84.53	53.90	43.56	44.19	41.57
	TRADES	83.17	59.22	52.63	50.79	49.21	83.04	57.46	49.81	49.01	47.03
	ALP	83.85	57.20	51.88	50.11	48.48	84.64	55.35	44.96	44.54	42.62
	$CAT_{TRA-ALP}$	83.91	**59.76**	**54.44**	52.56	**51.02**	84.67	**59.85**	52.51	51.43	49.31
		84.75	**59.76**	54.17	**52.72**	50.85	85.27	59.82	**52.56**	**51.83**	**49.64**
CIFAR-100	Natural	**75.55**	9.48	0.0	0.0	0.0	**75.39**	9.57	0.0	0.0	0.0
	AT	57.42	31.90	28.78	27.27	24.88	57.34	26.77	21.24	21.50	19.59
	TRADES	56.98	31.72	29.04	25.30	24.23	55.08	30.40	26.81	24.78	23.68
	ALP	61.01	31.41	26.78	25.68	23.51	58.4	27.97	22.63	21.87	20.42
	$CAT_{TRA-ALP}$	61.31	35.83	**33.09**	29.17	**27.17**	61.78	**35.84**	**32.76**	**29.48**	**27.29**
		62.53	**36.05**	32.92	29.16	26.90	62.52	35.79	32.51	29.24	26.73

Table 3: The black-box robustness results (accuracy $(\%)$) of CAT on CIFAR-10 and CIFAR-100. We only report the results of the best checkpoint. The best results are marked using **boldface**. Two ResNet-18 networks are used in our CAT framework. TRA-ALP is short for TRADES-ALP due to the limitation.

| Method | CIFAR-10 | | | | | CIFAR-100 | | | | |
	FGSM	PGD_{20}	PGD_{40}	CW_∞	Square	FGSM	PGD_{20}	PGD_{40}	CW_∞	Square
AT	64.54	61.70	61.57	61.42	56.16	39.15	37.56	37.46	38.85	30.11
TRADES	65.63	63.57	63.57	63.23	55.97	39.06	37.73	37.79	38.86	28.72
ALP	64.95	62.38	62.32	61.78	55.78	40.29	38.97	38.85	40.03	29.85
$CAT_{TRA-ALP}$	65.73	63.65	63.78	63.24	57.55	42.26	40.76	40.76	41.78	33.04
	66.06	**63.91**	**63.88**	**63.26**	**57.95**	**42.81**	**41.55**	**41.42**	**42.42**	**33.30**

4.4 COMPARISION TO KD-AT

In general, the robustness of large models is higher than that of small models under the same training settings. For example, WideResNet-34-10 (Zagoruyko & Komodakis, 2016) trained by TRADES can achieve 53.08% robustness against AA, while the accuracy of ResNet-18 is only 49.21%. From this motivation, some authors have used knowledge distillation to distill the robustness of large models to small models and obtained good results. Considering that CAT also involves the collaborative training of two models, we compare CAT with the KD-AT method. To give a fair comparison, unlike the previous experiments using two same size networks for CAT, we use two different size networks for CAT training and then report the accuracy of both the two networks, i.e., WideResNet-34-10 and ResNet-18. Note that, unlike the KD method where the teacher is trained in advance, our CAT is trained with both the large model and the small model simultaneously, so there is no concept of teacher and student. In another word, we extend previous off-line distillation to a on-line way and achieve better performance.

Table 5 shows the results of Knowledge Distillation-AT and CAT, where ARD (Goldblum et al., 2020), IAD (Zhu et al., 2021), and RSLAD (Zi et al., 2021) are trained by KD-AT using TRDES trained WideResNet-34-10 network as teacher (second row in Table 5). CAT was collaboratively

Table 4: Quantitative comparison with the state-of-the-art adversarial traing methods. Two WideResNet-34-10 networks are used in our CAT framework.

Method	Architecture	Nat	AA
Bag of Tricks for AT (Pang et al., 2020a)	WideResNet-34-10	86.28	53.84
HE* (Pang et al., 2020b)	WideResNet-34-20	85.14	53.74
LBGAT+TRADES ($\alpha = 0$)* (Cui et al., 2021)	WideResNet-34-20	**88.70**	53.57
LBGAT+TRADES ($\alpha = 0$) (Cui et al., 2021)	WideResNet-34-10	88.22	52.86
LBGAT+TRADES ($\alpha = 6$) (Cui et al., 2021)	WideResNet-34-10	81.98	53.14
Overfitting in AT* (Rice et al., 2020)	WideResNet-34-20	85.34	53.42
Overfitting in AT (Rice et al., 2020)	WideResNet-34-10	85.18	53.14
Self-Adaptive Training (Huang et al., 2020)	WideResNet-34-10	83.48	53.34
FAT (Zhang et al., 2020)	WideResNet-34-10	84.52	53.51
TRADES (Zhang et al., 2019)	WideResNet-34-10	84.92	53.08
LLR (Qin et al., 2019)	WideResNet-40-8	86.28	52.84
CAT$_{TRADES-ALP}$	WideResNet-34-10	86.22	54.11
		86.51	**54.20**

Table 5: Quantitative comparison with the state-of-the-art Knowledge-Distillation AT methods. We use WideResNet-34-10 and ResNet-18 networks in the CAT framework for a fair comparison.

Method	Architecture	Distillation	Role	Clean	AA
TRADES (Zhang et al., 2019)	WideResNet-34-10	-	teacher	84.92	53.08
ARD (Goldblum et al., 2020)	ResNet-18	✓	student	83.93	49.19
IAD (Zhu et al., 2021)	ResNet-18	✓	student	83.24	49.10
RSLAD (Zi et al., 2021)	ResNet-18	✓	student	83.38	51.49
CAT$_{TRADES-ALP}$	WideResNet-34-10	✗	-	**85.04**	**55.04**
	ResNet-18	✗	-	84.39	50.14

trained using two networks of different sizes. It can be seen that our method obtains good results and also obtains high clean accuracy.

5 CONCLUSIONS

In this paper, we first analyze the properties of different adversarial training methods and find that networks trained by different methods perform differently on sample instances, i.e., the network can correctly classify samples that are misclassified by other networks. Based on this observation, we propose a collaborative adversarial training framework, which aims to use the knowledge learned by peer networks to guide its learning. Thus improving the robustness of both networks. Extensive experiments on different datasets and different networks demonstrate the effectiveness of our approach, and state-of-the-art performance is achieved. Broadly, CAT can be easily extended to multiple networks for collaborative adversarial training, e.g, three peer networks. However, our method has some limitations the same as previous method that adversarial training consumes training resources, and CAT has to train two networks simultaneously. Work on how to accelerate CAT will be carried out in the future.

REFERENCES

Maksym Andriushchenko, Francesco Croce, Nicolas Flammarion, and Matthias Hein. Square attack: a query-efficient black-box adversarial attack via random search. In *ECCV*, 2020.

Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *2017 ieee symposium on security and privacy (sp)*, 2017.

Jianyu Chen, Bodi Yuan, and Masayoshi Tomizuka. Model-free deep reinforcement learning for urban autonomous driving. *arXiv preprint arXiv:1904.09503*, 2019.

Francesco Croce and Matthias Hein. Minimally distorted adversarial examples with a fast adaptive boundary attack. In *ICML*, 2020a.

Francesco Croce and Matthias Hein. Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks. In *ICML*, 2020b.

Jiequan Cui, Shu Liu, Liwei Wang, and Jiaya Jia. Learnable boundary guided adversarial training. In *ICCV*, 2021.

Yinpeng Dong, Fangzhou Liao, Tianyu Pang, Hang Su, Jun Zhu, Xiaolin Hu, and Jianguo Li. Boosting adversarial attacks with momentum. In *CVPR*, 2018.

Micah Goldblum, Liam Fowl, Soheil Feizi, and Tom Goldstein. Adversarially robust distillation. In *AAAI*, 2020.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

Geoffrey Hinton, Oriol Vinyals, Jeff Dean, et al. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

Lang Huang, Chao Zhang, and Hongyang Zhang. Self-adaptive training: beyond empirical risk minimization. *NeurIPS*, 2020.

Harini Kannan, Alexey Kurakin, and Ian Goodfellow. Adversarial logit pairing. *arXiv preprint arXiv:1803.06373*, 2018.

Bin Kong, Xin Wang, Zhongyu Li, Qi Song, and Shaoting Zhang. Cancer metastasis detection via spatially structured deep network. In *IPMI*, 2017.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *NeurIPS*, 2012.

Alex Krizhevsky et al. Learning multiple layers of features from tiny images. *Tech Report*, 2009.

Jiadong Lin, Chuanbiao Song, Kun He, Liwei Wang, and John E Hopcroft. Nesterov accelerated gradient and scale invariance for adversarial attacks. In *ICLR*, 2019.

Divyam Madaan, Jinwoo Shin, and Sung Ju Hwang. Adversarial neural pruning with latent vulnerability suppression. In *ICML*, 2020.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, and Pascal Frossard. Deepfool: a simple and accurate method to fool deep neural networks. In *CVPR*, 2016.

Muzammal Naseer, Salman Khan, Munawar Hayat, Fahad Shahbaz Khan, and Fatih Porikli. A self-supervised approach for adversarial robustness. In *CVPR*, 2020.

Nikhil R Pal and Sankar K Pal. A review on image segmentation techniques. *PR*, 1993.

Tianyu Pang, Xiao Yang, Yinpeng Dong, Hang Su, and Jun Zhu. Bag of tricks for adversarial training. In *ICLR*, 2020a.

Tianyu Pang, Xiao Yang, Yinpeng Dong, Kun Xu, Jun Zhu, and Hang Su. Boosting adversarial training with hypersphere embedding. *NeurIPS*, 2020b.

Nicolas Papernot, Patrick McDaniel, Xi Wu, Somesh Jha, and Ananthram Swami. Distillation as a defense to adversarial perturbations against deep neural networks. In *2016 IEEE symposium on security and privacy (SP)*, 2016.

Chongli Qin, James Martens, Sven Gowal, Dilip Krishnan, Krishnamurthy Dvijotham, Alhussein Fawzi, Soham De, Robert Stanforth, and Pushmeet Kohli. Adversarial robustness through local linearization. *NeurIPS*, 2019.

Joseph Redmon, Santosh Divvala, Ross Girshick, and Ali Farhadi. You only look once: Unified, real-time object detection. In *CVPR*, 2016.

Leslie Rice, Eric Wong, and Zico Kolter. Overfitting in adversarially robust deep learning. In *ICML*, 2020.

Adriana Romero, Nicolas Ballas, Samira Ebrahimi Kahou, Antoine Chassang, Carlo Gatta, and Yoshua Bengio. Fitnets: Hints for thin deep nets. *arXiv preprint arXiv:1412.6550*, 2014.

Cihang Xie, Yuxin Wu, Laurens van der Maaten, Alan L Yuille, and Kaiming He. Feature denoising for improving adversarial robustness. In *CVPR*, 2019.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric Xing, Laurent El Ghaoui, and Michael Jordan. Theoretically principled trade-off between robustness and accuracy. In *ICML*, 2019.

Jingfeng Zhang, Xilie Xu, Bo Han, Gang Niu, Lizhen Cui, Masashi Sugiyama, and Mohan Kankan-halli. Attacks which do not kill training make adversarial learning stronger. In *ICML*, 2020.

Jianing Zhu, Jiangchao Yao, Bo Han, Jingfeng Zhang, Tongliang Liu, Gang Niu, Jingren Zhou, Jianliang Xu, and Hongxia Yang. Reliable adversarial distillation with unreliable teachers. *arXiv preprint arXiv:2106.04928*, 2021.

Bojia Zi, Shihao Zhao, Xingjun Ma, and Yu-Gang Jiang. Revisiting adversarial robustness distilla-tion: Robust soft labels make student better. In *ICCV*, 2021.