DPP-TTS: Diversifying prosodic features of speech via determinantal point processes

Abstract

With the rapid advancement in deep generative models, recent neural text-to-speech models have succeeded in synthesizing human-like speech, even in an end-to-end manner. However, many synthesized samples often have a monotonous speaking style or simply follow the speaking style of their ground-truth samples. Although there have been many proposed methods to increase the diversity of prosody in speech, increasing prosody variance in speech often hurts the naturalness of speech. Recently, Determinantal point processes (DPPs) have shown remarkable results for modeling diversity in a wide range of machine learning tasks. However, their application in speech synthesis has not been explored. To enhance the expressiveness of speech, we propose DPP-TTS: a text-to-speech model based on a determinantal point process to diversify prosody in speech. The extent of prosody diversity can be easily controlled by adjusting parameters in our model. We demonstrate that DPP-TTS generates more expressive samples than baselines in the side-by-side comparison test while not harming the naturalness of the speech.

1 Introduction

In the past few years, text-to-speech models have made a lot of progress in synthesizing human-like speech (Shen et al., 2018; Ping et al., 2018; Li et al., 2019; Ren et al., 2019). Furthermore, in the latest studies, several text-to-speech models made high-quality speech samples even in the end-to-end setting without a two-stage synthesis process (Donahue et al., 2021; Kim et al., 2021). Based on these technical developments, text-to-speech models are now able to generate high-fidelity speech.

However, human speech contains many prosodic features like intonation, stress, and rhythm beyond textual features. Therefore, it is crucial to generate speech samples with rich prosody. There have been many attempts to synthesize speech with rich prosodic features. To incorporate rich prosodic features into speech, reference acoustic samples like mel-spectrograms are processed through reference encoder (Skerry-Ryan et al., 2018; Wang et al., 2018) or text-to-speech models are conditioned on prosodic features like duration, pitch and energy then these features are predicted or manually controlled at inference (Ren et al., 2021; La'ncucki, 2021). However, these methods have drawbacks that the bottleneck dimension should be carefully tuned for desirable results, or the prosody predictor just learns averaged prosodic features of training sets.

Meanwhile, generative models like VAEs and flow models (Hsu et al., 2019; Sun et al., 2020; Vall'es-P'erez et al., 2021; Lee et al., 2021; Valle et al., 2021) have been recently used for speech synthesis and their latent spaces are manipulated for generating more expressive speech. Controlling the amount of variation in the speech is achieved by generating samples in Gaussian prior with an adequate temperature, however, it has two major drawbacks. First, generating latent samples with high variance often make generated samples to be unstable in terms of the naturalness and intelligibility of speech. Second, sampling in the latent space might only cover major modes learned during the training stage and only monotonous prosodic patterns can occur in some segments of speech.

Determinantal point processes (DPPs) have shown great results for modeling diversity in various machine learning tasks and their applications. Its uses include text summarization (Cho et al., 2019), recommendation systems (Gartrell et al., 2021), multi-modal output generation (Elfeki et al., 2019), diverse trajectory forecasting (Yuan & Kitani, 2020), and machine translation (Meister et al., 2021). Determinantal point process (DPPs) offers us an efficient subset selection method by considering

both the quality and diversity of items within a set. Specifically, items within a set are sampled according to DPPs kernel which reflects the quality and diversity of items in the ground set. In some cases, we may need to incorporate the conditional information into the sampling process. To this end, conditional DPP (Kulesza & Taskar, 2012) has been widely used for sampling subset by setting the kernel conditioned on the specific information.

To use conditional DPP for sampling prosodic features of speech, two main issues should be considered. First, prosodic features are usually varying in length. Second, it is ambiguous what the ground set is in this problem. In this work, we resolve these issues by using a new similarity metric between prosodic features and adding a prosodic diversifying module (PDM) into the framework. Specifically, PDM generates candidates of prosodic features of speech by mapping latent codes from normal distribution to a new latent space and these candidates are used as the ground set in the sampling process. In addition, the similarity between two prosodic features is evaluated using soft dynamic time warping discrepancy (Soft-DTW) (Cuturi & Blondel, 2017) which enables to evaluate the similarity between features in different lengths.

The kernel matrix of conditional DPP is learned during the training by parameters of PDM getting updated. Specifically, parameters of the prosody diversifying module (PDM) are updated in the training stage with conditional maximum induced cardinality (MIC) objective which is adapted from MIC objective introduced in Gillenwater et al. (2018). We formally introduce the conditional MIC objective and its derivative for clarity in Section 4.

To implement the aforementioned DPP, a stochastic duration predictor and pitch predictor are introduced in this work. Both the duration and pitch predictor are built upon normalizing flows trained with the maximum likelihood (MLE) objective. At inference, the prosody predictor maps latent codes from a latent space to feature spaces with the inverse flow.

In experiments, we compare DPP-TTS with the state-of-the-art models including VITS (Kim et al., 2021) and Flowtron (Valle et al., 2021) in terms of prosody diversity and speech quality. The results demonstrate that our model generates speech with richer prosody than baselines while maintaining speech naturalness. We also demonstrate that our DPP-TTS can be used in real-time applications by evaluating the inference speed of our model.

In summary, our contributions follow:

- We propose a novel method for diversifying prosodic features of speech based on conditional DPPs by considering prosodic features of context words as conditions.
- To learn the kernel matrix of conditional DPPs, we propose to train prosody diversifying module (PDM) with the conditional maximum induced cardinality (MIC) objective.
- Experiments on the side-by-side comparison and the MOS test verify that our model outperforms the two baseline models in terms of prosodic diversity while maintaining the naturalness of speech.

2 BACKGROUND

2.1 DETERMINANTAL POINT PROCESSES

The core method in this work is that prosodic features of target words are sampled according to conditional DPPs kernel which reflects the similarity between the target and contexts. First, we will introduce DPPs before conditional DPPs. DPPs encourage diversity within a set by discouraging sampling similar items within the ground set. Formally, point process $\mathcal{P}$ is called a determinantal point process when $\boldsymbol{Y}$ is a random subset drawn according to $\mathcal{P}$, we have, for every $A \subseteq \mathcal{Y}$,

$$\mathcal{P}(A \subseteq \boldsymbol{Y}) \propto \det(\boldsymbol{K}_A), \tag{1}$$

where $\boldsymbol{K}$ is a positive definite matrix whose eigenvalues are all between 0 and 1 and $\boldsymbol{K}_A$ is a positive a definite matrix indexed by elements in A. The marginal probability of including two elements e_i and e_j is $K_{ii}K_{jj} - K_{ij}^2 = p(e_i \in \boldsymbol{Y})p(e_j \in \boldsymbol{Y}) - K_{ij}^2$. Therefore, the value of K_{ij}^2 models the extent of negative correlation between item i and j. More frequently, DPPs are defined by L-ensemble through real and symmetric matrix $\boldsymbol{L}$ instead of the marginal kernel $\boldsymbol{K}$:

$$\mathcal{P}_L(\boldsymbol{Y} = Y) = \frac{\det(\boldsymbol{L}_Y)}{\det(\boldsymbol{L} + \boldsymbol{I})}, \tag{2}$$

where $\det(\boldsymbol{L} + \boldsymbol{I})$ in the denominator acts as a normalization constant. The marginal kernel $\boldsymbol{K}$ and kernel $\boldsymbol{L}$ has the following relation:

$$\boldsymbol{K} = \boldsymbol{L}(\boldsymbol{L} + \boldsymbol{I})^{-1} = \boldsymbol{I} - (\boldsymbol{L} + \boldsymbol{I})^{-1} \tag{3}$$

To model diversity between items, the DPP kernel $\boldsymbol{L}$ is usually constructed as a symmetric similarity matrix, where S_{ij} represents the similarity between two items x_i and x_j. In Kulesza & Taskar (2010), authors proposed decomposing the kernel L as a a Gram matrix incorporating a quality vector to weigh each item according to its quality :

$$\mathcal{P}(J \subseteq Y) \propto \det(\phi(J)^{\mathrm{T}}\phi(J)) \prod_{e_i \in J} q^2(e_i) = \mathrm{Diag}(\boldsymbol{q}) \cdot \boldsymbol{S} \cdot \mathrm{Diag}(\boldsymbol{q}), \tag{4}$$

where $\phi_i \in \mathbb{R}^D$; $D \leq N$ and $||\phi_i||_2 = 1$. In this manner, the similarity matrix $\boldsymbol{S}$ is guaranteed to be real positive semidefinite matrix.

2.2 CONDITIONAL DETERMINANTAL POINT PROCESSES

By setting conditions of $\mathcal{P}$, DPPs can be extended to conditional DPPs, For $B \subseteq Y$ not intersecting with A we have

$$\mathcal{P}(\boldsymbol{Y} = A \cup B | A \subseteq \boldsymbol{Y}) = \frac{\mathcal{P}(\boldsymbol{Y} = A \cup B)}{\mathcal{P}(A \subseteq \boldsymbol{Y})} = \frac{\det(L_{A \cup B})}{\det(L + I_{\bar{A}})}, \tag{5}$$

where $I_{\bar{A}}$ is the matrix with ones in the diagonal entries indexed by elements of $\mathcal{Y} - A$ and zeros elsewhere. In Borodin & Rains (2004), authors showed that this conditional distribution is again a DPP, with a kernel given by

$$\boldsymbol{L}^A = ([(\boldsymbol{L} + \boldsymbol{I}_{\bar{A}})^{-1}]_{\bar{A}})^{-1} - \boldsymbol{I}. \tag{6}$$

In conditional DPPs, items in the ground set $\mathcal{Y}$ are sampled according to kernel given contexts. In this work, contexts of target words are used as conditions for conditional DPPs.

2.3 SOFT DYNAMIC TIME WARPING

To build the kernel of conditional DPPs, we need a measure of similarity between two temporal signals. Simple Euclidean distance is not applicable because two time signals often vary in their lengths. In this work, to calculate the similarity between two temporal features, soft dynamic time warping (Soft DTW) discrepancy is adapted. DTW computes the best possible alignment between two temporal signals. First, for the length of n and m signals, DTW computes n by m pairwise distance matrix between these points with a specific metric (e.g., Euclidean distance, L1 distance). After that, this matrix is used to solve the dynamic program using Bellman's recursion with a quadratic $\mathcal{O}(mn)$ cost.

Unfortunately, vanilla DTW cost is not easy to optimize because it only considers a single alignment between two temporal signals. Cuturi & Blondel (2017) proposed differentiable Soft-DTW which considers all possible alignments between two temporal series. Soft-DTW is differentiable in all of its arguments with quadratic cost. Formally, Soft-DTW is defined as follows:

$$\mathbf{dtw}_\gamma(\boldsymbol{x}, \boldsymbol{y}) := \min{}^\gamma\{\langle A, \delta(\boldsymbol{x}, \boldsymbol{y})\rangle, A \in \mathcal{A}_{n,m}\}, \tag{7}$$

where $\mathcal{A}_{n,m}$ denotes all possible alignments between $\boldsymbol{x}$ and $\boldsymbol{y}$ and $\min{}^\gamma$ is defined as

$$\min{}^\gamma\{a_1, ..., a_n\} := \begin{cases} \min_{i \leq n} a_i, & \text{if} \quad \gamma = 0 \\ -\gamma \log \sum_{i=1}^n e^{\frac{-a_i}{\gamma}}, & \text{otherwise} \end{cases} \tag{8}$$

A small magnitude of γ reflects the true discrepancy of two temporal signals, however, optimization becomes unstable.

3 TEXT-TO-SPEECH MODEL

In this section, we first describe the architecture of the text-to-speech model before adding prosody diversifying module (PDM). Our text-to-speech model is adapted from FastSpeech2 (Ren et al., 2021) and comprised the main seq2seq module and stochastic prosody predictor modules. The overall architecture is depicted in Figure 1a.

(a) Basic text-to-speech model (b) DPP-TTS inference

Figure 1: Diagrams describing (a): the basic text-to-speech model and (b) the inference of DPP-TTS.

3.1 SEQ2SEQ MODULE

Seq2seq model for generating mel-spectrograms from phoneme sequences is adapted from Fast-Speech2 with some modifications. The model consists of four main parts: a phoneme prenet, a phoneme encoder, a variance adaptor, and a mel-spectrogram decoder. In the phoneme encoder, phoneme sequences are processed through a stack of feed-forward transformer blocks with a relative positional representation (Shaw et al., 2018). Pitch embeddings and energy embeddings are added to encoded hidden representations and then hidden representations are expanded according to ground-truth duration labels which were obtained via monotonic alignment search (Kim et al., 2020) between phonemes and mel-spectrograms. Finally, expanded representations are processed through a stack of feed-forward transformer blocks and mel-spectrograms with 80 channels are generated after the linear projection. The seq2seq module is trained with L_1 distance between the predicted and target mel-spectrogram.

3.2 PROSODY PREDICTOR

In FastSpeech2, the variance adaptor consists of deterministic predictors for predicting prosodic features. However, a deterministic prosodic predictor is not expressive enough to learn the speaking style of a person. For diverse rhythm and pitch, a stochastic duration predictor and pitch predictor are built upon normalizing flows. Specifically, the stochastic duration predictor estimates the distribution of phoneme duration and the stochastic pitch predictor estimates the distribution of phoneme pitch from the hidden sequence. At the training stage, the prosody predictor learns the mapping from the distribution of prosodic features to normal distribution. At inference, it predicts the phoneme duration or pitch by reversing the learned flows.

As the prosody pattern of human speech is correlated with the local context and global context of the text, we design the architecture of the model to encode both the local and global features. Specifically, dilated convolution blocks are stacked to encode local features and a transformer block is used to encode global features in the coupling layers of normalizing flows. However, using the vanilla transformer to encode the global features in the coupling layer requires too large computational complexity. Therefore, Nyströmformer (Xiong et al., 2021) which is a Nyström-Based algorithm for approximating self-attention is used to encode global context for more efficient memory usage in the coupling layer of normalizing flow. Encoded local features and global features are concatenated and processed through LayerNorm (Ba et al., 2016), Mish activation (Misra, 2019) and a 1x1 convolution module.

Following the duration predictor model in Kim et al. (2021), variational dequantization (Ho et al., 2019) is used for the duration predictor since the phoneme duration is a discrete integer. In addition, variational augmentation (Chen et al., 2020) is used to expand channel dimensions for expressive

flows in both the duration and pitch predictor. The stochastic and pitch predictor are trained by maximizing their variational lower bounds (ELBO). Details of the duration and pitch predictor are described in Appendix A.

4 PROSODY DIVERSIFYING MODULE FOR DIVERSE PROSODIC FEATURES

In this section, we explain the prosody diversifying module (PDM) which is trained with the loss based on maximum induced cardinality (MIC), the process of building DPP kernel, and finally the conditional (MIC) objective for learning the kernel.

4.1 PROSODY DIVERSIFYING MODULE (PDM)

Although the stochastic duration and pitch predictor are trained for generating a speech with diverse rhythm and pitch, it is still not guaranteed that the synthesized sample with features from learned duration and pitch distribution gives us human-level expressivity. To address this issue, conditional DPPs are introduced with the aim to learn the kernel producing diverse prosodic features. A prosody diversifying module (PDM) is inserted in front of the prosody predictor to parameterize the kernel of conditional DPPs.

What parts of texts should be processed by PDM? Although there exists theoretical phonological hierarchy (Buuren, 1978) which starts from an utterance in the top level to syllables and phonemes in the low level, it is still challenging to generalize the basic segment of prosody events across people. In this work, as an alternative, noun phrases extracted from the sentence using Spacy[1] library are processed by PDM with an expectation to get the prosodic diversity in the phrase level.

Overview of PDM process First, context hidden sequences are processed by the trained prosody predictor and context prosodic features like duration and pitch are predicted. In Figure 2, these predicted features are denoted as d_L and d_R, each represents the left context and right context. Simultaneously, PDM takes hidden target and context sequences from the output of text encoder as inputs and outputs latent code $z \in \mathbb{R}^{N \times T}$, where N denotes the number of candidates, and T denotes the length of the target sequence. The latent codes z are processed through the prosody predictor and N prosodic features are predicted. The overall process is shown in Figure 2.

Figure 2: PDM training overview.

4.2 DPP KERNEL BUILD

Based on predicted prosodic features of the context d_L, d_R and target sequences $d_1, ..., d_N$, the kernel of conditional DPP is built incorporating both diversity and quality of the set. As mentioned, the kernel of DPP can be decomposed as $L = \text{Diag}(\boldsymbol{q}) \cdot S \cdot \text{Diag}(\boldsymbol{q})$, where q denotes the quality vectors of predicted features and S denotes the similarity matrix.

Similarity metric Target sequences and context sequences often vary in lengths, therefore the Euclidean distance is not applicable to calculate the similarity between two sequences. The similarity metric is calculated as follows based on Soft DTW:

$$\boldsymbol{S}_{i,j} = \exp(-k \cdot \mathbf{dtw}_\gamma^D(\boldsymbol{d}_i, \boldsymbol{d}_j)) \tag{9}$$

$\mathbf{dtw}_\gamma^D$ denotes soft-DTW discrepancy with a metric D and smoothing parameter γ. When the metric D is chosen as the L_1 distance $D(\boldsymbol{x}, \boldsymbol{y}) = \sum_i |\boldsymbol{x}_i - \boldsymbol{y}_i|$ or half gaussian $D(\boldsymbol{x}, \boldsymbol{y}) = ||\boldsymbol{x} - \boldsymbol{y}||_2^2 + \log(2 - \exp(-||\boldsymbol{x} - \boldsymbol{y}||_2^2))$, the similarity matrix is positive semi-definite (Cuturi et al., 2007; Blondel et al., 2021). In this work, L_1 distance is used as the metric of Soft-DTW so that $\boldsymbol{S}$ to be positive semi-definite.

---

[1]https://github.com/explosion/spaCy

Quality metric Based on estimated density of predicted features, quality scores are calculated. The density values of predicted features are calculated with importance sampling: $p(\boldsymbol{x}; \theta) \approx \sum_{i=1}^{N} \frac{p(\boldsymbol{x}, \boldsymbol{z}; \theta)}{q(\boldsymbol{z}|\boldsymbol{x}; \phi)}$. In the experiment, using raw density value resulted in not enough diverse sample, therefore quality values are not penalized if the density value is greater than a specific threshold. With log likelihood $p(x)$, the quality score is defined as

$$\boldsymbol{q}(x) = \begin{cases} w & \text{if } p(x) >= k \\ w \cdot \exp(-||p(x)||_2^2 + k^2) & \text{otherwise} \end{cases} \tag{10}$$

The threshold value k was set based on the average density of the dataset. Larger w value gives more weight on the quality term. In other words, samples with high density are more likely to be generated than diverse samples. Finally, the kernel of conditional DPPs is defines as $\boldsymbol{L} = \text{diag}(q) \cdot \boldsymbol{S} \cdot \text{diag}(q)$. A schematic diagram of building the conditional DPPs kernel is in Figure 3.

Figure 3: DPP kernel build overview.

4.3 OBJECTIVE FUNCTION

We need a measure of diversity with respect to kernel $\boldsymbol{L}$ to train the PDM. One straightforward choice is maximum likelihood (MLE) objective, $\log \mathcal{P}_{\boldsymbol{L}}(\boldsymbol{Y}) = \det(\boldsymbol{L})/\det(\boldsymbol{L} + I)$. However, there are some cases where two identical prosodic features (especially duration sequences) are sampled. This leads the objective value to be close to zero which makes the training process unstable. Instead, maximum induced cardinality (MIC) (Gillenwater et al., 2018) objective which is defined as $\mathbb{E}_{\boldsymbol{Y} \sim \mathcal{P}_{\boldsymbol{L}}}[|\boldsymbol{Y}|]$ can be an alternative. It does not suffer from training instability since identical items in the ground set $\mathcal{Y}$ are allowed. In this work, conditional MIC objective is used since the expected cardinality of the set without considering context is meaningless. The objective function with respect to the ground set $[d_L, d_R, d_1, d_2, ..., d_N]$ and its derivative are follows:

Proposition 1 (MIC objective of conditional DPPs). *With respect to the ground set* $[d_L, d_R, d_1, d_2, ..., d_N]$*, the MIC objective of conditional DPPs and its derivative are follows:*

$$\boldsymbol{L}_{MIC} = \text{tr}(\boldsymbol{I} - [(\boldsymbol{L}_\theta + \boldsymbol{I}_{\bar{A}})^{-1}]_{\bar{A}}), \quad \frac{\partial \boldsymbol{L}_{MIC}}{\partial \theta} = ((\boldsymbol{L} + \boldsymbol{I}_{\bar{A}})^{-1} \boldsymbol{I}_{\bar{A}} (\boldsymbol{L} + \boldsymbol{I}_{\bar{A}})^{-1})^{\text{T}} \boldsymbol{L}^{'}(\theta), \tag{11}$$

where A denotes the set of contexts (d_L, d_R), $\bar{A}$ denotes the complement of the set A and θ is the parameter of PDM.

Detailed proof is presented in Appendix B.

At inference, MAP inference is performed across sets with just a single item:

$$\boldsymbol{x}^* = \underset{\boldsymbol{x} \in \bar{A}}{\arg \max} \ \log \det(\boldsymbol{L}_{\{\boldsymbol{x}\} \cup A}) \tag{12}$$

The inference of DPP-TTS is described in Figure 1b. The detailed procedure of training PDM and the inference of DPP-TTS are in Appendix C. The loss function for training the PDM is the opposite of the conditional MIC objective.

(a) Side-by-Side evaluation results of a sentence.

(b) Side-by-Side evaluation results of a paragraph.

Figure 4: Side-by-Side evaluation results

5 EXPERIMENTS

In this section, we first explain the experimental setup and then human evaluation results and further evaluation results that are conducted to evaluate the proposed DPP-TTS. Audio samples used for the evaluation are in the supplementary material.

5.1 EXPERIMENTAL SETUP

Dataset and preprocessing We conducted experiments on the LJ Speech dataset which consists of audio clips with approximately 24 hours lengths. We split audio samples into 12500/100/500 samples for the training, validation, and test set. Audio samples with 22kHz sampling rate are transformed into 80 bands mel-spectrograms through the Short-time Fourier transform (STFT) with 1024 window size and 256 hop length. International Phonetic Alphabet (IPA) sequences are used as input for phoneme encoder. Text sequences are converted to IPA phoneme sequences using `Phonemizer`[2] software. Following Kim et al. (2020), the converted sequences are interspersed with blank tokens, which represent the transition from one phoneme to another phoneme.

Training Both the basic TTS and PDM are trained using the AdamW optimizer (Loshchilov & Hutter, 2019) with $\beta_1 = 0.8, \beta_2 = 0.99$ and $\lambda = 0.01$. The initial learning rate is 2×10^{-4} for the basic TTS and 1×10^{-5} for the PDM and the exponential learning decay is used for both of them. Basic TTS is trained with 16 batch size for 200k steps on 2 NVIDIA RTX 3080 GPUs. PDM is trained with 8 batch size for 5k steps on same devices.

Baseline We compare our model with two state-of-the-art models in terms of naturalness and prosody diversity. The first one is VITS (Kim et al., 2021) which is an end-to-end TTS model based on conditional VAE and normalizing flows. In all experiments, the temperature σ of the duration predictor in VITS was set 0.8. The second one is Flowtron (Valle et al., 2021) which is an autoregressive flow-based TTS model. In experiments, the temperature σ of Flowtron was set to 0.6. For our DPP-TTS and Flowtron, HiFi-GAN (Kong et al., 2020) is used as the vocoder for synthesizing waveforms from the mel-spectrograms.

5.2 HUMAN EVALUATION RESULTS

Side by side evaluation First, we conduct a side-by-side evaluation of the prosody of a sentence. In this experiment, texts from test samples from LJSpeech are synthesized. Target phrases extracted from the sentence are processed by PDM and pitch diversity modeling is used in DPP-TTS. Via Amazon Mechanical Turk (AMT), we assign five testers living in the United States to a pair of audio samples (i.e., DPP-TTS and a baseline), and ask them to listen to audio samples and choose among three options: (1): sample A has more varied prosody than sample B, (2): sample A and B are equally varied in prosody, (3): the opposite of option (1).

---

[2]https://github.com/bootphon/phonemizer

Model	Pitch σ_{frame}	Pitch $\sigma_{phoneme}$	Pitch Determinant	Duration $\sigma_{phoneme}$	Duration Determinant	Inference Time(s)
DPP-TTS	**0.012**	**0.014**	**2.92×10^{-14}**	**1.35**	**1.56×10^{-7}**	4.4×10^{-2}
VITS	0.010	0.011	5.58×10^{-17}	0.22	9.23×10^{-7}	**1.3×10^{-2}**

Table 2: Additional evaluation results. Numbers in bold denote the better result.

In addition, we also conduct a side-by-side evaluation of prosody in a paragraph since a monotonous pattern is prominent in long texts rather than a single sentence. We prepared two DPP-TTS versions: (1): DPP-TTS1: a model that has only duration diversifying module and DPP-TTS2: a model that has both duration and pitch diversifying module. In this experiment, only VITS is compared as the baseline. Likewise the evaluation of a sentence, listeners are asked to choose among three options.

Results are shown in Figure 4. In the side-by-side evaluation of prosody in a sentence, DPP-TTS outperforms VITS by a margin of 10 percent and Flowtron by a margin of 20 percent. In the side-by-side evaluation of prosody in a paragraph, DPP-TTS1 outperforms the baseline but DPP-TTS2 does not. We speculate that diversifying the duration and pitch simultaneously rather hurts the naturalness of speech.

Naturalness test In this experiment, we measure the Mean-Opinion-Score (MOS) for audio samples generated by TTS models. Likewise in the previous test, five testers are assigned to each audio sample. Testers are asked to give a score between 1 to 5 on a 9-scale based on the sample's naturalness. We used the same quality weight value $w = 10$ for DPP-TTS as in the side-by-side comparison test.

The MOS result is described in Table 1. Although DPP-TTS gets lower MOS than baselines, it yet still maintain a reasonable MOS of 3.6. It is noticeable there exists a large variance of MOS results in DPP-TTS compared to other TTS models. we speculate that subtle differences resulted from the control of prosodic features might sound unnatural for some people. Achieving more stable samples in terms of naturalness will be our future work.

Model	MOS
VITS	4.44 ± 0.165
Flowtron	3.78 ± 0.229
DPP-TTS	3.6 ± 0.356
Ground-truth	4.61 ± 0.118

Table 1: Mos evaluation results

5.3 ADDITIONAL EVALUATION

In this section, we use the following metrics for the evaluation of our DPP-TTS and VITS: (1) σ_{frame}: frame-level standard deviation of the pitch in a speech. All pitch values are normalized since speech samples have different absolute pitch values. Standard deviations are calculated over 50 generated samples. DIO algorithm (Morise et al., 2009) is used for pitch extraction. (2): $\sigma_{phoneme}$: phoneme-level standard deviation of duration or pitch in a speech. Likewise, the standard deviation values are calculated over 50 generated samples. (3): **Determinant**: determinant of the matrix with respect to a feature set J generated by multiple samples is used to evaluate the diversity of phoneme-level prosodic features of multiple generated samples. Cosine similarity is used as a metric between two sequences. Each set is constructed from 10 generated samples. (4): **Inference time**: the inference time for synthesizing one-second length waveform is calculated in the text-to-speech model. The inference speed is evaluated on Intel(R) Core(TM) i7-7800X CPU and a single NVIDIA RTX 3080 GPU. Computation time is averaged over 100 forward passes.

Table 2 shows the result of σ_{frame}, $\sigma_{phoneme}$, determinant and inference time. At both frame and phoneme levels, the standard deviation of the pitch in DPP-TTS results in higher values than the baseline. In addition, the standard deviation of duration at phoneme-level in DPP-TTS also results in a higher value than the baseline. It demonstrates that DPP-TTS generates a speech with more dynamic pitch and rhythm than the baseline. The determinants of duration and pitch sets of DPP-TTS outperform the baseline. It shows that DPP-TTS generates more diverse samples in terms of prosody than baseline. Finally, DPP-TTS results in 0.044 seconds of inference speed. Although its inference speed is slower than the baseline, our model is applicable in practice since the inference speed of our model is 22.7x faster than real-time.

(a) Pitch plot
with $w = 10$

(b) Pitch plot
with $w= 2$

(c) Log duration plot
with $w=10$

(d) Log duration plot
with $w=2$

Figure 5: Pitch and log duration plots with different values of quality weight. Green plots indicate the prosody prediction before MAP inference of DPP and red plots indicate the prosody prediction after MAP inference of DPP.

5.4 MODEL ANALYSIS

Adjusting the extent of variation To study the impact of quality weight w, we plot (normalized) pitch and log duration values at phoneme-level with different values of quality weight . Plots are shown in Figure 5. As expected, for a large magnitude of quality weight , the model learns diversifying prosodic features with small deviations from contexts. In contrast, for a small magnitude of quality weight , the model diversifies prosodic features with large deviations from contexts. We also found that a small magnitude of quality weight leads to faster convergence of the model but it easily hurts the naturalness of generated samples.

Unconditional MIC objective Instead of the conditional MIC objective, we also train our model with the vanilla MIC objective while the inference method is unchanged. We observe that generated samples lack rich prosody or result in unnatural prosody. It shows that it is important to sample prosodic features of target words according to processes conditioned on contexts.

Effect of number of candidates on diversity In this experiment, we study the effect of the number of candidates on the prosody diversity in generated samples. For a different number of candidates $n_c = 4, 8, 12$, DPP-TTS is trained up to 4k steps and all other hyperparameters remain unchanged. After training, we calculate pitch determinants over generated samples for

Number of candidates	Pitch determinant
$n_c = 4$	1.69×10^{-15}
$n_c = 8$	4.56×10^{-15}
$n_c = 12$	$\mathbf{7.8 \times 10^{-15}}$

Table 3: Pitch determinant values with different number of candidates

each setup. The result is reported in Table 3. We observe that using a large number of candidates results in more diverse samples although only a single prosody item is selected at MAP inference. We also find that using a large number of candidates has a regularization effect for training. Using a small number of candidates generates unstable speech samples in terms of naturalness, in contrast, using a large number of candidates results in more stable speech samples.

6 CONCLUSION

In this paper, we have proposed a novel prosody diversifying method based on conditional determinantal point processes (DPPs). To learn the kernel matrix of conditional DPPs, conditional determinantal point process (DPPs) is parameterized additional prosody diversifying module (PDM). To build the kernel, Soft dynamic time warping is adopted to measure the extent of similarity between two prosodic features, and the kernel of conditional DPPs is learned with conditional maximum induced cardinality (MIC) objective. In the experiment, we demonstrated that our new prosody diversifying method generates more dynamic samples than the baseline while maintaining the naturalness. In addition, we demonstrate that our model can be used in real-time applications by showing the inference speed of our model.

REFERENCES

Jimmy Ba, Jamie Ryan Kiros, and Geoffrey E. Hinton. Layer normalization. *ArXiv*, abs/1607.06450, 2016.

Mathieu Blondel, A. Mensch, and Jean-Philippe Vert. Differentiable divergences between time series. In *AISTATS*, 2021.

Alexei Borodin and Eric M. Rains. Eynard–mehta theorem, schur process, and their pfaffian analogs. *Journal of Statistical Physics*, 121:291–317, 2004.

L. V. Buuren. Phonological hierarchy in english. 1978.

Jianfei Chen, Cheng Lu, Biqi Chenli, J. Zhu, and Tian Tian. Vflow: More expressive generative flows with variational data augmentation. *ArXiv*, abs/2002.09741, 2020.

Sangwoo Cho, Chen Li, Dong Yu, H. Foroosh, and Fei Liu. Multi-document summarization with determinantal point processes and contextualized representations. *ArXiv*, abs/1910.11411, 2019.

Marco Cuturi and Mathieu Blondel. Soft-dtw: a differentiable loss function for time-series. In *ICML*, 2017.

Marco Cuturi, Jean-Philippe Vert, Øystein Birkenes, and T. Matsui. A kernel for time series based on global alignments. *2007 IEEE International Conference on Acoustics, Speech and Signal Processing - ICASSP '07*, 2:II–413–II–416, 2007.

Jeff Donahue, S. Dieleman, Mikolaj Binkowski, Erich Elsen, and K. Simonyan. End-to-end adversarial text-to-speech. *ArXiv*, abs/2006.03575, 2021.

Conor Durkan, Artur Bekasov, Iain Murray, and George Papamakarios. Neural spline flows. In *NeurIPS*, 2019.

M. Elfeki, C. Couprie, M. Rivière, and Mohamed Elhoseiny. Gdpp: Learning diverse generations using determinantal point process. In *ICML*, 2019.

Mike Gartrell, Insu Han, Elvis Dohmatob, Jennifer Gillenwater, and Victor-Emmanuel Brunel. Scalable learning and map inference for nonsymmetric determinantal point processes. *ArXiv*, abs/2006.09862, 2021.

Jennifer Gillenwater, A. Kulesza, Sergei Vassilvitskii, and Zelda E. Mariet. Maximizing induced cardinality under a determinantal point process. In *NeurIPS*, 2018.

Jonathan Ho, Xi Chen, A. Srinivas, Yan Duan, and P. Abbeel. Flow++: Improving flow-based generative models with variational dequantization and architecture design. *ArXiv*, abs/1902.00275, 2019.

Wei-Ning Hsu, Y. Zhang, Ron J. Weiss, H. Zen, Yonghui Wu, Yuxuan Wang, Yuan Cao, Ye Jia, Z. Chen, Jonathan Shen, P. Nguyen, and Ruoming Pang. Hierarchical generative modeling for controllable speech synthesis. *ArXiv*, abs/1810.07217, 2019.

Jaehyeon Kim, Sungwon Kim, Jungil Kong, and Sungroh Yoon. Glow-tts: A generative flow for text-to-speech via monotonic alignment search. *ArXiv*, abs/2005.11129, 2020.

Jaehyeon Kim, Jungil Kong, and Juhee Son. Conditional variational autoencoder with adversarial learning for end-to-end text-to-speech. *ArXiv*, abs/2106.06103, 2021.

Jungil Kong, Jaehyeon Kim, and Jaekyoung Bae. Hifi-gan: Generative adversarial networks for efficient and high fidelity speech synthesis. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 17022–17033. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/c5d736809766d46260d816d8dbc9eb44-Paper.pdf.

A. Kulesza and B. Taskar. Determinantal point processes for machine learning. *Found. Trends Mach. Learn.*, 5:123–286, 2012.

Alex Kulesza and Ben Taskar. Structured determinantal point processes. In *NIPS*, 2010.

Adrian La'ncucki. Fastpitch: Parallel text-to-speech with pitch prediction. In *ICASSP*, 2021.

Yoonhyung Lee, Joongbo Shin, and Kyomin Jung. Bidirectional variational inference for non-autoregressive text-to-speech. In *ICLR*, 2021.

N. Li, Shujie Liu, Yanqing Liu, Sheng Zhao, and Ming Liu. Neural speech synthesis with transformer network. In *AAAI*, 2019.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=Bkg6RiCqY7.

Clara Meister, Martina Forster, and Ryan Cotterell. Determinantal beam search. In *ACL/IJCNLP*, 2021.

Diganta Misra. Mish: A self regularized non-monotonic neural activation function. *ArXiv*, abs/1908.08681, 2019.

Masanori Morise, Hideki Kawahara, and Haruhiro Katayose. Fast and reliable f0 estimation method based on the period extraction of vocal fold vibration of singing voice and speech. 2009.

Wei Ping, Kainan Peng, Andrew Gibiansky, Sercan Ö. Arik, Ajay Kannan, Sharan Narang, Jonathan Raiman, and John Miller. Deep voice 3: Scaling text-to-speech with convolutional sequence learning. *arXiv: Sound*, 2018.

Yi Ren, Yangjun Ruan, Xu Tan, Tao Qin, Sheng Zhao, Zhou Zhao, and Tie-Yan Liu. Fastspeech: Fast, robust and controllable text to speech. In *NeurIPS*, 2019.

Yi Ren, Chenxu Hu, Xu Tan, Tao Qin, Sheng Zhao, Zhou Zhao, and Tie-Yan Liu. Fastspeech 2: Fast and high-quality end-to-end text to speech. *ArXiv*, abs/2006.04558, 2021.

Peter Shaw, Jakob Uszkoreit, and Ashish Vaswani. Self-attention with relative position representations. In *NAACL*, 2018.

Jonathan Shen, Ruoming Pang, Ron J. Weiss, M. Schuster, Navdeep Jaitly, Zongheng Yang, Z. Chen, Yu Zhang, Yuxuan Wang, R. Skerry-Ryan, R. Saurous, Yannis Agiomyrgiannakis, and Yonghui Wu. Natural tts synthesis by conditioning wavenet on mel spectrogram predictions. *2018 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 4779–4783, 2018.

R. Skerry-Ryan, Eric Battenberg, Y. Xiao, Yuxuan Wang, Daisy Stanton, Joel Shor, Ron J. Weiss, R. Clark, and R. Saurous. Towards end-to-end prosody transfer for expressive speech synthesis with tacotron. *ArXiv*, abs/1803.09047, 2018.

G. Sun, Y. Zhang, Ron J. Weiss, Yuanbin Cao, H. Zen, and Yonghui Wu. Fully-hierarchical fine-grained prosody modeling for interpretable speech synthesis. *ICASSP 2020 - 2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 6264–6268, 2020.

Rafael Valle, Kevin J. Shih, R. Prenger, and Bryan Catanzaro. Flowtron: an autoregressive flow-based generative network for text-to-speech synthesis. *ArXiv*, abs/2005.05957, 2021.

Iv'an Vall'es-P'erez, Julian Roth, Grzegorz Beringer, R. Barra-Chicote, and J. Droppo. Improving multi-speaker tts prosody variance with a residual encoder and normalizing flows. *ArXiv*, abs/2106.05762, 2021.

Yuxuan Wang, Daisy Stanton, Yu Zhang, R. Skerry-Ryan, Eric Battenberg, Joel Shor, Y. Xiao, Fei Ren, Ye Jia, and R. Saurous. Style tokens: Unsupervised style modeling, control and transfer in end-to-end speech synthesis. In *ICML*, 2018.

Yunyang Xiong, Zhanpeng Zeng, Rudrasis Chakraborty, Mingxing Tan, Glenn M. Fung, Yin Li, and Vikas Singh. Nyströmformer: A nyström-based algorithm for approximating self-attention. In *AAAI*, 2021.

Ye Yuan and Kris Kitani. Diverse trajectory forecasting with determinantal point processes. *ArXiv*, abs/1907.04967, 2020.

A DETAILS OF PROSODY PREDICTOR AND PDM

(a) Duration predictor   (b) Coupling block   (c) PDM block

Figure 6: Diagrams describing (a): the duration predictor, (b): Coupling block in normalizng flows and (c): Prosody diversifying module

A.1 PROSODY PREDICTOR

Training It is hard to use the maximum likelihood objective directly to train duration predictor because the duration of each phoneme is 1) a discrete integer and a scalar, which hinders expressive transformation because invertibility should remain in normalizing flow. To train duration predictor, duration values are extended to continuous values using variational dequantization (Ho et al., 2019) and are augmented with extra dimensions using variational data augmentation (Chen et al., 2020). Specifically, duration sequence d becomes continuous as $d - u$ where u's value is restricted to $[0, 1)$ and augmented as $[d - u, v]$ with a extra random variable v. Two random variables u and v are sampled through approximate posterior $q_\phi(u, v | d, h_{text})$. The ELBO can be calculated as follows:

$$\log p_\theta(d|h_{text}) \geq \mathbb{E}_{q_\phi(u,v|d,h_{text})}[\log \frac{p_\theta(d - u, v|h_{text})}{q_\phi(u, v|d, h_{text})}] \qquad (13)$$

Like the duration predictor, the ELBO for pitch predictor can be calculated as follows:

$$\log p_\theta(p|h_{text}) \geq \mathbb{E}_{q_\phi(v|p,h_{text})}[\log \frac{p_\theta(p, v|h_{text})}{q_\phi(v|p, h_{text})}], \qquad (14)$$

where p denotes the pitch sequences. Both the duration and pitch predictor are trained on negative lower bound of likelihood.

Architecture The pitch predictor and duration predictor share identical architecture except for the additional random variable u. We will introduce the architecture of the duration predictor whose diagram is shown in Figure 6a. Duration predictor consists of condition encoder for hidden sequence, posterior encoder for the duration sequence, and the main flow blocks $g(\cdot)$. Specifically, posterior encoder maps latent codes from normal distribution to random variable $[u, v]$ and flow $g(\cdot)$ maps $[d - u, v]$ to normal distribution. Figure 6b shows the coupling of normalizing flows. First, input x is split into $[x_0, x_1]$ and then x_0 is processed by a 1x1 convolution block. The output of the convolution block is processed by dilated convolution and Nystromer block and their outputs are concatenated. The concatenated output is processed by LayerNorm, Mish activation, and Convolution block. Finally, spline flows (Durkan et al., 2019) are parameterized by the output and then the output of spline flows y and x_0 are concatenated.

A.2 PDM

The architecture of PDM is shown in Figure 6c. First, the hidden sequence is processed by convolution block followed by the dilated convolution block conditioned on hidden sequences, Layernorm,

and 1x1 convolution block. After that, noise from a normal distribution is processed by 1x1 convolution followed by dilated convolution block, LayerNorm, and Mish activation.

B PROOF OF **Proposition 1**

Objective From equation [45] in (Kulesza & Taskar, 2012), the marginal kernel of conditional DPPs given the appearance of set A has a following form:

$$\boldsymbol{K}^A = \boldsymbol{I} - [(\boldsymbol{L} + \boldsymbol{I}_{\bar{A}})^{-1}]_{\bar{A}} \tag{15}$$

In addition, from equation [34] in Kulesza & Taskar (2012) the expected cardinality of $\boldsymbol{Y}$ given the marginal kernel $\boldsymbol{K}$ is:

$$\mathbb{E}[|\boldsymbol{Y}|] = \sum_{n=1}^{N} \frac{\lambda_n}{\lambda_n + 1} = \text{tr}(\boldsymbol{K}) \tag{16}$$

From equation 15, 16, the expected cardinality of conditional DPPs given the appearance of set A is:

$$\mathbb{E}[|\boldsymbol{Y}|] = \text{tr}(\boldsymbol{K}^A) = \text{tr}(\boldsymbol{I} - [(\boldsymbol{L} + \boldsymbol{I}_{\bar{A}})^{-1}]_{\bar{A}}) \tag{17}$$

Derivative For the proof, we will start with a following lemma:

Lemma 1. *Given a matrix E and non-singular matrix A, following equation holds:*

$$\frac{\partial}{\partial A} \text{tr}(E^{\text{T}} A^{-1} E) = -(A^{-1} E E^{\text{T}} A^{-1})^{\text{T}} \tag{18}$$

Proof. First, consider $\frac{\partial}{\partial A_{ij}} \text{tr}(E^{\text{T}} A^{-1} E)$. Since *trace* and derivative operator are interchangeable,

$$
\begin{aligned}
\frac{\partial}{\partial A_{ij}} \text{tr}(E^{\text{T}} A^{-1} E) &= \text{tr}(\frac{\partial}{\partial A_{ij}} (E^{\text{T}} A^{-1} E)) \\
&= -\text{tr}(E^{\text{T}} A^{-1} \frac{\partial A}{\partial A_{ij}} A^{-1} E)
\end{aligned}
\tag{19}
$$

By setting $\frac{\partial A}{\partial A_{ij}} = E^{ij}$ where E^{ij} denotes the matrix whose (i, j) component is 1 and 0 elsewhere and $\boldsymbol{C} = -E^{\text{T}} A^{-1} E^{ij} A^{-1} E$,

$$
\begin{aligned}
-\text{tr}(E^{\text{T}} A^{-1} E^{ij} A^{-1} E) &= \sum_{i'} C_{i'i'} \\
&= -\sum_{i'} \sum_{k_1} \sum_{k_2} (E^{\text{T}} A^{-1})_{i'k_1} E^{ij}_{k_1 k_2} (A^{-1} E)_{k_2 i'} \\
&= -\sum_{i'} (E^{\text{T}} A^{-1})_{i'i} (A^{-1} E)_{ji'} = \\
&= -\sum_{i'} (A^{-\text{T}} E)_{ii'} (E^{\text{T}} A^{-\text{T}})_{i'j} = -(A^{-\text{T}} E E^{\text{T}} A^{-\text{T}})_{ij} \\
&= -(A^{-1} E E^{\text{T}} A^{-1})^{\text{T}}_{ij}
\end{aligned}
\tag{20}
$$

$$\implies \frac{\partial}{\partial A_{ij}} \text{tr}(E^{\text{T}} A^{-1} E) = -(A^{-1} E E^{\text{T}} A^{-1})^{\text{T}}_{ij}.$$

Now, with respect to set a A whose cardinality is p and matrix $\boldsymbol{L} \in \mathbb{R}^{(p+q) \times (p+q)}$

$$
\begin{aligned}
&\frac{\partial}{\partial \theta} \text{tr}(\boldsymbol{I} - [(\boldsymbol{L} + \boldsymbol{I}_{\bar{A}})^{-1}]_{\bar{A}}) \\
&= -\frac{\partial}{\partial \theta} \text{tr}([(\boldsymbol{L} + \boldsymbol{I}_{\bar{A}})^{-1}]_{\bar{A}}) \\
&= -\frac{\partial}{\partial \theta} \text{tr}(E^{\text{T}} (\boldsymbol{L} + \boldsymbol{I}_{\bar{A}})^{-1} E),
\end{aligned}
\tag{21}
$$

where E denotes $\begin{bmatrix} \mathbf{0} \\ \boldsymbol{I}_q \end{bmatrix} \in \mathbb{R}^{(p+q) \times q}$. Then by Lemma 1.

$$
\begin{aligned}
-\frac{\partial}{\partial \theta} \mathrm{tr}(E^{\mathrm{T}}(\boldsymbol{L}+\mathbf{I}_{\bar{A}})^{-1}E) &= ((\boldsymbol{L}+I_{\bar{A}})^{-1}EE^{\mathrm{T}}(\boldsymbol{L}+\boldsymbol{I}_{\bar{A}})^{-1})^{\mathrm{T}}\boldsymbol{L}'(\theta) \\
&= ((\boldsymbol{L}+I_{\bar{A}})^{-1}\boldsymbol{I}_q(\boldsymbol{L}+\boldsymbol{I}_{\bar{A}})^{-1})^{\mathrm{T}}\boldsymbol{L}'(\theta)
\end{aligned}
\tag{22}
$$

The proof of Proposition 1 is now finished.

C   ALGORITHMS FOR PDM TRAINING AND INFERENCE OF DPP-TTS

C.1   PDM TRAINING

Algorithm 1 Training of PDM

Require: TextEncoder $f(\cdot)$, PDM parameterized θ, a prosody predictor (trained flow) $g(\cdot)$, number of candidates n_c, noise scale ϵ

1: **while** not converged **do**
2:    $h_{text} \leftarrow f(text)$
3:    Split h_{text} into $[h_{target}, h_{context}]$
4:    Sample latent code $z_{context} \in \mathbb{R}^T$ with noise scale ϵ
5:    Get prosodic features of contexts: $d_{context} \leftarrow g^{-1}(h_{context}, z_{context})$
6:    Get quality of contexts: $q_{context} =$ Density estimation$(d_{context})$
7:    Sample latent codes z_{target} with noise scale ϵ
8:    Get latent codes after PDM: $z_{target} \leftarrow \text{PDM}(z_{target}) \in \mathbb{R}^{n_c \times T}$
9:    Get n_c prosodic features of targets: $(d^1_{target}, d^2_{target}, ... d^{n_c}_{target})$
10:   Get quality of targets: $q_{target} =$ Density estimation(d_{target})
11:   Concatenate contexts and targets: $[q_{context}, q_{target}], [d_{context}, d_{target}]$
12:   Build the kernel of conditional DPPs:
      $\boldsymbol{L} \leftarrow$ Build kernel$([q_{context}, q_{target}], [d_{Context}, d_{target}])$
13:   Calculate the loss function: $L_{diversity} \leftarrow -\text{tr}(I - [(L + I_{\bar{A}})^{-1}]_{\bar{A}})$
14:   Update θ with the gradient $\nabla L_{diversity}$
15: **end while**

C.2   INFERENCE OF DPP-TTS

Algorithm 2 Inference of DPP-TTS

Require: TextEncoder $f(\cdot)$, Decoder $h(\cdot)$, PDM, a prosody predictor $g(\cdot)$, noise scale ϵ

1: $h_{text} \leftarrow f(text)$
2: Split h_{text} into $[h_{target}, h_{context}]$
3: Sample latent code $z_{context} \in \mathbb{R}^{rmT}$ with noise scale ϵ
4: Get prosodic features of contexts: $d_{context} \leftarrow g^{-1}(h_{context}, z_{context})$
5: Get quality of contexts: $q_{context} =$ Density estimation$(d_{context})$
6: Sample latent codes z_{target} with noise scale ϵ
7: Get latent codes after PDM: $z_{target} \leftarrow \text{PDM}(z_{target}) \in \mathbb{R}^{n_c \times T}$
8: Get n_c prosodic features of targets: $(d^1_{target}, d^2_{target}, ... d^{n_c}_{target})$
9: Get quality of targets: $q_{target} =$ Density estimation(d_{target})
10: Concatenate contexts and targets: $[q_{context}, q_{target}], [d_{context}, d_{target}]$
11: Build the kernel of conditional DPPs:
    $\boldsymbol{L} \leftarrow$ Build kernel$([q_{context}, q_{target}], [d_{Context}, d_{target}])$
12: Perform the MAP inference $d^* \leftarrow \arg\max_d \text{ logdet}(\boldsymbol{L}_{d \cup d_{context}})$
13: Synthesize wavs with prosodic features: $y \leftarrow h(h_{text}, d^*)$

D   SAMPLE PARAGRAPH FOR THE SIDE-BY-SIDE COMPARISON TEST

Now, cut to the future, about 10 days or so after all these events. Hale is in the Forge with Bernard in her custody. She's still searching for an encryption key that will allow Delos to decode all the guest data now apparently in their possession. She suggest that it's hidden in the dead Dolores. What she doesn't know is that it's not Bernard didn't transmit the guest data but data about the hosts, and Bernard has created a robot replica of Hale and installed it with Dolores's code. The new Hale appears from stage left, kills the old one and it's check mate to the hosts.