# DATA-EFFICIENT REINFORCEMENT LEARNING WITH SELF-PREDICTIVE REPRESENTATIONS

## ABSTRACT

While deep reinforcement learning excels at solving tasks where large amounts of data can be collected through virtually unlimited interaction with the environment, learning from limited interaction remains a key challenge. We posit that an agent can learn more efficiently if we augment reward maximization with self-supervised objectives based on structure in its visual input and sequential interaction with the environment. Our method, Self-Predictive Representations (SPR), trains an agent to predict its own latent state representations multiple steps into the future. We compute *target* representations for future states using an encoder which is an exponential moving average of the agent's parameters and we make predictions using a learned transition model. On its own, this future prediction objective outperforms prior methods for sample-efficient deep RL from pixels. We further improve performance by adding data augmentation to the future prediction loss, which forces the agent's representations to be consistent across multiple views of an observation. Our full self-supervised objective, which combines future prediction and data augmentation, achieves a median human-normalized score of 0.415 on Atari in a setting limited to 100k steps of environment interaction, which represents a 55% relative improvement over the previous state-of-the-art. Notably, even in this limited data regime, SPR exceeds expert human scores on 7 out of 26 games. We've made the code associated with this work available at https://anonymous.4open.science/r/b4b93ec6-6e5d-4f43-9b53-54bdf73bea95/.

## 1 INTRODUCTION

Deep Reinforcement Learning (deep RL, François-Lavet et al., 2018) has proven to be an indispensable tool for training successful agents on difficult sequential decision-making problems (Bellemare et al., 2013; Tassa et al., 2018). The success of deep RL is particularly noteworthy in highly complex, strategic games such as StarCraft (Vinyals et al., 2019) and DoTA2 (OpenAI et al., 2019), where deep RL agents now surpass expert human performance in some scenarios.

Deep RL involves training agents based on large neural networks using large amounts of data (Sutton, 2019), a trend evident across both model-based (Schrittwieser et al., 2019) and model-free (Badia et al., 2020) learning. The sample complexity of such state-of-the-art agents is often incredibly high: MuZero (Schrittwieser et al., 2019) and Agent-57 (Badia et al., 2020) use 10-50 years of experience per Atari game, and OpenAI Five (OpenAI et al., 2019) uses *45,000 years* of experience to accomplish its remarkable performance. This is clearly impractical: unlike easily-simulated environments such as video games, collecting interaction data for many real-world tasks is costly, making improved *data efficiency* a prerequisite for successful use of deep RL in these settings (Dulac-Arnold et al., 2019).

Meanwhile, new self-supervised representation learning methods have significantly improved data efficiency when learning new vision and language tasks, particularly in low data regimes or semi-supervised learning (Xie et al., 2019; Hénaff et al., 2019; Chen et al., 2020b). Self-supervised methods improve data efficiency by leveraging a nearly limitless supply of training signal from tasks generated on-the-fly, based on "views" drawn from the natural structure of the data (e.g., image patches, data augmentation or temporal proximity, see Doersch et al., 2015; Oord et al., 2018; Hjelm et al., 2019; Tian et al., 2019; Bachman et al., 2019; He et al., 2020; Chen et al., 2020a).

Motivated by successes in semi-supervised and self-supervised learning (Tarvainen & Valpola, 2017; Xie et al., 2019; Grill et al., 2020), we train better state representations for RL by forcing representa-

Figure 1: Median and Mean Human-Normalized scores of different methods across 26 games in the Atari 100k benchmark (Kaiser et al., 2019), averaged over 10 random seeds for SPR, and 5 seeds for most other methods except CURL, which uses 20. Each method is allowed access to only 100k environment steps or 400k frames per game. (*) indicates that the method uses data augmentation. SPR achieves state-of-art results on both mean and median human-normalized scores. Note that, even without data augmentation, SPR still outperforms all prior methods on both metrics.

tions to be temporally predictive and consistent when subject to data augmentation. Specifically, we extend a strong model-free agent by adding a dynamics model which predicts future latent representations provided by a parameter-wise exponential moving average of the agent itself. We also add data augmentation to the future prediction task, which enforces consistency across different views of each observation. Contrary to some methods (Kaiser et al., 2019; Hafner et al., 2019), our dynamics model operates entirely in the latent space and does not rely on reconstructing raw states.

We evaluate our method, which we call Self-Predictive Representations (SPR), on the 26 games in the Atari 100k benchmark (Kaiser et al., 2019), where agents are allowed only 100k steps of environment interaction (producing 400k frames of input) per game, which roughly corresponds to two hours of real-time experience. Notably, the human experts in Mnih et al. (2015) and Van Hasselt et al. (2016) were given the same amount of time to learn these games, so a budget of 100k steps permits a reasonable comparison in terms of data efficiency.

In our experiments, we augment a modified version of Data-Efficient Rainbow (DER) (van Hasselt et al., 2019) with the SPR loss, and evaluate versions of SPR with and without data augmentation. We find that each version is superior to controlled baselines. When coupled with data augmentation, SPR achieves a median score of 0.415, which is a state-of-the-art result on this benchmark, outperforming prior methods by a significant margin. Notably, SPR also outperforms human expert scores on 7 out of 26 games while using roughly the same amount of in-game experience.

## 2 METHOD

We consider reinforcement learning (RL) in the standard Markov Decision Process (MDP) setting where an agent interacts with its environment in *episodes*, each consisting of sequences of observations, actions and rewards. We use $o_t$, $a_t$ and $r_t$ to denote the observation, the action taken by the agent and the reward received at timestep $t$. We seek to train an agent whose expected cumulative reward in each episode is maximized. To do this, we combine a strong model-free RL algorithm, Rainbow (Hessel et al., 2018), with Self-Predictive Representations as an auxiliary loss to improve sample efficiency. We now describe our overall approach in detail.

### 2.1 DEEP Q-LEARNING

We focus on the Atari Learning Environment (Bellemare et al., 2013), a challenging setting where the agent takes discrete actions while receiving purely visual, pixel-based observations. A prominent method for solving Atari, Deep Q Networks (Mnih et al., 2015), trains a neural network $Q_\theta$ to approximate the agent's current *Q-function* (policy evaluation) while updating the agent's policy greedily with respect to this Q-function (policy improvement). This involves minimizing the error

Figure 2: An illustration of the full SPR method. Representations from the online encoder are used in the reinforcement learning task and for prediction of future representations from the target encoder via the transition model. The target encoder and projection head are defined as an exponential moving average of their online counterparts and are not updated via gradient descent. For brevity, we illustrate only the $k^{\text{th}}$ step of future prediction, but in practice we compute the loss over all steps from 1 to $K$. Note: our implementation for this paper includes $g_o$ in the Q-learning head.

between predictions from $Q_\theta$ and a target value estimated by $Q_\xi$, an earlier version of the network:

$$\mathcal{L}_{DQN} = \left( Q_\theta(o_t, a_t) - (r_t + \gamma \max_a Q_\xi(o_{t+1}, a)) \right)^2. \tag{1}$$

Various improvements have been made over the original DQN: Distributional RL (Bellemare et al., 2017) models the full distribution of future reward rather than just the mean, Dueling DQN (Wang et al., 2016) decouples the *value* of a state from the *advantage* of taking a given action in that state, Double DQN (Van Hasselt et al., 2016) modifies the Q-learning update to avoid overestimation due to the max operation, among many others. Rainbow (Hessel et al., 2018) consolidates these improvements into a single combined algorithm and has been adapted to work well in data-limited regimes (van Hasselt et al., 2019).

## 2.2 SELF-PREDICTIVE REPRESENTATIONS

For our auxiliary loss, we start with the intuition that encouraging state representations to be predictive of future observations given future actions should improve the data efficiency of RL algorithms. Let $(s_{t:t+K}, a_{t:t+K})$ denote a sequence of $K + 1$ previously experienced states and actions sampled from a replay buffer, where $K$ is the maximum number of steps into the future which we want to predict. Our method has four main components which we describe below:

- **Online and Target networks**: We use an *online encoder* $f_o$ to transform observed states $s_t$ into representations $z_t \triangleq f_o(s_t)$. We use these representations in an objective that encourages them to be *predictive* of future observations up to some fixed temporal offset $K$, given a sequence of $K$ actions to perform. We augment each observation $s_t$ independently when using data augmentation. Rather than predicting representations produced by the online encoder, we follow prior work (Tarvainen & Valpola, 2017; Grill et al., 2020) by computing target representations for future states using a *target encoder* $f_m$, whose parameters are an exponential moving average (EMA) of the online encoder parameters. Denoting the parameters of $f_o$ as $\theta_o$, those of $f_m$ as $\theta_m$, and the EMA coefficient as $\tau \in [0, 1)$, the update rule for $\theta_m$ is:

$$\theta_m \leftarrow \tau \theta_m + (1 - \tau)\theta_o. \tag{2}$$

The target encoder is not updated via gradient descent. The special case $\tau = 0$, $\theta_m = \theta_o$ is noteworthy, as it performs well when regularization is already provided by data augmentation.

- **Transition Model:** For the prediction objective, we generate a sequence of $K$ predictions $\hat{z}_{t+1:t+K}$ of future state representations $\tilde{z}_{t+1:t+K}$ using an action-conditioned *transition model* $h$. We compute $\hat{z}_{t+1:t+K}$ iteratively: $\hat{z}_{t+k+1} \triangleq h(\hat{z}_{t+k}, a_{t+k})$, starting from $\hat{z}_t \triangleq z_t \triangleq f_o(s_t)$. We compute $\tilde{z}_{t+1:t+K}$ by applying the target encoder $f_m$ to the observed future states $s_{t+1:t+K}$: $\tilde{z}_{t+k} \triangleq f_m(s_{t+k})$. The transition model and prediction loss operate in the latent space, thus avoiding pixel-based reconstruction objectives. We describe the architecture of $h$ in section 2.3.

- **Projection Heads:** We use online and target projection heads $g_o$ and $g_m$ (Chen et al., 2020a) to project online and target representations to a smaller latent space, and apply an additional *prediction head* $q$ (Grill et al., 2020) to the online projections to predict the target projections:

$$\hat{y}_{t+k} \triangleq q(g_o(\hat{z}_{t+k})), \; \forall \hat{z}_{t+k} \in \hat{z}_{t+1:t+K}; \quad \tilde{y}_{t+k} \triangleq g_m(\tilde{z}_{t+k}), \; \forall \tilde{z}_{t+k} \in \tilde{z}_{t+1:t+K}. \quad (3)$$

The target projection head parameters are given by an EMA of the online projection head parameters, using the same update as the online and target encoders.

- **Prediction Loss**: We compute the future prediction loss for SPR by summing over cosine similarities[1] between the predicted and observed representations at timesteps $t + k$ for $1 \leq k \leq K$:

$$\mathcal{L}^{\text{SPR}}(s_{t:t+K}, a_{t:t+K}) = -\sum_{k=1}^{K} \left( \frac{\tilde{y}_{t+k}}{||\tilde{y}_{t+k}||_2} \right)^{\top} \left( \frac{\hat{y}_{t+k}}{||\hat{y}_{t+k}||_2} \right), \quad (4)$$

where $\tilde{y}_{t+k}$ and $\hat{y}_{t+k}$ are computed from $(s_{t:t+K}, a_{t:t+K})$ as we just described.

We call our method Self-Predictive Representations (SPR), following the predictive nature of the objective and the use of an exponential moving average target network similar to (Tarvainen & Valpola, 2017; He et al., 2020). During training, we combine the SPR loss with the Q-learning loss for Rainbow. The SPR loss affects $f_o$, $g_o$, $q$ and $h$. The Q-learning loss affects $f_o$ and the Q-learning head, which contains additional layers specific to Rainbow. Denoting the Q-learning loss from Rainbow as $\mathcal{L}^{\text{RL}}$, our full optimization objective is: $\mathcal{L}_\theta^{\text{total}} = \mathcal{L}_\theta^{\text{RL}} + \lambda \mathcal{L}_\theta^{\text{SPR}}$.

Unlike some other proposed methods for representation learning in reinforcement learning (Srinivas et al., 2020), SPR can be used with or without data augmentation, including in contexts where data augmentation is unavailable or counterproductive. Moreover, compared to related work on contrastive representation learning, SPR does not use negative samples, which may require careful design of contrastive tasks, large batch sizes (Chen et al., 2020a), or the use of a buffer to emulate large batch sizes (He et al., 2020)

### 2.3 TRANSITION MODEL ARCHITECTURE

For the transition model $h$, we apply a convolutional network directly to the $64 \times 7 \times 7$ spatial output of the convolutional encoder $f_o$. The network comprises two 64-channel convolutional layers with $3 \times 3$ filters, with batch normalization (Ioffe & Szegedy, 2015) after the first convolution and ReLU nonlinearities after each convolution. We append a one-hot vector representing the action taken to each location in the input to the first convolutional layer, similar to Schrittwieser et al. (2019). We use a maximum prediction depth of $K = 5$, and we truncate calculation of the SPR loss at episode boundaries to avoid encoding environment reset dynamics into the model.

### 2.4 DATA AUGMENTATION

When using augmentation, we use the same set of image augmentations as in DrQ from Kostrikov et al. (2020), consisting of small random shifts and color jitter. We normalize activations to lie in $[0, 1]$ at the output of the convolutional encoder and transition model, as in Schrittwieser et al. (2019). We use Kornia (Riba et al., 2020) for efficient GPU-based data augmentations.

When not using augmentation, we find that SPR performs better when dropout (Srivastava et al., 2014) with probability $0.5$ is applied at each layer in the online and target encoders. This is consistent with Laine & Aila (2017); Tarvainen & Valpola (2017), who find that adding noise inside the network is important when not using image-specific augmentation, as proposed by Bachman et al. (2014). We found that dropout was not helpful when using image-specific augmentation.

---

[1]Cosine similarity is proportional to the "normalized L2" loss used in BYOL (Grill et al., 2020).

---

**Algorithm 1:** Self-Predictive Representations

---

Denote parameters of online encoder $f_o$ and projection $g_o$ as $\theta_o$
Denote parameters of target encoder $f_m$ and projection $g_m$ as $\theta_{\mathrm{m}}$
Denote parameters of transition model $h$, predictor $q$ and Q-learning head as $\phi$
Denote the maximum prediction depth as $K$
initialize replay buffer $B$
**while** *Training* **do**
   collect experience $(s, a, r, s')$ with $(\theta_o, \phi)$ and add to buffer $B$
   sample a minibatch of sequences of $(s, a, r, s') \sim B$
   **if** *augmentation* **then**
     | $s \leftarrow$ augment$(s)$
   **end**
   $z_0 \leftarrow f_\theta(s_0)$                             `// online representations`
   $l \leftarrow 0$
   **for** *k in (1, ..., K)* **do**
     | $\hat{z}_k \leftarrow h(\hat{z}_{k-1}, a_{k-1})$      `// latent states via transition model`
     | $\tilde{z}_k \leftarrow f_m(s_k)$                  `// target representations`
     | $\hat{y}_k \leftarrow q(g_o(\hat{z}_k)), \tilde{y}_k \leftarrow g_m(\tilde{z}_k)$         `// projections`
     | $l \leftarrow l - \left(\frac{\tilde{y}_k}{||\tilde{y}_k||_2}\right)^\top \left(\frac{\hat{y}_k}{||\hat{y}_k||_2}\right)$      `// SPR loss at step` $k$
   **end**
   $l \leftarrow \lambda l + \mathrm{RL\ loss}(s, a, r, s'; \theta_o)$     `// Add RL loss for batch with` $\theta_o$
   $\theta_o, \phi \leftarrow$ optimize$((\theta_o, \phi), l)$        `// update online parameters`
   $\theta_m \leftarrow \tau\theta_o + (1-\tau)\theta_m$        `// update target parameters`
**end**

---

## 2.5 IMPLEMENTATION DETAILS

For our Atari experiments, we largely follow van Hasselt et al. (2019) for DQN hyperparameters, with four exceptions. We follow DrQ (Kostrikov et al., 2020) by: using the 3-layer convolutional encoder from Mnih et al. (2015), using 10-step returns instead of 20-step returns for Q-learning, and not using a separate DQN target network when using augmentation[2]. We also perform two gradient steps per environment step instead of one. We show results for this configuration with and without augmentation in Table 5, and confirm that these changes are not themselves responsible for our performance. We reuse the first layer of the DQN MLP head as the SPR projection head $g_o$. When using dueling DQN (Wang et al., 2016), $g_o$ concatenates the outputs of the first layers of the value and advantage heads. When these layers are noisy (Fortunato et al., 2018), $g_o$ does not use the noisy parameters. Finally, we parameterize the predictor $q$ as a linear layer. Based on experiments over a subset of games, we use $\tau = 0.99$ when augmentation is disabled and $\tau = 0$ when enabled. For $\mathcal{L}_\theta^{\mathrm{total}} = \mathcal{L}_\theta^{\mathrm{RL}} + \lambda\mathcal{L}_\theta^{\mathrm{SPR}}$, we use $\lambda = 2$ based on early experiments. We list the complete hyperparameters in Table 3.

Our implementation uses `rlpyt` (Stooke & Abbeel, 2019) and `PyTorch` (Paszke et al., 2019).

## 3 RELATED WORK

### 3.1 DATA-EFFICIENT RL:

A number of works have sought to improve sample efficiency in deep RL. SiMPLe (Kaiser et al., 2019) learns a pixel-level transition model for Atari to generate simulated training data, achieving strong results on several games in the 100k frame setting. However, van Hasselt et al. (2019) and Kielak (2020) introduce variants of Rainbow (Hessel et al., 2018) tuned for sample efficiency, Data-Efficient Rainbow (DER) and OTRainbow, which achieve comparable or superior performance with far less computation.

---

[2]Note that this makes Double DQN updates (Van Hasselt et al., 2016) identical to standard DQN updates.

In the context of continuous control, several works propose to leverage a latent-space model trained on reconstruction loss to improve sample efficiency (Hafner et al., 2019; Lee et al., 2019; Hafner et al., 2020). Most recently, DrQ (Kostrikov et al., 2020) and RAD (Laskin et al., 2020) have found that applying modest image augmentation can substantially improve sample efficiency in reinforcement learning, yielding better results than prior model-based methods. Data augmentation has also been found to improve generalization of reinforcement learning methods (Combes et al., 2018; Laskin et al., 2020) in multi-task and transfer settings. We show that data augmentation can be more effectively leveraged in reinforcement learning by forcing representations to be consistent between different augmented views of an observation while also predicting future latent states.

## 3.2 REPRESENTATION LEARNING IN RL:

Representation learning has a long history of use in RL – see Lesort et al. (2018). For example, CURL (Srinivas et al., 2020) recently proposed a combination of image augmentation and a contrastive loss to perform representation learning for RL. However, follow-up results from RAD (Laskin et al., 2020) suggest that most of the benefits of CURL come from its use of image augmentation rather than its contrastive loss.

CPC (Oord et al., 2018), CPC|Action (Guo et al., 2018), ST-DIM (Anand et al., 2019) and DRIML (Mazoure et al., 2020) propose to optimize various temporal contrastive losses in reinforcement learning environments. We perform an ablation comparing such temporal contrastive losses to our method in Section 5. Kipf et al. (2019) propose to learn object-oriented contrastive representations by training a structured transition model based on a graph neural network.

SPR bears some resemblance to DeepMDP (Gelada et al., 2019), which trains a transition model with an unnormalized L2 loss to predict representations of future states, along with a reward prediction objective. However, DeepMDP uses its online encoder to generate prediction targets rather than employing a target encoder, and is thus prone to representational collapse (sec. C.5 in Gelada et al. (2019)). To mitigate this issue, DeepMDP relies on an additional observation reconstruction objective. In contrast, our model is self-supervised, trained entirely in the latent space, and uses a normalized loss. Our ablations (sec. 5) demonstrate that using a target encoder has a large impact on our method.

SPR is also similar to PBL (Guo et al., 2020), which directly predicts representations of future states. However, PBL uses two separate target networks trained via gradient descent, whereas SPR uses a single target encoder, updated without backpropagation. Moreover, PBL studies multi-task generalization in the asymptotic limits of data, whereas SPR is concerned with single-task performance in low data regimes, using $0.01\%$ as much data as PBL. Unlike PBL, SPR additionally enforces consistency across augmentations, which empirically provides a large boost in performance.

## 4 RESULTS

We test SPR on the sample-efficient Atari setting introduced by Kaiser et al. (2019) and van Hasselt et al. (2019). In this task, only 100,000 environment steps of training data are available – equivalent to 400,000 frames, or just under two hours – compared to the typical standard of 50,000,000 environment steps, or roughly 39 days of experience. When used without data augmentation, SPR demonstrates scores comparable to the previous best result from Kostrikov et al. (2020). When combined with data augmentation, SPR achieves a median human-normalized score of 0.415, which is a new state-of-the-art result on this task. SPR achieves super-human performance on seven games in this data-limited setting: Boxing, Krull, Kangaroo, Road Runner, James Bond and Crazy Climber, compared to a maximum of two for any previous methods, and achieves scores higher than DrQ (the previous state-of-the-art method) on 23 out of 26 games. See Table 1 for aggregate metrics and Figure 3 for a visualization of results. A full list of scores is presented in Table 4 in the appendix. For consistency with previous works, we report human and random scores from Wang et al. (2016).

### 4.1 EVALUATION

We evaluate the performance of different methods by computing the average episodic return at the end of training. We normalize scores with respect to expert human scores to account for different scales of scores in each game, as done in previous works. The human-normalized performance of an

Table 1: Performance of different methods on the 26 Atari games considered by Kaiser et al. (2019) after 100k environment steps. The results are recorded at the end of training and averaged over 10 random seeds for SPR and 5 for most other methods except CURL, which uses 20. SPR outperforms prior methods on all aggregate metrics, and exceeds expert human performance on 7 out of 26 games while using a similar amount of experience.

| Metric | Random | Human | SimPLe | DER | OTRainbow | CURL | DrQ | SPR (no Aug) | SPR |
|---|---|---|---|---|---|---|---|---|---|
| Mean Human-Norm'd | 0.000 | 1.000 | 0.443 | 0.285 | 0.264 | 0.381 | 0.357 | 0.463 | **0.704** |
| Median Human-Norm'd | 0.000 | 1.000 | 0.144 | 0.161 | 0.204 | 0.175 | 0.268 | 0.307 | **0.415** |
| Mean DQN@50M-Norm'd | 0.000 | 23.382 | 0.232 | 0.239 | 0.197 | 0.325 | 0.171 | 0.336 | **0.510** |
| Median DQN@50M-Norm'd | 0.000 | 0.994 | 0.118 | 0.142 | 0.103 | 0.142 | 0.131 | 0.225 | **0.361** |
| # Games Superhuman | 0 | N/A | 2 | 2 | 1 | 2 | 2 | 5 | **7** |

Figure 3: A boxplot of the distribution of human-normalized scores, averaged across 10 random seeds, for each method across the 26 Atari games under consideration after 100k environment steps.

agent on a game is calculated as $\frac{\text{agent score}-\text{random score}}{\text{human score}-\text{random score}}$ and aggregated across the 26 games by mean or median.

We find that human scores on some games are so high that differences between methods are washed out when normalizing scores, making it hard for these games to influence aggregate metrics. To address this, we also report DQN-normalized scores, defined analogously to human-normalized scores and calculated using scores from DQN agents (Mnih et al., 2015) trained over 50 million steps. We also find that the median metric is influenced only by a handful of games. Both these factors compound together to make the median human-normalized score not a reliable metric to judge performance over the complete distribution of games. Thus, we report other aggregate metrics in all results and ablations, and plot the distribution of scores over all the games in Figure 3.

Additionally, we note that the standard evaluation protocol of evaluating over only 500,000 frames per game is problematic, as the quantity we are trying to measure is expected return over episodes. Because episodes may last up to up to 108,000 frames, this method may collect as few as four complete episodes. As variance of results is already a concern in deep RL (see Henderson et al., 2018), we propose evaluating over 100 episodes irrespective of their length.

## 5 ANALYSIS

We now present several ablation studies to measure the contributions of components in our method.

**The target encoder** We find that using a separate target encoder is vital in all cases. A variant of SPR in which target representations are generated by the online encoder without a stopgradient (as done by e.g., Gelada et al., 2019) exhibits catastrophically reduced performance, with median human-normalized score of $0.278$ with augmentation versus $0.415$ for SPR. However, there is more flexibility in the EMA constant used for the target encoder. When using augmentation, a value of $\tau = 0$ performs best, while without augmentation we use $\tau = 0.99$. The success of $\tau = 0$ is

Table 2: Scores on the 26 Atari games under consideration for variants of SPR with ablated temporal prediction. All variants listed here use data augmentation.

| Variant | Human-Normalized Score | | DQN@50M-Normalized Score | |
| --- | --- | --- | --- | --- |
| | mean | median | mean | median |
| SPR | **0.704** | **0.415** | **0.510** | **0.361** |
| 1-step SPR | 0.570 | 0.301 | 0.337 | 0.346 |
| Non-temporal SPR | 0.507 | 0.271 | 0.326 | 0.295 |
| Rainbow (controlled, w/ aug.) | 0.480 | 0.346 | 0.284 | 0.278 |

interesting, since the related method BYOL reports poor representation learning performance in this case. We hypothesize that optimizing a reinforcement learning objective in parallel with the SPR loss explains this difference, as it provides an additional gradient which discourages representational collapse. Full results for these experiments are presented in Appendix C.

**Dynamics modeling is key**    A key distinction between SPR and other recent approaches leveraging representation learning for reinforcement learning, such as CURL (Srinivas et al., 2020) and DRIML (Mazoure et al., 2020), is our use of an explicit multi-step dynamics model. We test two ablated versions of SPR, one with no dynamics modeling and one that models only a single step of dynamics. Each of these variants has substantially degraded performance compared to five-step SPR, with extended dynamics modeling consistently improving performance (see Table 2). The non-temporal ablation we test is similar to using BYOL (Grill et al., 2020) as an auxiliary task, with particular architecture choices made for the projection layer and predictor.

**Comparison with contrastive losses**    Though many recent works in representation learning employ contrastive learning, we find that SPR consistently outperforms both temporal and non-temporal variants of contrastive losses (see Table 6, appendix), including CURL (Srinivas et al., 2020).

## 6  FUTURE WORK

Recent work in both visual (Chen et al., 2020b) and language representation learning (Brown et al., 2020) has suggested that self-supervised models trained on large datasets perform exceedingly well on downstream problems with limited data, often outperforming methods trained using only task-specific data. Future works could similarly exploit large corpora of unlabelled data, perhaps from multiple MDPs or raw videos, to further improve the performance of RL methods in low-data regimes. As the SPR objective is unsupervised, it could be directly applied in such settings.

Another interesting direction is to use the transition model learned by SPR for planning. MuZero (Schrittwieser et al., 2019) has demonstrated that planning with a model supervised via reward and value prediction can work extremely well given sufficient (massive) amounts of data. It remains unclear whether such models can work well in low-data regimes, and whether augmenting such models with self-supervised objectives such as SPR can improve their data efficiency.

## 7  CONCLUSION

In this paper we introduced Self-Predictive Representations (SPR), a self-supervised representation learning algorithm designed to improve the data efficiency of deep reinforcement learning agents. SPR learns representations that are both temporally predictive and consistent across different views of environment observations, by directly predicting representations of future states produced by a target encoder. SPR achieves state-of-the-art performance on the 100k steps Atari benchmark, demonstrating significant improvements over prior work. Our experiments show that SPR is highly robust, and is able to outperform the previous state of the art when either data augmentation or temporal prediction is disabled. We identify important directions for future work, and hope continued research at the intersection of self-supervised learning and reinforcement learning leads to algorithms which rival the efficiency and robustness of humans.

# REFERENCES

Ankesh Anand, Evan Racah, Sherjil Ozair, Yoshua Bengio, Marc-Alexandre Côté, and R Devon Hjelm. Unsupervised state representation learning in atari. In *NeurIPS*, 2019. Cited on page 6.

Philip Bachman, Ouais al Sharif, and Doina Precup. Learning with pseudo-ensembles. In *NeurIPS*, 2014. Cited on page 4.

Philip Bachman, R Devon Hjelm, and William Buchwalter. Learning representations by maximizing mutual information across views. In *NeurIPS*, 2019. Cited on page 1.

Adrià Puigdomènech Badia, Bilal Piot, Steven Kapturowski, Pablo Sprechmann, Alex Vitvitskyi, Daniel Guo, and Charles Blundell. Agent57: Outperforming the atari human benchmark. In *ICML*, 2020. Cited on page 1.

Marc G Bellemare, Yavar Naddaf, Joel Veness, and Michael Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47, 2013. Cited on pages 1 and 2.

Marc G Bellemare, Will Dabney, and Rémi Munos. A distributional perspective on reinforcement learning. In *ICML*, 2017. Cited on page 3.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020. Cited on page 8.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *ICML*, 2020a. Cited on pages 1, 4, and 14.

Ting Chen, Simon Kornblith, Kevin Swersky, Mohammad Norouzi, and Geoffrey Hinton. Big self-supervised models are strong semi-supervised learners. *arXiv preprint arXiv:2006.10029*, 2020b. Cited on pages 1 and 8.

Remi Tachet des Combes, Philip Bachman, and Harm van Seijen. Learning invariances for policy generalization. *arXiv preprint arXiv:1809.02591*, 2018. Cited on page 6.

Carl Doersch, Abhinav Gupta, and Alexei A Efros. Unsupervised visual representation learning by context prediction. In *ICCV*, 2015. Cited on page 1.

Gabriel Dulac-Arnold, Daniel Mankowitz, and Todd Hester. Challenges of real-world reinforcement learning. In *ICML*, 2019. Cited on page 1.

Meire Fortunato, Mohammad Gheshlaghi Azar, Bilal Piot, Jacob Menick, Matteo Hessel, Ian Osband, Alex Graves, Volodymyr Mnih, Remi Munos, Demis Hassabis, Olivier Pietquin, Charles Blundell, and Shane Legg. Noisy networks for exploration. In *ICLR*, 2018. Cited on page 5.

Vincent François-Lavet, Peter Henderson, Riashat Islam, Marc G Bellemare, and Joelle Pineau. An introduction to deep reinforcement learning. *arXiv preprint arXiv:1811.12560*, 2018. Cited on page 1.

Carles Gelada, Saurabh Kumar, Jacob Buckman, Ofir Nachum, and Marc G Bellemare. Deepmdp: Learning continuous latent space models for representation learning. In *ICML*, 2019. Cited on pages 6 and 7.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre H Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Daniel Guo, Mohammad Gheshlaghi Azar, et al. Bootstrap your own latent: A new approach to self-supervised learning. *arXiv preprint arXiv:2006.07733*, 2020. Cited on pages 1, 3, 4, 8, and 15.

Daniel Guo, Bernardo Avila Pires, Bilal Piot, Jean-bastien Grill, Florent Altché, Rémi Munos, and Mohammad Gheshlaghi Azar. Bootstrap latent-predictive representations for multitask reinforcement learning. In *ICML*, 2020. Cited on page 6.

Zhaohan Daniel Guo, Mohammad Gheshlaghi Azar, Bilal Piot, Bernardo A Pires, and Rémi Munos. Neural predictive belief representations. *ICML*, 2018. Cited on pages 6 and 14.

Danijar Hafner, Timothy Lillicrap, Ian Fischer, Ruben Villegas, David Ha, Honglak Lee, and James Davidson. Learning latent dynamics for planning from pixels. In *ICML*, 2019. Cited on pages 2 and 6.

Danijar Hafner, Timothy Lillicrap, Jimmy Ba, and Mohammad Norouzi. Dream to control: Learning behaviors by latent imagination. In *ICLR*, 2020. Cited on page 6.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *CVPR*, 2020. Cited on pages 1 and 4.

Olivier J Hénaff, Aravind Srinivas, Jeffrey De Fauw, Ali Razavi, Carl Doersch, SM Eslami, and Aaron van den Oord. Data-efficient image recognition with contrastive predictive coding. *arXiv preprint arXiv:1905.09272*, 2019. Cited on page 1.

Peter Henderson, Riashat Islam, Philip Bachman, Joelle Pineau, Doina Precup, and David Meger. Deep reinforcement learning that matters. In *AAAI*, 2018. Cited on page 7.

Matteo Hessel, Joseph Modayil, Hado van Hasselt, Tom Schaul, Georg Ostrovski, Will Dabney, Dan Horgan, Bilal Piot, Mohammad Gheshlaghi Azar, and David Silver. Rainbow: Combining improvements in deep reinforcement learning. In *AAAI*, 2018. Cited on pages 2, 3, and 5.

R Devon Hjelm, Alex Fedorov, Samuel Lavoie-Marchildon, Karan Grewal, Phil Bachman, Adam Trischler, and Yoshua Bengio. Learning deep representations by mutual information estimation and maximization. In *ICLR*, 2019. Cited on page 1.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *ICML*, 2015. Cited on page 4.

Łukasz Kaiser, Mohammad Babaeizadeh, Piotr Miłos, Błażej Osiński, Roy H Campbell, Konrad Czechowski, Dumitru Erhan, Chelsea Finn, Piotr Kozakowski, Sergey Levine, et al. Model based reinforcement learning for atari. In *ICLR*, 2019. Cited on pages 2, 5, 6, 7, and 13.

Kacper Piotr Kielak. Do recent advancements in model-based deep reinforcement learning really improve data efficiency?, 2020. URL https://openreview.net/forum?id=Bke9u1HFwB. Cited on pages 5 and 12.

Thomas Kipf, Elise van der Pol, and Max Welling. Contrastive learning of structured world models. In *ICLR*, 2019. Cited on page 6.

Ilya Kostrikov, Denis Yarats, and Rob Fergus. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. *arXiv preprint arXiv:2004.13649*, 2020. Cited on pages 4, 5, and 6.

Samuli Laine and Timo Aila. Temporal ensembling for semi-supervised learning. In *ICLR*, 2017. Cited on page 4.

Michael Laskin, Kimin Lee, Adam Stooke, Lerrel Pinto, Pieter Abbeel, and Aravind Srinivas. Reinforcement learning with augmented data. *arXiv preprint arXiv:2004.14990*, 2020. Cited on page 6.

Alex X Lee, Anusha Nagabandi, Pieter Abbeel, and Sergey Levine. Stochastic latent actor-critic: Deep reinforcement learning with a latent variable model. *arXiv preprint arXiv:1907.00953*, 2019. Cited on page 6.

Timothée Lesort, Natalia Díaz-Rodríguez, Jean-Franois Goudou, and David Filliat. State representation learning for control: An overview. *Neural Networks*, 108, 2018. Cited on page 6.

Bogdan Mazoure, Remi Tachet des Combes, Thang Doan, Philip Bachman, and R Devon Hjelm. Deep reinforcement and infomax learning. *arXiv preprint arXiv:2006.07217*, 2020. Cited on pages 6 and 8.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540), 2015. Cited on pages 2, 5, and 7.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018. Cited on pages 1, 6, and 14.

OpenAI, Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemysław Dębiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, Rafal Józefowicz, Scott Gray, Catherine Olsson, Jakub Pachocki, Michael Petrov, Henrique Pondé de Oliveira Pinto, Jonathan Raiman, Tim Salimans, Jeremy Schlatter, Jonas Schneider, Szymon Sidor, Ilya Sutskever, Jie Tang, Filip Wolski, and Susan Zhang. Dota 2 with large scale deep reinforcement learning. *arXiv preprint arXiv:1912.06680*, 2019. Cited on page 1.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. In *NeurIPS*, 2019. Cited on page 5.

Edgar Riba, Dmytro Mishkin, Daniel Ponsa, Ethan Rublee, and Gary Bradski. Kornia: an open source differentiable computer vision library for pytorch. In *The IEEE Winter Conference on Applications of Computer Vision*, 2020. Cited on page 4.

Julian Schrittwieser, Ioannis Antonoglou, Thomas Hubert, Karen Simonyan, Laurent Sifre, Simon Schmitt, Arthur Guez, Edward Lockhart, Demis Hassabis, Thore Graepel, et al. Mastering atari, go, chess and shogi by planning with a learned model. *arXiv preprint arXiv:1911.08265*, 2019. Cited on pages 1, 4, and 8.

Aravind Srinivas, Michael Laskin, and Pieter Abbeel. Curl: Contrastive unsupervised representations for reinforcement learning. In *ICML*, 2020. Cited on pages 4, 6, 8, and 14.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The Journal of Machine Learning Research*, 15(1), 2014. Cited on page 4.

Adam Stooke and Pieter Abbeel. rlpyt: A research code base for deep reinforcement learning in pytorch. *arXiv preprint arXiv:1909.01500*, 2019. Cited on page 5.

Richard Sutton. The bitter lesson. *Incomplete Ideas (blog)*, 2019. [http://www.incompleteideas.net/IncIdeas/BitterLesson.html](http://www.incompleteideas.net/IncIdeas/BitterLesson.html). Cited on page 1.

Antti Tarvainen and Harri Valpola. Mean teachers are better role models: Weight-averaged consistency targets improve semi-supervised deep learning results. In *NeurIPS*, 2017. Cited on pages 1, 3, 4, and 15.

Yuval Tassa, Yotam Doron, Alistair Muldal, Tom Erez, Yazhe Li, Diego de Las Casas, David Budden, Abbas Abdolmaleki, Josh Merel, Andrew Lefrancq, et al. Deepmind control suite. *arXiv preprint arXiv:1801.00690*, 2018. Cited on page 1.

Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive multiview coding. *arXiv preprint arXiv:1906.05849*, 2019. Cited on page 1.

Hado Van Hasselt, Arthur Guez, and David Silver. Deep reinforcement learning with double q-learning. In *AAAI*, 2016. Cited on pages 2, 3, and 5.

Hado P van Hasselt, Matteo Hessel, and John Aslanides. When to use parametric models in reinforcement learning? In *NeurIPS*, 2019. Cited on pages 2, 3, 5, 6, and 14.

Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 2019. Cited on page 1.

Tongzhou Wang and Phillip Isola. Understanding contrastive representation learning through alignment and uniformity on the hypersphere. *arXiv preprint arXiv:2005.10242*, 2020. Cited on page 14.

Ziyu Wang, Tom Schaul, Matteo Hessel, Hado Hasselt, Marc Lanctot, and Nando Freitas. Dueling network architectures for deep reinforcement learning. In *ICML*, 2016. Cited on pages 3, 5, and 6.

Qizhe Xie, Zihang Dai, Eduard Hovy, Minh-Thang Luong, and Quoc V Le. Unsupervised data augmentation for consistency training. *arXiv preprint arXiv:1904.12848*, 2019. Cited on page 1.

## A  ATARI DETAILS

We provide a full set of hyperparameters used in both the augmentation and no-augmentation cases in Table 3, including new hyperparameters for SPR.

Table 3: Hyperparameters for SPR on Atari, with and without augmentation.

| Parameter | Setting (for both variations) |
|---|---|
| Gray-scaling | True |
| Observation down-sampling | 84x84 |
| Frames stacked | 4 |
| Action repetitions | 4 |
| Reward clipping | [-1, 1] |
| Terminal on loss of life | True |
| Max frames per episode | 108K |
| Update | Distributional Q |
| Dueling | True |
| Support of Q-distribution | 51 |
| Discount factor | 0.99 |
| Minibatch size | 32 |
| Optimizer | Adam |
| Optimizer: learning rate | 0.0001 |
| Optimizer: $\beta_1$ | 0.9 |
| Optimizer: $\beta_2$ | 0.999 |
| Optimizer: $\epsilon$ | 0.00015 |
| Max gradient norm | 10 |
| Priority exponent | 0.5 |
| Priority correction | $0.4 \rightarrow 1$ |
| Exploration | Noisy nets |
| Noisy nets parameter | 0.5 |
| Training steps | 100K |
| Evaluation trajectories | 100 |
| Min replay size for sampling | 2000 |
| Replay period every | 1 step |
| Updates per step | 2 |
| Multi-step return length | 10 |
| Q network: channels | 32, 64, 64 |
| Q network: filter size | $8 \times 8, 4 \times 4, 3 \times 3$ |
| Q network: stride | 4, 2, 1 |
| Q network: hidden units | 256 |
| Non-linearity | ReLU |
| Target network: update period | 1 |
| $\lambda$ (SPR loss coefficient | 2 |
| $K$ (Prediction Depth) | 5 |

| Parameter | With Augmentation | Without Augmentation |
|---|---|---|
| Data Augmentation | Random shifts ($\pm 4$ pixels) & Intensity(scale=0.05) | None |
| Dropout | 0 | 0.5 |
| $\tau$ (EMA coefficient) | 0 | 0.99 |

### A.1  FULL RESULTS

We provide full results across all 26 games for the methods considered, including SPR with and without augmentation, in Table 4. Methods are ordered in rough order of their date of release or publication.

### A.2  CONTROLLED BASELINES

To ensure that the minor hyper-parameter changes we make to the DER baseline are not solely responsible for our improved performance, we perform controlled experiments using the same hyper-parameters and same random seeds for baselines. We find that our controlled Rainbow implementation without augmentation is slightly stronger than Data-Efficient Rainbow but comparable to Overtrained Rainbow (Kielak, 2020), while with augmentation enabled our results are somewhat stronger than DrQ.[3] None of these methods, however, are close to the performance of SPR.

---

[3]This is perhaps not surprising, given that the model used by DrQ omits many of the components of Rainbow.

Table 4: Mean episodic returns on the 26 Atari games considered by Kaiser et al. (2019) after 100k environment steps. The results are recorded at the end of training and averaged over 10 random seeds. SPR outperforms prior methods on all aggregate metrics, and exceeds expert human performance on 7 out of 26 games while using a similar amount of experience.

| Game | Random | Human | SimPLe | DER | OTRainbow | CURL | DrQ | SPR (no Aug) | SPR |
|---|---|---|---|---|---|---|---|---|---|
| Alien | 227.8 | 7127.7 | 616.9 | 739.9 | 824.7 | 558.2 | 771.2 | **847.2** | 801.5 |
| Amidar | 5.8 | 1719.5 | 88.0 | **188.6** | 82.8 | 142.1 | 102.8 | 142.7 | 176.3 |
| Assault | 222.4 | 742.0 | 527.2 | 431.2 | 351.9 | 600.6 | 452.4 | **665.0** | 571.0 |
| Asterix | 210.0 | 8503.3 | **1128.3** | 470.8 | 628.5 | 734.5 | 603.5 | 820.2 | 977.8 |
| Bank Heist | 14.2 | 753.1 | 34.2 | 51.0 | 182.1 | 131.6 | 168.9 | **425.6** | 380.9 |
| BattleZone | 2360.0 | 37187.5 | 5184.4 | 10124.6 | 4060.6 | 14870.0 | 12954.0 | 10738.0 | **16651.0** |
| Boxing | 0.1 | 12.1 | 9.1 | 0.2 | 2.5 | 1.2 | 6.0 | 12.7 | **35.8** |
| Breakout | 1.7 | 30.5 | 16.4 | 1.9 | 9.8 | 4.9 | 16.1 | 12.9 | **17.1** |
| ChopperCommand | 811.0 | 7387.8 | **1246.9** | 861.8 | 1033.3 | 1058.5 | 780.3 | 667.3 | 974.8 |
| Crazy Climber | 10780.5 | 35829.4 | **62583.6** | 16185.3 | 21327.8 | 12146.5 | 20516.5 | 43391.0 | 42923.6 |
| Demon Attack | 152.1 | 1971.0 | 208.1 | 508.0 | 711.8 | 817.6 | **1113.4** | 370.1 | 545.2 |
| Freeway | 0.0 | 29.6 | 20.3 | **27.9** | 25.0 | 26.7 | 9.8 | 16.1 | 24.4 |
| Frostbite | 65.2 | 4334.7 | 254.7 | 866.8 | 231.6 | 1181.3 | 331.1 | 1657.4 | **1821.5** |
| Gopher | 257.6 | 2412.5 | 771.0 | 349.5 | **778.0** | 669.3 | 636.3 | 774.5 | 715.2 |
| Hero | 1027.0 | 30826.4 | 2656.6 | 6857.0 | 6458.8 | 6279.3 | 3736.3 | 5707.4 | **7019.2** |
| Jamesbond | 29.0 | 302.8 | 125.3 | 301.6 | 112.3 | **471.0** | 236.0 | 367.2 | 365.4 |
| Kangaroo | 52.0 | 3035.0 | 323.1 | 779.3 | 605.4 | 872.5 | 940.6 | 1359.5 | **3276.4** |
| Krull | 1598.0 | 2665.5 | **4539.9** | 2851.5 | 3277.9 | 4229.6 | 4018.1 | 3123.1 | 3688.9 |
| Kung Fu Master | 258.5 | 22736.3 | **17257.2** | 14346.1 | 5722.2 | 14307.8 | 9111.0 | 15469.7 | 13192.7 |
| Ms Pacman | 307.3 | 6951.6 | **1480.0** | 1204.1 | 941.9 | 1465.5 | 960.5 | 1247.7 | 1313.2 |
| Pong | -20.7 | 14.6 | **12.8** | -19.3 | 1.3 | -16.5 | -8.5 | -16.0 | -5.9 |
| Private Eye | 24.9 | 69571.3 | 58.3 | 97.8 | 100.0 | **218.4** | -13.6 | 52.6 | 124.0 |
| Qbert | 163.9 | 13455.0 | **1288.8** | 1152.9 | 509.3 | 1042.4 | 854.4 | 606.6 | 669.1 |
| Road Runner | 11.5 | 7845.0 | 5640.6 | 9600.0 | 2696.7 | 5661.0 | 8895.1 | 10511.0 | **14220.5** |
| Seaquest | 68.4 | 42054.7 | **683.3** | 354.1 | 286.9 | 384.5 | 301.2 | 580.8 | 583.1 |
| Up N Down | 533.4 | 11693.2 | 3350.3 | 2877.4 | 2847.6 | 2955.2 | 3180.8 | 6604.6 | **28138.5** |
| Mean Human-Norm'd | 0.000 | 1.000 | 0.443 | 0.285 | 0.264 | 0.381 | 0.357 | 0.463 | **0.704** |
| Median Human-Norm'd | 0.000 | 1.000 | 0.144 | 0.161 | 0.204 | 0.175 | 0.268 | 0.307 | **0.415** |
| Mean DQN@50M-Norm'd | 0.000 | 23.382 | 0.232 | 0.239 | 0.197 | 0.325 | 0.171 | 0.336 | **0.510** |
| Median DQN@50M-Norm'd | 0.000 | 0.994 | 0.118 | 0.142 | 0.103 | 0.142 | 0.131 | 0.225 | **0.361** |
| # Superhuman | 0 | N/A | 2 | 2 | 1 | 2 | 2 | 5 | **7** |

Table 5: Scores on the 26 Atari games under consideration for our controlled Rainbow implementation with and without augmentation, compared to previous methods. The high mean DQN-normalized score of our DQN without augmentation is due to an atypically high score on Private Eye.

| Variant | Human-Normalized Score | | DQN@50M-Normalized Score | |
|---|---|---|---|---|
| | mean | median | mean | median |
| Rainbow (controlled, no aug) | 0.240 | 0.204 | 0.374 | 0.149 |
| OTRainbow | 0.264 | 0.204 | 0.197 | 0.103 |
| DER | 0.285 | 0.161 | 0.239 | 0.142 |
| Rainbow (controlled, w/ aug) | 0.480 | 0.346 | 0.284 | 0.278 |
| DrQ | 0.357 | 0.268 | 0.171 | 0.131 |

Table 6: Scores on the 26 Atari games under consideration for various contrastive alternatives to SPR implemented in our codebase. All variants listed here use data augmentation.

| Variant | Human-Normalized Score | | DQN@50M-Normalized Score | |
|---|---|---|---|---|
| | mean | median | mean | median |
| SPR | 0.704 | 0.415 | 0.510 | 0.361 |
| Rainbow (controlled) | 0.480 | 0.346 | 0.284 | 0.278 |
| Non-temporal contrastive | 0.379 | 0.200 | 0.268 | 0.179 |
| 1-step contrastive | 0.473 | 0.231 | 0.280 | 0.213 |
| 5-step contrastive | 0.506 | 0.172 | 0.239 | 0.142 |
| Uniformity loss | 0.422 | 0.176 | 0.271 | 0.144 |

## B    COMPARISON WITH A CONTRASTIVE LOSS

To compare SPR with alternative methods drawn from contrastive learning, we examine several variants of a contrastive losses based on InfoNCE (Oord et al., 2018):

- A contrastive loss based solely on different views of the same state, similar to CURL (Srinivas et al., 2020).

- A temporal contrastive loss with both augmentation and where targets are drawn one step in the future, equivalent to single-step CPC (Oord et al., 2018).

- A temporal contrastive loss with an explicit dynamics model, similar to CPC|Action (Guo et al., 2018). Predictions are made up to five steps in the future, and encodings of every state except $s_{t+k}$ are used as negative samples for $s_{t+k}$.

- A soft contrastive approach inspired by Wang & Isola (2020), who propose to decouple the repulsive and attractive effects of contrastive learning into two separate losses, one of which is similar to the SPR objective and encourages representations to be invariant to augmentation or noise, and one of which encourages representations to be uniformly distributed on the unit hypersphere. We optimize this uniformity objective jointly with the SPR loss, which takes the role of the "invariance" objective proposed by (Wang & Isola, 2020). We use $t = 2$ in the uniformity loss, and give it a weight equal to that given to the SPR loss, based on hyperparameters used by Wang & Isola (2020).

To create as fair a comparison as possible, we use the same augmentation (random shifts and intensity) and the same Rainbow hyperparameters as in SPR with augmentation. As in SPR, we calculate contrastive losses using the output of the first layer of the Q-head MLP, with a bilinear classifier (as in Oord et al., 2018). Following Chen et al. (2020a), we use annealed cosine similarities with a temperature of 0.1 in the contrastive loss. We present results in Table 6.

Although all of these variants outperform the previous contrastive result on this task, CURL, none of them substantially improve performance over the controlled Rainbow they use as a baseline. We consider these results broadly consistent with those of CURL, which observes a relatively small performance boost over their baseline, Data-Efficient Rainbow (van Hasselt et al., 2019).

## C    THE ROLE OF THE TARGET ENCODER IN SPR

We consider several variants of SPR with the target network modified, and present aggregate metrics for these experiments in Table 7. We first evaluate a a variant of SPR in which target representations are drawn from the online encoder and gradients allowed to propagate into the online encoder through them, effectively allowing the encoder to learn to make its representations more predictable. We find that this leads to drastic reductions in performance both with and without augmentation, which we attribute to representational collapse.

Table 7: Scores on the 26 Atari games under consideration for variants of SPR with different target encoder schemes, without augmentation.

| Variant Without Augmentation | Human-Normalized Score mean | median | DQN@50M-Normalized Score mean | median |
|---|---|---|---|---|
| SPR | 0.463 | 0.307 | 0.336 | 0.225 |
| No Stopgradient | 0.375 | 0.208 | 0.301 | 0.233 |
| With Augmentation | | | | |
| SPR | 0.704 | 0.415 | 0.510 | 0.361 |
| No Stopgradient | 0.515 | 0.278 | 0.344 | 0.231 |

Figure 4: Performance on a subset of 10 Atari games for different values of the EMA parameter $\tau$ with augmentation (left) and without (right). Scores are averaged across 10 seeds per game for each value of $\tau$. Self-normalized score is calculated separately for the augmentation and no-augmentation cases.

To illustrate the influence of the EMA constant $\tau$, we evaluate $\tau$ at 9 values logarithmically interpolated[4] between $0.999$ and $0$ on a subset of 10 Atari games.[5] We use 10 seeds per game, and evaluate SPR both with and without augmentation; parameters other than $\tau$ are identical to those listed in Table 3. To equalize the importance of games in this analysis, we normalize by the average score across all tested values of $\tau$ for each game to calculate a *self-normalized* score, as $\text{score}_{\text{sns}} \triangleq \frac{\text{agent score}-\text{random score}}{\text{average score}-\text{random score}}$.

We test $SPR$ both with and without augmentation, and calculate the self-normalized score separately between these cases. Results are shown in Figure 4. With augmentation, we observe a clear peak in performance at $\tau = 0$, equivalent to a target encoder with no EMA-based smoothing. Without augmentation, however, the story is less clear, and the method appears less sensitive to $\tau$ (note y-axis scales). We use $\tau = 0.99$ in this case, based on its reasonable performance and consistency with prior work (e.g., Grill et al., 2020). Overall, however, we note that SPR does not appear overly sensitive to $\tau$, unlike purely unsupervised methods such as BYOL; in no case does SPR fail to train.

We hypothesize that the difference between the augmentation and no-augmentation cases is partially due to augmentation rendering the stabilizing effect of using an EMA target network (e.g., as observed by Grill et al., 2020; Tarvainen & Valpola, 2017) redundant. Prior work has already noted that using an EMA target network can slow down learning early in training (Tarvainen & Valpola, 2017); in our context, where a limited number of environment samples are taken in parallel with optimization, this may "waste" environment samples by collecting them with an inferior policy. To resolve this, Tarvainen & Valpola (2017) proposed to increase $\tau$ over the course of training, slowing down changes to the target network later in training. It is possible that doing so here could allow SPR to achieve the best of both worlds, but it would require tuning an additional hyperparameter, the schedule by which $\tau$ is increased, and we thus leave this topic for future work.

---

[4]$\tau \in \{0.999, 0.9976, 0.9944, 0.9867, 0.9684, 0.925, 0.8222, 0.5783, 0\}$.

[5]Pong, Breakout, Up N Down, Kangaroo, Bank Heist, Assault, Boxing, BattleZone, Frostbite and Crazy Climber