Unsupervised Sentence Representation Learning with Syntactically Aligned Negative Samples

Abstract

Sentence representation learning are crucial for various natural language processing tasks. Data augmentation methods are typically employed during the training process to enhance model performance and generalization. However, when using data augmentation methods in existing sentence representation learning methods, challenges such as semantic inconsistencies and feature suppression persist. We propose a novel method for generating syntactically aligned negative samples (SAN) using a semantic importance-aware Masked Language Model (MLM) approach. By assessing the semantic contributions of individual words, we generate negative samples that have substantial textual overlap with the original sentences while conveying different meanings. To integrate them into exist contrastive learning framework, we propose the Hierarchical-InfoNCE loss (HiNCE), which combines both naive and syntactically aligned negative samples, applying different temperatures during training to enhance contrastive learning. Extensive evaluations across seven semantic textual similarity tasks demonstrate significant improvements over state-of-the-art models.

1 Introduction

Sentence embeddings map sentences into fixed-length vectors using machine learning techniques, such as neural networks, making semantically similar sentences be closer in vector space. Sentence representation learning plays a crucial role in various NLP tasks, including information retrieval (Le and Mikolov, 2014), semantic similarity comparison (Pennington et al., 2014), and translation quality evaluation (Zhang et al., 2020). With the rise of pre-trained language models (PLMs), researchers have achieved significant success by employing fine-tuning strategies based on PLMs. Specifically, BERT and its variants, such as RoBERTa (Liu et al., 1907), often use the final layer's [CLS] token to represent sentence vectors. In recent years, with the emergence of large language models like GPT and LLaMA, researchers have started to explore the potential of these models in generating more expressive embedding representations. For example, Wang et al. (2024a) utilize Mistral-7B as an embedding model. However, such methods typically requires substantial computational resources and processing power, while yielding only marginal performance improvements.

In the field of Unsupervised Sentence Representation Learning, model training typically employs either supervised or unsupervised learning approaches. For the semantic textual similarity (STS) task, supervised learning generally outperforms unsupervised methods. For instance, when using RoBERTa$_{large}$ as the base model and trained, supervised SimCSE (Gao et al., 2022) achieved a top score of 83.76 - a score that no unsupervised model has yet surpassed. However, the supervised approach requires extensive manual annotation, which is not scalable. In contrast, unsupervised learning has become the mainstream approach due to the relative ease of acquiring unlabeled data. Nevertheless, due to the limitations in unsupervised data diversity, researchers have focused on developing various data augmentation methods to improve the performance of unsupervised models.

To overcome these challenges and enhance the efficiency of data utilization in unsupervised learning, researchers have proposed various data augmentation methods, such as cutoff, word repetition, random word deletion, noise injection, and dropout noise. However, these methods come with certain limitations. The augmented samples may alter the overall or local semantics of the original samples, potentially causing semantic inconsistencies between the original and augmented data. This, in turn, would result in inconsistent embedding distributions.

In the existing training paradigm of unsupervised

Original Sentences	Syntactically Aligned negative Samples
The first series was confirmed on the 17 August 2017.	The last edition was held on the 20th May 2017.
His wife moved to Australia in 1956 along with a daughter.	They moved to london in 2013, with their son.
His first recording Artiste was the late Ebony Reign.	His first release on record was his first album release.
On Day 20, he was nominated to face the fourth eviction.	On may 20, she was nominated for being the first eviction.

Table 1: Example of syntactically aligned negative samples. Syntactically aligned negative samples share a significant amount of text with the original samples, but their sentence meanings are irrelevant.

contrastive learning, negative samples are derived from other sentences in the same mini-batch which share minimal textual overlap with anchor samples. In such cases, we believe this leads to feature suppression, a concept extensively discussed in the vision domain (Robinson et al., 2021) and explored in the NLP field by SNCSE (Wang et al., 2022). Feature suppression refers to a model's inability to disentangle textual similarity from semantic similarity. This can lead to inflated similarity scores for pairs with substantial lexical overlap, even when their underlying meanings diverge. To alleviate feature suppression, SNCSE introduced soft negative samples, which are constructed by adding negation to the original sentence. However, soft negative samples face a similar yet entirely opposite dilemma: these samples overlap too much with the original sentences at a literal level, differing only in the negation words, while being almost entirely semantically opposed. Such an augmentation method fails to enable the model to discern the subtle semantic variations caused by differences in lexical and grammatical structures. In this scenario, the effectiveness of soft negative samples in mitigating feature suppression is limited.

Is there a way to generate augmented samples that share substantial textual overlap with the original text while conveying distinct semantics? To better address the aforementioned issues, our work aims to explore the following two aspects: First, can we generate augmented samples that effectively capture the diversity, richness, and non-linearity of language concerning textual overlap and semantic relatedness? Second, how can these samples be effectively utilized within a contrastive learning framework? In contrast to existing approaches that employ rule-based methods or large language models for augmentation, we propose a novel sentence augmentation technique based on Masked Language Models (MLMs). This method generates new samples by predicting tokens that have been randomly masked. By controlling the masking ratio and the randomness of predictions, we can generate sentences that exhibit a wider range of diversity.

Specifically, we assess the semantic contribution of different words and use these values to determine the probability of masking them in the MLM task. Unlike previous negative samples, as shown in Table 1, our constructed syntactically aligned negative maintain the original sentence's syntactic structure while altering the content words (such as nouns, verbs, adjectives, and adverbs). We refer to them as isomorphic negative samples.

Syntactically aligned negative samples share substantial textual overlap with the original samples but differ in meaning, making it possible to disentangle textual similarity from semantic similarity in unsupervised contrastive learning.

We conducted a comprehensive evaluation across seven STS tasks, using the representative BERT and RoBERTa models as our backbone. We assessed the performance of our approach against four baselines: SimCSE, SNCSE, RanKCSE (Liu et al., 2023), and RLRD (Wang et al., 2024b). We improved the embedding of state-of-the-art models on all seven STS tasks, achieving superior results. A series of ablation studies further confirmed that our approach successfully disentangles textual similarity from semantic similarity, thereby mitigating feature suppression.

2 Related Work

2.1 Sentence Representation Learning

In the early works of sentence representation learning, sentence vector representations were primarily derived from methods such as Bag of Words, TF-IDF, Word2Vec, and its variants. With the rise of pre-trained language models (PLMs) like BERT (Devlin, 2018), leveraging transformer-based models to obtain sentence embeddings has become the dominant trend. Examples include ConSERT (Yan et al., 2021), SimCSE (Gao et al., 2022), and PromptBERT (Jiang et al., 2022). PLMs typically use the [CLS] token embedding or the output of the pooled representation for sentence embeddings.

(a) The architecture of SAN   (b) An illustration of SAN data augmentation process

Figure 1: (a) The framework applying Semantic Importance-Aware(SIA) MLMing with multiple masking iterations. (b) The process example demonstrates how words are masked based on their semantic contributions, with red indicating the highest probability of masking, followed by yellow, green, and black for decreasing probabilities.

Compared to earlier methods, the quality of sentence vectors obtained from PLMs is significantly improved. Recently, advanced approaches like RankCSE further enhance sentence embeddings by integrating ranking consistency and ranking distillation into a unified contrastive learning framework using teacher models.

2.2 Data Augmentation Methods

The current trend in sentence embeddings primarily relies on pre-trained language models (PLMs) such as BERT and RoBERTa, combined with contrastive learning for training and inference. Originally applied in computer vision, contrastive learning has been adopted in sentence representation learning and has proven to be an effective method. One of the key challenges in contrastive learning is the construction of positive and negative sample pairs. Supervised SimCSE utilizes the NLI (Natural Language Inference) dataset for training, achieving better performance compared to unsupervised methods. However, labeled datasets are often difficult to obtain. Therefore, designing and employing data augmentation methods to construct positive and negative sample pairs and applying unsupervised contrastive learning has become a mainstream approach.

ConSERT (Yan et al., 2021) employs adversarial attacks, token shuffling, truncation, and dropout strategies on the token embedding matrix to create positive samples. SNCSE (Wang et al., 2022) introduces the concept of soft negative samples and designs the Bidirectional Margin Loss (BML)

function, demonstrating better performance than SimCSE on both BERT and RoBERTa. Existing data augmentation methods include word repetition, random word deletion, word shuffling, and cutoff. However, these methods share a common limitation. First, they are primarily applied to construct positive samples, but the randomness introduced by these operations can alter the local or overall semantics of the sentence, resulting in inconsistent semantics. Second, soft negative sentence pairs share a large portion of the text or are even completely identical, which can hinder the model's ability to correctly interpret sentence meaning and impair its capacity to effectively learn sentence representations.

3 Method

3.1 Syntactically Aligned Data Augmentation

In existing contrastive learning approaches for STS, the design of positive and negative sample pairs can lead to feature suppression, where the model overly relies on superficial features—such as sentence length and lexical overlap—while neglecting deeper semantic nuances. This overreliance not only adversely affects the model's generalization ability in complex linguistic tasks but also results in the degradation of the model's representational space, causing inconsistent embedding distribution.

In linguistic, verbs and nouns are often considered the core elements in constructing sentence semantics, while the semantic contributions of modifying words such as adjectives and adverbs are rela-

POS	Score	POS	Score	POS	Score
NOUN	9	VREB	9	ADJ	8
PROPN	8	ADV	7	PRON	7
CCONJ	6	DET	6	ADP	5
CONJ	5	SCONJ	5	AUX	4
NUM	4	PART	3	INTJ	2
PUNCT	1	SYM	1	X	1

Table 2: Human-annotated importance scores indicating the semantic impact of different parts of speech.

tively minor. This perspective is supported by various linguistic theories, including Transformational-Generative Grammar (TGG) and Systemic Functional Grammar (SFG) based on this theoretical foundation, we proposes a method for generating syntactically aligned negative samples by modifying words that contribute significantly to meaning, thus creating syntactically similar pairs with high textual overlap but opposite or irrelevant semantics.

Our study will follow three steps: 1) assessing the magnitude of semantic effects of various parts-of-speech; 2) conducting part-of-speech tagging on the training dataset; 3) replacing words that significantly influence meaning. The initial step involves quantifying the semantic influence of parts of speech, for which "en_core_web_sm" model of spaCy[1] will be utilized as the tagging tool. This approach not only automates the tagging process but also allows for precise quantification of the semantic impact of different parts of speech through manual review.

Related research has shown that nouns and verbs contribute most significantly to the overall semantics of sentences (Pollard and Sag, 1994; Bresnan, 2001; Chomsky, 1957; Matthiessen and Halliday, 2009). Once these parts of speech are removed, the original meaning of the sentence becomes difficult to discern, leading to an assigned importance score of 9 for these categories. In contrast, adjectives, adverbs, and pronouns primarily affect semantic nuances, resulting in scores ranging from 6 to 8. Auxiliary verbs and prepositions play a role in grammatical structure comprehension but have a lesser direct semantic contribution, receiving scores of 3 to 5. Words that are difficult to classify are marked as "X," typically indicating a lower semantic importance. Detailed quantification results are presented in Table 2.

We employ a MLM to perform the token replacement, leveraging its ability to generate suitable re-

---

[1]The model and tool are available at: https://spacy.io and https://huggingface.co/spacy/en_core_web_sm.

placement words based on context, ensuring both semantic consistency and diversity. By masking the target words and feeding them into the MLM, we obtain sentences with appropriate substitutions.

We adopt a static tagging approach by first compiling a lexicon and assigning POS tags to each entry. In subsequent data processing, we assign a masking probability to each word based on its POS and its semantically importance score. Verbs and nouns are assigned the highest masking probabilities, while punctuation and "X" receive the lowest. After masking, the sentence is fed into the MLM to generate replacements. This mask-predict cycle is repeated several times to create syntactically aligned negative samples. Notably, in each iteration, the overall masking probabilities is kept low to avoid distorting the output by masking too many words at once. Through multiple iterations, even with a low masking probabilities per iteration, we are able to generate diverse augmented data (As shown in Figure 1).

Our method performs well on longer sentences; however, it encounters issues when applied to shorter sentences or phrases. In such cases, the process can lead to the replacement of most words with punctuation marks or other meaningless tokens. For instance, the sentence "Stafford acting General Secretary." might be augmented into "-., p." after applying data augmentation, which results in nonsensical token combinations that do not align with the definition of syntactically aligned negative samples and could negatively impact model training.

3.2 Hierarchical-InfoNCE

We first present the mathematical formulation for InfoNCE, as illustrated in Equation 1. In InfoNCE, negative samples are the other examples in the mini-batch excluding the anchor itself, and these negative samples generally share little textual similarity with the anchor. The objective of InfoNCE is to maximize the similarity between the anchor and the positive sample while minimizing the similarity between the anchor and the negative samples.

$$\mathcal{L}_{\text{InfoNCE}} = -\sum_{i=1}^{N} \log \frac{e^{sim(h_i, h_i^+)/\tau}}{\sum_{j=1}^{N} e^{sim(h_i, h_j)/\tau}} \quad (1)$$

where τ is a temperature hyperparameter and $sim(h_1, h_2)$ is the cosine similarity $\frac{h_1^\top h_2}{\|h_1\| \cdot \|h_2\|}$. In this work, we encode input sentences using a pre-

trained language model such as BERT or RoBERTa: $h = f_\theta(x)$, and then fine-tune all the parameters.

Based on the discussion in Section 3.1, the similarity between syntactically aligned negative samples and the anchor should be higher than that between the anchor and traditional negative samples, but lower than the similarity between the anchor and the positive samples. To further optimize this process, we propose adjusting the temperature parameter to influence the model's behavior. By increasing the temperature for syntactically aligned negative samples, we can decouple textual similarity from semantic similarity. This adjustment prevents the model from focusing too much on -syntactically aligned negative samples and neglecting other types of negative samples. While this approach may make the model more sensitive to certain negative samples, it risks reducing its ability to distinguish between others. Therefore, we raise the temperature between anchor and syntactically aligned negative samples, as reflected in our improved HiNCE, shown in Equation 2.

$$L_{\text{HiNCE}} = -\sum_{i=1}^{N} \log \frac{e^{sim(h_i, h_i^+)/\tau_1}}{\sum_{j=0}^{N}(e^{sim(h_i, h_j)/\tau_1} + e^{sim(h_i, h_j^-)/\tau_2})} \quad (2)$$

where τ_1 represents the temperature hyperparameter for the similarity between positive and negative sample pairs, while τ_2 is the temperature for the syntactically aligned negative sample pairs. h_i^- denotes the sentence embedding of the syntactically aligned negative sample produced by the encoder.

3.3 Combination with Other Methods

Syntactically aligned negative samples can be integrated into most existing methods within the same domain using HiNCE or other loss functions. We combine syntactically aligned negative samples with SimCSE (Gao et al., 2022), SNCSE, RanKCSE (Liu et al., 2023), and RLRD (Wang et al., 2024b).

Combination with SimCSE. The unsupervised SimCSE utilizes the standard InfoNCE loss function. To apply our method within the unsupervised SimCSE framework, we replace it with the HiNCE loss function, which is expressed in Equation 3.

$$\mathcal{L}_{\text{SimCSE+SAN}} = \mathcal{L}_{\text{HiNCE}}, \quad (3)$$

Combination with SNCSE. SNCSE constructs soft negative samples through explicit negation and trains using the InfoNCE and BML loss. We replace the InfoNCE loss function with HiNCE while keeping the other components in their original configuration. The final loss function is expressed in Equation 4.

$$\mathcal{L}_{SNCSE+SAN} = \mathcal{L}_{\text{HiNCE}} + \lambda\mathcal{L}_{\text{BML}}. \quad (4)$$

Combination with RankCSE. RankCSE integrates ranking consistency and ranking distillation with contrastive learning into a unified framework by introducing teacher models.

The $\mathcal{L}_{\text{rank}}$ term can take one of two forms: ListMLE (Xia et al., 2008) or ListNet (Cao et al., 2007). We choose ListMLE loss as the baseline for improvement. During the training process, the value of ListMLE loss is usually three orders of magnitude larger than that of InfoNCE loss in. Given the minimal contribution of the InfoNCE loss term within the total RankCSE loss, we apply syntactically aligned negative samples to both HiNCE and ListMLE. ListMLE, a machine learning algorithm for list ranking tasks, optimizes ranking outcomes by maximizing the pairwise ranking probabilities of all items in the list. We replace its inputs with anchor samples and corresponding syntactically aligned negative samples to derive the ListMLE-SAN loss term, as indicated in Equation 5. The final loss function combining RankCSE with our method is presented in Equation 6.

$$\mathcal{L}_{\text{ListMLE-SAN}} = -\sum_{i=1}^{N} \log P(\pi_i^T|S'(x_i), \tau_3), \quad (5)$$

where $S'(x_i) = \{\text{sim}(h_i, h_j^-)/\tau_3\}_{j=1}^{N}$, denoting the similarity list between the anchor samples obtained from the encoder and the embedding vectors of the syntactically aligned negative samples within the current batch. π_i^T represents the sorted indexes of the similarity scores calculated by the teacher model. It is noteworthy that low-quality samples within syntactically aligned negative samples can significantly impact the performance of ListMLE. To address this issue, we introduce a post-processing step where we replace these low-quality samples with soft negative samples from SNCSE. This refinement enhances the overall quality of our training data and mitigates potential performance degradation. $P(\pi|S, \tau)$ is the permutation probability $\prod_{i=1}^{n} \frac{e^{S\pi(i)/\tau}}{\sum_{j=i}^{n} e^{S\pi(j)/\tau}}$.

$$\mathcal{L}_{\text{RankCSE+SAN}} = \beta\mathcal{L}_{\text{consistency}} + \gamma\mathcal{L}_{\text{ListMLE}} + \mathcal{L}_{\text{HiNCE}} + \lambda\mathcal{L}_{\text{ListMLE-SAN}}, \quad (6)$$

Methods	STS12	STS13	STS14	STS15	STS16	STS-B	SICK-R	Avg.
SimCSE-BERT$_{base}$	68.59	82.62	74.60	81.87	78.67	78.06	72.04	76.64
+SAN	70.92	81.77	75.20	82.57	78.88	78.66	71.33	77.05↑
SNCSE-BERT$_{base}$	70.80	84.72	76.81	83.44	79.73	80.82	74.26	78.65
+SAN	71.12	84.48	77.12	83.77	80.68	81.52	**75.24**	79.13↑
RankCSE-BERT$_{base}$	74.89	85.85	77.86	84.82	**81.78**	81.95	73.94	80.16
+SAN	75.34	86.03	78.26	84.72	81.14	81.84	74.97	80.33↑
RLRD-BERT$_{base}$	75.44	86.31	79.15	85.81	81.34	82.91	75.12	80.87
+SAN	**75.68**	**86.38**	**79.47**	**85.93**	81.43	**83.05**	75.15	**81.01↑**
SimCSE-BERT$_{large}$	69.01	80.40	73.50	82.71	77.89	77.18	73.95	76.38
+SAN	70.40	84.68	77.04	84.16	78.86	78.88	75.13	78.45↑
SNCSE-BERT$_{large}$	71.48	86.25	78.12	85.24	80.17	81.84	75.15	79.75
+SAN	72.39	86.50	78.38	85.41	80.45	82.11	75.08	80.05↑
RankCSE-BERT$_{large}$	74.68	86.00	78.59	85.27	80.98	81.15	74.15	80.12
+SAN	74.99	86.04	78.92	85.22	80.38	81.17	74.96	80.24↑
RLRD-BERT$_{large}$	75.47	86.68	79.22	86.13	80.79	**82.62**	75.25	80.88
+SAN	**75.65**	**86.80**	**79.26**	**86.20**	**81.03**	82.46	**75.68**	**81.01↑**
SimCSE-RoBERTa$_{base}$	68.99	81.46	73.53	81.85	81.14	80.52	69.31	76.69
+SAN	69.14	81.54	73.09	81.61	81.97	81.08	70.14	76.94↑
SNCSE-RoBERTa$_{base}$	69.03	83.40	75.56	84.01	80.21	81.31	71.39	77.84
+SAN	70.85	83.90	**76.50**	**84.61**	81.24	82.42	**72.29**	78.83↑
RankCSE-RoBERTa$_{base}$	**73.34**	84.11	75.65	83.97	82.71	**82.89**	70.67	79.05
+SAN	73.25	**84.44**	75.99	84.25	**82.72**	82.68	70.84	**79.17↑**
SimCSE-RoBERTa$_{large}$	71.24	84.07	76.27	84.79	82.14	82.53	71.02	78.87
+SAN	71.62	84.32	75.94	84.68	81.38	82.61	71.75	78.90↑
SNCSE-RoBERTa$_{large}$	72.04	**85.98**	**79.32**	86.39	**82.45**	**83.95**	**76.88**	80.86
+SAN	73.17	85.57	79.22	**86.72**	82.05	83.61	76.83	**81.02↑**
RankCSE-RoBERTa$_{large}$	74.05	84.59	77.14	85.62	81.87	83.20	71.25	79.67
+SAN	**74.32**	84.59	76.86	85.39	82.39	83.19	71.69	79.78↑

Table 3: Main results of various contrastive learning methods on seven semantic textual similarity (STS) datasets. Each method is evaluated on full test sets by Spearman's correlation, "all" setting. Bold marks the best result among all competing methods under the same backbone model.

where β, γ, λ are hyperparameters that control the contribution of each loss component.

Combining with RLRD. The RLRD method enhances RankCSE by incorporating reinforcement learning techniques and additional loss functions, specifically InfoNCE, BML, and ListMLE losses. We replace the InfoNCE with HiNCE and introduce a new loss term, as presented in Equation 7.

$$\mathcal{L}_{\text{RLRD+SAN}} = \mu \mathcal{L}_{\text{BML}} + \lambda \mathcal{L}_{\text{ListMLE}} + \zeta \mathcal{L}_{\text{HiNCE}} + \beta \mathcal{L}_{\text{ListMLE-SAN}}. \quad (7)$$

4 Experiment

4.1 Datasets

We adopt a method similar to SimCSE, randomly selecting 1 million sentences from Wikipedia for unsupervised training. Ultimately, we compute similarity scores for sentence pairs in the STS dataset and calculate Spearman's correlation with human ratings as the final evaluation metric. We evaluate our method on the Semantic Textual Similarity (STS) dataset, which consists of 7 subtasks, including STS12-STS16 (Agirre et al., 2012, 2013, 2014, 2015, 2016), STSbenchmark (STS-B)(Cer et al., 2017), and SICK-Relatedness (SICK-R)(Marelli et al., 2014).

4.2 Implementation Details

We retrained four unsupervised sentence embedding models—SimCSE (Gao et al., 2022), SNCSE (Wang et al., 2022), RanKCSE (Liu et al., 2023), and RLRD (Wang et al., 2024b)—integrating them with our proposed syntactically aligned augmentation approach. We utilized pre-trained models including BERT-base-uncased, BERT-large-uncased, RoBERTa-base, and RoBERTa-large as encoders across all experiments. We employed the Wiki dataset used in SimCSE (Gao et al., 2022) as our self-supervised training dataset. All experiments were conducted on a single A100 40G GPU with mixed precision (fp16) training. We reproduced the results using the original settings from the cor-

responding papers. Additional training details can be found in the Appendix C.

4.3 Main Results

Table 3 presents the results of a single run, showing the performance of our method when integrated with various existing works. As demonstrated, our approach surpasses baseline scores in most cases. Notably, when combined with SimCSE and SNCSE, our method achieves significant improvements over the original methods. Specifically, the average Spearman's correlation coefficient for SimCSE-BERT$_{base}$ increased from 76.64 to 77.05, while for SNCSE-BERT$_{large}$, it rose from 78.65 to 79.75. Additionally, when applied to RankCSE, our method yielded even more pronounced results, with the average Spearman's correlation coefficient for RankCSE-BERT$_{base}$ improving from 80.16 to 80.33, and for RankCSE-BERT$_{large}$, from 80.12 to 80.24. Among methods utilizing BERT$_{base}$, the combination with RLRD achieved the highest result of 81.01. These confirm that integrating our method with existing approaches stably improves the quality of sentence representation.

4.4 Downstream Tasks

To assess the generalization capability of our method, we conducted extensive experiments across multiple task types: reranking, retrieval, and classification. For classification task, we evaluated our method on ten diverse tasks:: AmazonCounterfactual (O'Neill et al., 2021), AmazonReviews (Keung et al., 2020), Banking77 (Casanueva et al., 2020), Emotion (Saravia et al., 2018), MassiveIntent (FitzGerald et al., 2022), MassiveScenario (FitzGerald et al., 2022), MTOPDomain (Li et al., 2021), MTOPIntent (Li et al., 2021), ToxicConversations (cjadams, 2019) and TweetSentimentExtraction (Maggie, 2020). We report the classification accuracy as the main metric. We further evaluated our method on four reranking and retrieval tasks: AskUbuntuDupQuestions (Lei et al., 2016), MindSmallReranking (Wu et al., 2020), SciDocsRR (Cohan et al., 2020), StackOverflowDupQuestions (Liu et al., 2018) and QuoraRetrieval (Thakur et al., 2021). We report the mean MRR@1 and MAP@1 as the main results. As shown in Figure 2, both SimCSE+SAN and RankCSE+SAN outperformed their corresponding baseline models in reranking and retrieval tasks, with RankCSE+SAN achieving the highest scores in both tasks. Additionally, we assessed our method's performance on

Model	Avg. Classification Accuracy
SimCSE	0.6068
+SAN	0.6113↑
SNCSE	0.6170
+SAN	0.6106
RankCSE	0.6169
+SAN	**0.6290↑**
RLRD	0.6145
+SAN	0.6072

Table 4: Evaluation performance on classification tasks. The bold font indicates the highest score, while the underlined font represents the second highest score.

Figure 2: Absolute performance difference on reranking and retrieval tasks compared to SimCSE.

sentence-level classification tasks, with Table 4 presenting the average accuracy across ten sentence-level classification tasks. The results indicate that our method enhances the performance of certain baseline models on these tasks.

5 Ablation Study

5.1 Influence of Hyperparameters in HiNCE Loss

The performance of HiNCE is influenced by two hyperparameters: the dropout probabilities for syntactically aligned negative samples and the temperature hyperparameter associated with the similarity of anchor samples and syntactically aligned negative embeddings. This section examines the effects of these parameters on model performance. The dropout probabilities for syntactically aligned negative samples were adjusted within the range of [0.1, 0.15, 0.2], while the temperature hyperparameter was varied between [0.05, 0.075, 0.1].

As show in Figure 3, when the dropout probabilities remains constant, model performance improves with increasing values of τ_2. Notably, when $\tau_2 = 0.1$, models with different dropout probabil-

Figure 3: Influence of hyperparameters of HiNCE loss. τ_2 is the temperature hyperparameter corresponding to the similarity of sentence embeddings for anchor samples and syntactically aligned negative samples. p is the dropout probabilities of the model for syntactically aligned negative negative samples.

ities exhibit relatively high and consistent performance. These findings indicate that the temperature hyperparameter τ_2 is a critical factor, and its selection is essential for optimizing model performance. In contrast, while the dropout probabilities does impact performance to some extent, the variation is not as pronounced.

5.2 Alleviation of Feature Suppression

To conduct a more comprehensive analysis of our method's impact on feature suppression, we selected 1,900 sentence pairs from the STS task dataset that have a similarity score of at least 4 and a lexical overlap ratio of less than 0.6. These sentence pairs, while exhibiting low textual similarity, possess high semantic similarity, making them challenging for discrimination.

As illustrated in Figure 4, both SimCSE+SAN and SimCSE peak around 0.9; however, the distribution of SimCSE+SAN is more concentrated near this value. In contrast, SimCSE exhibits greater variability in its similarity estimates across a wider range of sentence pairs. This indicates that our method achieves more consistent similarity assessments for challenging cases.

6 Conclusion

In this paper, we propose a method that leverages the semantic impact of different parts of speech to generate syntactically aligned negative samples using MLM. We also proposed HiNCE loss, which

Figure 4: Cosine similarity distribution on different pairs.

utilizes these syntactically aligned negative samples to improve sentence embedding performance. Furthermore, our methods demonstrate improved performance when combined with other existing methods.

We evaluate our method across multiple tasks, including semantic textual similarity, re-ranking, retrieval, and classification, showcasing its excellent performance and generalization capability. Additionally, we conduct detailed ablation studies to justify the inner workings of syntactically aligned negative samples and HiNCE, as well as their impact on the model.

7 Limitations

The limitations of our research are as follows. First, we manually assigned semantic impact values to different parts of speech, but further exploration and refinement of these values are warranted. Second, during training, our model's input size increased by 0.5x compared to previous methods, leading to longer training times. Third, our current use of syntactically aligned negative samples is limited to HiNCE and ListMLE, without broader application to other loss functions. Finally, all experiments utilized only English datasets, and no testing was done on datasets in other languages.

Additionally, it is important to acknowledge potential risks associated with STS technology. These include privacy concerns related to the analysis of personal text data, the possibility of unintended bias if training data contains prejudices, and potential misuse for generating misleading content or manipulating social media algorithms.

In future work, we aim to explore improved

methods for determining semantic importance scores, including training customized models and designing more effective algorithms and extend the application of syntactically aligned negative samples.

References

Eneko Agirre, Carmen Banea, Claire Cardie, Daniel Cer, Mona Diab, Aitor Gonzalez-Agirre, Weiwei Guo, Inigo Lopez-Gazpio, Montse Maritxalar, Rada Mihalcea, et al. 2015. Semeval-2015 task 2: Semantic textual similarity, english, spanish and pilot on interpretability. In *Proceedings of the 9th international workshop on semantic evaluation (SemEval 2015)*, pages 252–263.

Eneko Agirre, Carmen Banea, Claire Cardie, Daniel Cer, Mona Diab, Aitor Gonzalez-Agirre, Weiwei Guo, Rada Mihalcea, German Rigau, and Janyce Wiebe. 2014. Semeval-2014 task 10: Multilingual semantic textual similarity. In *Proceedings of the 8th international workshop on semantic evaluation (SemEval 2014)*, pages 81–91.

Eneko Agirre, Carmen Banea, Daniel Cer, Mona Diab, Aitor Gonzalez Agirre, Rada Mihalcea, German Rigau Claramunt, and Janyce Wiebe. 2016. Semeval-2016 task 1: Semantic textual similarity, monolingual and cross-lingual evaluation. In *SemEval-2016. 10th International Workshop on Semantic Evaluation; 2016 Jun 16-17; San Diego, CA. Stroudsburg (PA): ACL; 2016. p. 497-511*. ACL (Association for Computational Linguistics).

Eneko Agirre, Daniel Cer, Mona Diab, and Aitor Gonzalez-Agirre. 2012. Semeval-2012 task 6: A pilot on semantic textual similarity. in* sem 2012: The first joint conference on lexical and computational semantics–volume 1: Proceedings of the main conference and the shared task, and volume 2: Proceedings of the sixth international workshop on semantic evaluation (semeval 2012). *Association for Computational Linguistics. URL http://www. aclweb. org/anthology/S12-1051*.

Eneko Agirre, Daniel Cer, Mona Diab, Aitor Gonzalez-Agirre, and Weiwei Guo. 2013. * sem 2013 shared task: Semantic textual similarity. In *Second joint conference on lexical and computational semantics (* SEM), volume 1: proceedings of the Main conference and the shared task: semantic textual similarity*, pages 32–43.

Joan Bresnan. 2001. *Lexical-Functional Syntax*. Blackwell Publishers, Oxford, UK.

Zhe Cao, Tao Qin, Tie-Yan Liu, Ming-Feng Tsai, and Hang Li. 2007. Learning to rank: from pairwise approach to listwise approach. In *Proceedings of the 24th International Conference on Machine Learning*, ICML '07, page 129–136, New York, NY, USA. Association for Computing Machinery.

Iñigo Casanueva, Tadas Temčinas, Daniela Gerz, Matthew Henderson, and Ivan Vulić. 2020. Efficient intent detection with dual sentence encoders. In *Proceedings of the 2nd Workshop on Natural Language Processing for Conversational AI*, pages 38–45, Online. Association for Computational Linguistics.

Daniel Cer, Mona Diab, Eneko Agirre, Inigo Lopez-Gazpio, and Lucia Specia. 2017. Semeval-2017 task 1: Semantic textual similarity-multilingual and cross-lingual focused evaluation. *arXiv preprint arXiv:1708.00055*.

Noam Chomsky. 1957. *Syntactic Structures*. Mouton, The Hague.

inversion Jeffrey Sorensen Lucas Dixon Lucy Vasserman nithum cjadams, Daniel Borkan. 2019. Jigsaw unintended bias in toxicity classification.

Arman Cohan, Sergey Feldman, Iz Beltagy, Doug Downey, and Daniel S. Weld. 2020. Specter: Document-level representation learning using citation-informed transformers. In *ACL*.

Jacob Devlin. 2018. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*.

Jack FitzGerald, Christopher Hench, Charith Peris, Scott Mackie, Kay Rottmann, Ana Sanchez, Aaron Nash, Liam Urbach, Vishesh Kakarala, Richa Singh, Swetha Ranganath, Laurie Crist, Misha Britan, Wouter Leeuwis, Gokhan Tur, and Prem Natarajan. 2022. Massive: A 1m-example multilingual natural language understanding dataset with 51 typologically-diverse languages. *Preprint*, arXiv:2204.08582.

Tianyu Gao, Xingcheng Yao, and Danqi Chen. 2022. Simcse: Simple contrastive learning of sentence embeddings. *Preprint*, arXiv:2104.08821.

Ting Jiang, Jian Jiao, Shaohan Huang, Zihan Zhang, Deqing Wang, Fuzhen Zhuang, Furu Wei, Haizhen Huang, Denvy Deng, and Qi Zhang. 2022. Promptbert: Improving bert sentence embeddings with prompts. *arXiv preprint arXiv:2201.04337*.

Phillip Keung, Yichao Lu, György Szarvas, and Noah A. Smith. 2020. The multilingual Amazon reviews corpus. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 4563–4568, Online. Association for Computational Linguistics.

Quoc Le and Tomas Mikolov. 2014. Distributed representations of sentences and documents. In *Proceedings of the 31st International Conference on Machine Learning*, volume 32 of *Proceedings of Machine Learning Research*, pages 1188–1196, Bejing, China. PMLR.

Tao Lei, Hrishikesh Joshi, Regina Barzilay, Tommi Jaakkola, Kateryna Tymoshenko, Alessandro Moschitti, and Lluís Màrquez. 2016. Semi-supervised

question retrieval with gated convolutions. In *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 1279–1289, San Diego, California. Association for Computational Linguistics.

Haoran Li, Abhinav Arora, Shuohui Chen, Anchit Gupta, Sonal Gupta, and Yashar Mehdad. 2021. MTOP: A comprehensive multilingual task-oriented semantic parsing benchmark. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pages 2950–2962, Online. Association for Computational Linguistics.

Jiduan Liu, Jiahao Liu, Qifan Wang, Jingang Wang, Wei Wu, Yunsen Xian, Dongyan Zhao, Kai Chen, and Rui Yan. 2023. Rankcse: Unsupervised sentence representations learning via learning to rank. *Preprint*, arXiv:2305.16726.

Xueqing Liu, Chi Wang, Yue Leng, and ChengXiang Zhai. 2018. Linkso: a dataset for learning to retrieve similar question answer pairs on software development forums. In *Proceedings of the 4th ACM SIGSOFT International Workshop on NLP for Software Engineering*, pages 2–5.

Y Liu, M Ott, N Goyal, J Du, M Joshi, D Chen, O Levy, M Lewis, L Zettlemoyer, and V Stoyanov. 1907. Roberta: A robustly optimized bert pretraining approach. arxiv [preprint](2019). *arXiv preprint arXiv:1907.11692*.

Wei Chen Maggie, Phil Culliton. 2020. Tweet sentiment extraction.

Marco Marelli, Stefano Menini, Marco Baroni, Luisa Bentivogli, Raffaella Bernardi, and Roberto Zamparelli. 2014. A SICK cure for the evaluation of compositional distributional semantic models. In *Proceedings of the Ninth International Conference on Language Resources and Evaluation (LREC'14)*, pages 216–223, Reykjavik, Iceland. European Language Resources Association (ELRA).

Christian MIM Matthiessen and Michael Alexander Kirkwood Halliday. 2009. Systemic functional grammar: A first step into the theory.

James O'Neill, Polina Rozenshtein, Ryuichi Kiryo, Motoko Kubota, and Danushka Bollegala. 2021. I wish I would have loved this one, but I didn't – a multilingual dataset for counterfactual detection in product review. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 7092–7108, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Jeffrey Pennington, Richard Socher, and Christopher Manning. 2014. GloVe: Global vectors for word representation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 1532–1543, Doha, Qatar. Association for Computational Linguistics.

Carl Pollard and Ivan A. Sag. 1994. *Head-Driven Phrase Structure Grammar*. The University of Chicago Press, Chicago.

Joshua Robinson, Li Sun, Ke Yu, Kayhan Batmanghelich, Stefanie Jegelka, and Suvrit Sra. 2021. Can contrastive learning avoid shortcut solutions? In *Advances in Neural Information Processing Systems*, volume 34, pages 4974–4986. Curran Associates, Inc.

Elvis Saravia, Hsien-Chi Toby Liu, Yen-Hao Huang, Junlin Wu, and Yi-Shin Chen. 2018. CARER: Contextualized affect representations for emotion recognition. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 3687–3697, Brussels, Belgium. Association for Computational Linguistics.

Nandan Thakur, Nils Reimers, Andreas Rücklé, Abhishek Srivastava, and Iryna Gurevych. 2021. BEIR: A heterogeneous benchmark for zero-shot evaluation of information retrieval models. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 2)*.

Hao Wang, Yangguang Li, Zhen Huang, Yong Dou, Lingpeng Kong, and Jing Shao. 2022. Sncse: Contrastive learning for unsupervised sentence embedding with soft negative samples. *Preprint*, arXiv:2201.05979.

Liang Wang, Nan Yang, Xiaolong Huang, Linjun Yang, Rangan Majumder, and Furu Wei. 2024a. Improving text embeddings with large language models. *Preprint*, arXiv:2401.00368.

Xintao Wang, Rize Jin, and Shibo Qi. 2024b. Reinforced multi-teacher knowledge distillation for unsupervised sentence representation. In *Artificial Neural Networks and Machine Learning – ICANN 2024*, pages 320–332, Cham. Springer Nature Switzerland.

Fangzhao Wu, Ying Qiao, Jiun-Hung Chen, Chuhan Wu, Tao Qi, Jianxun Lian, Danyang Liu, Xing Xie, Jianfeng Gao, Winnie Wu, and Ming Zhou. 2020. MIND: A large-scale dataset for news recommendation. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 3597–3606, Online. Association for Computational Linguistics.

Fen Xia, Tie-Yan Liu, Jue Wang, Wensheng Zhang, and Hang Li. 2008. Listwise approach to learning to rank: theory and algorithm. In *Proceedings of the 25th International Conference on Machine Learning*, ICML '08, page 1192–1199, New York, NY, USA. Association for Computing Machinery.

Yuanmeng Yan, Rumei Li, Sirui Wang, Fuzheng Zhang, Wei Wu, and Weiran Xu. 2021. Consert: A contrastive framework for self-supervised sentence representation transfer. *Preprint*, arXiv:2105.11741.

Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q. Weinberger, and Yoav Artzi. 2020. Bertscore:

Evaluating text generation with bert. *Preprint*, arXiv:1904.09675.

A Static tagging and dynamic tagging

In Section 3.1, the POS tagging methods consists of two approaches: dynamic tagging and static tagging. Dynamic tagging refers to inputting each sample from the corpus into spaCy for POS tagging. Static tagging pre-tags all vocabulary using a predefined dictionary and then tags the corpus based on a mapping table of vocabulary and their corresponding tags. The POS for each vocabulary is taken as the first output from spaCy. While dynamic tagging provides higher accuracy, it requires longer processing times. To balance accuracy and efficiency, we used the vocabulary from $BERT_{base}$ as our predefined dictionary and employed static tagging during the experimental procedure.

B Comparison with Existing Methods

We compared the performance of various methods using $BERT_{base}$ as the backbone network, as shown in Table 6, with all results derived from the original papers. Our method enhances the performance of SimCSE, SNCSE, and RLRD upon integration. For RankCSE, our method yielded a score of 80.33, which is higher than the reproduced result of 80.16 but lower than the original paper's result of 80.36. This discrepancy may be attributed to the fact that RankCSE has not released its code; we conducted our experiments using a community implementation of RankCSE, where differences in code details and hyperparameters may have contributed to this issue.

C Hyperparameters of SAN

We re-trained four previous unsupervised sentence embedding methods on STS tasks – SimCSE, SNCSE, RankCSE and RLRD – with our novel method, SAN. All embedding training models used $BERT_{base}$(110M), $BERT_{large}$(340M), $RoBERTa_{rmbase}$ (350M) or $RoBERTa_{large}$(110M) as a starting checkpoint. We replicated the results using the original settings from the corresponding papers, adjusting only the relevant parameters for the additional loss terms in the experiments that combined our method as shown in Table 5. We carry out grid-search of $\tau_2 \in \{0.05, 0.08, 0.1\}$, $p \in \{0.1, 0.15, 0.2, 0.25\}$ and the weight of $\mathcal{L}_{ListMLE-SAN} \in \{0.1, 0.15, 0.2\}$. Where τ_2 is

	$BERT_{base}$			
	SimCSE +SAN	SNCSE +SAN	RankCSE +SAN	RLRD +SAN
τ_2	0.05	0.05	0.05	0.05
p	0.2	0.2	0.2	0.2
$\mathcal{L}_{HiNCE}$	y	y	y	y
post-processing	-	-	y	y
$\mathcal{L}_{ListMLE-SAN}$	-	-	0.2	0.2

Table 5: Hyperparameters of SAN.

the temperature for the syntactically aligned negative sample pairs. p_2 is the dropout probabilities of the model for syntactically aligned negative samples. post-processing is lower-quality samples in the SAN set are replaced with soft negative samples generated from SNCSE. $\mathcal{L}_{ListMLE-SAN}$ is The ListMLE loss function using the similarity list of anchor samples and SAN as input. Following Gao et al. (2022), we used the validation performance on STS-B (one of the seven STS benchmark datasets) to select the best models.

D Computational Cost

All experiments were conducted on a single A100 (40GB) GPU, utilizing the same initialization, with all baseline models employing the same default random seed. $BERT_{base}$ was used as the MLM to generate SAN, with an average training time of approximately 2.5 hours. Upon incorporating our method, the training times for all baseline models increased. For instance, according to the data presented in Table 7, the average training minutes with our method was found to be 25% longer than that of the baseline models. This increase can primarily be attributed to the additional SAN introduced by our approach, which consequently led to longer training time.

E Case Study

We present several examples from the STS dataset with their similarity scores in Table 8, where the similarity scores of the sentence pairs exceed 4.8 (with a maximum score of 5) and the lexical overlap is below 0.6. These indicate that, after incorporating our method, SimCSE generates more effective similarity scores that are closer to the true values. This further demonstrates that while SimCSE primarily captures high-level semantic information through contrastive learning, our approach enhances its ability to capture low-level semantic details.

Methods	STS12	STS13	STS14	STS15	STS16	STS-B	SICK-R	Avg.
ConSERT	64.64	78.49	69.07	79.72	75.95	73.97	67.31	72.74
SimCSE	68.40	82.41	74.38	80.91	78.56	76.85	72.23	76.25
SAN-SimCSE	70.92	81.77	75.20	82.57	78.88	78.66	71.33	77.05
PromptBERT	71.56	84.58	76.98	84.47	80.60	81.60	69.87	78.54
SNCSE	70.67	84.79	76.99	83.69	80.51	81.35	74.77	78.97
SAN-SNCSE	71.12	84.48	77.12	83.77	80.68	81.52	**75.24**	79.13
SAN-RankCSE	75.34	86.03	78.26	84.72	81.14	81.84	74.97	80.33
RankCSE	75.66	86.27	77.81	84.74	81.10	81.80	75.13	80.36
RLRD	**75.84**	86.28	79.22	85.80	**81.43**	82.90	74.79	80.89
SAN-RLRD	75.68	**86.38**	**79.47**	**85.93**	81.43	**83.05**	75.15	**81.01**

Table 6: Sentence embedding performance on STS tasks (Spearman's correlation, "all" setting). We highlight the highest numbers among models with the same pre-trained encoder.

	SimCSE		SNCSE		RankCSE		RLRD	
	Baseline	+SAN	Baseline	+SAN	Baseline	+SAN	Baseline	+SAN
Epochs	1	1	1	1	1	1	4	4
Time	50min	63min	75min	99min	127min	143min	673min	793min
Time per epoch	50min	63min	75min	99min	127min	143min	168min	198min

Table 7: Training minutes for different models on BERT$_{base}$. Baseline denotes the training minutes of a method without adding any additional methods or components.

Sentence1	Sentence2	Label	SimCSE	SimCSE+SAN
ahmadinejad is embarking on an adventure ; bernanke is not.	ahmadinejad board in an adventure, not bernanke	5	0.7689	0.9200
The motocross rider is wearing blue and black pants	Blue and black pants are being worn by the motocross rider	5	0.7856	0.9096
bulb a and b are still contained within closed paths	bulbs a and b are in a closed path	5	0.7855	0.9003
the european union has got to do something and do it quickly.	the european union must be involved and do so quickly.	4.8	0.7967	0.9007
iran, atomic agency in first talks since rowhani election	iaea, iran to hold first nuclear talks since rohani election	4.8	0.7967	0.9007
Broccoli are being cut by a woman	A woman is cutting broccoli	4.8	0.8218	0.9220

Table 8: Examples from the STS dataset with their similarity scores. The label scores are from human annotations. The SimCSE and SimCSE+SAN similarity scores are from the model predictions respectively. It can be seen that our method generates more accurate similarity scores than SimCSE.

F Scientific Artifacts and Licensing

In this study, we utilized several scientific artifacts, including pre-trained language models, datasets, and related code. We employed BERT (Apache License 2.0) and RoBERTa (MIT License) as our foundational models, citing their original papers. Our data was sourced from SimCSE (MIT License), and we adhered to its licensing terms in our usage. Additionally, we incorporated open-source code and pre-trained models from SNCSE and RLRD, whose upstream repositories are also licensed under the MIT License. RankCSE (MIT License) was also utilized in our research. We ensured that our use of all these artifacts aligned with their original intentions and licensing conditions. Regarding the artifacts we created, we plan to release them under the MIT License to promote open sharing and further research within the scientific community.