Comparison of Uncertainty Quantification in Time Series Regression

Abstract

Increasingly high-stakes decisions are made using neural networks in order to make predictions. Specifically, meteorologists and hedge funds apply these techniques to time series data. When it comes to prediction, there are certain limitations for machine learning models (such as lack of expressiveness, vulnerability of domain shifts and overconfidence) which can be solved using uncertainty estimation. There is a set of expectations regarding how uncertainty should "behave". For instance, a wider prediction horizon should lead to more uncertainty or the model's confidence should be proportional to its accuracy. In this paper, different uncertainty estimation methods are compared to forecast meteorological time series data and evaluate these expectations. The results show how each uncertainty estimation method performs on the forecasting task, which partially evaluates the robustness of predicted uncertainty.

1 Introduction

Neural networks are often used to tackle complex tasks in fields such as robotics [14], computer vision [15], stock market/weather prediction [13], etc. Specifically, time series data with high volatility, rely heavily on neural networks when it comes to predicting future values. Nowadays many application specialists use AI for different applications that need robust predictions. Time series data is very important for some applications involving streaming or time varying data, such as sequences, weather or environmental variable predictions, and price modeling. These applications also require uncertainty quantification at the output for robust decision making [12].

However, there are still plenty of limitations that need to be taken into account. The most prominent issues described by [7] are: "black boxes" which suggests the lack of expressiveness and interpretability of the algorithm, vulnerability to domain shifts and struggle with identifying in-domain and out-of-domain data. This means that, for example, if an image classification model is trained to distinguish between cars and bikes, but during the testing a plane is given, the model will predict something instead of noticing the out-of-domain data. Neural network outputs do not provide uncertainty (how sure the given output is) and often make overconfident predictions, and are prone to adversarial attacks, which could cause them to malfunction.

The aforementioned limitations can be improved by estimating output uncertainty [5]. Given these estimates, a human supervisor could decide whether to use the network output (at least parts of the results) or disregard them. In particular time series data impose additional constraints on how predictive uncertainty can be interpreted, for example, it is expected that uncertainty increases with the prediction horizon [9]. The far future is harder to predict than the near future. Since all uncertainty methods are approximations of the true posterior distribution, this behavior is not ensured. This can be seen as a robustness concept applied to the uncertain predictions specifically for time series data.

Submitted to Workshop on Robustness in Sequence Modeling at the 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

In this paper, we make a comparison of uncertainty quantification methods for time series regression using multiple metrics measuring different effects, across two datasets of environmental and weather data. The contributions of this work are the comparison of uncertainty quantification methods for time series data, including a feed forward multi-layer perceptron (MLP) and a Long-Short Term Memory recurrent network (LSTM), a qualitative evaluation methodology that includes prediction horizon quality, a ranking of the evaluated methods, calibration error, and mean squared error. Our results provide insights that go beyond standard evaluation of time series methods with uncertainty.

2 Experimental Setup

Datasets. We used two weather and environmental/meteorology data sets.

PM 2.5 dataset Prediction is made with regard to PM2.5 concentration. This is also called fine particulate matter, which has a harmful effect on human health [11]. The dataset can be found at https://archive.ics.uci.edu/ml/datasets/Beijing+PM2.5+Data. This dataset consists of 43825 time series with 8 features measured for each time frame (year, month, day and hour). The 8 features are the following: PM2.5 concentration, Dew Point, Temperature, Pressure, Combined wind direction, Cumulated wind speed, Cumulated hours of snow, and Cumulated hours of rain.

Air Pressure dataset This is a weather time series data (it is referred to as **Air pressure data set**). This data set can be downloaded at https://www.bgc-jena.mpg.de/wetter/. In this data set, 14 different features were included: Air pressure, Air temperature, Potential temperature, Dew point temperature, Relative humidity, Saturation water vapor pressure, Actual water vapor pressure, Water vapor pressure, Deficit specific humidity, Water vapor concentration, Air density, Wind velocity, Maximum wind velocity and Wind direction. The data points are measured in every 10 minutes from 2009-2016. Since prediction regarding meteorological data is usually done by hours and the previous data set was also measured in each hour, the data set was converted from minute representation to hour representation by taking every 6^{th} data point only.

Both datasets have the same pre-processing, transforming to a time series with 12 past timesteps, to predict a single future timestep. To evaluate prediction horizon, we train models with up to 12 future timesteps.

Uncertainty Quantification Methods. We compare multiple methods, namely a baseline model with only aleatoric uncertainty using the Gaussian NLL loss (Equation 1), MC-Dropout [3], MC-DropConnect [10], Flipout [16], Bayes by Backpropagation (BBB) [2], and Ensembles [1].

Models. We use two models. One is an MLP with two hidden Dense layers with 32 neurons using the ReLU activation, and a single output layer with one neuron. The second model similar but replacing all Dense layers with LSTM [6], producing a recurrent architecture. To combine models with specific uncertainty quantification methods, all Dense layers are replaced with corresponding uncertainty layers (Dense with DropConnectDense, or FlipoutDense, VariationalDense, etc), except for the LSTM layers, which are standard LSTM layers since there are no variations of LSTM with uncertainty.

Training. Loss function is the mean squared error. The Adam optimizer was used for training with a learning rate of 0.001. The number of training epochs was set to 100. Each model is combined with an uncertainty quantification method, which produces mean $\mu(x)$ and standard deviation $\sigma(x)$ predictions for input x. The $\sigma(x)$ is the uncertainty value associated with the prediction.

Metrics. We used multiple metrics to evaluate different aspects of prediction quality. Mean absolute percentage error (MAPE) for direct prediction error, Mean squared error (MSE) for a global error metric, R^2 score for overall prediction quality, expected calibration error (ECE) for quality of the uncertainty output [4], and negative-log likelihood (NLL) for an overall combination of error and uncertainty outputs [8]. We evaluate these metrics for a single output step, and for 12 output steps.

The Gaussian Negative Log-likelihood is used as a metric for all models, and as a loss for the baseline model. This loss only estimates aleatoric uncertainty, and is presented in Equation 1

$$\text{NLL} = N^{-1} \sum_{i=1}^{N} \left(\log(\sigma_i^2) + \frac{(\mu_i - y_i)^2}{\sigma_i^2} \right) \tag{1}$$

Models/Metrics	MAPE ↓	MSE ↓	R^2 ↑	Calibration error ↓	NLL ↓
Baseline	51.85	0.45	0.56	0.21	5.57
Ensemble	**45.29**	**0.36**	**0.65**	**0.20**	**1.86**
Dropout	46.99	0.38	0.62	0.26	4.38
Dropconnect	59.14	0.52	0.49	0.25	5.52
BBB	47.00	0.37	0.64	0.37	29.71
Flipout	50.14	0.43	0.57	0.35	17.84

Table 1: Metrics scores of each model (PM2.5).

Models/Metrics	MAPE ↓	MSE ↓	R^2 ↑	Calibration error ↓	NLL ↓
Baseline (lstm)	50.16	0.46	0.55	0.28	8.04
Ensemble (lstm)	**43.13**	**0.34**	**0.67**	**0.17**	**1.61**
Dropout (lstm)	48.21	0.41	0.60	0.29	8.59
Dropconnect (lstm)	44.78	0.36	0.65	0.17	4.33
BBB (lstm)	92.48	1.15	-0.11	0.42	102.71
Flipout (lstm)	50.14	0.41	0.59	0.34	13.85

Table 2: Metrics scores of each model with recurrent layer (PM2.5).

Where N is the number of data points, μ_i is the predicted mean, σ_i^2 is the prediction variance, and y_i is the ground truth label.

Plotting metrics against the prediction horizon entails some expectations as the prediction horizon is longer (more timesteps into the future). Mean squared error, Mean absolute percentage error should increase with longer horizons, while the R^2 score should decrease. The calibration error should stay approximately constant, as increasing uncertainty should signal increasing error in the predictions, and NLL should stay approximately constant as this metric also considers uncertainty in its predictions.

3 Experimental Results

Our main numerical results are presented here. Tables 1 and 2 present results for the PM2.5 dataset, while tables 3 and 4 correspond to the Air Pressure dataset.

For PM2.5 MLP models, ensembles performed the best according to all metrics. Flipout and Baseline models were the worst fit for the data, but the scores were rather similar, there were no outliers. Flipout and BBB performed worse in uncertainty related metrics (CE and NLL) compared to other models. For the LSTM model, results are similar as the best algorithm is still the ensemble model but DropConnect performs much better. BBB performed extremely poorly, with a negative R2 score and an MSE larger than 1. Overall for both kinds of models, BBB predicts very poor uncertainty. Among all the models, Ensemble performed the best, with a slight margin ahead of Dropout or Dropconnect depending on the recurrent layers. Both the standard and recurrent versions of these models outperformed the other estimation methods.

For Air Pressure models, the results differ considerably from the PM2.5 dataset. before. For the MLP, the best model predictive model was Dropout. As before, Ensembles was the best in predicting uncertainty, since it produced the lowest NLL score and calibration error. Interestingly, the Baseline model was the best calibrated in a tie with Ensemble, which means that they were the least overconfident amongst the models. Among LSTM models, the best is again Ensembles, Dropconnect performed significantly better with LSTM. Both Flipout and BBB have really low performance both in predicting the true mean and the standard deviation. Note that BBB had really low calibration error compared to the previous cases.

In general, the models performed worse with the Air pressure than with the PM2.5 dataset. It is also worth mentioning that the Baseline model performed relatively well in all settings, especially with CE and NLL scores. Overall the best model for uncertainty was Ensemble however, in some cases, Dropout or Dropconnect outperformed it. An important detail that is often overlooked, is that our results show that a recurrent model (LSTM in this case) is not always the best model for prediction of time series data, an MLP can outperform LSTM, we see this in MLP Dropout on the Air pressure

Models/Metrics	MAPE ↓	MSE ↓	R^2 ↑	Calibration error ↓	NLL ↓
Baseline	57.19	0.53	0.36	0.18	2.62
Ensemble	51.37	0.42	0.49	**0.18**	**1.32**
Dropout	**50.18**	**0.40**	**0.51**	0.26	3.07
Dropconnect	64.17	0.62	0.25	0.30	18.84
BBB	57.56	0.65	0.21	0.38	38.70
Flipout	63.25	0.69	0.17	0.40	36.16

Table 3: Metrics scores of each model (Air pressure).

Models/Metrics	MAPE ↓	MSE ↓	R^2 ↑	Calibration error ↓	NLL ↓
Baseline (lstm)	62.31	0.62	0.25	0.29	6.70
Ensemble (lstm)	**53.26**	**0.46**	**0.45**	**0.17**	**1.56**
Dropout (lstm)	59.34	0.57	0.32	0.34	10.51
Dropconnect (lstm)	54.96	0.48	0.42	0.25	4.04
BBB (lstm)	101.22	2.18	-1.60	0.23	196.70
Flipout (lstm)	75.99	2.54	-2.04	0.43	96.60

Table 4: Metrics scores of each model with recurrent layer (Air pressure).

dataset. There are also interactions between quality of predicted uncertainty with LSTM, calibration error or NLL can increase or decrease, there is no general pattern.

We also provide a qualitative evaluation of prediction results, presented in Tables 5 and 6. The details of how these tables are made is provided in the appendix. These tables provide a ranking of uncertainty quantification methods across both datasets and model variations. Overall we find that the baseline model, ensembles, and dropout, are the best uncertainty quantification methods overall across MLP and LSTM models.

Metrics across prediction horizon are presented in Figures 3 to 6. These results are also analyzed in the qualitative results (Sec A). Overall the results are mixed, some model/uncertainty method combinations do meet the expectations, such as PM2.5 MLP Dropout, and Air Pressure LSTM Dropout. Overall our results in this category show that performing time series regression with uncertainty is far from trivial and many assumptions usual in sequence data can be broken.

Qualitative evaluation of the prediction horizon quality and confidence vs error plots shows that the baseline models, ensembles, and droput are the best overall, but still they do violate some assumption in some cases, no model fills all expectations in all metrics.

4 Conclusions and Future Work

In this work we have made a comprehensive evaluation of uncertainty quantification methods for time series data, on two regression datasets (PM2.5 and Air Pressure prediction), considering multiple factors like prediction quality, uncertainty quality, and in particular how the prediction horizon relates with predicted uncertainty. It was expected that uncertainty and error increase with predictions far into the future, but overall this does not always hold. It strongly depends on the uncertainty method and the base model (recurrent or feed forward).

The expectations of uncertainty when it comes to time series data can be partially fulfilled, but the choice of model is crucial. Ensemble and Dropout/Dropconnect models performed the best. However, the model selection is highly dependent on the dataset and task. The dataset and the model also influence the need for recurrent layers. For example, they outperformed the standard models in Confidence vs Error expectation but the horizon expectation worked better for the non-recurrent models.

For future work, we believe that developing uncertainty quantification methods that are directly designed for sequence and time series data is crucial. All the current methods were not directly designed for sequence data, they can be partially adapted, but overall these methods do not have built-in intuitions for long and short term in-sequence dependencies, which might improve performance.

References

[1] Lakshminarayanan Balaji, Pritzel Alexander, and Blundel Charles. Simple and scalable predictive uncertainty estimation using deep ensembles. 2017.

[2] Blundell Charles, Cornebise Julien, Kavukcuoglu Koray, and Wierstra Daan. Weight uncertainty in neural networks. *arXiv preprint arXiv:1505.05424*, 2015.

[3] Yarin Gal. Uncertainty in deep learning. *Ph.D. dissertation, University of Cambridge*, 2016.

[4] Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. In *International conference on machine learning*, pages 1321–1330. PMLR, 2017.

[5] Dan Hendrycks, Norman Mu, Ekin D Cubuk, Barret Zoph, Justin Gilmer, and Balaji Lakshminarayanan. Augmix: A simple data processing method to improve robustness and uncertainty. *arXiv preprint arXiv:1912.02781*, 2019.

[6] Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8):1735–1780, 1997.

[7] Gawlikowski Jakob, Mohsin Cedrique, Rovile N.T. andAlih, and Peter Jung. A survey of uncertainty in deep neural networks. 2021.

[8] Alex Kendall and Yarin Gal. What uncertainties do we need in bayesian deep learning for computer vision? *Advances in neural information processing systems*, 30, 2017.

[9] José Maria P Menezes Jr and Guilherme A Barreto. Long-term time series prediction with the narx network: An empirical evaluation. *Neurocomputing*, 71(16-18):3335–3343, 2008.

[10] Aryan Mobiny, Pengyu Yuan, Supratik K Moulik, Naveen Garg, Carol C Wu, and Hien Van Nguyen. Dropconnect is effective in modeling uncertainty of bayesian deep networks. *Scientific reports*, 11(1):1–14, 2021.

[11] C Arden Pope, III and Douglas W Dockery. 2006 critical review - health effects of fine particulate air pollution: lines that connect. *Journal of the Air and Waste Management Association*, 56(6), 6 2006.

[12] Matteo Sangiorgio and Fabio Dercole. Robustness of lstm neural networks for multi-step forecasting of chaotic time series. *Chaos, Solitons & Fractals*, 139:110045, 2020.

[13] Martin G Schultz, Clara Betancourt, Bing Gong, Felix Kleinert, Michael Langguth, Lukas Hubert Leufen, Amirpasha Mozaffari, and Scarlet Stadtler. Can deep learning beat numerical weather prediction? *Philosophical Transactions of the Royal Society A*, 379(2194):20200097, 2021.

[14] Niko Sünderhauf, Oliver Brock, Walter Scheirer, Raia Hadsell, Dieter Fox, Jürgen Leitner, Ben Upcroft, Pieter Abbeel, Wolfram Burgard, Michael Milford, et al. The limits and potentials of deep learning for robotics. *The International journal of robotics research*, 37(4-5):405–420, 2018.

[15] Matias Valdenegro-Toro. I find your lack of uncertainty in computer vision disturbing. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1263–1272, 2021.

[16] Yeming Wen, Paul Vicol, Jimmy Ba, Dustin Tran, and Roger B. Grosse. Flipout: Efficient pseudo-independent weight perturbations on mini-batches. *CoRR*, abs/1803.04386, 2018.

A Overall Ranking of Models

In this section we provide a qualitative evaluation of each uncertainty quantification method across the two kinds of models (MLP and LSTM) and the two datasets. First we define a set of expectations for how uncertainty should behave when it comes to prediction for time series data:

1. A wider prediction horizon should result in higher uncertainty.

2. Larger errors (for instance, mean squared error) should yield higher uncertainty.

3. The estimation of calibration error (whether the model is over or under-confident). This suggests that the standard deviation (in other words, the uncertainty) should be proportional to the accuracy of the model.

Then we define two categorical parameters. The first is about the quality of the prediction horizon:

Bad where there were no conclusive results.

Moderate when there were at least two metrics from which satisfied the expectations.

Good if three expectations are satisfied.

And about Confidence vs Error expectation, in this case:

Bad means that the error does not increase with larger uncertainty.

Moderate means that the error increases with uncertainty but it fluctuates at higher uncertainty.

Good the error increases with uncertainty and does not oscillate.

These results are presented in Tables 5 and 6.

Data						PM2.5	
Models/Metrics	MAPE	MSE	R^2	Calib error	NLL	Horizon	Confidence vs Error
Baseline	10	9	9	4	6	**Good**	Bad
Ensemble	**3**	**3**	**3**	**3**	**2**	**Good**	Moderate
Dropout	4	5	5	6	4	Moderate	Bad
Dropconnect	11	11	11	5	5	Bad	Moderate
BBB	5	4	4	11	11	Moderate	Bad
Flipout	7	8	8	10	10	Bad	Bad
Baseline (lstm)	9	10	10	7	7	Bad	**Good**
Ensemble (lstm)	**1**	**1**	**1**	**1**	**1**	Bad	**Good**
Dropout (lstm)	6	6	6	8	8	Bad	Moderate
Dropconnect (lstm)	**2**	**2**	**2**	**2**	**3**	Bad	Moderate
BBB (lstm)	12	12	12	12	12	Bad	Moderate
Flipout (lstm)	8	7	7	9	9	Bad	Moderate

Table 5: The table represents the ranking of models regarding the different metrics/tasks for the PM2.5 data. The Ensemble models and the LSTM version of the Dropconnect model performed the best. For the horizon check, only the Baseline model performed in the desired manner. Regarding the Confidence vs Error plots, the LSTM Baseline and Ensemble models performed as expected.

Data	Air pressure						
Models/Metrics	MAPE	MSE	R^2	Calib error	NLL	Horizon	Confidence vs Error
Baseline	5	5	5	**3**	**3**	Bad	Moderate
Ensemble	**2**	**2**	**2**	2	1	Moderate	Bad
Dropout	**1**	**1**	**1**	6	4	**Good**	Moderate
Dropconnect	10	8	8	8	8	Bad	Bad
BBB	6	9	9	10	10	Moderate	Moderate
Flipout	9	10	10	11	9	Moderate	Bad
Baseline (lstm)	8	7	7	7	6	Bad	**Good**
Ensemble (lstm)	**3**	**3**	**3**	1	**2**	Bad	**Good**
Dropout (lstm)	7	6	6	9	7	**Good**	**Good**
Dropconnect (lstm)	4	4	4	5	5	Bad	Bad
BBB (lstm)	12	11	11	4	12	Moderate	Moderate
Flipout (lstm)	11	12	12	12	11	Bad	Moderate

Table 6: The table represents the ranking of models regarding the different metrics/tasks for the Air pressure data. The Ensemble models and the Dropout model performed the best in general. For the uncertainty based metrics, the Baseline model was successful as well. Regrading the horizon check, the Dropout models significantly outperformed all the other model. Regarding the Confidence vs Error plots, the LSTM Baseline, Ensemble and Dropout models performed as expected.

B Broader Impact Statement

Neural networks can have a large impact on society, specially as models are increasingly used for real-world applications involving humans. In this paper about the combination of sequence data/time series and uncertainty quantification, we note the following misconceptions or possibly negative impacts:

- Uncertainty or standard deviation of model output should be used to decide if the prediction should be trusted, if uncertainty is too high, predictions can be rejected, but this has to be implemented in the system using the machine learning model. This is one of the major advantages of uncertainty, but it must be used to derive highly uncertain or ambiguous predictions to a human decision maker.

- Uncertainty values produced by machine learning models are only approximations of the true bayesian posterior distribution, thus these standard deviation predictions should not be blindly trusted, there are no strict guarantees that uncertainty is proportional to error, as results in our paper also show. These values should be used with care, specially in out of distribution settings.

- Time series data might contain structure across sequence/timesteps that is not obvious and might inadvertently leak user information, for example, revealing behavior changes over time, or leaking sensitive information that can be accumulated over time. Our paper does not study how output uncertainty could contribute to this effect.

C Error vs Confidence Plots

In this section we present all reliability plots and error vs confidence plots for both datasets. The error vs confidence plot is used to evaluate the quality of uncertainty in Section A.

(a) MLP models

(b) LSTM models

Figure 1: For MLP and LSTM models, we present the calibration/reliability plots (top row) and confidence vs error plots (bottom row) on the PM2.5 dataset.

(a) MLP models

(b) LSTM models

Figure 2: For MLP and LSTM models, we present the calibration/reliability plots (top row) and confidence vs error plots (bottom row) on the Air pressure dataset.

D Visualization of Wide Horizon Results

This section presents a visualization of all metrics with a variable prediction horizon, up to 12 timesteps into the future. These results are used in Section A to rank models according to quality of their prediction horizon, according to the expectation that uncertainty (standard deviation) should increase with longer prediction horizons (it is harder to predict the future, specially the far future), and this should also be reflected in error and other relevant metrics.

D.1 PM2.5 Dataset

(a) Baseline, Ensemble, Dropout

(b) DropConnect, BBB, Flipout.

Figure 3: Comparison of MAPE, MSE, R^2, CE, and NLL with different uncertainty methods for prediction horizon of the MLP model in the PM2.5 test set. The scores not always follow a gradual rise (or drop in case of R^2).

(a) Baseline, Ensemble, Dropout.

(b) DropConnect, BBB, Flipout.

Figure 4: Comparison of MAPE, MSE, R^2, CE, and NLL with different uncertainty methods for prediction horizon of the LSTM model in the PM2.5 test set. The scores not always follow a gradual rise (or drop in case of R^2).

D.2 Air Dataset

(a) Baseline, Ensemble, Dropout

(b) DropConnect, BBB, Flipout.

Figure 5: Comparison of MAPE, MSE, R^2, CE, and NLL with different uncertainty methods for prediction horizon of the MLP model in the Air test set. The scores not always follow a gradual rise (or drop in case of R^2).

(a) Baseline, Ensemble, Dropout.

(b) DropConnect, BBB, Flipout.

Figure 6: Comparison of MAPE, MSE, R^2, CE, and NLL with different uncertainty methods for prediction horizon of the LSTM model in the Air test set. The scores not always follow a gradual rise (or drop in case of R^2).