MoTE: Mixture of Task Experts for Embedding Models

Abstract

Dense embeddings are essential for Retrieval-Augmented Generation (RAG), search, classification, and clustering systems. Recent methods improve dense embeddings by enriching them with instructions that incorporate downstream task information, enabling a single model to generate task-specific embedding spaces. However, we empirically show that requiring all tasks to share the same model parameters imposes significant representational limitations. To address these challenges, we introduce Mixture of Task Experts (MoTE), a novel transformer block designed for embedding architectures. MoTE employs dedicated parameter sets tailored to the unique requirements of each task and is paired with a task-aware training framework to improve representation quality. Experiments on 56 datasets spanning 7 tasks demonstrate that MoTE outperforms instruction-conditioned models, achieving, on average, 1.62 higher NDCG@10 on retrieval datasets, 1.54 higher MAP on re-ranking datasets, and a 0.65 improvement in overall performance. Notably, these gains are achieved without altering inference-time information, training data, inference speed, or number of active parameters.

1 Introduction

Figure 1: Average inter-task cosine similarity for MoTE and traditional instruction-conditioned embedding models (Inst. EM). After convergence, task representations in Inst. EM are constrained to be more similar to each other compared to those produced by MoTE, which optimizes dedicated parameters for each task. This highlights the representational constraints of instruction-based multi-task embedding models.

Semantic text representations are cornerstone components on many real-world applications such as search, recommendation systems, and spam classification. These representations are commonly obtained using a machine learning model that embeds unstructured text into a dense n-dimensional vector. Embedding models are developed by simultaneously optimizing a transformer architecture towards a wide range of downstream tasks including Retrieval Augmented Generation (RAG) (Gao et al., 2023; Lewis et al., 2020), search (Wise et al., 2020), Semantic Text Similarity (STS) (Chandrasekaran & Mago, 2021), classification (O'Neill et al., 2021; Wang et al., 2021), and clustering (Xu et al., 2015). As a result, a single embedding model must generate high-quality embedding representations for an arbitrary range of downstream tasks with varying requirements.

To address this diverging requirements, Wang et al. (2022); Su et al. (2022) propose to use instructions to generate different text representations with the same model. By applying this technique in a corpus, a single embedding model can be used to generate multiple embedding spaces based on the conditioned downstream task. For example Wang et al. (2022) leverages the instruction "query:" for queries and "passage:" for passages in retrieval tasks. Performance gains derived from theses methods alongside their extensive adoption by state of the art embedding models (Wang et al., 2022; Su et al., 2022) has provided solid evidence of the importance of generating task-aware semantic representations.

We argue that while existing methods enhance the input context with downstream task information, they restrict the task-specific specialization of the resulting representations. This constraint arises because the model's parameters must still be jointly optimized (Figure 1). The issue becomes even more pronounced

Figure 2: Performance comparison of Inst. EM and MoTE across tasks.

during training, where the nuanced requirements of individual tasks are overlooked in favor of selecting a single combination of hyper-parameters[1]. Examples of such configurations include batching strategies, contrastive loss directionality, and contrastive temperature. This paper addresses these limitations in contemporary embedding models (Nussbaum et al., 2024; Li et al., 2023) through the following contributions:

1. We introduce *Mixture of Task Experts (MoTE)*[2], a novel Mixture of Experts (MoE) transformer block for embedding models with a dedicated set of parameters for each task. MoTE constitutes an alternative to traditional multi-task contrastive training of dense transformer blocks and can be easily up-cycled from contemporary instruction embedding models.

2. We introduce a novel *Task-Aware Training Strategy* that captures the nuanced requirements of different tasks by enabling a flexible hyper-parameter configuration during training.

Experiments on 56 datasets across 7 tasks (Muennighoff et al., 2022) show that MoTE achieves, on average, 1.62 higher NDCG@10 on retrieval datasets, 1.54 higher Mean Average Precision (MAP) on re-ranking datasets and 0.65 overall higher performance (Figure 2) compared to traditional multi-task contrastive training. Critically, these improvements are achieved with identical inference-time information, training data, latency, and number of active parameters. Lastly, we show that expert averaging can mitigate MoTE's increased memory footprint ($16 - 49\%$) while partially preserving its performance improvements.

2 BACKGROUND

2.1 TEXT EMBEDDING MODELS

Embedding models are generally trained with a data-quality curriculum consisting of three sequential stages of decreasing data volume and increasing quality: generic pre-training, contrastive pre-training, and contrastive fine-tuning. Historically, embedding models (Gao et al., 2021) have leveraged encoder-only models such as BERT (Devlin et al., 2018) or RoBerta (Liu et al., 2019) during the generic pre-training stage. However, with the development of more powerful Large Language Models (LLMs) (Muennighoff et al., 2024; Touvron et al., 2023a;b), recent research suggests to re-use these existing decoder-only models to initialize the weights of the contrastive pre-training

---

[1]In this paper, we use the term "hyper-parameter" broadly to encompass various training configurations, such as choice of loss function, selection of negative examples, batching strategy, and more.

[2]In this paper we use MoTE to refer to both the transformer block and the resulting architecture for readability purposes.

stage[3]. Following the generic pre-training stage, the contrastive pre-training stage (Wang et al., 2022; Su et al., 2022; Nussbaum et al., 2024; Chen et al., 2024) leverages curated co-occurring text pairs naturally found in the web such as question-answer pairs from Reddit[4] and StackOverflow[5], or title-passage pairs from Wikipedia[6] pages. During this stage the model is trained with contrastive objectives such as the InfoNCE (Oord et al., 2018) using in-batch negatives (Chen et al., 2020; He et al., 2020). Finally, the model goes through a contrastive fine-tuning stage (Wang et al., 2022; Su et al., 2022; Nussbaum et al., 2024; Chen et al., 2024) that leverages a smaller amount of curated datasets - like MSMARCO (Bajaj et al., 2016) or Natural Questions (NQ) (Kwiatkowski et al., 2019) - with an anchor, a positive, and a reduced number of high-quality hard negatives (negatives that are hard to distinguish from the positive) per sample[7].

2.2 Instruction Embeddings

A core challenge during the development of embedding models is the careful calibration of a unique embedding space capable of powering multiple downstream applications without significant performance degradations in any of them (Muennighoff et al., 2022; Neelakantan et al., 2022). For example, a STS task requires the semantically similar questions "Who was Isaac Newton?" and "Who was the father of Calculus?" to be close in the embedding space while a retrieval task requires them to be far apart because the latter does not answer the former (Gao et al., 2021). To address this challenge, Wang et al. (2024); Muennighoff et al. (2024); Wang et al. (2023); Zhang et al. (2023) augment the input text with contextual information about the downstream task. This strategy leverages text instructions to condition the generation of different embedding representations using the same model and text. Contemporary methods leveraging this strategy vary in the level of detail provided in the instructions. From example, Wang et al. (2022) use text-type or task-specific information such as "Query:" and "Document:" in retrieval use cases while Su et al. (2022) use dataset-specific instructions with more detailed information such as "Represent the Amazon comment for classifying the sentence as positive or negative:".

2.3 Mixture-of-Experts

The application of MoE (Yuksel et al., 2012) to generative models (Jiang et al., 2023; Touvron et al., 2023b) has recently increased the popularity of MoE transformer architectures (Jiang et al., 2024; Gao et al., 2022b). MoE architectures are composed of MoE blocks that replace traditional dense blocks throughout the architecture or at every other block. In dense transformer blocks all intermediate token representations are processed through a single Multi-Layer Perceptron (MLP). In contrast, MoE blocks leverage a dynamic routing mechanism g and multiple MLPs (or experts) to process intermediate token representations. Specifically, for each intermediate token representation, the routing mechanism g uses the token representation to identify the subset of experts that should process the representation (Lepikhin et al., 2020). Replicas of the intermediate token representation are then dispatched to the selected experts where they are processed independently. Lastly, a pooling layer aggregates the experts' output to generate a unique representation for each of the tokens. During training, an auxiliary expert-balancing objective is leveraged to learn the routing mechanism while ensure a consistent training of and a balanced workload across the experts modules (Jiang et al., 2024; Gao et al., 2022b).

2.4 Model Weight Averaging

Model weight averaging (McMahan et al., 2017; Gao et al., 2022a; Matena & Raffel, 2022; Wortsman et al., 2022) is a simple yet effective model combining technique where several model check-

---

[3]While embedding models initialized from decoder-only models (Muennighoff et al., 2024; Touvron et al., 2023a;b) perform better than those initialized from encoder-only models (Wang et al., 2022; Su et al., 2022; Nussbaum et al., 2024), they also tend to be larger (e.g. ∼7B parameters vs 100M - 1.5B parameters respectively). Thus, incurring in higher latency, lower throughput and higher output memory footprint.

[4]https://www.reddit.com/

[5]https://stackexchange.com/

[6]https://www.wikimedia.org/

[7]When hard negatives are not included in the datasets, existing literature proposes a range of approaches to mine them from the corpora: random sampling, semantic-similarity search, manual labeling/review, etc.

points of the same architecture are combined by averaging their model parameters. This has been shown to improve performance at inference time (Popel & Bojar, 2018), as well as generalization to out-of-distribution inputs (Rame et al., 2022). Similarly to the expert averaging described in section 5, Chronopoulou et al. (2023) shows that weight averaging of adapters trained on different domains yields better performance in hold-out domains compared to single adapter routing.

3 METHOD

3.1 MIXTURE OF TASK-EXPERTS

We set ourselves to tackle the representational limitations of instruction-conditioned embedding models while retaining their ability to share relevant task-independent knowledge. Following with the example in Section 2.2, consider that we want to embed "Who was Isaac Newton?", once for a retrieval-query use case and once for a classification use case. The embedding model should possess the ability to learn and apply specialized transformations that can prioritize information that will aid in matching relevant documents (e.g., the question asks about the entity Issac Newton and "who was" is tailored to retrieve biographical details) or emphasizing global features of the sentence for the classification tasks (e.g., question type classification) according to the intended downstream task. Second, in contrast to fully independent specialized models, task-independent knowledge should be shared and accessible across tasks. For example that "Newton" in this context refers to a person instead of a unit of measure should be learned across all experts regardless of which task the training data contained physics examples. This section describes how MoTE mitigates this limitations (Wang et al., 2024; Zhang et al., 2023).

Figure 3: MoTE leverage global and single-task parameters to balance the shared and specialized task knowledge respectively. Subfigure (a) illustrates the MoTE architecture with MoE blocks incorporated every other transformer block, subfigure (b) illustrates the routing mechanism within a MoE block and subfigure (c) illustrates the components of a single expert block.

MoTE accepts tuples $(i, [i|t])$ where $i \in \mathcal{I}$ represents the task instruction providing contextual information about the downstream task (e.g., "Query ", "Passage: ") and t denotes the input text. Consistent with contemporary instruction embedding models, the concatenated representation $[i|t]$ is processed through the embedding layer and transformer blocks. In contrast, the task instruction i id directly used by the MoE blocks (Figure 3-a).

The MoTE architecture interleaves MoTE blocks at Every Other Block (EOB) of the transformer architecture[8]. The MoE blocks employ a novel context-based routing mechanism $R : \mathcal{I} \rightarrow \mathcal{E}$ to establish a mapping between the tasks $i \in \mathcal{I}$ and the expert modules $e \in \mathcal{E}$ (Figure 3-b) that is used to

---

[8]Note that our choice of interleaving MoTE blocks at EOB is arbitrary and not fixed. In practice, MoTE blocks provide practitioners with the flexibility to determine which dense blocks to up-cycle based on their specific memory and performance requirements. This trade-off is further explored in Appendix C.

route the intermediate representation of $[i|t]$ through it's task-associated expert. Task-routing offers several advantages over standard MoE token-level routing. First, tokens belonging to the same sequence can be deterministically routed through the same expert based on their associated task, which is not guaranteed in token-level routing mechanisms. This approach facilitates the model's capacity to learn task-specific experts. Second, token-level MoE requires of an auxiliary objective to ensure a balanced of expert modules during training and a balanced expert workload during inference. In contrast, task-routing mitigates this complexity by optimizing intermediate token representations only through the primary loss function and relying on contextual task information to determine the sequence routing. Critically, by utilizing only one expert per MoE block, MoTE maintains the same number of active parameters, latency and computational efficiency as the original dense transformer architecture while enabling task-specialized weight representations.

As illustrated in Figure 3-c, the expert blocks e contain a MLP block and two normalization layers. The MLP component facilitates specialized transformations for different text types while the normalization layers enables MoTE to learn different centroids and variances for each taskBa (2016).

3.1.1 Up-cycling Initialization

MoTE's task-routing mechanism requires of task-augmented inputs to train the task experts. However, contemporary embedding models only leverage task-augmented inputs during contrastive training stages while relying on a task-agnostic generic pre-training stage. Consequently, this presents a challenge because experts can neither be meaningfully trained through the generic pre-training stage nor dense transformers checkpoints resulting from the generic pre-training stage can be directly leveraged to initialize the MoTE architecture prior the contrastive pre-training stage[9].

To overcome this limitation, we propose to up-cycle (Komatsuzaki et al., 2022; He et al., 2024) the dense transformer checkpoint resulting from the generic pre-training stage to initialize MoTE's contrastive pre-training stage. Existing dense embedding models are typically trained using task-agnostic self-supervised objectives such as masked language modeling or next token prediction. Consequently, their checkpoints contain a single MLP that is incompatible with MoTE's multi-expert architecture. Our proposed initialization strategy involves consistently replicating the original MLP block from the dense checkpoint across $|\mathcal{E}|$ expert modules.

By up-cycling pre-trained dense transformer checkpoints, we achieve four critical objectives. First, MoTE is capable of preserving the foundational linguistic knowledge acquired during generic pre-training. Second, it creates a coherent initialization of the task-experts when composed with the remaining weights of the architecture. Third, it enables us to leverage the rich pool of existing pre-trained langauge models. Lastly, it constitutes a flexible initialization strategy that supports a varying range of task-specialized experts in MoTE. This approach bridges the gap between task-agnostic generic pre-training and task-routed embedding models while providing a novel application of the MoE up-cycling mechanism.

3.2 Task-aware training

Embedding models must generate semantically meaningful representations across a diverse range of tasks and domains. We argue that downstream tasks exhibit distinct representation requirements, which manifest in nuanced approaches to hyper-parameter selection and training strategies. Consider the divergent characteristics of clustering and STS tasks. Clustering applications require identifying similar data points while distinguishing them from arbitrarily different samples across domains. Consequently, high-quality hard negatives must exhibit a large domain diversity independently of the anchor. In contrast, STS tasks require to discriminate between semantically similar yet distinct textual representations. Consequently, high-quality hard negatives must exhibit high semantic similarity to the anchor. These contrasting requirements often create optimization challenges where strategies optimal for one task can degrade the performance in another.

To overcome this limitation we propose to combine MoTE with a novel task-aware training strategy that addresses this challenges with the following mechanisms:

---

[9]Note that this challenge is not present between contrastive pre-training and contrastive fine-tuning as both stages leverage task information and the same number of experts

1. Dynamic Configuration Selection: Dynamically adapt training hyper-parameters (batching strategies, contrastive temperature, objective functions, etc) based on task-specific characteristics.
2. Gradient Specialization: During contrastive training, gradients are exclusively back-propagated through experts associated with the current text type. This approach enables task-specialized weight learning while maintaining a shared learning of the self-attention layers and dense transformer blocks.

The implementation of task-aware training relies on two core components: a hierarchical data structure and task-dependent hyper-parameters. The hierarchical structure is constructed by first stratifying training samples according to their underlying task $t \in \mathcal{T}$, and then further subdividing these task-specific groups by their source datasets, creating a two-level data hierarchy. This structured approach enables the creation of mini-batches that are dynamically composed based on specific task requirements, with task metadata seamlessly becoming accessible to the training pipeline. During the forward pass, hyper-parameters are dynamically selected by leveraging the task-specific metadata, allowing for nuanced parameter adaptations to the unique characteristics of each task. Consequently, this method facilitates an end-to-end task-aware training strategy that can flexibly accommodate various components of the learning process, including instruction handling, batching strategies, objective functions, and contrastive temperature selection amongst others.

While our task-aware training approach facilitates nuanced weight specialization, we recognize the potential computational challenges inherent in hyper-parameter optimization, which can increase the search space by a factor of $|\mathcal{T}|$. To address this computational complexity, we propose two mitigation strategies: (a) selectively focus hyper-parameter tuning on tasks where optimal training strategies remain ambiguous or where preliminary analyses suggest substantial performance variability, and (b) utilize the dense embedding model as a computational proxy to systematically explore and analyze the impact of different hyper-parameter values across tasks (Appendix A), thereby enabling a more efficient empirical evaluation that can reduce computational overhead to only require training one additional candidate when compared to hyper-parameter optimization of traditional training.

3.3 Expert Averaging

Due to the nature of the MoTE architectures we can increase the expressive power of the embedding model without requiring larger output sizes or incurring latency overheads. However, this method can negatively impact the model's throughput in selective use cases (e.g., document classification or retrieval indexing) due to the increased GPU memory consumption resulting in smaller batch size per device.

To address this limitation we developed a post-training approach that decreases the memory footprint by combining the independently-trained experts into a single expert. We refer to the resulting model as Expert Averaged (EA). Specifically, we obtain EA by averaging each of the layers across experts resulting in a single MLP block. After conducting this process we obtain a model that retains over 98.2% of the MoTE performance across tasks while maintaining the same number of layers and memory footprint as the original dense transformer architecture (Section 5.5).

4 Experimental Methodology

Evaluations are conducted on the (Nussbaum et al., 2024; Wang et al., 2022; 2023; Chen et al., 2024; Su et al., 2022) Massive Text Embedding Benchmark (MTEB) (Muennighoff et al., 2022) comprising 7 tasks and 56 datasets. We leverage the same metrics and evaluation procedure reported in MTEB and report average dataset performance for each task and across all tasks in the experiment. Table 1 provides a summary of the dataset distribution and task metrics.

To ensure experimental reproducibility, we employ the open-source artifacts from Nussbaum et al. (2024). Specifically, all candidates are trained using their publicly available neural architecture[10], initialized with the pre-trained masked language modeling (MLM) checkpoint[11], and trained on

---

[10]Available at: `https://github.com/nomic-ai/contrastors/blob/main/src/contrastors/models/encoder/modeling_nomic_bert.py`

[11]Accessible at: `https://huggingface.co/nomic-ai/nomic-bert-2048`

Task	Number of Datasets	Metric
Retrieval	15	NDCG@10
Classification	12	Accuracy
Clustering	11	Validity Measure
Re-ranking	4	Mean Average Precision (MAP)
Pair Classification	3	Average Precision (AP)
STS	10	Spearman correlation
Summarization	1	Spearman correlation

Table 1: Metrics and distribution of datasets across tasks in the MTEB benchmark

identical contrastive pre-training datasets for classification, clustering, and retrieval tasks[12]. These datasets were preprocessed using top-2 consistency filtering as proposed by (Nussbaum et al., 2024; Wang et al., 2022). Throughout the contrastive training process we consistently utilize the InfoNCE loss (Oord et al., 2018) and a AdamW optimizer with learning rate of 5×10^{-6} and weight decay of 0.1. The model is trained with a batch size of $6,144$ for a single epoch. During training we maintain an identical dataset-to-task mapping[13] as Nussbaum et al. (2024). Unless otherwise specified, the remaining hyper-parameters[14] are consistently replicated from Nussbaum et al. (2024) to ensure experimental control and isolate the independent variable in each experiment.

MoTE is implemented with 4-experts associated with classification, clustering, retrieval-query and retrieval-document. Each of the experts is associated with instructions "classification: ", "clustering: ", "search query: ", and "search document: " respectively. Throughout our experiments we comparatively evaluates MoTE against instruction-conditioned Embedding Models trained on identical datasets and using the same inference information. Both candidates are trained using task-aware training leveraging the contrastive temperature and batching strategy found in Appendix A using Inst. EM.

To further investigate the performance characteristics of MoTE, we incorporate three Specialized Embedding Models (SEM) into our comparative analysis. The SEM models are implemented using dense transformer architectures, each trained independently on distinct datasets focused on classification, clustering, and retrieval tasks. In contrast to MoTE, SEM models possess a larger aggregate parameter count, with the critical distinction that none of their layers undergo joint training.

5 RESULTS

5.1 PERFORMANCE ACROSS TASKS

This section explores the performance of MoTE in tasks seen during training, namely retrieval, classification and re-ranking. We compare MoTE, Inst. EM and SEM trained using the same configuration. For SEM, each task column value reflects the score of the task-specialized model. Thus, the only difference between the Inst. EM and MoTE candidates is the architecture.

Aligned with trends in multi-task embedding training, the results show that using a single model across tasks (Inst. EM and MoTE) achieves superior performance compared to task-specialized models (SEM). Furthermore, MoTE demonstrates additional gains over instruction-conditioned embedding models (Inst. EM), achieving $+1.62$ points in retrieval tasks and $+0.59$ points on average, highlighting the benefits of task-specialized experts (Table 2).

---

[12]Dataset source: https://huggingface.co/datasets/sentence-transformers/embedding-training-data

[13]Configuration available at: https://github.com/nomic-ai/contrastors/blob/main/src/contrastors/configs/data/contrastive_pretrain.yaml

[14]Available at: https://github.com/nomic-ai/contrastors/blob/main/src/contrastors/configs/train/contrastive_pretrain.yaml

	Retrieval (NDCG@10)	Classification (accuracy)	Clustering (validity measure)	Average (Dataset performance)
SEM	33.45	64.08	39.11	45.55
Inst. EM	45.58	68.74	**43.09**	52.47
MoTE	**47.20**	**69.17**	42.81	**53.06**

Table 2: Performance comparison of SEM (task-specialized models trained only on datasets for their respective tasks), Inst. EM, and MoTE across tasks seen during training. While Inst. EM and MoTE share the same training data and inference-time information, they differ in architecture, with MoTE utilizing task-specialized experts.

5.2 GENERALIZABILITY TO NEW TASKS

Conditioning embedding models on specific instructions to tailor text representations for a finite set of tasks risks creating overly specialized embedding spaces. This risk is further accentuated by MoTE, which leverages specialized parameters for each task. In this section, we evaluate MoTE generalizability to unseen tasks including re-ranking, pair-classification, STS, and summarization. To map new tasks to appropriate specialized models, instructions, or experts, we follow the instruction-task mapping strategy outlined in Nussbaum et al. (2024). Specifically, we associate retrieval task with re-ranking tasks and classification tasks with pair classification, STS and summarization tasks across all candidates.

	Reranking (MAP)	Pair Classification (AP)	STS (Spearman corr.)	Summarization (Spearman corr.)	Average (Dataset perf.)
SEM	48.03	73.30	75.09	26.45	55.72
Inst. EM	53.37	80.72	**80.02**	33.76	61.97
MoTE	**54.91**	**81.83**	79.96	**33.97**	**62.67**

Table 3: Performance comparison of Specialized Embedding Models (SEM), Instruction-conditioned Embedding Models (Inst. EM), and MoTE on unseen downstream tasks

Similar to Inst. EM, MoTE demonstrates strong generalization capabilities to unseen tasks (Table 3). Notably, MoTE achieves a +1.54 MAP improvement for re-ranking tasks, a +1.11 AP improvement in AP for pair classification, and only minor performance drops in STS. Overall, MoTE outperforms Inst. EM by +0.7 points on average across datasets of unseen tasks, highlighting its ability to generalize while maintaining robust performance.

5.3 LIMITATIONS OF INSTRUCTION-BASED MULTI-TASK LEARNING

Our initial conjecture was that relying solely on instructions to generate task-specific embedding spaces restricts the degree of task specialization these spaces can achieve. To test this hypothesis, we compare the inter-task similarity of embedding spaces produced by MoTE and Inst. EM, trained under identical conditions. Specifically, we embed a corpus of 128 Wikipedia articles[15] as classification, clustering, retrieval corpus, and retrieval query representations.

For each element in the corpus, we measure the cosine similarity between task-specific representations and compare the average similarity across tasks for MoTE and Inst. EM. Statistical significance is assessed using a one-sided Welch's t-test based on the hypothesis formulated in Expression 1, where $\mu_{\mathcal{M}}^{(T_1, T_2)}$ represents the true cosine similarity between tasks T_1 and T_2 for model $\mathcal{M}$.

$$H_0 : \mu_{MoTE}^{(T_1, T_2)} = \mu_{\text{Inst. EM}}^{(T_1, T_2)}$$
$$H_A : \mu_{MoTE}^{(T_1, T_2)} < \mu_{\text{Inst. EM}}^{(T_1, T_2)} \tag{1}$$

---

[15]Dataset available at: `https://huggingface.co/datasets/sentence-transformers/embedding-training-data/resolve/main/SimpleWiki.jsonl.gz`

Figure 4 illustrates the distributional differences in inter-task similarity between MoTE and Inst. EM. In addition to visual distinctions across most task pairs, the p-value in most cases falls below the 0.05 significance threshold, allowing us to reject the null hypothesis that MoTE and instruction-conditioned embeddings achieve, on average, the same level of task independence. These findings support our initial hypothesis that instruction-conditioned models with shared weights constrain the representational capacity of embedding models.

Interestingly, we observe that clustering and document retrieval experts do not exhibit a statistically significant increase in task specialization. This suggests that their embedding spaces may have a lower degree of independence, indicating potential for further memory optimization by sharing the same expert with different instructions for clustering and retrieval tasks. We leave this investigation for future work.

Figure 4: Inter-task similarity of text representation when using Inst. EM and MoTE. We observe that in most cases MoTE is able to reach a higher degree independence across tasks after the multi-task contrastive learning stage.

5.4 ABLATION: EFFECT OF THE TASK-AWARE TRAINING STRATEGY

We leverage task-aware training instead of traditional task-agnostic training. Task-aware training capture the distinctive training nuances across task by creates a dependency between the current mini-batch's task and the training hyper-parameters. In contrast, traditional task-agnostic training leverages the hyper-parameter combination that leads to the overall higher performance, disregarding individual task requirements. In this experiments we ablate both experiments over an hyper-parameter space composed of the batching strategy and contrastive temperature dimensions selected using the analysis in Appendix A over MTEB. Specifically, task-aware training employs homogeneous batching for retrieval mini-batches and heterogeneous batching in classification and clustering mini-batches and a contrastive temperature of 0.03 for retrieval and classification mini-batches and 0.06 for clustering mini-batches. Static training leverages an heterogeneous batching strategy and a 0.03 contrastive temperature.

Table 4 show that task-aware training leads to an average dataset performance improvement of 0.29 largely driven by improvements in retrieval of 0.71 NDCG@10 with only minnor regressions ($< .1$) in clustering, pair classification and STS.

5.5 EA: EXPERT AVERAGING

The main drawback of MoTE when compared to current dense alternatives is its higher memory consumption which can lead to lower throughput in real world applications such as RAG-indexing

	Static training	Task-aware training
Retrieval[1]	46.48	**47.20**
Classification[2]	69.00	**69.17**
Clustering[3]	**42.82**	42.81
Re-ranking[4]	54.69	**54.91**
Pair Classification[5]	**81.93**	81.83
STS[6]	79.70	**79.96**
Summarization[6]	**34.06**	33.97
Average dataset performance	58.78	**59.07**

[1] NDCG@10;   [2] accuracy;   [3] validity measure;   [4] MAP;   [5] AP;   [6] Spearman correlation

Table 4: Comparison of MoTE when trained with a static or a dynamic regime.

or classification which require bulk inference. To alleviate this problem we introduced an Expert Averaging (EA) compression mechanism to the MoTE architecture which alleviated the increased memory footprint at no additional training cost by averaging the expert blocks (Section 3.3). In this section we systematically study the performance retention of this technique compared to both MoTE and Inst. EM.

	Inst. EM	MoTE	EA
Retrieval[1]	45.58	47.20	46.93
Classification[2]	68.74	69.17	68.82
Clustering[3]	43.09	42.81	42.70
Reranking[4]	53.37	54.91	54.91
Pair Classification[5]	80.72	81.83	81.59
STS[6]	80.02	79.96	79.13
Summarization[6]	33.76	33.97	33.38
Average dataset performance	58.43	59.07	58.60

[1] NDCG@10;   [2] accuracy;   [3] validity measure;   [4] MAP;   [5] AP;   [6] Spearman correlation

Table 5: We observe that the EA-compressed MoTE retains 0.17 average dataset performance improvement compared to Inst. EM.

EA mitigates MoTE's increased memory footprint while retaining 0.17 average dataset performance over Inst. EM. The average performance retention is largely driven by retrieval and re-ranking tasks with of 1.35 NDCG@10 and 1.54 MAP performance improvements of EA over Inst. EM, respectively.

6 CONCLUSION

Traditionally, embedding models have relied on a single model to produce a single embedding space. The recent rise of instruction-conditioning strategies challenges this paradigm by enabling the generation of distinct downstream vector representations for the same input text using contextual task instructions. However, as demonstrated in this paper, this approach limits the model's expressive power. To address this, we introduced MoTE, a framework that employs a dedicated set of parameters for each task to enhance task specialization.

Through task-aware training, MoTE effectively captures the nuances of individual tasks during multi-task learning, resulting in significant performance improvements. Specifically, MoTE achieves, on average, 1.62 points higher NDCG@10 on retrieval datasets, 1.54 points higher Mean Average Precision (MAP) on re-ranking datasets, and 0.65 higher dataset performance across tasks. Critically, these improvements are achieved without altering inference-time information, training data, latency, or the number of active parameters, demonstrating MoTE's efficiency and effectiveness compared to traditional instruction-conditioned embedding models.

REFERENCES

Eneko Agirre, Daniel Cer, Mona Diab, and Aitor Gonzalez-Agirre. SemEval-2012 task 6: A pilot on semantic textual similarity. In Eneko Agirre, Johan Bos, Mona Diab, Suresh Manandhar, Yuval Marton, and Deniz Yuret (eds.), *SEM 2012: The First Joint Conference on Lexical and Computational Semantics – Volume 1: Proceedings of the main conference and the shared task, and Volume 2: Proceedings of the Sixth International Workshop on Semantic Evaluation (SemEval 2012)*, pp. 385–393, Montréal, Canada, 7-8 June 2012. Association for Computational Linguistics. URL https://aclanthology.org/S12-1051.

Jimmy Lei Ba. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

Payal Bajaj, Daniel Campos, Nick Craswell, Li Deng, Jianfeng Gao, Xiaodong Liu, Rangan Majumder, Andrew McNamara, Bhaskar Mitra, Tri Nguyen, et al. Ms marco: A human generated machine reading comprehension dataset. *arXiv preprint arXiv:1611.09268*, 2016.

Dhivya Chandrasekaran and Vijay Mago. Evolution of semantic similarity—a survey. *ACM Computing Surveys (CSUR)*, 54(2):1–37, 2021.

Jianlv Chen, Shitao Xiao, Peitian Zhang, Kun Luo, Defu Lian, and Zheng Liu. Bge m3-embedding: Multi-lingual, multi-functionality, multi-granularity text embeddings through self-knowledge distillation. *arXiv preprint arXiv:2402.03216*, 2024.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020.

Alexandra Chronopoulou, Matthew E Peters, Alexander Fraser, and Jesse Dodge. Adaptersoup: Weight averaging to improve generalization of pretrained language models. *arXiv preprint arXiv:2302.07027*, 2023.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

William Fedus, Barret Zoph, and Noam Shazeer. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity. *Journal of Machine Learning Research*, 23(120):1–39, 2022.

Tianyu Gao, Xingcheng Yao, and Danqi Chen. Simcse: Simple contrastive learning of sentence embeddings. *arXiv preprint arXiv:2104.08821*, 2021.

Yingbo Gao, Christian Herold, Zijian Yang, and Hermann Ney. Revisiting checkpoint averaging for neural machine translation. *arXiv preprint arXiv:2210.11803*, 2022a.

Yunfan Gao, Yun Xiong, Xinyu Gao, Kangxiang Jia, Jinliu Pan, Yuxi Bi, Yi Dai, Jiawei Sun, and Haofen Wang. Retrieval-augmented generation for large language models: A survey. *arXiv preprint arXiv:2312.10997*, 2023.

Ze-Feng Gao, Peiyu Liu, Wayne Xin Zhao, Zhong-Yi Lu, and Ji-Rong Wen. Parameter-efficient mixture-of-experts architecture for pre-trained language models. *arXiv preprint arXiv:2203.01104*, 2022b.

Ethan He, Abhinav Khattar, Ryan Prenger, Vijay Korthikanti, Zijie Yan, Tong Liu, Shiqing Fan, Ashwath Aithal, Mohammad Shoeybi, and Bryan Catanzaro. Upcycling large language models into mixture of experts. *arXiv preprint arXiv:2410.07524*, 2024.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 9729–9738, 2020.

Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. Mistral 7b. *arXiv preprint arXiv:2310.06825*, 2023.

Albert Q Jiang, Alexandre Sablayrolles, Antoine Roux, Arthur Mensch, Blanche Savary, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Emma Bou Hanna, Florian Bressand, et al. Mixtral of experts. *arXiv preprint arXiv:2401.04088*, 2024.

Aran Komatsuzaki, Joan Puigcerver, James Lee-Thorp, Carlos Riquelme Ruiz, Basil Mustafa, Joshua Ainslie, Yi Tay, Mostafa Dehghani, and Neil Houlsby. Sparse upcycling: Training mixture-of-experts from dense checkpoints. *arXiv preprint arXiv:2212.05055*, 2022.

Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, et al. Natural questions: a benchmark for question answering research. *Transactions of the Association for Computational Linguistics*, 7:453–466, 2019.

Dmitry Lepikhin, HyoukJoong Lee, Yuanzhong Xu, Dehao Chen, Orhan Firat, Yanping Huang, Maxim Krikun, Noam Shazeer, and Zhifeng Chen. Gshard: Scaling giant models with conditional computation and automatic sharding. *arXiv preprint arXiv:2006.16668*, 2020.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. Retrieval-augmented generation for knowledge-intensive nlp tasks. *Advances in Neural Information Processing Systems*, 33: 9459–9474, 2020.

Zehan Li, Xin Zhang, Yanzhao Zhang, Dingkun Long, Pengjun Xie, and Meishan Zhang. Towards general text embeddings with multi-stage contrastive learning. *arXiv preprint arXiv:2308.03281*, 2023.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

Michael S Matena and Colin A Raffel. Merging models with fisher-weighted averaging. *Advances in Neural Information Processing Systems*, 35:17703–17716, 2022.

Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial intelligence and statistics*, pp. 1273–1282. PMLR, 2017.

Niklas Muennighoff, Nouamane Tazi, Loïc Magne, and Nils Reimers. Mteb: Massive text embedding benchmark. *arXiv preprint arXiv:2210.07316*, 2022.

Niklas Muennighoff, Hongjin Su, Liang Wang, Nan Yang, Furu Wei, Tao Yu, Amanpreet Singh, and Douwe Kiela. Generative representation instruction tuning. *arXiv preprint arXiv:2402.09906*, 2024.

Arvind Neelakantan, Tao Xu, Raul Puri, Alec Radford, Jesse Michael Han, Jerry Tworek, Qiming Yuan, Nikolas Tezak, Jong Wook Kim, Chris Hallacy, et al. Text and code embeddings by contrastive pre-training. *arXiv preprint arXiv:2201.10005*, 2022.

Zach Nussbaum, John X Morris, Brandon Duderstadt, and Andriy Mulyar. Nomic embed: Training a reproducible long context text embedder. *arXiv preprint arXiv:2402.01613*, 2024.

James O'Neill, Polina Rozenshtein, Ryuichi Kiryo, Motoko Kubota, and Danushka Bollegala. I wish I would have loved this one, but I didn't – a multilingual dataset for counterfactual detection in product review. In Marie-Francine Moens, Xuanjing Huang, Lucia Specia, and Scott Wen-tau Yih (eds.), *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 7092–7108, Online and Punta Cana, Dominican Republic, November 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.emnlp-main.568. URL https://aclanthology.org/2021.emnlp-main.568.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Martin Popel and Ondřej Bojar. Training tips for the transformer model. *arXiv preprint arXiv:1804.00247*, 2018.

Alexandre Rame, Matthieu Kirchmeyer, Thibaud Rahier, Alain Rakotomamonjy, Patrick Gallinari, and Matthieu Cord. Diverse weight averaging for out-of-distribution generalization. *Advances in Neural Information Processing Systems*, 35:10821–10836, 2022.

Hongjin Su, Weijia Shi, Jungo Kasai, Yizhong Wang, Yushi Hu, Mari Ostendorf, Wen-tau Yih, Noah A Smith, Luke Zettlemoyer, and Tao Yu. One embedder, any task: Instruction-finetuned text embeddings. *arXiv preprint arXiv:2212.09741*, 2022.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023a.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023b.

Liang Wang, Nan Yang, Xiaolong Huang, Binxing Jiao, Linjun Yang, Daxin Jiang, Rangan Majumder, and Furu Wei. Text embeddings by weakly-supervised contrastive pre-training. *arXiv preprint arXiv:2212.03533*, 2022.

Liang Wang, Nan Yang, Xiaolong Huang, Linjun Yang, Rangan Majumder, and Furu Wei. Improving text embeddings with large language models. *arXiv preprint arXiv:2401.00368*, 2023.

Liang Wang, Nan Yang, Xiaolong Huang, Linjun Yang, Rangan Majumder, and Furu Wei. Multilingual e5 text embeddings: A technical report. *arXiv preprint arXiv:2402.05672*, 2024.

Zichen Wang, Steven A Combs, Ryan Brand, Miguel Romero Calvo, Panpan Xu, George Price, Nataliya Golovach, Emmanuel O Salawu, Colby J Wise, Sri Priya Ponnapalli, et al. Lm-gvp: A generalizable deep learning framework for protein property prediction from sequence and structure. *bioRxiv*, pp. 2021–09, 2021.

Colby Wise, Vassilis N Ioannidis, Miguel Romero Calvo, Xiang Song, George Price, Ninad Kulkarni, Ryan Brand, Parminder Bhatia, and George Karypis. Covid-19 knowledge graph: accelerating information retrieval and discovery for scientific literature. *arXiv preprint arXiv:2007.12731*, 2020.

Mitchell Wortsman, Gabriel Ilharco, Samir Ya Gadre, Rebecca Roelofs, Raphael Gontijo-Lopes, Ari S Morcos, Hongseok Namkoong, Ali Farhadi, Yair Carmon, Simon Kornblith, et al. Model soups: averaging weights of multiple fine-tuned models improves accuracy without increasing inference time. In *International conference on machine learning*, pp. 23965–23998. PMLR, 2022.

Jiaming Xu, Peng Wang, Guanhua Tian, Bo Xu, Jun Zhao, Fangyuan Wang, and Hongwei Hao. Short text clustering via convolutional neural networks. In *Proceedings of the 1st Workshop on Vector Space Modeling for Natural Language Processing*, pp. 62–69, 2015.

Seniha Esen Yuksel, Joseph N Wilson, and Paul D Gader. Twenty years of mixture of experts. *IEEE transactions on neural networks and learning systems*, 23(8):1177–1193, 2012.

Shengyu Zhang, Linfeng Dong, Xiaoya Li, Sen Zhang, Xiaofei Sun, Shuhe Wang, Jiwei Li, Runyi Hu, Tianwei Zhang, Fei Wu, et al. Instruction tuning for large language models: A survey. *arXiv preprint arXiv:2308.10792*, 2023.

Appendices

A   HYPERPARAMETER SENSITIVITY ANALYSIS

A.1   BATCHING STRATEGY

The selection of in-batch negative samples is inherently task-dependent, with varying embedding characteristics influencing optimal sampling approaches. Tasks emphasizing *local* semantic nuances, such as Semantic Textual Similarity (STS) (Agirre et al., 2012), require negatives that capture

proximal semantic distinctions. Consider paraphrase identification, where sentences like "Vivendi shares closed 1.9 percent at 15.80 euros in Paris after falling 3.6 percent on Monday" and "in new york, vivendi shares were 1.4 percent down at $18.29" demand fine-grained contextual differentiation. Conversely, tasks focused on *global* semantic representations, including classification and clustering, benefit from more diverse negative sampling strategies that capture broader semantic variations.

To empirically validate this hypothesis, we conducted a controlled experiment training an embedding model under two distinct sampling regimes: homogeneous and heterogeneous. By maintaining all other experimental parameters constant, we isolated the impact of sampling strategy.

Figure 5: Aggregate Performance: Batching Strategy

Figure 6: Task-Specific Performance: Batching Strategy

Figure 5 demonstrates that heterogeneous sampling yields the highest aggregate performance metric. However, a granular analysis in Figure 6 reveals nuanced task-specific variations: homogeneous sampling optimizes performance for local semantic tasks, while heterogeneous sampling proves superior for global embedding objectives. This underscores the critical insight that a universal sampling strategy cannot uniformly optimize performance across diverse downstream tasks.

A.2 CONTRASTIVE TEMPERATURE

Similar to batching strategies, different contrastive temperatures capture different requirements across downstream task. Lower contrastive temperatures place a higher relative weight on samples that are more semantically similar to the anchor, thus capturing *local* semantic nuances. In contrast, higher temperatures provide a more uniform distribution of the negative weights to capture difference across a more diverse set of negatives.

To empirically validate this hypothesis, we conducted a controlled experiment training an embedding model under two distinct contrastive temperatures: 0.03 and 0.06. By maintaining all other experimental parameters constant, we isolated the impact of contrastive temperature.

Figure 7 show that the overall optimal configuration is to choose a temperature of 0.03 but a more detailed analysis in Figure 8 shows that this configuration, while beneficial to the overall performance, hurts clustering tasks.

B   ABLATION: LEARNED TOKEN-LEVEL VS DETERMINISTIC SEQUENCE-LEVEL ROUTING

MoE literature (Section 2.3) leverages context-aware token representations to route the token through different experts allowing for a better generalization across domains. In contrast, MoTE generates dense embeddings by routing examples based on their task (sequence-level) without enforcing additional expert-balancing constraints. We systematically compare the performance difference impact of leveraging sequence-level task-routing mechanism instead of the traditional token-level routing mechanism (TLR) with the same number of experts. The input for both candidates is the augmented original text with the task prefix ("classification: ", "clustering: ", "search query: ", "search document: ").

Figure 7: Overall optimal contrastive temperature.

Figure 8: Optimal contrastive temperature per downstream task.

	Token-level routing	Sequence-level routing
Retrieval[1]	45.17	**47.20**
Classification[2]	67.98	**69.17**
Clustering[3]	42.69	**42.81**
Reranking[4]	54.40	**54.91**
Pair Classification[5]	80.84	**81.83**
STS[6]	78.47	**79.96**
Summarization[6]	32.67	**33.97**
Average dataset performance	57.86	**59.07**

[1] NDCG@10; [2] accuracy; [3] validity measure; [4] MAP; [5] AP; [6] Spearman correlation

Table 6: Comparison between token-level routing and task-based sequence-level routing (SLR)

Table 6 show that directly leveraging the task context (SLR) as an expert-routing mechanism leads to performance gains when compared to indirectly leveraging this information through the intermediate token representations (TLR).

C ABLATION: MoE ARCHITECTURE DESIGN

Contemporary MoE literature proposes two designs to integrated experts in the transformers architectures balancing between local and global layers. Specifically, MoE layers can be implemented at EOB (Lepikhin et al., 2020) or at Every transformer Block (EB) (Fedus et al., 2022). In this experiment we ablate this design choice for MoTE when implemented with task-experts at EOB and at EB.

	MoE at Every Block	MoE at Every Other Block
Retrieval[1]	**47.52**	47.20
Classification[2]	69.16	**69.17**
Clustering[3]	**42.89**	42.81
Re-ranking[4]	**54.93**	54.91
Pair Classification[5]	81.81	**81.83**
STS[6]	**80.06**	79.96
Summarization[6]	**34.32**	33.97
Average dataset performance	**59.19**	59.07

[1] NDCG@10; [2] accuracy; [3] validity measure; [4] MAP; [5] AP; [6] Spearman correlation

Table 7: Comparison between architectural MoE designs: experts Every-Other Block (EOB)

Table 7 shows that using MoE at EB and at EOB leads to 59.19 and 59.07 average dataset perfor-mance, respectively. Additionally, the memory footprint for these configurations is measured at 2.2 GB for EB and 1.6 GB for EOB. Given the significant memory savings, we implement MoTE with experts at EOB at the expense of 0.12 average dataset performance.

To further analyze memory consumption, we evaluate its scaling with the number of experts for Nussbaum et al. (2024)'s neural architecture. For EOB, the memory usage increases as follows: 1 expert consumes 1.1 GB, 2 experts require 1.3 GB, 3 experts need 1.5 GB, and 4 experts use 1.6 GB. In contrast, EB demonstrates a steeper memory growth, starting at 1.1 GB for 1 expert and rising to 1.5 GB, 1.8 GB, and 2.2 GB for 2, 3, and 4 experts, respectively.