Redundancy Resolution as Action Bias in Policy Search for Robotic Manipulation

Abstract: We propose a novel approach that biases actions during policy search by lifting the concept of redundancy resolution from multi-DoF robot kinematics to the level of the reward in deep reinforcement learning and evolution strategies. The key idea is to bias the distribution of executed actions in the sense that the immediate reward remains unchanged. The resulting biased actions favor secondary objectives yielding policies that are safer to apply on the real robot. We demonstrate the feasibility of our method, considered as policy search with redundant action bias (PSRAB), in a reaching and a pick-and-lift task with a 7-DoF Franka robot trained in RLBench – a recently introduced benchmark for robotic manipulation – using state-of-the-art TD3 deep reinforcement learning and OpenAI's evolutionary strategy. We show that it is a flexible approach without significant hyperparameter tuning and interference with the main objective even across different policy search methods and tasks of different complexity. We evaluate our approach in simulation and on the real robot.

Keywords: Deep Reinforcement Learning, Evolution Strategies, Redundancy Resolution, Action Bias

1   Introduction

Deep reinforcement learning has achieved remarkable success in recent years ranging from Atari games [1] to complex locomotion [2, 3] and dexterous manipulation tasks [4, 5]. Likewise, evolution strategies provide a highly scalable alternative, which is capable of reducing the effective wall-clock time to a fraction at the cost of sample efficiency [6, 7]. Despite their successes, both approaches are challenging to train on real-world systems due to their high sample complexity. Further, they still suffer significant instabilities [8] making them very prone to changes in hyperparameters and rewards. To improve the efficiency of learning and the quality of learned policies, reward shaping can be used, which however often needs significant fine-tuning. Another popular means for improvement is imitation learning, which enhances exploration and pushes the agent's policy towards demonstrated expert policies by inserting those into the replay buffer [10, 11, 12]. We interpret the latter as adding an expert bias on the training data.

We propose an alternative approach to add bias by lifting the concept of redundancy resolution from multi-DoF robot kinematics to the level of the reward in deep RL and evolution strategies. The key idea is to bias to the distribution of executed actions while keeping the immediate reward unchanged. This redundant action bias (RAB) favors secondary objectives, e.g., for pushing the agent towards safer state-space regions or avoiding obstacles. We investigate RAB for reaching and manipulation policies exploiting the kinematic positioning redundancy of 7-DOF arms. We show that for both, deep reinforcement learning and evolutionary strategies, RAB is a feasible means to consider secondary objectives without much interference with the main learning task. Our approach yields safer and more natural-looking policies while keeping the reward-function as simple as possible. In contrast to reward shaping, we also demonstrate that our approach does not require any fine-tuning when used in different policy search methods and across tasks of different complexity. Further, we show that our approach can handle interference between the main and secondary objective, and can enhance the performance of agents, which might get trapped in a local optimum. We denote this approach *policy search with redundant action bias* (PSRAB).

Submitted to the 5th Conference on Robot Learning (CoRL 2021). Do not distribute.

In our experiments, we train reinforcement learning agents using the state-of-the-art twin-delayed deep deterministic policy gradient (TD3) algorithm [3] as well as agents using OpenAI's evolution strategy [6] (OpenAI-ES). Training is conducted in RLBench [13], a benchmarking environment for robotic manipulation, on a simulated Franka Emika Panda robot arm. All agents are trained in joint-space on a reaching and a pick-and-lift task with varying kinematic redundancy resolution. Finally, all agents are evaluated on the real robot using zero-shot transfer.

2 Related Work

In recent years, a lot of work in robotics considered reinforcement learning in task-space as no forward kinematics need to be learned by the agent while redundancy resolution of complex robots is often left to the controller [10, 11, 14, 15]. For example, Kaspar et al. [14] trained a peg-in-hole task using a soft actor-critic (SAC) [16] agent to generate high-level commands in task-space. These commands were then translated to joint-space using the operational space control (OSC) framework [17], which handles the redundancy resolution. Note that this nevertheless requires the developer to define a redundancy resolution criterion as generally no degrees of freedom should remain uncontrolled. Besides this, delegating redundancy resolution to low-level controllers can yield interference with the main task, which can not be handled by the agent. Our results shows that training and resolving redundancy together in the joint-space allows a more flexible adaption by the agent.

Regarding learning in joint-space, Peng et al. [18] presented an approach that learned an object-pushing task using a simulator with randomized dynamics. They used a recurrent version of the deep deterministic policy gradient (DDPG) [19] algorithm with a long short-term memory (LSTM) network [20]. They used hindsight experience replay (HER) [15] to allow efficient training with sparse rewards. Despite the redundant robot arm, they did not explicitly handle redundancy. Our results, however, indicate that not handling redundancy results in policies with high variety, which even exploit idiosyncrasies of a simulator yielding unnatural behavior that is infeasible in reality. Kumar et al. [21] used a proximal policy optimization (PPO) agent to solve a reaching task on environments with surrounding obstacles. Additionally, they used curriculum learning to incrementally increase the state-space cardinality. They carefully shaped the reward function to utilize redundancy and avoid obstacle contact. In contrast, our approach directly learns on the full state-space and handles redundancy without reward-shaping. Huang et al. [9] presented a problem of reward-shaping for in-hand manipulation, where a penalty reward for non-gentleness led to policies that may avoid contact altogether. We argue that it is beneficial to keep the reward function as simple as possible and use conventional approaches, such as redundancy resolution, to take secondary objectives into account.

We use redundancy resolution to push the agent towards desired, e.g., safer, state-space regions. Hence, our approach can be associated with so-called safe reinforcement learning [22], which covers approaches that consider safety constraints during the learning and/or deployment process. The authors in [10, 11, 12] combined reinforcement learning with learning from demonstrations (LfD) to impose an expert bias on the training set. For example, Vecerik et al. [12] trained a DDPG agent on different insertion tasks, where expert demonstrations were collected beforehand and inserted into the replay buffer. They showed that using expert demonstrations with a prioritized experience replay (PER) buffer [23] allows efficient training in a sparse reward setting.

3 Algorithmic Background

We consider the standard reinforcement learning setup. At each time step t, the agent observes a state $s_t \in \mathcal{S}$ and uses its policy $\pi : \mathcal{S} \to \mathcal{A}$ to choose an action $a_t \in \mathcal{A}$, which results in a subsequent state $s_{t+1} \in \mathcal{S}$. After each taken action a_t, the reward function $r : \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ returns a scalar signal r_t, which evaluates the last state-action transition. The objective is to maximize the sum of discounted rewards $R_t = \sum_{i=t}^{T} \gamma^{i-t} r(s_i, a_i)$, where $\gamma \in [0, 1]$ is a discount factor and T is the length of an episode. We assume that a state s_t is fully observable for simplicity. We optimize a differentiable policy π_θ parametrized by θ with respect to the performance measure $J(\theta) = \mathbb{E}_{s \sim p_\pi}[R_t \mid \pi_\theta]$, where p_π is the likelihood of a trajectory under policy π. The parameters θ can be updated based on the positive gradient of the expected return such that $\theta_{t+1} \leftarrow \theta + \eta \nabla_\theta J(\theta)$, where $\nabla_\theta J(\theta)$ is the policy gradient, i.e., the gradient of the policy's performance. Policy gradient methods sample rollouts following their policy π and update the parameters based on the sampled policy gradient of an episode, which generally has high variance [24].

98 **Actor-Critic Methods:** In contrast, actor-critic methods learn either a state or action-value repre-
99 sentation and train the policy on that instead. Within this work, we consider an action-value function
100 $Q^\pi(s_t, a_t) = \mathbb{E}_{s_{i>t} \sim p_\pi, a_{i>t} \sim \pi}[R_t \mid s_t, a_t]$, which describes the estimated sum of discounted rewards
101 when starting in state s_t, taking action a_t, and following the policy π thereafter. The policy is con-
102 sidered as the actor while the action-value function is considered as the critic. For a deterministic
103 policy, Silver et al. [25] provided the deterministic policy gradient:

$$\nabla_\theta J(\theta) = \mathbb{E}_{s \sim p_\pi}[\nabla_a Q^\pi(s, a)|_{a = \pi(s)} \nabla_\theta \pi_\theta(s)]. \tag{1}$$

104 Action-value functions are expressed using the recursive bellman equation and can be solved using
105 the bootstrapping principle such as in Q-Learning. As we are interested in continuous state and
106 action-spaces, we use a differentiable function $Q_\phi(s_t, a_t)$ for the critic as well, where ϕ denotes
107 the parameter vector. We drop the dependency on π in Q as we optimize the critic off-policy by
108 minimizing the loss:

$$L(\phi) = \mathbb{E}_{s_t, s_{t+1} \sim p_\pi, a_t \sim \mu}[(Q_\phi(s_t, a_t) - \Upsilon_t)^2], \tag{2}$$

109 where μ is an arbitrary behavior policy, e.g., encouraging exploration, and Υ_t is the target used for
110 updating the critic:

$$\Upsilon_t = r(s_t, a_t) + \gamma Q_\phi(s_{t+1}, \pi(s_{t+1})). \tag{3}$$

111 **Deep Deterministic Policy Gradient (DDPG):** Approximate reinforcement learning is known to
112 be relatively unstable and sample inefficient. To tackle this, DDPG [2] builds on the success of deep
113 Q-learning [26] and adapts the two main mechanisms of the latter – target networks and experience
114 replay – to the actor-critic case. DDPG uses two target networks – one for the actor and one for the
115 critic – to generate a consistent target Υ. Both target networks slowly track their online counterparts.
116 The replay buffer stores every transition during training in a tuple of (s_t, a_t, r_t, s_{t+1}). The actor and
117 the critic are then updated on randomly sampled experience from the replay buffer. This breaks the
118 correlation between samples of an episode and allows sample reuse.

119 **Twin Delayed DDPG (TD3):** Fujimoto et al. [3] introduced three modification to DDPG to further
120 enhance performance and stabilize training. Firstly, they delayed the actor updates to enhance the
121 quality of action-values. That is, while the critic is updated every d_Q steps, the actor is updated every
122 d_π steps, where $d_q < d_\pi$. Secondly, they tackled the problem of narrow peaks in the action-value
123 estimate of deterministic policies by introducing target policy smoothing. During target generation
124 (c.f., Equation (3)), noise is added to the actions chosen by the policy. Thirdly, they tackled the
125 overestimation bias of actor-critic architectures by introducing a second critic (and target critic),
126 which are both used for target generation. That is, Equation (3) is adapted to:

$$\Upsilon_t = r(s_t, a_t) + \gamma \min_{i=1,2} Q'_{\phi', i}(s_{t+1}, \pi'_{\theta'}(s_{t+1}) + \tilde{\varepsilon}) \qquad \text{with } \tilde{\varepsilon} \sim \text{clip}(\mathcal{N}(0, \tilde{\sigma}), -c, c), \tag{4}$$

127 where $Q'_{\phi', i}$ is the target network of the i-th critic, $\pi'_{\theta'}$ is the target network of the actor, and $\tilde{\varepsilon}$ is a
128 noise vector drawn from a Gaussian with zero mean and variance $\tilde{\sigma}$ clipped between $-c$ and c.

129 **Evolution Strategies** Instead of optimizing the policy parameters, evolution strategies optimize the
130 parameters of a search distribution p_ψ from which the policy parameters can be sampled, where
131 ψ denotes the parameters of the search distribution. Therefore, we reformulate the reinforcement
132 learning problem to a black-box optimization (BBO) problem. The black-box function we want to
133 optimize is the fitness F of an offspring $\tilde{\theta}$ sampled from p_ψ on a complete episode under a parame-
134 terized policy $\pi_{\tilde{\theta}}$. That is, the performance measure used to optimize the search distribution's param-
135 eters is defined as $J(\psi) = \mathbb{E}_{\tilde{\theta} \sim p_\psi, s \sim p_\pi}[F(\tilde{\theta})] = \mathbb{E}_{\tilde{\theta} \sim p_\psi, s \sim p_\pi}[\hat{R}_0 | \pi_{\tilde{\theta}}]$, where $\hat{R}_0 = \sum_{i=0}^{T} r(s_i, a_i)$ is
136 the sum of undiscounted rewards when starting in an initial state s_0 and running a complete episode
137 under policy $\pi_{\tilde{\theta}}$. The parameters ψ can be updated using the gradient of $J(\psi)$ known as search
138 gradient [27]:

$$\nabla_\psi J(\psi) = \mathbb{E}_{\tilde{\theta} \sim p_\psi, s \sim p_\pi}[F(\tilde{\theta}) \nabla_\psi \ln p_\psi(\tilde{\theta})]. \tag{5}$$

139 **OpenAI-ES** OpenAI-ES [6] is a special type of evolution strategy, which uses an isotropic Gaussian
140 with a mean vector θ and a fixed standard deviation as its search distribution $p_\psi \sim \mathcal{N}(\theta, \sigma^2 I)$. As
141 the standard deviation is fixed, the search distribution's parameters ψ only include the mean vector

142 θ. Inserting the isotropic Gaussian into Equation (5) and approximating the expectation by sampling
143 yields:

$$\nabla_\theta J(\theta) \approx \frac{1}{\lambda N} \sum_{i=1}^{\lambda} \sum_{j=0}^{N_o} F_j(\tilde{\theta}) \frac{\tilde{\theta} - \theta}{\sigma^2} = \frac{1}{\lambda N \sigma} \sum_{i=1}^{\lambda} \sum_{j=0}^{N_o} F_j(\theta + \sigma \epsilon) \epsilon \,, \tag{6}$$

144 where λ is the number of offsprings drawn from p_ψ, N_o is the number of episodes on which an off-
145 spring is evaluated on, and ϵ is sampled from $\mathcal{N}(0, I)$ as $\tilde{\theta} \sim \mathcal{N}(\theta, \sigma^2 I)$ is equivalent to $\tilde{\theta} = \theta + \sigma \epsilon$.
146 OpenAI-ES uses mirrored sampling [28] and rank-based fitness shaping [27]. The latter substitutes
147 the fitness F_j in Equation (6) with rank-based utilities u_j, to render the algorithm invariant to rank-
148 preserving (i.e, strictly monotonic) transformation of the fitness function [29].

149 4   Policy Search with Redundant Action Bias

Kinematic Redundancy

$p = const.$
$r = const.$

Task Redundancy

$r = const.$

Figure 1: Kinematic redundancy (top) as a subtype of task redundancy (bottom), where the task is to reach the red dot.

150 This section presents our method to exploit redundancy for biasing the
151 actions in order to push the agent towards more desired state-space re-
152 gions, i.e., regions satisfying secondary objectives.

153 **Task Redundancy and Redundancy Constraint:** To avoid interference
154 with the main objective, we consider redundancy with respect to the re-
155 ward of a state-action transition. That is, a biased action $\hat{a}_t = a_t + \hat{b}$ is
156 redundant with respect to a_t in s_t, if the rewards of the biased and un-
157 biased state-action transition are equal, i.e., the redundancy constraint is
158 $r(s_t, \hat{a}_t) = r(s_t, a_t)$. As the reward remains unchanged, we denote this
159 as task redundancy. When the bias $\hat{b}$ does not affect the pose or the posi-
160 tion of the end-effector in a robotic task, it can be simplified to kinematic
161 redundancy as it is considered here. Figure 1 illustrates kinematic and
162 task redundancy in a reaching task. All rewards used are functions of the
163 end-effector position $p^{(e)}$ (c.f., Equation (13) and (15)) allowing us to
164 express the redundancy constraint using the position of the end-effector
165 after a state-action transition such that $p_{t+1}^{(e)}(s_t, \hat{a}_t) = p_{t+1}^{(e)}(s_t, a_t)$.

166 **Problem setting – State-Space and Action-Space, and Redundancy resolution:** Our task space
167 comprises proprioceptive information of the 7-DOF Panda robot arm and a task-specific sub-state:
168 joint positions $q \in \mathbb{R}^7$, joint velocities $\dot{q} \in \mathbb{R}^7$, joint torques $\tau \in \mathbb{R}^7$, joint position of the gripper
169 fingers $q_g \in \mathbb{R}^2$, a binary value $\kappa_g \in \{0, 1\}$ indicating whether the gripper is open or not, and
170 a task-specific sub-state $\xi \in \mathbb{R}^{N_\xi}$ (c.f., Equation (14)). Relying on velocity control in order to
171 apply standard robotic redundancy resolution methods, an action consists of desired joint velocities
172 $\dot{q}_d \in \mathbb{R}^7$ and a binary value $\kappa_d \in \{0, 1\}$ indicating whether the gripper should be closed or not:

$$s = (q, \dot{q}, \tau, q_g, \kappa_g, \xi)^\top \in \mathbb{R}^{24 + N_\xi} \qquad a = (\dot{q}_d, \kappa_d)^\top \in \mathbb{R}^8 \,. \tag{7}$$

173 In our tasks, we have redundancy in positioning of the $M = 3$ Cartesian DoF of the end-effector by
174 means of the $N = 7$ DoF of the robot. To resolve this redundancy, we generate motion $\dot{q}_0$ in the
175 null-space of the Jacobian J_v, which maps joint velocities $\dot{q}$ to linear velocities v of the end-effector:
176

$$\dot{q}_0 = (I - J_v^+ J_v)g \,, \tag{8}$$

177 where $J_v^+ = J_v^\top (J_v J_v^\top)$ is the right pseudoinverse of J_v and $(I - J_v^+ J_v)$ is a nullspace projector,
178 which maps an arbitrary vector $g \in \mathbb{R}^M$ into the Jacobian's nullspace.

179 **Secondary Objective and Action Bias:** Through the choice g, a secondary objective can be ex-
180 pressed. Our first objective is to stay close to a desired reference joint configuration $\tilde{q}$ such that the
181 loss can be defined as:

$$L_1(q) = \frac{1}{2}(q - \tilde{q})^\top W (q - \tilde{q}) \,, \tag{9}$$

182 where $W \in \mathbb{R}^{N \times N}$ is a diagonal matrix, which weights the error in each dimension. In doing so, we
183 can provide an upright joint configuration $\tilde{q}$ as a reference to avoid skewed configurations, which are
184 more likely to cause contact with the table and look less natural. We also define a loss for collision
185 avoidance in the sense that we want to minimize the distance between robot links and obstacles:

$$L_2(q) = \sum_{i=1}^{N} \sum_{j=1}^{K} w_{ii} \, d_{ij}(q)^{-1} \,, \tag{10}$$

where d_{ij} is the distance between the link of the i-th joint and the j-th obstacle, w_{ii} are the diagonal elements of W, and K is the number of obstacles. Regardless of the choice of loss, g can be defined as a step into the direction of the negative gradient of L. That is, $\dot{q}_0$ can be computed with:

$$\dot{q}_0 = -\alpha(\mathrm{I} - \mathrm{J}_v^+ \mathrm{J}_v)\nabla_q L(q), \tag{11}$$

where α denotes a step-size parameter. Now the velocities $\dot{q}_0$ can be used to bias the policy without interfering with the main task, i.e., changing the reward of a state-action transition:

$$\hat{a}_t = \underbrace{\pi_\theta(s_t)}_{a_t} + \hat{b} \qquad \text{with} \quad \hat{b} = (\dot{q}_0, 0)^\top. \tag{12}$$

To allow a comparison to evolution strategies, we add only the unbiased action a_t to the replay buffer, even though TD3 is able to learn on off-policy actions. Refinements for more complex biases using redundancy resolution, e.g. for considering whole stacks of lower priority tasks or through biasing the replay buffer, are beyond the scope of this paper and are left to future work.

Distribution Strategy While OpenAI-ES offers straightforward parallelization over a huge number of workers by default, TD3 was introduced as a serial approach. Nonetheless, as TD3 is an off-policy approach, it can be trained on data from parallel workers as well. Barth-Maron et al. [30] introduced a distributed version of DDPG, which runs multiple actors in parallel to generate experience that is added to a joint replay buffer. Then a single critic can be trained on data from the joint replay buffer. We also distribute training in TD3. However, unlike Barth-Maron et al. [30], we only distribute the simulation environment to different workers and run it with different seeds while using a single actor instead. This distribution strategy allows more efficient training on consumer PCs as it reduces communication bandwidth – only states and actions need to be communicated instead of actor parameters – and runs the single actor on the GPU to predict the actions of all workers at once. In contrast, we implemented OpenAI-ES similarly to the original authors, as it relies on the usage of different actors (c.f., Section 3).

5 Experiments

This section presents the results of this work. We train TD3 and OpenAI-ES with and without redundancy resolution on a reaching task, and on a pick-and-lift task. We evaluate the trained agents both in simulation and on the real robot. Videos of our results, supplementary material, and the code can be found on our project websites[1][2] (and in the supplements).

5.1 Simulation Setup

RLBench is based on PyRep [31] and CoppeliaSim [32] and provides the reaching and pick-and-lift tasks. However, some adaptions had to be made to the tasks and RLBench itself. At the time of writing, RLBench uses different time horizons for sole arm actions and arm actions with gripper usage. While a sole arm action is executed in a single time step, once a gripper action is triggered, the simulation runs in a loop until the gripper has changed its state while continuously repeating the arm action. This idiosyncrasy was learned by the agent and lead to inferior performance. Thus we separated arm and gripper actions: once a gripper action is triggered, arm actions are stalled. This is also beneficial for real-world application, as this relationship between arm and gripper actions allows scaling the arm actions almost independently of the gripper actuation.

Reaching Task The goal in the reaching task is to put the robot's tip at a target position – indicated by a red sphere (c.f., Figure 3). The target position is randomly sampled within a boundary in front of the robot. The task-specific sub-state (c.f. Equation (7)) consists of the target position: $\xi^{(reach)} = p_t^{(tar)} \in \mathbb{R}^3$. RLBench only comes with sparse rewards yet allows reward shaping. We use a distance-based reward $r^{(d)}$ for the reaching task:

$$r_t^{(reach)} = r^{(d)}(p_t^{(e)}, p_t^{(tar)}) = \beta \cdot \min\left\{ d(p_t^{(e)}, p_t^{(tar)})^{-1}, d_{\min}^{-1} \right\}, \tag{13}$$

where $d(.)$ is a distance function, $d_{\min}$ is a minimum distance to limit the maximum reward, and β is a scaling parameter.

---

[1] https://sites.google.com/view/redundant-action-bias
[2] https://git.rob.cs.tu-bs.de/public_repos/irp_papers/policy_search_with_redundancy_resolution

Figure 2: Validation results of TD3 and OpenAI-ES with and without redundancy resolution on different tasks. Every 2500 training episodes, all agents were evaluated on 1000 validation episodes.

Pick-and-Lift Task: The goal in the pick-and-lift task is to pick an object – a cube with an edge length of $5\,\mathrm{cm}$ – and lift it to a target position. The position of the object and the target position are sampled randomly within a boundary in front of the robot. The task-specific sub-state consists of the position of the object $p_t^{(obj)} \in \mathbb{R}^3$, the orientation of the latter encoded as a quaternion $\mathrm{q}_t^{(obj)} \in \mathbb{R}^4$, the position of the target $p_t^{(tar)} \in \mathbb{R}^3$, and a binary value ι_t indicating whether the object is grasped or not:

$$\xi^{(pal)} = \left(p_t^{(obj)}, \mathrm{q}_t^{(obj)}, p_t^{(tar)}, \iota_t \right)^\top \in \mathbb{R}^{11} \, . \tag{14}$$

As for the reaching task, we use distance-based rewards, which are extended with sparse rewards for (partial) success:

$$r_t^{(pal)} = \bar{\zeta}_t \left(r^{(d)}(p_t^{(e)}, p_t^{(obj)}) + \iota_t r^{(d)}(p_t^{(obj)}, p_t^{(tar)}) + \iota_t r^{(grasp)} \right) + \zeta_t r^{(succ)} \, , \tag{15}$$

where ζ_t is a binary value that is 1.0 for success and else 0.0, $r^{(succ)}$ is the reward for success, ι_t is binary value that is 1.0 if the object is grasped and else 0.0, and $r^{(grasp)}$ is the reward for grasping the object. $\bar{\zeta}_t$ is the negation of ζ_t.

Training: All critics and actors are trained with an identical network architecture as in [2]: two hidden layers with 400 and 300 neurons. For TD3, the Adam optimizer [30] was used with a learning rate of $1e^{-3}$ for the actor and the critic. At each time step, the critic is updated on a batch of 100 samples drawn randomly from the replay buffer. At the beginning of training, the replay buffer is filled to half with experience from a pure random policy. Then, the proportion of pure random actions is continuously decreased during training until its minimum. In addition, uncorrelated exploration noise is added to the actions. For the reaching task, we used an action delay of $d_\pi = 2$ and, for the pick-and-lift, we used $d_\pi = 20$, which was needed to stabilize training.

For OpenAI-ES, we use a momentum optimizer with a learning rate of $1e^{-2}$ and used a batchsize of 128 off-springs, which is significantly less than in [6], to limit the computational costs. Further, we found that the trained policy generalizes too much and lacks sensitivity to small changes in the state. This resulted in a policy that always puts the gripper in the center of the boundary. We found that evaluating each off-spring on N episodes (c.f., Equation (6)) – instead of one as done by the original authors – solved this problem. A detailed overview of parameters is given on our project website.

5.2 Results

Figure 2 presents the validation results of TD3 and OpenAI-ES agents trained on the reaching and the pick-and-lift task with and without redundancy resolution using a reference configuration, which

Figure 3: Impact of redundancy resolution on an OpenAI-ES agent when using a reference position (c.f., Equation (9)) in a reaching task.

Figure 4: Impact of redundancy resolution on a TD3 agent in a simulated and a real pick-and-lift task.

is shown on the left side. Note that the reward is shown per step for TD3 and per episode for OpenAI-ES, as the latter demands fixed episode lengths. Our intent is to show the difference in performance between an agent with and without RAB, and not between TD3 and OpenAI-ES. Further, note that the RAB was not adapted across the different agents and tasks. Starting with the TD3 agent in a reaching task (upper left plot), it can be seen that our approach does not have a noteworthy effect on the performance. Both agents solve the reaching tasks at the end of training. As can be seen in the upper right plot, OpenAI-ES agent was not able to fully solve the reaching task. RAB has a positive effect on an OpenAI-ES agent at the end of training. This is due to the fact that the agent without RAB learned in two stages; at the beginning of training, it updated towards policies, which quickly brought the end-effector in the vicinity of the target position's spawn boundary, and later it learned to reach the target position within the boundary. This resulted in a similar two-stage behavior in the final policy, where the agent quickly moves into the spawn boundary and then flips the gripper to reach the target. As RAB pushes the agent towards an upright configuration, the agent was able to smoothly reach the target, which also increased final performance. Figure 3 presents an exemplary episode. TD3 was also able to solve the pick-and-lift task, as shown in the lower-left plot. As can be seen, RAB slowed down training yet reaches a similar performance at the end. We hypothesize that this is due to the loss of one DoF of the end-effector when interacting with the table, which might simplify learning to grasp at the beginning of training. Further, it can be seen that the agent without RAB has a significantly higher variance in performance throughout the training, which can be traced back to the greater variance of the state distribution. Figure 4 presents an exemplary episode of a TD3 agent with and without RAB on a simulated and a real pick-and-lift task. As can be seen, RAB has a significant influence on the orientation of the end-effector allowing it to grasp the object without physical contact with the table. This allows the straightforward transfer of the trained policy from simulation to the real robot without compromising safety. It is noted that the choice of weights W and the step-size α (c.f., Equation (9) and (11)) control the strength of the bias and thus the final orientation of the end-effector; i.e., the greater W and α the closer is the policy

Figure 5: Biasing the agent's actions to grasp from the right using a inclined reference position in a pick-and-lift task.

Figure 6: Biasing the agent's actions to avoid collision with an obstacle using a distance-maximizing loss (c.f., Equation (10)) in a reaching task.

to the reference configuration yet the smaller the agent's influence on the configuration. Finally, the lower right plot shows the performance of an OpenAI-ES agent on a pick-and-lift task. As can be seen, neither of the agents was able to solve the task as they get stuck in a local optimum, which is approaching the object. As for TD3, RAB reduced the variance in performance and led to slightly worse performance.

RAB can be used for different desired end-effector orientations as well. As an example, in Figure 5 we provided a reference position where the end-effector is inclined to the right. Passing the latter to a TD3 with RAB on a pick-and-lift task yielded a policy that grasps from the right, which was very rarely experienced without RAB. Note that such a reference position causes more interference with the main objective, as the resulting policy generates more complex trajectories. Interestingly, setting W and α too low allowed the agent to overcome the bias resulting in policies that evenly grasp the object, similarly to Figure 4. This shows that training and resolving redundancy together in the same action-space allows a more flexible adaption by the agent in case of interference.

Finally, we have used the loss shown in Equation (10) to maximize the distance between the robot's links and an obstacle. Figure 6 presents the results of a TD3 agent on a reaching task. As can be seen, RAB resulted in a policy that ducks under the obstacle. It is emphasized that the agent can not "see" the obstacle, as it is not part of its state-space nor is it included in the reward. Note that RAB does not guarantee collision-free policies when considering kinematic redundancy, as it does not control end-effector movement. We provide more material on the presented as well as on further experiments, especially on the real robot, on our project website (and in the supplements).

6 Conclusion

We demonstrated the use of an action bias derived from the concept of redundancy resolution known from multi-DoF robot kinematics to push the agent towards desired state-space regions in order to satisfy secondary objectives. This allows us to keep the reward function as simple as possible, which streamlines the setup of reinforcement learning environments. We showed that our approach can be applied across different tasks and policy search methods without much hyperparameter tuning and performance loss while allowing flexible adaption by the agent in case of interference with the main objective.

Even though we have considered kinematic redundancy only, it is straightforward to use action redundancy in more general ways, such as to bias the end-effector position as well (c.f., Figure 1), given that the redundancy constraint holds and the immediate reward is not affected. However, it does interfere with the long-term goal of the policy, which we here deliberately exploit to our purpose. But future work has to investigate further which biases are feasible and shed more light on how more complex hierarchies of sub-tasks might use such indirect interaction with the learning without destabilizing it.

References

[1] V. Mnih, A. P. Badia, M. Mirza, A. Graves, T. Lillicrap, T. Harley, D. Silver, and K. Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International Conference on Machine Learning*, volume 48, pages 1928–1937, New York, United States, June 2016.

[2] T. P. Lillicrap, J. J. Hunt, A. Pritzel, N. Heess, T. Erez, Y. Tassa, D. Silver, and D. Wierstra. Continuous control with deep reinforcement learning. In *International Conference on Learning Representations*, San Juan, Puerto Rico, May 2016.

[3] S. Fujimoto, H. van Hoof, and D. Meger. Addressing function approximation error in actor-critic methods. In *International Conference on Machine Learning*, volume 80, pages 1587–1596, Stockholm, Sweden, July 2018.

[4] O. Andrychowicz, B. Baker, M. Chociej, R. Józefowicz, B. McGrew, J. Pachocki, A. Petron, M. Plappert, G. Powell, A. Ray, J. Schneider, S. Sidor, J. Tobin, P. Welinder, L. Weng, and W. Zaremba. Learning dexterous in-hand manipulation. *The International Journal of Robotics Research*, 39(1):3–20, Nov. 2019. doi:10.1177/0278364919887447.

[5] A. Rajeswaran, V. Kumar, A. Gupta, G. Vezzani, J. Schulman, E. Todorov, and S. Levine. Learning complex dexterous manipulation with deep reinforcement learning and demonstrations. In *Conference of Robotics: Science and Systems*, Pittsburgh, Pennsylvania, USA, June 2018. doi:10.15607/RSS.2018.XIV. 049.

[6] T. Salimans, J. Ho, X. Chen, S. Sidor, and I. Sutskever. Evolution strategies as a scalable alternative to reinforcement learning. *arXiv*, Mar. 2017.

[7] F. H. Patryk Chrabaszcz, Ilya Loshchilov. Back to basics: Benchmarking canonical evolution strategies for playing atari. In *International Joint Conference on Artificial Intelligence*, pages 1419–1426, Stockholm, Sweden, July 2018.

[8] O. Sigaud and F. Stulp. Policy search in continuous action domains: An overview. *Neural Networks*, 113: 28–40, May 2019. doi:10.1016/j.neunet.2019.01.011.

[9] S. H. Huang, M. Zambelli, J. Kay, M. F. Martins, Y. Tassa, P. M. Pilarski, and R. Hadsell. Learning gentle object manipulation with curiosity-driven deep reinforcement learning. *arXiv*, Mar. 2019.

[10] A. Nair, B. McGrew, M. Andrychowicz, W. Zaremba, and P. Abbeel. Overcoming exploration in reinforcement learning with demonstrations. In *International Conference on Robotics and Automation (ICRA)*, pages 6292 – 6299, Brisbane, Australia, May 2018. doi:10.1109/icra.2018.8463162.

[11] G. Zuo, Q. Zhao, J. Lu, and J. Li. Efficient hindsight reinforcement learning using demonstrations for robotic tasks with sparse rewards. *International Journal of Advanced Robotic Systems*, 17(1), Jan. 2020. doi:10.1177/1729881419898342.

[12] M. Vecerik, T. Hester, J. Scholz, F. Wang, O. Pietquin, B. Piot, N. Heess, T. Rothörl, T. Lampe, and M. Riedmiller. Leveraging demonstrations for deep reinforcement learning on robotics problems with sparse rewards. *arXiv*, Oct. 2018.

[13] S. James, Z. Ma, D. R. Arrojo, and A. J. Davison. RLBench: The robot learning benchmark & learning environment. *IEEE Robotics and Automation Letters*, 5(2):3019–3026, Apr. 2020. doi:10.1109/lra.2020. 2974707.

[14] M. Kaspar, J. Muñoz Osorio, and J. Bock. Sim2real transfer for reinforcement learning without dynamics randomization. In *International Conference on Intelligent Robots and Systems (IROS)*, Las Vegas, Nevada, USA, Oct. 2020.

[15] M. Andrychowicz, F. Wolski, A. Ray, J. Schneider, R. Fong, P. Welinder, B. McGrew, J. Tobin, O. Pieter Abbeel, and W. Zaremba. Hindsight experience replay. In *Conference on Neural Information Processing Systems (NIPS)*, Long Beach, California, United States, Dec. 2017.

[16] T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning*, volume 80, pages 1861–1870, Stockholm, Sweden, 2018. PMLR.

[17] O. Khatib. A unified approach for motion and force control of robot manipulators: The operational space formulation. *Journal on Robotics and Automation*, 3(1):43–53, 1987. doi:10.1109/JRA.1987.1087068.

[18] X. B. Peng, M. Andrychowicz, W. Zaremba, and P. Abbeel. Sim-to-real transfer of robotic control with dynamics randomization. In *International Conference on Robotics and Automation (ICRA)*, pages 1–8, Brisbane, Australia, May 2018. doi:10.1109/ICRA.2018.8460528.

[19] N. Heess, J. J. Hunt, T. P. Lillicrap, and D. Silver. Memory-based control with recurrent neural networks. *arXiv*, 2015.

[20] S. Hochreiter and J. Schmidhuber. Long short-term memory. *Neural Computation*, 9:1735–80, 12 1997. doi:10.1162/neco.1997.9.8.1735.

[21] V. Kumar, D. Hoeller, B. Sundaralingam, J. Tremblay, and S. Birchfield. Joint space control via deep reinforcement learning. *arXiv*, Nov. 2020.

[22] J. García, Fern, and o Fernández. A comprehensive survey on safe reinforcement learning. *Journal of Machine Learning Research*, 16(42):1437–1480, 2015.

[23] T. Schaul, J. Quan, I. Antonoglou, and D. Silver. Prioritized Experience Replay. In *International Conference on Learning Representations (ICLR)*, San Juan, Puerto Rico, May 2016.

[24] R. S. Sutton; and A. G. Barto. *Reinforcement Learning*. The MIT Press, 2018.

[25] D. Silver, G. Lever, N. Heess, T. Degris, D. Wierstra, and M. Riedmiller. Deterministic policy gradient algorithms. In *International Conference on Machine Learning*, volume 32, pages 387–395, Beijing, China, 2014.

[26] V. Mnih, K. Kavukcuoglu, D. Silver, A. A. Rusu, J. Veness, M. G. Bellemare, A. Graves, M. Riedmiller, A. K. Fidjeland, G. Ostrovski, S. Petersen, C. Beattie, A. Sadik, I. Antonoglou, H. King, D. Kumaran, D. Wierstra, S. Legg, and D. Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, Feb. 2015. doi:10.1038/nature14236.

[27] D. Wierstra, T. Schaul, T. Glasmachers, Y. Sun, J. Peters, and J. Schmidhuber. Natural evolution strategies. *Journal of Machine Learning Research*, 15(27):949–980, 2014.

[28] D. Brockhoff, A. Auger, N. Hansen, D. V. Arnold, and T. Hohm. Mirrored sampling and sequential selection for evolution strategies. In *International Conference on Parallel Problem Solving from Nature*, pages 11 – 21, Kraków, Poland, Sept. 2010. Springer.

[29] N. Hansen. The cma evolution strategy: A tutorial. *arXiv*, 2016.

[30] G. Barth-Maron, M. W. Hoffman, D. Budden, W. Dabney, D. Horgan, D. TB, A. Muldal, N. Heess, and T. Lillicrap. Distributed distributional deterministic policy gradients. In *International Conference on Learning Representations*, Vancouver, Canada, May 2018.

[31] S. James, M. Freese, and A. J. Davison. Pyrep: Bringing v-rep to deep robot learning. *arXiv*, June 2019.

[32] E. Rohmer, S. P. N. Singh, and M. Freese. Coppeliasim (formerly v-rep): a versatile and scalable robot simulation framework. In *International Conference on Intelligent Robots and Systems (IROS)*, Tokyo, Japan, 2013.