◄◉►Proppo: a Message Passing Framework for Customizable and Composable Learning Algorithms

Paavo Parmas[*]
Kyoto University
paavo@sys.i.kyoto-u.ac.jp

Takuma Seno[†]
Keio University
seno@ailab.ics.keio.ac.jp

Abstract

While existing automatic differentiation (AD) frameworks allow flexibly composing model architectures, they do not provide the same flexibility for composing learning algorithms—everything has to be implemented in terms of back-propagation. To address this gap, we invent Automatic Propagation (AP) software, which generalizes AD, and allows custom and composable construction of complex learning algorithms. The framework allows packaging custom learning algorithms into propagators that automatically implement the necessary computations, and can be reused across different computation graphs. We implement Proppo, a prototype AP software package built on top of the Pytorch AD framework. To demonstrate the utility of Proppo, we use it to implement Monte Carlo gradient estimation techniques, such as reparameterization and likelihood ratio gradients, as well as the total propagation algorithm and Gaussian shaping gradients, which were previously used in model-based reinforcement learning, but do not have any publicly available implementation. Finally, in minimalistic experiments, we show that these methods allow increasing the gradient estimation accuracy by orders of magnitude, particularly when the machine learning system is at the edge of chaos.[3]

1 Introduction

(a) Direct approach (b) Library approach (c) Automatic propagation software approach

Figure 1: A simplified taxonomy of machine learning (ML) software development methodologies. The *computation software* refers to existing ML tools such as PyTorch (Paszke et al., 2019) or NumPy (Harris et al., 2020); the *software library* is reusable code for a new ML method.

When a machine learning (ML) researcher comes up with a new algorithm, they are faced with a dilemma: do they directly implement an application of their algorithm using existing ML tools (Fig. 1a); or do they implement a library for their algorithm, then use the library to implement the desired application (Fig. 1b). The first approach is faster, because the researcher only has to worry about the details of the specific application; the second approach may take longer to implement, but will enable reuse of the code and speed up implementing future applications. Clearly, the second

---

[*]Affiliated with the Okinawa Institute of Science and Technology (OIST) during much of the project.

[†]Hired by OIST during his contribution to the project. Currently working at Sony AI.

[3]The code will be made available at https://github.com/proppo/proppo.

36th Conference on Neural Information Processing Systems (NeurIPS 2022).

approach is preferable in the long-term. Our work aims to overcome this dilemma by simplifying the intermediate stage of implementing reusable code for the algorithm. The approach is illustrated in Fig. 1c, where, our invention, *automatic propagation software*, ameliorates the shortcomings of existing tools that we utilize concurrently to implement reusable code for a new algorithm. This interusability was a key design choice, as it allows benefitting from the rich ML software ecosystem.

In ML a vast amount of effort has already been placed in developing computational software related to back propagation, ranging from established automatic differentiation (AD) libraries (Paszke et al., 2019; Tokui et al., 2015; Abadi et al., 2016; Bradbury et al., 2018); newer AD libraries(Oktay et al., 2020; Paszke et al., 2021); deep learning libraries (Chollet et al., 2015); extensions to AD libraries (Dangel et al., 2020; Rogozhnikov, 2021) to frameworks that use these AD libraries as tools to implement algorithms (Krieken et al., 2021; Tran et al., 2016; Gardner et al., 2018). Moreover, some libraries do not directly build on these frameworks, but can be combined together, e.g., Ray (Moritz et al., 2018) for distributed computing. Creating each one of these libraries takes significant effort, and it makes sense to build on the work of others to simplify implementing new algorithms. Due to this, new implementations tend to follow the old design paradigms of existing software.

Barham and Isard (2019) described this situation with the sentence "Machine learning systems are stuck in a rut". They argued that current ML systems are optimized for computations encountered by popular algorithms, yet, other calculations may be slow, despite in principle requiring a similar amount of operations. Such an imbalance would discourage researchers from trying new ideas that require novel forms of computation. Our own observation is that existing AD frameworks encourage implementing algorithms by designing a differentiable "surrogate loss" (Schulman et al., 2015; Foerster et al., 2018) often employed for implementations of Monte Carlo (MC) gradient estimators (Krieken et al., 2021). However, this may not be the most natural way to express the algorithms, or indeed, it may not even be possible. Minka (2019) argued that a general-purpose ML language should "simplify implementation of *all* ML algorithms", and promoted a message passing approach.

Message passing (MP) is a promising candidate for a general ML framework because of the many already existing efficient algorithms that are based on it. Some of the prominent MP algorithms are belief propagation (Pearl, 1982) and expectation propagation (Minka, 2001) in probabilistic modeling, and turbo codes in information theory (McEliece et al., 1998). In modern deep learning, MP is used in graph neural networks (Wu et al., 2020). Also, back propagation can be seen as an MP algorithm that passes the gradient messages backwards. A closely related framework to MP is the Actor Model of computation (Hewitt et al., 1973), where programs operate by actors passing messages between each other. The Actor Model has been suggested as a promising framework for parallel AI systems (Hewitt and Lieberman, 1983) and has been noted to enable modularity (Agha, 1986). We aim to incorporate these strengths into a practical general-purpose message passing framework that enables conveniently implementing a variety of MP algorithms, and propose automatic propagation (AP).

We list our desiderata for a general-purpose framework, and the approach we take to meet these desired properties in Proppo, our prototype AP software package.

Ease of use. Proppo is implemented entirely in Python, a language favored by ML researchers.

Flexibility. Proppo allows implementing arbitrary message passing algorithms.

Computational speed. Proppo interfaces with existing computational frameworks such as PyTorch to achieve efficient computation. Proppo adds functionality to such frameworks; the computational speed will depend on how the user implements their algorithm.

Reusability of code. Proppo allows packaging algorithms into propagators—the key building blocks of AP software—that encapsulate an algorithm and can be reused across different computation graphs.

Composability. Proppo includes special sequence propagators (Sec. 3.3) that allow combining multiple propagators together to form new propagators. These new propagators may then be further composed, allowing to deal with arbitrary complexity.

The main functionality of Proppo is to provide base classes for the propagators, and to implement automatic message passing. When a user wants to implement a new algorithm, they need to create the propagators to represent their algorithm as a message passing program. When a user wants to use an existing algorithm, they can simply download the existing propagators, and apply them in their code.

To demonstrate the utility of Proppo, we use it to implement the total propagation (TP) and Gaussian shaping (GS) gradient algorithms (Parmas et al., 2018; Parmas, 2018). Both of these are techniques for MC gradient estimation without previously existing publicly available implementations, and they were one of our key motivations for this research. In particular, the probabilistic computation graph framework (Parmas, 2018, 2020) influenced our thinking on MC gradient estimation, as it makes clear that MC gradient estimators can be implemented as MP programs passing information backwards. Our experimental results in Sec. 4.2 and App. C.3 demonstrate orders of magnitude improvement in gradient accuracy for these methods. The improvement was particularly large when the system was at the *edge of chaos*. This implies that AP software can achieve fundamentally better computational results compared to the current AD software paradigm. To demonstrate the scalability and practicality of Proppo, in our concurrent work (Anonymous, 2022) we use Proppo to replicate the model-based RL results of (Parmas et al., 2018) and we apply TP to the high dimensional visual MBRL algorithm Dreamer (Hafner et al., 2020). All our results imply that Proppo is scalable, leads to more modular code, simplifies implementation of some algorithms and can lead to greatly improved performance.

2 Preliminaries

2.1 Automatic differentiation software

A recent review of AD in ML was written by Baydin et al. (2018). To explain the functionality of AD software, suppose that a user has written a program to compute the output of a function $y = f(\boldsymbol{x})$ given the input $\boldsymbol{x}$. In such a situation, AD software can automatically obtain the gradient $\nabla_{\boldsymbol{x}} f(\boldsymbol{x})$. Such functionality is achieved by differentiating each intermediate computation and applying the chain rule. A series of computations can be represented as a directed acyclic graph with nodes and their associated variables $\boldsymbol{x}_i$, and with an edge from node i to j when the variable $\boldsymbol{x}_j$ is computed with a function $f_k(\boldsymbol{x}_i, \ldots)$ taking the variable at node i as an input. In this case, the total derivative from $\boldsymbol{x}$ to y can be obtained by summing the product of derivatives across all paths between the two nodes (Bauer, 1974),

$$\nabla_{\boldsymbol{x}} f(\boldsymbol{x}) = \sum_{\text{Path} \in \text{Paths}[\boldsymbol{x} \to y]} \prod_{\text{Edge}[l \to k] \in \text{Path}} \frac{\partial \boldsymbol{x}_k}{\partial \boldsymbol{x}_l}. \tag{1}$$

A naïve way to implement AD would be to compute the intermediate Jacobians $\frac{\partial \boldsymbol{x}_k}{\partial \boldsymbol{x}_l}$ by differentiating the operations $f_k(\boldsymbol{x}_l, \ldots)$. However, note that this will require storing full Jacobian matrices having size $K \times L$, where K and L are the respective dimensionalities of the variables. Moreover, if the gradient were computed by multiplying the Jacobians in the forward direction from $\boldsymbol{x}$ to y, this would require matrix-matrix multiplications at each step, and may incur a large computational cost. Reverse mode automatic differentiation (also known as back propagation), overcomes this issue by performing the computations backwards from the y node. As y is just a 1 dimensional scalar, its local Jacobian is a vector. Therefore the computation at the last step is a vector-matrix product, yielding another vector. This vector is propagated backwards, yielding a vector at each backward step. This allows computing the total gradient using only vector-matrix products, leading to a large computational saving compared to computing the gradients in the forward direction using matrix-matrix products.

Another subtle point is that it is not necessary to compute the intermediate Jacobians $\frac{\partial \boldsymbol{x}_k}{\partial \boldsymbol{x}_l}$, one merely needs a means to compute $\boldsymbol{v}^T \frac{\partial \boldsymbol{x}_k}{\partial \boldsymbol{x}_l}$, where $\boldsymbol{v}$ is the back propagated gradient vector. So in practice, AD software often only stores the variables necessary to evaluate, $\boldsymbol{v}^T \frac{\partial \boldsymbol{x}_k}{\partial \boldsymbol{x}_l}$, and never explicitly computes $\frac{\partial \boldsymbol{x}_k}{\partial \boldsymbol{x}_l}$. This leads to further computational and memory savings, as the full Jacobian matrices with size $K \times L$ need not be stored. In PyTorch, this is implemented in the `torch.autograd.backward(tensors, grad_tensors)` function, where `tensors` corresponds to $\boldsymbol{x}_k$ and `grad_tensors` corresponds to $\boldsymbol{v}$. All in all, AD software implements *forward* functions to cache the necessary data at each node, and *backward* functions to evaluate the vector-Jacobian product at each node using the cache, resulting in efficient and automatic computation of the gradient.

2.2 Basics of Monte Carlo gradient estimation

In ML, the computations may be stochastic, and the objective is an expectation $J = \mathbb{E}_{\boldsymbol{x} \sim p(\boldsymbol{x};\beta)}[f(\boldsymbol{x})]$. In this case, it is not clear how to directly differentiate the stochastic operations, and we use

Monte Carlo (MC) methods to obtain an estimator, $\hat{g}$, for the gradient $\frac{dJ}{d\beta}$, s.t. $\mathbb{E}[\hat{g}] = \frac{dJ}{d\beta}$. Such methods have been reviewed in ML by Mohamed et al. (2020). The two major MC gradient estimators are the reparameterization (RP) (Rezende et al., 2014; Kingma and Welling, 2013) and likelihood ratio (LR) (Williams, 1992; Glynn, 1990) gradient estimators. The LR method uses $f(\boldsymbol{x})$ to construct an estimator, whereas RP uses $\nabla_{\boldsymbol{x}} f(\boldsymbol{x})$. Total propagation (TP) (Parmas et al., 2018) combines LR and RP using inverse variance weighting. Moreover, TP does so at a step-wise level at each sampling node. The required step-wise computations interfere with the natural operation of back propagation, necessitating AP software to implement TP. We give more background on these methods in App. A.

3 Proppo explanation

Figure 2: Automatic propagation framework (Sec. 3). A subset of the nodes ○ are designated as propagation nodes ○ forming the propagation graph. The propagation manager ▽ traverses the propagation graph and activates the propagators to ensure the correct functioning of the implemented algorithm. Here, the propagation graph is illustrated as a chain, but it may also have a graph structure. The gray dashed lines show the corresponding same nodes in the propagation and computation graphs.

A schematic illustration of automatic propagation software is provided in Fig. 2. Automatic propagation is *not* an alternative to existing frameworks, such as AD packages, rather, it adds functionality on top of them, and can be used in conjunction. We first explain the Proppo framework, in its simplest form, which is one specific implementation of AP software; we explain the different components of the framework (Sec. 3.1), then the processes by which they operate (Sec. 3.2). Finally, we explain AP from a more general perspective (App. B.1), loosening some of the specific choices in Proppo.

3.1 Components of Proppo

Computation nodes. Automatic propagation software can be combined together with any other computation package or program code. These external packages can be used regularly as one would usually write code. However, at certain locations in the code, the user can specify special computations that will determine what algorithm is implemented using the AP software. These special computations will create *propagation nodes* ○.

Propagation nodes. The propagation nodes determine the structure of the operations performed in the AP software. In Proppo, each propagation node includes the three components: (1) a pointer to a propagator ·○· that determines the forward and backward computations belonging to the node, (2) a cache/memory that stores necessary information for the computations occurring at the node, (3) a message box for incoming messages ⊠ from other propagation nodes.

Propagators. The propagators are the key components of AP software. The propagators determine the computations performed at each propagation node. In Proppo, each propagator implements a forward and backward mode of computation. The forward function is used when the node is first created; it may take an input from the program code, perform computations, store data in the memory of the node, and produce an output. The backward function is used in later processing; it performs computations using the stored data in the memory and incoming messages to the node, and sends messages ⊠ to other nodes in the propagation graph.

✉ **Messages.** Globally, the algorithms are implemented by passing messages between the propagation nodes. Each message includes the two components: (1) the contents of the message, (2) an address determining where the message should be sent. A typical address may be a pointer to the parent node of the current propagation node, so that the messages are passed backwards.

⬡ **Propagation manager.** In Proppo, all of the messages are first passed to the propagation manager, then the propagation manager decides where to send the message based on the address in the message. The propagation manager also has other important roles: it constructs the propagation graph, keeps track of the nodes, activates the propagators and passes messages.

3.2 Typical program flow and usage of automatic propagation software

Usage of AP software can be broadly categorized into two: (1) implementing a new algorithm into an AP package, (2) using an algorithm already implemented in AP software. We start by explaining how one would typically use an already existing algorithm packaged into AP software. We begin by explaining a minimalistic code snippet in Fig. 3 of MC gradient estimation with Proppo.

```
1
2
3
4
5 state = torch.randn(batch_size,
6                     num_dimensions)
7 for t in range(horizon_length):
8     state = rnn(state)
9
10
11 loss = loss_func(state)
12 loss.backward()
```

```
1 # Configuration code
2 prop = RPProp(config) # Choose RPProp or LRProp
3 manager = PropagationManager(
4                       default_propagator=prop)
5 # Program code
6 state = torch.randn(batch_size, num_dimensions)
7 for t in range(horizon_length):
8     state = rnn(state)
9     state = manager.forward(state)
10
11 loss = loss_func(state)
12 manager.backward(loss)
```

(a) PyTorch code   (b) Proppo code combined with PyTorch code

Figure 3: Code for estimating the gradient w.r.t. the parameters of a recurrent neural network (`rnn`).

Minimalistic code example. In the example in Fig. 3a, a batch of initial states (`state`) is sampled from a Gaussian distribution (lines 5–6), this batch is pushed through the recurrent neural network (`rnn`) for `horizon_length` times, then a loss is computed using the function `loss_func`, finally the gradients are backpropagted from the loss node by calling `loss.backward()`. As explained in the preliminaries (Sec. 2.1), the gradients will backpropagate until the parameter node in the computation graph. The regular PyTorch code in Fig. 3a computes the gradient using back propagation; the Proppo code in Fig. 3b modifies the computation by adding noise into the forward computation, and estimating the gradient using either RP gradients or LR gradients. Conveniently, only the definition of the propagator on line 2 has to be changed to switch between using LR or RP gradients. Moreover, settings such as whether the LR gradient should use a baseline or not can be specified in the `config` without having to modify the program code. Finally, note that instead of changing the behavior to use MC gradient estimators by using `RPProp` or `LRProp`, one could also simply use standard back propagation by setting an appropriate different propagator in the configuration. This was a minimalistic example to give a taste of how Proppo might be used. In practice both the configuration and program code may be more complicated with multiple types of propagators. We will explain how existing AP algorithms would typically be used with reference to this minimalistic example.

Using an AP algorithm. The code for using AP software can be broadly separated into two: the *configuration code* that sets up the AP software and selects the algorithm to be used, and the *program code* that determines how and where the algorithm is applied. It may be beneficial to keep these sections of the code distinct to improve the readability and modularity.

In the minimalistic example in Fig. 3b the *configuration code* is on lines 2–4. When configuring the code, the user instantiates the propagator and propagation manager objects from their existing class code, while giving them the appropriate configuration. A propagator may be created using

$$\text{propagator} = \text{Propagator}(\text{config}).$$

There are different propagator classes, and the user would use a different command for the different types of propagators. Some propagators may allow for a configuration input to make small tweaks to

the behavior. The propagation manager may be created using

$$\text{manager = PropagationManager(config)}.$$

Here the configuration input may define default propagators to be used for specified computations, default message passing styles, etc. The configuration in the RNN example was simple, but in general the configuration may be more complicated and include setting up many different types of propagators and equipping them to the manager by assigning them names by which the manager identifies them.

After selecting the desired algorithm by properly configuring the AP software, the user must modify the *program code* to make it compatible with the AP software and properly implement the algorithm. In the minimalistic example in Fig. 3b, the program code is on lines 6–12, and the modifications to use Proppo are on lines 9 and 12. We emphasize that the same modifications may be compatible with multiple algorithms, so that only the configuration code has to be modified to switch between the algorithms. The main purpose of the modifications to the program code are to activate the propagators and construct the propagation graph. A propagator is activated using the command

$$\text{output = manager.forward(input, arguments)}.$$

This command will add a node into the propagation graph of the manager. In the current case, the `manager` has been equipped with the default propagator `prop`. When `manager` calls the forward function, it will create a new node, and assign the `prop` propagator to it. Then, the forward method of `prop` is called with the `input`. The forward method applies some modification to the input, stores data in the memory of the node, and produces an output. Note that the data stored in the memory of the node will be used later during the backward pass of the algorithm.

The `arguments` input to the `forward` function serves multiple purposes. One of the main purposes is to modify the behavior of the propagator in some way. For example, in the minimalistic code in Fig. 3b the propagator injects noise into `state` to produce the output, so one part of the `arguments` may be the type of noise and the parameters of the noise distribution. Note that often these settings can be defined in the configuration without having to modify the `arguments`, e.g. the type of distribution may just be fixed in the configuration code. Another role of the `arguments` is to modify the targets where the messages should be sent if the default setting is unsuitable. Furthermore, if multiple types of propagators are necessary to implement the algorithm, the `arguments` may also be used to select between different propagators equipped to the manager.

Finally, the backward pass of the algorithm is invoked by calling

$$\text{manager.backward()}.$$

When the `manager.backward` function is called, the manager will typically call the `backward` function of the propagator of the last node, pass the message to its target node, call the `backward` function of the previous node, and iterate this process from the end of the graph until the beginning. If the propagators are correctly implemented, and the propagation graph is correctly constructed, this framework allows automatically using an algorithm available in the AP software.

A keen reader may have noticed that in the minimalistic example in Fig. 3b an additional `loss` input was given to the `backward` call. This is a convenience implemented in Proppo, where the manager will automatically add a propagator corresponding to the loss as the final node before starting to iterate backwards on the propagation graph. Alternatively, the same operations could have been implemented by the commands `manager.append_loss(loss)` followed by `manager.backward()`. Internally, `append_loss(·)` simply calls the forward method of a special propagator designed for adding a node corresponding to a loss. In Proppo, yet another way how the lines 11–12 for adding the loss could have been implemented is the following: `manager.append_loss(state, lossfunc=loss_func)` followed by `manager.backward()`. In this case, the loss function `loss_func` is passed to the propagator directly via the `lossfunc` keyword, and the propagator will compute the loss by inputting `state` into `loss_func`. The last method of implementation is beneficial for compatibility between different types of loss propagators, for example, it is useful for easily switching between the loss operations necessary for Gaussian shaping gradients and a regular loss computation. We see that there are many different ways to implement the same algorithm using propagators.

Creating an AP algorithm. In the previous section, we saw that the functionality of an AP algorithm is determined by the implementation of the propagators. Consequently, creating a new AP algorithm requires implementing the appropriate propagators corresponding to the desired algorithm.

In Proppo, several base classes for new propagators are already provided, and the user must only implement the `forward` and `backward` methods of the propagators.

In principle, the `forward` and `backward` methods can contain arbitrary code, and there is no restriction on what they can do. The programmer must figure out how to implement their algorithm through a process of storing data in the `forward` pass, and further computations and message passing in the `backward` pass. The programmer must also decide how many different types of propagators are necessary for their algorithm, and also how they are intended to be used in the *program code*. Like with any software, good design of the code and clear documentation are crucial for usability.

Throughout our discussion of AP software, we have promised composability and customizability of the algorithms. We note that merely using AP software to implement an algorithm does not guarantee that the algorithm will be composable. It is up to the creator of the algorithm to design the propagators so as to facilitate such desirable properties. However, we find that the paradigm of propagators is a good framework by which to construct an algorithm in a composable way. In particular, in Sec. 3.3 we highlight common propagator types that can lead to composable and flexible algorithms.

3.3 Example elementary propagators

In AP software, composability is achieved by deriving new propagators from already existing propagators. The simplest form of this may be to connect propagators into a chain, and activate their methods in sequence. In Proppo, we provide two propagators with such functionality, `ComboProp` and `ChainProp`. While both of these methods activate the forward and backward methods of the constituent propagators sequentially, they differ in how the messages and nodes are handled.

ComboProp. This propagator is a simple way to connect propagators into a chain. The output of the forward method of one propagator is fed into the input of the next propagator, and each propagator operates on the same node. Likewise, the backward methods use the data in the same node, and the messages are simply combined together and passed to the backward method of the previous propagator. `ComboProp` is suitable for simple combinations of propagators; however, it can run into problems when trying to implement more complex behaviors. Namely, the different propagators may overwrite data stored by other propagators leading to unexpected consequences.

ChainProp. This propagator provides a more systematic way to combine propagators, so as to overcome the sometimes unpredictable behavior of `ComboProp`. To rigorously define the behavior, `ChainProp` internally creates its own propagation graph, connecting nodes with propagators into a chain, and assigning a propagation manager to handle the message passing. The constituent propagators may themselves also be of the `ChainProp` type. This way, propagation graphs can be embedded into other propagation graphs, creating a hierarchy of connected propagators all handled by their own managers. This system allows safely composing propagators to define complex behaviors.

BackPropagator. This example propagator is often composed with a *base propagator* using `ComboProp`. In Pytorch, the `torch.autograd.backward(tensors, grad_tensors)` method allows inputting lists of tensors and gradients, so that the backpropagation can be commenced at multiple tensors at the same time using a single call. In the composition, the *base propagator* produces a tensor and the gradients, and `BackPropagator` commences the back propagation on the AD computation graph. Importantly, usually the config of the propagator allows determining whether `BackPropagator` should be included in the combo sequence or not. This is useful, if one wants to omit immediately backpropagating gradients in favor of grouping multiple tensors together and initiating each backprop simultaneously with a single call.

3.4 Example Monte Carlo gradient estimator propagators

One of our main motivations for developing AP software was to enable easy implementation of advanced MC gradient estimation methods, such as total propagation or Gaussian shaping gradients. We provide detailed pseudo code for these propagator implementations in App. B.2. Here, we briefly outline some of the more prominent propagator implementations.

Reparameterization. In PyTorch, RP gradients are already implemented, and it is possible to obtain reparameterized samples from a distribution, so that the gradients automatically flow through. Alternatively, the output can be detached, and the gradients passed backwards using `BackPropagator`.

Likelihood ratio. Typically, LR gradients are implemented in AD software by constructing a surrogate loss (Schulman et al., 2015) of the form $\log p(x; \theta) f(x)$, and then differentiating this w.r.t. θ to obtain the LR gradient. In Proppo, we do not need to construct such a surrogate loss. We instead store $\log p(x; \theta)$ in the node as a tensor, then during the backward pass, we set $f(x)$ as the input gradient, and back propagate it into $\log p(x; \theta)$, using the `BackPropagator` in Sec. 3.3.

Total propagation. TP requires storing both data for RP and LR in its node. In addition, it requires setting a target tensor in the AD computation graph where the variances of LR and RP will be computed for the inverse variance weighting. We implement this by storing a pointer to the target tensor, and use `torch.autograd.grad` to compute the LR and RP gradients. After computing the gradient variances, the mixture weight can be computed, and `BackPropagator` from Sec. 3.3 is used for one last back propagation with the combined gradient.

3.5 Implementation and computation speed considerations

Primarily, Proppo does not perform any major computations on its own; it merely manages the operations performed by other computational tools (Sec. 3). This overhead is negligible for moderate size computations as confirmed by benchmarking experiments (App. B.3) and real applications (Anonymous, 2022). Experiments also confirmed that Proppo can scale to millions of propagation nodes (App. B.4). The scalability could be further increased by running multiple propagation managers on the propagation graph in parallel, and we plan to implement this in future work.

4 Chaotic net minimalistic experiments for comparing gradient estimators

In this section we show minimalistic easily reproducible experiments using the Proppo framework. The main aim is to demonstrate that there exist situations where TP and GS gradients can improve the gradient accuracy by multiple orders of magnitude compared to conventional gradient estimation methods. The main result for TP is in Fig. 4, while the experiments for GS are in App. C.3.

4.1 Setup: gradient variance of a recurrent neural network with chaotic behavior

In our experiments, we estimate the gradient, g, of an expected loss $\mathbb{E}_{p(\boldsymbol{x}; \beta)}[f(\boldsymbol{x})]$, w.r.t. a parameter β, using various different MC gradient estimation methods. We repeat this estimation many times, and compute the empirical variance of the gradient estimators, $\hat{\mathbb{V}}[g]$, from the set of estimates $\{g^{(k)}\}_{k=1}^{K}$. In terms of the particular situation we consider, we were motivated by PIPPS (Parmas et al., 2018), where they showed a situation where chaos-like properties of the dynamics caused the RP gradient variance to explode, while LR gradients were robust. Parmas et al. (2018) considered a cart-pole swing-up and balancing task; while this task appears simple, there is still redundant complexity as the control policy had a high-dimensional parameter. Moreover, while the fractal input-output patterns that they visualized are strongly suggestive that the system was chaotic, it falls short of a rigorous proof. Therefore, we devised a similar simplified system based on a recurrent neural network (RNN).

We consider a particular 2-dimensional sigmoid recurrent neural network that was mathematically proven to exhibit chaotic behavior by Wang (1991). Formally, the system dynamics are given by

$$\boldsymbol{x}_{t+1} = \text{Sigmoid}(\beta W \boldsymbol{x}_t) + \varepsilon, \tag{2}$$

where $\text{Sigmoid}(y) \coloneqq \frac{1}{1+\exp(-y)}$, $W = \begin{bmatrix} -5 & 5 \\ -25 & 25 \end{bmatrix}$, β is the inverse temperature, a variable parameter of the network, $\varepsilon \sim \mathcal{N}(0, I\sigma^2)$ is Gaussian noise added to the state at each time step,[4] $\sigma = 0.001$ is the standard deviation of the added activation noise, and the initial state is $\boldsymbol{x}_0 = [0.35; 0.55]$. We use a batch size, $B = 1000$, and simulate this system for H time steps. We compute a quadratic loss at the final time step $L(\boldsymbol{x}_H) = \frac{1}{2}(\boldsymbol{x}_H - \mathbf{1})^{\mathsf{T}}(\boldsymbol{x}_H - \mathbf{1})$ and estimate the influence through all time steps to obtain the gradient w.r.t. β. Wang (1991) explained that β controls the dynamics of the system. When β is small, the system is well-behaved, but as β is increased, the system becomes chaotic through a period-doublings mechanism. We discuss this system in greater depth in App. C.1.

---

[4]Note that Wang (1991) did not add any noise to the system, but the system still shows similar behavior even when such noise is added. We added this noise to be able to use LR gradients.

(a) Variance of RP, LR and TP gradient estimators against the inverse temperature β for various horizons.

(b) Improvement of TP over the best between LR and RP for each β.

Figure 4: Comparison of the RP, LR and TP gradient estimators on the chaotic RNN task. See Sec. 4.1 and Fig. 9 for the description of the task, and Sec. 4.2 for the discussion of the experiment. The main result is that TP provides a large improvement at the edge of chaos regime around $\beta \sim 2.5$.

4.2 Single path experiment: showing the advantage of total propagation

Experimental setup. We consider an experiment on the simple RNN system (Sec. 4.1). We compute the gradient variances of RP, LR and TP gradients, and plot these against β. We considered the horizons $H \in \{10, 25, 50, 100\}$. The batch size was $B = 1000$ for 1 gradient estimate, $\boldsymbol{g}$ (averaged over the batch), and we performed this estimated $K = 800$ times. We compute the empirical gradient variance of the K estimates, $\{\boldsymbol{g}^{(k)}\}_{k=1}^{K}$. We use the percentile bootstrap method to estimate 95% confidence intervals. The results are in Fig. 4.

Results. The gradient variances are plotted in Fig. 4a. We see that RP is much more accurate than LR at low β, but the gradient variance of RP explodes as the system transitions to chaos around $\beta = 2.5$. This effect is stronger as the horizon is increased. Fig. 4b shows the ratio of improvement of TP over the best between RP and LR at each β. We see that around the edge of chaos at $\beta = 2.5$ TP improves by up to around 100 times compared to the best choice between RP and LR.

Discussion. Previously (Parmas et al., 2018) already showed an example where the RP gradient variance explodes. They also showed that LR was robust to this issue, and demonstrated that TP improves the performance. However, in their results, while the improvement of both TP and LR was huge compared to RP in the chaotic regime, the improvement of TP over LR was comparatively small, up to around a 3 times improvement. Here, on the other hand, we showed that TP can simultaneously improve over both RP and LR by multiple orders of magnitude. We also elucidated that the improvement may be particularly large at the edge of chaos. The simplicity of our RNN example allowed examining the advantage of TP in greater depth with better reproducibility.

In Fig. 4b, we have additionally plotted the performance for an optimal "naïve" gradient combination based on applying inverse variance weighting to LR and RP computed separately,[5] without taking advantage of the graph structure of the computations. Such a naïve method was first mentioned by Parmas et al. (2018) who immediately skipped it for TP, because of its conceptual issues; however,

---

[5]Strictly speaking, we did not actually combine the gradient estimates, but only computed the variance of an idealized version of this estimator by using the precise variances $\mathbb{V}[\boldsymbol{g}_{\mathrm{RP}}]$ and $\mathbb{V}[\boldsymbol{g}_{\mathrm{LR}}]$. In practice, one also has to estimate these variances and the mixing ratio from each batch of samples.

later Metz et al. (2019) "followed the insight" from Parmas et al. (2018) and used the naïve method in the context of metalearning. In Fig. 4b, we see that the naïve method performs poorly, leading to hardly any improvement in gradient accuracy compared to the best between RP and LR.

Indeed, when combining statistical estimators, the theoretical maximum accuracy is the sum of the accuracies of the individual estimators. If two estimators are equally good, this would maximally lead to a doubling of the accuracy. However, in Fig. 4b we see improvements far exceeding this limit. Such a result was possible because TP takes advantage of the graph structure of the computations. It not only improves the accuracy of the final result, it also improves the accuracy of the intermediate gradient computations that are propagated backwards. The improvements in the accuracy of the intermediate calculations have a compounding effect, leading to orders of magnitude improvement of the final result. This advantage of TP highlights that automatic propagation software such as Proppo can produce results unattainable by standard back propagation procedures.

5   Related work

From the point of view of MC gradient estimation, the concurrent work, Storchastic (Krieken et al., 2021) is the most closely related to ours. Storchastic is a library for MC gradient estimation implemented in PyTorch based on the surrogate loss formalism (Schulman et al., 2015; Foerster et al., 2018). Their user interface of using a `.backward()` function is similar to ours, as both were inspired by the PyTorch interface that is the same. However, Storchastic is not an AP software, and for instance, it does not enable implementing Total Propagation.

From a conceptual point of view, the Actor Model (Hewitt et al., 1973) is related. In the Actor Model, everything in the program are actors and they communicate with each other via message passing. However, practically, Proppo is not implemented as an actor system. Unlike in an actor system, the propagators acting at the nodes can interact with outside objects directly without explicitly implemented messaging mechanisms. From a theoretical point of view, one could consider these interactions as "passing messages" but practically, these interactions are not implemented based on the actor formalism. Instead, AP software aims to be pragmatic and flexible to enable interusability with existing ML tools. A further difference is that AP automates the default messaging targets. Prominent Actor Model implementations, such as Akka (Boner et al., 2010) are typically used for server and web apps, and they are not primarily meant for implementing machine learning algorithms. Nevertheless, studying existing actor systems may inspire improvements to AP implementations.

6   Discussion & Conclusions

Recently, many impressive results were achieved by leveraging large scale data and computation together with basic algorithms (Brown et al., 2020; Ramesh et al., 2022; Chowdhery et al., 2022). We ask whether simple algorithms are used, simply because researchers and engineers have difficulty with properly implementing more complicated ones? There is no guarantee that merely scaling up our existing algorithms will be sufficient for satisfactory performance in the long term of ML research; we must also explore algorithmic improvements. We hope that automatic propagation will enable the proliferation of complex algorithms by providing a standard for sharing and building ML tools.

Author Contributions

Paavo Parmas invented automatic propagation software, designed and implemented most of the code including the key parts, ran the experiments, and wrote the paper.
Takuma Seno worked part-time to help write the code and give advice on the software engineering aspects in the early stages of the project. He also gave comments on the paper.

Acknowledgements

The project was started with funding provided by the Proof of Concept Program at the Okinawa Institute of Science and Technology (OIST). Most of the key contributions were made during this stage. PP finished the project while hired under the Cyborg-AI project supported by NEDO, Japan. PP would like to thank the Neural Computation Unit at OIST for administrative support while the project was being conducted at OIST.

References

Abadi, M., Barham, P., Chen, J., Chen, Z., Davis, A., Dean, J., Devin, M., Ghemawat, S., Irving, G., Isard, M., et al. (2016). TensorFlow: A system for Large-Scale machine learning. In *12th USENIX symposium on operating systems design and implementation (OSDI 16)*, pages 265–283. 1

Agha, G. (1986). *Actors: a model of concurrent computation in distributed systems*. 1

Anonymous (2022). Anonymous. In *Anonymous*, page 0000. 1, 3.5, B.3

Barham, P. and Isard, M. (2019). Machine learning systems are stuck in a rut. In *Proceedings of the Workshop on Hot Topics in Operating Systems*, pages 177–183. 1

Bauer, F. L. (1974). Computational graphs and rounding error. *SIAM Journal on Numerical Analysis*, 11(1):87–96. 2.1

Baydin, A. G., Pearlmutter, B. A., Radul, A. A., and Siskind, J. M. (2018). Automatic differentiation in machine learning: a survey. *Journal of Marchine Learning Research*, 18:1–43. 2.1

Boner, J. et al. (2010). Akka. `https://akka.io/`. 5

Bradbury, J., Frostig, R., Hawkins, P., Johnson, M. J., Leary, C., Maclaurin, D., Necula, G., Paszke, A., VanderPlas, J., Wanderman-Milne, S., and Zhang, Q. (2018). JAX: composable transformations of Python+NumPy programs. 1

Brown, T., Mann, B., Ryder, N., Subbiah, M., Kaplan, J. D., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., et al. (2020). Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901. 6

Chollet, F. et al. (2015). Keras. `https://keras.io`. 1

Chowdhery, A., Narang, S., Devlin, J., Bosma, M., Mishra, G., Roberts, A., Barham, P., Chung, H. W., Sutton, C., Gehrmann, S., et al. (2022). Palm: Scaling language modeling with pathways. *arXiv preprint arXiv:2204.02311*. 6

Dangel, F., Kunstner, F., and Hennig, P. (2020). BackPACK: Packing more into backprop. In *International Conference on Learning Representations*. 1

Fairbank, M. (2008). Reinforcement learning by value gradients. *arXiv preprint arXiv:0803.3539*. A.2

Foerster, J., Farquhar, G., Al-Shedivat, M., Rocktäschel, T., Xing, E., and Whiteson, S. (2018). Dice: The infinitely differentiable Monte Carlo estimator. In *International Conference on Machine Learning*, pages 1529–1538. 1, 5

Gardner, J., Pleiss, G., Weinberger, K. Q., Bindel, D., and Wilson, A. G. (2018). Gpytorch: Blackbox matrix-matrix gaussian process inference with gpu acceleration. *Advances in neural information processing systems*, 31. 1

Glynn, P. W. (1990). Likelihood ratio gradient estimation for stochastic systems. *Communications of the ACM*, 33(10):75–84. 2.2

Greensmith, E., Bartlett, P. L., and Baxter, J. (2004). Variance reduction techniques for gradient estimates in reinforcement learning. *Journal of Machine Learning Research*, 5(Nov):1471–1530. A.1

Hafner, D., Lillicrap, T., Ba, J., and Norouzi, M. (2020). Dream to control: Learning behaviors by latent imagination. In *International Conference on Learning Representations*. 1

Harris, C. R., Millman, K. J., van der Walt, S. J., Gommers, R., Virtanen, P., Cournapeau, D., Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., van Kerkwijk, M. H., Brett, M., Haldane, A., del Río, J. F., Wiebe, M., Peterson, P., Gérard-Marchant, P., Sheppard, K., Reddy, T., Weckesser, W., Abbasi, H., Gohlke, C., and Oliphant, T. E. (2020). Array programming with NumPy. *Nature*, 585(7825):357–362. 1

Hewitt, C., Bishop, P., and Steiger, R. (1973). A universal modular actor formalism for artificial intelligence. In *Proceedings of the 3rd international joint conference on Artificial intelligence*, pages 235–245. 1, 5

Hewitt, C. and Lieberman, H. (1983). Design issues in parallel architecture for artificial intelligence. In *In Proc. 28th IEEE Computer Society Int. Conf,, San Francisco CA*. Citeseer. 1

Ingraham, J., Riesselman, A., Sander, C., and Marks, D. (2019). Learning protein structure with a differentiable simulator. In *International Conference on Learning Representations*. C.1

Jankowiak, M. and Obermeyer, F. (2018). Pathwise derivatives beyond the reparameterization trick. In *International Conference on Machine Learning*, pages 2240–2249. A.1

Kingma, D. P. and Welling, M. (2013). Auto-encoding variational Bayes. *arXiv preprint arXiv:1312.6114*. 2.2

Krieken, E., Tomczak, J., and Ten Teije, A. (2021). Storchastic: A framework for general stochastic automatic differentiation. *Advances in Neural Information Processing Systems*, 34. 1, 5

Maclaurin, D., Duvenaud, D., and Adams, R. (2015). Gradient-based hyperparameter optimization through reversible learning. In *International conference on machine learning*, pages 2113–2122. PMLR. C.1

McEliece, R. J., MacKay, D. J. C., and Cheng, J.-F. (1998). Turbo decoding as an instance of pearl's" belief propagation" algorithm. *IEEE Journal on selected areas in communications*, 16(2):140–152. 1

Metz, L., Maheswaranathan, N., Nixon, J., Freeman, C. D., and Sohl-Dickstein, J. (2019). Understanding and correcting pathologies in the training of learned optimizers. In *International Conference on Machine Learning*. 4.2, C.1

Minka, T. (2019). From automatic differentiation to message passing. Slides for Presentation at Advances and challenges in machine learning languages workshop. [Online; https://tminka.github.io/papers/acmll2019/minka-acmll2019-slides.pdf]. 1

Minka, T. P. (2001). Expectation propagation for approximate bayesian inference. In *Proceedings of the Seventeenth conference on Uncertainty in artificial intelligence*, pages 362–369. 1

Mohamed, S., Rosca, M., Figurnov, M., and Mnih, A. (2020). Monte Carlo gradient estimation in machine learning. *Journal of Machine Learning Research*, 21:1–62. 2.2

Moritz, P., Nishihara, R., Wang, S., Tumanov, A., Liaw, R., Liang, E., Elibol, M., Yang, Z., Paul, W., Jordan, M. I., et al. (2018). Ray: A distributed framework for emerging AI applications. In *13th USENIX Symposium on Operating Systems Design and Implementation (OSDI 18)*, pages 561–577. 1

Oktay, D., McGreivy, N., Aduol, J., Beatson, A., and Adams, R. P. (2020). Randomized automatic differentiation. In *International Conference on Learning Representations*. 1

Owen, A. B. (2013). *Monte Carlo theory, methods and examples*. A.1

Parmas, P. (2018). Total stochastic gradient algorithms and applications in reinforcement learning. In *Advances in Neural Information Processing Systems*, pages 10204–10214. 1, A.1, A.2, A.2, A.2, A.2, A.2, C.3

Parmas, P. (2020). *Total stochastic gradient algorithms and applications to model-based reinforcement learning*. PhD thesis, Okinawa Institute of Science and Technology Graduate University. 1, A.1

Parmas, P., Rasmussen, C. E., Peters, J., and Doya, K. (2018). PIPPS: Flexible model-based policy search robust to the curse of chaos. In *International Conference on Machine Learning*, pages 4062–4071. 1, 2.2, 4.1, 4.2, A.1, A.2, A.2, C.1, 8

Parmas, P. and Sugiyama, M. (2021). A unified view of likelihood ratio and reparameterization gradients. In *International Conference on Artificial Intelligence and Statistics*, pages 4078–4086. PMLR. A.1

Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., et al. (2019). Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32. 1

Paszke, A., Johnson, D. D., Duvenaud, D., Vytiniotis, D., Radul, A., Johnson, M. J., Ragan-Kelley, J., and Maclaurin, D. (2021). Getting to the point: index sets and parallelism-preserving autodiff for pointful array programming. *Proceedings of the ACM on Programming Languages*, 5(ICFP):1–29. 1

Pearl, J. (1982). Reverend bayes on inference engines: a distributed hierarchical approach. In *Proceedings of the Second AAAI Conference on Artificial Intelligence*, pages 133–136. 1, B.1

Ramesh, A., Dhariwal, P., Nichol, A., Chu, C., and Chen, M. (2022). Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*. 6

Rezende, D. J., Mohamed, S., and Wierstra, D. (2014). Stochastic backpropagation and approximate inference in deep generative models. In *International Conference on Machine Learning*, pages 1278–1286. 2.2, A.1

Rogozhnikov, A. (2021). Einops: Clear and reliable tensor manipulations with einstein-like notation. In *International Conference on Learning Representations*. 1

Schulman, J., Heess, N., Weber, T., and Abbeel, P. (2015). Gradient estimation using stochastic computation graphs. In *Advances in Neural Information Processing Systems*, pages 3528–3536. 1, 3.4, 5, A.1

Silver, D., Lever, G., Heess, N., Degris, T., Wierstra, D., and Riedmiller, M. (2014). Deterministic policy gradient algorithms. In *International conference on machine learning*, pages 387–395. PMLR. A.2

Suh, H. J., Simchowitz, M., Zhang, K., and Tedrake, R. (2022). Do differentiable simulators give better policy gradients? In *International Conference on Machine Learning*, pages 20668–20696. PMLR. C.1

Sutton, R. S., McAllester, D. A., Singh, S. P., and Mansour, Y. (2000). Policy gradient methods for reinforcement learning with function approximation. In *Advances in neural information processing systems*, pages 1057–1063. A.2

Tokui, S., Oono, K., Hido, S., and Clayton, J. (2015). Chainer: a next-generation open source framework for deep learning. In *Proceedings of workshop on machine learning systems (LearningSys) in the twenty-ninth annual conference on neural information processing systems (NIPS)*, volume 5, pages 1–6. 1

Tran, D., Kucukelbir, A., Dieng, A. B., Rudolph, M., Liang, D., and Blei, D. M. (2016). Edward: A library for probabilistic modeling, inference, and criticism. *arXiv preprint arXiv:1610.09787*. 1

Wang, Q. (2013). Forward and adjoint sensitivity computation of chaotic dynamical systems. *Journal of Computational Physics*, 235:1–13. C.1

Wang, X. (1991). Period-doublings to chaos in a simple neural network: An analytical proof. *Complex Systems*, 5(4):425–441. 4.1, 4.1, 4, C.1, 8

Weaver, L. and Tao, N. (2001). The optimal reward baseline for gradient-based reinforcement learning. In *Proceedings of the Seventeenth conference on Uncertainty in artificial intelligence*, pages 538–545. Morgan Kaufmann Publishers Inc. A.1

Williams, R. J. (1992). Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256. 2.2

Wu, Z., Pan, S., Chen, F., Long, G., Zhang, C., and Philip, S. Y. (2020). A comprehensive survey on graph neural networks. *IEEE transactions on neural networks and learning systems*, 32(1):4–24. 1

Xu, J., Makoviychuk, V., Narang, Y., Ramos, F., Matusik, W., Garg, A., and Macklin, M. (2021). Accelerated policy learning with parallel differentiable simulation. In *International Conference on Learning Representations*. C.1

Appendices: ◄⊙►Proppo: a Message Passing Framework for Customizable and Composable Learning Algorithms

A Monte Carlo gradient estimators

A.1 Basic Monte Carlo gradient estimation

In this section we provide additional background explanations on the two main gradient estimators: reparameterization gradients (RP) and likelihood ratio gradients (LR). Both are MC gradient estimation methods, i.e., they provide estimators, $\hat{g}$, s.t. $\mathbb{E}\left[\hat{g}\right] = \frac{\mathrm{d}}{\mathrm{d}\beta}\mathbb{E}_{\boldsymbol{x}\sim p(\boldsymbol{x};\beta)}\left[f(\boldsymbol{x})\right]$.

RP. In RP, one samples from a simple fixed distribution $\varepsilon \sim p(\boldsymbol{\varepsilon})$, and one defines a transformation, $\mathcal{T}$, dependent on β s.t. $\mathcal{T}(\boldsymbol{\varepsilon};\beta)$ has the same distribution as a sample from the original distribution $\boldsymbol{x} \sim p(\boldsymbol{x};\beta)$. Then, the derivative can be pushed inside the expectation, and the gradient can be estimated as

$$\frac{\mathrm{d}}{\mathrm{d}\beta}\mathbb{E}_{\boldsymbol{x}\sim p(\boldsymbol{x};\beta)}\left[f(\boldsymbol{x})\right] = \mathbb{E}_{\boldsymbol{\varepsilon}\sim p(\boldsymbol{\varepsilon})}\left[\frac{\mathrm{d}}{\mathrm{d}\beta}f\big(\mathcal{T}(\boldsymbol{\varepsilon};\beta)\big)\right] = \mathbb{E}_{\boldsymbol{\varepsilon}\sim p(\boldsymbol{\varepsilon})}\left[\frac{\mathrm{d}f}{\mathrm{d}\boldsymbol{x}}\frac{\mathrm{d}\mathcal{T}(\boldsymbol{\varepsilon};\beta)}{\mathrm{d}\beta}\right]. \tag{3}$$

For example, for a 1-dimensional Gaussian distribution $\mathcal{N}(x;\mu,\sigma)$, one possible reparameterization is $\mathcal{T}(\varepsilon;\mu,\sigma) = \mu + \varepsilon\sigma$, where $\varepsilon \sim \mathcal{N}(\varepsilon;0,1)$, and then $\frac{\mathrm{d}\mathcal{T}}{\mathrm{d}\mu} = 1$ and $\frac{\mathrm{d}\mathcal{T}}{\mathrm{d}\sigma} = \varepsilon$.

LR. While RP used the gradient of f to construct an estimator, LR, instead, uses its value. The LR gradient estimator is characterized by the equation

$$\frac{\mathrm{d}}{\mathrm{d}\beta}\mathbb{E}_{\boldsymbol{x}\sim p(\boldsymbol{x};\beta)}\left[f(\boldsymbol{x})\right] = \mathbb{E}_{\boldsymbol{x}\sim p(\boldsymbol{x};\beta)}\left[\frac{\mathrm{d}\log p(\boldsymbol{x};\beta)}{\mathrm{d}\beta}(f(\boldsymbol{x}) - b)\right], \tag{4}$$

where b is a baseline for variance reduction, often computed as the batch mean of the samples $b = \frac{1}{B}\sum_{i=1}^{B}f(\boldsymbol{x}^{(i)})$.

Both LR and RP estimators are interchangeable (as long as the gradients and value of f are available), and which one is better depends on the specific situation. While RP tends to handle high dimensional spaces better (Rezende et al., 2014), it often fails on long computation graphs (Parmas et al., 2018). On the other hand, LR has robust behavior, and does not require access to ∇f, but does not scale well with the dimensionality. The two estimators were recently unified by Parmas and Sugiyama (2021) based on an intuititve probability flow theory related to the work of Jankowiak and Obermeyer (2018).

A key metric to determine which gradient estimator is effective is the *variance* of the gradient estimator, $\mathbb{V}\left[\hat{g}\right]$. The variance can be reduced by a factor $1/K$ by computing K samples of the same estimator and averaging; therefore, we could consider a reduction in the gradient variance by a factor K to be roughly equivalent to increasing the computation speed by a K factor.[6] For this reason, much research on MC gradient estimators has focused on reducing the variance, primarily by using control variates and baselines (Greensmith et al., 2004; Weaver and Tao, 2001); or conditioning and importance sampling (Owen, 2013). Another line of research takes advantage of the graph structure of the computations to obtain more accurate gradient estimates (Parmas et al., 2018; Parmas, 2018, 2020). While the former methods are readily implemented using the surrogate loss formalism (Schulman et al., 2015), the latter methods are not easily implemented, motivating the creation of Proppo.

In this section, we discussed how the basic estimators are implemented through a single sampling operation. In the next section, we discuss graphs with multiple stochastic operations, and also introduce the total propagation and Gaussian shaping gradient methods, which take advantage of this graph structure.

A.2 Monte Carlo gradient estimation on Probabilistic Computation Graphs

In the deterministic case, the total derivative intuitively decomposes into a sum across the paths as shown in Eq. (1); Parmas (2018) explained that a similar framework can be employed for stochastic graphs, using their probabilistic computation graph (PCG) formalism. In a PCG, we note that while the sampling operations themselves are *stochastic*, the relationship between the marginal distributions

---

[6]Note that in practice parallel computation may allow increasing the batch size without proportionally increasing the computation time, if the computational resources are not already maxed out. Moreover, reducing the gradient variance by a factor K may not guarantee proportionally faster optimization because increasing the gradient accuracy has diminishing returns once the gradient is sufficiently accurate.

at nodes is *deterministic*. Therefore, by denoting $\zeta_{\boldsymbol{x}_i}$ as the abstract parameters of the marginal distribution at the node i, and replacing the usual derivative with functional derivatives between the probability distributions, we can obtain a similar decomposition of the total gradient as in Eq. (1)

$$\frac{\mathrm{d}\zeta_y}{\mathrm{d}\beta} = \sum_{\mathrm{Path}\in\mathrm{Paths}[\boldsymbol{\beta}\rightarrow y]} \prod_{\mathrm{Edge}[l\rightarrow k]\in\mathrm{Path}} \frac{\partial\zeta_{\boldsymbol{x}_k}}{\partial\zeta_{\boldsymbol{x}_l}} \tag{5}$$

Parmas (2018) proposed a further decomposition by assigning a set of intermediate nodes $\mathcal{N}$, and considering the paths passing through the nodes $n\in\mathcal{N}$ giving the equation

$$\frac{\mathrm{d}\zeta_y}{\mathrm{d}\beta} = \sum_{n\in\mathcal{N}} \left(\sum_{\mathrm{Path}\in\mathrm{Paths}[n\rightarrow y]} \prod_{\mathrm{Edge}[l\rightarrow k]\in\mathrm{Path}} \frac{\partial\zeta_{\boldsymbol{x}_k}}{\partial\zeta_{\boldsymbol{x}_l}} \right) \left(\sum_{\mathrm{Path}\in\mathrm{Paths}[\beta\rightarrow n]\setminus\mathcal{N}} \prod_{\mathrm{Edge}[l\rightarrow k]\in\mathrm{Path}} \frac{\partial\zeta_{\boldsymbol{x}_k}}{\partial\zeta_{\boldsymbol{x}_l}} \right),$$
$$\tag{6}$$

where $\mathrm{Paths}[\beta\rightarrow n]\setminus\mathcal{N}$ denotes the paths going from β to n, but not passing through nodes in $\mathcal{N}$. Parmas (2018) further showed that Eqs. (5) and (6) can be combined to yield

$$\frac{\mathrm{d}\zeta_y}{\mathrm{d}\beta} = \sum_{n\in\mathcal{N}} \frac{\mathrm{d}\zeta_y}{\mathrm{d}\zeta_n} \left(\sum_{\mathrm{Path}\in\mathrm{Paths}[\beta\rightarrow n]\setminus\mathcal{N}} \prod_{\mathrm{Edge}[l\rightarrow k]\in\mathrm{Path}} \frac{\partial\zeta_{\boldsymbol{x}_k}}{\partial\zeta_{\boldsymbol{x}_l}} \right), \tag{7}$$

and they explained that this equation generalizes the deterministic and stochastic policy gradient theorems (Sutton et al., 2000; Silver et al., 2014). In particular, the $\frac{\mathrm{d}\zeta_y}{\mathrm{d}\zeta_n}$ terms are estimated by total derivative estimators, such as LR or value gradient methods (Fairbank, 2008), whereas the effect of the local partial derivatives, $\frac{\partial\zeta_{\boldsymbol{x}_k}}{\partial\zeta_{\boldsymbol{x}_l}}$, is estimated by pathwise estimators, such as direct differentiation or RP. They also proposed more advanced estimators: total propagation that combines RP and LR (Parmas et al., 2018) and Gaussian shaping gradients that use a different decomposition of the paths to obtain a gradient estimator (Parmas, 2018).

Total propagation (TP). Inverse variance weighting is the optimal method to take a weighted average of two uncorrelated statistical estimators, as is well known in statistics. The TP method (Parmas et al., 2018) uses this weighting scheme to obtain a weighted average of LR and RP, based on the observation that both estimators are interchangeable. In particular, it performs the computation $\hat{\boldsymbol{g}}_{\mathrm{TP}} = k\hat{\boldsymbol{g}}_{\mathrm{LR}} + (1-k)\hat{\boldsymbol{g}}_{\mathrm{RP}}$, where $k = \mathbb{V}[\hat{\boldsymbol{g}}_{\mathrm{RP}}]/(\mathbb{V}[\hat{\boldsymbol{g}}_{\mathrm{LR}}] + \mathbb{V}[\hat{\boldsymbol{g}}_{\mathrm{RP}}])$, i.e. it picks $k \propto \frac{1}{\mathbb{V}[\hat{\boldsymbol{g}}_{\mathrm{LR}}]}$ and $(1-k) \propto \frac{1}{\mathbb{V}[\hat{\boldsymbol{g}}_{\mathrm{RP}}]}$. The gradient variances for computing the weights are obtained from the empirical variances of the gradient samples. Moreover, TP is not a simple combination of the two estimators computed separately on the whole graph, instead, it combines the two estimates at each sampling node, and propagates the combined gradient backwards, potentially leading to much increased accuracy (the advantage is experimentally clear in Sec. 4.2). However, this kind of gradient variance estimation during the backward computation poses problems for existing AD software, as it cannot be implemented by differentiating a surrogate loss.

Gaussian shaping gradients (GS). The GS method (Parmas, 2018) is interesting because it allows obtaining an LR type gradient estimator while using ∇f instead of f as is usual in LR gradients. This allows better scalability with the dimensionality compared to a regular LR method, as we show experimentally in Sec. C.3. The basic idea is to assume a Gaussian density with parameters $\boldsymbol{\mu}$ and Σ at a distal node n, then construct an LR-type gradient estimator for these parameters, estimating the gradients $\frac{\mathrm{d}\boldsymbol{\mu}}{\mathrm{d}\boldsymbol{x}}$ and $\frac{\mathrm{d}\Sigma}{\mathrm{d}\boldsymbol{x}}$. Assuming a cost function $c(\boldsymbol{x}_n)$ that depends on $\boldsymbol{x}_n$, we can resample points on the approximated Gaussian distribution, estimate the gradients $\frac{\mathrm{d}\mathbb{E}[c]}{\mathrm{d}\boldsymbol{\mu}}$ and $\frac{\mathrm{d}\mathbb{E}[c]}{\mathrm{d}\Sigma}$ and apply the chain rule to obtain the total gradient from $\boldsymbol{x}$ to c. The final algorithm resembles LR, except that the usual f multiplier is replaced with a different scalar given by the dot product of some statistics of the distribution at $\boldsymbol{x}_n$ with $\frac{\mathrm{d}\mathbb{E}[c]}{\mathrm{d}\boldsymbol{\mu}}$ and $\frac{\mathrm{d}\mathbb{E}[c]}{\mathrm{d}\Sigma}$. Similarly to TP, this method is also cumbersome to implement by differentiating a surrogate loss, but can be intuitively expressed as a message passing program that can be implemented in Proppo.

B Automatic Propagation software: additional details and experiments

B.1 A generalized view of automatic propagation software

In the main contents, we introduced AP software from the viewpoint of Proppo, our prototype implementation of an AP library. We did this to provide a concrete example to aid in clarity. More generally, AP software may have many more features than introduced, or on the contrary, it may also be more minimalistic than our example with Proppo. In this section we aim to clarify what type of additional features we foresee to be useful for AP software, and also to clarify what are the minimum requirements for something to qualify as an AP library.

First, we note that it may be useful for the `forward` computations to also be able to send messages. Moreover, it can be beneficial for the forward methods to be able to pass information to the propagation manager, so as to automate the choice of propagators for subsequent nodes. In fact, Proppo already implements such automation in the choice of the configuration for the loss propagators depending on what type of MC gradient estimator was previously used. This observation points toward generalizations concerning the methods of the propagators as well as the managers.

Regarding the propagators, in our discussion we limited the computations to `forward` and `backward` computations. However, there is no need for such a restriction, and in general we require propagators to implement *types* of computations, where `forward` and `backward` are just two possible types. The different types of computations can in general access and modify the memory in the node, and may send messages to other nodes. We note that the distinction between types of computations is superficial because the multiple types of computations may also be embedded into a single type of computation, where an input can be passed to switch between the different embedded computations.

Regarding the propagation manager, this was merely our choice of implementation to keep track of the propagation graph, automatically decide on the order of activating the propagators, and to deal with passing the messages. Any other method to implement such functionality would also be allowed.

In summary the crucial aspects to automatic propagation software are:

1. Nodes that can store information.

2. Propagators that can be associated to the nodes. The propagators have user programmable methods that can directly modify the information in the nodes that they are linked to, and can indirectly influence other nodes by sending them messages containing general information.

3. The methods of the propagators may directly interact with processes and information external to the nodes.

4. When a message is sent from a propagator operating at a node, if a target for the message was not explicitly specified by the user, a default target is determined.

5. It is possible to trigger the system so that the propagators at multiple nodes are automatically activated in sequence.

Regarding points 4 and 5, we envision that typically the nodes will be arranged in an acyclic directed graph structure, and the system can be triggered to traverse the graph backwards, activating the `backward` method of the propagator at each node, and sending the messages to the parent nodes. Even if the contents of a message are not intended to be used by a direct parent node, but they are meant for a node earlier in the graph, as long as this message is continually routed backwards it will eventually reach the target destination. Thus we envision that such a default setting will allow implementing a wide range of algorithms. In fact, there already exist many prominent machine learning algorithms that operate purely based on sending messages backwards locally, e.g. back propagation or belief propagation (Pearl, 1982).

B.2 Examples of propagators and their details: customizability and composability

In this section we aim to illustrate the composability and customizability that can be achieved in AP software. These properties are achieved by using the sequence propagators described in Sec. 3.3. These propagators allow combining multiple propagators together into a sequence to compose new propagators. The forward and backward methods of the propagators will be activated in sequence.

One of our main design patterns to effectively use these sequence propagators is to create a base propagator for each non-trivial functionality that we want to implement. Then we plug these base propagators together into a chain to achieve all of the desired properties. Some of these base propagators may be reused across many different composite propagators, allowing to create compact code. For example the `BackPropagator` in Sec. 3.3 can be combined with many different MC gradient estimation propagators to initialize the back propagation of the gradients.

Another feature of the sequence propagators is that they allow optional propagators in the sequence. These optional propagators can be turned on or off using keyword arguments when instantiating the propagator from the class. Essentially, this allows creating a factory for a composite propagator with a rich configuration space. In the following, we give pseudocode and details of several MC gradient estimation propagators, their constituent propagators, and explain how they interact.

BackPropagator

This propagator commences backpropagating the gradients at a computation node.

Forward:
```
pass
```

The forward method does not do anything, as this propagator is designed to be combined together with other propagators that will perform the necessary forward computations.

Backward:
```
get from message:  tensors, grad_tensors
call:  torch.autograd.backward(tensors, grad_tensors)
```

The backward method retrieves the tensors and gradients, and backpropagates them using AD software as explained in Sec. 2. One of the propagators that can be combined together with `BackPropagator` is `RPBase` for reparameterization gradients explained next.

RPBase

This is the base propagator for reparameterization gradients. It injects reparameterized noise into an input variable, and allows backpropagating through this stochasticity.

Forward:
```
input from program code:  x
inject reparameterized noise into x
store into node:  output, detached output
```

Backward:
```
get grads from detached output
message:  (output, grads)
```

Note that the backward method does not backpropagate the gradients on the computation graph. It merely forms the pair of the output node and its corresponding gradient. To have this gradient be backpropagated as well, the following compound `RPProp` propagator can be used.

RPProp

This propagator applies the reparameterization transformations and also automatically commences the backpropagation on the computation graph.

Sequence: `[Optional(BackPropagator), RPBase]`

Here we used the `Optional()` notation to mean that the `BackPropagator` can be either included or omitted using a keyword, i.e., `RPProp(backprop=False)` would omit the `BackPropagator`. If it is included, then having simply plugged these two propagators together causes the gradients to be backpropagated on the computation graph as well—`RPBase` will form the (`tensors`, `grad_tensors`) pair, and `BackPropagator` will commence the back propagation.

LossBase

In many machine learning tasks, there are loss nodes that we want to propagate gradients from. Moreover, for likelihood ratio gradient estimators, we may also want to send the value of the loss itself backwards as well. This propagator implements the required base functionality.

Configuration: whether gradients are needed or not

Forward:
```
compute loss
store loss in the node
```

Backward:
```
get from message:  incoming sum of losses
optional:  create tensors and grad_tensors for the loss
optional:  sum new loss with incoming losses
message:  [(tensors, grad_tensors), sum of losses]
```

LossProp

To add automatic gradient backpropagation, or baseline computations to the loss node, we create a compound propagator with the following sequence.

Sequence: [Optional(BackPropagator), Optional(BaselineProp), LossBase]

BaselineProp

In LossProp, one part of the sequence was the baseline propagator. The baseline propagator subtracts a baseline from the sum of the loss to reduce the likelihood ratio gradient variance.

Configuration: the type of baseline function to use, e.g., subtract the mean

Forward:
```
pass
```

Like the BackPropagator, the baseline propagator is also designed to be used together with other propagators, and it does not need its own forward method.

Backward:
```
compute baseline
subtract baseline from losses
message:  loss with baseline subtracted
```

LRBase

This propagator implements the base functionality for using likelihood ratio gradient estimators.

Forward:
```
input from program code:  x
inject noise into x
compute log p(x)
store into node:  log p(x)
```

Backward:
```
get from message:  incoming loss with the baseline subtracted if available
get from node:  log p(x)
message:  (tensors=log p(x), grad_tensors=loss)
```

LRProp

This propagator adds optional backpropagation and baseline functionality to the base propagator for LR gradients.

Sequence: `[Optional(BackPropagator), LRBase, Optional(BaselineProp)]`

Notice that in `LRProp` the `BaselineProp` is at the right side of the sequence, whereas for `LossProp` it is at the left side. The backward sequence commences from right to left. In the `LRProp` case, we want to subtract the baseline before estimating the LR gradient, whereas in the `LossProp` case, we want to subtract the baseline in the end, after having computed the loss. Which one is better is problem dependent—if there is a single loss node, but many LR nodes, it may be better to subtract the baseline at the loss node, and *vice versa*.

TPBase

This is the base propagator for the most complicated propagator we show in our examples here—it implements the computations for the total propagation algorithm.

Configuration: what node to use for inverse variance weighting

Forward:
```
input from program code:  x
inject reparameterized noise into x
compute log p(x)
store into node:  log p(x), output, detached output
```

Backward:
```
get from message:  incoming loss with the baseline subtracted if available
get from node:  log p(x), output, detached output
get grads from detached output
compute LR and RP gradients until the inverse gradient variance node
perform inverse variance weighting and compute the mixing ratio, k
message:  (tensors=[log p(x), x], grad_tensors=[k*loss, (1-k)*grads])
```

Note that here we are packing two sets of `tensors` and `grad_tensors` together into a list. The `torch.autograd.backward()` function that is called in `BackPropagator` can handle lists of such pairs, and simultaneously invoke the backpropagtion, so there is no issue.

TotalProp

Finally, this propagator adds the back propagation and baseline functionalities to the base propagator for TP gradients.

Sequence: `[Optional(BackPropagator), TPBase, Optional(BaselineProp)]`

B.3 Computational time comparison

Setup. To give an indication of the overhead in computational time caused by using Proppo, we perform experiments with a similar recurrent neural network as in Sec. 4.1, but while varying the batch size (Fig. 5) or dimensionality (Fig. 6). When varying the batch size, the dimensionality was fixed to 500; and when varying the dimensionality, the batch size was fixed to 1000. The horizon was 10. We performed the forward and backward computations 100 times and estimated the average computation time both on a CPU and on a GPU. The computation times were normalized with the minimum computation time at the corresponding setting to better highlight the ratio difference. We compared the computation times of RP, LR, TP and when implementing RP without using Proppo. Moreover, for RP, we test two implementations: one which detaches the tensors at each propagation node, and manually back propagates the gradients; and another that does not detach the tensors, and allows PyTorch to handle the gradient back propagation.

Discussion.   In the results in Figs. 5 and 6 we see that for very small problem sizes, Proppo causes a significant overhead, but as the problem size becomes larger, the overhead becomes negligible. For large problem sizes, typically TP required 2 times more computational time. Compared to a 100 time reduction in gradient variance (Sec. 4.1), this additional computational time is negligible (note that the naïve way to reduce gradient variance by a factor K is to increase the batch size by the same factor K roughly requiring K times more computational time). We also note that in a typical full implementation of an ML algorithm, Proppo may be used in only some section of the computations. In this case, the overhead caused by Proppo may be only a small fraction of the total computational time associated with the algorithm. We observed this point in our concurrent work in model-based reinforcement learning (Anonymous, 2022), where the total change in computational time was typically less than 50% extra.

Another point to note is the difference between the used *framework* and *implementation* of an algorithm. The performance will primarily depend on the implementation. Proppo allows creating multiple implementations, fast or slow ones (e.g., compare the two implementations of RP). The main point is not so much that the computation time might increase a bit if Proppo is used, but rather that using Proppo enables implementing algorithms that would be cumbersome to implement otherwise. The current implementations are also not fully tuned, and can be implemented to run faster. In particular, the implementation of TP has issues with scalability if the number of parameters used for the inverse variance weighting becomes large, but we have found sensible solutions to this issue in our concurrent work (Anonymous, 2022).

Figure 5: Computation times of algorithms in Proppo when varying the batch size (Sec. B.3).

(a) Computation time on a CPU

(b) Computation time on a GPU

Figure 6: Computation times of algorithms in Proppo when varying the dimensionality (Sec. B.3).

B.4 Scaling with the number of nodes

Setup. We perform an experiment to test how Proppo scales with the number of propagation nodes. In the experiment, we connect nodes into a chain with a dummy propagator that performs no computations, but merely stores an empty node in the forward pass, and sends empty messages in the backwards pass. This experiment allows testing the overhead associated with the "bookkeeping" performed by Proppo. We ran 10 experiments, and averaged the elapsed time. We tested values between 10 and 10^7 nodes, and the experiment was performed on an Intel i9 CPU. In Fig. 7, we show the results separately for the forward and backwards pass, as well as the total elapsed time.

Discussion. The results in Fig. 7 show that the computation time increases linearly. In particular, we see that the time spent per node is roughly 10^{-6} seconds. This means that if the computations performed by the propagator take longer than 10^{-6} seconds, we would expect the additional overhead for storing nodes and passing messages caused by Proppo to be negligible. This overhead will be non-negligible for extremely simple calculations such as summing scalars together; however, the aim of Proppo is to facilitate implementing complicated algorithms. For complicated algorithms, we expect the computations at each node to take longer than 10^{-6} seconds, so in practice, the overhead caused by Proppo will be negligible. Moreover, we see that Proppo can scale to millions of propagation nodes, while, in our experience applying Proppo to practical problems, we have so far not needed more than a thousand nodes. Finally, we note that this experiment does not guarantee that the implementation utilizing Proppo will have the same computation time as one without it. Typically, when Proppo is used, it would tweak the operation of some underlying computational software. These tweaks may interfere with the normal operation of the computational software, making it perform

slightly slower. For example, when Proppo is used to override the standard back propagation in PyTorch, it would manually pass gradients backwards at the propagation nodes, instead of letting PyTorch automatically back propagate. This may slow down the computation due to the interference. To obtain optimal performance, one should only use Proppo when it is needed, or when it increases convenience due to greater modularity.

Figure 7: Scaling of computation time with the number of propagation nodes (Sec. B.4).

C   Chaotic net: Additional details, explanations and experiments

In Sec. C.1, we provide additional explanations about the chaotic net experiments (Sec. 4); in Sec. C.2, we provide additional explanations of the single path experiment (Sec. 4.2); in Sec. C.3, we present an additional experiment designed to show the utility and better scalability w.r.t. the dimensionality of Gaussian shaping gradients.

C.1   Explanation of chaotic dynamics of the recurrent neural network

Wang (1991) explained that the inverse temperature parameter β controls the dynamics of the RNN system introduced in Sec. 4.1. When β is small, the system is well-behaved, but as β is increased, the system becomes chaotic through a period-doublings mechanism. They illustrated this via a bifurcation diagram that we have replicated in Fig. 8a. In this figure, for each β we simulate the system for 10000 steps, and plot the first dimension x_1 of the last 500 steps onto the figure as dots (note that one obtains a similar diagram when considering x_2, the second dimension of the system). We see that when β is small (around 1), all of the dots are at the same position; hence the system converged to a fixed state. As β is increased, the system starts oscillating between two states. As β is further increased, the states further split, with a phase transition happening around $\beta = 2.5$ leading to chaotic oscillation.

This chaotic behavior causes the gradient to be ill-behaved as illustrated in Fig. 8b. In this figure, we followed the experimental protocol of Parmas et al. (2018), and plotted the RP derivative of the loss function w.r.t. β while keeping the random number seed fixed. We see that the derivative is well-behaved in the non-chaotic region, but starts rapidly oscillating up and down with a large magnitude as the system becomes chaotic at the phase transition around $\beta = 2.5$. Moreover, the gradient variance also explodes. Parmas et al. (2018) explained this behavior by plotting the loss landscape of their system w.r.t. the start position. We have replicated a similar result for the RNN system in Fig. 8c. Recall from the preliminaries (Sec. 2, see also Eq. (7)) that the total derivative sums the terms $\frac{\mathrm{d}L}{\mathrm{d}\boldsymbol{x}} \frac{\mathrm{d}\boldsymbol{x}}{\mathrm{d}\beta}$ for each time step. As the loss landscape L has a fractal structure due to the chaotic properties of the system, the gradient $\frac{\mathrm{d}L}{\mathrm{d}\boldsymbol{x}}$ is oscillating rapidly. Thus, if one tries to average the gradients together over some region of this landscape by sampling the gradients in said region, the variance of this estimate will explode, and it is impossible to compute a sensible gradient direction using the RP method. The LR gradient, on the other hand, does not use $\frac{\mathrm{d}L}{\mathrm{d}\boldsymbol{x}}$, it only uses L to estimate the gradient. Thus, small amplitude fluctuations of L do not affect the LR gradient, and it is robust to the issues with chaos.

Similar chaotic properties occur in many ML tasks. We already introduced the work of Parmas et al. (2018) in model-based reinforcement learning that was the basis for much of our discussion. Their work appears to be the first to discuss the explosion of the gradient variance due to chaos when the computations are stochastic, and they also suggested to incorporate LR methods to tackle the issue. Similar chaotic properties have also been discussed in metalearning (Maclaurin et al., 2015; Metz et al., 2019), protein folding software (Ingraham et al., 2019) and differentiable simulation (Xu et al., 2021; Suh et al., 2022). Moreover, the effect of chaos on estimating the sensitivity of fluid simulations has also been studied in many works, e.g., the work by Wang (2013). We believe that our minimalistic experiment captures interesting characteristics of such challenging ML tasks.

(a) Bifurcation diagram for x_1 (b) Gradient (c) Loss landscape w.r.t. start location

Figure 8: Illustration of the behavior of the chaotic sigmoid recurrent neural network (Sec. 4.1). (a) Bifurcation diagram of the RNN. The activation noise was removed, $\sigma = 0$, to replicate previous results with a deterministic RNN (Wang, 1991). Note that the result does not change much when noise is added, the dots are just spread out around the location on the current figure. (b) Gradient of the objective plotted against β, similarly to (Parmas et al., 2018). The horizon was $H = 100$. (c) Fractal loss landscape. The parameters were $\beta = 3.5$, resolution of the grid: 500×500, horizon: $H = 15$. We also added a fixed perturbation on W_{11} sampled from a Gaussian with standard deviation $\sigma_w = 0.1$. This was done for aesthetic reasons, and to show that the system stays chaotic even when perturbed.

C.2 Additional details of the single path chaotic net experiment

Figure 9: Single path chaotic RNN probabilistic computation graph diagram.

Figure 9 includes a schematic diagram of the RNN computations in the experiments in Sec. 4.2. The computations start from an initial state x_0, and are simulated forwards for H steps. A loss, L, is computed at the last step. All of the nodes when $t \geq 1$ are propagation nodes ◯. The x nodes are propagation nodes due to the sampling of noise, and gradient estimation, while the loss node, L, is implemented as a loss propagator. The β node ◯ is the parameter node where the inverse variance weights are computed for use in the TP algorithm.

C.3 Multi path experiment: showing the advantage of Gaussian shaping gradients

Experimental setup. In this section, the main aim is to show the better scalability of Gaussian shaping gradients compared to regular LR gradients. To this end, we modify the simple RNN in Sec. 4.1 by replicating multiple instances of this RNN, and computing them in parallel; thus, increasing the dimensionality of the system. The setup is illustrated in Fig. 10. The additional parallel dimensions act as nuisance variables on the final loss, increasing the variance of the LR gradient estimator. Formally, the state is modified into $\tilde{x} := [x^{(1)}; \dots; x^{(D)}]$, and the evolution of each $x^{(d)}$ is computed separately according to Eq. (2). While the initial state is the same for each d, the added activation noise ε is different, so the trajectories for each parallel path are different. The loss is computed at the final step as $\tilde{L}(\tilde{x}_H) = \frac{1}{2}(\tilde{x}_H - \mathbf{1})^\mathrm{T}(\tilde{x}_H - \mathbf{1})$. Note that the parameters of the

Figure 10: Multi path chaotic RNN probabilistic computation graph diagram.

networks W and β are *not* shared across the paths, and we estimate the gradient only through the first path according to $\beta^{(1)}$. If instead the β parameter were shared, the problems of LR demonstrated in this section would not appear. Gaussian shaping modifies the gradient estimation method by resampling the batch in the first path at the last step $\{\boldsymbol{x}_H^{(1,m)}\}_{m=1}^B$ from a fitted Gaussian distribution (this node is illustrated as ◎ in Fig. 10). The other experimental details are the same as before in Sec. 4.2. We estimate the gradient when $\beta \in \{2.0, 2.5, 3.5\}$, and plot the gradient variance against the number of parallel paths D (Fig. 11).

Results.   The results are in Fig. 11. We see that the regular LR has a linearly increasing variance as the dimensionality D is increased, whereas the variance of GS stays constant. The variance of RP also stays constant with the dimensinality irrespective of whether GS is used or not; however, RP is inaccurate in the chaotic regime with $\beta \in \{2.5, 3.5\}$. The variance of TP follows a similar pattern to LR; however, for $\beta = 2.0$ the variance of the regular TP does not increase, because RP gradients are accurate in that scenario. We also see that TP outperformed the other estimators in all cases.

Discussion.   Previously, Parmas (2018) explained a potential advantage of GS in terms of the bias that it adds—smoothing the loss with a Gaussian may promote unimodality simplifying some optimization problems. However, they did not demonstrate a fundamental advantage in terms of computational complexity. Here, on the other hand, we have demonstrated a fundamental advantage of GS in terms of its scalability with the dimensionality D. This newly shown effect is particularly important when the system is near-chaotic, and regular back propagation gradients are ill-behaved.

Our newly shown advantage of GS may pose it beneficial for optimizing complex model architectures. When there are several modules independently influencing the behavior of downstream components of the system, GS may disentangle the individual contributions, and enable efficient optimization. As GS is not practical to implement using standard automatic differentiation software, our result highlights that automatic propagation software such as Proppo may enable training previously untrainable machine learning systems composed of complex networks of connected modules.

Figure 11: Comparison of Gaussian shaping (GS) gradient estimators with their regular counterparts in terms of scalability w.r.t. the dimensionality of the system D. The discussion of the experiment is in Sec. C.3. The main result is that the variance of the regular LR increases linearly as D is increased, whereas the GS variant has a constant variance.

D Proppo prototype code listings

This section contains prototype code for Proppo, as well as its application to create MC gradient estimator propagators. The code describes one possible prototype of automatic propagation software, but there may also be other implementations. The code here is not intended for use—it is provided for archival purposes. Code for use will be uploaded to https://github.com/proppo/proppo.

Propagation manager.

```
1   # propagation_manager.py
2   import torch
3   import proppo.back_methods as back_methods
4   import proppo.propagators as propagators
5   from proppo.containers import Node, Message
6
7
8   def _reversed_enumerate(l):
9       count = len(l)
10      for value in reversed(l):
11          count -= 1
12          yield count, value
13
14
15  class PropagationManager:
16      """ Propagation Manager class.
17      This class enables custom forward and backward propagations for flexibly
18      designing new gradient estimation and learning algorithms for computational
19      graphs, e.g. neural networks.
20
21      """
22
23      def __init__(self,
24                   default_propagator=propagators.BackPropagator(),
25                   loss_propagator=None,
26                   terminal_propagator=propagators.BackPropagator()):
27          self.nodes = []
28          self.node_pointer = 0  # Pointer for the current position on the tape.
29          self.default_propagator = default_propagator
30          self.propagators = {}
31          if loss_propagator:
32              self.loss_propagator = loss_propagator
33          elif default_propagator:
34              self.loss_propagator = self.default_propagator.loss_propagator()
35          # The terminal propagator exists to handle any remaining messages
36          # once the backward pass has finished. For example, a common use
37          # case is to use BackPropagator() to call backprop once all
38          # outputs and gradients have been assembled for the backprop call,
39          # # if these can be performed in parallel.
40          self.terminal_propagator = terminal_propagator
41          if self.terminal_propagator != None:
```

```
42                self.forward(x=None, local_propagator=terminal_propagator)
43                self.nodes[0]['clear'] = False
44
45        def add_propagator(self, name, propagator):
46            self.propagators[name] = propagator
47
48        def forward(
49                self,
50                x,
51                force_targets=None,
52                local_propagator=None,
53                get_node=False,
54                **kwargs):
55            """ Register input as a node, and returns output through local forward
56                function.
57
58            """
59            # Do modification to x, e.g. add noise
60            if local_propagator != None:
61                if isinstance(local_propagator, str):
62                    local_propagator = self.propagators[local_propagator]
63                node = local_propagator.forward(x, **kwargs)
64            else:
65                node = self.default_propagator.forward(x, **kwargs)
66
67            if not isinstance(node, Node):
68                node = Node.from_container(node)
69
70            # set local backward propagator for later use with the
71            # propagator.backward method
72            node.assign_propagator(local_propagator)
73
74            if force_targets != None:
75                node['force_targets'] = force_targets
76
77            if 'output' in node:
78                output = node['output']
79            else:
80                output = None
81
82            if node['register_node']:
83                if self.node_pointer > (len(self.nodes) - 1):
84                    self.nodes.append(node)
85                else:
86                    self.nodes[self.node_pointer] = node
87                self.node_pointer += 1
88
89            # Return output as well as pointers to the messages and
90            # node content.
91            # The node pointer is given if one wants to retrospectively change
92            # something in the node, e.g. if one wants to target messages to
93            # future nodes.
94
95            if get_node:
96                return (output, self.nodes[self.node_pointer])
97            else:
98                return output
99
100
101        def backward(self, loss=None, clear_nodes=False, message=None):
102            """ Execute backward propagation at the registered nodes one by one.
103
104            """
105            # backward until the last node
106            if loss != None:
107                self.append_loss(loss)
108
109            if message != None:  # TODO, send message to node instead.
110                self._send_message(
111                    message=message
112                )  # message should be of Message type and include the target
113
114            # Loop through all nodes in reverse order, calling the
115            # custom backward method of that node
116            for i, node in _reversed_enumerate(self.nodes):
117                self.node_pointer = i
118                if node.propagator != None:
119                    messages = node.backward()
120                else:
121                    messages = self.default_propagator.backward(
122                        node, node.messages)
```

```
123
124              # Clear node and message tape content, then send the message;
125              # this allows to send a message to the propagators own slot
126              # as well (i.e. to keep a history between different
127              # manager.backward() calls). Node can optionally be not cleared,
128              # but message_tape is always cleared. (To keep a history, in
129              # message tape, the propagator should send a message to itself).
130              if node['clear']:
131                  self.nodes[i].clear()
132              self.nodes[i].messages.clear()
133              if messages != None:  # TODO: loop through the message items
134                  for target, message_container in messages.messages():
135                      # choose the priority target, transform the target, send the message
136                      targets = self._target_conflict_resolution(target, node)
137                      target_nodes = self._find_nodes(targets)
138                      self._send_messages(message_container, target_nodes)
139
140          # refresh node history
141          if clear_nodes:  # TODO: remove message tape
142              if self.terminal_propagator:
143                  self.nodes = [self.nodes[0]]
144              else:
145                  self.nodes = []
146
147          if self.terminal_propagator:
148              self.node_pointer = 1
149          else:
150              self.node_pointer = 0
151
152          return messages  # The last remaining messages are returned if desired.
153
154      def _send_message(self, message, target_node):
155          if target_node != None:
156              target_node.receive(message)
157
158      def _send_messages(self, messages, targets):
159          if isinstance(targets, list):
160              for target in targets:
161                  self._send_message(messages, target)
162          else:
163              self._send_message(messages, targets)
164
165      def _target_conflict_resolution(self, target, node):
166          if 'force_targets' in node:
167              targets = node['force_targets']
168              return targets
169          elif target != None:
170              return target
171          elif 'targets' in node:
172              return node['targets']
173          else:
174              targets = -1
175              return targets
176
177      def _find_node(self, target):
178          if isinstance(target, int):
179              node_index = target + self.node_pointer
180              if (node_index < 0) or (node_index > (len(self.nodes) + 1)):
181                  target = None  # If out of bounds, don't send
182              else:
183                  target = self.nodes[node_index]
184          return target
185
186      def _find_nodes(self, targets):
187          if isinstance(targets, (list, tuple)):
188              targets = [self._find_node(t) for t in targets]
189              return targets
190          else:
191              targets = self._find_node(targets)
192              return targets
193
194      def append_loss(self, loss_node, loss_propagator=None, **kwargs):
195          if loss_propagator is None:
196              loss_propagator = self.loss_propagator
197          out = self.forward(x=loss_node,
198                             targets=None,
199                             local_propagator=loss_propagator,
200                             get_message_box=False,
201                             get_node=False,
202                             **kwargs)
203          return out
```

```
204
205     def size(self):
206         """ Returns the number of the registered nodes.
207
208         Returns:
209             int: the number of nodes.
210
211         """
212         return len(self.nodes)
```

Listing 1: Example prototype Python code for a Propagation Manager class

Smart containers and contents.

```python
1  # containers.py
2  from typing import List
3
4  class Content():
5
6      __slots__ = ('_content', )
7
8      def __init__(self, content):
9          if isinstance(content, Content):
10             self._content = content.get()
11         else:
12             self._content = content
13
14     def get(self):
15         return self._content
16
17     def set(self, value):
18         if isinstance(value, Content):
19             v = value.get()
20         else:
21             v = value
22
23         self._content = v
24
25     def update(self, value):
26         if hasattr(self.get(), 'update'):
27             if isinstance(value, Content):
28                 v = value.get()
29             else:
30                 v = value
31             self.get().update(v)
32         else:
33             self.set(value)
34
35     def __repr__(self):
36         return 'Content(' + str(self._content) + ')'
37
38     def __str__(self):
39         return str(self._content)
40
41     def __add__(self, value):
42         if isinstance(value, Content):
43             return self.get() + value.get()
44         else:
45             return self.get() + value
46
47     def __mul__(self, value):
48         return self.get() * value.get()
49
50     def __rmul__(self, value):
51         return self.get() * value.get()
52
53     def __matmul__(self, value):
54         return self.get() @ value.get()
55
56
57  class Summed(Content):
58
59      def update(self, value):
60          self.set(self + value)
61
62      def __repr__(self):
63          return 'Summed(' + str(self._content) + ')'
64
65
```

```
66  class Locked(Content):
67
68      def set(self, value):
69          raise RuntimeError(
70              'Attempting to call ".set()" on a Locked type'
71              ' Content. Locked type Content objects are used'
72              ' for contents that are never supposed to be updated.')
73
74      def __repr__(self):
75          return 'Locked(' + str(self._content) + ')'
76
77
78  class Listed(Content):
79
80      def __init__(self, *args):
81          list_content = []
82          for content in args:
83              if isinstance(content, Content):
84                  list_content.append(content.get())
85              else:
86                  list_content.append(content)
87          super().__init__(list_content)
88
89      def __repr__(self):
90          return 'Listed(' + str(self._content) + ')'
91
92      def update(self, *args):
93          if len(args) == 1:
94              if not isinstance(args[0], Listed):
95                  listed_content = Listed(args[0])
96              else:
97                  listed_content = args[0]
98          else:
99              list_vals = []
100             for arg in args:
101                 if isinstance(arg, Content):
102                     if isinstance(arg, Listed):
103                         list_vals += arg.get()
104                     else:
105                         list_vals.append(arg.get())
106                 else:
107                     list_vals.append(arg)
108             listed_content = Listed(*list_vals)
109
110         self._content = self + listed_content
111
112     def set(self, *args):
113         listed_content = []
114         for value in args:
115             if isinstance(value, Content):
116                 v = value.get()
117                 if not isinstance(value, Listed):
118                     v = [v]
119             else:
120                 v = [value]
121             listed_content += v
122
123         self._content = listed_content
124
125
126 class Container():
127
128     __slots__ = ('_contents', )
129
130     def __init__(self, cont_dict=None, **kwargs):
131         self._contents = {}
132         if cont_dict != None:
133             kwargs.update(cont_dict)
134         for k, v in kwargs.items():
135             if not isinstance(v, Content):
136                 val = Content(v)
137             else:
138                 val = v
139             self._contents[k] = val
140
141     def clear(self):
142         self._contents.clear()
143
144     def get_contents(self):
145         return self._contents
146
```

```python
147         def set_content(self, key, value):
148             if not isinstance(value, Content):
149                 v = Content(value)
150             else:
151                 v = value
152
153             if key in self._contents:
154                 self._contents[key].set(v)
155             else:
156                 self._contents[key] = v
157
158         def get(self, key):
159             return self[key]
160
161         def item_iter(self):
162             for k in self.keys():
163                 yield (k, self[k])
164
165         def items(self):
166             return self.item_iter()
167
168         def keys(self):
169             return self._contents.keys()
170
171         def _update_keys(self):
172             return self._contents.keys()
173
174         def value_iter(self):
175             for k in self.keys():
176                 yield self[k]
177
178         def values(self):
179             return self.value_iter()
180
181         def pop(self, key):
182             return self._contents.pop(key).get()
183
184         def __str__(self):
185             return 'Contents: ' + str(self._contents)
186
187         def __iter__(self):
188             return iter(self.keys())
189
190         def __getitem__(self, k):
191             return self._contents[k].get()
192
193         def __setitem__(self, k, v):
194             self.set_content(k, v)
195
196         def __contains__(self, k):
197             return k in self._contents
198
199         def update(self, container):
200             # Works for both dict or container.
201             if isinstance(container, dict):
202                 c = Container(cont_dict=container)
203             else:
204                 c = container
205
206             for k in c._update_keys():
207                 if k in self._update_keys():
208                     self._contents[k].update(c._contents[k])
209                 else:
210                     self.set_content(k, c._contents[k])
211
212
213    class Node(Container):
214        __slots__ = ('_contents', 'messages', 'propagator')
215
216        def __init__(self,
217                     cont_dict=None,
218                     box_class=Container,
219                     propagator=None,
220                     **kwargs):
221            super().__init__(cont_dict=cont_dict, **kwargs)
222            self.messages = box_class()
223            self.propagator = propagator
224
225        @classmethod
226        def from_container(cls, container):
227            kwargs = {}
```

```
228             if 'box_class' in container:
229                 kwargs['box_class'] = container.pop('box_class')
230             if 'propagator' in container:
231                 kwargs['propagator'] = container.pop('propagator')
232             if isinstance(container, Container):
233                 cont_dict = container.get_contents()
234             elif isinstance(container, dict):
235                 cont_dict = container
236             else:
237                 raise TypeError('container must be of Container or dict type.')
238
239             return Node(cont_dict=cont_dict, **kwargs)
240
241         def forward(self, x, **kwargs):
242             return self.propagator.forward(x, **kwargs)
243
244         def backward(self):
245             return self.propagator.backward(self, self.messages)
246
247         def receive(self, message):
248             # TODO: add more message box classes
249             if isinstance(message, Message):
250                 for m in message.containers():
251                     self.messages.update(m)
252             else:
253                 self.messages.update(message)
254
255         def assign_propagator(self, propagator):
256             self.propagator = propagator
257
258
259 class Message(Container):
260     __slots__ = ('_contents', 'multi_message')
261
262     def __init__(self, cont_dict=None, target=-1, container=None, **kwargs):
263         if container == None:
264             super().__init__(
265                 cont_dict={target: Container(cont_dict=cont_dict, **kwargs)})
266         else:
267             super().__init__(cont_dict={target: container})
268         self.multi_message = False
269
270     def _switch_multi(self):
271         if len(self.targets()) > 1:
272             self.multi_message = True
273         else:
274             self.multi_message = False
275
276     def _get_main_message(self):
277         return self._contents[next(iter(self.targets()))].get()
278
279     def get_message(self, target):
280         return self._contents[target].get()
281
282     def __str__(self):
283         return 'Message: ' + str(self._contents)
284
285     def targets(self):
286         return Container.keys(self)
287
288     def iter_containers(self):
289         for t in self.targets():
290             yield self.get_message(t)
291
292     def containers(self):
293         return self.iter_containers()
294
295     def iter_messages(self):
296         for t in self.targets():
297             yield (t, self.get_message(t))
298
299     def messages(self):
300         return self.iter_messages()
301
302     def iter_keys(self):
303         for container in self.containers():
304             for k in container.keys():
305                 yield k
306
307     def keys(self):
308         if self.multi_message == False:
```

```
309                  return self._get_main_message().keys()
310             else:
311                  return self.iter_keys()
312
313        def iter_items(self):
314             for container in self.containers():
315                  for item in container.items():
316                       yield item
317
318        def items(self):
319             if self.multi_message == False:
320                  return super().items()
321             else:
322                  return self.iter_items()
323
324        def iter_values(self):
325             for container in self.containers():
326                  for value in container.values():
327                       yield value
328
329        def values(self):
330             if self.multi_message == False:
331                  return super().values()
332             else:
333                  return self.iter_values()
334
335        def pop(self, k):
336             if self.multi_message == True:
337                  out = super().pop(k)
338                  self._switch_multi()
339                  return out
340             else:
341                  return self._get_main_message().pop(k)
342
343        def pop_message(self, k):
344             out = super().pop(k)
345             self._switch_multi()
346             return out
347
348        def update(self, message):
349             if isinstance(message, Message):
350                  super().update(message)
351                  self._switch_multi(
352                  )  # check whether a message with a new target was added
353             elif isinstance(message, (Container, dict)):
354                  if self.multi_message == False:
355                       self._get_main_message().update(message)
356                  else:
357                       raise TypeError(
358                            'Current Message contains multiple targets. Updating'
359                            ' with Container is disabled due to ambiguity'
360                            ' in the target. Turn container into Message'
361                            ' type with a specified target, then update'
362                            ' the current message.')
363             else:
364                  raise TypeError('Message can only be updated with a Message'
365                                  ' or Container type.')
366
367        def __getitem__(self, k):
368             if self.multi_message == False:
369                  return self._get_main_message()[k]
370             else:
371                  return super().__getitem__(k)
372
373        def __setitem__(self, k, v):
374             if self.multi_message == False:
375                  self._get_main_message().set_content(k, v)
376             else:
377                  super().__setitem__(k, v)
378
379        def __contains__(self, k):
380             if self.multi_message == False:
381                  return k in self._get_main_message()
382             return super().__contains(k)
```

Listing 2: Example prototype Python code for smart contents and containers

Smart initializers.

```python
1  # initializers.py
2  from collections import OrderedDict
3  from functools import partial
4  import copy
5
6
7  class Init():
8
9      def __init__(self, cls, *args, defaults=None, kwdefaults=None, **kwargs):
10         self._cls = cls
11         if kwdefaults != None:
12             self.kwdefaults = {**kwdefaults, **kwargs}
13         elif kwargs != {}:
14             self.kwdefaults = kwargs
15         if defaults != None:
16             self.defaults = (*args, *defaults)
17         elif args != ():
18             self.defaults = args
19
20     def __call__(self, *args, **kwargs):
21         if hasattr(self, 'kwdefaults'):
22             input_kwargs = {**self.kwdefaults, **kwargs}
23         else:
24             input_kwargs = kwargs
25         # Note that concatenating defaults and args is not allowed
26         # due to ambiguity of when to overwrite.
27         # TODO: fix the default arguments so that they are first
28         # converted into keyword arguments, and then merged with the
29         # keyword arguments. If there is a conflict, e.g., the same
30         # keyword exists in both sets, then raise an error.
31         if hasattr(self, 'defaults') and len(args) == 0:
32             input_args = self.defaults
33         else:
34             input_args = args
35
36         return self._call(*input_args, **input_kwargs)
37
38     def _call(self, *args, **kwargs):
39         return self._cls(*args, **kwargs)
40
41     @classmethod
42     def init(cls, *args, **kwargs):
43         return Init(cls, *args, **kwargs)
44
45  class Lock(Init):
46
47     def __init__(self, *args, allow_unused=False, **kwargs):
48         super().__init__(*args, **kwargs)
49         self.allow_unused = allow_unused
50
51     def __call__(self, *args, allow_unused=False, **kwargs):
52         if allow_unused or self.allow_unused:
53             return super().__call__()
54         elif len(args) == 0 and len(kwargs) == 0:
55             return super().__call__()
56         else:
57             raise RuntimeError('allow_unused permission is False.'
58                                ' The Lock initalizer allows only'
59                                ' initializing with the default parameters.'
60                                ' Remove args and kwargs inputs from'
61                                ' initialization.')
62
63  class Optional(Init):
64     """ Initializer that only initializes when the on flag is
65     True. Otherwise, an instance of the class is not created, it returns None.
66     """
67     def _call(self, on, *args, **kwargs):
68         if on:
69             return super()._call(*args, **kwargs)
70         else:
71             return None
72
73  class Choice(Init):
74     def __init__(self, cls, *args, **kwargs):
75         if not isinstance(cls, (tuple, dict)):
76             raise TypeError('cls input must be of type tuple or dict.')
77         else:
78             super().__init__(cls, *args, **kwargs)
79
80     def _call(self, choice, *args, **kwargs):
81         return self._cls[choice](*args, **kwargs)
```

```python
82
83  class Empty(Init):
84      def __init__(self):
85          pass
86
87      def __call__(self, *args, **kwargs):
88          self._call()
89
90      def _call(self, *args, **kwargs):
91          raise RuntimeError('Trying to initialize a ChainInit containing'
92                             ' an empty Init. First reconfigure the'
93                             ' ChainInit to replace the Empty Init.'
94                             ' Empty Inits are used in template'
95                             ' ChainInits to indicate what slot has to be'
96                             ' changed.')
97
98  class ChainInit():
99
100     def __init__(self, regular_dict=False, **kwargs):
101
102         if regular_dict:
103             self._chaininit = {}
104         else:
105             self._chaininit = OrderedDict()
106
107         for k, v in kwargs.items():
108             if isinstance(v, Init):
109                 init = v
110             else:
111                 init = Init(v)
112             self._chaininit[k] = init
113
114     def __call__(self, **kwargs):
115         return self.init(**kwargs)
116
117     def items(self):
118         return self._chaininit.items()
119
120     def values(self):
121         return self._chaininit.values()
122
123     def keys(self):
124         return self._chaininit.keys()
125
126     def __iter__(self):
127         return self._chaininit.__iter__()
128
129     def __contains__(self, key):
130         return key in self._chaininit
131
132     def __getitem__(self, key):
133         return self._chaininit[key]
134
135     def __len__(self):
136         return len(self._chaininit)
137
138     @staticmethod
139     def _init_inputs(init, inputs=None):
140
141         if inputs == None:
142             obj = init()
143         elif isinstance(inputs, tuple):
144             arginputs = []
145             kwinputs = {}
146             for inp in inputs:
147                 if isinstance(inp, dict):
148                     kwinputs.update(inp)
149                 else:
150                     arginputs.append(inp)
151             obj = init(*arginputs, **kwinputs)
152         elif isinstance(inputs, dict):
153             obj = init(**inputs)
154         else:
155             obj = init(inputs)
156         return obj
157
158     def init(self, dictionary=False, **kwargs):
159
160         chainobjs = []
161         chainkeys = []
162
```

```
163            # Check that all keys exist
164            for key in kwargs:
165                if key not in self._chaininit:
166                    raise KeyError(key, 'not included in keys of the ChainInit.')
167
168            for k, init in self._chaininit.items():
169                inputs = kwargs.get(k, None) # kwarg if exists, otherwise None
170
171                obj = self._init_inputs(init, inputs)
172
173                if obj != None:
174                    chainobjs.append(obj)
175                    chainkeys.append(k)
176            if not dictionary:
177                return chainobjs
178            else:
179                return {k: obj for k, obj in zip(chainkeys, chainobjs)}
180
181        def reconf(self, **kwargs):
182            # Create a new ChainInit by reconfiguring the current
183            # ChainInit. For example, replace the Empty initializer
184            # of the current ChainInit to create a functioning ChainInit.
185            # You may also change the default parameters of the Inits.
186
187            chaindict = copy.copy(self._chaininit)
188            for k, v in kwargs.items():
189                if k not in chaindict:
190                    raise KeyError('Key does not exist in the ChainInit'
191                                   ' that you are trying to reconfigure.')
192                else:
193                    if isinstance(v, Init):
194                        chaindict[k] = v
195                    else:
196                        initializer = type(chaindict[k])
197                        cls = chaindict[k]._cls
198                        initializer = partial(initializer, cls)
199                        chaindict[k] = self._init_inputs(initializer, v)
200
201            return ChainInit(**chaindict)
202
203
204 class ChainInitTemplate(ChainInit):
205
206     def __call__(self, **kwargs):
207         initializers = super().__call__(dictionary=True, **kwargs)
208         return ChainInit(**initializers)
```

Listing 3: Example prototype python code for smart initializers in Proppo

Propagators.

```python
1  # propagators.py
2  import proppo.forward_methods as fm
3  import proppo.back_methods as bm
4  import proppo.baseline_funcs as baselines
5  import proppo as pp
6  from proppo.utils import inverse_variance_weighting
7  from proppo.containers import Node, Message, Container
8  from proppo.initializers import (ChainInit, Optional, Init, Empty,
9                                   ChainInitTemplate)
10
11 import copy
12
13
14 class Propagator:
15     """ This pairs together the forward and backward methods.
16
17     """
18
19     def __init_subclass__(cls, **kwargs):
20         cls.default_init_kwargs = kwargs
21
22     def __init__(self, **kwargs):
23         self.default_forward_kwargs = kwargs
24
25     def forward(self, x, **kwargs):
26         # Overwrite default arguments, then pass as input
27         input_kwargs = {**self.default_forward_kwargs, **kwargs}
28
```

```
29          # Must create a new node, and pass this to forward, otherwise
30          # the propagators at different forward steps will overwrite, the
31          # contents of the previous propagation.
32          node = {}
33          node = self.forward_impl(x, node, **input_kwargs)
34
35          # Flag to store the node in manager.
36          if 'register_node' not in node:
37              node['register_node'] = True
38          # Flag to clear node in manager after backwarding the node.
39          if 'clear' not in node:
40              node['clear'] = True
41
42          if isinstance(node, dict):
43              node = Container(cont_dict=node)
44
45          return node
46
47      def forward_impl(self, x, node={}, **kwargs):
48          return node
49
50      def backward(self, node, message):
51          message_in = message
52          message_out = self.backward_impl(node, message_in)
53
54          # for backwards compatibility, convert dictionaries
55          if not isinstance(message_out, Message):
56              if isinstance(message_out, dict):
57                  if 'targets' in message_out:
58                      target = message_out.pop('targets')
59                      message_out = Message(cont_dict=message_out, target=target)
60                  else:
61                      message_out = Message(cont_dict=message_out)
62              elif isinstance(message_out, Container):
63                  message_out = Message(container=message_out)
64
65          return message_out
66
67      def backward_impl(self, node, message):
68          message_out = Message(cont_dict=message.get_contents())
69          return message_out
70
71      def loss_propagator(self):
72          """ Returns the default loss propagator that should
73          be applied when appending a loss after having called
74          manager.forward using the current propagator.
75
76          """
77          return LossProp()
78
79
80  class SequenceProp(Propagator):
81      """ Base class for sequence based propagators, used to construct them.
82
83      """
84
85      def __init_subclass__(cls,
86                            propagators=ChainInit(),
87                            **kwargs):
88          super().__init_subclass__(**kwargs)
89          cls.propagators = propagators
90
91      def _split_prop_kwargs(self, kwargs):
92          prop_kwargs = {}
93          for k in self.propagators:
94              if k in kwargs:
95                  prop_kwargs[k] = kwargs.pop(k)
96          return prop_kwargs, kwargs
97
98      def __init__(self,
99                   propagators=[], # A list of already initialized propagators.
100                  **kwargs):
101
102          default_init_kwargs = copy.copy(self.default_init_kwargs)
103
104          if propagators != []:
105              input_kwargs = {**default_init_kwargs, **kwargs}
106
107              super().__init__(**input_kwargs)
108              self.propagators = propagators
109          else:
```

```
110              def_prop_kwargs, def_init_kwargs = self._split_prop_kwargs(
        default_init_kwargs)
111              prop_kwargs, init_kwargs = self._split_prop_kwargs(kwargs)
112              input_kwargs = {**def_init_kwargs, **init_kwargs}
113
114              super().__init__(**input_kwargs)
115
116              input_prop_kwargs = {**def_prop_kwargs, **prop_kwargs}
117
118              self.propagators = self.propagators(**input_prop_kwargs)
119
120
121  class ComboProp(SequenceProp):
122      """ Combines propagators, and applies them in a sequence, updating
123      message and node in-place.
124
125      """
126
127      def forward_impl(self, x, node={}, **kwargs):
128          for prop in self.propagators:
129              node_out = prop.forward_impl(x, node, **kwargs)
130              node.update(node_out)
131          return node
132
133      def backward_impl(self, node, message):
134
135          final_message = Message(cont_dict=message.get_contents())
136          for prop in reversed(self.propagators):
137              message_in = final_message._get_main_message()
138
139              message_out = prop.backward_impl(node, message_in)
140
141              # for backwards compatibility, convert dictionaries
142              if isinstance(message_out, dict):
143                  if 'targets' in message_out:
144                      target = message_out.pop('targets')
145                      message_out = Message(cont_dict=message_out, target=target)
146                  else:
147                      message_out = Message(cont_dict=message_out)
148
149              final_message.update(message_out)
150
151          return final_message
152
153
154  class BackPropagator(Propagator):
155      """ Base propagator that will backprop gradient messages, if they
156      are sent into this propagator.
157
158      """
159
160      def backward_impl(self, node, message):
161
162          message_out = bm.backward(node, message)
163          return message_out
164
165
166  class BaselineProp(Propagator):
167      """ Class for adding a baseline subtraction to the local losses.
168
169      """
170
171      def __init__(self, baseline_func=baselines.mean_baseline, **kwargs):
172          super().__init__(**kwargs)
173          self.baseline_func = baseline_func  # Default baseline function
174
175          # Note: if one wants to change the baseline function for just one
176          # forward call compared to the default baseline function in a chain
177          # of forward propagations, then they should define a new propagator
178          # object for that new forward call. I could also allow giving an
179          # additional argument in the forward call to specify a baseline
180          # for just that node; however, this would not
181          # give a key error if someone accidentally mistypes the key, and
182          # may lead to bugs, so I avoid it.
183
184      def backward_impl(self, node, message):
185          local_loss = message.pop('local_loss')
186          # Need to remove local_loss from previous message, and create
187          # a new message to avoid duplicating loss in the ComboProp
188          # backward_impl method.
189          if isinstance(self.baseline_func, (list, tuple)):
```

```
190            baselined_loss = copy.copy(local_loss)
191            for func in reversed(self.baseline_func):
192                baselined_loss = func(baselined_loss, node)
193        else:
194            baselined_loss = self.baseline_func(local_loss, node)
195
196        message_out = {
197            'baselined_loss': baselined_loss,
198            'local_loss': local_loss
199        }
200        return message_out
201
202
203 mcgrad_temp = ChainInitTemplate(backprop=Optional(
204     Optional.init(BackPropagator, True), False),
205                                     base=Init,
206                                     baseline=Optional(
207     Optional.init(BaselineProp, True), False)
208 )
209
210
211 class PauseBase(Propagator):
212     """ A propagator that pauses all incoming gradients, then sends the
213     combined gradient backwards.
214
215     """
216
217     def forward_impl(self, x, node={}, **kwargs):
218         node = fm.detached_output(x, **kwargs)
219         return node
220
221     def backward_impl(self, node, message):
222         message_out = bm.rp_gradient(node, message)
223         return message_out
224
225
226 class SkipProp(Propagator):
227     """ A propagator that sends all incoming messages backward
228     a determined length, skipping the nodes inbetween.
229
230     """
231
232     def __init__(self, skip=1, **kwargs):
233         super().__init__(**kwargs)
234         self.skip = skip
235
236     def forward_impl(self, x, node={}, **kwargs):
237         node['output'] = x
238         return node
239
240     def backward_impl(self, node, message):
241         message['targets'] = -self.skip
242         return message
243
244
245 class PauseProp(ComboProp, propagators=mcgrad_temp(backprop=True,
246                                                    base=PauseBase)):
247     pass
248
249
250 class SumBase(Propagator):
251     """ Propagator that adds a local variable with a different variable in
252     messages. This is usually used to accumulate a sum of variables during the
253     backward pass, e.g. sum the rewards to obtain the return in reinforcement learning.
254
255     """
256
257     def __init__(self, sum_name, local_variable, **kwargs):
258         self.sum_name = sum_name
259         self.local_variable = local_variable
260         super().__init__(**kwargs)
261
262     def backward_impl(self, node, message):
263         current_sum = message.pop(self.sum_name, 0)
264         message = {self.sum_name: message[self.local_variable] + current_sum}
265
266         return message
267
268
269 class ChainProp(SequenceProp):
270     """ Chains together a set of propagators into a single propagator.
```

```
271          The implementation is based on creating a new PropagationManager object
272          to correctly apply the propagators in sequence without any implementation
273          errors. The propagators to chain together should be given as a list
274          or tuple of Propagator instances during creation. The propagators
275          themselves can also be Chain propagators, which allows for defining
276          complex propagation strategies using nested propagation managers.
277
278          """
279
280      def forward_impl(self, x, node={}, chain_kwargs=[], **kwargs):
281          manager = pp.PropagationManager(default_propagator=None,
282                                          terminal_propagator=None)
283          if chain_kwargs:
284              for prop, kwarg in zip(self.propagators, chain_kwargs):
285                  kwarg.update(kwargs)
286                  x = manager.forward(x, local_propagator=prop, **kwarg)
287          else:
288              for prop in self.propagators:
289                  x = manager.forward(x, local_propagator=prop, **kwargs)
290
291          node = {'output': x, 'manager': manager}
292          if manager.size() == 0:
293              node['register_node'] = False
294          return node
295
296      def backward_impl(self, node, message):
297          message_out = node['manager'].backward(message=message)
298          return message_out
299
300      def loss_propagator(self):
301          """ By default, usually the last one in the chain
302          contains the correct loss propagator.
303
304          """
305          return self.propagators[-1].loss_propagator()
306
307
308  class RPBase(Propagator):
309      """ Base class for RP propagator.
310
311      """
312
313      def forward_impl(self, x, node={}, detach=True, **kwargs):
314          node = fm.rp_noise(x, detach=detach, **kwargs)
315          return node
316
317      def backward_impl(self, node, message):
318          message_out = bm.rp_gradient(node, message)
319          return message_out
320
321
322  class RPProp(ComboProp, propagators=mcgrad_temp(backprop=True,
323                                                 base=RPBase)):
324      """ RP propagator combining the functionality from ComboProp.
325
326      """
327      pass
328
329
330  class LossBase(Propagator):
331      """ Base class for loss nodes in the computational graph.
332
333      """
334
335      def __init__(self, loss_name='local_loss', **kwargs):
336          super().__init__(**kwargs)
337          self.loss_name = loss_name
338
339      def forward_impl(self, x, node={}, lossgrad=True, lossfunc=None, **kwargs):
340          if lossfunc:
341              if isinstance(x, dict):
342                  losses = lossfunc(**x)
343              else:
344                  losses = lossfunc(x)
345          else:
346              losses = x
347
348          node = fm.loss_forward(losses, sum_loss=True, lossgrad=lossgrad)
349          return node
350
351      def backward_impl(self, node, message):
```

```
352            message_out = bm.loss_backward(node, message, loss_name=self.loss_name)
353            return message_out
354
355
356    class LossProp(ComboProp,
357                   propagators=ChainInit(
358                       backprop=Optional(BackPropagator, True),
359                       baseline=Optional(BaselineProp,
360                                         True,
361                                         baseline_func=baselines.mean_baseline),
362                   base=LossBase)):
363        """ Propagator adding Baseline and ComboProp functionality to Loss nodes.
364
365        """
366        pass
367
368
369    class LRBase(Propagator):
370        """ Base class for likelihood ratio gradient propagators.
371
372        """
373
374        def forward_impl(self, x, node, **kwargs):
375            node = fm.lr_noise(x, **kwargs)
376            return node
377
378        def backward_impl(self, node, message):
379            message_out = bm.lr_gradient(node, message)
380            return message_out
381
382
383    class LRProp(ComboProp, propagators=mcgrad_temp(backprop=True,
384                                                    base=LRBase,
385                                                    baseline=True)):
386        """ Class adding ComboProp functionality to LR gradient propagators.
387
388        """
389
390        def loss_propagator(self):
391            return LossProp(backprop=False, lossgrad=False)
392
393
394    class TPBase(Propagator):
395        """ Base class for total propagation gradient propagators.
396
397        """
398
399        def __init__(self,
400                     var_weighting_func=inverse_variance_weighting,
401                     **kwargs):
402            super().__init__(**kwargs)
403            self.var_weighting_func = var_weighting_func
404
405        def forward_impl(self, x, node, **kwargs):
406            node = fm.totalprop_noise(x, **kwargs)
407            return node
408
409        def backward_impl(self, node, message):
410            message_out = bm.totalprop_gradient(
411                node, message, var_weighting_func=self.var_weighting_func)
412            return message_out
413
414
415    class TotalProp(ComboProp,
416                    propagators=mcgrad_temp(backprop=True,
417                                            base=TPBase,
418                                            baseline=True)
419    ):
420        """ Class adding ComboProp functionality to total propagation
421        gradient propagation nodes.
422
423        """
424        pass
```

Listing 4: Example prototype python code for propagators for MC gradient estimation

Forward methods.

```
1  # forward_methods.py
```

```python
import torch
import collections

def detached_output(x, requires_grad=True, **kwargs):
    x_detached = x.detach()
    if requires_grad:
        x_detached.requires_grad_()
    node = {'output': x_detached, 'pre_output': x, 'register_node': True}
    return node

def loss_forward(x, lossgrad=False, sum_loss=True, **kwargs):
    """ Method to register a loss node. It will either
    just pass the loss in the local_loss slot, or will
    also backprop the gradient.

    """
    if x.dim() == 1:
        x = x.reshape([x.numel(), 1])

    node = detached_output(x, requires_grad=False)
    node['lossgrad'] = lossgrad
    node['sum_loss'] = sum_loss
    return node

def rp_noise(x, dist_class, dist_params, detach=True, **kwargs):
    """ Returns noisy node for reparametrization trick

    """
    if isinstance(dist_params, (tuple, list)):
        dist = dist_class(*dist_params)
    if isinstance(dist_params, dict):
        dist = dist_class(**dist_params)
    if isinstance(dist_params, collections.Callable):
        dist = dist_class(**dist_params(x))

    x_noisy = x + dist.rsample()

    if detach:
        node = detached_output(x_noisy)
    else:
        node = {'output': x_noisy, 'register_node': False}
    return node

def lr_noise(x, dist_class, dist_params, requires_grad=False, **kwargs):
    """ Returns noisy node for likelihood ratio

    """
    if isinstance(dist_params, (tuple, list)):
        dist = dist_class(*dist_params)
    if isinstance(dist_params, dict):
        dist = dist_class(**dist_params)
    if isinstance(dist_params, collections.Callable):
        dist = dist_class(**dist_params(x))

    x_noisy = x + dist.rsample()
    log_prob = dist.log_prob(x_noisy.detach() - x)
    node = detached_output(x_noisy, requires_grad=requires_grad)
    node['log_prob'] = log_prob
    return node

def totalprop_noise(x,
                    dist_class,
                    dist_params,
                    ivw_target,
                    k_interval=1,
                    **kwargs):
    """ Returns noisy node for total propagation

    """
    node = lr_noise(x,
                    dist_class=dist_class,
                    dist_params=dist_params,
                    requires_grad=True)
    node['ivw_target'] = ivw_target
    node['k_interval'] = k_interval
```

```
82        return node
```

Listing 5: Example prototype python code for the forward methods of the propagators

Backward methods.

```
1  # back_methods.py
2  import torch
3  from proppo.utils import inverse_variance_weighting
4  from proppo.containers import Listed
5
6
7  def backward(node, message, grad_name=None):
8      """ This one is special for calling backward.
9      Removes outputs and grads from message, calls backward,
10     and passes the remaining message backwards.
11
12     """
13     if 'outputs' in message:
14         outputs = message.pop('outputs')
15         grads = message.pop('grads')
16     else:
17         return message
18
19     torch.autograd.backward(tensors=outputs, grad_tensors=grads)
20     return {}
21
22
23  def loss_backward(node, message_in, loss_name):
24      local_loss = node['output']
25      if node['sum_loss']:
26          if loss_name in message_in:
27              local_loss += message_in[loss_name]
28
29      outputs = node['pre_output']
30      # Grads is set so that the gradient of the average loss is computed.
31      message = {loss_name: local_loss}
32
33      if node['lossgrad']:
34          ones_matrix = torch.tensor([1.0], device=outputs.device).expand(
35              outputs.size())
36          grads = {
37              'outputs': Listed(outputs),
38              'grads': Listed(ones_matrix / torch.numel(outputs))
39          }
40          message.update(grads)
41
42      return message
43
44
45  def rp_gradient(node, message_in):
46      """ Returns output tensor and its gradient for reparametrization trick.
47
48      """
49      detached_output = node['output']
50      output = node['pre_output']
51      message = {
52          'outputs': Listed(output),
53          'grads': Listed(detached_output.grad)
54      }
55
56      return message
57
58
59  def lr_gradient(node, message_in):
60      """ Returns output tensor and its gradient for likelihood ratio
61
62      """
63      if 'baselined_loss' in message_in:
64          local_loss = message_in['baselined_loss']
65      else:
66          local_loss = message_in['local_loss']
67
68      lr_grad_outputs = local_loss / torch.numel(local_loss)
69      log_prob = node['log_prob']
70
71      lr_grad_outputs = lr_grad_outputs.expand(log_prob.shape)
72
73      message = {'outputs': Listed(log_prob), 'grads': Listed(lr_grad_outputs)}
```

```python
74        return message
75
76
77 def totalprop_gradient(node,
78                        message_in,
79                        var_weighting_func=inverse_variance_weighting):
80     """ Returns output tensors and their gradients for total propagation.
81
82     The total propagation is a combination of the reparametrization trick and
83     the likelihood ratio.
84     Each gradient will be combined based on inverse variance weighting.
85
86     """
87     detached_output = node['output']
88     output = node['pre_output']
89     log_prob = node['log_prob']
90     ivw_target = node['ivw_target']
91     k_interval = node['k_interval']
92
93     if 'k_counter' in message_in:
94         k_counter = message_in.pop('k_counter')
95     else:
96         k_counter = 0
97
98     if 'baselined_loss' in message_in:
99         local_loss = message_in['baselined_loss']
100     else:
101         local_loss = message_in['local_loss']
102     # Make LR gradients compute mean gradient
103     local_loss = local_loss / torch.numel(local_loss)
104
105     lr_grad_outputs = local_loss.expand(log_prob.shape)
106
107     if k_counter % k_interval == 0:
108         rp_grads = torch.autograd.grad(outputs=output,
109                                        inputs=ivw_target,
110                                        grad_outputs=detached_output.grad,
111                                        retain_graph=True)
112
113         lr_grads = torch.autograd.grad(outputs=log_prob,
114                                        inputs=ivw_target,
115                                        grad_outputs=lr_grad_outputs,
116                                        retain_graph=True)
117
118         k_lr, k_rp = var_weighting_func(lr_grads, rp_grads)
119     else:
120         k_lr, k_rp = message_in['k_lr_k_rp']
121
122     outputs = Listed(log_prob, output)
123     grads = Listed(k_lr * lr_grad_outputs, k_rp * detached_output.grad)
124     message_grads = {'outputs': outputs, 'grads': grads, 'targets': -1}
125
126     message_k = {
127         'k_counter': k_counter + 1,
128         'k_lr_k_rp': (k_lr, k_rp),
129         'targets': 0
130     }
131
132     if k_interval > 1:
133         messages = (message_grads, message_k)
134     else:
135         messages = message_grads
136     return messages
```

Listing 6: Example prototype python code for the backward methods of the propagators

Baseline functions.

```python
1 # baseline_funcs.py
2 import torch
3
4
5 def mean_baseline(local_losses, node=None):
6     with torch.no_grad():
7         batch_size = local_losses.numel()
8
9         # leave-one-out baselines
10        sum_loss = local_losses.sum()
11        # The division by (batch_size - 1) instead of (batch_size)
```

```
12            # is algebraically equivalent to a leave-one-out baseline.
13            sum_loss = (sum_loss - local_losses) / (batch_size - 1)
14            losses = local_losses - sum_loss
15        return losses
16
17
18 def no_baseline(local_losses, node=None):
19        return local_losses
```

Listing 7: Example prototype python code for the baseline methods used in LR-based MC gradient estimators

Utilities.

```
1 # utils.py
2 import torch
3
4
5 def expand(data, batch_size):
6     """ Returns the tensor with batch dimension expanded.
7
8     Arguments:
9         data (torch.Tensor): input tensor
10        batch_size (int): batch size for expansion
11
12    Returns:
13        torch.Tensor: output tensor
14
15    """
16    return data.expand((batch_size, ) + data.shape)
17
18
19 def inverse_variance_weighting(x1, x2, scalar_estimate=True):
20     """ Returns weights of inverse variance weighting for each input.
21
22     """
23
24    if isinstance(x1, (list, tuple)) and isinstance(x2, (list, tuple)):
25        x1_vars = []
26        x2_vars = []
27        c_list = []
28        for v1, v2 in zip(x1, x2):
29            assert v1.shape == v2.shape
30            batch_size = v1.shape[0]
31
32            d1 = v1 - v1.mean(dim=0, keepdims=True)
33            d2 = v2 - v2.mean(dim=0, keepdims=True)
34
35            c1 = torch.max(torch.abs(d1))
36            c2 = torch.max(torch.abs(d2))
37            c = torch.max(c1, c2)
38            c_list.append(c)
39
40            if c == 0:
41                x1_vars.append(torch.tensor(0.0, device=c.device))
42                x2_vars.append(torch.tensor(0.0, device=c.device))
43            else:
44                x1_vars.append(torch.sum((d1 / c)**2))
45                x2_vars.append(torch.sum((d2 / c)**2))
46        x1vec = torch.tensor(x1_vars)
47        x2vec = torch.tensor(x2_vars)
48        cvec = torch.tensor(c_list)
49        cmax = torch.max(cvec)
50        if cmax == 0:
51            x1_var = torch.tensor(1.0, device=cmax.device)
52            x2_var = torch.tensor(1.0, device=cmax.device)
53        else:
54            cvec = (cvec / cmax)**2
55            x1_var = torch.sum(x1vec * cvec)
56            x2_var = torch.sum(x2vec * cvec)
57    else:
58        assert x1.shape == x2.shape
59        batch_size = x1.shape[0]
60
61        d1 = x1 - x1.mean(dim=0, keepdims=True)
62        d2 = x2 - x2.mean(dim=0, keepdims=True)
63
64        c1 = torch.max(torch.abs(d1))
65        c2 = torch.max(torch.abs(d2))
```

```
66          c = torch.max(c1, c2)
67
68          if c == 0:
69              x1_var = torch.tensor(1.0, device=c.device)
70              x2_var = torch.tensor(1.0, device=c.device)
71          else:
72              x1_var = torch.sum((d1 / c)**2)
73              x2_var = torch.sum((d2 / c)**2)
74
75      k_x1 = x2_var / (x1_var + x2_var)
76      k_x1 = torch.clip(k_x1, 0, 1)
77
78      if torch.isnan(k_x1):
79          print('Warning: estimated k was nan. Automatically changed to 0.5.')
80      k_x1[torch.isnan(k_x1)] = 0.5   # when 0/0 error occurs, take them equally.
81
82      return k_x1, 1.0 - k_x1
```

Listing 8: Example prototype python code for utility functions used in Proppo

References

Abadi, M., Barham, P., Chen, J., Chen, Z., Davis, A., Dean, J., Devin, M., Ghemawat, S., Irving, G., Isard, M., et al. (2016). TensorFlow: A system for Large-Scale machine learning. In *12th USENIX symposium on operating systems design and implementation (OSDI 16)*, pages 265–283. 1

Agha, G. (1986). *Actors: a model of concurrent computation in distributed systems*. 1

Anonymous (2022). Anonymous. In *Anonymous*, page 0000. 1, 3.5, B.3

Barham, P. and Isard, M. (2019). Machine learning systems are stuck in a rut. In *Proceedings of the Workshop on Hot Topics in Operating Systems*, pages 177–183. 1

Bauer, F. L. (1974). Computational graphs and rounding error. *SIAM Journal on Numerical Analysis*, 11(1):87–96. 2.1

Baydin, A. G., Pearlmutter, B. A., Radul, A. A., and Siskind, J. M. (2018). Automatic differentiation in machine learning: a survey. *Journal of Marchine Learning Research*, 18:1–43. 2.1

Boner, J. et al. (2010). Akka. https://akka.io/. 5

Bradbury, J., Frostig, R., Hawkins, P., Johnson, M. J., Leary, C., Maclaurin, D., Necula, G., Paszke, A., VanderPlas, J., Wanderman-Milne, S., and Zhang, Q. (2018). JAX: composable transformations of Python+NumPy programs. 1

Brown, T., Mann, B., Ryder, N., Subbiah, M., Kaplan, J. D., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., et al. (2020). Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901. 6

Chollet, F. et al. (2015). Keras. https://keras.io. 1

Chowdhery, A., Narang, S., Devlin, J., Bosma, M., Mishra, G., Roberts, A., Barham, P., Chung, H. W., Sutton, C., Gehrmann, S., et al. (2022). Palm: Scaling language modeling with pathways. *arXiv preprint arXiv:2204.02311*. 6

Dangel, F., Kunstner, F., and Hennig, P. (2020). BackPACK: Packing more into backprop. In *International Conference on Learning Representations*. 1

Fairbank, M. (2008). Reinforcement learning by value gradients. *arXiv preprint arXiv:0803.3539*. A.2

Foerster, J., Farquhar, G., Al-Shedivat, M., Rocktäschel, T., Xing, E., and Whiteson, S. (2018). Dice: The infinitely differentiable Monte Carlo estimator. In *International Conference on Machine Learning*, pages 1529–1538. 1, 5

Gardner, J., Pleiss, G., Weinberger, K. Q., Bindel, D., and Wilson, A. G. (2018). Gpytorch: Blackbox matrix-matrix gaussian process inference with gpu acceleration. *Advances in neural information processing systems*, 31. 1

Glynn, P. W. (1990). Likelihood ratio gradient estimation for stochastic systems. *Communications of the ACM*, 33(10):75–84. 2.2

Greensmith, E., Bartlett, P. L., and Baxter, J. (2004). Variance reduction techniques for gradient estimates in reinforcement learning. *Journal of Machine Learning Research*, 5(Nov):1471–1530. A.1

Hafner, D., Lillicrap, T., Ba, J., and Norouzi, M. (2020). Dream to control: Learning behaviors by latent imagination. In *International Conference on Learning Representations*. 1

Harris, C. R., Millman, K. J., van der Walt, S. J., Gommers, R., Virtanen, P., Cournapeau, D., Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., van Kerkwijk, M. H., Brett, M., Haldane, A., del Río, J. F., Wiebe, M., Peterson, P., Gérard-Marchant, P., Sheppard, K., Reddy, T., Weckesser, W., Abbasi, H., Gohlke, C., and Oliphant, T. E. (2020). Array programming with NumPy. *Nature*, 585(7825):357–362. 1

Hewitt, C., Bishop, P., and Steiger, R. (1973). A universal modular actor formalism for artificial intelligence. In *Proceedings of the 3rd international joint conference on Artificial intelligence*, pages 235–245. 1, 5

Hewitt, C. and Lieberman, H. (1983). Design issues in parallel architecture for artificial intelligence. In *In Proc. 28th IEEE Computer Society Int. Conf,, San Francisco CA*. Citeseer. 1

Ingraham, J., Riesselman, A., Sander, C., and Marks, D. (2019). Learning protein structure with a differentiable simulator. In *International Conference on Learning Representations*. C.1

Jankowiak, M. and Obermeyer, F. (2018). Pathwise derivatives beyond the reparameterization trick. In *International Conference on Machine Learning*, pages 2240–2249. A.1

Kingma, D. P. and Welling, M. (2013). Auto-encoding variational Bayes. *arXiv preprint arXiv:1312.6114*. 2.2

Krieken, E., Tomczak, J., and Ten Teije, A. (2021). Storchastic: A framework for general stochastic automatic differentiation. *Advances in Neural Information Processing Systems*, 34. 1, 5

Maclaurin, D., Duvenaud, D., and Adams, R. (2015). Gradient-based hyperparameter optimization through reversible learning. In *International conference on machine learning*, pages 2113–2122. PMLR. C.1

McEliece, R. J., MacKay, D. J. C., and Cheng, J.-F. (1998). Turbo decoding as an instance of pearl's" belief propagation" algorithm. *IEEE Journal on selected areas in communications*, 16(2):140–152. 1

Metz, L., Maheswaranathan, N., Nixon, J., Freeman, C. D., and Sohl-Dickstein, J. (2019). Understanding and correcting pathologies in the training of learned optimizers. In *International Conference on Machine Learning*. 4.2, C.1

Minka, T. (2019). From automatic differentiation to message passing. Slides for Presentation at Advances and challenges in machine learning languages workshop. [Online; https://tminka.github.io/papers/acmll2019/minka-acmll2019-slides.pdf]. 1

Minka, T. P. (2001). Expectation propagation for approximate bayesian inference. In *Proceedings of the Seventeenth conference on Uncertainty in artificial intelligence*, pages 362–369. 1

Mohamed, S., Rosca, M., Figurnov, M., and Mnih, A. (2020). Monte Carlo gradient estimation in machine learning. *Journal of Machine Learning Research*, 21:1–62. 2.2

Moritz, P., Nishihara, R., Wang, S., Tumanov, A., Liaw, R., Liang, E., Elibol, M., Yang, Z., Paul, W., Jordan, M. I., et al. (2018). Ray: A distributed framework for emerging AI applications. In *13th USENIX Symposium on Operating Systems Design and Implementation (OSDI 18)*, pages 561–577. 1

Oktay, D., McGreivy, N., Aduol, J., Beatson, A., and Adams, R. P. (2020). Randomized automatic differentiation. In *International Conference on Learning Representations*. 1

Owen, A. B. (2013). *Monte Carlo theory, methods and examples*. A.1

Parmas, P. (2018). Total stochastic gradient algorithms and applications in reinforcement learning. In *Advances in Neural Information Processing Systems*, pages 10204–10214. 1, A.1, A.2, A.2, A.2, A.2, A.2, C.3

Parmas, P. (2020). *Total stochastic gradient algorithms and applications to model-based reinforcement learning*. PhD thesis, Okinawa Institute of Science and Technology Graduate University. 1, A.1

Parmas, P., Rasmussen, C. E., Peters, J., and Doya, K. (2018). PIPPS: Flexible model-based policy search robust to the curse of chaos. In *International Conference on Machine Learning*, pages 4062–4071. 1, 2.2, 4.1, 4.2, A.1, A.2, A.2, C.1, 8

Parmas, P. and Sugiyama, M. (2021). A unified view of likelihood ratio and reparameterization gradients. In *International Conference on Artificial Intelligence and Statistics*, pages 4078–4086. PMLR. A.1

Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., et al. (2019). Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32. 1

Paszke, A., Johnson, D. D., Duvenaud, D., Vytiniotis, D., Radul, A., Johnson, M. J., Ragan-Kelley, J., and Maclaurin, D. (2021). Getting to the point: index sets and parallelism-preserving autodiff for pointful array programming. *Proceedings of the ACM on Programming Languages*, 5(ICFP):1–29. 1

Pearl, J. (1982). Reverend bayes on inference engines: a distributed hierarchical approach. In *Proceedings of the Second AAAI Conference on Artificial Intelligence*, pages 133–136. 1, B.1

Ramesh, A., Dhariwal, P., Nichol, A., Chu, C., and Chen, M. (2022). Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*. 6

Rezende, D. J., Mohamed, S., and Wierstra, D. (2014). Stochastic backpropagation and approximate inference in deep generative models. In *International Conference on Machine Learning*, pages 1278–1286. 2.2, A.1

Rogozhnikov, A. (2021). Einops: Clear and reliable tensor manipulations with einstein-like notation. In *International Conference on Learning Representations*. 1

Schulman, J., Heess, N., Weber, T., and Abbeel, P. (2015). Gradient estimation using stochastic computation graphs. In *Advances in Neural Information Processing Systems*, pages 3528–3536. 1, 3.4, 5, A.1

Silver, D., Lever, G., Heess, N., Degris, T., Wierstra, D., and Riedmiller, M. (2014). Deterministic policy gradient algorithms. In *International conference on machine learning*, pages 387–395. PMLR. A.2

Suh, H. J., Simchowitz, M., Zhang, K., and Tedrake, R. (2022). Do differentiable simulators give better policy gradients? In *International Conference on Machine Learning*, pages 20668–20696. PMLR. C.1

Sutton, R. S., McAllester, D. A., Singh, S. P., and Mansour, Y. (2000). Policy gradient methods for reinforcement learning with function approximation. In *Advances in neural information processing systems*, pages 1057–1063. A.2

Tokui, S., Oono, K., Hido, S., and Clayton, J. (2015). Chainer: a next-generation open source framework for deep learning. In *Proceedings of workshop on machine learning systems (LearningSys) in the twenty-ninth annual conference on neural information processing systems (NIPS)*, volume 5, pages 1–6. 1

Tran, D., Kucukelbir, A., Dieng, A. B., Rudolph, M., Liang, D., and Blei, D. M. (2016). Edward: A library for probabilistic modeling, inference, and criticism. *arXiv preprint arXiv:1610.09787*. 1

Wang, Q. (2013). Forward and adjoint sensitivity computation of chaotic dynamical systems. *Journal of Computational Physics*, 235:1–13. C.1

Wang, X. (1991). Period-doublings to chaos in a simple neural network: An analytical proof. *Complex Systems*, 5(4):425–441. 4.1, 4.1, 4, C.1, 8

Weaver, L. and Tao, N. (2001). The optimal reward baseline for gradient-based reinforcement learning. In *Proceedings of the Seventeenth conference on Uncertainty in artificial intelligence*, pages 538–545. Morgan Kaufmann Publishers Inc. A.1

Williams, R. J. (1992). Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256. 2.2

Wu, Z., Pan, S., Chen, F., Long, G., Zhang, C., and Philip, S. Y. (2020). A comprehensive survey on graph neural networks. *IEEE transactions on neural networks and learning systems*, 32(1):4–24. 1

Xu, J., Makoviychuk, V., Narang, Y., Ramos, F., Matusik, W., Garg, A., and Macklin, M. (2021). Accelerated policy learning with parallel differentiable simulation. In *International Conference on Learning Representations*. C.1