Batch Bayesian optimisation via density-ratio estimation with guarantees

Abstract

Bayesian optimisation (BO) algorithms have shown remarkable success in applications involving expensive black-box functions. Traditionally BO has been set as a sequential decision-making process which estimates the utility of query points via an acquisition function and a prior over functions, such as a Gaussian process. Recently, however, a reformulation of BO via density-ratio estimation (BORE) allowed reinterpreting the acquisition function as a probabilistic binary classifier, removing the need for an explicit prior over functions and increasing scalability. In this paper, we present a theoretical analysis of BORE's regret and an extension of the algorithm with improved uncertainty estimates. We also show that BORE can be naturally extended to a batch optimisation setting by recasting the problem as approximate Bayesian inference. The resulting algorithm comes equipped with theoretical performance guarantees and is assessed against other batch BO baselines in a series of experiments.

1 INTRODUCTION

Bayesian optimisation (BO) algorithms provide flexible black-box optimisers for problems involving functions which are noisy or expensive to evaluate [1]. Typical BO approaches place a probabilistic model over the objective function which is updated with every new observation in a sequential decision-making process. Most methods are based on Gaussian process (GP) surrogates [2], which provide closed-form analytic expressions for the model's posterior distribution and allow for a number of theoretical performance guarantees [3–5]. However, GP surrogates have a number of limitations, such as not easily scaling to high-dimensional domains, high computational complexity and requiring a careful choice of covariance function and hyper-parameters [2]. Non-GP-based BO methods have also been proposed in the literature, such as BO methods based on neural networks [6, 7] and random forests [8] regression models.

As an alternative to improving the model, Tiao et al. [9] focus on the acquisition function, which in BO frameworks represents the guide that takes the model predictions into account. They show that one can derive the acquisition function directly without an implicit model by reinterpreting the expected improvement [4, 1] via a density-ratio estimation problem. Applying this perspective, the acquisition function can then be derived as a classification model, which can be represented by flexible parametric models, such as deep neural networks, and efficiently trained via stochastic gradient descent. The resulting method, called *Bayeisan optimisation via density-ratio estimation* (BORE) is then shown to outperform a variety of traditional GP-based and non-GP baselines.

Despite the significant performance gains, BORE has only been applied to a sequential setting and not much is known about the method's theoretical guarantees. Batch BO methods have the potential to speed up optimisation in settings where multiple queries to the objective function can be evaluated simultaneously [10–13]. Given its flexibility to apply models which can scale to large datasets, it

37 is therefore a natural question as to whether BORE can be readily extend to the batch setting in a
38 computationally efficient way.

39 In this paper, we extend the BORE framework to the batch setting and analyse its theoretical
40 performance. To derive theoretical guarantees, we first show that the original BORE can be improved
41 by accounting for uncertainty in the classifier's predictions. We then propose a novel method, called
42 BORE++, which uses an upper confidence bound over the classifier's predictions as its acquisition
43 function. The method comes equipped with guarantees in the probabilistic least-squares setting. We
44 provide extensions for both BORE and BORE++ to the batch setting. Lastly, we present experimental
45 results demonstrating the performance of the proposed algorithms in practical optimisation problems.

2 Related work

47 Since their proposal by Schonlau et al. [14], batch Bayesian optimisation methods have appeared in
48 various forms in the literature. Many methods are based on heuristics derived from estimates given
49 by a Gaussian process regression model [12, 11]. Others are based on Monte Carlo estimates of
50 multi-query acquisition functions [10, 13]. Despite that, the prevalent approaches to batch BO are
51 still based on a GP regression model, which require prior knowledge about the objective function and
52 do not scale to high-dimensional problems. We instead take a different approach by viewing BO as a
53 density-ratio estimation problem following the work by Tiao et al. [9]. For batch design, we take an
54 optimisation-as-inference approach [15, 16] by applying Stein variational gradient descent, a non-
55 parametric approximate inference method [17], which has been recently combined with GP-based
56 BO [18, 19]. Our theoretical results, however, are agnostic to the choice of inference algorithm.

3 Background

58 We consider a global optimisation problem over a compact search space $\mathcal{X} \subset \mathbb{R}^d$ of the form:

$$\mathbf{x}^* \in \underset{\mathbf{x} \in \mathcal{X}}{\operatorname{argmin}} f(\mathbf{x}), \tag{1}$$

59 where $f : \mathcal{X} \to \mathbb{R}$ is assumed to be a black-box objective function, i.e., we have no access to gradients
60 nor analytic formulations of it. In addition, we are only allowed to collect up to T observations
61 $y_t := f(\mathbf{x}_t) + \epsilon_t$, for $t \in \{1, \ldots, T\}$, which are corrupted by additive noise ϵ_t.

3.1 Bayesian optimisation

63 Bayesian optimisation (BO) algorithms approach the problem in Equation 1 via sequential decision
64 making [1]. At each iteration, BO selects a query point $\mathbf{x}_t \in \mathcal{X}$ by maximising an acquisition function
65 $a(\mathbf{x}|\mathcal{D}_t)$.

$$\mathbf{x}_t \in \underset{\mathbf{x} \in \mathcal{X}}{\operatorname{argmax}} \, a(\mathbf{x}|\mathcal{D}_{t-1}) \tag{2}$$

66 The acquisition function encodes information provided by the observations collected so far $\mathcal{D}_t :=$
67 $\{\mathbf{x}_i, y_i\}_{i=1}^{t-1}$ using a probabilistic model over f, typically a Gaussian process (GP) [2], conditioned on
68 the data. After collecting an observation y_t, the dataset is updated with the new query-observation
69 pair $\mathcal{D}_t := \mathcal{D}_{t-1} \cup \mathbf{x}_t, y_t$. This process then repeats for a given number of iterations T.

3.2 The expected improvement algorithm

71 A popular acquisition function in the BO literature is the expected improvement (EI) [4]. At iteration
72 $t \geq 1$, one can define $\tau := \min_{i<t} y_t$ as an incumbent target. The expected improvement is then
73 defined as:

$$a_{\mathrm{EI}}(\mathbf{x}|\mathcal{D}_{t-1}) := \mathbb{E}[\max\{0, \tau - f(\mathbf{x})\} | \mathcal{D}_{t-1}]. \tag{3}$$

74 In the case of a GP prior on $f|\mathcal{D}_{t-1} \sim \mathcal{GP}(\mu_{t-1}, k_{t-1})$, for any point $\mathbf{x}$ where $\sigma_{t-1}(\mathbf{x}) > 0$, the EI
75 is given by:

$$a_{\mathrm{EI}}(\mathbf{x}|\mathcal{D}_{t-1}) = (\tau - \mu_{t-1}(\mathbf{x}))\Psi(s_{t-1}) + \sigma_{t-1}(\mathbf{x})\psi(s_{t-1}), \tag{4}$$

76 where $s_{t-1} := \frac{\tau - \mu_{t-1}(\mathbf{x})}{\sigma_{t-1}(\mathbf{x})}$, if $\sigma_{t-1}^2(\mathbf{x}) := k_{t-1}(\mathbf{x}, \mathbf{x}) > 0$. For points $\mathbf{x} \in \mathcal{X}$ where $\sigma_{t-1}(\mathbf{x}) = 0$,
77 i.e., there is no posterior uncertainty, we set $a_{\mathrm{EI}}(\mathbf{x}|\mathcal{D}_{t-1}) := 0$ by convention. Here $\Psi(s)$ and $\psi(s)$
78 denote, respectively, the cumulative distribution function (CDF) and the probability density function
79 (PDF) of the standard normal distribution evaluated at $s \in \mathbb{R}$.

Algorithm 1: BORE

---

1 **for** $t \in \{1, \ldots, T\}$ **do**
2 $\quad$ $\tau := \hat{\Phi}_{t-1}^{-1}(\gamma)$
3 $\quad$ $z_i := \mathbb{I}[y_i \leq \tau], \quad i \in \{1, \ldots, t-1\}$
4 $\quad$ $\tilde{\mathcal{D}}_{t-1} := \{\mathbf{x}_i, z_i\}_{i=1}^{t-1}$
5 $\quad$ $\hat{\pi}_t \in \operatorname{argmin}_\pi \mathcal{L}[\pi | \tilde{\mathcal{D}}_{t-1}]$
6 $\quad$ $\mathbf{x}_t \in \operatorname{argmax}_{\mathbf{x} \in \mathcal{X}} \hat{\pi}_{t-1}(\mathbf{x})$
7 $\quad$ $y_t := f(\mathbf{x}_t) + \epsilon_t$
8 **end**

3.3 Bayesian optimisation via density-ratio estimation (BORE)

The EI acquisition function can be reformulated as a density ratio between two probability distributions under certain assumptions [20, 9]. Let $\ell(\mathbf{x}) := p(\mathbf{x}|y \leq \tau)$ represent the probability density over $\mathbf{x} \in \mathcal{X}$ conditioned on the observation y being below a threshold $\tau \in \mathbb{R}$. Conversely, let $g(\mathbf{x}) := p(\mathbf{x}|y > \tau)$. For $\gamma \in [0,1]$, the γ-relative density ratio between these two probability densities is:

$$\rho_\gamma(\mathbf{x}) := \frac{\ell(\mathbf{x})}{\gamma \ell(\mathbf{x}) + (1-\gamma)g(\mathbf{x})}, \quad \mathbf{x} \in \mathcal{X}, \tag{5}$$

noting that $\gamma = 0$ leads to the usual probability density ratio definition, $\rho_0(\mathbf{x}) = {\ell(\mathbf{x})}/{g(\mathbf{x})}$. Now if we choose $\tau := \Phi^{-1}(\gamma)$, where $\Phi(s) := p(y \leq s)$ represents the cumulative distribution function of the marginal distribution of observations,[1] for $s \in \mathbb{R}$, and then replace τ in Equation 3, Bergstra et al. [20] have shown that[2] $a_{\mathrm{EI}}(\mathbf{x}) \propto \rho_\gamma(\mathbf{x})$, for $\mathbf{x} \in \mathcal{X}$. Based on this fact, Tiao et al. [9] showed:

$$a_{\mathrm{EI}}(\mathbf{x}) \propto \rho_\gamma(\mathbf{x}) = \gamma^{-1}\pi(\mathbf{x}), \quad \mathbf{x} \in \mathcal{X}, \tag{6}$$

where $\pi(\mathbf{x}) := p(y \leq \tau | \mathbf{x})$ can be approximated by a probabilistic classifier trained with a proper scoring rule, such as the binary cross-entropy loss:

$$\mathcal{L}_t[\pi] := \sum_{i=1}^{t} z_i \log \pi(\mathbf{x}_i) + (1 - z_i)\log(1 - \pi(\mathbf{x}_i)). \tag{7}$$

Other examples of proper scoring rules include the least-squares loss, which leads to probabilistic least-squares classifiers [21], and the zero-one loss. We refer the reader to Gneiting and Raftery [22] for a review and theoretical analysis on this topic.

BORE is summarised in Algorithm 1. As seen, the marginal observations distribution CDF $\Phi(s) := p(y \leq s)$ is replaced by the empirical approximation $\hat{\Phi}_t(s) := \frac{1}{t}\sum_{i=1}^{t}\mathbb{I}[y_i \leq s]$ and its corresponding quantile function $\hat{\Phi}_t^{-1}$. At each iteration, observations are labelled according to the estimated γth quantile τ, and a classifier $\hat{\pi}_t$ is trained by minimising the loss $\mathcal{L}[\pi|\tilde{\mathcal{D}}_t]$ over the data points $\tilde{\mathcal{D}}_t$. A query point $\mathbf{x}_t$ is chosen by maximising the classifier's probabilities, which in our case corresponds to maximising the expected improvement. A new observation is collected, and the algorithm continues running up to a given number of iterations T. As demonstrated, no explicit probabilistic model for f is needed, only a classifier, which can be efficiently trained via, e.g., stochastic gradient descent.

4 Analysis of the BORE framework

In this section, we analyse limitations of the BORE framework in modelling uncertainty and analyse its effects on the algorithm's performance. As presented in Section 3.3, at each iteration $t \geq 1$, the original BORE framework trains a probabilistic classifier $\hat{\pi}_t(\mathbf{x})$ to approximate $p(y \leq \tau | \mathbf{x})$, where τ denotes the γth quantile of the marginal observations distribution, i.e., $p(y \leq \tau) = \gamma$. This approach leads to a maximum likelihood estimate for the classifier $\hat{\pi}$, which may not properly account for the uncertainty in the classifier's approximation.

---

[1]Note that $p(y \leq s) = \int_{\mathcal{X}} p(y \leq s|\mathbf{x})p(\mathbf{x}) \,\mathrm{d}\mathbf{x}$, where we may assume $p(\mathbf{x})$ uniform.
[2]Bergstra et al. [20] and Tiao et al. [9] also rely on the mild assumption that $p(\mathbf{x}|y) \approx \ell(\mathbf{x})$ for all $y \leq \tau$.

Since BORE is based on probabilistic classifiers, instead of regression models as in traditional BO frameworks [1], a natural first question to ask is whether a classifier can guide it to the global optimum of the objective function. The following lemma answers this question and is a basis for our analysis.

Lemma 1. *Let $f : \mathcal{X} \to \mathbb{R}$ be a continuous function over a compact space $\mathcal{X}$. Assume that, for any $\mathbf{x} \in \mathcal{X}$, we observe $y = f(\mathbf{x}) + \epsilon$, where ϵ is i.i.d. noise with a strictly monotonic cumulative distribution function $\Phi_\epsilon : \mathbb{R} \to [0, 1]$. Then, for any $\tau \in \mathbb{R}$, we have:*

$$\operatorname*{argmax}_{\mathbf{x} \in \mathcal{X}} p(y \leq \tau | \mathbf{x}, f) = \operatorname*{argmin}_{\mathbf{x} \in \mathcal{X}} f(\mathbf{x}) \,. \tag{8}$$

Proof. As the observation noise CDF is monotonic, by basic properties of the argmax, we have:

$$\operatorname*{argmax}_{\mathbf{x} \in \mathcal{X}} p(y \leq \tau | \mathbf{x}, f) = \operatorname*{argmax}_{\mathbf{x} \in \mathcal{X}} \Phi_\epsilon(\tau - f(\mathbf{x})) = \operatorname*{argmin}_{\mathbf{x} \in \mathcal{X}} f(\mathbf{x}) \,, \tag{9}$$

which concludes the proof. $\qquad\square$

According to this lemma, maximising class probabilities is equivalent to optimising the objective function when the classifier is optimal, i.e., it has perfect knowledge of f. This result holds for any given threshold $\tau \in \mathbb{R}$. We only make a mild assumption on the CDF of the observation noise Φ_ϵ, which is satisfied for any probability distribution with support covering the real line (e.g. Gaussian, Student-T, Cauchy, etc.).[3]

To analyse BORE's optimisation performance, we will aim to bound the algorithm's instant regret:

$$r_t := f(\mathbf{x}_t) - f(\mathbf{x}^*), \quad t \geq 1, \tag{10}$$

and its cumulative version $R_T := \sum_{t=1}^{T} r_t$. Sub-linear bounds on R_T lead to a no-regret algorithm, since $\lim_{T \to \infty} \frac{R_T}{T} = 0$ and $\min_{t \leq T} r_t \leq \frac{R_T}{T}$.

Assuming that there is an optimal classifier $\pi^* : \mathcal{X} \to [0, 1]$, which is such that $\pi^*(\mathbf{x}) = p(y \leq \tau | \mathbf{x}, f)$, for a given $\tau \in \mathbb{R}$, we can directly relate the classifier probabilities to the objective function f values, since:

$$\pi^*(\mathbf{x}) = p(y \leq \tau | \mathbf{x}, f) = \Phi_\epsilon(\tau - f(\mathbf{x})) \quad \therefore \quad f(\mathbf{x}) = \tau - \Phi_\epsilon^{-1}(\pi^*(\mathbf{x})) \,. \tag{11}$$

The existence of the inverse Φ_ϵ^{-1} is ensured by the strict monotonicity assumption on Φ_ϵ in Lemma 1. Under this observation, the algorithm's regret at any iteration $t \geq 1$ can be bounded in terms of classifier probabilities:

$$r_t = f(\mathbf{x}_t) - f(\mathbf{x}^*) = \Phi_\epsilon^{-1}(\pi^*(\mathbf{x}^*)) - \Phi_\epsilon^{-1}(\pi^*(\mathbf{x}_t)) \leq L_\epsilon(\pi^*(\mathbf{x}^*) - \pi^*(\mathbf{x}_t)) \,, \tag{12}$$

where L_ϵ is any Lipschitz constant for Φ_ϵ^{-1}, which exists since $\mathcal{X}$ is compact. Therefore, we should be able to bound BORE's regret by analysing the approximation error for $\hat{\pi}_t$ at each iteration $t \geq 1$.

Although approximation guarantees for classification algorithms under i.i.d. data settings are well known [28], each observation in BORE depends on the previous ones via the acquisition function. This process is also not necessarily stationary, so that we cannot apply known results for classifiers under stationary processes [29]. In the next section, we consider a particular setting for learning a classifier which allows us to bound the prediction error under BORE's data-generating process.

4.1 Probabilistic least-squares classifiers

We consider the case of probabilistic least-squares (PLS) classifiers [30, 31]. In particular, we model a probabilistic classifier $\pi : \mathcal{X} \to [0, 1]$ as an element of a reproducing kernel Hilbert space (RKHS) $\mathcal{H}$ associated with a positive-definite kernel $k : \mathcal{X} \times \mathcal{X} \to \mathbb{R}$. A RKHS is a space of functions equipped with inner product $\langle \cdot, \cdot \rangle_k$ and norm $\|\cdot\|_k := \sqrt{\langle \cdot, \cdot \rangle_k}$ [32]. For the purposes of this analysis, we will also assume that $k(\mathbf{x}, \mathbf{x}) \leq 1$, for all $\mathcal{X}$.[4] This setting allows for both linear and non-parametric models. Gaussian assumptions on the function space would lead us to GP-based PLS classifiers [2],

---

[3]This result could also be easily extended to distributions with bounded support as long as their CDF is monotonic within it. However, we keep the support as $\mathbb{R}$ for simplicity, and the extension is left for future work.

[4]This assumption can always be satisfied by proper scaling.

but we are not restricted by Gaussianity in our analysis. If the kernel k is universal, as Φ_ϵ is injective, we can also see that the RKHS assumption allows for modelling any continuous function.

For a given $\tau \in \mathbb{R}$, a PLS classifier is obtained by minimising the regularised squared-error loss:

$$\hat{\pi}_t \in \underset{\pi \in \mathcal{H}}{\operatorname{argmin}} \sum_{i=1}^{t} (z_i - \pi(\mathbf{x}_i))^2 + \lambda\|\pi\|_k^2, \quad t \geq 1, \tag{13}$$

where $\lambda > 0$ is a given regularisation factor and $z_i := \mathbb{I}[y_i \leq \tau] \in \{0, 1\}$. In the RKHS case, the solution to the problem above is available in closed form [33, 21] as:

$$\hat{\pi}_t(\mathbf{x}) = \mathbf{k}_t(\mathbf{x})^\mathsf{T}(\mathbf{K}_t + \lambda\mathbf{I})^{-1}\mathbf{z}_t, \quad \mathbf{x} \in \mathcal{X}, t \geq 1, \tag{14}$$

where $\mathbf{k}_t(\mathbf{x}) := [k(\mathbf{x}, \mathbf{x}_1), \ldots, k(\mathbf{x}, \mathbf{x}_t)]^\mathsf{T} \in \mathbb{R}^t$, $\mathbf{K}_t := [k(\mathbf{x}_i, \mathbf{x}_j)]_{i,j=1}^t \in \mathbb{R}^{t \times t}$ and $\mathbf{z}_t := [z_1, \ldots, z_t]^\mathsf{T} \in \mathbb{R}^t$. This PLS approximation may not yield a valid classifier, since it is possible that $\hat{\pi}_t(\mathbf{x}) \notin [0, 1]$ for some $\mathbf{x} \in \mathcal{X}$. However, it allows us to place a confidence interval on the optimal classifier's prediction, as presented in the following theorem, which is based on theoretical results from the online learning literature [34, 35]. Our proofs can be found in the supplement.

Theorem 1. *Given $\tau \in \mathbb{R}$, assume $\pi(\mathbf{x}) := \Phi_\epsilon(\tau - f(\mathbf{x}))$ is such that $\pi \in \mathcal{H}$, and $\|\pi\|_k \leq b$. Let $\{\mathbf{x}_t\}_{t=1}^\infty$ be a $\mathcal{X}$-valued discrete-time stochastic process predictable with respect to the filtration $\{\mathfrak{F}_t\}_{t=0}^\infty$. Let $\{z_t\}_{t=1}^\infty$ be a real-valued stochastic process such that $\nu_t := z_t - \pi(\mathbf{x}_t)$ is 1-sub-Gaussian conditionally on $\mathfrak{F}_{t-1}$, for all $t \geq 1$. Then, for any $\delta \in (0, 1)$, with probability at least $1 - \delta$, we have that:*

$$\forall \mathbf{x} \in \mathcal{X}, \quad |\pi(\mathbf{x}) - \hat{\pi}_t(\mathbf{x})| \leq \beta_t(\delta)\sigma_t(\mathbf{x}), \quad \forall t \geq 1, \tag{15}$$

where $\beta_t(\delta) := b + \sqrt{2\lambda^{-1}\log(|\mathbf{I} + \lambda^{-1}\mathbf{K}_t|^{1/2}/\delta)}$, with $|\mathbf{A}|$ denoting the determinant of matrix $\mathbf{A}$, and $\sigma_t^2(\mathbf{x}) := k(\mathbf{x}, \mathbf{x}) - \mathbf{k}_t(\mathbf{x})^\mathsf{T}(\mathbf{K}_t + \lambda\mathbf{I})^{-1}\mathbf{k}_t(\mathbf{x}), \quad \mathbf{x} \in \mathcal{X}, \quad t \geq 1$.

4.2 Regret analysis for BORE

We now consider BORE with a PLS classifier. For this analysis, we will assume an ideal setting where τ is fixed, possibly corresponding to the true γth quantile of the observations distribution. However, our results hold for any choice of $\tau \in \mathbb{R}$ and can therefore be assumed to approximately hold for a varying τ which is converging to a fixed value. In this setting, the algorithm's choices are given by:

$$\mathbf{x}_t \in \underset{\mathbf{x} \in \mathcal{X}}{\operatorname{argmax}} \hat{\pi}_{t-1}(\mathbf{x}), \tag{16}$$

where $\hat{\pi}_t$ is the estimator in Equation 14. we can then apply Theorem 1 to the classifier-based regret in Equation 12 to obtain a regret bound. For this result, we will also need the following quantity:

$$\xi_N := \max_{\{\mathbf{x}_i\}_{i=1}^N \subset \mathcal{X}} \frac{1}{2}\log|\mathbf{I} + \lambda^{-1}\mathbf{K}_N|, \quad N \geq 1, \tag{17}$$

where the maximisation is taken over the discrete set of locations $\{\mathbf{x}_i\}_{i=1}^N \subset \mathcal{X}$ and $\mathbf{K}_N := [k(\mathbf{x}_i, \mathbf{x}_j)]_{i,j=1}^N$. This quantity denotes the maximum information gain of a Gaussian process model after N observations. We are now ready to state our theoretical result regarding BORE's regret.

Theorem 2. *Under the conditions in Theorem 1, with probability at least $1 - \delta$, $\delta \in (0, 1)$, the instant regret of the BORE algorithm with a PLS classifier after $T \geq 1$ iterations is bounded by:*

$$r_t \leq L_\epsilon\beta_{t-1}(\delta)(\sigma_{t-1}(\mathbf{x}_t) + \sigma_{t-1}(\mathbf{x}^*)), \tag{18}$$

and the cumulative regret by:

$$R_T \leq L_\epsilon\beta_T(\delta)\left(\sqrt{4(T+2)\xi_T} + \sum_{t=1}^T \sigma_{t-1}(\mathbf{x}^*)\right). \tag{19}$$

As Theorem 2 shows, the regret of the BORE algorithm in the PLS setting is comprised of two components. The first term is related to the regret of a GP-UCB algorithm [see 36, Thr. 3] and its known to grow sub-linearly for a few popular kernels, such as the squared exponential and the Matérn class [3, 37]. The second term, however, reflects the uncertainty of the algorithm around the optimum

location $\mathbf{x}^*$. If the algorithm never samples at that location, this second summation might have a mostly linear growth, which will not lead to a vanishing regret. In fact, if we consider Equation 14 and a RKHS with a translation-invariant kernel, we see that, as soon as an observation $z_t = 1$ is collected at a location $\mathbf{x}_t \neq \mathbf{x}^*$, that location will constitute the maximum of the classifier output. Then the algorithm would keep returning to that same location, missing opportunities to sample at $\mathbf{x}^*$.

It is worth noting that Theorem 2 reflects the regret of BORE in an idealistic setting where the algorithm uses the optimal PLS estimator in the function space $\mathcal{H}$. However, if we train a parametric classifier, such as neural network, via gradient descent, the behaviour will not necessarily be the same, and the algorithm might still achieve a good performance. In the original BORE paper, for instance, a parametric classifier is trained by minimising the binary cross-entropy loss [9] and leads to a successful performance in experiments. Neural network models trained via stochastic gradient descent are known to provide approximate samples of a posterior distribution [38, 39], instead of an optimal best-fit predictor, which might make BORE behave like Thompson sampling [40] (see discussion in the appendix). Nevertheless, Theorem 2 still shows us that BORE may get stuck into local optima, which is not ideal for BO methods. In the next section, we present an extension of the BORE framework which addresses this shortcoming.

5 BORE++: improved uncertainty estimates

As discussed in the previous section, the lack of uncertainty quantification in the estimation of the classifier for the original BORE might lead to sub-optimal performance. To address this shortcoming, we present an approach for uncertainty quantification in the BORE framework which leads to improvements in performance and theoretical optimality guarantees. Our approach is based on using an upper confidence bound (UCB) on the predicted class probabilities as the acquisition function for BORE. Due to its improved uncertainty estimates, we call this approach BORE++.

5.1 Class-probability upper confidence bounds

We propose replacing $\hat{\pi}_t$ in Algorithm 1 by an upper confidence bound which is such that:
$$\forall t \geq 1, \quad \pi^*(\mathbf{x}) \leq \pi_{t,\delta}(\mathbf{x}), \quad \forall \mathbf{x} \in \mathcal{X} \tag{20}$$
which with probability greater than $1 - \delta$, given $\delta \in (0, 1)$. Therefore, $\pi_{t,\delta}(\mathbf{x})$ represents an upper quantile over the optimal class probability $\pi^*(\mathbf{x})$. BORE++ selects $\mathbf{x}_t \in \operatorname{argmax}_{\mathbf{x} \in \mathcal{X}} \pi_{t-1,\delta}(\mathbf{x})$.

To derive an upper confidence bound on a classifier's predictions $\pi(\mathbf{x})$, we can take a few different approaches. For a parametric model $\pi_{\boldsymbol{\theta}}$, a Bayesian model updating the posterior $p(\boldsymbol{\theta}|\mathcal{D}_t)$ leads to a corresponding predictive distribution over $\pi_{\boldsymbol{\theta}}(\mathbf{x})$. This is the case of ensemble models [41], for instance, where we approximate predictions $p(y \leq \tau_t|\mathbf{x}, \mathcal{D}_t) \approx \frac{1}{M} \sum_{i=1}^M \pi_{\boldsymbol{\theta}^i}(\mathbf{x})$ with $\boldsymbol{\theta}^i \sim p(\boldsymbol{\theta}|\mathcal{D}_t)$. Instead of using the expected class probability, however, BORE++ uses an (empirical) quantile approximation for $\pi_{t,\delta}$ to ensure Equation 20 holds. Bayesian neural networks [42], random forests [43], dropout methods, etc. [44], also constitute valid approaches for predictive uncertainty estimation. An alternative approach is to place a non-parametric prior over π^*, such as a Gaussian process model [2], which allows for the modelling of uncertainty directly in the function space where π^* lies. In the next section, we present a concrete derivation of BORE++ for the PLS classifier setting which takes the non-parametric perspective and allows us to derive theoretical performance guarantees.

5.2 BORE++ with PLS classifiers

In the PLS setting, the result in Theorem 1 gives us a closed-form expression for a classifier upper confidence bound satisfying the condition in Equation 20. Given $\delta \in (0, 1)$, we set:
$$\pi_{t,\delta}(\mathbf{x}) := \min(1, \max(0, \hat{\pi}_t(\mathbf{x}) + \beta_t(\delta)\sigma_t(\mathbf{x}))) \in [0, 1], \quad \mathbf{x} \in \mathcal{X}, \tag{21}$$
where σ_t and β_t are set according to Theorem 1. We then obtain the following result for BORE++.

Theorem 3. *Under the assumptions in Theorem 1, running the BORE++ algorithm with a PLS classifier $\pi_{t,\delta}$ as defined above yields, with probability at least $1 - \delta$, an instant regret bound of:*
$$r_t \leq 2L_\epsilon \beta_t(\delta)\sigma_t(\mathbf{x}), \quad \forall t \geq 1, \tag{22}$$
and a cumulative regret bound after $T \geq 1$ iterations:
$$R_T \leq 4L_\epsilon \beta_T(\delta)\sqrt{(T+2)\xi_T} \in \mathcal{O}\left(\sqrt{T}(b\sqrt{\xi_T} + \xi_T)\right). \tag{23}$$

According to Theorem 3, the regret of BORE++ vanishes if the maximum information gain ξ_T grows sub-linearly, since $\lim_{T \to \infty} \frac{R_T}{T} = 0$ and $\min_{t \le T} r_t \le \frac{R_T}{T}$. Sub-linear growth is known to be achieved for popular kernels, such as the squared exponential, the Matérn family and linear kernels [3, 37]. This result also tells us that theoretically BORE++ performs no worse than GP-UCB since they share similar regret bounds [3, 36]. However, in practice, the BORE++ framework offers a series of practical advantages over GP-UCB, such as no need for an explicit surrogate model, and a classifier which does not need to be a GP and can therefore be more flexible and scalable to high-dimensional problems and large amounts of data. The connection with GP-UCB, instead, brings us new insights into how the density-ratio BO algorithm can still share some of the well known guarantees of traditional BO methods.

6 Batch BORE

This section proposes an extension of the BORE framework which allows for multiple queries to the objective function to be performed in parallel. Although many methods for batch BO have been previously proposed in the literature, we here focus on approaching batch optimisation as an approximate Bayesian inference problem. Instead of having to derive complex heuristics to approximate the utility of a batch of query points, we can view points in a batch as samples from a posterior probability distribution which uses the acquisition function as a likelihood.

6.1 BORE batches via approximate inference

Applying an optimisation-as-inference perspective to BORE, we can formulate a batch BO algorithm which does not require an explicit regression model for f. The classifier $\hat{\pi}(\mathbf{x}) \approx p(y \le \tau | \mathbf{x})$ naturally turns out as a likelihood function over query locations $\mathbf{x} \in \mathcal{X}$. Since the search space $\mathcal{X}$ is compact, we can assume a uniform prior distribution $p(\mathbf{x}) \propto 1$. Also note that the normalisation constant in this case is simply $\int_{\mathcal{X}} p(y \le \tau | \mathbf{x}) p(\mathbf{x}) \, \mathrm{d}\mathbf{x} = p(y \le \tau) = \gamma$. Our posterior distribution then becomes:

$$\ell(\mathbf{x}) = p(\mathbf{x} | y \le \tau) = \frac{p(y \le \tau | \mathbf{x}) p(\mathbf{x})}{p(y \le \tau)} \, . \tag{24}$$

Therefore, we formulate a batch version of BORE as an inference problem aiming for:

$$q^* \in \underset{q \in \mathcal{P}}{\arg\min} \, D_{\mathrm{KL}}(q || \ell), \tag{25}$$

where $D_{\mathrm{KL}}(q || \ell)$ denotes the Kullback-Leibler (KL) divergence between q and ℓ, and $\mathcal{P}$ represents the space of probability distributions over $\mathcal{X}$. Sampling from ℓ would allow us to obtain the points of interest in the search space, including the optimum $\mathbf{x}^*$ and other locations where $y \le \tau$. However, as the true $p(y \le \tau | \mathbf{x})$ is unknown, we instead formulate a proxy inference problem with respect to a surrogate target distribution $\hat{p}_t$ based on the classifier model. For BORE, we set $\hat{p}_t(\mathbf{x}) \propto \hat{\pi}_{t-1}(\mathbf{x})$, while for BORE++ the setting is $\hat{p}_t(\mathbf{x}) \propto \pi_{t-1,\delta}(\mathbf{x})$. In contrast to $\ell(\mathbf{x}) \propto p(y \le \tau | \mathbf{x})$, the normalisation constant for the surrogate distributions is unknown, leading us to a proxy problem:

$$q_t \in \underset{q \in \mathcal{P}}{\arg\min} \, D_{\mathrm{KL}}(q || \hat{p}_t) \tag{26}$$

The variational inference problem above can be efficiently solved via Stein variational gradient descent (SVGD) [17], which we describe next.

6.2 Batch sampling via Stein variational gradient descent

In our implementation, we apply SVGD to approximately sample a batch $\mathcal{B}_t := \{\mathbf{x}_{t,i}\}_{i=1}^{M}$ of $M \ge 1$ points from $\hat{p}_t$. Other approximate inference algorithms could also be applied. One of the main advantages of SVGD, however, is that it encourages diversification in the batch, capturing the possible multimodality of $\hat{p}_t$. Given the batch locations, observations can be collected in parallel and then added to the dataset to update the classifier model.

SVGD is an approximate inference algorithm which represents a variational distribution q as a set of particles $\{\mathbf{x}^i\}_{i=1}^{M}$ [17]. The particles are initialised as i.i.d. samples from an arbitrary base distribution

(a) Regret	(b) Objective function example

Figure 1: Theory assessment experiment results. The plots show the averaged regret as a function of the number of iterations. Results were averaged over 10 trials. The shaded area corresponds to the 95% confidence interval obtained by linear interpolation.

and then optimised via a sequence of smooth transformations towards the target distribution, which in our case corresponds to $\hat{p}_t \propto \pi_{t-1,\delta}$. The SVGD steps are given by:

$$\mathbf{x}_t^i \leftarrow \mathbf{x}_t^i + \alpha \boldsymbol{\zeta}_t(\mathbf{x}_t^i), \quad i \in \{1, \ldots, M\}, \tag{27}$$

$$\boldsymbol{\zeta}_t(\mathbf{x}) := \frac{1}{M} \sum_{j=1}^{M} k(\mathbf{x}_t^j, \mathbf{x}) \nabla_{\mathbf{x}_t^j} \log \pi_{t-1,\delta}(\mathbf{x}^j) + \nabla_{\mathbf{x}_t^j} k(\mathbf{x}_t^j, \mathbf{x}), \tag{28}$$

where $k : \mathcal{X} \times \mathcal{X} \to \mathbb{R}$ is a positive-definite kernel, and $\alpha > 0$ is a small step size. Intuitively, the first term in the definition of $\boldsymbol{\zeta}_t$ guides the particles to the modes of $\hat{p}_t$, while the second term encourages diversification by repelling nearby particles. Theoretical convergence guarantees [23, 24] and practical extensions, such as second-order methods [25, 26] and derivative-free approaches [27], have been proposed in the literature. Further details on SVGD can be found in Liu and Wang [17].

6.3 Regret bound for Batch BORE++ with PLS classifiers

We follow the derivations in Oliveira et al. [45] to derive a distributional regret bound for batch BORE++ with respect to its target sampling distribution ℓ, which is presented in the following result.

Theorem 4. *Under the same assumptions in Theorem 1, running batch BORE++ with $\pi_{t,\delta}$ set as in Equation 21, we obtain a bound on the instantaneous distributional regret:*

$$\bar{r}_t := \mathbb{E}_{\mathbf{x} \sim \hat{p}_t}[f(\mathbf{x})] - \mathbb{E}_{\mathbf{x} \sim \ell}[f(\mathbf{x})] \leq 2 L_\epsilon L_\pi \beta_{t-1}(\delta) \mathbb{E}_{q_t}[\sigma_{t-1}], \quad t \geq 1, \tag{29}$$

where $L_\pi := \max_{\mathbf{x} \in \mathcal{X}} \frac{1}{\pi(\mathbf{x})}$, and on the cumulative distributional regret at $T \geq 1$:

$$\bar{R}_T := \sum_{t=1}^{T} \bar{r}_t \leq 4 L_\epsilon L_\pi \beta_T(\delta) \sqrt{(T+2)\xi_T} \in \mathcal{O}(\sqrt{T}(b\sqrt{\xi_T} + \sqrt{\xi_T \xi_{MT}})) \tag{30}$$

both of which hold with probability at least $1 - \delta$.

As in the case of non-batch BORE++, the distributional regret bounds for the batch algorithm also grow sub-linearly for most popular kernels, leading to an asymptotically vanishing simple regret. Although different, to compare the distributional regret of batch BORE++ with the non-distributional regret bounds for BORE++, we may consider a case where τ is set to the function minimum $\tau := f(\mathbf{x}^*) = \min_{\mathbf{x} \in \mathcal{X}} f(\mathbf{x})$ and the observation noise is small. In this case, the batch sampling distribution would converge to a Dirac at the optimum, so that $\mathbb{E}_{\mathbf{x} \sim \ell}[f(\mathbf{x})] \approx f(\mathbf{x}^*)$. Compared to the regret of non-batch BORE++ (Theorem 3) after collecting an equivalent number of observations $T' := MT$, the expected regret of the batch version of BORE++ after T iterations is then lower by a factor of ξ_T / ξ_{MT}, noting that $\xi_T \leq \xi_{T'} = \xi_{MT}$. Therefore, batch BORE++ should be able to achieve lower regret per runtime than sequential BORE++ with an equivalent number of observations.

7 Experiments

This section presents experiments assessing the theoretical results and evaluating batch BORE on a series of global optimisation benchmarks. We compared our methods against GP-based BO baselines in both experiments sets. Additional experiments and details are presented in the appendix.

Figure 2: Performance on global optimisation benchmarks. The plots show the simple regret, i.e., $\min_{t \leq T} r_t$, of each algorithm as a function of the number of iterations T. Results were averaged over 5 trials. The shaded area corresponds to the 95% confidence interval obtained by linear interpolation.

7.1 Theory assessment

We first present simulated experiments assessing the theoretical results in practice testing BORE and BORE++ in the PLS setting. As a baseline, we compare both methods against GP-UCB. This experiment was run by generating a random base classifier in the RKHS $\mathcal{H}_k$ and then a corresponding objective function via the inverse noise CDF Φ_ϵ^{-1}. The search space was set as a uniformly-sampled finite subset of the unit interval $\mathcal{X} := [0, 1] \subset \mathbb{R}$. We applied the theory-backed settings for BORE++ (Section 3.3) and GP-UCB [35], while BORE employed the optimal PLS classifier (Equation 14).

As the results in Figure 1 show, BORE using an optimal PLS classifier simply gets stuck at a its initial point, resulting in constant regret. BORE++, however, is able to progress in the optimisation problem towards the global optimum, outperforming the GP-UCB baseline.

7.2 Global optimisation benchmarks

We evaluated the proposed SVGD-based batch BORE method in a series of test functions for global optimisation comparing it against other BO baselines. In particular, for our comparisons, we ran the locally penalised EI (LP-EI) method [11] and the Monte Carlo based q-EI method [10], which are both based on the EI algorithm, like BORE. Results are presented in Figure 2. All methods ran for $T := 200$ iterations and used of batch size of 10 evaluations per iteration. Additional experimental details are deferred to the supplementary material.

As Figure 2 shows, batch BORE is able to outperform its baselines on most of the global optimisation benchmarks. We also note that, in some case, due to its complexity the LP-EI method becomes computationally infeasible after 100 iterations, having to be aborted halfway through the optimisation. Batch BORE, however, is able to maintain steady performance throughout its runs.

8 Conclusion

This paper presented an extension of the BORE framework to the batch setting alongside the theoretical analysis of the proposed extension and an improvement over the original BORE. Theoretical results in terms of regret bounds and experimental results show that BORE methods are able to obtain performance guarantees and outperform traditional BO baselines. As future work, we plan to investigate BORE under different loss functions and analyse other batch design settings.

References

[1] Bobak Shahriari, Kevin Swersky, Ziyu Wang, Ryan P. Adams, and Nando De Freitas. Taking the human out of the loop: A review of Bayesian optimization. *Proceedings of the IEEE*, 104 (1):148–175, 2016.

[2] Carl E. Rasmussen and Christopher K. I. Williams. *Gaussian Processes for Machine Learning*. The MIT Press, Cambridge, MA, 2006.

[3] Niranjan Srinivas, Andreas Krause, Sham M. Kakade, and Matthias Seeger. Gaussian Process Optimization in the Bandit Setting: No Regret and Experimental Design. In *Proceedings of the 27th International Conference on Machine Learning (ICML 2010)*, pages 1015–1022, 2010.

[4] Adam D. Bull. Convergence Rates of Efficient Global Optimization Algorithms. *Journal of Machine Learning Research (JMLR)*, 12:2879–2904, 2011.

[5] Zi Wang, Beomjoon Kim, and Leslie Kaelbling. Regret bounds for meta Bayesian optimization with an unknown Gaussian process prior. In *Conference on Neural Information Processing Systems*, Montreal, Canada, 2018.

[6] Jasper Snoek, Oren Rippel, Kevin Swersky, Ryan Kiros, Nadathur Satish, Narayanan Sundaram, M Patwary, Prabhat, and R Adams. Scalable Bayesian optimization using deep neural networks. In *International Conference on Machine Learning (ICML)*, Lille, France, 2015.

[7] Jost Tobias Springenberg, Klein Aaron, Stefan Falkner, and Frank Hutter. Bayesian optimization with robust Bayesian neural networks. In *Advances in Neural Information Processing Systems (NIPS)*, Barcelona, Spain, 2016.

[8] Frank Hutter, Holger H Hoos, and Kevin Leyton-Brown. Sequential model-based optimization for general algorithm configuration. In *International conference on learning and intelligent optimization*, pages 507–523. Springer, 2011.

[9] Louis C Tiao, Aaron Klein, Matthias Seeger, Edwin V Bonilla, Cédric Archambeau, and Fabio Ramos. Bayesian Optimization by Density-Ratio Estimation. In *Proceedings of the 38th International Conference on Machine Learning*, Proceedings of Machine Learning Research. PMLR, Jul 2021.

[10] Jasper Snoek, Hugo Larochelle, and Ryan P. Adams. Practical bayesian optimization of machine learning algorithms. In F. Pereira, C. J. C. Burges, L. Bottou, and K. Q. Weinberger, editors, *Advances in Neural Information Processing Systems 25*, pages 2951–2959. Curran Associates, Inc., 2012.

[11] Javier Gonzalez, Zhenwen Dai, Philipp Hennig, and Neil D. Lawrence. Batch Bayesian optimization via local penalization. In *International Conference on Artificial Intelligence and Statistics (AISTATS)*, pages 648–657, Cadiz, Spain, 2016.

[12] Zi Wang, Chengtao Li, Stefanie Jegelka, and Pushmeet Kohli. Batched high-dimensional Bayesian optimization via structural kernel learning. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 3656–3664, International Convention Centre, Sydney, Australia, 2017. PMLR.

[13] James T. Wilson, Frank Hutter, and Marc Peter Deisenroth. Maximizing acquisition functions for Bayesian optimization. In *32nd Conference on Neural Information Processing Systems (NeurIPS 2018)*, Montréal, Canada, 2018.

[14] Matthias Schonlau, William J. Welch, and Donald R. Jones. Global versus local search in constrained optimization of computer models. *New Developments and Applications in Experimental Design*, 34:11–25, 1998.

[15] Emanuel Todorov. General duality between optimal control and estimation. In *Proceedings of the 47th IEEE Conference on Decision and Control*, Cancun, Mexico, 2008.

[16] Matthew Fellows, Anuj Mahajan, Tim G. J. Rudner, and Shimon Whiteson. VIREL: A variational inference framework for reinforcement learning. In *33rd Conference on Neural Information Processing Systems (NeurIPS 2019)*, Vancouver, Canada, 2019.

[17] Qiang Liu and Dilin Wang. Stein variational gradient descent: A general purpose Bayesian inference algorithm. In *Advances in Neural Information Processing Systems (NIPS)*, 2016.

[18] Chengyue Gong, Jian Peng, and Qiang Liu. Quantile Stein Variational Gradient Descent for Batch Bayesian Optimization. In *Proceedings of the 36th International Conference on Machine Learning*, Long Beach, CA, USA, 2019.

[19] Rafael Oliveira, Lionel Ott, and Fabio Ramos. Distributional Bayesian optimisation for variational inference on black-box simulators. In *2nd Symposium on Advances in Approximate Bayesian Inference*, Vancouver, Canada, 2019.

[20] James S Bergstra, Rémi Bardenet, Yoshua Bengio, and Balázs Kégl. Algorithms for Hyperparameter Optimization. In *Advances in Neural Information Processing Systems*, pages 2546–2554, 2011.

[21] Masashi Sugiyama, Hirotaka Hachiya, Makoto Yamada, Jaak Simm, and Hyunha Nam. Least-squares probabilistic classifier: A computationally efficient alternative to kernel logistic regression. In *Proceedings of International Workshop on Statistical Machine Learning for Speech Processing (IWSML2012)*, Kyoto, Japan, 2012.

[22] Tilmann Gneiting and Adrian E Raftery. Strictly proper scoring rules, prediction, and estimation. *Journal of the American Statistical Association*, 102(477):359–378, 2007.

[23] Qiang Liu. Stein variational gradient descent as gradient flow. In *Advances in Neural Information Processing Systems*, pages 8854–8863, Long Beach, CA, USA, 2017.

[24] Anna Korba, Adil Salim, Michael Arbel, Giulia Luise, and Arthur Gretton. A non-asymptotic analysis for Stein variational gradient descent. In *Advances in Neural Information Processing Systems*, Vancouver, Canada, 2020.

[25] Gianluca Detommaso, Tiangang Cui, Alessio Spantini, Youssef Marzouk, and Robert Scheichl. A Stein variational Newton method. In *32nd Conference on Neural Information Processing Systems (NeurIPS 2018)*, Montréal, Canada, 2018.

[26] Chang Liu, Jingwei Zhuo, Pengyu Cheng, Ruiyi Zhang, Jun Zhu, and Lawrence Carin. Understanding and accelerating particle-based variational inference. In *36th International Conference on Machine Learning (ICML 2019)*, Long Beach, CA, 2019.

[27] Jun Han and Qiang Liu. Stein variational gradient descent without gradient. In *35th International Conference on Machine Learning (ICML 2018)*, 2018.

[28] Andrew R Barron. Approximation and estimation bounds for artificial neural networks. *Machine learning*, 14(1):115–133, 1994.

[29] Ingo Steinwart and Andreas Christmann. Fast learning from Non-i.i.d. observations. In *Advances in Neural Information Processing Systems 22*, pages 1768–1776, 2009.

[30] Reinhard Selten. Axiomatic characterization of the quadratic scoring rule. *Experimental Economics*, 1(1):43–62, 1998.

[31] J. A. K. Suykens and J. Vandewalle. Least squares support vector machine classifier. *Neural Processing Letters*, 9:293–300, 1999.

[32] Bernhard Schölkopf and Alexander J. Smola. *Learning with kernels: support vector machines, regularization, optimization, and beyond*. MIT Press, Cambridge, Mass, 2002.

[33] Yasin Abbasi-Yadkori, David Pal, and Csaba Szepesvari. Improved Algorithms for Linear Stochastic Bandits. In *Advances in Neural Information Processing Systems (NIPS)*, pages 1–19, 2010.

[34] Yasin Abbasi-Yadkori. *Online Learning for Linearly Parametrized Control Problems*. Phd, University of Alberta, 2012.

[35] Audrey Durand, Odalric-Ambrym Maillard, and Joelle Pineau. Streaming kernel regression with provably adaptive mean, variance, and regularization. *Journal of Machine Learning Research*, 19(1):650–683, 2018.

[36] Sayak Ray Chowdhury and Aditya Gopalan. On Kernelized Multi-armed Bandits. In *Proceedings of the 34th International Conference on Machine Learning (ICML)*, Sydney, Australia, 2017.

[37] Sattar Vakili, Kia Khezeli, and Victor Picheny. On information gain and regret bounds in gaussian process bandits. In Arindam Banerjee and Kenji Fukumizu, editors, *Proceedings of The 24th International Conference on Artificial Intelligence and Statistics*, volume 130 of *Proceedings of Machine Learning Research*, pages 82–90. PMLR, 13–15 Apr 2021.

[38] Johnathan M Bardsley, Antti Solonen, Heikki Haario, and Marko Laine. Randomize-then-optimize: A method for sampling from posterior distributions in nonlinear inverse problems. *SIAM Journal on Scientific Computing*, 36(4):A1895 – A1910, 2014.

[39] Stephan Mandt, Matthew D. Hoffman, and David M. Blei. Stochastic gradient descent as approximate Bayesian inference. *Journal of Machine Learning Research*, 18, 2017.

[40] Daniel Russo and Benjamin Van Roy. An Information-Theoretic Analysis of Thompson Sampling. *Journal of Machine Learning Research (JMLR)*, 17:1–30, 2016.

[41] Lior Rokach. Ensemble-based classifiers. *Artificial intelligence review*, 33(1):1–39, 2010.

[42] William D Penny and Stephen J Roberts. Bayesian neural networks for classification: how useful is the evidence framework? *Neural networks*, 12(6):877–892, 1999.

[43] Yali Amit and Donald Geman. Shape quantization and recognition with randomized trees. *Neural Computation*, 9(7):1545–1588, 07 1997.

[44] Nicholas G. Polson and Vadim Sokolov. Deep learning: A Bayesian perspective. *Bayesian Analysis*, 12(4):1275–1304, 2017.

[45] Rafael Oliveira, Lionel Ott, and Fabio Ramos. No-Regret Approximate Inference via Bayesian Optimisation. In *37th Conference on Uncertainty in Artificial Intelligence (UAI 2021)*, 2021.