# RISP: Rendering-Invariant State Predictor with Differentiable Simulation and Rendering for Cross-Domain Parameter Estimation

## Abstract

This work considers identifying parameters characterizing a physical system's dynamic motion directly from a video whose rendering configurations are inaccessible. Existing solutions require massive training data or lack generalizability to unknown rendering configurations. We propose a novel approach that marries domain randomization and differentiable rendering gradients to address this problem. Our core idea is to train a rendering-invariant state-prediction (RISP) network that transforms image differences into state differences independent of rendering configurations, e.g., lighting, shadows, or material reflectance. To train this predictor, we formulate a new loss on rendering variances using gradients from differentiable rendering. Moreover, we present an efficient, second-order method to compute the gradients of this loss, allowing it to be integrated seamlessly into modern deep learning frameworks. We evaluate our method in rigid-body and deformable-body environments using four tasks: state estimation, system identification, imitation learning, and visuomotor control, including a challenging task of emulating dexterous motion of a robotic hand from a video. Compared with existing methods, our approach achieves significantly lower errors in almost all tasks and has better generalizability among unknown rendering configurations[1].

## 1 Introduction

Reconstructing dynamic information about a physical system directly from a video has received considerable attention in the robotics, machine learning, computer vision, and graphics communities. This problem is fundamentally challenging because of its deep coupling among physics, geometry, and perception of a system. Traditional solutions like motion capture systems (Vicon; OptiTrack; Qualisys) can provide high-quality results but require prohibitively expensive external hardware platforms. More recent development in differentiable simulation and rendering provides an inexpensive and attractive alternative to the motion capture systems and has shown promising proof-of-concept results (Jatavallabhula et al., 2021). However, existing methods in this direction typically assume the videos come from a *known* renderer. Such an assumption limits their usefulness in inferring dynamic information from an *unknown* rendering domain, which is common in real-world applications due to the discrepancy between rendering and real-world videos. Existing techniques for aligning different rendering domains, e.g., CycleGAN (Zhu et al., 2017), may help alleviate this issue. However, they typically require access to the target domain with massive data, which is not always available. To our best knowledge, inferring dynamic parameters of a physical system directly from videos under *unknown* rendering conditions remains far from being solved, and our work aims to fill this gap.

Our work proposes a novel approach by combining three key ideas to address this challenging problem: domain randomization, state estimation, and rendering gradients. Domain randomization is a classic technique for transferring knowledge between domains, e.g., deploying control policy trained in simulation to hardware platforms. The key idea is to let the algorithm in the source domain see massive samples under varying rendering configurations so that it is robust to discrepancies between source and target domains. We borrow this classic idea but upgrade it with two key innovations that substantially improve its effectiveness in our problem. First, we notice that image differences

---

[1]Project page: https://sites.google.com/view/risp-iclr-2022/home.

| Quadrotor | Cube | Hand | Rod |
|:---:|:---:|:---:|:---:|

Figure 1: A gallery of our four environments (left to right) across three rendering domains (top to bottom). For each environment, we train a RISP with images under varying lighting, background, and materials generated from a differentiable render (top). Each environment then aims to find proper system and control parameters to simulate and render the physical system (middle) so that it matches the dynamic motion of a reference video (bottom) with unknown rendering configurations. We deliberately let three rows use renderers with vastly different rendering configurations.

are sensitive to changes in rendering configurations. Therefore, they hardly reflect those rendering-invariant, dynamics-related parameters that we genuinely aim to match. This observation motivates us to propose a rendering-invariant state predictor (RISP) that extracts state information of a physical system from videos. By comparing in the state space instead of the image space, we rule out the interference of varying rendering configurations in videos from different rendering domains.

The second innovation in our approach is to leverage rendering gradients from a differentiable renderer. Traditionally, domain randomization exploits data in the source domain without using their first-order information. Now that we have access to a differentiable renderer, their rendering gradients provide rich information that we should make full use of to train RISP. Essentially, requiring the output of RISP to be agnostic to rendering configurations equals enforcing its gradients for rendering parameters to be zero. Based on this idea, we propose a new loss function using rendering gradients and show an efficient method for integrating it into modern deep learning frameworks.

Putting all these ideas together, we provide a powerful pipeline that effectively infers parameters of a physical system directly from video input under random rendering configurations. We demonstrate the efficacy of our approach on a variety of challenging tasks, including state estimation, system identification, imitation learning, and visuomotor control, with input videos generated from unknown rendering conditions. We evaluate these tasks on rigid-body systems with and without contact, an articulate-body system, and a deformable-body system (Fig. 1), including a challenging dexterous hand (Xu et al., 2021). The experimental results show that our approach outperforms the state-of-the-art technique (Jatavallabhula et al., 2021) by a large margin in most of these tasks, which is primarily due to the inclusion of rendering gradients in the training process.

In summary, our work makes the following contributions. First, we investigate and identify the bottleneck in inferring state, system, and control parameters of physical systems from videos under various rendering configurations (Sec. 3.1). Second, we propose a novel solution that combines domain randomization, state estimation, and differentiable rendering gradients to achieve general-izability across multiple rendering domains (Sec. 3.2). Third, we demonstrate the efficacy of our approach on several challenging tasks in rigid-body and deformable-body environments, including state estimation, system identification, imitation learning, and visuomotor control (Sec. 4). We will release our code and data along with the paper upon publication for readers to reproduce our results.

## 2 RELATED WORK

**Differentiable simulation** Differentiable simulation is a family of simulation methodology that equips traditional simulation with gradient information for simulation inputs. This additional gradient

Figure 2: An overview of our method (Sec. 3). We first train RISP using images rendered with random states and rendering parameters (top). We then append RISP to the output of a differentiable renderer, leading to a fully differentiable pipeline from system and control parameters to states predicted from images (middle). Given reference images generated from unknown parameters (dashed gray boxes) in the target domain (bottom), we feed them to RISP and minimize the discrepancies between predicted states (rightmost green-gray box) to reconstruct the underlying system parameters, states, or actions.

information connects simulation tasks with classic numerical optimization techniques. Previous works have demonstrated the power of gradients from a differentiable simulator in rigid-body dynamics (Geilinger et al., 2020; Degrave et al., 2019; de Avila Belbute-Peres et al., 2018; Xu et al., 2021), deformable-body dynamics (Du et al., 2021b;a; Hu et al., 2019; Hahn et al., 2019), fluids (Du et al., 2020; McNamara et al., 2004; Hu et al., 2020), and co-dimensional objects (Qiao et al., 2020; Liang et al., 2019), many of which show successful applications in system identification (Hahn et al., 2019), trajectory optimization (Hu et al., 2019), and closed-loop control (Du et al., 2021b). Our work is closely related to the progress in this field as we make heavy use of differentiable simulators in our pipeline. However, our contribution is orthogonal to them: we treat differentiable simulation as a black box, and our proposed approach is agnostic to the choice of simulators, as demonstrated by our environments involving rigid bodies, articulated bodies, and deformable bodies.

**Differentiable rendering** Differentiable rendering methods offer gradient information for rendering inputs, e.g., lighting, materials, cameras, or shapes (Ramamoorthi et al., 2007; Li et al., 2015; Jarosz et al., 2012). The state-of-the-art differentiable renderers (Li et al., 2018; Nimier-David et al., 2019) are very powerful in handling sophisticated gradients even with the existence of discontinuities from occlusion or advanced global illumination effects. Our work leverages the power of these differentiable renderers but with a quite different focus: while these differentiable renderers typically optimize rendering parameters using gradient-based optimization, our work instead uses rendering gradients as guidance to optimize parameters external to the renderer, which we hope can broaden the potential applications for differentiable rendering in the future.

**Domain randomization** Our approach is closely related to domain randomization in the learning and robotics communities for transferring knowledge between domains having discrepancies (Tobin et al., 2017; Peng et al., 2018; Andrychowicz et al., 2020; Sadeghi & Levine, 2017; Tan et al., 2018). The intuition is that a model can hopefully cross the domain discrepancy by seeing a large amount of random data in the source domain. This often requires tedious data generation and leads to robust but conservative performances in the target domain. Our core idea in this work is distinctive from this line of research in that the generalizability of our method comes from a more *accurate* model that aims to match first-order gradient information, while the generalizability of domain randomization comes from a more *robust* model that attempts to absorb domain discrepancies by behaving conservatively.

## 3 METHOD

Given a video showing the dynamic motion of a physical system, our goal is to infer the unknown state, system, or control parameters directly from the video, with partial knowledge about the physics

model and rendering conditions. Specifically, we assume we know the governing equations of the physical system (e.g., Newton's law for rigid-body systems) and the camera position in the video, but the exact system, control, or rendering parameters are not exposed.

To solve this problem, we propose a pipeline that consists of two components: 1) a differentiable simulation and rendering engine; 2) a novel rendering-invariant state-prediction network (RISP). Our differentiable simulation and rendering engine simulates and renders the state of a physical system into an image output, and RISP learns to reconstruct state information of the physical system from images generated under varying rendering configurations. Putting these two components together, we have a pipeline that can faithfully recover dynamic information of a physical system from a new video with unseen rendering configurations. We give an overview of our approach in Fig. 2.

## 3.1 DIFFERENTIABLE SIMULATION AND RENDERING ENGINE

Given a physical system with known dynamic model $\mathcal{M}$, we first use a differentiable simulator to simulates its states based on action inputs at each time step after time discretization:

$$\mathbf{s}_{i+1} = \mathcal{M}_{\phi}(\mathbf{s}_i, \mathbf{a}_i), \quad \forall i = 0, 1, \cdots, N-1, \tag{1}$$

where $N$ is the number of time steps in a rollout of physics simulation, and $\mathbf{s}_i$, $\mathbf{s}_{i+1}$ and $\mathbf{a}_i$ represent the state and action vectors at the corresponding time steps, respectively. The $\phi$ vector encodes the system parameters in the model, e.g., mass, inertia, and elasticity. Next, we apply a differentiable renderer $\mathcal{R}$ to generate an image $\mathbf{I}_i$ for each state $\mathbf{s}_i$:

$$\mathbf{I}_i = \mathcal{R}_{\psi}(\mathbf{s}_i), \quad \forall i = 0, 1, \cdots, N. \tag{2}$$

Here, $\psi$ is a vector encoding rendering parameters whose gradients are available in the renderer $\mathcal{R}$. Examples of $\psi$ include light intensity, material reflectance, or background color. By abuse of notation, we re-write the workflow of our simulation and rendering engine to a compact form:

$$\{\mathbf{I}_i\} = \mathcal{R}_{\psi}[\underbrace{\mathcal{M}_{\phi}(\mathbf{s}_0, \{\mathbf{a}_i\})}_{\{\mathbf{s}_i\}}]. \tag{3}$$

In other words, given an initial state $\mathbf{s}_0$ and a sequence of actions $\{\mathbf{a}_i\}$, we generate a sequence of states $\{\mathbf{s}_i\}$ from simulation and renders the corresponding image sequence $\{\mathbf{I}_i\}$. The task of recovering unknown information from a reference video $\{\mathbf{I}_i^{\text{ref}}\}$ can be formulated as follows:

$$\min_{\mathbf{s}_0, \{\mathbf{a}_i\}, \phi, \psi} \quad \mathcal{L}(\{\mathbf{I}_i^{\text{ref}}\}, \{\mathbf{I}_i\}), \tag{4}$$

$$\text{s.t.} \quad \{\mathbf{I}_i\} = \mathcal{R}_{\psi}[\mathcal{M}_{\phi}(\mathbf{s}_0, \{\mathbf{a}_i\})], \tag{5}$$

where $\mathcal{L}$ is a loss function penalizing the difference between the generated images and their references. Assuming that the simulator $\mathcal{M}$ and the renderer $\mathcal{R}$ are differentiable with respect to their inputs, we can run gradient-based optimization algorithms to solve Eqn. (4). This is essentially the idea proposed in $\nabla\text{Sim}$, the state-of-the-art method for identifying parameters directly from video inputs (Jatavallabhula et al., 2021). Specifically, $\nabla\text{Sim}$ defines $\mathcal{L}$ as a norm on pixelwise differences.

One major limitation in Eqn. (4) is that it expects reasonably similar initial images $\{\mathbf{I}_i\}$ and references $\{\mathbf{I}_i^{\text{ref}}\}$ to successfully solve the optimization problem. Indeed, since the optimization problem is highly nonlinear due to its coupling between simulation and rendering, local optimization techniques like gradient-descent can be trapped into local minima easily if $\{\mathbf{I}_i\}$ and $\{\mathbf{I}_i^{\text{ref}}\}$ are not close enough. While $\nabla\text{Sim}$ has reported promising results when $\{\mathbf{I}_i\}$ and $\{\mathbf{I}_i^{\text{ref}}\}$ are rendered with moderately different $\psi$, we found in our experiments that directly optimizing $\mathcal{L}$ defined on the image space rarely works when the two rendering domains are vastly different (Fig. 1). Therefore, we believe it requires a fundamentally different solution, motivating us to propose RISP in our method.

## 3.2 RISP: RENDERING-INVARIANT STATE-PREDICTION NETWORK

The difficulty of generalizing Eqn. (4) across different rendering domains is partially explained by the fact that the loss $\mathcal{L}$ is defined on the differences in the image space, which is sensitive to changes in rendering configurations. To address this issue, we notice from many differentiable simulation papers that a loss function in the state space is fairly robust to random initialization (Du et al., 2021b; 2020;

Liang et al., 2019), inspiring us to redefine $\mathcal{L}$ in a state-like space. More concretely, we introduce a rendering-invariant state-prediction (RISP) network $\mathcal{N}$ that takes as input an image $\mathbf{I}$ and outputs a state prediction $\hat{\mathbf{s}} = \mathcal{N}(\mathbf{I})$. We then redefine the optimization problem in Eqn. (4) as follows (Fig. 2):

$$\min_{\mathbf{s}_0, \{\mathbf{a}_i\}, \boldsymbol{\phi}, \boldsymbol{\psi}} \quad \mathcal{L}(\mathcal{N}_{\boldsymbol{\theta}}(\{\mathbf{I}_i^{\text{ref}}\}), \mathcal{N}_{\boldsymbol{\theta}}(\{\mathbf{I}_i\})), \tag{6}$$

$$\text{s.t.} \quad \{\mathbf{I}_i\} = \mathcal{R}_{\boldsymbol{\psi}}[\mathcal{M}_{\boldsymbol{\phi}}(\mathbf{s}_0, \{\mathbf{a}_i\})]. \tag{7}$$

Note that the RISP $\mathcal{N}_{\boldsymbol{\theta}}$, parametrized by $\boldsymbol{\theta}$, is pre-trained and fixed in this optimization problem. Essentially, Eqn. (6) maps the two image sequences to the predicted state space, after which the standard gradient-descent optimization follows. A well-trained network $\mathcal{N}$ can be interpreted as an "inverse renderer" $\mathcal{R}^{-1}$ that recovers the rendering-invariant state vector regardless of the choice of rendering parameters $\boldsymbol{\psi}$, giving Eqn. (6) the power to match the information behind image sequences $\{\mathbf{I}_i\}$ and references $\{\mathbf{I}_i^{\text{ref}}\}$ when they are generated with different rendering parameters $\boldsymbol{\psi}$ or even different renderers $\mathcal{R}$. Below, we present two ideas to train the network $\mathcal{N}$:

**The first idea: domain randomization** Our first idea is to massively sample state-rendering pairs $(\mathbf{s}_j, \boldsymbol{\psi}_j)$ and render the corresponding image $\mathbf{I}_j = \mathcal{R}_{\boldsymbol{\psi}_j}(\mathbf{s}_j)$, giving us a training set $\mathcal{D}$ consisting of state-rendering-image tuples: $\mathcal{D} = \{(\mathbf{s}_j, \boldsymbol{\psi}_j, \mathbf{I}_j)\}$. We then train $\mathcal{N}$ using $L1$ loss:

$$\mathcal{L}^{\text{error}}(\boldsymbol{\theta}, \mathcal{D}) = \sum_{(\mathbf{s}_j, \boldsymbol{\psi}_j, \mathbf{I}_j) \in \mathcal{D}} \underbrace{\mathcal{L}(\mathbf{s}_j, \mathcal{N}_{\boldsymbol{\theta}}(\mathbf{I}_j))}_{\mathcal{L}_j^{\text{error}}}. \tag{8}$$

The intuition is straightforward: $\mathcal{N}_{\boldsymbol{\theta}}$ learns to generalize over rendering configurations because it sees images generated with various rendering parameters $\boldsymbol{\psi}$. This is exactly the domain randomization idea that the learning community has been using in cross-domain applications (Tobin et al., 2017), and we borrow this idea to solve our problem across different rendering domains.

**The second idea: rendering gradients** One major bottleneck in domain randomization is its needs for massive training data that spans the whole distribution of rendering parameters $\boldsymbol{\psi}$. Noting that a perfectly rendering-invariant $\mathcal{N}$ must satisfy the following condition:

$$\frac{\partial \mathcal{N}_{\boldsymbol{\theta}}(\mathcal{R}_{\boldsymbol{\psi}}(\mathbf{s}))}{\partial \boldsymbol{\psi}} \equiv \mathbf{0}, \quad \forall \mathbf{s}, \boldsymbol{\psi}, \tag{9}$$

we consider adding a regularizer to the training loss:

$$\mathcal{L}^{\text{train}}(\boldsymbol{\theta}, \mathcal{D}) = \mathcal{L}^{\text{error}} + \gamma \underbrace{\sum_{(\mathbf{s}_j, \boldsymbol{\psi}_j, \mathbf{I}_j) \in \mathcal{D}} \|\frac{\partial \mathcal{N}_{\boldsymbol{\theta}}(\mathcal{R}_{\boldsymbol{\psi}_j}(\mathbf{s}_j))}{\partial \boldsymbol{\psi}_j}\|_{\text{F}}}_{\mathcal{L}^{\text{reg}}}, \tag{10}$$

where $\| \cdot \|_{\text{F}}$ indicates the Frobenius norm and $\gamma$ is a weight in front of the regularizer $\mathcal{L}^{\text{reg}}$. The intuition is that by suppressing this Jacobian to zero, we encourage the network $\mathcal{N}$ to flatten out its landscape along the dimension of rendering parameters $\boldsymbol{\psi}$, and rendering-invariance follows. To implement this loss, we apply the chain rule:

$$\frac{\partial \mathcal{N}_{\boldsymbol{\theta}}(\mathcal{R}_{\boldsymbol{\psi}_j}(\mathbf{s}_j))}{\partial \boldsymbol{\psi}_j} = \frac{\partial \mathcal{N}_{\boldsymbol{\theta}}(\mathbf{I}_j)}{\partial \boldsymbol{\psi}_j} = \frac{\partial \mathcal{N}_{\boldsymbol{\theta}}(\mathbf{I}_j)}{\partial \mathbf{I}_j} \frac{\partial \mathbf{I}_j}{\partial \boldsymbol{\psi}_j}, \tag{11}$$

where the first term $\frac{\partial \mathcal{N}_{\boldsymbol{\theta}}(\mathbf{I}_j)}{\partial \mathbf{I}_j}$ is available in any modern deep learning frameworks and the second term $\frac{\partial \mathbf{I}_j}{\partial \boldsymbol{\psi}_j}$ can be obtained from the state-of-the-art differentiable renderer (Nimier-David et al., 2019). We can now see more clearly the intuition behind RISP: it requires the network's sensitivity about input images to be orthogonal to the direction that rendering parameters can influence the image, leading to a rendering-invariant prediction.

We stress that the design of this new loss in Eqn. (10) is non-trivial. In fact, both $\mathcal{L}^{\text{error}}$ and $\mathcal{L}^{\text{reg}}$ have their unique purposes and must be combined: $\mathcal{L}^{\text{error}}$ encourages $\mathcal{N}$ to fit its output to individually different states, and $\mathcal{L}^{\text{reg}}$ attempts to smooth out its output along the $\boldsymbol{\psi}$ dimension. Specifically, $\mathcal{L}^{\text{reg}}$ cannot be optimized as a standalone loss because it leads to a trivial solution of $\mathcal{N}$ always predicting constant states. Putting $\mathcal{L}^{\text{error}}$ and $\mathcal{L}^{\text{reg}}$ together forces them to strike a balance between predicting accurate states and ignoring noises from rendering conditions, leading to a network $\mathcal{N}$ that truly learns the "inverse renderer" $\mathcal{R}^{-1}$.

It remains to show how to compute the gradient of the regularizer $\mathcal{L}^{\text{reg}}$ with respect to the network parameters $\boldsymbol{\theta}$, which is required by gradient-based optimizers to minimize this new loss. As the loss definition now includes first-order derivatives, computing its gradients involves second-order partial derivatives, which can be tedious and time-consuming if implemented carelessly with multiple loops. Our last contribution is to provide an efficient method for computing the gradients of $\mathcal{L}^{\text{reg}}$ with respect to $\boldsymbol{\theta}$, which we formally state below and can be fully implemented with existing learning and rendering tools (PyTorch and `mitsuba`-2 in our experiments):

**Theorem 1** *Assume forward mode differentiation is available in the renderer $\mathcal{R}$ and reverse mode differentiation is available in the network $\mathcal{N}$, we can compute a stochastic gradient $\frac{\partial \mathcal{L}^{\text{reg}}}{\partial \boldsymbol{\theta}}$ with a small batch size in $\mathcal{O}(|\mathbf{s}||\boldsymbol{\theta}|)$ time using pre-computed data occupying $\mathcal{O}(\sum_j |\boldsymbol{\psi}_j||\mathbf{I}_j|)$ space.*

In particular, we stress that computing the gradients of $\mathcal{L}^{\text{reg}}$ does not require second-order gradients in the renderer $\mathcal{R}$, which exceeds the capability of almost all existing differentiable renderers we are aware of. We leave the proof of this theorem in our supplemental material.

**Further speedup** Theorem 1 states that it takes time linear to the network size and state dimension to compute the gradients of $\mathcal{L}^{\text{reg}}$. The $\mathcal{O}(|\mathbf{s}||\boldsymbol{\theta}|)$ time cost is affordable for very small rigid-body systems (e.g., $|\mathbf{s}| < 10$) but not scalable for larger systems. Therefore, we use a slightly different regularizer in our implementation:

$$\mathcal{L}^{\text{train}}(\boldsymbol{\theta}, \mathcal{D}) = \mathcal{L}^{\text{error}} + \gamma \sum_{(\mathbf{s}_j, \boldsymbol{\psi}_j, \mathbf{I}_j) \in \mathcal{D}} \|\frac{\partial \mathcal{L}_j^{\text{error}}}{\partial \boldsymbol{\psi}_j}\|. \tag{12}$$

In other words, we instead encourage the state prediction error to be rendering-invariant. It can be seen from the proof in Theorem 1 that this new regularizer requires only $\mathcal{O}(\boldsymbol{\theta})$ time to compute its gradients, and we have found empirically that this new regularizer leads to comparable performance to Eqn. (10) but is much faster. We leave a theoretical analysis between the differences of the two regularizers to future work.

## 4 EXPERIMENTS

In this section, we conduct various experiments to study the following questions:

- Q1: Is pixelwise loss on videos across rendering domains sufficient for parameter prediction?
- Q2: If pixelwise loss is not good enough, are there other competitive alternatives to the state-prediction loss in our approach?
- Q3: How does our approach compare with directly optimizing state discrepancies?
- Q4: Is the loss on rendering gradients necessary?

### 4.1 EXPERIMENTAL SETUP

**Environments** We implement four environments: a rigid-body environment without contact (**quadrotor**), a rigid-body environment with contact (**cube**), an articulated body (**hand**), and a deformable-body environment (**rod**) (Fig. 1). Each environment is equipped with a differentiable simulator (Xu et al., 2021; Du et al., 2021b) and a differentiable renderer (Li et al., 2018). We deliberately generated the training set in Sec. 3 using a different renderer (Nimier-David et al., 2019).

**Tasks** We consider four types of tasks defined on the physical systems in all environments: state estimation, system identification, imitation learning, and visuomotor control. The state estimation task require a model to predict the state of the physical system from a given image and serves as a prerequisite for the other downstream tasks. The system identification and imitation learning tasks aim to recover the system parameters and control signals of a physical system from the video, respectively. Finally, in the visuomotor control task, we replace the video with a target image showing the desired state of the physical system and aim to discover the proper control signals that steer the system to the desired state. In all tasks, we use a photorealistic renderer (Pharr et al., 2016) to generate the target video or image and intentionally diversify the rendering configurations between training and target images (Fig. 1).

**Baselines** We consider two strong baselines: the **pixelwise-loss** baseline is used by $\nabla$Sim (Jataval-labhula et al., 2021), which is the state-of-the-art method for identifying system parameters directly

from video inputs. We implement $\nabla \text{Sim}$ by removing RISP from our method and backpropagating the pixelwise loss on images through differentiable rendering and simulation. We run this baseline to analyze the limit of pixelwise loss in downstream tasks. The second baseline is **preceptual-loss** (Johnson et al., 2016), which replaces the pixelwise loss in $\nabla \text{Sim}$ with loss functions based on high-level features extracted by a pre-trained CNN. By comparing this baseline with our method, we can justify why we choose to let RISP predict states instead of other percepual features.

We also include two weak baselines used by $\nabla \text{Sim}$: the **average** baseline is a deterministic method that always returns the average quantity observed from the training set, and the **random** baseline returns a guess randomly drawn from the data distribution used to generate the training set. We use these two weak baselines to avoid designing environments and tasks that are too trivial to solve.

**Our methods** We consider two versions of our methods in Sec. 3: **ours-no-grad** implements the domain randomization idea without using the proposed regularizers, and **ours** is the full approach that includes the regularizer using rendering gradients. By comparing between them, we aim to better understand the value of the rendering gradients in our proposed method.

**Oracle** Throughout our experiments, we also consider an oracle method that directly minimizes the state differences obtained from simulation outputs without further rendering. In particular, this oracle sees the ground-truth states for each image in the target video or image, which is inaccessible to all baselines and our methods. We consider this approach to be an oracle because it is a subset of our approach that involve differentiable physics only, but it needs a perfect state-prediction network. This oracle can give us an upper bound for the performance of our method.

| | quadrotor | cube | hand | rod |
|---|---|---|---|---|
| average | $0.5994 \pm 0.0000$ | $0.5920 \pm 0.0000$ | $0.2605 \pm 0.0000$ | $0.9792 \pm 0.0000$ |
| random | $0.9661 \pm 0.7548$ | $0.9655 \pm 0.8119$ | $0.8323 \pm 0.5705$ | $1.2730 \pm 0.7197$ |
| ours-no-grad | $0.3114 \pm 0.3191$ | $0.2805 \pm 0.3199$ | $0.1155 \pm 0.0505$ | $0.0201 \pm 0.0087$ |
| ours | $\mathbf{0.1505 \pm 0.1163}$ | $\mathbf{0.1642 \pm 0.1887}$ | $\mathbf{0.0974 \pm 0.0255}$ | $\mathbf{0.0194 \pm 0.0048}$ |

Table 1: State estimation results (Sec. 4.2). Each entry in the table reports the mean and standard deviation of the state estimation error computed from 800 images under 4 rendering configurations.

## 4.2 STATE ESTIMATION RESULTS

In this task, we generate in each environment 800 images with randomly sampled states under 4 rendering configurations. We then predict the states of the physical system from these images and report the mean and standard deviation of the state prediction errors in Table 1. Note that we exclude the **perceptual-loss** and **pixelwise-loss** baselines as they do not require a state prediction step.

Overall, we find that the state estimation results from our methods are significantly better than all baselines across the board. The two weak baselines perform poorly, confirming that this state-estimation task cannot be solved trivially. We highlight that our method with the rendering-gradient loss predicts the most stable and accurate state of the physical system across the board, which strongly demonstrates that RISP learns to make predictions independent of various rendering configurations.

## 4.3 SYSTEM IDENTIFICATION RESULTS

Our system identification task aims to predict the system parameters of a physical system, e.g., mass, density, stiffness, or elasticity by watching a reference video with known action sequences. For each environment, we manually design a sequence of actions and render a reference video of its dynamic motion. Next, we randomly pick an initial guess of the system parameters and run gradient-based optimization using all baselines, our methods, and the oracle. We repeat this experiment 4 times with randomly generated rendering conditions and initial guesses and report the mean and standard deviation of each system parameter in Table 2. The near-perfect performance of the oracle suggests that these system identification tasks are feasible to solve as long as a reliable state estimation is available. Both of our methods outperform almost all baselines by a large margin, sometimes even by orders of magnitude. This is as expected, since the previous task already suggests that our methods can predict states from a target video much more accurate than baselines, which is a crucial prerequisite for solving system identification. The only exception is in the **cube** environment, where

the pixelwise loss performs surprisingly well. We hypothesize it may be due to its relatively simple geometry and high contrast from the background (Fig. 1).

| | **quadrotor** mass | **cube** stiffness | **hand** joint stiffness | **rod** Young's modulus |
|---|---|---|---|---|
| random | 9.22e-2±3.83e-2 | 2.31e-1±9.57e-2 | 5.70e-1±1.62e-1 | 1.30e6±1.35e6 |
| pixelwise-loss | 7.22e-2±5.26e-2 | **2.24e-3±1.74e-3** | 1.04e-1±9.62e-2 | 8.50e5±1.42e6 |
| perceptual-loss | 6.45e-2±5.23e-2 | 1.16e-1±5.83e-2 | 1.10e-1±1.18e-1 | 8.32e5±1.43e6 |
| ours-no-grad | 6.07e-2±4.34e-2 | 1.16e-1±6.20e-2 | 4.85e-2±**2.16e-2** | 8.78e4±1.52e5 |
| ours | **1.18e-2±1.93e-2** | 6.76e-3±7.23e-3 | **3.96e-2**±2.73e-2 | **9.31e1±4.21e1** |
| oracle | 2.36e-5±2.41e-5 | 1.15e-3±8.60e-4 | 3.92e-3±4.40e-4 | 4.36e0±3.57e0 |

Table 2: System identification results (Sec. 4.3). Each entry reports the mean and standard deviation of the parameter estimation error computed from 4 random initial guesses and rendering conditions.

Figure 3: Imitation learning in the **hand** environment. Given a reference video (bottom row, shown as five intermediate frames), the goal is to reconstruct a sequence of actions that resembles its motion. We show the motions generated using a randomly chosen initial guess of the actions (top row) and optimized actions using our method with rendering gradients (**ours**, middle row).

## 4.4 IMITATION LEARNING RESULTS

Our imitation learning tasks consider the problem of emulating the dynamic motion of a reference video. The experiment setup is similar to the system identification task except that we swap the known and unknown variables in the environment: the system parameters are now known, and the goal is to infer the unknown sequence of actions from the reference video. Note that the **cube** environment is excluded because it has no control signals. As before, we repeat the experiment in all environments 4 times with randomly generated rendering configurations and initial guesses of the actions. We report the results in Table 3 and find that our method with rendering gradients (**ours** in the table) achieves much lower errors, indicating that we resemble the motions in the video much more accurately. The errors from **pixelwise-loss** have smaller variations across rendering domains but are larger than ours, indicating that it struggles to solve this task under all four rendering configurations. In addition, the oracle finds a sequence of actions leading to more similar motions than our method, but it requires full and accurate knowledge of the state information which is rarely accessible from a video. We visualize our results in the **hand** environment in Fig. 3.

## 4.5 VISUOMOTOR CONTROL RESULTS

Lastly, we consider visuomotor control defined as follows: given a target image displaying the desired state of the physical system, we optimize a sequence of actions that steer the physical system to the target state from a randomly generated initial state. We set the target states by selecting them from the ground truth in the imitation learning tasks. We report in Table 4 the state error computed from experiments repeated with various rendering configurations and initial guesses. The state error is defined as L1 distances between the desired state and the final state from the simulator. The smaller state error and standard deviation from our methods in Table 4 shows the advantages of our approach over other baselines. As before, the performance from all methods is capped by the oracle, which requires much more knowledge about the ground-truth state.

|  | quadrotor | hand | rod |
|---|---|---|---|
| average | $28.40 \pm 0.00$ | $7.62 \pm 0.00$ | $30.20 \pm 0.00$ |
| random | $1120 \pm 113$ | $10.27 \pm 0.91$ | $29.89 \pm 0.61$ |
| pixelwise-loss | $12.65 \pm \mathbf{0.13}$ | $6.71 \pm \mathbf{0.07}$ | $29.57 \pm 0.85$ |
| perceptual-loss | N/A | $5.10 \pm 1.80$ | $14.61 \pm 5.13$ |
| ours-no-grad | $25.07 \pm 5.76$ | $7.12 \pm 0.71$ | $\mathbf{0.83} \pm 0.35$ |
| ours | $\mathbf{2.63} \pm 1.86$ | $\mathbf{1.52} \pm 0.18$ | $1.05 \pm \mathbf{0.27}$ |
| oracle | $0.79 \pm 0.44$ | $0.02 \pm 0.02$ | $0.28 \pm 0.16$ |

Table 3: Imitation learning results. Each entry reports the mean and standard deviation of the state discrepancy computed from 4 randomly generated initial guesses and rendering conditions. N/A indicates failure of convergence after optimization.

|  | quadrotor | hand | rod |
|---|---|---|---|
| average | $1.38 \pm 0.00$ | $0.23 \pm 0.00$ | $0.89 \pm 0.00$ |
| random | $63.93 \pm 9.44$ | $0.32 \pm 0.06$ | $0.87 \pm 0.06$ |
| pixelwise-loss | $3.02 \pm 1.35$ | $0.25 \pm 0.05$ | $0.05 \pm 0.01$ |
| perceptual-loss | $1.59 \pm 0.26$ | $0.28 \pm 0.05$ | $0.11 \pm 0.06$ |
| ours-no-grad | $1.30 \pm \mathbf{0.15}$ | $0.23 \pm 0.06$ | $\mathbf{0.04} \pm \mathbf{0.0002}$ |
| ours | $\mathbf{0.54} \pm 0.25$ | $\mathbf{0.11} \pm \mathbf{0.02}$ | $\mathbf{0.04} \pm 0.0006$ |
| oracle | $0.15 \pm 0.09$ | $0.002 \pm 0.00$ | $0.01 \pm 0.02$ |

Table 4: Visuomotor control results. Each entry reports the mean and standard deviation of the state discrepancy computed from 4 randomly generated initial guesses and rendering conditions.

## 4.6 ABLATION STUDY

We end our experiments by a comparison between **ours** and ours-no-grad that can show the data efficiency from adding rendering gradients. We reuse the state estimation data sets (Table 1) on **quadrotor** but vary the number of rendering configurations between 1 and 10. We then train both of our methods for 100 epochs and report their performances on a test set consisting of 200 randomly states, each of which is augmented by 10 unseen rendering configurations. The right inset summarizes the performances of **ours** (solid lines) and **ours-no-grad** (dashed lines) under varying number of rendering configurations, with the green, orange, and red colors corresponding to results trained on 1, 10, and randomly sampled rendering configurations. It is obvious to see that all solid lines reach a lower state estimation loss than their dashed counterparts, indicating that our rendering gradient digs more information out of the same amount

of rendering configurations. It is worth noting that with only 10 rendering configurations (orange solid line), our method with rendering gradients achieves a lower loss than the one without but using randomly sampled rendering configurations (red dashed line), which reflects the better data efficiency.

By comparing **ours** and **ours-no-grad** from Table 1, 2, 3, and 4, we can see that having the rendering gradients in our approach is crucial to its substantially better performance. We stress that having a rendering-invariant state estimation is the core source of generalizability in our approach and the key to success in many downstream tasks.

## 5 CONCLUSIONS

In this work, we have proposed a principle framework that integrates rendering-invariant state-prediction into a differentiable simulation and rendering engine for cross-domain parameter estimation from videos. Extensive experiments on multiple evaluation tasks involving both rigid-body and deformable-body physics have shown that our method indeed could perform more robust than pixelwise loss used before on unseen rendering configurations. The additional ablated study further confirms the effectiveness of using the gradients from differentiable rendering for learning a more data-efficient and generalizable state predictor. In the future, we plan to extend our framework to real-world scenarios.

# REFERENCES

OpenAI: Marcin Andrychowicz, Bowen Baker, Maciek Chociej, Rafal Józefowicz, Bob McGrew, Jakub Pachocki, Arthur Petron, Matthias Plappert, Glenn Powell, Alex Ray, Jonas Schneider, Szymon Sidor, Josh Tobin, Peter Welinder, Lilian Weng, and Wojciech Zaremba. Learning dexterous in-hand manipulation. *The International Journal of Robotics Research*, 39(1):3–20, 2020. doi: 10.1177/0278364919887447. URL https://doi.org/10.1177/0278364919887447. 3

Filipe de Avila Belbute-Peres, Kevin Smith, Kelsey Allen, Josh Tenenbaum, and J. Zico Kolter. End-to-end differentiable physics for learning and control. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL https://proceedings.neurips.cc/paper/2018/file/842424a1d0595b76ec4fa03c46e8d755-Paper.pdf. 3

Jonas Degrave, Michiel Hermans, Joni Dambre, and Francis wyffels. A differentiable physics engine for deep learning in robotics. *Frontiers in Neurorobotics*, 13:6, 2019. ISSN 1662-5218. doi: 10.3389/fnbot.2019.00006. URL https://www.frontiersin.org/article/10.3389/fnbot.2019.00006. 3

Tao Du, Kui Wu, Andrew Spielberg, Wojciech Matusik, Bo Zhu, and Eftychios Sifakis. Functional optimization of fluidic devices with differentiable stokes flow. *ACM Trans. Graph.*, 39(6), November 2020. ISSN 0730-0301. doi: 10.1145/3414685.3417795. URL https://doi.org/10.1145/3414685.3417795. 3, 4

Tao Du, Josie Hughes, Sebastien Wah, Wojciech Matusik, and Daniela Rus. Underwater soft robot modeling and control with differentiable simulation. *IEEE Robotics and Automation Letters*, 6(3): 4994–5001, 2021a. doi: 10.1109/LRA.2021.3070305. 3

Tao Du, Kui Wu, Pingchuan Ma, Sebastien Wah, Andrew Spielberg, Daniela Rus, and Wojciech Matusik. DiffPD: Differentiable projective dynamics with contact. *ACM Trans. Graph. (accepted with minor revisions)*, 2021b. 3, 4, 6, 14

Moritz Geilinger, David Hahn, Jonas Zehnder, Moritz Bächer, Bernhard Thomaszewski, and Stelian Coros. ADD: Analytically differentiable dynamics for multi-body systems with frictional contact. *ACM Trans. Graph.*, 39(6), November 2020. ISSN 0730-0301. doi: 10.1145/3414685.3417766. URL https://doi.org/10.1145/3414685.3417766. 3

David Hahn, Pol Banzet, James M. Bern, and Stelian Coros. Real2Sim: Visco-elastic parameter estimation from dynamic motion. *ACM Trans. Graph.*, 38(6), November 2019. ISSN 0730-0301. doi: 10.1145/3355089.3356548. URL https://doi.org/10.1145/3355089.3356548. 3

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016. 13

Yuanming Hu, Jiancheng Liu, Andrew Spielberg, Joshua B. Tenenbaum, William T. Freeman, Jiajun Wu, Daniela Rus, and Wojciech Matusik. ChainQueen: A real-time differentiable physical simulator for soft robotics. In *2019 International Conference on Robotics and Automation (ICRA)*, pp. 6265–6271, 2019. doi: 10.1109/ICRA.2019.8794333. 3

Yuanming Hu, Luke Anderson, Tzu-Mao Li, Qi Sun, Nathan Carr, Jonathan Ragan-Kelley, and Frédo Durand. DiffTaichi: Differentiable programming for physical simulation. In *International Conference on Learning Representations*, 2020. 3

Stephen James, Paul Wohlhart, Mrinal Kalakrishnan, Dmitry Kalashnikov, Alex Irpan, Julian Ibarz, Sergey Levine, Raia Hadsell, and Konstantinos Bousmalis. Sim-to-real via sim-to-sim: Data-efficient robotic grasping via randomized-to-canonical adaptation networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 12627–12637, 2019. 13

Wojciech Jarosz, Volker Schönefeld, Leif Kobbelt, and Henrik Wann Jensen. Theory, analysis and applications of 2d global illumination. *ACM Trans. Graph.*, 31(5), September 2012. ISSN 0730-0301. doi: 10.1145/2231816.2231823. URL https://doi.org/10.1145/2231816.2231823. 3

Krishna Murthy Jatavallabhula, Miles Macklin, Florian Golemo, Vikram Voleti, Linda Petrini, Martin Weiss, Breandan Considine, Jerome Parent-Levesque, Kevin Xie, Kenny Erleben, Liam Paull, Florian Shkurti, Derek Nowrouzezahrai, and Sanja Fidler. gradsim: Differentiable simulation for system identification and visuomotor control. *International Conference on Learning Representations (ICLR)*, 2021. URL https://openreview.net/forum?id=c_E8kFWfhp0. 1, 2, 4, 6

Justin Johnson, Alexandre Alahi, and Li Fei-Fei. Perceptual losses for real-time style transfer and super-resolution. In *European conference on computer vision*, pp. 694–711. Springer, 2016. 7

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014. 13

Tzu-Mao Li, Jaakko Lehtinen, Ravi Ramamoorthi, Wenzel Jakob, and Frédo Durand. Anisotropic gaussian mutations for metropolis light transport through hessian-hamiltonian dynamics. *ACM Trans. Graph.*, 34(6), October 2015. ISSN 0730-0301. doi: 10.1145/2816795.2818084. URL https://doi.org/10.1145/2816795.2818084. 3

Tzu-Mao Li, Miika Aittala, Frédo Durand, and Jaakko Lehtinen. Differentiable monte carlo ray tracing through edge sampling. *ACM Trans. Graph. (Proc. SIGGRAPH Asia)*, 37(6):222:1–222:11, 2018. 3, 6

Junbang Liang, Ming Lin, and Vladlen Koltun. Differentiable cloth simulation for inverse problems. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/28f0b864598a1291557bed248a998d4e-Paper.pdf. 3, 5

Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. *arXiv preprint arXiv:1608.03983*, 2016. 13

Antoine McNamara, Adrien Treuille, Zoran Popović, and Jos Stam. Fluid control using the adjoint method. *ACM Trans. Graph.*, 23(3):449–456, August 2004. ISSN 0730-0301. doi: 10.1145/1015706.1015744. URL https://doi.org/10.1145/1015706.1015744. 3

Merlin Nimier-David, Delio Vicini, Tizian Zeltner, and Wenzel Jakob. Mitsuba 2: A retargetable forward and inverse renderer. *Transactions on Graphics (Proceedings of SIGGRAPH Asia)*, 38(6), December 2019. doi: 10.1145/3355089.3356498. 3, 5, 6

OptiTrack. Optitrack motion capture systems. https://optitrack.com/. Accessed: 2021-10-05. 1

Xue Bin Peng, Marcin Andrychowicz, Wojciech Zaremba, and Pieter Abbeel. Sim-to-real transfer of robotic control with dynamics randomization. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 3803–3810, 2018. doi: 10.1109/ICRA.2018.8460528. 3

Matt Pharr, Wenzel Jakob, and Greg Humphreys. *Physically based rendering: From theory to implementation*. Morgan Kaufmann, 2016. 6

Yi-Ling Qiao, Junbang Liang, Vladlen Koltun, and Ming Lin. Scalable differentiable physics for learning and control. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 7847–7856. PMLR, 13–18 Jul 2020. URL https://proceedings.mlr.press/v119/qiao20a.html. 3

Qualisys. Qualisys motion capture systems. https://www.qualisys.com/. Accessed: 2021-10-05. 1

Prajit Ramachandran, Barret Zoph, and Quoc V Le. Searching for activation functions. *arXiv preprint arXiv:1710.05941*, 2017. 13

Ravi Ramamoorthi, Dhruv Mahajan, and Peter Belhumeur. A first-order analysis of lighting, shading, and shadows. *ACM Transactions on Graphics (TOG)*, 26(1):2–es, 2007. 3

Fereshteh Sadeghi and Sergey Levine. Cad2rl: Real single-image flight without a single real image. In *Proceedings of Robotics: Science and Systems*, Cambridge, Massachusetts, July 2017. doi: 10.15607/RSS.2017.XIII.034. 3

Jie Tan, Tingnan Zhang, Erwin Coumans, Atil Iscen, Yunfei Bai, Danijar Hafner, Steven Bohez, and Vincent Vanhoucke. Sim-to-real: Learning agile locomotion for quadruped robots. In *Proceedings of Robotics: Science and Systems*, Pittsburgh, Pennsylvania, June 2018. doi: 10.15607/RSS.2018.XIV.010. 3

Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 23–30, 2017. doi: 10.1109/IROS.2017.8202133. 3, 5

Dmitry Ulyanov, Andrea Vedaldi, and Victor Lempitsky. Instance normalization: The missing ingredient for fast stylization. *arXiv preprint arXiv:1607.08022*, 2016. 13

Vicon. VICON: award-winning motion capture systems. https://www.vicon.com/. Accessed: 2021-10-05. 1

Jie Xu, Tao Chen, Lara Zlokapa, Michael Foshey, Wojciech Matusik, Shinjiro Sueda, and Pulkit Agrawal. An End-to-End Differentiable Framework for Contact-Aware Robot Design. In *Proceedings of Robotics: Science and Systems*, Virtual, July 2021. doi: 10.15607/RSS.2021.XVII.008. 2, 3, 6, 14

Jun-Yan Zhu, Taesung Park, Phillip Isola, and Alexei A Efros. Unpaired image-to-image translation using cycle-consistent adversarial networks. In *Proceedings of the IEEE international conference on computer vision*, pp. 2223–2232, 2017. 1

## A    PROOF OF THE THEOREM

For brevity, we remove the summation in $\mathcal{L}^{\text{reg}}$ and drop the index $j$ to focus on deriving the gradients of the Frobenius term with respect to the network parameters $\boldsymbol{\theta}$. Now let $\mathbf{G}$ be the Jacobian matrix inside the Frobenius norm, and let $i$ and $j$ be its row and column indices. We now derive the gradient of $\mathcal{L}^{\text{reg}}$ with respect to the $k$-th parameter in $\boldsymbol{\theta}$ as follows:

$$\frac{\partial \mathcal{L}^{\text{reg}}}{\partial \boldsymbol{\theta}_k} = \sum_{ij} 2\mathbf{G}_{ij} \frac{\partial \mathbf{G}_{ij}}{\partial \boldsymbol{\theta}_k} \tag{13}$$

$$= \sum_{ij} 2\mathbf{G}_{ij} \frac{\partial}{\partial \boldsymbol{\theta}_k} [\frac{\partial \mathcal{N}_{\boldsymbol{\theta}}(\mathbf{I})_i}{\partial \mathbf{I}} : \frac{\partial \mathbf{I}}{\partial \boldsymbol{\psi}_j}], \tag{14}$$

$$= \sum_{ij} 2\mathbf{G}_{ij} [\frac{\partial^2 \mathcal{N}_{\boldsymbol{\theta}}(\mathbf{I})_i}{\partial \mathbf{I} \partial \boldsymbol{\theta}_k} : \frac{\partial \mathbf{I}}{\partial \boldsymbol{\psi}_j}] \tag{15}$$

$$= \sum_{i} \frac{\partial^2 \mathcal{N}_{\boldsymbol{\theta}}(\mathbf{I})_i}{\partial \mathbf{I} \partial \boldsymbol{\theta}_k} : (\sum_{j} 2\mathbf{G}_{ij} \frac{\partial \mathbf{I}}{\partial \boldsymbol{\psi}_j}) \tag{16}$$

$$= \sum_{i} \frac{\partial^2 \mathcal{N}_{\boldsymbol{\theta}}(\mathbf{I})_i}{\partial \mathbf{I} \partial \boldsymbol{\theta}_k} : 2\sum_{j} (\frac{\partial \mathcal{N}_{\boldsymbol{\theta}}(\mathbf{I})_i}{\partial \mathbf{I}} : \frac{\partial \mathbf{I}}{\partial \boldsymbol{\psi}_j}) \frac{\partial \mathbf{I}}{\partial \boldsymbol{\psi}_j}. \tag{17}$$

The derivation suggests that we can loop over the state dimension (indexed by $i$) and run backpropagation to obtain $\frac{\partial \mathcal{L}^{\text{reg}}}{\partial \boldsymbol{\theta}}$, assuming that all $\frac{\partial \mathbf{I}}{\partial \boldsymbol{\psi}_j}$ are available. In fact, $\frac{\partial \mathbf{I}}{\partial \boldsymbol{\psi}_j}$ depends on the training data only and remains constant throughout the whole optimization process, so we can pre-compute them in the training set, occupying an extra space of $\mathcal{O}(\sum |\boldsymbol{\psi}||\mathbf{I}|)$. Typically, $|\boldsymbol{\psi}_j|$ is a small number (less than 10 in most of our experiments), so it is affordable to store it with the images generated in the data set. This is also why we prefer a differentiable renderer that offers forward mode differentiation.

Assuming all $\frac{\partial \mathbf{I}}{\partial \boldsymbol{\psi}_j}$ are ready to use, we can implement Eqn. (17) by two backpropagations for each state dimension $i$. First, backpropagating through $\mathcal{N}$ to obtain $\frac{\partial \mathcal{N}_{\boldsymbol{\theta}}(\mathbf{I})_i}{\partial \mathbf{I}}$. Next, we use $\frac{\partial \mathbf{I}}{\partial \boldsymbol{\psi}_j}$ to assemble the adjoint vector (the second summation in Eqn. (17)). Finally, we use the adjoint vector to backpropagate again through the second-order partial derivatives $\frac{\partial^2 \mathcal{N}_{\boldsymbol{\theta}}(\mathbf{I})_i}{\partial \mathbf{I} \partial \boldsymbol{\theta}}$. Note that there is no need for looping over $k$ in the second backpropagation. The total time cost is therefore $\mathcal{O}(|\mathbf{s}||\boldsymbol{\theta}|)$.

## B    IMPLEMENTATION DETAILS

### B.1    RENDERING-INVARIANT STATE PREDICTION NETWORK

**Network setting**    We build the network upon a modified version of ResNet-18 (9). All layers are followed by instance normalization (33) without affine parameters, following James et al. (12). Since ReLU degenerates second derivatives to constant values, we replace it with *Swish* non-linearities (28). We change the last layer of ResNet-18 backbone to a linear projection layer with the same number of output with the state dimension.

**Training**    We use *Adam* optimizer (16) with a learning rate of 1e-2 and a weight decay of 1e-6 for training. The learning rate has a cosine decay scheduler (20). We train the network for 100 epochs. We set the batch size to 16 by default. To avoid model collapse in the early stage of training, we linearly increase the magnitude coefficient of the rendering gradients from 0 to a environment-specific value: we set it to 1 for *quadrotor*, 20 for *cube*, 100 for *hand*, and 30 for *rod*.

### B.2    EXPERIMENTS

We share the same experiment settings across imitation learning, and visuomotor control experiments experiments. We use RMSProp optimizer with a learning rate of 3e-3 and a momentum of 0.5. We optimize the system parameters or the action parameters by 100 iterations.

### B.3 ENVIRONMENTS

#### B.3.1 QUADCOPTOR

**State space**  We define the physical system of *quadcoptor* as a rigid body system without contact. We explicitly mark a task as "failed" when the center of the quadcoptor has an Euclidean distance to the origin $(0, 0, 0)$ of over 1000 at anytime. We define the state of the quadcoptor as its world position $(x, y, z)$ and rotation angles $(\text{yaw}, \text{pitch}, \text{roll})$. To alleviate the negative impact from the discontinuity of rotation angles, we design the output of the network as:

$$(x, y, z, \sin(\text{yaw}), \sin(\text{pitch}), \sin(\text{roll}), \cos(\text{yaw}), \cos(\text{pitch}), \cos(\text{roll})), \tag{18}$$

and later restore the rotation angles by $\text{atan2}$.

**Action space**  The control signals are 4-d representing the torques applied on 4 propellers. The magnitude of control signals is clamped to $[-500, 500]$.

**Parameter space**  In system identification experiment, we uniformly sample the mass of the quadcoptor within $[2.8, 3.2)$. The ground-truth value of the mass is 3.

#### B.3.2 CUBE

**State space**  We define the physical system of *cube* as a rigid body system with contact. Similar to *quadcoptor* environment, we design the output of the network as a 9-d vector following 18.

**Parameter space**  In *cube* environment, we adopt a soft contact model paramterized by the spring stiffness $k_n$. In system identification experiment, we train $\lambda_k = \log_{10} k_n$ for better numerical stability and performance. We uniformly sample $\lambda_k$ within $[5.5, 6.5)$. The ground-truth value of $\lambda_k$ is 6.

#### B.3.3 HAND

**State space**  We define the physical system of *hand* as an articulated body system powered by (35). We fix the palm on the world frame and model the articulations as revolve joints. There are 13 joints in this environment, and each joints is clamped within $[-\frac{\pi}{4}, \frac{\pi}{4}]$. We define the state space of *hand* as a 13-d vector representing the angles of each joint $\{\theta_{1\ldots13}\}$.

**Action space**  The hand is controlled by applying torque on each joint. We paramterize the control signal of each finger at time $t$ by:

$$u_t = m_j \sin\left(2\pi \min\left(1.0, \max\left(0.0, \frac{1}{T}(t - \delta_j)\right)\right)\right),$$

where $0 \leq m_j \leq 1$ and $0 \leq \delta_j \leq 40$ denote the action magnitude and action bias of finger $j$, and $T = 40$ is the period.

**Parameter space**  For each finger, we let the joint stiffness of all joints on the finger available for training, making the parameter space a 5-d space. We uniformly sample the joint stiffness within $[0.0, 1.0)$. The ground-truth values of the joint stiffness are all 1.0.

#### B.3.4 ROD

**State space**  We define the physical system of *rod* as a soft-body dynamics system powered by (6). We fix both ends of the rod and apply a gravity force on it. We define a 10-d state space by evenly selecting 10 sensors along the central spine and track their positions along the vertical direction.

**Action space**  We apply an external force on the center of the rob vertically as the action signal. We clamp the action within $[-500, 500)$.

**Parameter space.**  We parameter the *rod* environment by Young's modulus $E$. We train $\lambda_E = \log_{10} E$ for better numerical stability and performance. We uniformly sample $\lambda_E$ within $[4, 7)$ where the ground-truth value of $\lambda_E$ is 5.