TextTN: Probabilistic Encoding of Language on Tensor Network

Abstract

As a novel model that bridges machine learning and quantum theory, tensor network (TN) has recently gained increasing attention and successful applications for processing natural images. However, for natural languages, it is unclear how to design a probabilistic encoding architecture to efficiently and accurately learn and classify texts based on TN. This paper proposes a general two-step scheme of text classification based on Tensor Network, which is named as TextTN. TextTN first encodes the word vectors in a probabilistic space by a generative TN (word-GTN), and then classifies a text sentence using a discriminative TN (sentence-DTN). Moreover, in sentence-DTN, its hyper-parameter (i.e., bond-dimension) can be analyzed and selected by the theoretical property of TextTN's expressive power. In experiments, our TextTN also obtains the state-of-the-art result on SST-5 sentiment classification task.

1 Introduction

Machine learning incorporating with the quantum mechanics forms a novel interdisciplinary field known as quantum machine learning (Huggins et al., 2019; Ran et al., 2020). Tensor network (TN) as a novel model has become prominent in the field of quantum machine learning (Biamonte et al., 2017). On the one hand, tensor network can be used as mathematical tool to enhance the theoretical understanding of existing neural network methods (Levine et al., 2018; 2019). On the other hand, based on tensor network, new machine learning algorithms have been proposed, e.g., discriminative TN (DTN) (Stoudenmire & Schwab, 2016) for supervised tasks and generative TN (GTN) (Han et al., 2018) for unsupervised scenarios (Han et al., 2018). Based on the natural analogy between the quantum concepts (e.g., quantum many-body system (Levine et al., 2018)) and the image representation, many studies and applications are conducted for processing and learning natural pictures (Stoudenmire & Schwab, 2016; Sun et al., 2020; Liu et al., 2019). However, for natural languages, it remains unclear how to design an efficient and effective TN approach, which can accurately learn and classify texts.

In the field of natural language processing (NLP), researchers have realized the analogy between the quantum many-body wave function and the word interactions (by the tensor product) in a text sentence, and developed a quantum-inspired language representation (Zhang et al., 2018). Based on the quantum many-body physics and tensor decomposition techniques, Zhang et al. (2018) provided a mathematical understanding of existing convolution neural network (CNN) based text classification methods. Similarly, a tensor space language model (TSLM) has been built based on the tensor network formulation (Zhang et al., 2019). This work shows that TSLM is a more generalized language model compared with $n-$gram and recurrent neural network (RNN) based language models. In implementation, however, TSLM did not provide a tensor network algorithm. The challenge lies in the high dimensionality of each word vector, which is much higher than the dimensionality of each pixel representation in image scenarios. After the tensor product of a number of word vectors, the resulting high-order tensors will become computationally intractable.

More recently, a tensor network algorithm, namely uniform matrix product state (u-MPS) model, has been proposed for probabilistic modeling of a text sequence (Miller et al., 2020). u-MPS is evaluated on a context-free language task, which uses an synthetic data set. However, u-MPS has not been applied in a real-world NLP task, e.g., typical language modeling or text classification task. In addition, the expressive power of u-MPS has not been investigated. The expressive power of tensor

network is a fundamental property of various TNs and has been systematically studied for tensor network factorizations of multivariate probability distributions (Glasser et al., 2019). This motivates us to make use of the theoretical property of TN's expressive power, for developing a tensor network based probabilistic model for natural language representation and classification [1].

To build such a text tensor network, we need to address two research problems in this paper. First, how to design a probabilistic encoding architecture to efficiently and effectively learn and classify the text. Second, how to analyse its expressive power, and make use of such analyses for more theoretical understanding and practical effectiveness of the text tensor network.

In this paper, we propose a novel tensor network architecture, named as TextTN. TextTN encodes each word vector in word-GTNs and classifies the sentence in a sentence-DTN. First, the proposed word-GTNs train a TN for each word and treat each element of a word vector as a node. In this manner, the word-GTNs firstly map a high-dimensional word vector a low-dimensional linear space by the tensor network operators. Then, the second layer tensor network, called as sentence-DTN, trains a TN for each sentence, by regarding the low-dimensional word vector obtained by word-GTNs as its input.

In TextTN, a sentence is represented by the tensor product among word vectors. Therefore, the interaction information among different word vectors and different dimensions are both modeled in TextTN. Such interactions, are encoded in the high-order weighted tensors, which represent a high-order semantic space. In both word-GTNs and sentence-DTN, the high-order tensor can be solved by the tensor network, i.e., a matrix product state model, which uses the idea of low-rank approximation that can conquer the exponential wall problem (Watson & Dunn, 2010).

In sentence-DTN, the bond-dimension is an important hyper-parameter and reflects the expressive power of TextTN. In this paper, we analyze the upper and lower bounds of the bond-dimension. Particularly, its lower bound can be determined by the entanglement entropy, which can be considered as a measurement of the communication information encoded in tensor network. A reference bond-dimension can be set as this lower bound, as we assume that a larger value means an information redundancy and a smaller value indicates an insufficiency of the TN's expressive power. In the experiments, such a reference bond-dimension can achieve effective classification results, which indicates the TextTN's practical advantage in its potential to save hyper-parameter tuning efforts.

Moreover, the word interaction has been taken into account in sentence-DTN by the joint effect of different words for the later class predication by the loss functions. For the learning algorithm, we observe that different word positions have different weights in a sentence, so that the one-function (for a specific position) training in the original DTN is inappropriate. Therefore, we propose an all-function training process in the sentence-DTN to improve the stability of TextTN.

We have evaluated TextTN in four major text classification datasets (MR, Subj, CR and MPQA). The results show that TextTN outperforms convolutional neural network (CNN) on all the datasets. This departs from vision tasks where according to the recent literature, a tensor network has not been reported to outperform CNN (Kim, 2014). In addition, based on the word vectors from the pre-trained model BERT, the TextTN has better results than the BERT model on SST-2 and SST-5 tasks, and the accuracy of BERT+TextTN is comparable with the state of the art (SOTA) result on SST-5 dataset.

2 BACKGROUND

We now provide the background of Matrix product States (MPS), a family of tensor networks. MPS (Schollwock, 2011) is also known as the tensor train decomposition (Oseledets, 2011). Because of the low degree of freedom, the research based on MPS is developing rapidly. At present, the tensor network based on MPS can be roughly divided into two categories. One is the Generative Tensor Network (GTN) (Han et al., 2018; Sun et al., 2020), and the other one is the supervised tensor network (also named as Discriminative Tensor Network, DTN) (Stoudenmire & Schwab, 2016). Then, we briefly describe existing GTN and DTN models for image classification tasks.

GTNs are used to model the joint probability distribution of given data. For a picture X with n pixels, each pixel is encoded into a two-dimensional vector $\boldsymbol{x}_i = (p_i, 1 - p_i)^T$ by a feature mapping from a

---

[1]In this paper, we focus on the text classification task. However, the idea and formulation of our proposed approach are general and have potential in other NLP tasks.

Figure 1: The schematic of tensor networks based on MPS. Left is GTNs and right is DTN.

pixel's value (Sun et al., 2020), where $i \in \{1, \ldots, n\}$ and p_i is the mapped probabilities of the pixel x_i. The representation of the picture X can be give out $\Phi(X)$ through the operator of tensor product between these vectors $\boldsymbol{x}_i$. A joint probability distribution of the picture X is computed by the GTNs.

$$P_j(X) = |\mathbf{W}_j \bullet \Phi(X)|^2 \tag{1}$$

where $P_j(X)$ represents the probability of a picture X with respect to the category j ($j \in \{1, \ldots, m\}$), m is the number of the categories on an image classification dataset, and $\bullet$ is the operator of tensor contraction. The MPS decomposition of the j^{th} n-order weight tensor $\mathbf{W}_j$ can be written as:

$$\mathbf{W}_j = \sum_{\{\alpha\}} A_{s_1}^{\alpha_1} A_{s_2}^{\alpha_1 \alpha_2} \ldots A_{s_n}^{\alpha_{n-1}} \tag{2}$$

In the left of the Figure 1, we give out an illustrative GTNs in two categories (i.e., m=2). Second or third order tensors A_{s_i} ($i \in \{1, \ldots, n\}$) are from the decomposition of the weight tensor $\mathbf{W}_j$. Each 'virtual' indicator α_k ($k \in \{1, \ldots, n-1\}$) is the rank obtained from the tensor-train decomposition (Oseledets, 2011), and the 'physical' indicator s_i is the dimension of the pixel x_i.

DTN is used to identify the class or label of a picture and computes a conditional probability distribution $P(y|X)$. In DTN, the conditional probability distribution $P(y|X)$ is computed as follows.

$$P(y|X) = \mathbf{W}^l \bullet \Phi(X). \tag{3}$$

where the (n+1)-order weight tensor $\mathbf{W}^l$ is decomposed into a MPS and l is an extra order/index representing the label:

$$\mathbf{W}^l = \sum_{\{\alpha\}} A_{s_1}^{\alpha_1} \ldots A_{s_i}^{l;\alpha_{i-1}\alpha_i} \ldots A_{s_n}^{\alpha_{n-1}} \tag{4}$$

where $P(y|X)$ is a vector and encodes the conditional probability distribution of outputting y given a picture X. Eq. 3 is defined to classify the input X by choosing the label for which the value in the vector $P(y|X)$ is largest. In practice, the MPS shown in the right of Figure 1 is a supervised learning model (Stoudenmire & Schwab, 2016), and these rank values $\{\alpha_k\}$ are set to be equal as the hyper-parameter (bond-dimension) in TN.

3 TENSOR NETWORK FOR LANGUAGE ENCODING AND CLASSIFICATION

Problem setting Our goal is to develop a tensor network architecture to encode and classify a sentence of words in a TN's probabilistic manner. For a sentence with n words (i.e, S=$(w_1, \ldots, w_n)$), the tensor representation of the sentence can be written as ($\boldsymbol{w}_1 \otimes \ldots \otimes \boldsymbol{w_i} \otimes \ldots \otimes \boldsymbol{w}_n$) (Zhang et al., 2019), where $\boldsymbol{w}_i$ are the word vectors. However, as aforementioned in Introduction, because of the dimensional disaster, it is infeasible to directly input such as a sentence representation into a tensor network. In order to solve this problem and still model the word interaction on a high-order tensor (denoted as $\mathbf{W}^l$), we can formalize the TN model as follows:

$$\begin{aligned} P(y|S) &= \mathbf{W}^l \bullet f(S) \\ &= \mathbf{W}^l \bullet (f(\boldsymbol{w}_1) \otimes f(\boldsymbol{w}_2) \otimes \ldots \otimes f(\boldsymbol{w}_n)) \end{aligned} \tag{5}$$

where f is an operator to encode a sentence in a low-dimensional probabilistic space.

In our work, word-GTNs are used to encode the word vectors into a low-dimensional space, and then the new representation of word can be efficiently inputted to the tensor network. Specifically, the

function f in Eq 5 is embodied as word-GTNs (in Section 3.1), and $\mathbf{W}^l$ is embodied as sentence-DTN (in Section 3.2). In the process of text classification, the word-GTNs and sentence-DTN are unified into a new TN framework (TextTN), as shown in Figure 2. Bond-dimension is an important hyper-parameter which reflects the expressive power of TN model and influences the effectiveness of text classification. In Section 3.2, we propose a reference bond-dimension that can be computed based on the entanglement entropy. Besides, to improve the stability of sentence-DTN, all-function learning on sentence-DTN is proposed in Section 3.3.

3.1 Word Encoding Based on word-GTNs

We unfasten TextTN step by step in the sentence representation and classification problem. First, m word-GTNs are used to encode word vectors to a low-dimensional space, where $m(m > 1)$ corresponds to the dimension of the low-dimensional space. In Figure 2, as an example, two word-GTNs are used to encode each word in a sentence, with shared parameters for each word. Firstly, each element of word embedding vector is mapped by a feature mapping. Then, each word is represented as a d-order tensor by calculating the tensor product of each element after feature mapping. For example, for a word vector $\boldsymbol{w_i} = (\theta_1, \ldots, \theta_d)^T$, the tensor product representation is shown as follows:

$$\phi(\boldsymbol{w}_i) = \begin{pmatrix} \cos\left(\frac{\pi}{2}\theta_1\right) \\ \sin\left(\frac{\pi}{2}\theta_1\right) \end{pmatrix} \otimes \ldots \otimes \begin{pmatrix} \cos\left(\frac{\pi}{2}\theta_d\right) \\ \sin\left(\frac{\pi}{2}\theta_d\right) \end{pmatrix} \tag{6}$$

where $\otimes$ is the tensor product, and $\phi(\boldsymbol{w}_i)$ is the tensor product representation of word w_i. The feature mapping (i.e., $\cos\left(\cdot\right)$ and $\sin\left(\cdot\right)$) is motivated by "spin" vectors encoded in quantum systems, which is usually used in TN (Stoudenmire & Schwab, 2016; Han et al., 2018).

Then, two word-GTNs are used to encode the tensor $\Phi(\boldsymbol{w}_i)$ and get the probability distribution $\boldsymbol{v}_i$, $i \in \{1, \ldots, n\}$ (see Figure 2). Specifically, for word w_i, each word-GTN can encode the word into a probability value $P_j^i, j \in \{1, 2\}$. In the following, $\boldsymbol{v}_i$ is represented by a 2-dimensional vector $(P_1^i, P_2^i)^T$ which is calculated by:

$$\boldsymbol{v}_i = f(\boldsymbol{w}_i) = \begin{pmatrix} P_1^i \\ P_2^i \end{pmatrix} = \begin{pmatrix} |\mathbf{W}_1 \bullet \phi(\boldsymbol{w}_i)|^2 \\ |\mathbf{W}_2 \bullet \phi(\boldsymbol{w}_i)|^2 \end{pmatrix} \tag{7}$$

where $\bullet$ is the operator of tensor contraction, $\mathbf{W}_1$ and $\mathbf{W}_2$ are two weight tensors to be learned in word-GTNs, and shared for all word vectors in a sentence. The probability condition of $P_1^i + P_2^i = 1$ is then achieved by the $softmax$ in practice.

word-GTNs are different from the existing GTNs shown in Background section. The word-GTNs are used to learning the new word representation (rather than text representation), and the existing GTNs are used to classify the pictures (not for pixels). Since a word does not have a class or label, the output of word-GTNs corresponds to the probabilities in a low-dimensional feature space.

Regarding the dimension of low-dimensional space of word-GTNs. i.e, m, we will show that the upper bound of the bond dimension of TextTN is $m^{\lfloor n/2 \rfloor}$ in Theorem 1. The expressive power of the model will increase exponentially along with the increasing m (Khrulkov et al., 2018). Therefore, the dimension m should be set as a small value (e.g., 2 in this section) to prevent a too large expressive power. This observation is also supported by our experiments.

3.2 Analysis of Bond-dimension on Sentence-DTN

After we use word-GTNs, the new representation of a sentence S can be written as $(\boldsymbol{v}_1 \otimes \ldots \otimes \boldsymbol{v}_n)$. which is a n-order tensor. We now introduce a sentence-DTN to classify sentences. This sentence-DTN is a MPS which is from the tensor-train decomposition (Oseledets, 2011) of high-order tensor. By inputting the sentence vector obtained by word-GTNs, the sentenc-DTN can be formalized as:

$$\begin{aligned} P(y|S) &= \mathbf{W}^l \bullet (\boldsymbol{v}_1 \otimes \ldots \otimes \boldsymbol{v}_n) \\ &= A_{S_1}(\boldsymbol{v}_1) A_{S_2}(\boldsymbol{v}_2) \ldots A_{S_i}^l(\boldsymbol{v}_i) \ldots A_{S_n}(\boldsymbol{v}_n) \end{aligned} \tag{8}$$

which is a $n+1$-order MPS. As we introduced in Background, we can set the rank values as an equal value (bond-dimension), i.e., $\alpha_1 = \ldots = \alpha_j = \ldots = \alpha_{n-1}$. In other words, the bond dimension is set as r

Figure 2: The diagram about the model architecture of TextTN.

$(r=\alpha_j)$. Then, each element of $\mathbf{W}^l$ can be calculated as follows,

$$\mathbf{W}^l{}_{S_1,\dots,S_n} = \sum_{\{\alpha_j=1\}}^{r} A^{\alpha_1}_{s_1} \dots A^{l;\alpha_{j-1}\alpha_j}_{s_i} \dots A^{\alpha_{n-1}}_{s_n} \tag{9}$$

The bond-dimension r is the hyper-parameter which can reflect the expressive power of a tensor network. Inspired by (Deng et al., 2017), we analyze the bond-dimension by the entanglement entropy, as defined in Definition 1.

Definition 1. *For an $n+1$-order weight tensor $\mathbf{W}^l$ decomposed to a matrix product states (MPS), λ ($\lambda \leq r$) singular values can be given out in the $\lfloor \frac{n}{2} \rfloor$-th node of MPS. The entanglement entropy is calculated by the singular-value vector $\boldsymbol{g}_k$ as*

$$E = -\sum_{k=1}^{\lambda} \boldsymbol{g}_k^2 \log \boldsymbol{g}_k{}^2 \tag{10}$$

where λ is the number of non-zero singular values, $\log$ is the log to the base 2, and the normalization condition of the singular-value vector $\sum_{k=1}^{R} g_k^2 = 1$ is satisfied.

Entanglement entropy measures the amount of communication information in TN (Levine et al., 2019). We can derive the lower bond of the bond dimension based on Entanglement entropy, and the upper bond based on the length of sentence for TextTN. According to the research (Khrulkov et al., 2018), the upper bond of the bond-dimension can be given out and is $m^{\lfloor n/2 \rfloor}$, where m is the inputting dimension of each node in MPS, and n is the number of the nodes, i.e., the length of sentence. Based on the above ideas, we introduce the Theorem 1 as follows.

Theorem 1. *For the input of the sentence-DTN $\{\boldsymbol{v}_1, \dots, \boldsymbol{v}_n\}$, the bond-dimension is bounded as*

$$m^{\lfloor n/2 \rfloor} \geq bond-dimension \geq \lfloor 2^E \rfloor. \tag{11}$$

where E is the entanglement entropy of TextTN, m is the inputting dimension of sentence-DTN, and $\lfloor\ \rfloor$ indicates rounding down, the reference bond-dimension is equal to $\lfloor 2^E \rfloor$.

Proof. The proof can be found in Appendix B. □

Based on the lower-bound of the bond dimension, we propose to identify the reference bond-dimension of TextTN. According to Eq. 11, the lower bond can be determined by the entanglement entropy. If the bond-dimension is less than $\lfloor 2^E \rfloor$, TN model can not effectively model sufficient information measured by the entanglement entropy. If otherwise the bond-dimension is larger than $\lfloor 2^E \rfloor$, although TextTN's expressive power increases, it can not model more information, since the additional information/features learned are corresponding to zero singular values. Therefore, a reference bond-dimension can be estimated by the lower bond of bond-dimension in Eq. 11, and we will evaluate such as reference bond-dimension in experiments.

3.3 ALL-FUNCTION LEARNING ON SENTENCE-DTN

In the original DTN, the position of l in Figure 2 can be moved from A_{S_1} to A_{S_n} in the process of training. It means that any position can be selected for l, leading to a variance for different positions in the processes of training and prediction. The following Claim 1 shows that the original DTN corresponds to one probability function from a functions set.

Claim 1. *For an input* $S = \{\boldsymbol{v}_1, \boldsymbol{v}_2, \ldots, \boldsymbol{v}_n\}$, *the original DTN (Stoudenmire & Schwab, 2016) computes the conditional probability* $P(y|S)$, *which can be considered as a function from a set* T *of functions which compute all the possible conditional probabilities. Such a set is defined as:*

$$T = \{P(y|\boldsymbol{v}_1; \boldsymbol{v}_2 \ldots \boldsymbol{v}_n), \ldots, P(y|\boldsymbol{v}_1 \ldots \boldsymbol{v}_i; \boldsymbol{v}_{i+1} \ldots, \boldsymbol{v}_n), \ldots, P(y|\boldsymbol{v}_1 \ldots \boldsymbol{v}_{n-1}; \boldsymbol{v}_n)\}, \quad (12)$$

where i *the location of segmentation for the input* S, *and is also a position of label* l.

Proof. The proof can be found in Appendix C. $\square$

In the original DTN (Stoudenmire & Schwab, 2016), the loss function is defined as $L(\mathbf{W}^l) = \sum_{j=1}^{N} l(\langle f(S), \mathbf{W}^l \rangle, \boldsymbol{y})$ based on the l in a fixed position, which only corresponds to one probability function. If one function is learned, the different aspects probability distribution for the tensor decomposition in different position can not be considered. To solve this problem, we propose to model all functions in the set T in Eq. 12, with a new loss defined as follows:

$$L(\mathbf{W}^l, \mathbf{g}) = \frac{1}{N} \sum_{j=1}^{N} CE(\sum_{i=1}^{n} \mathbf{g_i} \langle f(S), \mathbf{W}^{l_i} \rangle, \boldsymbol{y}) \quad (13)$$

where CE is cross-entropy, $\boldsymbol{y}$ is the label that is represented by a one-hot vector, N is the number of samples, n is the length of the sentence, $\mathbf{g}$ is a parameter vector and $\mathbf{g_i}$ is a value in the vector. $\langle f(S), \mathbf{W}^{l_i} \rangle$ is one function from the function set T. The sentence-DTN with all-function learning is expected to achieve higher accuracy than the original DTN.

4 EXPERIMENTS

In this section, we divide the experiment into two parts based on the theories presented above. The first set of experiments is to verify the effectiveness of TextTN. The second set of experiment is to verify that the effectiveness of the reference bond-dimension, which can be computed by Eq. 11 based on the entanglement entropy for different datasets. A Python implementation of the proposed algorithm is placed in Supplementary Material.

4.1 TEXT CLASSIFICATION EVALUATION OF TEXTTN

Datasets and Benchmarks: Six text classification datasets are used in our experiments. **MR** (Pang & Lee, 2004b): Movie reviews are divided into positive and negative categories; **CR** (Hu & Liu, 2004): Customer reviews set where the task is to predict positive or negative product reviews; **Subj**: Subjectivity dataset where the target is to classify a text as being subjective or objective; **MPQA** (Wiebe et al., 2005): Opinion polarity detection subtask; **SST-5** (Pang & Lee, 2004a): The movie reviews in the Stanford Sentiment Treebank, which is a fine-grained classification task (negative, somewhat negative, neutral, somewhat positive, positive); **SST-2** (Socher et al., 2013): Stanford Sentiment Treebank with binary classes. The evaluation metric is "Accuracy" of all tasks.

For CR, MR, MPQA, and Subj tasks, we use publicly word vectors (Word2vec) (Pennington et al., 2014) with 300 dimensions. For SST-2 and SST-5, the Bert-Large pre-trained model (Devlin et al., 2019) is used to obtain word vectors, and the dimension of the word vector from the BERT is 1024. More dataset statistics and experimental settings are given out in the Appendix D.1.

Table 1: The comparison of experimental results between TextTN and other benchmarks. Accuracy is the evaluation metric.

Model	MR	CR	Subj	MPQA
CNN	81.5	85.0	93.4	89.6
DiSAN	–	84.8	94.2	90.1
Capsule-B	**82.3**	85.1	93.8	–
SGC	75.9	–	–	–
MPSAN	–	85.4	94.6	**90.4**
TextTN	82.2	**85.7**	**95.3**	**90.4**

Table 2: The comparison between TextTN and other complicated models based on pre-trained model.

Model	SST-5	SST-2
BCN+ELMo	54.7	–
Star-Transformer	53	–
FLOATER-large	–	**96.7**
CNN_Large	–	94.6
BERT	52.9	94.6
BERT+TextTN	**54.8**	95.3

Table 3: Ablation experiments. The comparative results between TextTN without all-function learning (TextTN w/o all-function), TextTN without word-GTNs (TextTN w/o w-GTNs), and TextTN on four classification datasets (CR, Subj, MPQA and MR). The accuracy is adopted as the evaluation metric.

Model	MR	CR	Subj	MPQA
TextTN w/o w-GTNs	75.1	74.3	90.0	88.8
TextTN w/o all-function	80.5	84.1	94.4	89.8
TextTN	82.2	85.7	95.3	90.4

Ten benchmarks are used to compare with TextTN. In Table 1, **CNN** (Kim, 2014) is used for classification; **DiSAN** (Shen et al., 2017) is a self-attention based model; **Capsule-B** (Yang et al., 2018) is a capsule neural network; **SGC** (Wu et al., 2019) proposes a graph neural network; **MPSAN** (Dai et al., 2020) designs a novel self-attention network. In Table 2 , **BCN+ELMo** (Peters et al., 2018) is a a deep bidirectional language model; **Star-Transformer** (Guo et al., 2019) is a improved Transformer network; **BERT** (Devlin et al., 2019) , **CNN_Large** (Baevski et al., 2019) and **FLOATER** (Liu et al., 2020) are complicated neural network models based on the BERT_Large pre-trained model.

Experimental Results and Analysis: First, TextTN is experimented on four datasets. The results in Table 1 show that TextTN has better results than CNN (Kim, 2014) on MR (+0.7%), CR (+0.7%), Subj (+1.9%) and MPQA (+0.8%). Moreover, compared with the state-of-the-art self-attention based model MPSAN (Dai et al., 2020), TextTN outperforms its results on CR by 0.3%, Subj by 0.7%, and obtains a same result 90.4% on MPQA.

After that, TextTN is experimented with the pre-training word vectors from BERT on SST-2 and SST-5. The results are shown in Table 2. In this experiment, BERT+TextTN achieves the comparable result with the model ELECTRA (Clark et al., 2020), and obtains higher results than BERT (Devlin et al., 2019) by 0.7% on SST-2. For SST-5 dataset, BERT+TextTN outperforms the state-of-the-art results 54.7 by 0.1%, and is higher than BERT (Devlin et al., 2019) by 1.9%.

In order to verify the effectiveness of all-function learning and word-GTNs, we perform ablation experiments shown as Table 3. First, when TextTN is without the all-function learning (TextTN w/o all-function), the classification accuracy declines to varying degrees on the four data sets. The accuracy values on MR, CR, Subj and MPQA drop by 1.7%, 1.6%, 0.9% and 0.6%, respectively. The results verify that the method of all-function learning for text classification is effective and useful.

In addition, in Table 3, we evaluate the effectiveness of word-GTNs by ablation experiments. TextTN w/o w-GTNs means that we directly average the word vectors of words in a sentence to obtain the sentence representation. On the contrary, TextTN uses word-GTNs to generate sentence representations. Compared with TextTN, the accuracy of TextTN w/o w-GTNs are largely reduced on four dataset. In particular, CR drops by 11.4%, MR, MPQA, and Subj decrease by 7.1%, 5.3%, and 1.6%, respectively. This shows that word-GTNs can effectively model word dependence in sentences and provide more effective semantic information for the classifier.

Finally, we analyze the impact of different word vector dimensions on the performance of TextTN, and the results are shown in the Appendix D.2. In addition, in the Section 3.1, the dimension m of probability encoding is a hyper-parameter set to 2. In order to verify this choice, we conduct a comparative experiment, and the results in Appendix D.3 illustrate that compared with $m = 2$, the accuracy of classification with $m > 2$ has not been improved, or even decreased.

Figure 3: On four classification tasks (MR, CR, MPQA and Subj), we calculate the entanglement entropy and evaluate the accuracy of TextTN, respectively, with different bond-dimensions set from 5 to 30.

4.2 EVALUATION OF THE REFERENCE BOND-DIMENSION OF TEXTTN

In Theorem 1, we show that the lower-bound of the bond-dimension can be derived by the entanglement entropy, and then consider such a lower bound can be the reference bond-dimension of TextTN. In order to evaluate such a reference hyper-parameter value, we designed experiments as follows. First, we can compute the entanglement entropy through the initialized training of TextTN on text classification datasets (see Appendix D.4 for details). After that, based on the entanglement entropy, the reference bond-dimension can be computed.

For MR, CR, MPQA and Subj datasets, their accuracy scores are highest when the bond-dimensions of sentence-DTN are 21,18,19 and 20, respectively. These values (i.e., 21,18,19 and 20), are actually the reference bond-dimensions, which are computed based on the entanglement entropy from the initialized training. Specifically, these values can be computed by Eq. 11, i.e., $\lfloor 2^{4.40} \rfloor = 21$, $\lfloor 2^{4.20} \rfloor = 18$, $\lfloor 2^{4.32} \rfloor = 19$ and $\lfloor 2^{4.37} \rfloor = 20$, respectively. In Figure 3, four charts show that the accuracy values reach the highest point when the reference bond-dimensions are computed as 21(MR), 18(CR), 19(MPQA) and 20(Subj).

As shown in Figure 3, by reducing and increasing the bond-dimension with respect to its reference value, we also observe interesting results about the accuracy. For example, in the MR task, when bond dimension ≤ 21 accuracy is less than the accuracy when the bond-dimension is the reference value 21. If bond dimension ≥ 21, the accuracy begins to decline, but the updated entanglement entropy value (computed by the non-zero single values of sentence-DTN) remains stably. The same results are shown on the other three data sets, i.e., CR, MPQA and Subj.

In summary, the above results show the effectiveness of the reference bond-dimension. However, a more rigorous analysis about the reference bond-dimension and the classification effectiveness of TextTN is still an open research question.

5 CONCLUSION AND FUTURE WORK

In this paper, we propose a text tensor network, named as TextTN, which aims at encoding each word (in a sentence) from a high dimensional vector to a low-dimensional vector by word-GTNs. After that, the new sentence representations can be inputted to the sentence-DTN to carry out the sentence classification. The proposed TextTN achieves better results than CNN, and even better experimental results than some neural network models, such as HCapsNet. In addition, TextTN also achieves the experimental results that largely exceeds GTNs in all datasets. The entanglement entropy is defined in TextTN and is helpful to identify the the reference bond-dimension which usually achieves the best accuracy in our experiments.

In the future, we would like to further investigate more theoretical evidence and understanding of using of the entanglement entropy to set an optimal bound dimension. In the practical point of view, we can apply TextTN on more NLP tasks and test the effectiveness of both TextTN and its reference hyper-parameters.

REFERENCES

Alexei Baevski, Sergey Edunov, Yinhan Liu, Luke Zettlemoyer, and Michael Auli. Cloze-driven pretraining of self-attention networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 5363–5372, 2019.

Jacob Biamonte, Peter Wittek, Nicola Pancotti, Patrick Rebentrost, Nathan Wiebe, and Seth Lloyd. Quantum machine learning. *Nature*, 549(7671):195–202, 2017.

Kevin Clark, Minh-Thang Luong, Quoc V Le, and Christopher D Manning. Electra: Pre-training text encoders as discriminators rather than generators. *arXiv preprint arXiv:2003.10555*, 2020.

Biyun Dai, Jinlong Li, and Ruoyi Xu. Multiple positional self-attention network for text classification. In *AAAI*, pp. 7610–7617, 2020.

Dong-Ling Deng, Xiaopeng Li, and S Das Sarma. Quantum entanglement in neural network states. *Physical Review X*, 7(2):021021, 2017.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, 2019.

Ivan Glasser, Ryan Sweke, Nicola Pancotti, Jens Eisert, and Ignacio Cirac. Expressive power of tensor-network factorizations for probabilistic modeling. In *Advances in Neural Information Processing Systems*, pp. 1498–1510, 2019.

Qipeng Guo, Xipeng Qiu, Pengfei Liu, Yunfan Shao, Xiangyang Xue, and Zheng Zhang. Star-transformer. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 1315–1325, 2019.

Zhao-Yu Han, Jun Wang, Heng Fan, Lei Wang, and Pan Zhang. Unsupervised generative modeling using matrix product states. *Physical Review X*, 8(3):031012, 2018.

Minqing Hu and Bing Liu. Mining and summarizing customer reviews. In Won Kim, Ron Kohavi, Johannes Gehrke, and William DuMouchel (eds.), *Proceedings of the Tenth ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, Seattle, Washington, USA, August 22-25, 2004*, pp. 168–177. ACM, 2004. doi: 10.1145/1014052.1014073. URL https://doi.org/10.1145/1014052.1014073.

William Huggins, Piyush Patil, Bradley Mitchell, K Birgitta Whaley, and E Miles Stoudenmire. Towards quantum machine learning with tensor networks. *Quantum Science and technology*, 4(2):024001, 2019.

Valentin Khrulkov, Alexander Novikov, and Ivan V. Oseledets. Expressive power of recurrent neural networks. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL https://openreview.net/forum?id=S1WRibb0Z.

Yoon Kim. Convolutional neural networks for sentence classification. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 1746–1751, 2014.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In Yoshua Bengio and Yann LeCun (eds.), *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL http://arxiv.org/abs/1412.6980.

Yoav Levine, David Yakira, Nadav Cohen, and Amnon Shashua. Deep learning and quantum entanglement: Fundamental connections with implications to network design. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL https://openreview.net/forum?id=SywXXwJAb.

Yoav Levine, Or Sharir, Nadav Cohen, and Amnon Shashua. Quantum entanglement in deep learning architectures. *Physical review letters*, 122(6):065301, 2019.

Ding Liu, Shi-Ju Ran, Peter Wittek, Cheng Peng, Raul Blázquez García, Gang Su, and Maciej Lewenstein. Machine learning by unitary tensor network of hierarchical tree structure. *New Journal of Physics*, 21(7):073059, 2019.

Xuanqing Liu, Hsiang-Fu Yu, Inderjit Dhillon, and Cho-Jui Hsieh. Learning to encode position for transformer with continuous dynamical model. *arXiv preprint arXiv:2003.09229*, 2020.

Jacob Miller, Guillaume Rabusseau, and John Terilla. Tensor networks for language modeling. *arXiv preprint arXiv:2003.01039*, 2020.

Alexander Novikov, Mikhail Trofimov, and Ivan Oseledets. Exponential machines. *arXiv preprint arXiv:1605.03795*, 2016.

Ivan Oseledets. Tensor-train decomposition. *SIAM Journal on Scientific Computing*, 33(5):2295–2317, 2011.

Bo Pang and Lillian Lee. A sentimental education: Sentiment analysis using subjectivity summarization based on minimum cuts. In Donia Scott, Walter Daelemans, and Marilyn A. Walker (eds.), *Proceedings of the 42nd Annual Meeting of the Association for Computational Linguistics, 21-26 July, 2004, Barcelona, Spain*, pp. 271–278. ACL, 2004a. doi: 10.3115/1218955.1218990. URL https://www.aclweb.org/anthology/P04-1035/.

Bo Pang and Lillian Lee. A sentimental education: Sentiment analysis using subjectivity summarization based on minimum cuts. In Donia Scott, Walter Daelemans, and Marilyn A. Walker (eds.), *Proceedings of the 42nd Annual Meeting of the Association for Computational Linguistics, 21-26 July, 2004, Barcelona, Spain*, pp. 271–278. ACL, 2004b. doi: 10.3115/1218955.1218990. URL https://www.aclweb.org/anthology/P04-1035/.

Jeffrey Pennington, Richard Socher, and Christopher D Manning. Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pp. 1532–1543, 2014.

Matthew Peters, Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and Luke Zettlemoyer. Deep contextualized word representations. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 2227–2237, 2018.

Shi-Ju Ran, Emanuele Tirrito, Cheng Peng, Xi Chen, G Su, and M Lewenstein. Tensor network contractions. *LNP*, 964, 2020.

U Schollwock. The density-matrix renormalization group in the age of matrix product states. *Annals of Physics*, 326(1):96–192, 2011.

Tao Shen, Tianyi Zhou, Guodong Long, Jing Jiang, Shirui Pan, and Chengqi Zhang. Disan: Directional self-attention network for rnn/cnn-free language understanding. *arXiv preprint arXiv:1709.04696*, 2017.

Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D. Manning, Andrew Y. Ng, and Christopher Potts. Recursive deep models for semantic compositionality over a sentiment treebank. In *Proceedings of the 2013 Conference on Empirical Methods in Natural Language Processing, EMNLP 2013, 18-21 October 2013, Grand Hyatt Seattle, Seattle, Washington, USA, A meeting of SIGDAT, a Special Interest Group of the ACL*, pp. 1631–1642. ACL, 2013. URL https://www.aclweb.org/anthology/D13-1170/.

E Miles Stoudenmire and David J Schwab. Supervised learning with quantum-inspired tensor networks. *arXiv: Machine Learning*, 2016.

Zheng-Zhi Sun, Cheng Peng, Ding Liu, Shi-Ju Ran, and Gang Su. Generative tensor network classification model for supervised machine learning. *Physical Review B*, 101(7):075135, 2020.

Deborah K Watson and Martin Dunn. Rearranging the exponential wall for large n-body systems. *Physical review letters*, 105(2):020402, 2010.

Janyce Wiebe, Theresa Wilson, and Claire Cardie. Annotating expressions of opinions and emotions in language. *language resources and evaluation*, 39:165–210, 2005.

Felix Wu, Amauri Souza, Tianyi Zhang, Christopher Fifty, Tao Yu, and Kilian Weinberger. Simplifying graph convolutional networks. In *International Conference on Machine Learning*, pp. 6861–6871, 2019.

Min Yang, Wei Zhao, Jianbo Ye, Zeyang Lei, Zhou Zhao, and Soufei Zhang. Investigating capsule networks with dynamic routing for text classification. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 3110–3119, 2018.

Lipeng Zhang, Peng Zhang, Xindian Ma, Shuqin Gu, Zhan Su, and Dawei Song. A generalized language model in tensor space. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 7450–7458, 2019.

Peng Zhang, Zhan Su, Lipeng Zhang, Benyou Wang, and Dawei Song. A quantum many-body wave function inspired language modeling approach. In *Proceedings of the 27th ACM International Conference on Information and Knowledge Management*, pp. 1303–1312, 2018.

A BASIC KNOWLEDGE ABOUT TENSOR NETWORK (TN)

We now describe some basic knowledge on tensor and tensor network, as well as the matrix product states (MPS).

Tensor: A tensor can simply be thought of as multi-dimensional array. The order of a tensor is defined to the number of indexing entries in the array. For example, in Figure 4(a), the vector v with the index $i \in [m]^2$ is a one-order tensor, and the matrix A with two indexes (or nodes) $i \in [m]$ and $j \in [n]$ is a two-order tensor. After that, a n-order tensor is drawn in Figure 4(a) with n nodes, $d_1, d_2, \ldots$, and d_n, where each node corresponds to an input on TN.

Tensor Network (TN): A TN as a weighted graph, where each node corresponds to a tensor. The order of the tensor is the degree of the node in the graph. The weight of each edge is referred to as its bond dimension. A fundamental operator in tensor analysis is the tensor product, which is denoted as $\otimes$. It is an operator that intakes two tensors (or two vectors).

Matrix Product State: MPS is a kind of TN, which is showed in Figure 4(b). A n-order weight tensor W in Figure 4(b) can be decomposed into a MPS, which has n nodes. In the MPS, α_1, α_2, $\ldots$, α_{n-1} are the indexes of bond dimensions (also named as TT-rank in some works (Novikov et al., 2016; Han et al., 2018)).

B PROOF OF THEOREM 1

In TextTN, the bond-dimension is an important hyper-parameter which directly influences the expressive power of tensor network models (i.e., TextTN). In general, the larger bond-dimension a TN model has, the stronger expressive power the TN model will be. However, TN models with too large expressive power are not to improve the effective of model. In order to find a proper bond-dimension to model TextTN for achieving a higher accuracy, we can compute the reference bond-dimension by the entanglement entropy. The entanglement entropy in TextTN have been defined in **Definition 1.**

The entanglement entropy can be computed in the process of TextTN training. After that, we need to find the smallest bond-dimension that can effectively characterize the entanglement entropy. The smallest bond-dimension is a reference bond-dimension in TextTN. The Theorem 1 shows how to compute a reference bond-dimension.

Theorem 1. For the input of the sentence-DTN $\{v_1, \ldots, v_n\}$, the bond- dimension is bounded as

$$m^{\lfloor n/2 \rfloor} \geq bond-dimension \geq \lfloor 2^E \rfloor. \tag{14}$$

---

[2] $i \in [m]$ also is written as $i \in \{1, 2, \ldots, m\}$

Figure 4: The schematic diagram of tensors and tensor network

Figure 5: The diagram about the computing of singular values for the entanglement entropy. The left is the position of separation in sentence-DTN (the position is $v_{\lfloor n/2 \rfloor}$), and the right is the representation of singular values in the process of SVD for sentence-DTN.

where E is the entanglement entropy of TextTN, m is the inputting dimension of sentence-DTN, and $\lfloor \rfloor$ indicates rounding down, the reference bond-dimension is equal to $\lfloor 2^E \rfloor$.

Proof. As shown in Eq. 14, to calculate the reference bond dimension for TextTN, the entanglement entropy is first computed, which is defined in the Definition 1. Practically, the singular values between $v_{\lfloor n/2 \rfloor}$ and $v_{\lfloor n/2 \rfloor+1}$ in Figure 5 can be obtained in the training process of TextTN, when TextTN converges.

Assume that $bond-dimension$ of TextTN is equal to k. The maximal entanglement entropy is computed when the k singular values in TextTN are equal. Eq. 15 gives out the maximal entanglement entropy based on a fixed bond-dimension k.

$$E = -\sum_{i=1}^{k} \frac{1}{k} \log \frac{1}{k} = \log k, \tag{15}$$

On both sides of the equation, doing the exponential calculations in base 2 on both sides of the equation, the new equation can be computed as follows,

$$2^E = k. \tag{16}$$

When k singular values are not equal, the inequality can be written as

$$k \geq 2^E. \tag{17}$$

To ensure that $bond - dimension$ represented by k, is an integer, the inequality can rewritten as $k \geq \lfloor 2^E \rfloor$, where $\lfloor \ \rfloor$ indicates rounding down.

Therefore, the inequality $bond - dimension \geq \lfloor 2^E \rfloor$ in Eq 11 can be established. Recall that the entanglement entropy E computed by Eq. 15 represents the maximal amount of information that TextTN can model. Eq. 17 implies that the maximal entanglement entropy E determines the lower bound of the bond-dimension of TextTN. If the bond-dimension of TextTN is less than $\lfloor 2^E \rfloor$, the maximal amount of information cannot be achieved by TextTN. If the bond-dimension of TextTN is greater than $\lfloor 2^E \rfloor$, TextTN will not model more information than E, since E is the maximal entanglement entropy; In this case, the TextTN will be more complicated. Then, with no more information modeled but more complicated model, it is possible to cause the overfitting problem. Therefore, the *reference bond-dimension* is equal to $\lfloor 2^E \rfloor$. □

Theorem 1 has also been validated in practice. In the process of TextTN training, we can compute the entanglement entropy of TextTN according to the Definition 1. When this training process converges, the maximal entanglement entropy is obtained. In addition, TextTNs with different bond-dimensions are experimented. At the beginning, the classification accuracy of TextTN increases with the increasing of the bond-dimension. When the bond-dimension increases to a certain value, the accuracy of TextTN begins to decline slowly. Such a certain value is the reference bond-dimension and can be computed by $\lfloor 2^E \rfloor$, when the training process converges.

C PROOF OF CLAIM 1

Claim 1 For an input $S = \{\boldsymbol{v}_1, \boldsymbol{v}_2, \ldots, \boldsymbol{v}_n\}$, the original DTN (Stoudenmire & Schwab, 2016) computes the conditional probability $P(y|S)$, which can be considered as a function from a set T of functions which compute all the possible conditional probabilities. Such a set is defined as:

$$T = \{P(y|\boldsymbol{v}_1; \boldsymbol{v}_2 \ldots \boldsymbol{v}_n), \ldots, P(y|\boldsymbol{v}_1 \ldots \boldsymbol{v}_i; \boldsymbol{v}_{i+1} \ldots, \boldsymbol{v}_n), \ldots, P(y|\boldsymbol{v}_1 \ldots \boldsymbol{v}_{n-1}; \boldsymbol{v}_n)\}, \quad (18)$$

where i the location of segmentation for the input S, and is also a position of label l.

Figure 6: The diagram of all-function learning for tensor network. (a) The conditional probability functions for the output in different position $S_i (i \in \{1, \ldots, n\})$. (b) Getting an all-function $f(S)$ by combining all functions $f^i(S)$ from different positions.

Proof. For an input $S = \{\boldsymbol{v}_1, \ldots, \boldsymbol{v}_n\}$, which is from the output of word-DTNs, a n-order tensor, i.e., the input of the sentence-DTN, is given by the operator of tensor product between vectors, $\boldsymbol{v}_i$, $i \in \{1, \ldots, n\}$. The parameter tensor $\mathbf{W}^l$ in DTN is a $(n+1)$-order tensor. There is a mode (or an index) in tensor $\mathbf{W}^l$ to control the number of class in the classification task, which is l. As shown in Figure 6 (a), in the processing of training, the index l is moved from S_1 to S_n.

When the position of l is S_1, the input S is split two parts, which are $I = \{\boldsymbol{v}_1\}$ and $J = \{\boldsymbol{v}_2, \ldots, \boldsymbol{v}_n\}$, the basic events are I and J, the classification function $f^1(S)$ can be represented by condition probability as follows,

$$f^1(S) = P(y|I, J) = P(y|\boldsymbol{v}_1; \boldsymbol{v}_2 \ldots \boldsymbol{v}_n). \quad (19)$$

When the position of separation i is $1 < i < n$, the input S is separated into two parts, which are $I = \{\boldsymbol{v}_1, \ldots, \boldsymbol{v}_i\}$ and $J = \{\boldsymbol{v}_{i+1}, \ldots, \boldsymbol{v}_n\}$, the function $f^1(S)$ is represented

$$f^i(S) = P(y|\boldsymbol{v}_1 \ldots \boldsymbol{v}_i; \boldsymbol{v}_{i+1} \ldots \boldsymbol{v}_n). \quad (20)$$

Table 4: Statistics of all datasets. $Metrics$: Evaluation Metric, L: maximum sample length, N: Dataset examples, N_{train}: training examples, N_{test}: testing examples, N_{dev}: verification examples, $|V|$: vocabulary size, C: number of target categories.

Dataset	$Metrics$	L	N	N_{train}	N_{test}	N_{dev}	$|V|$	C
CR	Accuracy	105	3775	CV	CV	CV	5340	2
MR	Accuracy	56	10662	CV	CV	CV	18765	2
MPQA	Accuracy	36	10606	CV	CV	CV	6246	2
Subj	Accuracy	120	10000	CV	CV	CV	21323	2
SST-2	Accuracy	65	~67K	~65K	1821	872	CV	2
SST-5	Accuracy	53	11855	8544	2210	1101	17836	5

When the position of separation i is $i=n-1$, the function $f^1(S)$ is denoted Eq. 21 similar to Eq. 19 and Eq. 20.

$$f^{n-1}(S) = P(y|\boldsymbol{v}_1 \ldots \boldsymbol{v}_{n-1}; \boldsymbol{v}_n). \tag{21}$$

For different functions $f^i(S)$, they represent different condition probabilities. In the existing work (Stoudenmire & Schwab, 2016), i.e., original DTN, one function is used to classify the input S. $\square$

In order to model all functions in the process of training, and one function learning cannot model all conditional probabilities in the input S, we propose all-function learning method for text classification, which is showed in Figure 6 (b). We adopt weighted summation for these functions (i.e., $f(S)=\sum_{i=1}^n \mathbf{g_i} f^i(S)$, where $\mathbf{g}$ is a parameter vector, $\mathbf{g_i}$ is an element from the vector $\mathbf{g}$).

D   EXPERIMENTAL RESULTS AND ANALYSIS

In this section, we first describe the datasets used in our experiments.

D.1   DATASETS

The statistics of six datasets are showed in Table 4. For CR, MR, MPQA and Subj datasets, they all have a total file. Therefore, we randomly select 10% of the file as the validation set and test set, respectively, and select 80% of the file as the train set. The evaluating indicator of all text classification tasks is the "Accuracy".

For CR, MR, MPQA and Subj tasks, we implement our model with Pytorch-1.20, and train them on a Nvidia P40 GPU. As for learning method, we use the Adam optimizer Kingma & Ba (2015) and an exponentially decaying learning rate with a linear warm up. For SST-2 and SST-5 dataset, the initialized learning rate is 5e-5.

D.2   COMPARISON BETWEEN DIFFERENT DIMENSIONS OF PRE-TRAINED WORD VECTORS

As shown in Table 5, we compare the accuracy of TextTN using word2vec (300-dimension) and Bert_large (1024-dimension) pre-trained word vectors,respectively, for nine text classification tasks (e.g., MR, CR and SST-5). The results show that the accuracy for six tasks will have a significantly increase as the dimension of word representations increases in TextTN. Especially for SST-5 and MR, the results of 1024-dimensional word embedding has over 5% increases compared with the results of 300-dimensional word embedding. Comparative experiments show that TextTN has better learning effects for high-dimensional word representations containing more semantic information.

Table 5: Experiments with varying input word embedding dimensions in six classification datasets

Model	MR	CR	Subj	MPQA	SST-5	SST-2
TextTN (dim-300)	82.2	85.7	95.3	90.4	48.1	91.4
TextTN (dim-1024)	87.4	89.7	97.1	91.5	54.8	95.3

Figure 7: The entanglement entropy in different training epochs on four datasets, including MR, CR, MPQA and Subj when the initialized training.

Table 6: Experiments with different dimensions of probability encoding on Subj dataset.

Dimension	2	3	4	5	6	7	8	9	10
TextTN	95.3	95.0	94.5	94.2	94.6	94.4	94.7	94.6	94.4

D.3 A EXPERIMENT ABOUT THE DIMENSION OF PROBABILITY ENCODING

In Section 3.1, we analyze that the dimension m of probability encoding can not exceed 2. In this experiment, we evaluate the conclusion. As shown in Table 6, we compare the accuracy of the TextTN with different probability encoding dimensions set from 2 to 10. In addition, reported results are the average of 10 runs. The results illustrate that when $m = 2$, the accuracy of classification is 95.3, and when $m > 2$, the accuracy has a significant decrease. In particular, the accuracy only achieves 94.2 when $m = 5$, dropping by 1.1%. The Experimental results verify the effectiveness of $m = 2$.

D.4 THE INITIALIZED TRAINING ON TEXTTN

In order to get the entanglement entropy in the initialized training, we set 80 epochs to training the TextTN. In this process, the entanglement entropy, which is computed according to Determinate 1, gradually converges to a determinate value as the increasing of training epoch.