CoGANs: Collaborative Generative Adversarial Networks

Abstract

In complex creative scenarios, co-creativity by multiple agents offer great advantages. Each agent has a specific skill set and a set of abilities, which is sometimes not enough to perform a general, large and complex task single-handed. These kinds of tasks benefit substantially from collaboration. In deep learning applications, data generation is an example of such a complex, potentially multi-modal task. Previous Generative Adversarial Networks (GANs) focused on using a single generator to generate multi-modal datasets, which is sometimes known to face issues such as mode-collapse and failure to converge. The multi-generator based works such as MGAN, MMGAN, MADGAN and AdaGAN either require training a classifier online, the use of complex mixture models or sequentially adding generators, which is computationally complex. In this work, we present a simple, novel approach of training collaborative GANs (CoGAN), with multiple generators and a single critic/discriminator, without introducing external complexities such as a classifier model. We show that this method of workload division meets the state-of-the-art quality metrics, and makes GAN training robust. We present a proof-of-concept on the MNIST dataset, which has 10 modes of data. The individual generators learn to generate different digits from the distribution, and together learn to generate the whole distribution. We introduce a new component to the generator loss during GAN training, based on the Total Variation Distance (TVD) and show that it significantly improves stability during training and performance over state-of-the-art single generator GANs.

1 Introduction

The 7 C's of creativity as stated by Lubart (2017) describe the main aspects of the creativity: Creators (person-centered characteristics), Creating (the creative process), Collaborations (co-creating), Contexts (environmental conditions), Creations (the nature of creative work), Consumption (the adoption of creative products) and Curricula (the development and enhancement of creativity). With respect to human beings, "Creators" refer to any and all who engage in creative thinking. When people learn about new topics, they create cognitive structures that allow them to understand the topics; they generate concepts that are new to them, although possibly already very well known to others. This is creativity at a strictly intra-personal level. When working in a social setting, such as a company or a classroom, one has to broaden this horizon to include "Co-creativity"."Creativity through collaboration" summarizes the definition of co-creativity as defined by Lubart (2017). Often, collaborators have different or complementary skills that enable them to frequently produce shared creations that they could not or would not produce on their own (Lubart & Thornhill-Miller, 2020). AI-aided co-creation has also been proven to improve general well-being (Yu et al., 2021).
Generative Adversarial Nets (GANs) are implicit generative models where one or more generators play a zero-sum game with a discriminator to recreate and potentially expand a chosen dataset. According to the definition established above, the generator models in modern day GANs such as those described in the works of Goodfellow et al. (2014); Radford et al. (2015); Arjovsky et al. (2017); Gulrajani et al. (2017) exhibit creativity on an intra-personal level. Accordingly, generative networks have been applied in many creative applications such as painting (Ganin et al., 2018; Mellor et al., 2019; Parikh & Zitnick, 2020), doodling (Ha & Eck, 2017; Cao et al., 2019) and extending fictional languages (Zacharias et al., 2022). Most noticeable, in all the applications listed above, a single generative agent was applied to perform a complex task rather than breaking it down into smaller,

more easily manageable sub-tasks.

Other implementations of GANs such as MGAN (Hoang et al., 2017), MMGAN (Pandeva & Schubert, 2019), MADGAN (Ghosh et al., 2018) and AdaGAN (Tolstikhin et al., 2017) try to rectify the missing co-creativity functionality of GANs by using a mixture of multiple generators, modeling the input latent space as a mixture model, requiring the discriminator to classify as well and sequentially train and add generators to the mixture, respectively. MGAN and MADGAN require the discriminator to have classification capabilities and both implementations force the generators to generate different modes. The AdaGAN implementation poses a problem of computational complexity because of the sequential training nature. MMGAN on the other hand focuses on using mixtures at the input latent space level rather than on separating generators.

Our work stands to provide an easier approach to co-creativity than the ones presented above. It does not require the online training of a classifier, we do use a pre-trained MNIST classifier to augment the generator loss with the Total Variation Distance (TVD) to enforce mode separation during training, but mode separation maybe enforced using other methods, not requiring this pre-trained classifier at all. We also show that this is easily and efficiently scalable to more than two generators, which can all be trained in parallel without making complex transformations to the latent space.

Analogous to human behaviour in a social setting, collaboration among two or more such generators allows each individual generator to focus on and specialize in a specific sub-task, making the training process more stable, the generated images clearer and the distribution of the generated images closer to the actual distribution of the chosen MNIST dataset.

2 BACKGROUND

2.1 GANS

Generative Adversarial Nets (GANs) (Goodfellow et al., 2014) were first presented as a novel, game-theory based approach towards data generation. These type of networks consist of two Artificial Neural Networks (ANNs), where the *generator* ($G(\mathbf{z})$) takes in noise, that is randomly sampled from a possibly multi-dimensional distribution, and using its weight parameters, transforms it into another distribution. The noise $\mathbf{z} \sim P_z$ is transformed into $\tilde{\mathbf{x}}$ through successive linear transformations followed by the application of non-linear activation functions.

The second model, termed as the *discriminator* ($D(\mathbf{x})$), takes as an input batches of real and fake data points and outputs a 0 or 1 based on whether it computes the data point to be from the generator's distribution (P_g) or the actual data distribution (P_r), respectively. The goal of the generator is to minimize the Jensen-Shannon divergence (JSD) between P_r and P_g. The objective function that is being solved under this setup is given by

$$\min_{G} \max_{D} \mathbb{E}_{\mathbf{x} \sim P_r}[log(D(\mathbf{x})] + \mathbb{E}_{\tilde{\mathbf{x}} \sim P_g}[log(1 - D(\tilde{\mathbf{x}})] \tag{1}$$

Where $\tilde{\mathbf{x}} = G(\mathbf{z})$, $\mathbf{z} \sim P_z$, P_r is the data distribution, P_g is the generator distribution and G and D are the *generator* function and *discriminator* function, respectively.

This particular approach is unstable during training and suffers from commonly known problems such as failure to converge, mode collapse and vanishing gradients (Arjovsky & Bottou, 2017). According to Arjovsky et al. (2017), the distance metric (JSD), which this method attempts to minimize, suffers from potential discontinuities with respect to the generator's parameters, leading to training difficulty. A variation of this method is the Deep Convolution GAN (DCGAN) (Radford et al., 2015), that uses Convolutional Neural Networks (CNNs), to improve image data generation significantly, but ends up suffering from the same problems in training, as specified above.

2.2 WGAN AND WGAN-GP

Wasserstein GAN (WGAN) (Arjovsky et al., 2017) presents an improvement over vanilla GANs by presenting and rectifying problems with the GAN objective function. The claim is that the original objective function which the GAN generator aims to minimize (the JSD) can at times be discontinuous with respect to the generator's parameters, which induces instability during the training. Two notable changes were made, to rectify the training instabilities: changing the distance metric to Wasserstein distance or Earth-Mover distance and changing the *discriminator* network to a *critic*

network, that instead of outputting a 0 or a 1, outputs a linear activation of the output layer. These changes required the addition of the constraint that the weights of the critic network must satisfy the Lipschitz constraints. These constraints were enforced using *weight clipping* in the original paper, i.e. $\mathbf{w} \in [-0.01, 0.01]^l$. The objective function which the WGAN solves can be given by

$$\min_G \max_{D \in \mathbb{D}} \mathbb{E}_{\mathbf{x} \sim P_r}[D(\mathbf{x})] - \mathbb{E}_{\tilde{\mathbf{x}} \sim P_g}[D(\tilde{\mathbf{x}})], \tag{2}$$

which is obtained by using the Kantorovich-Rubinstein duality (Villani, 2009). Here, $\mathbb{D}$ is the space of 1-Lipschitz functions, P_g is the generator distribution, P_r is the data distribution and $\tilde{\mathbf{x}} = G(\mathbf{z})$, $\mathbf{z} \sim P_z$. In that case, under an optimal critic, minimizing the value function with respect to the generator parameters minimizes $W(P_r, P_g)$, $W(.,.)$ denoting the Wasserstein distance.

The WGAN-GP method (Gulrajani et al., 2017) is an improvement over this method which uses their novel *gradient penalty* loss, instead of the former *weight clipping* to implicitly enforce the Lipschitz constraints. The new objective function solved by WGAN-GP is given by

$$\min_G \max_{D \in \mathbb{D}} \mathbb{E}_{\mathbf{x} \sim P_r}[D(\mathbf{x})] - \mathbb{E}_{\tilde{\mathbf{x}} \sim P_g}[D(\tilde{\mathbf{x}})] + \lambda * \mathbb{E}_{\hat{\mathbf{x}} \sim P_{\hat{\mathbf{x}}}}[(||\nabla_{\hat{\mathbf{x}}} D(\hat{\mathbf{x}})||_2 - 1)^2], \tag{3}$$

where the first two terms are the same as equation (2) and the third one is the *gradient penalty* (GP) term. Here, $\hat{\mathbf{x}} = \epsilon \mathbf{x} + (1 - \epsilon)\tilde{\mathbf{x}}$ and $\epsilon \sim U[0, 1]$. $P_{\hat{\mathbf{x}}}$ is the probability distribution associated with $\hat{\mathbf{x}}$. $\lambda = 10$ is the default gradient penalty coefficient as in the original paper.

The training stability improvement because of using Wasserstein distance paired with the GP to implicitly apply the Lipschitz constraint shows a substantial improvement over vanilla GANs. The WGAN-GP method is very closely related to the implementation presented in this contribution. When we refer to *convergence*, it will be equivalent to saying that the discriminator loss goes to 0.

2.3 GANs for multi-modal datasets

In past works, there have been attempts with varied scope, to learn multi-modal datasets such as multi-class generation. The most notable are the MMGAN by Pandeva & Schubert (2019), MGAN by Hoang et al. (2017), MAD-GAN by Ghosh et al. (2018) and AdaGAN by Tolstikhin et al. (2017). MMGAN approaches multi-modal generation task by considering the latent space $\mathbf{z}$ as a Gaussian mixture model consisting multiple modes. Initially, a Gaussian distribution is sampled from a cluster of Gaussian distributions $(Cat(K, 1/K))$, where the dataset has K "clusters". Then, $\mathbf{z}$ is sampled from this distribution and transformed by the generator to create images. This method uses an extra *encoder* (E) model to predict the cluster of data objects.

The MGAN method (Hoang et al., 2017) implements multiple generators that generate K different batches. One of these batches is sampled randomly using a predefined distribution π. The generated batch is fed into a "discriminator + classifier" network with shared weights in all layers except the output layer. The goal of the classifier is to predict which generator generated the images, and the discriminator has the same functionality as the vanilla GAN method.

MAD-GAN (Ghosh et al., 2018) is a method which combines the classifier and discriminator functionalities into a single model.

All of the previously mentioned methods require that an extra model be trained with the original GAN or multi-generator setup to force separation of modes among the generators. Unlike these methods, AdaGAN introduces a sequential "training+adding generators" approach. This approach is computationally inefficient as shown by Hoang et al. (2017).

Although the results suggest that these methods work well, they require adding an extra step in the training process. The method presented in this contribution manages to achieve promising results without the need of such additions.

2.4 GAN evaluation metrics

The most commonly used metrics in the GAN community to evaluate the generated images is the Inception Score (IS) as introduced in Salimans et al. (2016). This method is an objective metric which evaluates two things: Image quality and image diversity. It uses the pre-trained InceptionV3 model

(Szegedy et al., 2014) to predict the class probabilities. This is actually the conditional probability of class prediction given the image $p(y|x)$. The marginal distribution $p(y)$ is calculated using the batch-wise average of $p(y|x)$. Finally the KL-Divergence is calculated using

$$KLD = p(y|x) * (log(p(y|x)) - log(p(y)))\tag{4}$$

This is performed over multiple batches and the final score is reported as the mean and standard deviation of all the batches.

Over the past few years, IS has started to be considered an unreliable metric for evaluation, especially for datasets that are not ImageNet (Barratt & Sharma, 2018). A better evaluation metric that has become more popular is the Frechet Inception Distance (FID) (Heusel et al., 2017). This metric uses the InceptionV3 model without the final classification layer. The latent distribution generated by the InceptionV3 network for real and fake images is compared. Specifically, the FID metric is given by

$$FID = (\mu_1 - \mu_2)^2 + Tr(C_1 + C_2 - \sqrt{C_1 * C_2})\tag{5}$$

where μ_1 and μ_2 are means of the latent representation of fake and real data, respectively and C_1 and C_2 are their covariance matrices. This metric was proposed as an improvement over the IS. However, it suffers from some of the same issues as the IS because of the fact that InceptionV3 is pre-trained on a 1000 class dataset of RGB images.

For our particular use case with MNIST (a grayscale dataset with only 10 classes), we used the `tensorflow-gan` library's built in method `mnist_frechet_distance` function. This function uses a pre-trained MNIST classifier, rather than the less relevant InceptionV3, to calculate the Frechet distance.

3 METHODS

3.1 DATASET

MNIST is a very well-known dataset. It contains 60,000 images (train set) and 10,000 images (test set) of handwritten digits belonging to 10 classes (numbers 0-9) of 28x28x1 pixels per image. It is widely used for proof-of-concepts of various model architectures and training protocols related to image classification or generation. This is because it is easily available through TensorFlow and PyTorch, smaller images make it easier to implement on simplistic hardware and it has well-defined modes in the dataset. This is the dataset we used for our experiments. The train set was used during the training procedures and the test set was used to evaluate our models. We resized the images to 32x32 to maintain the dimensions as a power of 2, to maintain even dimensions while using strided convolutions. We also normalized pixel values to lie between -1 and 1, as this has been shown to perform better in WGAN-GP (Gulrajani et al., 2017).

3.2 THE TVD LOSS COMPONENT

The Total Variation Distance (TVD) is a quantity that measures the distance between two categorical distributions and is defined as:

$$TVD(P, Q) = \frac{1}{2} \sum_{x \in \mathbf{X}} |P(x) - Q(x)|\tag{6}$$

We assumed each class in the MNIST dataset is a mode. To enforce mode separation among individual generators, we augmented the generator loss in the original WGAN-GP paper (Gulrajani et al., 2017) with a TVD based component. We chose this as the preferred metric because it has well defined bounds ($TVD(P, Q) \in [0, 1]$) and is easy to compute for categorical distributions. It is also commutative, that is $TVD(i, j) = TVD(j, i)$.

We used a pre-trained MNIST classifier (C) to obtain *softmax* scores for each generated batch $\tilde{\mathbf{x}}_i$ resulting in n categorical distributions. We needed the classifier to be simple and fast. So, we trained a very basic convolution neural network to perform this loss computation. Refer to Appendix A for more information and convergence graphs. We obtained a peak accuracy of 99% after training. Subsequently, we defined the distance metric $\Delta = \frac{1}{N} \sum_{i=1}^{n} \sum_{j=i+1}^{n} TVD(C(\tilde{\mathbf{x}}_i), C(\tilde{\mathbf{x}}_j))$, which is just the average pairwise TVD (where N is the number of unique pairs of categorical distributions using 'n' generators). Finally, we introduced this term to the loss of each generator to get:

$$L_{G,i} = -\mathbb{E}_{\tilde{\mathbf{x}}_i \sim P_{Gi}} D(\tilde{\mathbf{x}}_i) - \gamma * \Delta \qquad i = 1, 2, ..., n\tag{7}$$

where the first term is the original generator loss from the WGAN-GP paper. The hyperparameter γ is the distance weight. We carried out experiments to find the optimal γ which produces the best possible FID (refer to Section 4).

3.3 The training algorithm

The training algorithm remained the same for all the experiments. However, in each experiment, the effect of each newly introduced parameter (namely, γ and n) was tested. The specific values used for each experiment, are specified in Section 4. All other hyperparameters are constant throughout all experiments. The batch size m has to be varied to maintain divisibility by n in step 4 of the algorithm. However, we restricted this value to one of two possible values $[500, 504]$, to maintain approximate similarity. Specifically, for $n = 1, 2, 4, 5, 10$, $m = 500$ and for $n = 3, 6, 7, 8, 9$, $m = 504$. We used the generator learning rate and discriminator learning rate $\alpha_g = \alpha_d = 0.0002$. We chose the number of discriminator training iterations per generator iteration, $n_d = 3$, following the recommendations of Gulrajani et al. (2017). Also following their recommendations, we used the *Adam* optimizer, setting $\beta_1 = 0.5$ and $\beta_2 = 0.9$ for all our experiments. The $\circ$ symbol denotes concatenation along batch dimension. $\lambda = 10$ is the gradient penalty weight as described in Eq. equation 3. The algorithm pseudocode can be found in Algorithm 1 below.

Algorithm 1 Training algorithm

Require: β_1, β_2, α, the *Adam* parameters, γ the distance weight, n the number of generators, n_d the number of discriminator iterations per generator iteration, λ the GP coefficient and m the batch size, α_g, α_d, the learning rates and a pre-trained classifier (C).
Require: initial discriminator parameters w_0, initial generator parameters $\theta_{0,i} \forall i = 1, 2, ..., n$
  1: **while** θ_i have not converged **do**
  2:     **for** $t = 1, ..., n_d$ **do**
  3:         Sample real data batch $\mathbf{x} \sim P_r$, latent variable batch $\mathbf{z} \sim p(\mathbf{z})$ and $\epsilon \sim U[0, 1]$.
  4:         Split the latent vector batch into n sub-batches $(\mathbf{z}_1, ..., \mathbf{z}_n)$
  5:         $\tilde{\mathbf{x}}_i \leftarrow G_i(\mathbf{z}_i) \qquad \forall i = 1, ..., n$
  6:         $\tilde{\mathbf{x}} \leftarrow \tilde{\mathbf{x}}_1 \circ \tilde{\mathbf{x}}_2 \circ ... \circ \tilde{\mathbf{x}}_n$
  7:         $\hat{\mathbf{x}} \leftarrow \epsilon\mathbf{x} + (1 - \epsilon)\tilde{\mathbf{x}}$
  8:         $L_d \leftarrow \frac{1}{m}\sum_{i=1}^{m}[D_w(\tilde{\mathbf{x}}) - D_w(\mathbf{x}) + \lambda(||\nabla_{\hat{\mathbf{x}}}D(\hat{\mathbf{x}})||_2 - 1)^2]$
  9:         $w \leftarrow Adam(\nabla_w L_d, w, \alpha, \beta_1, \beta_2)$
10:     **end for**
11:     sample n latent variable batches $\mathbf{z}_i \sim p(\mathbf{z})$
12:     $\tilde{\mathbf{x}}_i \leftarrow G_i(\mathbf{z}_i) \qquad \forall i = 1, ..., n$
13:     **if** $\gamma \neq 0$ **then**
14:         $\Delta \leftarrow \frac{1}{N}\sum_{i=1}^{n}\sum_{j=i+1}^{n} TVD(C(\tilde{\mathbf{x}}_i), C(\tilde{\mathbf{x}}_j))$
15:         $L_{g,i} \leftarrow \frac{1}{m}\sum_{k=1}^{m}[-D(G_i(\mathbf{z})) - \gamma\Delta]$
16:     **else**
17:         $L_{g,i} \leftarrow \frac{1}{m}\sum_{k=1}^{m} -D(G_i(\mathbf{z}))$
18:     **end if**
19:     $\theta_i \leftarrow Adam(\nabla_{\theta_i} L_{g,i}, \theta_i, \alpha, \beta_1, \beta_2)$
20: **end while**

---

4 Experiments

For all the experiments, we used the same model architectures for all the generators and the discriminators, the details of which can be found in Appendix B.
We performed 3 broad categories of experiments -

1. Baseline experiments as a proof of concept of our new method.

2. Optimizing for the hyperparameter γ.

3. Experiments comparing number of generators versus performance (in terms of FID).

In the baseline experiments, we ran 2 tests, with 2 generators each. In the first test, we set the $\gamma = 0$. This test is termed as *batch concatenation*, because it is equivalent to the following - Each Generator (G_i) generates `batch_size/n` images, during each iteration of Discriminator (D) training, where n is the number of generators. These individual generations ($\tilde{\mathbf{x}}_i$) are of size (`batch_size/n`, 32, 32, 1). We concatenate them along the batch dimension to generate $\tilde{\mathbf{x}}$, i.e.:

$$\tilde{\mathbf{x}} = \tilde{\mathbf{x}}_1 \circ \tilde{\mathbf{x}}_2 \circ ... \circ \tilde{\mathbf{x}}_n$$

This $\tilde{\mathbf{x}}$ is then used in the WGAN-GP objective function equation 3. In the second test, we set $\gamma = 5.0$, an arbitrary value to see the impact of the new loss component on convergence. Here we trained all models until convergence was reached.

In the second category, we fixed the number of generators $n = 5$ and the number of epochs $= 70$. We carried out 3 tests:

- Constant γ throughout training at discrete values $[0, 5, 10, 11, 12, 13, 14, 15, 20]$.
- Linear decay from $\gamma = 20$ to $\gamma = 5$, so that the effective weight is equal to the average of the two ($\gamma_{eff} = 12.5$), which we found to be close to the optimal for the setup.
- Sudden death, where $\gamma = 20$ for the first 20 epochs of training and then it is equal to 0 for the remainder.

In the final category, we swept the number of generators $n = [1, 2, ..., 10]$ to see how it affects the performance. In this category of experiments, the constant parameter $\gamma = 12.2$ was chosen after the optimizations performed in the second category of experiments. Here, we trained all models until convergence was reached.

5 RESULTS AND DISCUSSION

If we run our experiments, with $n = 1$, we can also evaluate the state-of-the-art FID for a vanilla WGAN-GP. We performed a session of training under these conditions and as can be observed in the Fig. 4, the current state-of-the-art WGAN-GP gives us an $FID \sim 4.25$. In all the future discussions, we will compare the obtained values to this one.

5.1 BASELINE EXPERIMENTS

We ran both of the two generators experiments until convergence 3 times, to test robustness. The convergence graphs for one training session are presented in Fig. 1. Fig. 1b shows the convergence graph for batch concatenation (b.c.) + TVD and Fig. 1a shows just batch concatenation (b.c.) based generator loss. We see from the graphs that both of the generators are converging at a similar pace (the lines overlap with each other), under both loss functions. The discriminator loss going to 0 indicates that it predicts negative and positive values with almost equal probability (meaning the system has converged). The network managed to converge all 3 times for both loss functions ($\gamma = 0$ and $\gamma = 5$).

After convergence, we measured **3 metrics**: FID, calculated according to Eq. equation 5; $TVD(C(G_1(\mathbf{z}_1)), C(G_2(\mathbf{z}_2)))$ and; average class probabilities (softmax) for each generators' generations, as predicted by C. These metrics are presented in Tables 1 and 2.

Table 1: FID and TVD metric comparison

Loss	FID	TVD
b.c. only	4.738	0.9832
TVD + b.c.	3.602	0.9965

We see in Table 2 that the two generators specialize in generating disjoint subsets of classes. The actual samples generated by each generator can be seen in Fig.2. We see that they are indeed from separate classes for different generators and of very high quality. We can also observe (Table 1) how introducing a small non-zero constant $\gamma = 5$ drastically improves the FID as well as the TVD.

(a) Convergence graphs for batch concatenation only

(b) Convergence graphs for batch concatenation augmented with TVD

Figure 1: 2 Generator convergence graphs

Table 2: Average class probabilities

b.c. only	0	1	2	3	4	5	6	7	8	9
generator 0	00.00	**27.23**	**13.23**	00.63	**18.91**	00.00	00.00	**22.46**	00.32	**17.23**
generator 1	**19.15**	00.01	08.94	**19.75**	00.06	**17.19**	**18.35**	00.29	**14.93**	01.31
TVD+b.c.	0	1	2	3	4	5	6	7	8	9
generator 0	**18.98**	**21.77**	00.47	00.03	**18.96**	00.00	00.13	**19.47**	00.49	**19.69**
generator 1	00.51	00.04	**21.25**	**19.79**	00.16	**17.90**	**23.48**	00.01	**16.82**	00.05

5.2 TVD LOSS WEIGHT EXPERIMENTS

5.2.1 DISCRETE CONSTANT

In this experiment we swept gamma across the following values - $[0, 5, 10, 11, 12, 13, 14, 15, 20]$ and kept it constant throughout the 70 epochs of training. We fixed the number of generators to 5. We evaluated each time using the FID metric. The plot of the parametric sweep is seen in Figure 3. We can see that there is an optimum value for the TVD loss weight (approximately $\gamma = 12.2$).

5.2.2 LINEAR DECAY

In this experiment, we again fixed the number of generators to 5 and the number of epochs to 70. We linearly decayed the parameter γ from 20 to 5, giving us an effective $\gamma_{eff} = 12.5$. We evaluated the FID and TVD after training is complete and received $FID = 3.5379$ and $TVD = 0.9999$. This method clearly gives an improvement over the state-of-the-art FID as well as optimal mode separation.

5.2.3 SUDDEN DEATH

Keeping the other elements of the setup exactly the same, we now keep $\gamma = 20$ for the first 20 epochs of training and then $\gamma = 0$ for the remaining 50. We end up with $FID = 2.6685$ and $TVD = 0.9998$, which again is an improvement over the state-of-the-art FID along with great mode separation.

This result is interesting as it suggests that one does not need to enforce mode separation (or compute the pairwise TVD) for all of the training epochs. Once the modes have sufficiently separated, we can remove the TVD loss component and the generators will keep generating separate modes and in a much better quality than current state-of-the-art.

(a) Samples generated by `gen0` (**tvd+b.c.**)

(b) Samples generated by `gen1` (**tvd+b.c.**)

(c) Samples generated by `gen0` (**b.c. only**)

(d) Samples generated by `gen1` (**b.c. only**)

Figure 2: Samples generated by both the methods

Figure 3: FID vs γ sweep

5.3 NUMBER OF GENERATORS SWEEP

From the above experiments we found an optimal value for $\gamma = 12.2$ which we fixed and kept constant for this experiment. We changed n from 1 to 10 (1 representing current state-of-the-art). We trained each setup until convergence or 250 epochs, whichever came first. We set the early stopping criterion as: *less than 0.01 change in the objective for 5 consecutive epochs*. We decided to do this because when we tried running for a fixed number of epochs, we realized that for $n = 3, 6, 7, 9$ the generators did not converge in the same number of epochs. Here we notice that the mode separation problem is much more difficult because of the non-divisibility of 10 (the number of modes) by n, which results in one or more modes of the dataset being *assigned* to a different generator during different training epochs. As we can also see in Fig. 4, the FID values for these specific values of n are much higher, denoting a much worse performance. The FID for $n = 4$ and $n = 5$ is the lowest, showing us that having more generators does not imply better performance and this is another parameter that can be optimized.

Figure 4: FID vs no. of generators

6 CONCLUSIONS

We introduced a novel approach in training WGANs in a collaborative manner which we call CoGANs. This approach can be used to model complex, multi-modal datasets in a better way. We showed that using our approach outperforms state-of-the-art GANs on the MNIST dataset in terms of FID and manages to improve overall stability, robustness and performance of GANs. We also introduced a new loss component that can be added to the generator loss during training. We observed that even adding this loss for a short amount of time in the initial training can drastically improve performance. We can also tune the weight of this loss to fit the number of generators we plan to use.

A major disadvantage of the current method is the fact that we need a pre-trained classifier to calculate a loss during training, which is not efficient. Majority of the future work will involve finding better losses to enforce mode separation without the use of a classifier. The eventual goal of this research is to use multiple simple generator models to generate multi-modal data rather than a single large, complex network. This research is a also contribution towards modelling co-creativity in humans. Study of this model can help us better understand and implement creativity promoting interactions.

REFERENCES

Martin Arjovsky and Léon Bottou. Towards principled methods for training generative adversarial networks, 2017. URL https://arxiv.org/abs/1701.04862.

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein gan, 2017. URL https://arxiv.org/abs/1701.07875.

Shane Barratt and Rishi Sharma. A note on the inception score, 2018. URL https://arxiv.org/abs/1801.01973.

Nan Cao, Xin Yan, Yang Shi, and Chaoran Chen. Ai-sketcher : A deep generative model for producing high-quality sketches. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33:2564–2571, 07 2019. doi: 10.1609/aaai.v33i01.33012564.

Yaroslav Ganin, Tejas Kulkarni, Igor Babuschkin, S. M. Ali Eslami, and Oriol Vinyals. Synthesizing programs for images using reinforced adversarial learning, 2018. URL https://arxiv.org/abs/1804.01118.

Arnab Ghosh, Viveka Kulharia, Vinay Namboodiri, Philip H.S. Torr, and Puneet K. Dokania. Multi-agent diverse generative adversarial networks. In *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8513–8521, 2018. doi: 10.1109/CVPR.2018.00888.

Ian J. Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial networks, 2014. URL https://arxiv.org/abs/1406.2661.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of wasserstein gans. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/892c3b1c6dccd52936e27cbd0ff683d6-Paper.pdf.

David Ha and Douglas Eck. A neural representation of sketch drawings, 2017. URL https://arxiv.org/abs/1704.03477.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. 2017. doi: 10.48550/ARXIV.1706.08500. URL https://arxiv.org/abs/1706.08500.

Quan Hoang, Tu Dinh Nguyen, Trung Le, and Dinh Phung. Multi-generator generative adversarial nets, 2017. URL https://arxiv.org/abs/1708.02556.

Todd Lubart. The 7 c's of creativity. *The Journal of Creative Behavior*, 51(4):293–296, 2017. doi: https://doi.org/10.1002/jocb.190. URL https://onlinelibrary.wiley.com/doi/abs/10.1002/jocb.190.

Todd Lubart and Branden Thornhill-Miller. *Creativity: An Overview of the 7C's of Creative Thought*, pp. 277–305. 04 2020. ISBN ISBN 978-3-947732-35-7 (Hardcover) ISBN 978-3-947732-34-0 (Softcover) ISBN 978-3-947732-33-3 (PDF). doi: 10.17885/heiup.470.c6678.

John F. J. Mellor, Eunbyung Park, Yaroslav Ganin, Igor Babuschkin, Tejas Kulkarni, Dan Rosenbaum, Andy Ballard, Theophane Weber, Oriol Vinyals, and S. M. Ali Eslami. Unsupervised doodling and painting with improved spiral, 2019. URL https://arxiv.org/abs/1910.01007.

Teodora Pandeva and Matthias Schubert. Mmgan: Generative adversarial networks for multi-modal distributions, 2019. URL https://arxiv.org/abs/1911.06663.

Devi Parikh and C. Lawrence Zitnick. Exploring crowd co-creation scenarios for sketches, 2020. URL https://arxiv.org/abs/2005.07328.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks, 2015. URL https://arxiv.org/abs/1511.06434.

Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans, 2016. URL https://arxiv.org/abs/1606.03498.

Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions, 2014. URL https://arxiv.org/abs/1409.4842.

Ilya O Tolstikhin, Sylvain Gelly, Olivier Bousquet, Carl-Johann SIMON-GABRIEL, and Bernhard Schölkopf. Adagan: Boosting generative models. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/d0010a6f34908640a4a6da2389772a78-Paper.pdf.

Cédric Villani. *Optimal transport: old and new*, volume 338. Springer, 2009.

Haizi Yu, James A. Evans, Donna Gallo, Adam Kruse, William M. Patterson, and Lav R. Varshney. Ai-aided co-creation for wellbeing. In Andrés Gómez de Silva Garza, Tony Veale, Wendy Aguilar, and Rafael Pérez y Pérez (eds.), *Proceedings of the Twelfth International Conference on Computational Creativity, México City, México (Virtual), September 14-18, 2021*, pp. 453–456. Association for Computational Creativity (ACC), 2021. URL `https://computationalcreativity.net/iccc21/wp-content/uploads/2021/09/Wkshp4.pdf`.

Thomas Zacharias, Ashutosh Taklikar, and Raja Giryes. Extending the vocabulary of fictional languages using neural networks. *CoRR*, abs/2201.07288, 2022. URL `https://arxiv.org/abs/2201.07288`.

A   APPENDIX - CLASSIFIER TRAINING

We present specific information about the classifier in this section. The network architecture Fig. 5 and convergence graphs Fig. 6 are presented below. Each `conv_block` contains a *convolutional layer* with a 5x5 filter and number of filters going from 64 to 512 in powers of 2. Each *convolutional layer* is followed by *BatchNormalization*, *ReLU* and *Dropout* with $drop\_prob = 0.3$. The `MLP` block contains 2 layers of 128 neurons each followed by a 10 neuron output layer. As observed in 6b, the peak accuracy of our classifier was $\sim 99\%$.

Figure 5: Classifier model

B   APPENDIX - GENERATOR AND DISCRIMINATOR MODELS

We implemented very simple *Generator* and *Discriminator*. The exact models are presented in Fig. 7a and Fig. 7b. Each `conv_block` is exactly the same as the one implemented for the *Classifier*, except the use of *Layer normalization* instead of *Batch normalization*, as recommended in Arjovsky et al. (2017). Each `upsample_block` consists of a *2D Upsampling layer* with a factor of 2x2 followed by a *convolutional layer* with filter size 3x3 and stride 1x1. These operations are followed by *LeakyReLU* activation with $\alpha = 0.2$. *Batch normalization* is applied after the activation. The final `upsample_block` also uses *dropout* with $drop\_prob = 0.3$. The final `upsample_block` uses the *tanh* activation function to squash the values between -1 and 1.

(a) Training loss   (b) Training accuracy

Figure 6: Classifier convergence graphs

(a) Generator model   (b) Discriminator model

Figure 7: Models

C   APPENDIX - OTHER EXPERIMENTS

Setting $\gamma = 0$ and $n = 4$, we ran the setup until convergence. This method is an extended version of the batch concatenation (b.c.) method as described in 4, to four generators instead of two. The convergence graphs show that all 4 generators converge at the same pace (the lines overlap) and the discriminator loss converges to 0 (Fig. 8). Our method improves the state-of-the-art with an $FID = 2.9439$ implying that high quality images are generated that match the dataset distribution. Table 3 and Fig. 9 show the average class probabilities and correspondingly generated samples. This method of training results in an average pairwise $TVD = 0.9633$.

In Table 3, the values in bold represent which generator gives the maximum probability over that class. The number 2 is generated by generator 1, 2 and 3 and the "workload" required for this digit is being distributed among the three of them. We can see that for $\gamma = 0$, the TVD metric goes down as expected, but we can still obtain a comparable FID to what we can achieve using the TVD loss component.

Figure 8: Convergence graph for 4 generators

(a) Samples generated by `gen0`

(b) Samples generated by `gen1`

(c) Samples generated by `gen2`

(d) Samples generated by `gen3`

Figure 9: Samples generated by the 4 generators

Table 3: Average class probabilities($\gamma = 0$, $n = 4$)

Generator number	0	1	2	3	4	5	6	7	8	9
generator 0	00.02	00.15	00.04	13.00	06.91	04.92	**36.91**	00.11	**33.14**	04.79
generator 1	**38.99**	00.00	11.32	**22.84**	00.01	**24.13**	00.03	00.00	02.33	00.33
generator 2	00.15	**45.49**	15.88	00.14	**31.99**	00.68	02.65	00.86	00.84	01.31
generator 3	00.36	00.29	**22.05**	02.46	00.72	00.95	00.00	**41.96**	01.94	**29.24**