Increasing the Coverage and Balance of Robustness Benchmarks by Using Non-Overlapping Corruptions

Abstract

Neural Networks are sensitive to various corruptions that usually occur in real-world applications such as blurs, noises, low-lighting conditions, etc. To estimate the robustness of neural networks to these common corruptions, we generally use a group of modeled corruptions gathered into a benchmark. We argue that corruption benchmarks often have a poor coverage: being robust to them only imply being robust to a narrow range of corruptions. They are also often unbalanced: they give too much importance to some corruptions compared to others. In this paper, we propose to build corruption benchmarks with only non-overlapping corruptions, to improve their coverage and their balance. Two corruptions overlap when the robustnesses of neural networks to these corruptions are correlated. We propose the first metric to measure the overlapping between two corruptions. We provide an algorithm that uses this metric to build benchmarks of Non-Overlapping Corruptions. Using this algorithm, we build from ImageNet a new corruption benchmark called ImageNet-NOC. We show that ImageNet-NOC is balanced and covers several kinds of corruptions that are not covered by ImageNet-C.

1 Introduction

Neural Networks perform poorly when they deal with images that are drawn from a different distribution than their training samples. Indeed, neural networks are sensitive to adversarial examples (Szegedy et al., 2014), background changes (Xiao et al., 2020), and common corruptions (Hendrycks & Dietterich, 2019).

Common corruptions are perturbations that change the appearance of images without changing their semantic content. For instance, neural networks are sensitive to noises (Koziarski & Cyganek, 2017), blurs (Vasiljevic et al., 2016) or lighting condition variations (Dogancan Temel & AlRegib, 2017). Contrary to adversarial examples (Szegedy et al., 2014), common corruptions are not artificial perturbations especially crafted to fool neural networks. They naturally appear in industrial applications without any human interfering, and can significantly reduce the performances of neural networks.

A neural network is robust to a corruption c, when its performances on samples corrupted with c are close to its performances on clean samples. Some methods have been recently proposed to make neural networks more robust to common corruptions (Geirhos et al., 2019; Hendrycks* et al., 2020; Evgenia Rusak, 2020).

To determine whether these approaches are effective, it is required to have a method to measure the neural network robustness to common corruptions. The most commonly used method consists in evaluating the performances of neural networks on images distorted by various kinds of common corruptions: (Hendrycks & Dietterich, 2019; Karahan et al., 2016; Geirhos et al., 2019; Dogancan Temel & AlRegib, 2017). In this study, we call the group of perturbations used to make the robustness estimation a corruption benchmark. We also use this term to refer to a set of test images that have been corrupted with these various corruptions. We identify two important factors that should be taken into account when building a corruption benchmark: the **balance** and the **coverage**.

In this paper, we consider that a corruption c is covered by a benchmark, when increasing the robustness of a network to all the corruptions of this benchmark, also increases the robustness of the

network to c. For instance, a benchmark that contains a motion blur corruption covers the defocus blur corruption, because the robustnesses towards these two corruptions are correlated (Vasiljevic et al., 2016). The coverage of a benchmark is defined as the number of corruptions covered by this benchmark. The more a benchmark covers a wide range of common corruptions, the more it gives a complete view of the robustness of a neural network.

At the same time, we consider a benchmark as balanced when it gives the same importance to the robustness to every corruption it contains. For instance, according to a balanced benchmark, being robust to noises is as important as being robust to brightness variations. We argue that most of the existing corruption benchmarks are unbalanced: they give too much importance to the robustness to some corruptions compared to others.

The coverage and balance of corruption benchmarks are related to the notion of **corruption overlappings**. We say that two corruptions overlap when the robustnesses of neural networks towards these corruptions are correlated. The contribution of this paper is fourfold:

1. We propose the first method to estimate to what extent two corruptions overlap.
2. We show that building corruption benchmarks with non-overlapping corruptions make them more balanced and able to cover a wider range of corruptions.
3. We propose a method to build benchmarks that contain only non-overlapping corruptions.
4. We use this method to build from ImageNet, a benchmark of Non-Overlapping Corruptions called ImagNet-NOC, to estimate the robustness of image classifiers to common corruptions. We show that ImagNet-NOC is balanced and covers corruptions that are not covered by ImageNet-C: a reference corruption benchmark (Hendrycks & Dietterich, 2019).

2 BACKGROUND AND RELATED WORKS

2.1 ESTIMATING THE ROBUSTNESS OF NETWORKS WITH OUT-OF-DISTRIBUTION SAMPLES

Studying the performances of neural networks on samples that lie outside training distributions, is a widely studied domain. Being able to understand out-of-distribution (o.o.d) samples is essential to guarantee that neural networks are reliable in real-world applications. Several benchmarks and methods have been proposed to study this field. For instance, ImageNet-A (Dan Hendrycks & Song, 2019) is a simple benchmark for ImageNet classifiers that contains samples drawn from a different source than the one used to build ImageNet. Adversarial examples, are samples that have been slightly modified to fool neural networks (Szegedy et al., 2014). Making sure that models are robust to these kinds of o.o.d samples is essential in terms of security. Artistic renditions (Hendrycks et al., 2020) or sketches (Haohan et al., 2019), can also be useful to determine if neural networks understand the abstract concepts we want them to learn. Methods to study how classifiers are affected by background changes have also been recently proposed (Beery et al., 2018; Xiao et al., 2020).

Another important aspect of the robustness of neural networks to o.o.d samples, is the robustness to common corruptions. This aspect of the robustness is generally estimated by gathering several commonly encountered corruptions, and by testing the performances of neural networks on images corrupted with these corruptions. Diverse selections of common corruptions have been proposed to make a robustness estimation (Karahan et al., 2016; Laugros et al., 2019; Geirhos et al., 2019). In particular, ImageNet-C is a popular benchmark used to measure the robustness of ImageNet classifiers (Hendrycks & Dietterich, 2019). Different common corruption benchmarks have also been proposed in the context of object detection (Claudio Michaelis, 2020), scene classification (Tadros et al., 2019) or, eye-tracking (Che et al., 2020). It is worth noting that some transformations that are in between adversarial attacks and common corruptions have been recently proposed to measure the robustness of image classifiers (Kang et al., 2019; Isaac Dunn, 2019; Liu et al., 2019).

2.2 CORRUPTION OVERLAPPINGS IN BENCHMARKS

It has been noticed that the robustness of a network to one kind of blur is largely correlated with its robustness to other kinds of blurs (Vasiljevic et al., 2016). The robustnesses to diverse kinds of noises have also been shown to be closely related (Laugros et al., 2019). Even for two corruptions that do not look similar to the human eye, increasing the robustness of a model to one of these corruptions,

can imply increasing the robustness to the other corruption (Kang et al., 2019). In general, it has been shown that the robustnesses to the corruptions that distort the high-frequency content of images are correlated (Yin et al., 2019).

In the context of adversarial examples, it is known that the robustness towards one adversarial attack can be correlated with the robustness to another attack (Tramer & Boneh, 2019). So, it is generally recommended to evaluate the adversarial robustness with attacks that are clearly different from each other (Carlini et al., 2019). The experiments carried out in this paper suggest that this recommendation should also be followed in the context of common corruption robustness estimation.

2.3 EXPERIMENTAL SET-UP

For every training of this study, we use the following parameters. The used optimizer is SGD with a momentum of 0.9. The used cost function is a cross-entropy function, with a weight decay set to 10e-4. Models are trained for 40 epochs with a batch size of 256. The initial learning rate is set to 0.1 and is divided by 10 at epoch 20 and 30.

In all the experiments we use ImageNet-100: a subset of ImageNet that contains every tenth ImageNet class by WordNetID order (Deng et al., 2009). All images are resized to the 224x224 format, and randomly horizontally flipped with a probability of 0.5 during trainings. When we use a data augmentation with a corruption in a training, half of the images of each training batch are transformed with the corruption, while the other half is not corrupted. We call standard model, the model trained without any data augmentation.

3 CORRUPTION OVERLAPPING

3.1 THE CORRUPTION OVERLAPPING SCORE

We consider that two corruptions overlap when the robustness to one of these corruptions is correlated with the robustness to the other corruption. In this section, we propose a methodology to determine to what extent two corruptions overlap.

The Robustness Score. To determine whether two corruptions overlap, we first need to introduce a metric called the robustness score. This score gives an estimation of the robustness of a model m to a corruption c. It is computed with the following formula: $R_c^m = \frac{A_c}{A_{clean}}$.

A_{clean} is the accuracy of m on an uncorrupted test set and A_c is the accuracy of m on the same test set corrupted with c. $R_c^m \in [0, 1]$, the more m is robust to c and the more R_c^m is close to 1. This metric is used in the methodology we propose to estimate the overlapping between two corruptions.

The Corruption Overlapping Score. We consider two neural networks $m1$ and $m2$ and two corruptions $c1$ and $c2$. $m1$ and $m2$ are identical, and trained with exactly the same settings except that their training sets are respectively augmented with the corruptions $c1$ and $c2$. We propose a method to measure to what extent $c1$ and $c2$ overlap. The idea of the method is to see if a data augmentation with $c1$ makes a model more robust to $c2$ and conversely. To determine this, $m1$, $m2$, and a test set are used to compute the following expression:

$$(R_{c1}^{m2} - R_{c1}^{standard}) + (R_{c2}^{m1} - R_{c2}^{standard}) \tag{1}$$

The first term of (1) measures whether $m2$ is more robust to $c1$ than a model trained without data augmentation (the standard model). Symmetrically, the second term measures whether $m1$ is more robust than the standard model to $c2$. In other words, the expression (1) estimates if increasing the robustness to $c2$ implies an increase of robustness to $c1$ and vice versa. Then, the higher (1) is, the more the robustnesses to $c1$ and $c2$ are correlated, i.e. the more $c1$ and $c2$ overlap. To be more convenient, we would like to build a corruption overlapping score equal to 1 when $c1 = c2$, and equal to 0 when the robustnesses to $c1$ and $c2$ are not correlated at all. We propose a new expression that respects both conditions:

$$O_{c_1,c_2} = \max\{0, \frac{1}{2} * \left(\frac{R_{c2}^{m1} - R_{c2}^{standard}}{R_{c2}^{m2} - R_{c2}^{standard}} + \frac{R_{c1}^{m2} - R_{c1}^{standard}}{R_{c1}^{m1} - R_{c1}^{standard}} \right)\} \tag{2}$$

The expression (2) is a normalized version of (1). It measures the overlapping between two corruptions while respecting the conditions mentioned above. Indeed, if a data augmentation with $c1$ does not increase the robustness to $c2$ at all and conversely, then the ratios in (2) are null or negative, so the whole overlapping score is maximized to zero. In other words, when $c1$ and $c2$ do not overlap at all, the overlapping score is equal to 0. Besides, when $c1 = c2$, $R_{c2}^{m1} = R_{c2}^{m2}$ and $R_{c1}^{m2} = R_{c1}^{m1}$, so both ratios of (2) are equal to 1. Then, $O_{c_1,c_2} = 1$ when $c1$ and $c2$ completely overlap.

How to compute an overlapping score. To get the overlapping score between $c1$ and $c2$, we follow the method illustrated in Figure 1. This method has six steps, and requires to have a training set, a test set and three untrained models that share the same architecture ($m1$, $m2$ and $standard$). The step (1), consists in using the corruptions $c1$ and $c2$ to get two training sets, each corrupted with one corruption. Then, the obtained corrupted sets are used to train the models $m1$ and $m2$ in step (2). The standard model is also trained during this step but only with non-corrupted samples. In step (3), similarly to step (1), we use $c1$ and $c2$ to get two corrupted versions of the test set. The accuracies of the three models on the three test sets are computed in step (4). The scores obtained are used in step (5), to get the robustness scores of each model for the corruptions $c1$ and $c2$. The results obtained are used to compute the overlapping score between $c1$ and $c2$ in step (6).

Figure 1: Methodology used to compute the overlapping score between two corruptions c_1 and c_2.

3.2 Corruption Overlapping and Coverage of Benchmarks

With our definition, a corruption c is covered by a benchmark, when increasing the robustness of a network to all the corruptions of this benchmark, also increases the robustness of the network to c. The more a benchmark covers a wide range of corruptions, the more being robust to this benchmark provides a strong guarantee about the robustness of a neural network. Then, a benchmark should cover as much common corruptions as possible.

To illustrate the notion of coverage, let us consider *bench1*, a benchmark that contains three corruptions of ImageNet-C: Gaussian noise, shot noise and impulse noise (Hendrycks & Dietterich, 2019). We also consider *bench2*, that contains the Gaussian noise, brightness and elastic corruptions of ImageNet-C. Intuitively, being robust to *bench1* implies being robust only to noises while being robust to *bench2* implies being robust to a wider range of corruptions. Then, we can suppose that *bench1* has a lower coverage than *bench2*.

When we compute the overlapping scores of these benchmarks, we observe that the overlapping between the corruptions of *bench1* are close to 1, while they are close to 0 in *bench2* (see Figure 3). The corruptions of *bench1* clearly overlap while the ones of *bench2* do not. We argue that the overlappings in benchmarks tend to reduce their coverage. Indeed, the more two corruptions c_1 and c_2 overlap, the more it is likely that a corruption covered by c_1 is also covered by c_2 and conversely. So, when two corruptions overlap, their range of covered corruptions overlap too. By reducing the overlappings in a benchmark, we separate the ranges of corruptions covered by the corruptions of this benchmark, which results in increasing its coverage. In Section 5.2, we show that we can cover the fifteen corruptions of ImageNet-C with only eight non-overlapping corruptions.

3.3 Corruption Overlapping and Balance of Benchmarks

We consider that a benchmark is balanced, when it gives the same importance to the robustness to every corruption it contains. For instance in Section 5.3, we show that the ImageNet-C benchmark gives more importance to the blur corruptions than to the corruptions that affect the brightness of images. Yet, in a real-world applications, we think that being robust to different kinds of blurs is not more valuable than being robust to lighting condition variations. Being unbalanced is in general not a desirable property, it makes benchmarks give biased estimations of neural network robustness.

Overlappings between the corruptions of a benchmark can make it unbalanced. Let us consider three corruptions c_1, c_2, and c_3 with c_1 and c_2 that completely overlap, and c_1 and c_2 that do not overlap at all with c_3. A model robust to c_3, is robust to one third of the corruptions of the benchmark. But a model robust to c_1 is also robust to c_2, because c_1 and c_2 overlap. So being robust to c_1 or c_2 implies being robust to two third of the corruptions of the benchmark. Then, this benchmark rewards more the robustness to c_1 or c_2 than the robustness to c_3: it is unbalanced. In general, if one corruption contributes more to the total overlapping of a benchmark than another corruption of this benchmark, then the benchmark is unbalanced. In Section 5.3, we show that a benchmark built with non-overlapping corruptions is more balanced than ImageNet-C.

4 Construction of a Non-Overlapping Corruption Benchmark: ImageNet-NOC

We present Algorithm 1: a general method to build benchmarks that do not contain any overlapping corruption. We argue that this method helps to build balanced benchmarks that have a large coverage.

Algorithm 1 Methodology Proposed to Build a Benchmark of Non-Overlapping Corruptions

Require: S a set of common corruptions
Require: A $train\ set$, a $test\ set$ and a neural network $architecture$
Require: An $overlapping\ threshold$: the maximum overlapping score allowed in the benchmark
    (0) $n \leftarrow 2$. n is the current number of corruptions in the benchmark. It is initialized to 2.
    (1) Use the $train\ set$, the $test\ set$ and the chosen network $architecture$ to apply the methodology presented in Section 3.1, to get all the overlapping scores between the corruptions of S.
    (2) Use these overlapping scores to retain all the combinations of n corruptions for which the overlapping scores between these n corruptions are underneath the $overlapping\ threshold$.
    (3) Run $n \leftarrow n + 1$.
    (4) Repeat steps (2) and (3) until no combination is retained in step (2).
    (5) Among all the retained combinations, retain the ones that contain the highest number of corruptions.
    (6) Among the remaining combinations, select the one with the lowest mean overlapping score to form the benchmark.

We want to use this algorithm to build a new benchmark that measures the robustness of image classifiers to common corruptions. Algorithm 1 requires to gather a large group S of commonly encountered corruptions. S should be as large as possible to traduce the diversity of common corruptions that can be encountered in real-world applications. We implement two dozens of image corruptions to constitute S, they are illustrated in Figure 2. All these corruptions are associated with a severity range. A value is randomly chosen from the severity range of the considered corruption each time an image is corrupted. The higher this value is, the more the aspect of the corrupted image changes. More information about the modeled common corruptions can be found in Appendix A.

We apply Algorithm 1, using this set of corruptions, the ImageNet $train\ set$ and $test\ set$, and the ResNet-18 $architecture$; with different values of the $overlapping\ threshold$. The corruption benchmarks obtained for different values of the threshold are shown in Appendix B. The higher the overlapping threshold is, the more the number of corruptions included in the constructed benchmarks increases, and so does the coverage of the constructed benchmarks. However, the coverage gain due to the increase of the threshold is reduced by overlappings, because overlapping corruptions tend to cover the same kind of corruptions. Besides, as explained in Section 3.3, the more there are overlappings in a benchmark, the more it is likely to be unbalanced. All in all, selecting the

Figure 2: Illustrations of the common corruptions gathered to run the Algorithm 1.

Figure 3: The overlapping scores between the corruptions of ImageNet-NOC (left) and ImageNet-C (right).

overlapping threshold, determines when the coverage gain does not worth the balance loss. Choosing this value depends on the application case and the kind of robustness estimation we want to make.

We propose to study the set of eight corruptions obtained with $overlapping\ threshold = 0.1$, which is: *rain, quantization, shear, brightness, hue, vertical_artifacts, blur* and *border*. The overlapping scores between these corruptions are displayed in Figure 3. Eight corrupted ImageNet validation sets that are corrupted each with one of the eight corruptions, are gathered to form **ImageNet-NOC**.

How to Use ImageNet-NOC. We recommend to use the CE metric (Hendrycks & Dietterich, 2019) to measure the robustness of an image classifier to an ImageNet-NOC corruption. The mean CE score computed with a benchmark is called mCE. Using the mCE metric avoids several pitfalls when measuring the robustness of neural networks. To compute a CE score, it is required to get the error rate of a pretrained AlexNet model, on the ImageNet validation set corrupted with the considered corruption. The error rates of the torchvision pretrained AlexNet computed with the corruptions introduced in this paper are displayed in Appendix A. We provide the ImageNet-NOC CE scores of some traditionally used ImageNet classifiers in Appendix C. More details about how to use ImageNet-NOC can be found by visiting [Link available upon acceptance].

5 COMPARISON BETWEEN IMAGENET-NOC AND IMAGENET-C

5.1 CORRUPTION OVERLAPPINGS IN IMAGENET-C AND IMAGENET-NOC

ImageNet-C is a benchmark commonly used to measure the robustness of ImageNet classifiers to common corruptions (Hendrycks & Dietterich, 2019). It is built on fifteen common corruptions called Gaussian noise, shot noise, impulse noise, defocus blur, glass blur, motion blur, zoom blur, snow, frost, fog, brightness, contrast, elastic, pixelate, and jpeg compression. Each corruption is associated with five severity levels that determine to what extend the corrupted images are distorted.

Using the ResNet-18 model, the ImageNet training and validation sets, we apply the method illustrated in Figure 1 to get the overlapping score of every couple of ImageNet-C corruptions. The cor-

Table 1: Upper Table: the CE scores of m_{INOC} on ImageNet-C (the lower is the better). Lower Table: the CE scores of m_{IC} on the ImageNet-NOC corruptions.

	Clean	Gauss	Shot	Impul	Defo	Glass	Motion	Zoom	Snow	Frost	Fog	Bright	Contr	Elastic	Pixel	Jpeg	mCE
standard	0.247	120	119	121	147	121	117	107	97	108	97	93	115	67	78	56	104
m_{INOC}	0.199	92	94	93	102	112	86	78	69	81	67	41	97	63	71	53	81

	Clean	Quant	Blur	Vert-Arti	Rain	**Border**	Shear	Bright	**Hue**	mCE
standard	0.247	87	122	77	71	**67**	79	117	**88**	89
m_{IC}	0.239	44	15	39	58	**79**	49	72	**117**	59

ruption severity is randomly selected for each image corrupted in the process. The obtained scores are displayed in the right array of Figure 3. We observe that all the corruptions that damage the textures in images (blurs, noises, pixelate and jpeg compression) significantly overlap. This result is consistent with the experiments carried out by Yin et al. (2019): they argue that the robustnesses of neural networks to corruptions that alter high-frequency information of images are correlated. Concerning the corruptions that alter low-frequency information of images, the overlappings are less pronounced. But we do observe some significant overlappings. There is a clear overlapping between fog and contrast or between snow and frost. As explained in Section 3.2 and 3.3, all these overlappings suggest that ImageNet-C is unbalanced and has a poor coverage. Figure 3 reveals that ImageNet-NOC contains far less overalpping corruptions than ImageNet-C.

We compute the overlapping scores of ImageNet-C and ImageNet-NOC a second time using the DenseNet-121 architecture instead of the ResNet-18 one. The results are displayed in Appendix D. The aspect of the similarity matrices obtained with the DenseNet-121 is the same as the ones obtained with the ResNet-18. Consequently, it is important to note that the overlapping scores and the architecture of the models used to compute them are largely independent.

5.2 COVERAGE OF IMAGENET-NOC AND IMAGENET-C

In this section we want to compare the coverages of ImageNet-NOC and ImageNet-C. To achieve this, we train two ResNet-18 called m_{INOC} and m_{IC}. A data augmentation procedure with all the ImageNet-C corruptions is used to train m_{IC}. Each corrupted image of this training is modified by one randomly selected corruption of ImageNet-C, with a randomly chosen severity. Similarly, m_{INOC} is trained with a data augmentation procedure with all the ImageNet-NOC corruptions. After the trainings, we measure the robustness of m_{INOC} to every corruption of ImageNet-C by computing its CE scores. We also measure the CE scores of m_{IC} towards the ImageNet-NOC corruptions. We compare the obtained scores of both models with the ones of the standard model in Table 1. The first column of this Table contains the error rates on non-corrupted ImageNet samples.

We observe that the m_{INOC} model is significantly more robust than the standard model to all the ImageNet-C corruptions. However, the m_{IC} model is not robust to some corruptions of ImageNet-NOC (*hue* and *border*). So, ImageNet-C does not cover the ImageNet-NOC corruptions while ImageNet-NOC covers all the corruptions of ImageNet-C. As argued in Section 3.2, using non-overlapping corruptions helps to build benchmarks that have a larger coverage.

5.3 BALANCE OF IMAGENET-NOC AND IMAGENET-C

We carry out an experiment to compare the balance of ImageNet-NOC and ImageNet-C. We train one ResNet-18 for each corruption of ImageNet-NOC and ImageNet-C. So, fifteen models are trained using a data augmentation procedure with one corruption of ImageNet-C, and eight others are trained with one corruption of ImageNet-NOC. Then, we estimate the robustness of the first fifteen ResNet-18 on ImageNet-C by computing their mCE scores. We also get the mCE scores of the eight remaining ResNet-18 on ImageNet-NOC. The obtained scores are displayed in Tables 2.a, 2.b. The CE scores computed to get the mCE scores can be found in Appendix E.

The mCE scores obtained in Table 2.a are very different from each other. For instance, the mCE score of the model trained with *defocus_blur*, is much lower than the one trained with *brightness*. Then, according to the robustness estimation made with ImageNet-C, one of the models is much

(2.a) The ImageNet-C mCE scores of models, each trained with one corruption of ImageNet-C.

	Gauss	Shot	Impul	Defo	Glass	Motion	Zoom	Snow	Frost	Fog	Bright	Contr	Elastic	Pixel	Jpeg
mCE	71	71	71	54	56	63	68	83	79	86	89	78	92	85	94

(2.b) The ImageNet-NOC mCE scores of models, each trained with one corruption of ImageNet-NOC.

	Quant	Blur	Vert-Arti	Rain	Border	Shear	Bright	Hue
mCE	83	79	83	83	81	90	79	88

Table 3: Comparison between the ImageNet-NOC CE scores of ANT[3x3], SIN+IN and the standard ResNet-50.

	Clean	Quant	Blur	Vert-Arti	Rain	**Border**	Shear	Bright	Hue	**mCE**
Standard	0.239	130	60	95	93	**53**	87	71	58	**81**
ANT[3x3]	0.239	85	56	80	109	**58**	76	67	55	**73**
SIN+IN	0.254	85	55	74	86	**56**	82	61	49	**68**

more robust than the other one. In other words, the ImageNet-C benchmark gives more importance to the robustness to *defocus_blur* than to the robustness to *brightness*: ImageNet-C is unbalanced.

We observe far less variations in the mCE scores in Table 2.b than in Table 2.a. More precisely, the difference between the lowest mCE and the highest mCE in Table 2.a and 2.b are respectively 40 and 11. And the standard deviation of the mCE scores in these Tables are respectively 12.1 and 3.7. Then, the importance given by ImageNet-C to the robustness of its corruptions, varies a lot with the considered corruption. This variation is way less important for our benchmark. Then, ImageNet-NOC is significantly more balanced than ImageNet-C.

5.4 Performances on ImageNet-NOC of Models Robust to ImageNet-C

We want to evaluate the performances on ImageNet-NOC of models that have been demonstrated to be robust to ImageNet-C. To achieve it, we select two models called *SIN+IN* and *ANT[3x3]*. *SIN+IN* is a ResNet-50 proposed by Geirhos et al. (2019), that is trained with a stylized version of ImageNet. *ANT[3x3]* is a ResNet-50 trained with a data augmentation strategy called Adversarial Noise Training (Evgenia Rusak, 2020). We compare in Table 3 the ImageNet-NOC CE scores of these two models with the ones of the torchvision pretrained ResNet-50.

SIN+IN and *ANT[3x3]* have been shown to be robust to Imagenet-C, yet we observe that both models are not robust to the *border* corruption. Interestingly, we show in Section 5.2, that *border* is not covered by ImageNet-C. This result confirms that ImageNet-NOC covers some aspects of the neural network robustness that are not covered by ImageNet-C.

We notice in the last column of Table 3, that *SIN+IN* is more robust than *ANT[3x3]* to ImageNet-NOC. Yet, on ImageNet-C, it is *ANT[3x3]* that reaches the better mCE score (Evgenia Rusak, 2020). This result confirms that ImageNet-NOC gives a different view on the common corruption robustness than ImageNet-C. We argue that ImageNet-NOC should be prefered to ImageNet-C because of its coverage and balance.

6 Conclusion

We proposed a metric called the corruption overlapping score, that measures to what extend the robustnesses towards two corruptions are correlated. We showed that the overlappings between the corruptions of a benchmark can reduce its coverage and make it unbalanced. We provided a benchmark of Non-Overlapping Corruptions called ImageNet-NOC to measure the robustness of image classifiers. We showed that ImageNet-NOC is balanced and covers several kinds of common corruptions that are not covered by ImageNet-C. ImageNet-NOC is built thanks to the method we proposed to construct non-overlapping corruption benchmarks. This method can be easily adapted to other computer vision tasks. We hope it will be used to build other non-overlapping corruption benchmarks, that will help to make better estimations of the robustness of neural networks.

REFERENCES

Sara Beery, Grant Van Horn, and Pietro Perona. Recognition in terra incognita. In *Proceedings of the European Conference on Computer Vision (ECCV)*, September 2018.

Nicholas Carlini, Anish Athalye, Nicolas Papernot, Wieland Brendel, Jonas Rauber, Dimitris Tsipras, Ian Goodfellow, Aleksander Madry, and Alexey Kurakin. On evaluating adversarial robustness. *arXiv preprint arXiv:1902.06705*, 2019.

Zhaohui Che, Ali Borji, Guangtao Zhai, Xiongkuo Min, Guodong Guo, and Patrick Le Callet. How is gaze influenced by image transformations? dataset and model. *Trans. Img. Proc.*, 2020. doi: 10.1109/TIP.2019.2945857.

Robert Geirhos Evgenia Rusak Oliver Bringmann Alexander S. Ecker Matthias Bethge Wieland Brendel Claudio Michaelis, Benjamin Mitzkus. Benchmarking robustness in object detection: Autonomous driving when winter is coming. *arXiv:1907.07484*, 2020.

Steven Basart JacobSteinhardt Dan Hendrycks, Kevin Zhao and Dawn Song. Natural adversarial examples. *ArXiv, abs/1907.07174*, 2019.

J. Deng, W. Dong, R. Socher, L. Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2009.

Mohit Prabhushankar Dogancan Temel, Gukyeong Kwon and Ghassan AlRegib. Cure-tsr: Challenging unreal and real environments for traffic sign recognition. *NIPS Workshop*, 2017.

Roland S. Zimmermann Julian Bitterwolf Oliver Bringmann Matthias Bethge Wieland Brendel Evgenia Rusak, Lukas Schott. A simple way to make neural networks robust against diverse image corruptions. *ECCV*, 2020.

Robert Geirhos, Patricia Rubisch, Claudio Michaelis, Matthias Bethge, Felix A. Wichmann, and Wieland Brendel. Imagenet-trained CNNs are biased towards texture; increasing shape bias improves accuracy and robustness. In *International Conference on Learning Representations*, 2019.

Wang Haohan, Songwei G, Lipton Zachary, and Xing Eric P. Learning robust global representations by penalizing local predictive power. In *Advances in Neural Information Processing Systems 32*. 2019.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *Proceedings of the International Conference on Learning Representations*, 2019.

Dan Hendrycks, Steven Basart, Norman Mu, Saurav Kadavath, Frank Wang, Evan Dorundo, Rahul Desai, Tyler Zhu, Samyak Parajuli, Mike Guo, Dawn Song, Jacob Steinhardt, and Justin Gilmer. The many faces of robustness: A critical analysis of out-of-distribution generalization. *arXiv preprint arXiv:2006.16241*, 2020.

Dan Hendrycks*, Norman Mu*, Ekin Dogus Cubuk, Barret Zoph, Justin Gilmer, and Balaji Lakshminarayanan. Augmix: A simple method to improve robustness and uncertainty under data shift. In *International Conference on Learning Representations*, 2020.

Hadrien Pouget Daniel Kroening Tom Melham Isaac Dunn, Laura Hanu. Investigating distributional robustness: Semantic perturbations using generative models. *ECCV Workshop on Adversarial Robustness in the Real World*, 2019.

Daniel Kang, Yi Sun, Dan Hendrycks, Tom Brown, and Jacob Steinhardt. Testing robustness against unforeseen adversaries. *arXiv preprint arXiv:1908.08016*, 2019.

S. Karahan, M. Kilinc Yildirum, K. Kirtac, F. S. Rende, G. Butun, and H. K. Ekenel. How image degradations affect deep cnn-based face recognition? In *2016 International Conference of the Biometrics Special Interest Group (BIOSIG)*, pp. 1–5, Sep. 2016.

Micha Koziarski and Boguslaw Cyganek. Image recognition with deep neural networks in presence of noise dealing with and taking advantage of distortions. *Integrated Computer-Aided Engineering*, 24:1–13, 08 2017.

Alfred Laugros, Alice Caplier, and Matthieu Ospici. Are adversarial robustness and common perturbation robustness independant attributes ? In *The IEEE International Conference on Computer Vision (ICCV) Workshops*, Oct 2019.

Hsueh-Ti Derek Liu, Michael Tao, Chun-Liang Li, Derek Nowrouzezahrai, and Alec Jacobson. Beyond pixel norm-balls: Parametric adversaries using an analytically differentiable renderer. In *International Conference on Learning Representations*, 2019.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *International Conference on Learning Representations*, 2014.

Timothy Tadros, Nicholas C. Cullen, Michelle R. Greene, and Emily A. Cooper. Assessing neural network scene classification from degraded images. *ACM Trans. Appl. Percept.*, 2019. ISSN 1544-3558. doi: 10.1145/3342349.

Florian Tramer and Dan Boneh. Adversarial training and robustness for multiple perturbations. In *Advances in Neural Information Processing Systems 32*. Curran Associates, Inc., 2019.

Igor Vasiljevic, Ayan Chakrabarti, and Gregory Shakhnarovich. Examining the impact of blur on recognition by convolutional networks. *arXiv preprintarXiv:1611.05760*, 2016.

Kai Xiao, Logan Engstrom, Andrew Ilyas, and Aleksander Madry. Noise or signal: The role of image backgrounds in object recognition. *ArXiv preprint arXiv:2006.09994*, 2020.

Dong Yin, Raphael Gontijo Lopes, Jonathon Shlens, Ekin D. Cubuk, and Justin Gilmer. A fourier perspective on model robustness in computer vision. *ICML Workshop on Uncertainty and Robustness in Deep Learning*, 2019.

A   PRESENTATION OF THE MODELED COMMON CORRUPTIONS

The common corruptions gathered in Section 4 are implemented with computationally cheap image transformations that can be easily added in an image pipeline. We provide in Figures 5 and 6, information about how the common corruptions used in this study are modeled. These corruptions are implemented for images that have pixel values in [0-1].

The *Severity Range* column of these arrays precises how the severity of each corruption is set. The lower bound of each severity range is selected to get a robustness score of 0.95 with the standard ResNet-18 model, tested on the ImageNet validation set that has been altered with the considered corruption. The upper bound is selected to get a robustness score of 0.5 in the same conditions. The upper bounds of the *hue* and *gray_scale* corruptions are different because these corruptions are not harmful enough to reach a robustness score of 0.5. They respectively reach a robustness score of 0.63 and 0.70 for the standard ResNet-18. The last column of the Figures 5 and 6 corresponds to the error rate of the torchvision pretrained AlexNet on the ImageNet validation set corrupted with the corruption indicated in the first column.

In Section 4, by completing the step (1) of Algorithm 1, we compute the overlapping scores between the corruptions gathered in Figure 2. These overlapping scores are displayed in Figure 4.

Figure 4: Overlapping scores between all the common corruptions displayed in Figure 2,

Corruption Name	Illustration	Description	Severity Range	AlexNet Error Rate
Quantization		Quantize the pixel values into a few quantization levels	Number of levels: 4 to 9	0.592
Gaussian Noise		Add zero mean Gaussian noise to the image	Standard deviation: 0.05 to 0.18	0.620
Salt Pepper Noise		Add salt-pepper noise in the image	Propability of each pixel to be changed: 0.003 to 0.032	0.649
Blur		Interpolate the image with its equivalent blured with five convolution with a 3x3 filter. The filter is filled is the value 1.	Interpolation factor associated to the blured image: 0.4 to 0.95	0.570
Thumbnail Resize		Apply a bilinear interpolation twice. Firstly to reduce the size of the image. Secondly to get back to its original size.	Reduction factor: 1.1 to 3.25	0.574
Pixelate		Convolve the image with a mean pooling filter	Size of the filter and padding used: 2 to 4	0.760
Artifacts		Add artifacts into the image. The artifacts are made with a small dotted lines	Number of artifacts: 15 to 170	0.746
Vertical Artifacts		The same corruption than Artifacts except that the artifacts are rotated by 90 degrees	Number of artifacts: 15 to 180	0.758
Rhombus		Several randomly selected 7x7 rhombus like areas are each filled with a unique pixel value	Number of rhombus: 9 to 76	0.728
Rain		Randomly select circle areas (7 radius circles). For these areas, add 1 to the pixel values and divide the result by 2	Number of circles: 12 to 120	0.748
Circles		Several randomly selected circle areas (7 radius circles) are each filled with a unique pixel value	Number of circles: 7 to 50	0.720
Obstruction		One randomly chosen square area is filled with a unique pixel value	Size of the square 47 to 125	0.597

Figure 5: Presentation of half of the group of common corruptions displayed in Figure 2. The other half is presented in Figure 6.

Corruption Name	Illustration	Description	Severity Range	AlexNet Error Rate
Border		Fill the border of images with a unique pixel value	Thickness of the corrupted area: 9 to 46 pixels	0.670
Translation		One horizontal and one vertical translation	Number of pixels translated for both translations: 15 to 62	0.603
Shear		Horizontal Shear	Maximum pixel translation due to the shear: 0.39	0.657
Elastic		Crop the height or the width of the image. The image is then resized to its original size	Number of cropped pixel: 44 to 110	0.541
Rotation		Clockwise or anticlockwise rotation	Degree of the rotation: 7 to 50	0.711
Backlight		Split the image into two areas and select a value. Add this value to all pixel of one of the area and substract the value for the other.	Value added or subtracted: 0.11 to 0.44	0.591
Brightness		Select a unique value. Add this value or substract it to all the pixel value of the image	Value added or subtracted: 0.16 to 0.51	0.577
Contrast		Reduce the contrast of images	Contrast reduction factor: 0.33 to 0.74	0.576
Color Distortion		Add a unique value to all pixels of one of the RGB channel	Value added: 0.09 to 0.40	0.606
Gray Scale		Interpolate the image with its gray scale version	Interpolation factor associated with the gray scale image: 0.49 to 1	0.580
Hue		Shift cyclically the value of the pixels of the channel H in the HSV format	Value of the shifting: 0.05 to 0.5	0.684

Figure 6: Presentation of half of the group of common corruptions displayed in Figure 2. The other half is presented in Figure 5.

B BENCHMARKS OBTAINED FOR DIFFERENT VALUES OF THE OVERLAPPING THRESHOLD

Figure 7: Benchmarks obtained when running Algorithm 1, for different values of the overlapping threshold. The third column contains the overlapping scores between the corruptions of the benchmarks.

C   PERFORMANCES OF VARIOUS MODELS ON IMAGENET-NOC

Table 4: ImageNet-NOC CE scores obtained with several pretrained torchvision classifiers.

	Clean	Quant	Blur	Vert-Arti	Rain	Border	Shear	Bright	Hue	mCE
AlexNet	43.5	100	100	100	100	100	100	100	100	100
SqueezeNet	41.8	143	97	109	111	93	99	109	86	106
VGG-11	31.0	193	90	156	94	70	107	92	77	110
VGG-19-BN	25.8	175	70	113	77	55	91	71	53	88
ResNet-18	30.2	128	68	103	84	69	92	80	64	86
ResNet-50	23.9	130	60	95	93	53	87	71	58	81
DenseNet-121	25.3	101	58	98	89	55	72	57	54	73
DenseNet-201	22.8	89	54	86	84	49	69	52	50	66

D   OVERLAPPINGS OBTAINED FOR TWO DIFFERENT ARCHITECTURES

Figure 8: The corruption overlapping scores in ImageNet-C computed with the ResNet-18 (left) and DenseNet-121 (right) architectures.

Figure 9: The corruption overlapping scores in ImageNet-NOC computed with the ResNet-18 (left) and DenseNet-121 (right) architectures.

E CE SCORES OF MODELS TRAINED WITH A DATA AUGMENTATION WITH AN IMAGENET-C CORRUPTION

We provide in Table 5 and 6, the CE scores computed and averaged to get the mCE scores of Tables 2.a and 2.b. The first column of these arrays contains the error rate on the non-corrupted ImageNet validation set.

Table 5: CE scores computed with models trained with a data augmentation with one corruption of ImageNet-C. Each line refers to one model trained with one corruption of ImageNet-C and each column refers to one corruption of ImageNet-C.

	Clean	Gauss	Shot	Impul	Defo	Glass	Motion	Zoom	Snow	Frost	Fog	Bright	Contr	Elastic	Pixel	Jpeg	mCE
Standard	0.247	121	119	122	147	121	118	107	97	109	98	94	116	68	79	56	104
Gauss	0.264	6.0	9	8	122	88	100	95	87	93	125	107	129	58	19	15	71
Shot	0.269	10	6	9	125	92	102	96	84	94	126	103	128	59	20	16	71
Impul	0.272	10	11	4	123	88	99	96	91	93	127	102	129	54	17	14	71
Defo	0.300	62	62	63	6	25	36	34	76	77	82	91	93	46	2	50	54
Glass	0.287	74	73	74	24	8	32	30	81	81	83	95	99	34	2	55	56
Motion	0.263	92	92	92	55	41	6	26	76	94	73	97	93	42	10	53	63
Zoom	0.254	98	98	99	60	50	31	6	88	97	77	101	98	45	24	51	68
Snow	0.263	114	113	118	115	91	87	87	5	74	97	84	117	54	40	52	83
Frost	0.259	109	111	112	118	87	99	89	40	9	69	60	108	57	28	84	79
Fog	0.254	117	116	118	136	115	100	86	76	79	2	58	57	73	88	72	86
Bright	0.235	108	111	110	142	113	112	104	86	88	75	7	100	72	60	55	89
Contr	0.282	96	98	100	131	103	97	87	82	76	50	72	2	66	53	50	78
Elastic	0.200	124	122	125	127	92	91	72	92	110	98	104	118	19	22	61	92
Pixel	0.251	99	98	102	129	87	96	93	93	95	90	86	108	53	5	42	85
Jpeg	0.256	86	86	88	143	110	118	113	98	102	120	101	129	66	32	11	94

Table 6: CE scores computed with models trained with a data augmentation with one corruption of ImageNet-NOC. Each line refers to one model trained with one corruption of ImageNet-NOC and each column refers to one corruption of ImageNet-NOC.

	Clean	Quant	Blur	Vert-Arti	Rain	Border	Shear	Bright	Hue	mCE
standard	0.247	87	122	77	71	67	79	117	88	89
Quant	0.237	9	125	77	90	70	90	124	80	83
Blur	0.251	79	7	61	72	82	90	132	106	79
Vert-Arti	0.242	79	133	4	63	80	84	119	104	83
Rain	0.231	86	131	78	2	73	82	115	97	83
Border	0.241	89	123	71	73	8	74	118	89	81
Shear	0.234	129	127	65	85	75	6	133	102	90
Bright	0.236	75	125	78	77	73	92	21	89	79
Hue	0.261	83	139	91	96	74	101	116	1	88