SELF-SUPERVISED CONTINUAL LEARNING

ABSTRACT

This paper proposes *Self-Supervised Continual Learning (SCL)* for regularization-based class incremental learning. In SCL, the novel pretext task utilizes randomly-transformed labels without depending on data-augmented transforms. *SCL* trained with a novel incremental task-regularizer with the orthogonal weight modifications backbone shows promising performance on different datasets.

1 INTRODUCTION

Humans have an unparalleled capacity to incrementally apprehend newer tasks in their daily lives without forgetting the skills gained in the past. Though deep learning architectures show plasticity towards learning new tasks, unlike humans, they suffer from catastrophic forgetting McCloskey & Cohen (1989); Ratcliff (1990); McClelland et al. (1995); French (1999). To address this in a Class Incremental Learning (CIL) setting, we propose a self-supervision-based approach, termed as Self-Supervised Continual Learning (SCL) that is computationally efficient, easy to deploy, and maintains plasticity without additional memory reserves. By utilizing limited data available at each incremental task, we employ self-supervised pretraining termed as *Random Label Augmentation (RLA)* to extract a diverse set of features. The RLA pretext task synthesizes information from different parts of an image using randomly generated labels in a multi-task setting, thereby providing rich and diverse features to the model (Refer Figure 1). Further, we employ a task-wise regularizer that prevents information loss during weight sharing between the pretext and downstream tasks. The downstream training utilizes the *Orthogonal Weight Modifications (OWM) Zeng et al. (2019)* to mitigate catastrophic forgetting.

2 METHODOLOGY

Figure 1 illustrates the pretext and downstream training framework for a single incremental task t. The pretext and downstream training is performed iteratively for each incremental task $t \in [1, T]$.

Self-Supervised Pre-Training: In Self-Supervised Learning (SSL), the input images are generally augmented during pretext training, which is computationally inefficient. Consequently, we propose *Random Label Augmentation (RLA)*, based on augmenting the makeshift targets instead of images. These labels are randomly generated for M tasks, each with k classes. The training is performed in a multi-task fashion with different fully-connected layers for each M tasks. The major advantage of *RLA* over the existing approaches (for eg. rotation pretext Komodakis & Gidaris (2018)) is that the training time and computational resource usage do not dramatically rise owing to an increase in the amount of augmented data (such as $4\times$ in the case of rotation pretext). Self-supervised pre-training in CIL setting is integrated by training the network for a pretext task p at each incremental task t using images available for that task. During each $t \in [1, T]$, we define a pretext model with parameters (ω_p^t, ψ_p^t) and downstream model with parameters $(\omega_d{}^t, \phi_d{}^t)$ for feature extraction and classification, respectively. Weights ω_p^t are transferred to the downstream task d for t. M

Figure 1: Illustration of the proposed pretext and the downstream task for an incremental task t.

| Methods | Split-CIFAR10 | Split-CIFAR100 | | | Split-SVHN |
	5 tasks	2 tasks	5 tasks	10 tasks	5 tasks
Finetuning	18.81 ± 0.59	28.43 ± 1.08	12.34 ± 0.62	9.56 ± 0.55	7.58 ± 0.57
OWM Zeng et al. (2019)	55.71 ± 0.49	40.30 ± 0.65	33.17 ± 0.79	29.86 ± 0.33	73.50 ± 0.81
MUC* Liu et al. (2020)	-	33.86 ± 0.72	28.05 ± 1.22	22.07 ± 0.90	-
IL2A* Zhu et al. (2021)	-	43.29 ± 0.43	32.63 ± 0.86	21.45 ± 0.67	-
SSRE* Zhu et al. (2022)	-	41.06 ± 0.87	$\mathbf{36.82 \pm 0.70}$	$\mathbf{31.35 \pm 1.0}$	-
SCL (w/o RLA) (Ours)	58.48 ± 0.18	42.97 ± 0.31	32.40 ± 0.48	29.81 ± 1.10	74.25 ± 0.34
SCL (Ours)	$\mathbf{59.02 \pm 0.09}$	$\mathbf{43.69 \pm 0.29}$	$\underline{33.77 \pm 0.26}$	30.52 ± 0.72	$\mathbf{74.94 \pm 0.27}$

Table 1: Average test accuracy for the proposed method. The best performance is depicted by **bold** and the second best by underline. * depicts that the results for algorithms were computed with the paper's official code repository using the protocols described in this paper.

branches of the pretext training are added to the network corresponding to each of the M tasks. This model is trained as a multi-task learning network where meaningful representations are extracted and for each of the M tasks, and ψ_p^t are trained with the cumulative loss incurred from all the tasks. We minimize the cross-entropy loss function in the multi-task fashion between the target vector of randomly generated labels and the predicted vector. In the CIL setting, the model usually learns discriminative features from images that are required for the current incremental task t. These features are not discriminative enough as more tasks are introduced to the model. Pre-training the model with unlabeled data drives the model to extract more and more meaningful information from each input. Thus, the proposed pretext task aims at learning generalized diverse features from the limited data, henceforth saving training time and computational resources. After pre-training, weights (ω_p^t, ψ_p^t) for t, weights ω_p^t are transferred to the downstream model for (ω_d^t, ϕ_d^t).

Downstream Training in Class-Incremental Setting: The downstream task in a CIL setting involves learning weights (ω_d^t, ϕ_d^t) of the downstream model for each incremental task t. This is the point where the catastrophic forgetting begins to manifest. To address this, we propose an incremental-task regularizer coupled with the *Orthogonal Weight Modification* Zeng et al. (2019) backbone. In practical instances, the dataset associated with the new incremental task t may belong to an entirely different distribution. Training the existing model on this new, out-of-distribution dataset may lead to excessive modification of ω_p^t and ω_d^t. Consequently, the final model may fail to generalize on the old incremental tasks $t_{1:t-1}$. To prevent forgetting at each incremental step, we incorporate a regularization term in the calculated loss, ensuring that the weights are not drastically modified after each pre-training and downstream classification cycle. We add weight regularization as $R(\omega_p^t) = \frac{\alpha}{2} \left\| \omega_p^t - \omega_d^{t-1} \right\|_2^2 + \frac{\beta}{2} \left\| \omega_p^t \right\|_2^2$ between ω_d^{t-1} of the task $t-1$ and ω_p^t of the current task t to mitigate forgetting at this step. The regularizer $R(.)$ is minimized with α and β as hyperparameters. α aggravates the loss, forcing the model not to deviate much from the model trained on the previous task and β handles the induced sparsity on the model.

3 RESULTS

We evaluate the proposed algorithm on split-CIFAR10, split-CIFAR100, and split-SVHN datasets. Table 1 illustrates the efficacy of the proposed algorithm when compared with the existing state-of-the-art regularization-based CIL algorithms. We observe that the SCL algorithm outperforms the existing algorithms on split-CIFAR10 and split-SVHN datasets for 5 tasks. For the split-CIFAR100 dataset, SCL achieves state-of-the-performance for 2 tasks and achieves competitive performance for 5 and 10 tasks. For ablation experiments, we test the performance by fine-tuning for each incremental task and observe that the model can retain the information from only the last incremental task T only. Further, the task-regularizer with OWM backbone is added to the framework, which achieves state-of-the-art performance on split-CIFAR10 and split-SVHN datasets. To validate the contribution of RLA in the pipeline, the proposed RLA is replaced with popular SSL pretext tasks, and the performance reported in Table 2 (appendix) highlights the efficacy of RLA.

4 CONCLUSION

We introduce the novel idea of utilizing self-supervised learning for regularization-based class incremental learning, that is data and compute efficient. With this work, we also aim to attract researchers toward the potential of label transformations instead of conventional data augmentation for unsupervised learning.

URM STATEMENT

The authors acknowledge that at least one key author of this work meets the URM criteria of ICLR 2023 Tiny Papers Track.

REFERENCES

Robert M French. Catastrophic forgetting in connectionist networks. *Trends in cognitive sciences*, 3(4):128–135, 1999.

Wenpeng Hu, Zhou Lin, Bing Liu, Chongyang Tao, Zhengwei Tao, Jinwen Ma, Dongyan Zhao, and Rui Yan. Overcoming catastrophic forgetting for continual learning via model adaptation. In *International conference on learning representations*, 2018.

Nikos Komodakis and Spyros Gidaris. Unsupervised representation learning by predicting image rotations. In *International conference on learning representations (ICLR)*, 2018.

Alex Krizhevsky. Learning multiple layers of features from tiny images. pp. 32–33, 2009. URL https://www.cs.toronto.edu/~kriz/learning-features-2009-TR.pdf.

Gustav Larsson, Michael Maire, and Gregory Shakhnarovich. Colorization as a proxy task for visual understanding. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 6874–6883, 2017.

Yu Liu, Sarah Parisot, Gregory Slabaugh, Xu Jia, Ales Leonardis, and Tinne Tuytelaars. More classifiers, less forgetting: A generic multi-classifier paradigm for incremental learning. In *Computer Vision–ECCV 2020: 16th European Conference, Glasgow, UK, August 23–28, 2020, Proceedings, Part XXVI 16*, pp. 699–716. Springer, 2020.

James L McClelland, Bruce L McNaughton, and Randall C O'Reilly. Why there are complementary learning systems in the hippocampus and neocortex: insights from the successes and failures of connectionist models of learning and memory. *Psychological review*, 102(3):419, 1995.

Michael McCloskey and Neal J Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. In *Psychology of learning and motivation*, volume 24, pp. 109–165. Elsevier, 1989.

Roger Ratcliff. Connectionist models of recognition memory: constraints imposed by learning and forgetting functions. *Psychological review*, 97(2):285, 1990.

Guanxiong Zeng, Yang Chen, Bo Cui, and Shan Yu. Continual learning of context-dependent processing in neural networks. *Nature Machine Intelligence*, 1(8):364–372, 2019.

Fei Zhu, Zhen Cheng, Xu-Yao Zhang, and Cheng-lin Liu. Class-incremental learning via dual augmentation. *Advances in Neural Information Processing Systems*, 34:14306–14318, 2021.

Kai Zhu, Wei Zhai, Yang Cao, Jiebo Luo, and Zheng-Jun Zha. Self-sustaining representation expansion for non-exemplar class-incremental learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9296–9305, 2022.

A   EXPERIMENTAL SETTINGS

The proposed algorithm is evaluated on three datasets: split-CIFAR10, split-CIFAR100, and split-SVHN. We report the *average test accuracy*, which is defined as the average of test accuracies achieved across all tasks. All experiments are performed using *five seeds*.

A.1   DATASETS AND PROTOCOL:

The training and evaluation are performed in a class-incremental setting following the standard protocols defined in the works of Zeng et al. Zeng et al. (2019) and Hu et al. Hu et al. (2018) on split-CIFAR10 Krizhevsky (2009), split-CIFAR100 Krizhevsky (2009), and split-SVHN datasets. The split-CIFAR10 and split-SVHN datasets are used for evaluation on 2 classes per task, and split-CIFAR100 is used for training and evaluation on 10, 20, and 50 classes per task.

Pretext Task	Average Accuracy (%)	
	split-CIFAR10	split-SVHN
Rotation Komodakis & Gidaris (2018)	56.70 ± 0.52	73.79 ± 0.31
Colorization Larsson et al. (2017)	55.82 ± 0.48	73.03 ± 0.33
RLA (proposed)	$\mathbf{59.02 \pm 0.09}$	$\mathbf{74.94 \pm 0.27}$

Table 2: Performance of the proposed algorithm by replacing the proposed Random Label Augmentation (RLA) task with Rotation and Image Colorization pretext tasks on the split-CIFAR10 and split-SVHN datasets for 5 incremental tasks.

A.2   COMPARISON ALGORITHMS:

The results of the proposed algorithm are compared with various benchmark algorithms in the domain of regularization-based CIL- (1) OWM Zeng et al. (2019), (2) MUC Liu et al. (2020), (3) IL2A Zhu et al. (2021), and (4) SSRE Zhu et al. (2022). The baselines are run using the original open-source codes with the same network architecture as the one used in the proposed SCL. The details of this network are described in Section A.3.

A.3   IMPLEMENTATION DETAILS

For all experiments, we use a 3-layer CNN network consisting of three fully-connected layers. The network architecture is consistent with the one employed in work from Zeng et al. (2019). In our experiments, we train the model using randomly generated labels for three tasks ($M = 3$), each of which has two classes ($k = 2$). The extracted features are utilized by three separate classification heads, each of which has two fully-connected layers. All training is performed using the Stochastic Gradient Descent (SGD) optimizer for 50 epochs with the learning rate set to 0.001. The hyperparameters $alpha$ and $beta$ have been set to the values 10 and 18 for the split-CIFAR10 dataset and the split-CIFAR100 dataset, respectively, while for the split-SVHN datasets, these values are 5 and 12. All of the experiments are carried out on five seeds, and the results are reported as the overall average, along with the standard deviation for all of the seeds. The algorithm is implemented in Pytorch.