BOIL: Towards Representation Change for Few-shot Learning

Abstract

Model Agnostic Meta-Learning (MAML) is one of the most representative gradient-based meta-learning algorithms. MAML learns new tasks with a few data samples with inner updates from a meta-initialization point and learns the meta-initialization parameters with outer updates. It has recently been hypothesized that *representation reuse*, which makes little change in efficient representations, is the dominant factor in the performance of the meta-initialized model through MAML rather than *representation change*, which makes a significant change in representations. In this work, we investigate the necessity of *representation change* for the ultimate goal of few-shot learning, which is solving domain-agnostic tasks. To this aim, we propose a novel meta-learning algorithm, coined as *BOIL* (Body Only update in Inner Loop), that updates only the body (extractor) of the model and freezes the head (classifier) of the model during inner loop updates. BOIL leverages *representation change*, not *representation reuse*. The frozen head cannot be better than even a random guessing classifier at the initial point of new tasks, and feature vectors (representations) have to move quickly to their corresponding frozen head vectors. We visualize this property using cosine similarity, CKA, and empirical results without the head. Although the inner loop updates purely hinge on *representation change*, BOIL empirically shows significant performance improvement over MAML, especially on cross-domain tasks. The results imply that *representation change* in gradient-based meta-learning approaches is a critical component.

1 Introduction

Meta-learning, also known as "learning to learn," is the methodology that imitates human intelligence that can adapt quickly with even a small amount of previously unseen data using previous learning experiences. To this aim, meta-learning with deep neural networks have mainly been studied with metric- and gradient-based approaches. Metric-based meta-learning (Koch, 2015; Vinyals et al., 2016; Snell et al., 2017; Sung et al., 2018) compares the distance between feature embeddings using models as a mapping function of data into an embedding space, whereas gradient-based meta-learning (Ravi & Larochelle, 2016; Finn et al., 2017; Nichol et al., 2018) learns the parameters quickly to be optimized when the models encounter new tasks.

Model-agnostic meta-learning (MAML) (Finn et al., 2017) is the most representative gradient-based meta-learning algorithm. MAML algorithm consists of two optimization loops: inner loop and outer loop. The inner loop learns task-specific knowledge, and the outer loop finds a universally good meta-initialized parameter so that the inner loop can quickly learn any task from the initial point with few examples. This algorithm has been highly influential to the research field of meta-learning, and numerous follow-up studies have been conducted (Oreshkin et al., 2018; Rusu et al., 2018; Zintgraf et al., 2018; Yoon et al., 2018; Finn et al., 2018; Triantafillou et al., 2019; Sun et al., 2019; Na et al., 2019; Tseng et al., 2020).

Very recent studies (Raghu et al., 2020; Arnold et al., 2019) attributed the success of MAML to high-quality features prior to the inner updates from the meta-initialized parameters. For instance, Raghu et al. (2020) claimed that MAML learns new tasks by updating the head (the last fully connected layer) with almost the same features (the output of the penultimate layer) from the meta-initialized network. In this paper, we categorize the learning patterns as follows: a small change in the representations during the task learning is named *representation reuse*, whereas a big change is named *representation change*.[1] Then, *representation reuse* was the common belief of MAML.

---

[1] *representation reuse* and *representation change* in our paper correspond to *feature reuse* and *rapid learning* in (Raghu et al., 2020), respectively. To prevent confusion caused by terminology, we re-express the terms.

(a) MAML/ANIL.   (b) BOIL.

Figure 1: **Difference in task-specific (inner) updates between MAML/ANIL and BOIL**. In the figure, the lines mean the decision boundaries defined by the head (classifier) of the network. The different shapes and colors mean different classes. (a) MAML updates mainly head with negligible change in body (extractor), hence representations on the feature space are almost identical. ANIL does not change in body during inner updates, hence those are identical. Whereas, (b) BOIL updates body only without change in head during inner updates, hence representations on the feature space change significantly with the fixed decision boundaries. We visualize the representations from various data sets using UMAP (Uniform Manifold Approximation and Projection for dimension reduction) (McInnes et al., 2018) in Appendix B.

Herein, we pose an intriguing question: *Is representation reuse is enough for meta-learning?* We believe the key of successful meta-learning is closer to *representation change* than *representation reuse*. More importantly, *representation change* is crucial for cross-domain adaptation, considered as the ultimate goal of meta-learning. On the contrary, the MAML accomplished with *representation reuse* might be trained poorly for cross-domain adaptation, since the success of *representation reuse* might heavily rely on the similarity between the source and the target domains.

To answer this question, we propose a novel meta-learning algorithm that leverages *representation change*. Our contributions are summarized as follows:

- We put emphasis on the necessity of *representation change* for meta-learning via cross-domain adaptation experiments.
- We propose a simple but effective meta-learning algorithm that *learns the Body (extractor) of the model Only in the Inner Loop*, coined as BOIL. We empirically show that BOIL improves the performance over all benchmark data sets and that this improvement is particularly noticeable on fine-grained data sets or cross-domain adaptation.
- We interpret the connection BOIL and the algorithm using preconditioning gradients (Flennerhag et al., 2020) and show compatibility, improving performance.
- We demonstrate that the BOIL algorithm enjoys *representation reuse* on the low-/mid-level body and *representation change* on the high-level body using the cosine similarity and the Centered Kernel Alignment (CKA). We visualize the features between before and after adaptation, and empirically analyze the effectiveness of the body of BOIL with ablation study of eliminating head.
- For ResNet architectures, we propose a disconnection trick that removes the backpropagation path of the last skip connection. The disconnection trick strengthens *representation change* on the high-level body.

2   PROBLEM SETTING

2.1   META-LEARNING FRAMEWORK (MAML)

The MAML(Model-agnostic Meta-learning) algorithm (Finn et al., 2017) attempts to meta-learn the best initialization of parameters for a task-learner. It consists of two main optimization loops, i.e., the inner loop and the outer loop. We first sample a batch of tasks within a data set distribution. Each task τ_i consists of a support set S_{τ_i} and a query set Q_{τ_i}. When we sample a support set for each task, we first sample n labels from the label set and then sample k instances for each label, and thus each support set contains $n \times k$ instances. For a query set, we sample instances from the same labels with the support set.

With these composed tasks, the MAML algorithm performs meta-training and meta-testing. During meta-training, we first sample a meta-batch consisting of B tasks from the meta-training data set. In the *inner loops*, we update the meta-initialized parameters θ to task-specific parameters θ_{τ_i} using the *task-specfic* loss $L_{S_{\tau_i}}(f_\theta)$ as follows:[2]

$$\theta_{\tau_i} = \theta - \alpha \nabla_\theta L_{S_{\tau_i}}(f_\theta) \tag{1}$$

---

[2]Although the inner loop(s) can be applied in one or more steps, for the sake of simplicity, we consider only the case of a single inner loop.

Using the query set of the corresponding task, we compute the loss $L_{Q_{\tau_i}}(f_{\theta_{\tau_i}})$ based on each inner updated parameter. By summing all these losses, the *meta-loss* of each meta-batch, $L_{meta}(\theta)$, is computed. The meta-initialized parameters are then updated using the meta-loss in the *outer loop* through a gradient descent.

$$\theta' = \theta - \beta\nabla_\theta L_{meta}(\theta), \text{ where } L_{meta}(\theta) = \sum_{i=1}^{B} L_{Q_{\tau_i}}(f_{\theta_{\tau_i}}) \tag{2}$$

In meta-testing, the inner loop, which can be interpreted as task-specific learning, is the same as in meta-training. However, the outer loop only computes the accuracy using a query set of tasks and does not perform a gradient descent, and thus it does not update the meta-initialization parameters.

2.2 EXPERIMENTAL SETUP

We used two backbone networks, **4conv network** with 64 channels from Vinyals et al. (2016) and **ResNet-12** starting with 64 channels and doubling them after every block from Oreshkin et al. (2018). For the batch normalization layers, we used batch statistics instead of the running statistics during meta-testing, following the original MAML (Finn et al., 2017). We trained all models 30,000 epochs and then used *the model with the best accuracy on meta-validation data set* to verify performance. We applied an inner update *once* both meta-training and meta-testing. The outer learning rate is set to 0.001 and the inner learning rate is set to 0.5 for all the baselines and our models. All results were reproduced by our group and reported as the average and standard deviation of the accuracies over 5 × 1,000 tasks and the values in parenthesis in the algorithm name column of tables are the number of shots. We validated both MAML/ANIL and BOIL on two general data sets, **miniImageNet** (Vinyals et al., 2016) and **tieredImageNet** (Ren et al., 2018), and two specific data sets, **Cars** (Krause et al., 2013) and **CUB** (Welinder et al., 2010). Note that our algorithm is not for the state-of-the-art performance, but for the proposal of the new learning scheme for meta-learning. Full details on the implementation and data sets are described in Appendix A.[3] In addition, the results of the other data sets at a size of 32 × 32 and the 4conv network with 32 channels from Finn et al. (2017) (i.e., original setting) are reported in Appendix C and Appendix E, respectively.

3 BOIL (BODY ONLY UPDATE IN INNER LOOP)

3.1 THE ULTIMATE GOAL OF META-LEARNING: DOMAIN-AGNOSTIC ADAPTATION

Recently, Raghu et al. (2020) proposed two opposite hypotheses, *representation reuse* and *representation change*, and demonstrated that *representation reuse* is the dominant factor of MAML. We can discriminate two hypotheses according to which part of the neural network, body or head, is mostly updated through the inner loop. Here, the body indicates all the convolutional layers, and the head indicates the remaining fully connected layer. In a word, the *representation change* hypothesis attributes the capability of MAML to the updates on the body, while the *representation reuse* hypothesis considers that the network's body is already universal to various tasks before inner loops. To demonstrate the *representation reuse* hypothesis of MAML, they proposed the ANIL (Almost No Inner Loop) algorithm, which only updates the head in the inner loops during training and testing, and showed that ANIL has comparable performance to MAML. It implies that the representation trained by MAML/ANIL, even before updated task-specifically, is sufficient to achieve the desired performance. Furthermore, they proposed the NIL-testing (No Inner Loop) algorithm, which removes the head and performs unseen tasks only using the distance between the representations of a support set and those of a query set during testing to identify the capability of *representation reuse*. NIL-testing of MAML also has comparable performance to MAML. Based on these results, it was claimed that the success of MAML is attributed to *representation reuse*.

Here, we investigate the necessity of *representation change*. We believe that the meta-trained models should have good performances in many other domains, referred to as *domain-agnostic adaptation* in this paper. To this end, *representation reuse* is not appropriate since *representation reuse* uses the similarity between the source and target domains. The higher the similarity is, the higher the efficiency. Therefore, when there are no strong similarities between the source and the target domains, good representations for the source domain could be imperfect representations for the target domain. Table 2, our experimental results on cross-domain tasks, shows that the MAML enjoying *representation reuse* is worse than BOIL leveraging *representation change*, which will be discussed in details from the next section.

---

[3]All implementations except for WarpGrad are based on Torchmeta (Deleu et al., 2019), and all results were reproduced according to our details.

3.2 BOIL ALGORITHM

Inspired by the necessity, we design an algorithm that updates only the body of the model and freezes the head of the model during the task learning to enforce *representation change* via inner updates. Because the gradients must be back-propagated to update the body, we set the learning rate of the head to zero in inner updates during both meta-training and meta-testing. Otherwise, learning and evaluation procedures of BOIL are the same as those of MAML. Therefore, the computational overhead does not change.

Formally speaking, with the notations used in Section 2.1, the meta-initialized parameters θ can be separated into body parameters θ_b and head parameters θ_h, i.e., $\theta = \{\theta_b, \theta_h\}$. For a sample image $x \in \mathbb{R}^i$, an output can be expressed as $\hat{y} = f_\theta(x) = f_{\theta_h}(f_{\theta_b}(x)) \in \mathbb{R}^n$ where $f_{\theta_b}(x) \in \mathbb{R}^d$. The task-specific body parameters θ_{b,τ_i} and head parameters θ_{h,τ_i} through an inner loop given task τ_i are then as follows:

$$\theta_{b,\tau_i} = \theta_b - \alpha_b \nabla_{\theta_b} L_{S_{\tau_i}}(f_\theta) \ \& \ \theta_{h,\tau_i} = \theta_h - \alpha_h \nabla_{\theta_h} L_{S_{\tau_i}}(f_\theta) \tag{3}$$

where α_b and α_h are the inner loop learning rates corresponding to the body and head, respectively. MAML usually sets $\alpha = \alpha_b = \alpha_h (\neq 0)$, ANIL sets $\alpha_b = 0$ and $\alpha_h \neq 0$, and BOIL sets $\alpha_b \neq 0$ and $\alpha_h = 0$.

This simple difference forces the change of the dominant factor of task-specific updates, from the head to the body. Figure 1 shows the main difference in the inner updates between MAML/ANIL and BOIL. To solve new tasks, the head mainly or only changes in MAML/ANIL (Raghu et al., 2020), whereas in BOIL, the body only changes.

3.2.1 PERFORMANCE IMPROVEMENT ON BENCHMARK DATA SETS AND CROSS-DOMAIN TASKS

Table 1: Test accuracy (%) of 4conv network on benchmark data sets. The values in parenthesis in the algorithm name column of tables are the number of shots.

Domain	General (Coarse-grained)		Specific (Fine-grained)	
Dataset	miniImageNet	tieredImageNet	Cars	CUB
MAML(1)	47.44 ± 0.23	47.44 ± 0.18	45.27 ± 0.26	56.18 ± 0.37
ANIL(1)	47.82 ± 0.20	$\mathbf{49.35 \pm 0.26}$	46.81 ± 0.24	57.03 ± 0.41
BOIL(1)	$\mathbf{49.61 \pm 0.16}$	48.58 ± 0.27	$\mathbf{56.82 \pm 0.21}$	$\mathbf{61.60 \pm 0.25}$
MAML(5)	61.75 ± 0.42	64.70 ± 0.14	53.23 ± 0.26	69.66 ± 0.03
ANIL(5)	63.04 ± 0.42	65.82 ± 0.12	61.95 ± 0.38	70.93 ± 0.28
BOIL(5)	$\mathbf{66.45 \pm 0.37}$	$\mathbf{69.37 \pm 0.12}$	$\mathbf{75.18 \pm 0.21}$	$\mathbf{75.96 \pm 0.17}$

Table 2: Test accuracy (%) of 4conv network on cross-domain adaptation.

adaptation	general to general		general to specific		specific to general		specific to specific	
meta-train	tieredImageNet	miniImageNet	miniImageNet	miniImageNet	Cars	Cars	CUB	Cars
meta-test	miniImageNet	tieredImageNet	Cars	CUB	miniImageNet	tieredImageNet	Cars	CUB
MAML(1)	47.60 ± 0.24	51.61 ± 0.20	33.57 ± 0.14	40.51 ± 0.08	26.95 ± 0.15	28.46 ± 0.18	32.22 ± 0.30	29.64 ± 0.19
ANIL(1)	49.67 ± 0.31	52.82 ± 0.29	34.77 ± 0.31	41.12 ± 0.15	28.67 ± 0.17	29.41 ± 0.19	33.07 ± 0.43	28.32 ± 0.32
BOIL(1)	$\mathbf{49.74 \pm 0.26}$	$\mathbf{53.23 \pm 0.41}$	$\mathbf{36.12 \pm 0.29}$	$\mathbf{44.20 \pm 0.15}$	$\mathbf{33.71 \pm 0.13}$	$\mathbf{34.06 \pm 0.20}$	$\mathbf{35.44 \pm 0.46}$	$\mathbf{34.79 \pm 0.27}$
MAML(5)	65.22 ± 0.20	65.76 ± 0.27	44.56 ± 0.21	53.09 ± 0.16	30.64 ± 0.19	32.62 ± 0.21	41.24 ± 0.21	32.18 ± 0.13
ANIL(5)	66.47 ± 0.16	66.52 ± 0.28	46.55 ± 0.29	55.82 ± 0.21	35.38 ± 0.10	36.94 ± 0.10	43.05 ± 0.23	37.99 ± 0.15
BOIL(5)	$\mathbf{69.33 \pm 0.19}$	$\mathbf{69.37 \pm 0.23}$	$\mathbf{50.64 \pm 0.22}$	$\mathbf{60.92 \pm 0.11}$	$\mathbf{44.51 \pm 0.25}$	$\mathbf{46.09 \pm 0.23}$	$\mathbf{47.30 \pm 0.22}$	$\mathbf{45.91 \pm 0.28}$

Table 1 and Table 2 displays BOIL's superiority on most benchmark data sets and on cross-domain adaptation tasks, where the source and target domains differ (i.e., the meta-training and meta-testing data sets are different). In Table 1, performance improvement is especially noticeable on specific domain data sets CUB and Cars. The results demonstrate that *representation change* is necessary even if there is a similarity between the source and target domains. Table 2 shows that BOIL is closer to the ultimate goal of meta-learning, domain-agnostic adaptation.

Recently, Guo et al. (2019) noted that existing meta-learning algorithms have weaknesses in terms of the cross-domain adaptation. We divide the cross-domain adaptation into four cases: general to general, general to specific, specific to general, and specific to specific. Previous studies considered the cross-domain scenario from a general domain to a specific domain (Chen et al., 2019; Guo et al., 2019). In this paper, we also evaluate the reverse case. BOIL outperforms MAML/ANIL not only on the typical cross-domain adaptation scenario but also on the reverse scenario. This performance improvement implies that the *representation change* in BOIL enables the model to adapt to an unseen target domain that is different from the source domain. In particular, the performance improvement, when the domain changes from birds (CUB as a meta-train set) to cars (Cars as a meta-test set), implies that the *representation change* in BOIL enables the model to adapt to an unseen target domain that is entirely different from the source domain.

3.2.2 BOIL AND PRECONDITIONING GRADIENTS

Some aspects of BOIL could be explained by preconditioning gradients (Lee & Choi, 2018; Flennerhag et al., 2020). Preconditioning gradients happens when a particular layer is shared over all tasks, warping spaces (rotating, scaling, etc.). For instance, one might think that the frozen head of BOIL is a warp layer of the entire body (Flennerhag et al., 2020).

Preconditioning gradients can avoid overfitting in a high-capacity model (Flennerhag et al., 2020), and the benefit is still valid in BOIL. Indeed, many prior works suffer from the overfitting problem, and thus, it is challenging to train the backbone network more extensive than the 4conv network with 32 filters (Finn et al., 2017). On the contrary, BOIL can increase the validation accuracy with bigger networks. The accuracy of models with 32, 64, and 128 filters continues to rise to 64.02, 66.72, and 69.23, without overfitting. We report this result and training and valid accuracy curves of BOIL for three different network sizes where bigger networks are trained well in Appendix D. We further hypothesize that the head is the most critical part of the overfitting problem, and BOIL can succeed in dealing with the problem by simply ignoring the head in inner loops.

However, one essential difference between BOIL and preconditioning gradients is whether the head is frozen or not. All the prior works never freeze the last fully connected layer or use any additional fully connected layer to precondition gradients for it, and hence *representation reuse* is still the major factor of their training. To our best knowledge, BOIL is the first work that enforces *representation change* by freezing the head in inner loops.

To investigate the gain from *representation change*, we adapt BOIL to WarpGrad (Flennerhag et al., 2020).[4] Four different models are tested, and their architectures are fully described in Appendix F. Table 3 shows the test accuracy of the four models, where BOIL-WarpGrad models freeze the fully connected layer from the corresponding Warp-Grad model. It is observed that BOIL-WarpGrad improves WarpGrad, particularly without the last warp conv. It can be explained that the last convolution layer must be updated for boosting *representation change*.

Model	Accuracy
WarpGrad w/ last warp head	83.19 ± 0.79
WarpGrad w/o last warp head	83.16 ± 0.69
BOIL-WarpGrad w/ last warp conv	83.68 ± 0.82
BOIL-WarpGrad w/o last warp conv	$\mathbf{84.88} \pm 0.42$

Table 3: Test accuracy(%) of WarpGrad and BOIL-WarpGrad over 5×100 tasks.

4 REPRESENTATION CHANGE IN BOIL

4.1 REPRESENTATION CHANGE BEFORE/AFTER ADAPTATION

(a) MAML.   (b) ANIL.   (c) BOIL.

Figure 2: Cosine similarity of 4conv network.

To analyze whether the learning scheme of BOIL is *representation reuse* or *representation change*, we explore the layer-wise alteration of representations before and after adaptation. We compute the cosine similarities and CKA values of convolution layers with the meta-trained 4conv network (as detailed in Appendix A). We first investigate the cosine similarity between the representations of a query set including 5 classes and 15 samples per class after every convolution module. In Figure 2, the orange line represents the average of the cosine similarities between the samples having the same class, and the blue line represents the average of cosine similarities between the samples having different classes. In Figure 2, each algorithm's left panel is before inner loop adaptation, and the right panel is after inner loop adaptation.

---

[4]we follow the setting in https://github.com/flennerhag/warpgrad and the details about this implementation in Appendix F.

The key observations from Figure 2, also discussed with other experiments in Section 4.2, are as follows:

- The cosine similarities of MAML and ANIL have the similar patterns (Figure 2a and Figure 2b), supporting *representation reuse* only. Their patterns do not have any noticeable difference before and after the adaptation. They make the average of the cosine similarities monotonically decrease and make the representations separable by the classes when the representations reach the last convolution layer. These analyses mean that effectiveness of MAML and ANIL heavily lean on the meta-initialized body, not the task-specific adaptation.

- The cosine similarities of BOIL have a different pattern from those of MAML and ANIL Figure 2c), supporting *representation change*. The BOIL's pattern changes to distinguish classes before and after adaptation. Before adaptation, BOIL reduces the average of the cosine similarities only up to conv3, and all the representations are concentrated regardless of their classes after the last convolution layer. Hence, BOIL's meta-initialized body cannot distinguish the classes. However, after adaptation, the similarity of different classes rapidly goes down on conv4, which means the body can distinguish the classes through adaptation.

- The reason why the change of BOIL before and after adaptation exists only on conv4 is the peculiarity of the convolutional body analyzed by Zeiler & Fergus (2014). Although the general and low-level features produced via the front convolution layers, e.g., colors, lines, and shapes, do not differ much from the task-specific adaptation, the discriminative features produced via the last convolution layer (conv4) differ from class to class. Arnold et al. (2019) also investigated the importance of the last convolutional layer on performance in the MAML setting. These changes before and after the adaptation support that BOIL enjoys *representation reuse* in a low- and mid-level of the body and *representation change* in a high-level of the body.

Through these observations, we believe that MAML follows the *representation reuse* training scheme, whereas BOIL follows both *representation reuse* (before the last layer) and *representation change* (at the last layer) training schemes.

Next, we demonstrate that BOIL enjoys both *representation reuse* on the low- and mid-level layers and *representation change* on the high-level layer by computing the CKA (Kornblith et al., 2019) between before and after adaptation. When the CKA between two representations is close to 1, the representations are almost identical. In Figure 3, as mentioned in (Raghu et al., 2020), CKA shows that MAML/ANIL algorithms do not change representation in the body. However, BOIL change representation on the last convolution layer. This result indicates that the BOIL algorithm learns rapidly via *representation change*.

Figure 3: CKA of 4conv.

4.2 EMPIRICAL ANALYSIS OF REPRESENTATION CHANGE IN BOIL

Table 4: Test accuracy (%) of 4conv network according to the head's existence before/after an adaptation.

meta-train	Cars							
meta-test	Cars				CUB			
head	w/ head		w/o head (NIL-testing)		w/ head		w/o head (NIL-testing)	
adaptation	before	after	before	after	before	after	before	after
MAML(1)	20.03 ± 0.25	45.27 ± 0.26	47.87 ± 0.18	47.23 ± 0.24	20.01 ± 0.08	29.64 ± 0.19	**31.01** ± 0.26	31.15 ± 0.23
ANIL(1)	20.01 ± 0.18	46.81 ± 0.24	**49.45** ± 0.18	49.45 ± 0.18	20.02 ± 0.08	28.32 ± 0.32	29.72 ± 0.27	29.72 ± 0.27
BOIL(1)	20.19 ± 0.19	**56.82** ± 0.21	25.46 ± 0.29	**52.36** ± 0.13	19.96 ± 0.12	**34.79** ± 0.27	22.93 ± 0.17	**34.51** ± 0.21
MAML(5)	20.11 ± 0.16	53.23 ± 0.26	59.67 ± 0.22	59.38 ± 0.23	20.00 ± 0.22	32.18 ± 0.13	36.12 ± 0.24	36.61 ± 0.19
ANIL(5)	20.09 ± 0.17	61.95 ± 0.38	**67.03** ± 0.36	67.03 ± 0.36	19.99 ± 0.18	37.99 ± 0.15	**43.27** ± 0.31	43.27 ± 0.31
BOIL(5)	20.04 ± 0.08	**75.18** ± 0.21	36.65 ± 0.11	**71.52** ± 0.27	20.02 ± 0.05	**45.91** ± 0.28	29.04 ± 0.18	**47.02** ± 0.25

Table 4 describes the test accuracy on Cars and CUB of the model meta-trained on Cars before and after an inner update according to the presence of the head. To evaluate the performance in a case without a classifier, we first create a template of each class by averaging the representations from the support set. Then, the class of the sample from the query set is predicted as the class whose template has the highest cosine similarity with the representation of the sample. It is the same with NIL-testing in (Raghu et al., 2020).

The results provide some intriguing interpretations:

- **with the head in all algorithms** Before adaptation, all algorithms on the same- and cross-domain are unable to distinguish all classes (20%). This status could be considered as an optimum of meta-initialization. We also discuss it in Appendix H. Besides, in BOIL, the representations have to move quickly to their corresponding frozen head. Moreover, after adaptation, BOIL overwhelms the performance of other algorithms. It means *representation change* of BOIL is more effective than *representation reuse* of MAML/ANIL.
- **without the head in MAML/ANIL** Because representations from the body are evaluated before and after adaptation in this setting, it is possible to evaluate the performance of the body of each algorithm. In this situation, MAML and ANIL already generate sufficient representation before adaptation, with little difference between before and after adaptation. This shows that the body of MAML and ANIL, as seen in section 4.1, do not change in the task-specific adaptation.
- **without the head in BOIL** BOIL shows steep performance improvements through adaptation on the same- and cross-domain. These results show that the body of BOIL could be task-specifically updated. After adaptation, BOIL overwhelms MAML and ANIL, which shows that a poor body can be a superior body via just adaptation in *representation change*.

To summarize, the meta-initialization by MAML and ANIL provides efficient representations through the body even before the adaptation. By contrast, although BOIL's meta-initialization provides less efficient representations compared to MAML and ANIL, the body can extract more efficient representations through task-specific adaptation based on *representation change*.

5 BOIL TO A LARGER NETWORK

Table 5: 5-Way 5-Shot test accuracy (%) of ResNet-12. LSC means Last Skip Connection.

Meta-train	miniImageNet			Cars		
Meta-test	miniImageNet	tieredImageNet	Cars	Cars	miniImageNet	CUB
MAML w/ LSC	68.46 ± 0.22	71.67 ± 0.13	43.67 ± 0.30	75.69 ± 0.25	34.42 ± 0.06	36.13 ± 0.09
MAML w/o LSC	68.12 ± 0.20	70.31 ± 0.10	41.58 ± 0.25	74.00 ± 0.15	37.65 ± 0.11	34.91 ± 0.14
ANIL w/ LSC	68.39 ± 0.31	71.93 ± 0.11	45.28 ± 0.19	79.68 ± 0.22	35.03 ± 0.07	35.06 ± 0.12
ANIL w/o LSC	67.22 ± 0.19	69.79 ± 0.24	43.55 ± 0.13	75.51 ± 0.08	38.15 ± 0.15	36.10 ± 0.19
BOIL w/ LSC	70.57 ± 0.23	71.86 ± 0.21	49.75 ± 0.31	81.13 ± 0.14	45.89 ± 0.32	43.69 ± 0.10
BOIL w/o LSC	$\mathbf{71.26} \pm 0.23$	$\mathbf{74.12} \pm 0.30$	$\mathbf{49.77} \pm 0.24$	$\mathbf{84.21} \pm 0.08$	$\mathbf{48.41} \pm 0.18$	$\mathbf{44.24} \pm 0.19$

Many recent studies (Oreshkin et al., 2018; Vuorio et al., 2019; Rusu et al., 2018; Sun et al., 2019) have used deeper networks such as ResNet (He et al., 2016), Wide-ResNet (Zagoruyko & Komodakis, 2016), or DenseNet (Huang et al., 2017) as a backbone network. The deeper networks, in general, use feature wiring structures that connect layers to facilitate feature propagation. We explore the applicability of BOIL to a deeper network with the wiring structure, ResNet-12, and propose a simple trick to boost the *representation change* by disconnecting the last skip connection. The trick is explained in Section 5.1.

Table 5 shows the test accuracy results of ResNet-12, which is meta-trained and meta-tested with various data sets according to the fineness of the domains. This result indicates that BOIL can be applied to other general architectures by showing a better performance than MAML not only on standard benchmark data sets but also on cross-domain adaptation. Note that BOIL has achieved the best performance without the last skip connection in every experiment.

5.1 DISCONNECTION TRICK

Connecting the two learning schemes and ResNet's wiring structure, we propose a simple trick to eliminate the skip connection of the last residual block, which is referred to as the disconnection trick. In section 4.1, we confirmed that the model learned with BOIL applies the *representation reuse* at the low- and mid-level of the body and *representation change* at the high-level of the body.

To investigate the effects of skip connections on a *representation change* learning scheme, we analyze the cosine similarity after every residual block in the same way as Figure 2. Figure 4a shows that ResNet with skip connections on all blocks changes not only the last block but also other blocks rapidly. Because skip connections strengthen the gradient back-propagation, the scope of *representation change* extends to the front. Therefore, to achieve both the effective *representation reuse* and the *representation change* of BOIL, we suggest a way to weaken the gradient back-propagation from the loss function by removing the skip connection of the last block. As shown in

Figure 4: Cosine similarity of ResNet-12.

Figure 4b, with this simple disconnection trick, ResNet can improve the effectiveness of BOIL, as well as the *representation reuse* at the front blocks of the body and the *representation change* at the last block, and significantly improves the performance, as described in Table 5.

6 RELATED WORK

MAML (Finn et al., 2017) is one of the most famous algorithms in gradient-based meta-learning, achieving a competitive performance on few-shot learning benchmark data sets (Vinyals et al., 2016; Ren et al., 2018; Bertinetto et al., 2018; Oreshkin et al., 2018). To tackle the task ambiguity caused by data insufficiency in few-shot learning, numerous studies have sought to extend MAML in various ways. Some studies (Oreshkin et al., 2018; Sun et al., 2019; Vuorio et al., 2019) have proposed feature modulators that make task-specific adaptation more amenable by shifting and scaling the representations extracted from the network body. In response to the lack of data for task-specific updates, there have also been attempts to incorporate additional parameters in a small number, rather than the entire model parameters (Zintgraf et al., 2018; Rusu et al., 2018; Lee & Choi, 2018; Flennerhag et al., 2020). With a similar approach, some studies suggested a way to update only the heads in the inner loop, which has been further improved to update the head using linear separable objectives. (Raghu et al., 2020; Bertinetto et al., 2018; Lee et al., 2019b). Grant et al. (2018); Finn et al. (2018); Yoon et al. (2018); Na et al. (2019) have taken a probabilistic approach using Bayesian modeling and variational inference. Unlike prior studies, we proposed a new training paradigm reinforcing a task-specific update by the model itself.

Few-shot learning has recently been expanding beyond the standard n-way k-shot classification to tackle the more realistic problems. Triantafillou et al. (2019) constructed a more scalable and realistic dataset, called a meta-data set, which contains several data sets collected from different sources. Lee et al. (2019a) addressed n-way any-shot classification considering the imbalanced data distribution in real-world. Furthermore, some studies (Cai & Shen, 2020; Chen et al., 2019) have recently explored few-shot learning on cross-domain adaptation, which is one of the ultimate goals of meta-learning. In addition, Guo et al. (2019) suggested a new cross-domain benchmark dataset for few-shot learning and showed that the current meta-learning algorithms (Finn et al., 2017; Vinyals et al., 2016; Snell et al., 2017; Sung et al., 2018; Lee et al., 2019b) underachieve compared to simple fine-tuning on cross-domain adaptation. We demonstrated that task-specific update with *representation change* is efficient on cross-domain adaptation.

7 CONCLUSION

In this study, we investigated the necessity of *representation change* for solving domain-agnostic tasks and proposed the BOIL algorithm, which is designed to enforce *representation change* by learning only the body of the model in the inner loop. We connected BOIL with preconditioning gradients and showed that the effectivenesses from it, overfitting reduction and robustness to hyperparameter change, are still valid. Furthermore, we adapt BOIL to WarpGrad, showing performance improvement. This result decouples the benefits of *representation change* and preconditioning gradients. Next, we demonstrated that BOIL trains a model to follow the *representation reuse* scheme on the low- and mid-level body but trains it to follow the *representation change* scheme on the high-level body using the cosine similarity and the CKA. We validated the BOIL algorithm on various data sets, including miniImageNet, tieredImageNet, Cars, and CUB, and cross-domain adaptation using a standard 4conv network. The experimental results showed significant improvement over MAML/ANIL, particularly cross-domain adaptation, implying that *representation change* should be considered for adaptation to unseen tasks. We hope our study inspires *representation change* in gradient-based meta-learning approaches.

REFERENCES

Sébastien MR Arnold, Shariq Iqbal, and Fei Sha. Decoupling adaptation from modeling with meta-optimizers for meta learning. *arXiv preprint arXiv:1910.13603*, 2019.

Luca Bertinetto, Joao F Henriques, Philip HS Torr, and Andrea Vedaldi. Meta-learning with differentiable closed-form solvers. *arXiv preprint arXiv:1805.08136*, 2018.

John Cai and Sheng Mei Shen. Cross-domain few-shot learning with meta fine-tuning. *arXiv preprint arXiv:2005.10544*, 2020.

Wei-Yu Chen, Yen-Cheng Liu, Zsolt Kira, Yu-Chiang Frank Wang, and Jia-Bin Huang. A closer look at few-shot classification. *arXiv preprint arXiv:1904.04232*, 2019.

Tristan Deleu, Tobias Würfl, Mandana Samiei, Joseph Paul Cohen, and Yoshua Bengio. Torchmeta: A Meta-Learning library for PyTorch, 2019. URL https://arxiv.org/abs/1909.06576. Available at: https://github.com/tristandeleu/pytorch-meta.

Rafael Rego Drumond, Lukas Brinkmeyer, Josif Grabocka, and Lars Schmidt-Thieme. Hidra: Head initialization across dynamic targets for robust architectures. In *Proceedings of the 2020 SIAM International Conference on Data Mining*, pp. 397–405. SIAM, 2020.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 1126–1135. JMLR. org, 2017.

Chelsea Finn, Kelvin Xu, and Sergey Levine. Probabilistic model-agnostic meta-learning. In *Advances in Neural Information Processing Systems*, pp. 9516–9527, 2018.

Sebastian Flennerhag, Andrei A. Rusu, Razvan Pascanu, Francesco Visin, Hujun Yin, and Raia Hadsell. Meta-learning with warped gradient descent. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=rkeiQlBFPB.

Erin Grant, Chelsea Finn, Sergey Levine, Trevor Darrell, and Thomas Griffiths. Recasting gradient-based meta-learning as hierarchical bayes. *arXiv preprint arXiv:1801.08930*, 2018.

Yunhui Guo, Noel CF Codella, Leonid Karlinsky, John R Smith, Tajana Rosing, and Rogerio Feris. A new benchmark for evaluation of cross-domain few-shot learning. *arXiv preprint arXiv:1912.07200*, 2019.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Nathan Hilliard, Lawrence Phillips, Scott Howland, Artëm Yankov, Courtney D Corley, and Nathan O Hodas. Few-shot learning with metric-agnostic conditional embeddings. *arXiv preprint arXiv:1802.04376*, 2018.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4700–4708, 2017.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. *arXiv preprint arXiv:1502.03167*, 2015.

Gregory Koch. Siamese neural networks for one-shot image recognition. 2015.

Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. Similarity of neural network representations revisited. *arXiv preprint arXiv:1905.00414*, 2019.

Jonathan Krause, Michael Stark, Jia Deng, and Li Fei-Fei. 3d object representations for fine-grained categorization. In *Proceedings of the IEEE international conference on computer vision workshops*, pp. 554–561, 2013.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Hae Beom Lee, Hayeon Lee, Donghyun Na, Saehoon Kim, Minseop Park, Eunho Yang, and Sung Ju Hwang. Learning to balance: Bayesian meta-learning for imbalanced and out-of-distribution tasks. *arXiv preprint arXiv:1905.12917*, 2019a.

Kwonjoon Lee, Subhransu Maji, Avinash Ravichandran, and Stefano Soatto. Meta-learning with differentiable convex optimization. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 10657–10665, 2019b.

Yoonho Lee and Seungjin Choi. Gradient-based meta-learning with learned layerwise metric and subspace. In *International Conference on Machine Learning*, pp. 2927–2936, 2018.

Subhransu Maji, Esa Rahtu, Juho Kannala, Matthew Blaschko, and Andrea Vedaldi. Fine-grained visual classification of aircraft. *arXiv preprint arXiv:1306.5151*, 2013.

Leland McInnes, John Healy, Nathaniel Saul, and Lukas Großberger. Umap: Uniform manifold approximation and projection. *Journal of Open Source Software*, 3(29), 2018.

Donghyun Na, Hae Beom Lee, Saehoon Kim, Minseop Park, Eunho Yang, and Sung Ju Hwang. Learning to balance: Bayesian meta-learning for imbalanced and out-of-distribution tasks. *arXiv preprint arXiv:1905.12917*, 2019.

Alex Nichol, Joshua Achiam, and John Schulman. On first-order meta-learning algorithms. *arXiv preprint arXiv:1803.02999*, 2018.

Maria-Elena Nilsback and Andrew Zisserman. Automated flower classification over a large number of classes. In *2008 Sixth Indian Conference on Computer Vision, Graphics & Image Processing*, pp. 722–729. IEEE, 2008.

Boris Oreshkin, Pau Rodríguez López, and Alexandre Lacoste. Tadam: Task dependent adaptive metric for improved few-shot learning. In *Advances in Neural Information Processing Systems*, pp. 721–731, 2018.

Aniruddh Raghu, Maithra Raghu, Samy Bengio, and Oriol Vinyals. Rapid learning or feature reuse? towards understanding the effectiveness of maml. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=rkgMkCEtPB.

Sachin Ravi and Hugo Larochelle. Optimization as a model for few-shot learning. 2016.

Mengye Ren, Eleni Triantafillou, Sachin Ravi, Jake Snell, Kevin Swersky, Joshua B Tenenbaum, Hugo Larochelle, and Richard S Zemel. Meta-learning for semi-supervised few-shot classification. *arXiv preprint arXiv:1803.00676*, 2018.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International journal of computer vision*, 115(3):211–252, 2015.

Andrei A Rusu, Dushyant Rao, Jakub Sygnowski, Oriol Vinyals, Razvan Pascanu, Simon Osindero, and Raia Hadsell. Meta-learning with latent embedding optimization. *arXiv preprint arXiv:1807.05960*, 2018.

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In *Advances in neural information processing systems*, pp. 4077–4087, 2017.

Qianru Sun, Yaoyao Liu, Tat-Seng Chua, and Bernt Schiele. Meta-transfer learning for few-shot learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 403–412, 2019.

Flood Sung, Yongxin Yang, Li Zhang, Tao Xiang, Philip HS Torr, and Timothy M Hospedales. Learning to compare: Relation network for few-shot learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1199–1208, 2018.

Eleni Triantafillou, Tyler Zhu, Vincent Dumoulin, Pascal Lamblin, Utku Evci, Kelvin Xu, Ross Goroshin, Carles Gelada, Kevin Swersky, Pierre-Antoine Manzagol, et al. Meta-dataset: A dataset of datasets for learning to learn from few examples. *arXiv preprint arXiv:1903.03096*, 2019.

Hung-Yu Tseng, Hsin-Ying Lee, Jia-Bin Huang, and Ming-Hsuan Yang. Cross-domain few-shot classification via learned feature-wise transformation. *arXiv preprint arXiv:2001.08735*, 2020.

Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Daan Wierstra, et al. Matching networks for one shot learning. In *Advances in neural information processing systems*, pp. 3630–3638, 2016.

Risto Vuorio, Shao-Hua Sun, Hexiang Hu, and Joseph J Lim. Multimodal model-agnostic meta-learning via task-aware modulation. In *Advances in Neural Information Processing Systems*, pp. 1–12, 2019.

P. Welinder, S. Branson, T. Mita, C. Wah, F. Schroff, S. Belongie, and P. Perona. Caltech-UCSD Birds 200. Technical Report CNS-TR-2010-001, California Institute of Technology, 2010.

Bing Xu, Naiyan Wang, Tianqi Chen, and Mu Li. Empirical evaluation of rectified activations in convolutional network. *arXiv preprint arXiv:1505.00853*, 2015.

Jaesik Yoon, Taesup Kim, Ousmane Dia, Sungwoong Kim, Yoshua Bengio, and Sungjin Ahn. Bayesian model-agnostic meta-learning. In *Advances in Neural Information Processing Systems*, pp. 7332–7342, 2018.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

Matthew D Zeiler and Rob Fergus. Visualizing and understanding convolutional networks. In *European conference on computer vision*, pp. 818–833. Springer, 2014.

Luisa M Zintgraf, Kyriacos Shiarlis, Vitaly Kurin, Katja Hofmann, and Shimon Whiteson. Fast context adaptation via meta-learning. *arXiv preprint arXiv:1810.03642*, 2018.

A IMPLEMENTATION DETAIL

A.1 n-WAY k-SHOT SETTING

We experimented in the 5-way 1-shot and 5-way 5-shot, and the number of shots is marked in parentheses in the algorithm name column of all tables. During meta-training, models are inner loop updated only once, and the meta-batch size for the outer loop is set to 4. During meta-testing, the number of task-specific (inner loop) updates is the same as meta-training. All models are trained for 30,000 iterations, and all the reported results are based on the model with the best validation accuracy.

A.2 MODEL IMPLEMENTATIONS

In our experiments, we employ 4conv network and ResNet-12 for MAML and BOIL algorithms. 4conv network has of 4 convolution modules, and each module consists of a 3×3 convolution layer with 64 filters, batch normalization (Ioffe & Szegedy, 2015), a ReLU non-linearity, a 2×2 max-pool. This model is also the same as MAML except for the number of filters. However, we experiment with both MAML and BOIL with the 64 filters network for a fair comparison. ResNet-12 (He et al., 2016) has the same structure with the feature extractor of TADAM (Oreshkin et al., 2018). It has four residual blocks, and each block consists of 3 modules of convolution, batch normalization, and leaky ReLU (Xu et al., 2015). Every end of each residual block, 2×2 max-pool is applied, and the number of convolution filters is doubled from 64 on each block. Each block also has a wiring structure known as skip connection, which is a link made up of additions between the block's input and output feature for strengthening feature propagation.

Our proposed algorithms can be implemented by just dividing learning rates into for the body and the head. Table 6 shows the learning rates of each network and algorithm. α_b and α_h are the learning rates of the body and the head of the model during inner loops, and β_b and β_h are the learning rates of the body and the head of the model during outer loops.

	4conv network			ResNet-12		
	MAML	ANIL	BOIL	MAML	ANIL	BOIL
α_b	0.5	0.0	0.5	0.3	0.0	0.3
α_h	0.5	0.5	0.0	0.3	0.3	0.0
β_b	0.001	0.001	0.001	0.001	0.001	0.001
β_h	0.001	0.001	0.001	0.001	0.001	0.001

Table 6: Learning rates according to the algorithms.

A.3 DATASET

We validate the BOIL and MAML algorithms on several data sets, considering image size and fineness. Table 7 is the summarization of the used data sets.

Table 7: Summary of data sets.

Data sets	miniImageNet	tieredImageNet	Cars	CUB
Source	Russakovsky et al. (2015)	Russakovsky et al. (2015)	Krause et al. (2013)	Welinder et al. (2010)
Image size	84×84	84×84	84×84	84×84
Fineness	Coarse	Coarse	Fine	Fine
# meta-training classes	64	351	98	100
# meta-validation classes	16	97	49	50
# meta-testing classes	20	160	49	50
Split setting	Vinyals et al. (2016)	Ren et al. (2018)	Tseng et al. (2020)	Hilliard et al. (2018)
Data sets	FC100	CIFAR-FS	VGG-Flower	Aircraft
Source	Krizhevsky et al. (2009)	Krizhevsky et al. (2009)	Nilsback & Zisserman (2008)	Maji et al. (2013)
Image size	32×32	32×32	32×32	32×32
Fineness	Coarse	Coarse	Fine	Fine
# meta-training classes	60	64	71	70
# meta-validation classes	20	16	16	15
# meta-testing classes	20	20	15	15
Split setting	Bertinetto et al. (2018)	Oreshkin et al. (2018)	Na et al. (2019)	Na et al. (2019)

B VISUALIZATION USING UMAP

Through section 4.1, we show that conv4 in a 4conv network is the critical layer where *representation change* happens. We visualize these representations, the output of conv4, of samples from various data sets using UMAP (McInnes et al., 2018), which is an algorithm for general non-linear dimension reduction. *Samples with the same line color belong to the same class*. Many examples show the consistency with the intuition shown in Figure 1. When 1) similar instances with different classes are sampled together and 2) representations on the meta-train data set cannot capture representations on the meta-test data set, MAML/ANIL seems to be challenging to cluster samples on representation space since they are based on *representation reuse*.

B.1 BENCHMARK DATA SETS

(a) MAML.   (b) ANIL.   (c) BOIL.

Figure 5: UMAP of samples from miniImageNet using the model meta-trained on miniImageNet.

(a) MAML.   (b) ANIL.   (c) BOIL.

Figure 6: UMAP of samples from Cars using the model meta-trained on Cars.

B.2 CROSS-DOMAIN ADAPTATION

(a) MAML.   (b) ANIL.   (c) BOIL.

Figure 7: UMAP of samples from tieredImageNet using the model meta-trained on miniImageNet.

(a) MAML.   (b) ANIL.   (c) BOIL.

Figure 8: UMAP of samples from Cars using the model meta-trained on miniImageNet.

(a) MAML.   (b) ANIL.   (c) BOIL.

Figure 9: UMAP of samples from miniImageNet using the model meta-trained on Cars.

(a) MAML.   (b) ANIL.   (c) BOIL.

Figure 10: UMAP of samples from CUB using the model meta-trained on Cars.

C   RESULTS ON OTHER DATA SETS

We applied our algorithm to other data sets with image size of 32×32. Similar to the analyses on section 4, these data sets can be divided into two general data sets, **CIFAR-FS** (Bertinetto et al., 2018) and **FC100** (Oreshkin et al., 2018), and two specific data sets, **VGG-Flower** (Nilsback & Zisserman, 2008) and **Aircraft** (Maji et al., 2013). Table 8, Table 9, and Table 10 generally show the superiority of BOIL even if image size is extremely tiny.

Table 8: Test accuracy (%) of 4conv network on benchmark dataset.

Domain	General (Coarse-grained)		Specific (Fine-grained)	
Dataset	CIFAR-FS	FC100	VGG-Flower	Aircraft
MAML(1)	56.55 ± 0.45	35.99 ± 0.48	60.94 ± 0.35	52.27 ± 0.23
ANIL(1)	57.13 ± 0.47	36.37 ± 0.33	63.05 ± 0.30	$\mathbf{54.54} \pm 0.16$
BOIL(1)	$\mathbf{58.03} \pm 0.43$	$\mathbf{38.93} \pm 0.45$	$\mathbf{65.64} \pm 0.26$	53.37 ± 0.29
MAML(5)	70.10 ± 0.29	47.58 ± 0.30	75.13 ± 0.43	63.44 ± 0.26
ANIL(5)	69.87 ± 0.39	45.65 ± 0.44	72.07 ± 0.48	63.21 ± 0.16
BOIL(5)	$\mathbf{73.61} \pm 0.32$	$\mathbf{51.66} \pm 0.32$	$\mathbf{79.81} \pm 0.42$	$\mathbf{66.03} \pm 0.14$

Table 9: Test accuracy (%) of 4conv network on cross-domain adaptation.

adaptation	general to general		general to specific		specific to general		specific to specific	
meta-train	FC100	CIFAR-FS	CIFAR-FS	CIFAR-FS	VGG-Flower	VGG-Flower	Aircraft	VGG-Flower
meta-test	CIFAR-FS	FC100	VGG-Flower	Aircraft	CIFAR-FS	FC100	VGG-Flower	Aircraft
MAML(1)	62.58 ± 0.35	52.81 ± 0.28	49.69 ± 0.24	27.03 ± 0.18	34.38 ± 0.19	32.45 ± 0.23	37.05 ± 0.19	25.70 ± 0.19
ANIL(1)	$\mathbf{63.05} \pm 0.39$	$\mathbf{55.36} \pm 0.47$	50.61 ± 0.29	27.39 ± 0.09	35.90 ± 0.20	33.84 ± 0.30	31.59 ± 0.22	24.55 ± 0.14
BOIL(1)	60.71 ± 0.43	54.18 ± 0.35	$\mathbf{56.77} \pm 0.35$	$\mathbf{29.29} \pm 0.10$	$\mathbf{39.15} \pm 0.20$	$\mathbf{34.37} \pm 0.14$	$\mathbf{49.85} \pm 0.26$	$\mathbf{29.05} \pm 0.16$
MAML(5)	75.32 ± 0.34	63.00 ± 0.18	64.49 ± 0.23	33.85 ± 0.25	46.81 ± 0.11	42.06 ± 0.43	47.74 ± 0.07	30.65 ± 0.19
ANIL(5)	$\mathbf{77.01} \pm 0.51$	63.89 ± 0.16	64.20 ± 0.10	33.24 ± 0.21	44.52 ± 0.25	40.51 ± 0.26	50.28 ± 0.12	28.74 ± 0.23
BOIL(5)	76.33 ± 0.30	$\mathbf{68.55} \pm 0.20$	$\mathbf{74.93} \pm 0.11$	$\mathbf{39.96} \pm 0.11$	$\mathbf{55.48} \pm 0.21$	$\mathbf{47.17} \pm 0.38$	$\mathbf{64.68} \pm 0.23$	$\mathbf{39.81} \pm 0.25$

Table 10: 5-Way 5-Shot test accuracy (%) of ResNet-12. The lsc means the last skip connection.

Meta-train	CIFAR-FS			VGG-Flower		
Meta-test	CIFAR-FS	FC100	VGG-Flower	VGG-Flower	CIFAR-FS	Aircraft
MAML w/ lsc	75.30 ± 0.19	69.34 ± 0.35	65.82 ± 0.30	74.82 ± 0.29	42.91 ± 0.20	28.50 ± 0.12
MAML w/o lsc	71.72 ± 0.19	67.60 ± 0.34	59.20 ± 0.26	72.07 ± 0.29	39.27 ± 0.23	26.94 ± 0.18
ANIL w/ lsc	74.87 ± 0.11	75.34 ± 0.45	63.72 ± 0.40	77.02 ± 0.29	45.80 ± 0.32	27.24 ± 0.13
ANIL w/o lsc	71.39 ± 0.28	69.29 ± 0.32	52.70 ± 0.24	72.13 ± 0.39	38.99 ± 0.22	26.09 ± 0.08
BOIL w/ lsc	$\mathbf{78.17} \pm 0.14$	$\mathbf{77.22} \pm 0.45$	73.90 ± 0.38	82.00 ± 0.17	50.91 ± 0.35	35.54 ± 0.25
BOIL w/o lsc	77.38 ± 0.10	70.98 ± 0.34	$\mathbf{73.96} \pm 0.27$	$\mathbf{83.97} \pm 0.17$	$\mathbf{55.82} \pm 0.44$	$\mathbf{37.74} \pm 0.21$

D   OVERFITTING ISSUE

We employ networks with various sizes of filters, e.g., 32, 64, 128. The best validation scores of each model are 64.01, 66.72, 69.23, and these results mean that with BOIL, the more extensive network yields higher accuracy without overfitting.

Figure 11: Training/Validation Accuracy curve on miniImageNet according to filters in BOIL.

E RESULTS UNDER THE ORIGINAL HYPERPARAMETERS

We also evaluate our algorithm in the original setting (50 times smaller inner learning rate than ours) and confirm that BOIL is more robust to the change of hyperparameters than MAML. Such a characteristic is investigated in Lee & Choi (2018). Figure 12 shows the validation accuracy of BOIL and MAML/ANIL with the same hyperparameters optimized for MAML. It is observed that BOIL is the best or near-best, although the hyperparameters are not optimized for BOIL. Moreover, BOIL rapidly adapts and achieves considerable performance through just one adaptation.

Figure 12: Accuracy on miniImageNet according to the number of adaptation(s).

Table 11: Test accuracy (%) under the same architecture, learning rate, and the number of inner updates with (Finn et al., 2017; Raghu et al., 2020).

Meta-train	miniImageNet			Cars		
Meta-test	miniImageNet	tieredImageNet	Cars	Cars	miniImageNet	CUB
MAML(1)	46.25 ± 0.18	49.45 ± 0.14	34.78 ± 0.36	46.02 ± 0.33	28.87 ± 0.11	29.92 ± 0.23
ANIL(1)	47.20 ± 0.27	50.04 ± 0.13	32.87 ± 0.39	45.31 ± 0.27	29.12 ± 0.11	30.39 ± 0.21
BOIL(1)	$\mathbf{47.76} \pm 0.31$	$\mathbf{51.35} \pm 0.18$	$\mathbf{34.89} \pm 0.23$	$\mathbf{50.54} \pm 0.41$	$\mathbf{32.40} \pm 0.19$	$\mathbf{32.99} \pm 0.29$
MAML(5)	$\mathbf{64.83} \pm 0.30$	$\mathbf{67.06} \pm 0.25$	48.25 ± 0.24	$\mathbf{69.27} \pm 0.27$	$\mathbf{43.52} \pm 0.20$	45.12 ± 0.20
ANIL(5)	62.59 ± 0.39	65.55 ± 0.16	45.44 ± 0.18	62.67 ± 0.25	36.89 ± 0.16	40.38 ± 0.19
BOIL(5)	64.40 ± 0.28	65.81 ± 0.26	$\mathbf{48.39} \pm 0.25$	68.56 ± 0.34	43.34 ± 0.21	$\mathbf{46.32} \pm 0.11$

Table 12: Test accuracy (%) according to the number of adaptation(s). Training and testing are on miniImageNet.

Adaptation #	1	2	3	4	5	6	7	8	9	10
MAML(1)	32.01 ± 0.24	36.21 ± 0.17	42.74 ± 0.20	45.54 ± 0.18	46.04 ± 0.16	46.21 ± 0.19	46.17 ± 0.18	46.20 ± 0.18	46.22 ± 0.16	46.25 ± 0.18
ANIL(1)	20.97 ± 0.03	31.68 ± 0.25	41.41 ± 0.26	45.69 ± 0.20	46.78 ± 0.26	46.95 ± 0.30	47.05 ± 0.31	47.10 ± 0.30	47.17 ± 0.28	47.20 ± 0.27
BOIL(1)	$\mathbf{45.79} \pm 0.45$	$\mathbf{47.15} \pm 0.30$	$\mathbf{47.46} \pm 0.34$	$\mathbf{47.61} \pm 0.34$	$\mathbf{47.67} \pm 0.31$	$\mathbf{47.70} \pm 0.32$	$\mathbf{47.70} \pm 0.33$	$\mathbf{47.71} \pm 0.34$	$\mathbf{47.74} \pm 0.32$	$\mathbf{47.76} \pm 0.31$
MAML(5)	20.02 ± 0.00	20.15 ± 0.02	60.31 ± 0.34	63.78 ± 0.34	$\mathbf{64.41} \pm 0.35$	$\mathbf{64.55} \pm 0.33$	$\mathbf{64.64} \pm 0.31$	$\mathbf{64.72} \pm 0.31$	$\mathbf{64.77} \pm 0.30$	$\mathbf{64.83} \pm 0.40$
ANIL(5)	20.00 ± 0.00	24.52 ± 0.19	51.59 ± 0.17	58.84 ± 0.46	62.06 ± 0.37	62.34 ± 0.36	62.45 ± 0.38	62.51 ± 0.37	62.55 ± 0.38	62.59 ± 0.39
BOIL(5)	$\mathbf{58.15} \pm 0.23$	$\mathbf{62.42} \pm 0.33$	$\mathbf{63.56} \pm 0.26$	$\mathbf{64.04} \pm 0.30$	64.21 ± 0.28	64.27 ± 0.30	64.32 ± 0.30	64.35 ± 0.29	64.38 ± 0.28	64.40 ± 0.28

F WARPGRAD AND BOIL-WARPGRAD

F.1 IMPLEMENTATION DETAIL

We follow the default setting of the public code except for meta train steps and the number of filters, following (Flennerhag et al., 2020). We change meta train steps to 100 and the number of filters to 128. The task is 20way-5shot(in expectation) on Omniglot. Here, "in expectation" means that 100 samples are used for task-specific updates, but the number of samples per class is not the same.

F.2 ARCHITECTURE

Here are the architectures of WarpGrad and BOIL-WarpGrad. The WarpGrad w/o last warp head model is the default one in the original code.

Figure 13: Architectures of WarpGrad and BOIL-WarpGrad.

G   Results according to the existence of the head on other data sets

Table 13 shows that the results of NIL-testing of 4conv network meta-trained on miniImageNet.

Table 13: Test accuracy (%) of 4conv network according to the head's existence before/after an adaptation.

meta-train	miniImageNet							
meta-test	miniImageNet				Cars			
head	w/ head		w/o head (NIL-testing)		w/ head		w/o head (NIL-testing)	
adaptation	before	after	before	after	before	after	before	after
MAML(1)	19.96 ± 0.25	47.44 ± 0.23	48.28 ± 0.20	47.87 ± 0.14	20.05 ± 0.16	33.57 ± 0.14	34.47 ± 0.19	34.36 ± 0.16
ANIL(1)	20.09 ± 0.19	47.92 ± 0.20	$\mathbf{48.86 \pm 0.12}$	$\mathbf{48.86 \pm 0.12}$	20.16 ± 0.05	34.77 ± 0.31	$\mathbf{35.48 \pm 0.24}$	$\mathbf{35.48 \pm 0.24}$
BOIL(1)	19.94 ± 0.13	$\mathbf{49.61 \pm 0.16}$	24.07 ± 0.19	46.73 ± 0.17	19.94 ± 0.06	$\mathbf{36.12 \pm 0.29}$	23.30 ± 0.15	34.07 ± 0.32
MAML(5)	20.04 ± 0.17	61.75 ± 0.42	64.61 ± 0.39	64.47 ± 0.39	19.97 ± 0.18	44.56 ± 0.21	47.66 ± 0.28	47.53 ± 0.28
ANIL(5)	20.09 ± 0.13	63.04 ± 0.42	$\mathbf{66.11 \pm 0.51}$	$\mathbf{66.11 \pm 0.51}$	20.08 ± 0.07	46.55 ± 0.29	$\mathbf{49.62 \pm 0.20}$	49.62 ± 0.20
BOIL(5)	20.04 ± 0.21	$\mathbf{66.45 \pm 0.37}$	32.03 ± 0.16	64.61 ± 0.27	20.06 ± 0.16	$\mathbf{50.64 \pm 0.22}$	30.33 ± 0.18	$\mathbf{50.40 \pm 0.30}$

H   Additional considerations of the head of BOIL

We additionally discuss what the ideal meta-initialization is. Because the few-shot classification tasks are constructed with sampled classes each time, every task consists of different classes. Since the class indices are randomly assigned at the beginning of each task learning, the meta-initialized parameters cannot contain any prior information on the class indices. For instance, it is not allowed that the meta-initialized parameters encode class similarities between class i and class j. Any biased initial guess could hinder the task learning. The meta-initialized parameters should be in-between (local) optimal points of tasks as depicted in Figure 14 so that the network can adapt to each task with few task-specific updates.[5]

Figure 14: Ideal meta-initialization.

(a) Comparison with *centering* algorithm.   (b) Comparison with *fix* algorithm.

Figure 15: Valid accuracy curves of (a) centering algorithm and (b) fix algorithm on Cars.

When the head parameters $\theta_h = [\theta_{h,1}, ..., \theta_{h,n}]^\top \in \mathbb{R}^{n \times d}$ have orthonormal rows (i.e., $\|\theta_{h,i}\|_2 = 1$ for all i and $\theta_{h,i}^\top \theta_{h,j} = 0$ for all $i \neq j$), the meta-initialized model can have the unbiased classifier. Here, $a^\top$ denotes the transpose of a and $\| \cdot \|_2$ denotes the Euclidean norm. With the orthonormal rows, therefore, each logit value $\theta_{h,j}^\top f_{\theta_b}(x)$ can be controlled independently of other logit values. Recall that the softmax probability p_j for class j of sample x is computed as follows:

$$p_j(x) = \frac{e^{\theta_{h,j}^\top f_{\theta_b}(x)}}{\sum_{i=1}^n e^{\theta_{h,i}^\top f_{\theta_b}(x)}} = \frac{1}{\sum_{i=1}^n e^{(\theta_{h,i} - \theta_{h,j})^\top f_{\theta_b}(x)}}. \tag{4}$$

In Equation 4, indeed, the softmax probability only depends on the differences of the rows of the head parameters $\theta_{h,i} - \theta_{h,j}$. Adding a vector to all the rows (i.e., $\theta_{h,i} \leftarrow \theta_{h,i} + c$ for all i) does not change the softmax vector. So, we can expect the same nice meta-initialized model, when a parallel shift of the rows of the head parameters can make orthonormal rows. To support this

---

[5]The similar consideration is discussed in (Drumond et al., 2020).

experimentally, we design the *centering* algorithm that operates a parallel shift of θ_h by subtracting the average of the row vectors of θ_h after every outer update on both MAML and BOIL, i.e., $[\theta_{h,1} - \bar{\theta}_h, ..., \theta_{h,n} - \bar{\theta}_h]^\top$ where $\bar{\theta}_h = \frac{1}{n}\sum_{i=1}^{n}\theta_{h,i}$. Figure 15a shows that this parallel shift operations does not affect the performance of two algorithms on Cars.

Figure 16: Average of cosine similarities between gaps.

Next, we investigate the cosine similarity between $\theta_{h,i}^\top - \theta_{h,k}^\top$ and $\theta_{h,j}^\top - \theta_{h,k}^\top$ for all different i, j, and fixed k. From the training procedures of MAML and BOIL, it is observed that the average of cosine similarities between the two gaps keeps near 0.5 during meta-training (Figure 16). Note that 0.5 is the cosine similarity between $\theta_{h,i}^\top - \theta_{h,k}^\top$ and $\theta_{h,j}^\top - \theta_{h,k}^\top$ when $\theta_{h,i}^\top$, $\theta_{h,j}^\top$, and $\theta_{h,k}^\top$ are orthonormal. From the results, we evidence that the orthonormality of θ_h is important for the meta-initialization and meta learning algorithms naturally keep the orthonormality.

From the above observation, we design the *fix* algorithm that fixes θ_h to be orthonormal for the meta-initialized model. Namely, MAML-fix updates θ_h in inner loops only, and BOIL-fix does not update θ_h. The *fix* algorithm can be easily implemented by initializing θ_h to be orthonormal through the Gram-Schmidt method from a random matrix and setting the learning rate for the head of the model during the outer loop to zero.

Figure 15b depicts the valid accuracy curves of the *fix* algorithm on Cars. The experiments substantiate that orthonormal rows of θ_h are important and that BOIL improves the performance. (1) Comparing MAML to MAML-fix (the left panel of Figure 15b), MAML-fix outperforms MAML. It means that the outer loop calculated through the task-specific head following MAML is detrimental because the outer loop just adds unnecessary task-specific information to the model. (2) Comparing vanilla models to fix models (both panels of Figure 15b), fixed meta-initialized head with orthonormality is less over-fitted, which is explained through the train accuracy curves in Appendix B. (3) Comparing BOIL to BOIL-fix (the right panel of Figure 15b), although BOIL-fix can achieve almost the same performance with BOIL with sufficient iterations, BOIL converges faster to a better local optimum. This is because θ_h is trained so that the inner loop can easily adapt $f_{\theta_b}(x)$ to each class.