# KNOWLEDGE INFUSED DECODING

## ABSTRACT

Pre-trained language models (LMs) have been shown to memorize a substantial amount of knowledge from the pre-training corpora; however, they are still limited in recalling factually correct knowledge given a certain context. Hence. they tend to suffer from counterfactual or hallucinatory generation when used in knowledge-intensive natural language generation (NLG) tasks. Recent remedies to this problem focus on modifying either the pre-training or task fine-tuning objectives to incorporate knowledge, which normally require additional costly training or architecture modification of LMs for practical applications.

We present **K**nowledge **I**nfused **D**ecoding (KID)—a novel decoding algorithm for generative LMs, which dynamically infuses external knowledge into each step of the LM decoding. Specifically, we maintain a local knowledge memory based on the current context, interacting with a dynamically created external knowledge trie, and continuously update the local memory as a knowledge-aware constraint to guide decoding via reinforcement learning. On six diverse knowledge-intensive NLG tasks, task-agnostic LMs (e.g., GPT-2 and BART) armed with KID outperform many task-optimized state-of-the-art models, and show particularly strong performance in few-shot scenarios over six related knowledge-infusion techniques. Human evaluation confirms KID's ability to generate more relevant and factual language for the input context when compared with multiple baselines. Finally, KID also alleviates exposure bias and provides stable generation quality when generating longer sequences.

## 1  INTRODUCTION

Pre-trained language models (LMs) have been shown to capture rich semantic and syntactic features, as demonstrated by the state-of-the-art performance on many generation tasks such as abstractive summarization (Zhang et al., 2020b; Chu & Liu, 2019) and dialogue generation (Roller et al., 2021; Zhang et al., 2020c). Their generations, however, can be quite limited in scenarios requiring *knowledge*—they frequently struggle with issues such as being easily misguided by phrase co-occurrence (e.g., *"Talk? Birds can talk."*), failing to handle negation (e.g., *"The theory of relativity was **not** developed by Einstein."*) (Kassner & Schütze, 2020), and being unable to compare common-sense concepts, such as time (Qin et al., 2021) and digits (Talmor et al., 2020).

To enhance the performance of LMs on knowledge-intensive NLG tasks[1], prior studies have proposed to re-train LMs with knowledge-aware objectives (Zhou et al., 2020; Xiong et al., 2020; Zhang et al., 2019) or add special architectures to encode knowledge (Bosselut et al., 2019; Logan et al., 2019; Peters et al., 2019b) from external resources (e.g., knowledge graphs such as CONCEPTNET (Speer et al., 2017) and ATOMIC (Sap et al., 2019)). These methods, though yielding impressive results on many downstream tasks, can be computationally expensive. More importantly, knowledge *implicitly* parameterized in LM architectures is difficult to revise and expand (Lewis et al., 2020b), and wrong generations are hard to diagnose due to lack of interpretation (Talmor et al., 2020), which heavily limits their real-world applications.

More recent retrieval-based models try to tackle these problems by augmenting inputs with retrieved knowledge evidence (Lee et al., 2019; Guu et al., 2020). For example, RAG (Lewis et al., 2020b) lever-

---

[1]We define knowledge-intensive NLG tasks as those whose input context alone does not provide complete knowledge for a legitimate and plausible generation. Knowledge-intensive NLG tasks are a central focus of many related works (Xiong et al., 2020; Zhou et al., 2020; Lewis et al., 2020b).

ages non-parametric memory to access extensive knowledge (in the form of unstructured documents), and jointly fine-tunes a parametric LM (i.e., BART (Lewis et al., 2020a)) to enable knowledge-aware generation. A key limitation of such methods is that they retrieve documents only once while grounding them in the input *static* context, and thus cannot support the *dynamic* nature of the context as new tokens are generated. The static knowledge becomes a major problem for tasks where longer and abstractive generation is expected, such as open-ended story generation (Mostafazadeh et al., 2016), multi-turn dialogues (Zhao et al., 2020), and conversation summarization (Gliwa et al., 2019). Moreover, in a recent study, Krishna et al. (2021) replaced the knowledge retriever in RAG with a random retriever and found little difference in the resulting performance on a long-form QA task named ELI5 (Fan et al., 2019b), indicating the model may not be actually grounding its text generation to the retrieved documents.

To address these limitations, in this work, we present a novel decoding algorithm KID, aiming to better infuse knowledge into generation in a dynamic manner. Instead of solely relying on the *static* knowledge retrieved at beginning, during each step of LM decoding, KID *dynamically* searches promising continuation from retrieved knowledge, to guide the current step generation. Specifically, KID maintains a local knowledge memory, interacts it with a knowledge trie dynamically created from retrieved supporting documents, and updates the local memory as a knowledge-aware constraint to guide the generation. The key intuition behind KID is that existing LM pre-training objectives are usually defined at the token level yet do not explicitly model concept-centric knowledge (Xiong et al., 2020) — thus motivating us to reshape the probability mass at each step decoding towards the distribution of entities in knowledge.

The contributions of this work are three-fold: *First*, we introduce KID as a model and task agnostic decoding method that integrates knowledge on the fly and can be applied to various knowledge-intensive tasks with different generative LMs. *Second*, from a docoding perspective, on six knowledge-intensive NLG tasks, GPT2 (Radford et al., 2019) and BART (Lewis et al., 2020a) equipped with KID significantly outperform conventional beam search or sampling decoding by a large margin. *Third*, from a knowledge infusion perspective, unlike six strong knowledge-infusion baselines which require either additional retraining or special architecture modifications, KID leverages knowledge more effectively as a light-weight knowledge infusion solution. Additionally, in few-shot scenarios KID significantly improves over them, demonstrating its generalization ability in low-resource and domain shifting regimes.

## 2    RELATED WORK

We briefly review existing work enhancing LMs with external knowledge and representative decoding algorithms for generation.

**Enhancing Language Model with Knowledge.** Large language models implicitly encode knowledge in their parameters but with limits (Petroni et al., 2019; Kassner & Schütze, 2020; Lin et al., 2020a). Several architectures and objective functions have been proposed to explicitly encode external knowledge (Sun et al., 2020; Logan et al., 2019; Roberts et al., 2020; Levine et al., 2020), or to augment LM pre-training data with retrieved knowledge (Lewis et al., 2020b; Guu et al., 2020; Lee et al., 2019). However, Talmor et al. (2020) notes that the reasoning ability of such LMs is strongly tied to the context seen during pre-training and is thus hard to generalize to new domains. Built on LMs, KID incorporates extra knowledge from external resources (Wikipedia) and thus shows strong performance in knowledge-intensive NLG tasks.

**Better Decoding Algorithm.** Two common strategies dominate the decoding algorithms used by most generative models: beam search which maximizes likelihood in a local horizon (due to finite beam size), and sampling decoding (e.g., top-$k$ sampling (Fan et al., 2018; Holtzman et al., 2018)) which relies on randomness. Holtzman et al. (2020) find beam search often produces generic and repetitive generation, while top-$k$ sampling tends to pick unlikely tokens which creates incoherent and unrelated sequences. Existing attempts to mitigate these problems include reranking (Adiwardana et al., 2020; Shao et al., 2017), adding control signals (Zhang et al., 2018; Xing et al., 2017), and self-adaptive truncation (Welleck et al., 2020; Peters et al., 2019a). None of these decoding algorithms consider integrating knowledge in the generation process. Reflective decoding (West et al., 2021) and DeLorean (Qin et al., 2020) are two recent decoding algorithms that focus on abductive

commonsense reasoning. Reflective decoding in particular has the potential to be extended to other knowledge-intensive tasks. We compare it with KID in our experiments.

## 3  KNOWLEDGE INFUSED DECODING

We detail the implementation of KID in this section. As shown in Figure 1, KID comprises of three steps: retrieving relevant knowledge (§3.1), constructing external and local knowledge memory (§3.2), and guiding current step decoding under the constraint of the knowledge trie (§3.3).

### 3.1  RETRIEVING EXTENSIVE KNOWLEDGE FROM WIKIPEDIA

The first step of KID is to retrieve several context-relevant documents to ground the following generation. We use DPR (Karpukhin et al., 2020) as our general-purpose knowledge retriever, which projects contexts and relevant documents to a 768-dim shared embedding space using a bi-encoder network (i.e., two independent BERTs (Devlin et al., 2019)). Here, the documents refer to the 100-word chunks of Wikipedia passages released by RAG (Lewis et al., 2020b), a total of 21M documents as our knowledge source $\mathbb{Z}$. We pre-load the weights from the latest checkpoint of DPR (March 2021), as it improves retrieval performance by using mined negative samples and contrastive learning, which is also suggested by Jernite (2020). During retrieval, we perform a maximum inner-product search (MIPS) with faiss[2] accelerated by GPU (Johnson et al., 2019). Formally, we retrieve $k$ most relevant document $z_{[1,...,k]} \in \mathbb{Z}$ of context $x_{\text{context}}$ as:

$$z_{[1,...,k]} = \left\{ z_i \in \mathbb{Z} | \text{topk} \left\{ \text{BERT}(x_{\text{context}})^\top \cdot \text{BERT}(z_i) \right\} \right\} \quad (1)$$

where $\text{BERT}(\cdot)$ means the vectors encoded by BERT. The number of retrieved documents $k$ is a task-specific hyper-parameter—we discuss its impact on performance in §4.3.

### 3.2  CONSTRUCTING EXTERNAL AND LOCAL KNOWLEDGE MEMORIES

We convert multi-document input retrieved from previous step into compressed knowledge memories, in order to 1) allow relevant knowledge to be easily identified, 2) reduce the memory footprint of the knowledge, whose size grows linearly with the number of retrieved documents.

Following design choice of previous successful methods (Bosselut et al., 2021; Huang et al., 2020; Fan et al., 2019a), we adopt co-reference resolution and open information extraction (OpenIE) (Stanovsky et al., 2018) to convert plain text into triplet form[3]. For example, knowledge statement like *"Iceland is a Nordic island country in the North Atlantic Ocean and it is the most sparsely populated country in Europe."* will be converted to **subject-relation-object** triplets such as ⟨***subj***:Iceland, ***rel***:is, ***obj***:Nordic island country⟩, ⟨***subj***:Iceland, ***rel***:is, ***obj***:most sparsely populated country in Europe⟩, etc. To account for overlapping elements from these triplets, we use a prefix tree (namely Knowledge Trie $G_{\text{ext}}$) to store and organize the extracted triplets, by setting the subject in each triplet as the key in the $G_{\text{ext}}$. Note that unlike common character-level dictionary tries (Chen et al., 2020; Germann et al., 2009), in $G_{\text{ext}}$ each triplet is stored in token unit as our goal is to efficiently query and traverse the knowledge triplets stored in it.

A tree structure encoding knowledge is appealing to knowledge intensive NLG tasks, since 1) the *non-cyclic* structure helps reduce repetitions in generations, and 2) querying a prefix tree can be efficiently completed in constant time ($O(|x_{\text{context}}|)$) which does not involve any costly traversal on the graph (Ji et al., 2020; Zhang et al., 2020a), regardless of the scale of grounding knowledge (normally $|x_{\text{context}}| \ll |k$ Wiki docs$|$). We also maintain a local memory $G_{\text{loc}}$ that records all the mentioned *nouns* and *verbs* in current context[4], to focus on concept-centric knowledge (Zhou et al., 2020; Lin et al., 2020b).

---

[2]The faiss project can be found here: https://github.com/facebookresearch/faiss.

[3]As an empirical trick we also remove the stop words in the documents as they seldom carry knowledge.

[4]We tag *nous* and *verbs* with flair POS: https://huggingface.co/flair/pos-english.

**Step 1**. Knowledge Retrieval   **Step 2**. KG Construction   **Step 3**. Interaction Guided Decoding

Figure 1: Overview of our KID decoding algorithm. For a given context $x_{\text{context}}$, we first retrieve $k$ most relevant Wikipedia documents $z_{[1,\dots,k]}$ with a knowledge retriever (Step 1), and then convert them into compressed knowledge trie $G_{\text{ext}}$ (Step 2). Meanwhile, the local memory $G_{\text{loc}}$ will keep track of concept mentions in current context, and in the final step (Step 3), it will continuously query the knowledge trie with max number of hops $h_{\text{max}}$ (also serves as the window size of $G_{\text{loc}}$). Current step LM decoding will be guided by the query results with policy gradient, to generate new token $y_i$.

### 3.3 Knowledge Trie Constrained Decoding via Policy Gradient

**Background.**   Current generative LMs are trained to maximize the probability of generating ground-truth tokens at each decoding step. Assuming $\boldsymbol{y}_{1:T}^* = \{y_1^*, y_2^*, ..., y_T^*\}$ is the ground-truth output sequence for a given context $x_{\text{context}}$, the MLE objective minimizes the following loss:

$$J_{\text{MLE}} = -\sum_{i=1}^{T} \log p(y_t^* | y_1^*, ..., y_{t-1}^*, x_{\text{context}}) . \tag{2}$$

In knowledge-intensive NLG tasks, however, it is reported that the MLE training goal does not explicitly model knowledge, and thus the LM often produces counterfactual generation by surface-level misguidance (Zhou et al., 2020; Petroni et al., 2019). Furthermore, the teacher-forcing algorithm used by MLE training leads to the exposure bias problem (Ranzato et al., 2016), as the LM has access to ground truth sequence up to the next token during training, but does not have such signal during testing, which causes accumulated errors when generating longer sequence (Paulus et al., 2018). Both problems heavily limit the performance of popular LMs on diverse knowledge-intensive NLG tasks. One remedy is to learn a generation *policy* that not only maximizes knowledge correctness but also alleviates exposure bias in longer generation, which can be made possible with policy gradient in reinforcement learning (RL).

**Knowledge Trie Constrained Decoding.**   To formulate NLG as a RL problem, we define the *state* as the generated tokens before $t$ (i.e., $s_t = y_{<t}$), and the *action* as the current step output token (i.e., $a_t = y_t$). The softmax output of the language modeling head, i.e., a categorical distribution $p_t$ over the entire vocabulary, is considered as the policy $\pi_t$ for picking token $y_t$ (action $a_t$) given the state $s_t = y_{<t}$ (Guo et al., 2021; Liu et al., 2020). Note that $p_t$ (i.e., $\pi_t$) could be from either a pre-trained LM or a LM fine-tuned with task data. While conventional sampling decoding and beam search pick next token directly from $p_t$, here we look to inject knowledge to adjust $p_t$ to guide decoding.

For current input context $x_{\text{context}}$ at step $t$, we first take its concept mentions in local memory $\{c_1, c_2, ..., c_m\} \subset G_{\text{loc}}$, and then query the knowledge trie $G_{\text{ext}}$ with these concepts by max hops of $h_{\text{max}}$. The union of queried results of all hops $\mathbb{V}_i = \{v_1^i, v_2^i, ..., v_n^i\}$ for $i = 1, .., h_{\text{max}}$ then serve as knowledge demonstrations for current step generation. To put probability mass on tokens aligning with these demonstrations, we compute the $t$-th step knowledge gain $r_t$ as the total log probability of all retrieved tokens from $G_{\text{ext}}$ under decoding policy $\pi_t$ as $r_t = \sum_{i=1}^{h_{\text{max}}} \sum_{v \in \mathbb{V}_i} \mathbb{I}[v]^\top \cdot \log \pi_t$, where $\mathbb{I}[\cdot]$ is the indicator function that will output an one-hot vector with a 1 in the coordinate of token $v$ in the vocabulary and 0's elsewhere. With $r_t$, we define the $t$-th step reward $J_{\text{RL},t}$ on trajectories $\tau$ induced by $\pi_t$ as:

$$J_{\text{RL},t} = \mathbb{E}_{\tau \sim \pi_t} \left( \frac{\pi_t^*(a_t|s_t)}{\pi_t(a_t|s_t)} \cdot r_t \right) - \beta \text{KL}(\pi_t || \pi_t^*) , \tag{3}$$

where $\pi_t^*$ is the desired policy (a vector initialized from $\pi_t$) to produce tokens approaching knowledge demonstrations, and the KL penalty term $\text{KL}(\pi_t||\pi_t^*)$ is to avoid the updated policy drifts too much away from the original one, also known as *trust region* constraint (Schulman et al., 2017; 2015). Note that we use off-policy sampling to collect trajectories, with an importance weight $\pi_t^*/\pi_t$ to calibrate the knowledge gain $r_t$, which can stabilize the optimization (Munos et al., 2016).

---

**Algorithm 1:** Trie-Constrained Policy Gradient

---

**for** $t = 1, 2, \ldots$ **do**

  Collect samples $(a_t|s_t)$ by vanilla policy $\pi_t$;
  Compute reward $J_{\text{RL},t}$ by Eq. (3);
  Compute updated policy
   $\pi_t^* \leftarrow \arg\max_{\pi_t^*} J_{\text{RL},t}$ by taking $K = 3$
   steps of SGD (via Adam);
  **if** $\text{KL}(\pi_t||\pi_t^*) \geq 2\sigma$ **then**
   | $\beta_{t+1} = 2\beta_t$;
  **else if** $\text{KL}(\pi_t||\pi_t^*) \leq \sigma/2$ **then**
   | $\beta_{t+1} = \beta_t/2$;
  **end**
  Generate token $y_t$ with updated policy $\pi_t^*$;

**end**

---

Algorithm 1 shows how we obtain the updated policy through policy gradient. We set $\beta$ dynamically to control the KL penalty within the reward function. The target divergence $\sigma$ tunes the strength of knowledge infusion—smaller $\sigma$ means less infusion while larger $\sigma$ provides more space for policy gradient (We set $\sigma$ to 0.02 across all tasks). To generate the actual token for step $t$, we pick from the updated policy $\pi_t^*$ with sampling decoding. The token should conform to the knowledge demonstrations, since its corresponding hidden states have shifted towards $\mathbb{V}$ due to policy gradient.

Prior approaches have also explored to set sequence-level metrics such as BLEU (Papineni et al., 2002) as the reward to directly optimize the generation quality (Li et al., 2016; Paulus et al., 2018). However, many studies report such sparse reward will cause low efficiency optimization (i.e., $J_t = 0$, $\forall t < T$) (Guo et al., 2021). Our trie-constrained policy gradient method seemingly mitigates this problem by using an immediate reward ($J_{\text{RL}}^{\theta*}$) at each step with reasonable approximation. Recent off-line RL for NLG work show promising results when using data itself (rather than metrics) to estimate rewards (Pang & He, 2020; Jaques et al., 2020)—our design of knowledge trie echoes their findings. The gold data distribution memorized in trie is treated as guidance to reshape each step probability distribution, and thus brings benefits on alleviating exposure bias during long generation.

## 4 EXPERIMENTS

### 4.1 EXPERIMENTS SETTINGS

We consider three diverse types of knowledge-intensive tasks for evaluation:

**Abstractive Question Answering.** We study Abstractive QA, which requires the model to *generate* free-form answers to the questions. We choose long-form QA task ELI5 (Fan et al., 2019b) and MSMARCO NLG task v2.1 (Nguyen et al., 2016) as two commonsense QA tasks whose questions can be mostly answered by referring to Wikipedia passages. We also use two extra QA tasks PIQA (Bisk et al., 2020) and PubMedQA (Jin et al., 2019) whose questions require domain-specific knowledge to answer (i.e., physical interaction knowledge for PIQA, and medical knowledge for PubMedQA). We calculate BLEU-1 and ROUGE-L scores to be able to compare directly with related work (Lewis et al., 2020b; Krishna et al., 2021).

**Logic-centric Writing.** We also investigate whether KID can benefit NLG tasks that do not have an explicit query form for certain knowledge (i.e., with specific questions, like QA tasks). We study ROC story ending generation (Mostafazadeh et al., 2016), which requires generating a legitimate ending given a four-sentence context, and $\alpha$NLG (Bhagavatula et al., 2020) which requires generating reasonable hypothesis given two observations. We follow related work and NLG leaderboards (Zhou et al., 2020; Guan et al., 2020) in using BLEU-1 and ROUGE-L as evaluation metrics.

**Dialogue Generation.** Chitchat dialogues are normally multi-turn discussions over a variety of topics or concepts, which often involve topical and factual knowledge (Petroni et al., 2021). We study two dialogue datasets that require knowledge grounding: Wizard of Wikipedia (WoW) (Dinan et al., 2019), where the speaker in the conversation must ground their utterances in Wikipedia passages, and

Table 1: Benchmark results on six diverse knowledge-intensive tasks. Compared with beam search (Beam) and sampling decoding (Sample), KID decoding improves the generation quality in general (by at most 15%). For each LM, we report their performance in zero-shot setting (*), and that of being fine-tuned (FT). We color (▨▨▨) those results of KID that achieve > 5% improvement over the next-best performance. We also annotate the performance reported by published state-of-the-art models to date (- means missing official reports).

| Existing Method | ELI5 | | MSMARCO | | ROC | | $\alpha$NLG | | WoW | | MuTual | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | B-1 | R-L | B-1 | R-L | B-1 | R-L | B-1 | R-L | F-1 | R-L | MRR$_G$ | R-L |
| **GPT2-M** [345M]* | 14.6 | 16.1 | 28.8 | 24.5 | 12.0 | 13.9 | 13.2 | 15.0 | 9.3 | 10.8 | 29.7 | 7.1 |
| - FT + Beam | 22.9 | 24.6 | 44.1 | 44.3 | 26.4 | 20.6 | 19.4 | 25.7 | 10.3 | 12.1 | 47.9 | 11.3 |
| - FT + Sampling | 23.8 | 25.4 | 46.2 | 44.4 | 26.0 | 20.0 | 18.9 | 25.1 | 12.6 | 11.9 | 51.6 | 20.3 |
| - FT + KID | **27.9** | **26.6** | **47.4** | **47.8** | **28.1** | **21.2** | **21.7** | **26.9** | **16.4** | **15.9** | **53.3** | **22.4** |
| **BART-L** [406M]* | 21.4 | 20.6 | 19.1 | 13.8 | 12.5 | 16.7 | 24.6 | 28.0 | 8.1 | 8.5 | 35.1 | 12.9 |
| - FT + Beam | 25.6 | 24.7 | 44.5 | 44.6 | 22.3 | 20.2 | 31.9 | 34.1 | 10.9 | 11.9 | 49.2 | 20.6 |
| - FT + Sampling | 25.8 | 25.1 | 48.4 | 47.3 | 24.4 | 20.9 | 30.5 | 33.6 | 12.2 | 15.0 | 53.7 | 20.4 |
| - FT + KID | **27.4** | **26.3** | **51.9** | **48.1** | **26.5** | **21.3** | **33.4** | **35.6** | **18.7** | **16.6** | **54.5** | **22.7** |
| **Published SotA**$^\diamond$ | - | 26.2 | - | 49.6 | 26.3 | 20.8 | - | 45.0 | 13.5 | 15.5 | - | - |

MuTual (Cui et al., 2020), where utterances have to be a logically-coherent continuation of the given multi-turn context. We follow existing work and the leaderboard of WoW in using F-1/ROUGE-L for WoW and MRR/ROUGE-L for MuTual evaluations.

We take two types of generative language models (LMs) as representatives to demonstrate the effectiveness of KID: 1) Auto-Regressive LMs, such as GPT-2 (Radford et al., 2019), GPT-3 (Brown et al., 2020), and 2) Text2Text LMs, such as BART (Lewis et al., 2020a), T5 (Raffel et al., 2020). Specifically, we choose GPT2-medium and BART-large because of their comparable sizes (345M vs 406M). We also compare with other baseline models with KID in §4.2. We tune the hyperparameters based on the models' performance on an in-house split dev set, and report the results that were best on the official dev set[5]. Code for KID will be made publicly available.

## 4.2 MAIN RESULTS ON DECODING PERFORMANCE

**Comparison with off-the-shelf decoding methods.** Table 1 compares the results of GPT2-medium and BART-large on six diverse NLG tasks with beam search (Beam), sampling (Sampling), and our proposed KID decoding algorithm. Compared with the other two commonly used decoding algorithms, knowledge-guided KID achieves better results for all the cases, with significant improvements (with p-value $p < 0.01$) over the next-best decoding strategy (e.g., 4.1 absolute increase for BLEU-1 in ELI5 (GPT2), and 6.5 for BLEU-1 in $\alpha$NLG (BART)). We also notice that KID brings greater improvements to auto-regressive language models – above 5% improvement in 9 out of 12 metrics for GPT2-medium, in contrast to 7 out of 12 for text2text language model (BART-large). The reason could be that the reinforcement learning objective of KID is more similar to the MLE objective of GPT2 than the denoising objective of BART (Pang & He, 2020; Guo et al., 2021). Compared with task-specific state-of-the-art models[6], task-agnostic LMs armed with KID can beat SOTA results on three different tasks (ELI5, ROC, WoW), which is not possible when beam search and sampling decoding is used. This interesting observation demonstrates a huge potential in inference-time optimization, which we believe is worth exploring further.

**Comparison with existing knowledge-infusion methods.** Besides evaluating KID from a pure decoding perspective, we also compare KID with existing methods of integrating knowledge for knowledge-intensive NLG tasks. In addition to ELI5 and MSMARCO, we also evaluate on two

---

[5]For sampling decoding, we run experiments with all combinations of top-$p$ ($p \in [0, 0.1, ..., 1]$) and top-$k$ ($k \in [0, 10, ..., 100]$), while for beam search, we sweep the number of beams from 1 to 10. With the updated decoding policy, KID uses sampling decoding (with similar search to get optimum $p$ and $k$) to pick actual tokens.

[6]Published SotA models to date (October 2021): ELI5 (RAG (Lewis et al., 2020b)), MSMARCO (Masque (Nishida et al., 2019)), ROC(Knowledge-enhanced GPT2 (Guan et al., 2020)), $\alpha$NLG (T5 (Raffel et al., 2019)), WoW (BART+DPR (Petroni et al., 2021)), and MuTual (Human Performance (Cui et al., 2020)). The information mainly comes from corresponding leaderboards.

Table 2: Performance of 6 related works on Wiki-answerable ELI5 and MSMARCO, and out-of-domain PIQA and PubMedQA QA tasks. We report ROUGE-L score with 10% and 100% of the training data. As a model-agnostic method, KID shows particularly strong performance in few-shot scenarios, which can better help LMs transfer to new domain with minimum training data.

| Method / Available FT Data | ELI5 | | MSMARCO | | PIQA | | PubMedQA | |
|---|---|---|---|---|---|---|---|---|
| | 10% | 100% | 10% | 100% | 10% | 100% | 10% | 100% |
| **GPT2 + Knowledge** (KG Triplets Post-train; 2020) | 9.3 | 15.7 | 15.9 | 31.3 | _7.5_ | 16.2 | 3.6 | 8.4 |
| **GRF** (Multi-Hop Flow on KG; 2020) | 12.9 | 18.0 | 16.4 | 37.9 | 4.0 | 10.9 | 6.8 | 9.1 |
| **GPT2 + COMeT Emb.** (KG Embedding Fuse; 2020) | _13.4_ | 17.3 | _19.7_ | 33.7 | 6.4 | 16.5 | 4.5 | 5.8 |
| **RAG** (Wiki Retrieval Augmented; 2020b) | 5.7 | _21.4_ | 15.7 | _40.8_ | 3.2 | 17.3 | 1.2 | 6.7 |
| **QA-GNN** (GNN + Attention; 2021) | 6.2 | 19.5 | 13.5 | 40.5 | 6.3 | **19.1** | _7.8_ | **11.7** |
| **ReFlective** (Forward + Backward LMs; 2021) | 8.7 | 18.2 | 14.7 | 34.5 | 5.9 | 16.7 | 4.1 | 9.2 |
| **Ours:** KID (with GPT2-medium) | **15.2** | **26.6** | **26.1** | **47.8** | **10.5** | _18.4_ | **9.9** | _11.5_ |

extra QA tasks: PIQA and PubMedQA (discussed in §4.1), where answers are considered to be *not* fully covered by Wiki knowledge. Besides RAG (Lewis et al., 2020b), we consider several competitive prior methods incorporating knowledge including a) **GPT2 + Knowledge** (Guan et al., 2020), which post-trains GPT2 on triplets-converted augmentation data (e.g., ⟨*helium*, *is*, *gas*⟩ → *"helium is gas."*); b) **GPT2 + COMeT Embeddings**, which fuses knowledge-aware embeddings (e.g., from CoMET (Bosselut et al., 2019); c) **QA-GNN** (Yasunaga et al., 2021), which traverses a graph neural network; d) **GRF** (Ji et al., 2020), which leverages attentions from GNN; e) **Reflective** decoding (West et al., 2021), which relies on forward and backward LMs to encode bi-directional context for generation.

As shown in Table 2 (columns with 100% training data), overall KID significantly outperforms all other methods on ELI5 and MSMARCO with 5.2 and 7.0 ROUGE-L points improvements over second-best method (RAG) respectively, and it performs comparably with the best performing method (QA-GNN) on PIQA and PubMedQA. Note that unlike QA-GNN, KID doesn't require specific model architecture to integrate knowledge for generation because of its decoding nature. For baselines, **GPT2+Knowledge** seems to bring benefits to tasks requiring physical knowledge, but the rigid conversion limits the LM's generation ability in tasks whose expressions are more diverse (e.g., ELI5); concatenating knowledge-aware embeddings as extra encoding (**GPT2+COMeT** also leads to limited performance.

We also evaluate on a few-shot setting, where only 10% of task training data is available to mimic domains for which ample training data in unavailable or difficult to acquire in practice. This settings also tests a method's ability to transfer to new domain and generalize to unseen entities, concepts or events. Also shown in Table 2, KID with a LM similar in size to the baselines (GPT2-medium) achieves best few-shot performance in all four tasks, including PIQA and PubMedQA. Our experiments find baseline methods tend to generate off-topic and hallucinatory answers when the expected answer length is long (e.g., ELI5 and PIQA). RAG shows limited performance in few-shot scenarios, due to its static knowledge retrieved by initial context cannot be generalized to newly generated tokens. KID, instead, dynamically searches references for grounding, thus showing more agility in unfamiliar context.

## 4.3  ABLATION STUDIES FOR THE BEST PERFORMING KID

**How to choose retriever?** We experiment with replacing the default DPR document retriever of KID, with popular retrievers including the TF-IDF retriever from DrQA (Chen et al., 2017), and the Wiki retriever used in BLINK (Wu et al., 2020). We also experiment with a random retriever baseline that retrieves documents randomly given the context. We choose two tasks ELI5 and WoW that provide ground-truth knowledge provenance, which are also the only two KILT tasks requiring long and abstractive generation (Petroni et al., 2021). Following KILT benchmarking metrics, we use precision@1 (Prec@1) to measure the top-1 retrieval accuracy, and ROUGE-L (R-L) to evaluate generation quality. We also consider directly measuring how much knowledge in the ground-truth

Figure 2: Impact of hyperparameters on KID's ELI5 performance when (a) more documents are retrieved, and (b) more hops taken when querying the knowledge trie. (c) Average human ratings on different-length sequences generated by KID, sampling, beam search, and reflective decoding. KID generation has more stable quality across lengths by restraining exposure bias.

evidence (provenance) appear in the actual generation. We compute knowledge Coverage (Cov) (used in Guan et al. (2020)) which is the 1-gram overlap between the triplets of provenance and the generation, to measure the extent to which our generation is actually using the retrieved knowledge.

Table 3 shows the corresponding results. For reference, RAG obtains nearly equivalent performance (R-L and Cov) with random retriever and the DPR[FT][7], which indicates its generation mainly relies on the fine-tuned BART and ignores retrieved knowledge (also observed in Krishna et al. (2021)). In contrast, KID with the default DPR retriever outperforms all other retrievers and RAG variants in retrieval accuracy (Prec@1), knowledge coverage (Cov) and final generation quality (R-L). We observe high correlation between (Cov, R-L) and Prec@1, indicating that a good knowledge retrieval is essential for knowledge-intensive NLG tasks.

Table 3: A closer comparison of BART-L with KID and RAG (Lewis et al., 2020b) which also leverages retrieved Wikipedia passages as knowledge. We switch between different retrievers to study its impact on retrieval accuracy (Prec@1), generation quality (R-L), and knowledge coverage (Cov).

|  | ELI5 | | | WoW | | |
|---|---|---|---|---|---|---|
|  | Prec@1 | R-L | Cov | Prec@1 | R-L | Cov |
| RAG w/. Random | 3.4 | 21.3 | 2.62 | 15.6 | 10.4 | 9.12 |
| RAG w/. DPR[FT] | 16.7 | 21.4 | 2.68 | 26.3 | 11.8 | 11.8 |
| KID w/. Random | 3.4 | 16.5 | 1.34 | 15.6 | 9.5 | 7.79 |
| KID w/. TF-IDF | 11.0 | 20.9 | 3.88 | 41.9 | 15.4 | 12.8 |
| KID w/. BLINK | 8.9 | 21.5 | 2.87 | 24.3 | 10.0 | 8.31 |
| KID w/. DPR (default) | 17.3 | 26.3 | 4.39 | 45.5 | 16.6 | 15.7 |

Table 4: The performance (R-L) on ELI5 of LMs with different sizes (similar architecture). Vanilla LMs (*) benefit more with KID than the fine-tuned ones (FT). (The absolute gain over the next-best is annotated.)

|  | ELI5 | | |
|---|---|---|---|
| **Model** | Beam | Sample | KID |
| GPT2-M* | 16.0 | 16.1 | 20.2▲4.1 |
| GPT2-M[FT] | 24.6 | 25.4 | 26.6▲1.2 |
| GPT3-1.3B* | 21.7 | 22.0 | 24.5▲2.5 |
| GPT3-1.3B[FT] | 24.9 | 25.5 | 26.6▲1.1 |
| GPT3-2.7B* | 22.8 | 24.6 | 26.7▲2.1 |

**How much knowledge do we need?** We also study the impact of *number of documents* ($k$) we retrieve and number of hops ($h_{max}$) we use to query the knowledge trie, two factors that determine how much knowledge we use to ground the generation. As shown in Figure 2 (a) and (b), for the example task ELI5, we find the generation performance measured by ROUGE-L does not benefit from simply more retrieved documents—an optimum $k$ is 5 through empirical observation, and similarly, $h_{max} = 4$ brings best performance. A larger $k$ might risk retrieving less relevant Wiki documents and a larger hop $h_{max}$ with deeper traverse through the knowledge trie tends to bring in off-topic knowledge. We also plot the average time consumed for generating each sentence as reference (the second $y$-axis in Figure 2 (a) and (b)), which demonstrate the best performing $k = 5$ and $h_{max} = 4$ achieve a reasonable trade-off between generation quality and decoding speed.

In Figure 2 (c), we quantify the exposure bias problem through human judgements. We first sample 200 ELI5 test set questions and generate answers of various lengths $\{80, 100, ..., 260\}$ (260 is the average sequence length in training set) with beam search, sampling, reflective (West et al., 2021), and KID. We then ask humans to rate these generations with 7-point Likert scoring (Joshi et al., 2015) how likely the generated text is a natural sentence. Each generation receives at least 15 ratings. We

---

[7]RAG fine-tunes the query encoder of DPR with BART, which differs the off-the-shelf DPR used in KID.

Table 5: Human assessments of generation in terms of Relevance and Factuality on a 7-point Likert scale. We run paired sample $t$-test comparing human references (Gold) with beam search (BM) with beam size 5, sampling (SP) with top $p = 0.9$ and $k = 20$, reflective (RFLC) decoding, and our KID generation. $p$ value describes the significance of difference from Gold. (* corresponds to $p$-value< 0.05 and ** to 0.01.)

| | | ELI5 | | | | | aNLG | | | | | WoW | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Gold | BM | SP | RFLC | **KID** | Gold | BM | SP | RFLC | **KID** | Gold | BM | SP | RFLC | **KID** |
| **Relevance** | Mean | 5.14 | 4.51 | 4.97 | 4.73 | 5.07 | 5.42 | 5.22 | 5.10 | 5.27 | 5.36 | 4.62 | 4.68 | 4.44 | 4.35 | 4.57 |
| | $p$-value | - | .00** | .10 | .03* | .30 | - | .14 | .02* | .17 | .23 | - | .12 | .10 | .06 | .30 |
| **Factuality** | Mean | 4.95 | 4.37 | 4.61 | 4.23 | 4.87 | 5.35 | 5.17 | 5.19 | 5.25 | 5.30 | 4.72 | 4.20 | 4.38 | 4.41 | 4.53 |
| | $p$-value | - | .14 | .00** | .00** | .24 | - | .05 | .06 | .30 | .41 | - | .00** | .06* | .15 | .29 |

observe that both beam search and sampling methods suffer from the exposure bias problem[8], since their ratings deteriorate as the length grows. Reflective decoding exhibits similar trend since it stills relies on MLE training. KID, instead, dynamically infuses global knowledge with LM predictions at each step and thus can mitigate exposure bias by imitating non-local demonstrations.

**Does the size of LM matter?** We run experiments with different sizes of LMs that have the similar architecture (GPT2-medium, and GPT3 with 1.3B, and 2.7B parameters[9]). Table 4 shows that overall larger LMs benefits all decoding methods with KID consistently outperforming Beam search and sampling decoding. In addition, KID brings more gain for non-finetuned LMs than fine-tuned ones, potentially because the fine-tuning LM is already fit onto the new domain thus less knowledge infusion is needed. Interestingly with KID, vanilla GPT3-2.7B outperforms its 1.3B fine-tuned counterpart, which is especially meaningful since ever-large foundation models (Bommasani et al., 2021) are expensive to fine-tune effectively on common hardware settings (Liu et al., 2021).

## 4.4 HUMAN EVALUATION

We recruited 300 MTurk participants to manually examine generated outputs of several decoding algorithm for 1) **Relevance** (i.e., *"What's the relevance level between the generated text and the given context?"* Answer is from 1-*totally not relevant* to 7-*totally relevant*), and 2) **Factuality** (i.e., *"What's the factuality level of the generated text?"* Answer is from 1-*totally not factual* to 7-*very well factual*). Each participant was asked to review five sample generations without revealing their source. We used paired samples $t$-tests to examine the difference between human references and other decoding methods generation. As Table 5 shows, KID generates similar quality sequences as human references without significant differences across all three tasks, while in ELI5, beam search and reflective decoding generation are rated significantly low in both relevance and factuality, partially due to exposure bias in longer generation.

## 5 CONCLUSIONS AND FUTURE WORK

In this work, we proposed KID, a novel decoding algorithm which in each step of decoding dynamically fetches knowledge and guides token decoding via interaction between a local knowledge memory and a constructed external knowledge trie. Given its decoding nature, KID doesn't require architecture changes to existing LMs and is applicable to various generative LMs. Evaluations on six knowledge-intensive NLG tasks demonstrated the effectiveness of KID and that its generations are aligned with human references in terms of relevance and factual correctness. In addition, KID is also found to alleviate exposure bias and maintain quality for long generations.

Future work of KID could study more efficient data structures to accelerate knowledge fetching and integration. One could also investigate combining KID with prompt based generations to further boost the performance, especially in the few-shot settings. Another direction is to further study the integration of KID with full size foundation models, like GPT-3 175B to understand KID's potential.

---

[8]We use beam size 5 for beam search, and top $p = 0.9$ and $k = 20$ for sampling decoding, as they yield best ROUGE-L score during automatic evaluation.

[9]We adopt the public implementation of GPT3—GPT-Neo (github.com/EleutherAI/gpt-neo).

## ETHICS AND REPRODUCIBILITY STATEMENT

The goal of KID is to provide a general-purpose knowledge infusing decoding algorithm by leveraging retrieved Wikipedia documents. Still, the generation of KID can be affected by certain biases from the LM it is based on though those biases may be partially mitigated by the knowledge demonstrations. Another major ethical consideration is that KID can mimic undesirable attributes of the target knowledge source documents that could be non-contemporary and do not represent current norms and practices—and KID has no scheme to diagnose these problems. Furthermore, our experiments and analysis are done in English, and therefore we do not claim that our findings will generalize across all languages, although our framework has potential to be extended to other languages with necessary modifications.

For reproducibility, evaluations of KID and baseline methods are all conducted on public NLG data sets. We compare results from published papers and public leaderboards. We will make the code and scripts for reproducing KID publicly available on GitHub.

## REFERENCES

Daniel Adiwardana, Minh-Thang Luong, David R So, Jamie Hall, Noah Fiedel, Romal Thoppilan, Zi Yang, Apoorv Kulshreshtha, Gaurav Nemade, Yifeng Lu, et al. Towards a human-like open-domain chatbot. *arXiv preprint arXiv:2001.09977*, 2020.

Chandra Bhagavatula, Ronan Le Bras, Chaitanya Malaviya, Keisuke Sakaguchi, Ari Holtzman, Hannah Rashkin, Doug Downey, Wen-tau Yih, and Yejin Choi. Abductive commonsense reasoning. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=Byg1v1HKDB.

Yonatan Bisk, Rowan Zellers, Ronan LeBras, Jianfeng Gao, and Yejin Choi. PIQA: reasoning about physical commonsense in natural language. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pp. 7432–7439. AAAI Press, 2020. URL https://aaai.org/ojs/index.php/AAAI/article/view/6239.

Rishi Bommasani, Drew A Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, et al. On the opportunities and risks of foundation models. *arXiv preprint arXiv:2108.07258*, 2021. URL https://arxiv.org/pdf/2108.07258.pdf.

Antoine Bosselut, Hannah Rashkin, Maarten Sap, Chaitanya Malaviya, Asli Celikyilmaz, and Yejin Choi. COMET: Commonsense transformers for automatic knowledge graph construction. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 4762–4779, Florence, Italy, 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1470. URL https://www.aclweb.org/anthology/P19-1470.

Antoine Bosselut, Ronan Le Bras, and Yejin Choi. Dynamic neuro-symbolic knowledge graph construction for zero-shot commonsense question answering. In *AAAI*, pp. 4923–4931, 2021. URL https://ojs.aaai.org/index.php/AAAI/article/view/16625.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 1877–1901. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/1457c0d6bfcb4967418bfb8ac142f64a-Paper.pdf.

Danqi Chen, Adam Fisch, Jason Weston, and Antoine Bordes. Reading Wikipedia to answer open-domain questions. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1870–1879, Vancouver, Canada, 2017. Association for Computational Linguistics. doi: 10.18653/v1/P17-1171. URL https://www.aclweb.org/anthology/P17-1171.

Pinzhen Chen, Nikolay Bogoychev, Kenneth Heafield, and Faheem Kirefu. Parallel sentence mining by constrained decoding. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 1672–1678, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.152. URL https://www.aclweb.org/anthology/2020.acl-main.152.

Eric Chu and Peter J. Liu. Meansum: A neural model for unsupervised multi-document abstractive summarization. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 1223–1232. PMLR, 2019. URL http://proceedings.mlr.press/v97/chu19b.html.

Leyang Cui, Yu Wu, Shujie Liu, Yue Zhang, and Ming Zhou. MuTual: A dataset for multi-turn dialogue reasoning. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 1406–1416, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.130. URL https://aclanthology.org/2020.acl-main.130.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423. URL https://www.aclweb.org/anthology/N19-1423.

Emily Dinan, Stephen Roller, Kurt Shuster, Angela Fan, Michael Auli, and Jason Weston. Wizard of wikipedia: Knowledge-powered conversational agents. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019. URL https://openreview.net/forum?id=r1l73iRqKm.

Angela Fan, Mike Lewis, and Yann Dauphin. Hierarchical neural story generation. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 889–898, Melbourne, Australia, 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1082. URL https://www.aclweb.org/anthology/P18-1082.

Angela Fan, Claire Gardent, Chloé Braud, and Antoine Bordes. Using local knowledge graph construction to scale Seq2Seq models to multi-document inputs. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 4186–4196, Hong Kong, China, 2019a. Association for Computational Linguistics. doi: 10.18653/v1/D19-1428. URL https://www.aclweb.org/anthology/D19-1428.

Angela Fan, Yacine Jernite, Ethan Perez, David Grangier, Jason Weston, and Michael Auli. ELI5: Long form question answering. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 3558–3567, Florence, Italy, 2019b. Association for Computational Linguistics. doi: 10.18653/v1/P19-1346. URL https://www.aclweb.org/anthology/P19-1346.

Ulrich Germann, Eric Joanis, and Samuel Larkin. Tightly packed tries: How to fit large models into memory, and make them load fast, too. In *Proceedings of the Workshop on Software Engineering, Testing, and Quality Assurance for Natural Language Processing (SETQA-NLP 2009)*, pp. 31–39, Boulder, Colorado, 2009. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/W09-1505.

Bogdan Gliwa, Iwona Mochol, Maciej Biesek, and Aleksander Wawer. SAMSum corpus: A human-annotated dialogue dataset for abstractive summarization. In *Proceedings of the 2nd Workshop on*

*New Frontiers in Summarization*, pp. 70–79, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-5409. URL https://www.aclweb.org/anthology/D19-5409.

Jian Guan, Fei Huang, Zhihao Zhao, Xiaoyan Zhu, and Minlie Huang. A knowledge-enhanced pretraining model for commonsense story generation. *Transactions of the Association for Computational Linguistics*, 8:93–108, 2020. doi: 10.1162/tacl_a_00302. URL https://www.aclweb.org/anthology/2020.tacl-1.7.

Han Guo, Bowen Tan, Zhengzhong Liu, Eric P Xing, and Zhiting Hu. Text generation with efficient (soft) q-learning. *arXiv preprint arXiv:2106.07704*, 2021. URL https://arxiv.org/pdf/2106.07704.pdf.

Kelvin Guu, Kenton Lee, Zora Tung, Panupong Pasupat, and Ming-Wei Chang. Retrieval augmented language model pre-training. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pp. 3929–3938. PMLR, 2020. URL http://proceedings.mlr.press/v119/guu20a.html.

Ari Holtzman, Jan Buys, Maxwell Forbes, Antoine Bosselut, David Golub, and Yejin Choi. Learning to write with cooperative discriminators. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1638–1649, Melbourne, Australia, 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1152. URL https://www.aclweb.org/anthology/P18-1152.

Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. The curious case of neural text degeneration. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=rygGQyrFvH.

Luyang Huang, Lingfei Wu, and Lu Wang. Knowledge graph-augmented abstractive summarization with semantic-driven cloze reward. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 5094–5107, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.457. URL https://www.aclweb.org/anthology/2020.acl-main.457.

Natasha Jaques, Judy Hanwen Shen, Asma Ghandeharioun, Craig Ferguson, Agata Lapedriza, Noah Jones, Shixiang Gu, and Rosalind Picard. Human-centric dialog training via offline reinforcement learning. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 3985–4003, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.327. URL https://www.aclweb.org/anthology/2020.emnlp-main.327.

Yacine Jernite. Explain anything like i'm five: A model for open domain long form question answering, 2020. URL https://yjernite.github.io/lfqa.html.

Haozhe Ji, Pei Ke, Shaohan Huang, Furu Wei, Xiaoyan Zhu, and Minlie Huang. Language generation with multi-hop reasoning on commonsense knowledge graph. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 725–736, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.54. URL https://www.aclweb.org/anthology/2020.emnlp-main.54.

Qiao Jin, Bhuwan Dhingra, Zhengping Liu, William Cohen, and Xinghua Lu. PubMedQA: A dataset for biomedical research question answering. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 2567–2577, Hong Kong, China, 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1259. URL https://www.aclweb.org/anthology/D19-1259.

Jeff Johnson, Matthijs Douze, and Hervé Jégou. Billion-scale similarity search with gpus. *IEEE Transactions on Big Data*, 2019. URL https://ieeexplore.ieee.org/abstract/document/8733051.

Ankur Joshi, Saket Kale, Satish Chandel, and D Kumar Pal. Likert scale: Explored and explained. *British Journal of Applied Science & Technology*, 7(4):396, 2015.

Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. Dense passage retrieval for open-domain question answering. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 6769–6781, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.550. URL https://www.aclweb.org/anthology/2020.emnlp-main.550.

Nora Kassner and Hinrich Schütze. Negated and misprimed probes for pretrained language models: Birds can talk, but cannot fly. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 7811–7818, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.698. URL https://www.aclweb.org/anthology/2020.acl-main.698.

Kalpesh Krishna, Aurko Roy, and Mohit Iyyer. Hurdles to progress in long-form question answering. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 4940–4957, Online, 2021. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/2021.naacl-main.393.

Kenton Lee, Ming-Wei Chang, and Kristina Toutanova. Latent retrieval for weakly supervised open domain question answering. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 6086–6096, Florence, Italy, 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1612. URL https://www.aclweb.org/anthology/P19-1612.

Yoav Levine, Barak Lenz, Or Dagan, Ori Ram, Dan Padnos, Or Sharir, Shai Shalev-Shwartz, Amnon Shashua, and Yoav Shoham. SenseBERT: Driving some sense into BERT. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 4656–4667, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.423. URL https://www.aclweb.org/anthology/2020.acl-main.423.

Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Veselin Stoyanov, and Luke Zettlemoyer. BART: Denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 7871–7880, Online, 2020a. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.703. URL https://www.aclweb.org/anthology/2020.acl-main.703.

Patrick S. H. Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive NLP tasks. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020b. URL https://proceedings.neurips.cc/paper/2020/hash/6b493230205f780e1bc26945df7481e5-Abstract.html.

Jiwei Li, Will Monroe, Alan Ritter, Dan Jurafsky, Michel Galley, and Jianfeng Gao. Deep reinforcement learning for dialogue generation. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pp. 1192–1202, Austin, Texas, 2016. Association for Computational Linguistics. doi: 10.18653/v1/D16-1127. URL https://www.aclweb.org/anthology/D16-1127.

Bill Yuchen Lin, Seyeon Lee, Rahul Khanna, and Xiang Ren. Birds have four legs?! NumerSense: Probing Numerical Commonsense Knowledge of Pre-Trained Language Models. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 6862–6868, Online, 2020a. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.557. URL https://www.aclweb.org/anthology/2020.emnlp-main.557.

Bill Yuchen Lin, Wangchunshu Zhou, Ming Shen, Pei Zhou, Chandra Bhagavatula, Yejin Choi, and Xiang Ren. CommonGen: A constrained text generation challenge for generative commonsense reasoning. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pp. 1823–1840, Online, 2020b. Association for Computational Linguistics. doi: 10.18653/v1/2020.findings-emnlp.165. URL https://www.aclweb.org/anthology/2020.findings-emnlp.165.

Ruibo Liu, Guangxuan Xu, Chenyan Jia, Weicheng Ma, Lili Wang, and Soroush Vosoughi. Data boost: Text data augmentation through reinforcement learning guided conditional generation. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 9031–9041, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.726. URL https://www.aclweb.org/anthology/2020.emnlp-main.726.

Xiao Liu, Yanan Zheng, Zhengxiao Du, Ming Ding, Yujie Qian, Zhilin Yang, and Jie Tang. Gpt understands, too. *arXiv preprint arXiv:2103.10385*, 2021.

Robert Logan, Nelson F. Liu, Matthew E. Peters, Matt Gardner, and Sameer Singh. Barack's wife hillary: Using knowledge graphs for fact-aware language modeling. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 5962–5971, Florence, Italy, 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1598. URL https://www.aclweb.org/anthology/P19-1598.

Nasrin Mostafazadeh, Nathanael Chambers, Xiaodong He, Devi Parikh, Dhruv Batra, Lucy Vanderwende, Pushmeet Kohli, and James Allen. A corpus and cloze evaluation for deeper understanding of commonsense stories. In *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 839–849, San Diego, California, 2016. Association for Computational Linguistics. doi: 10.18653/v1/N16-1098. URL https://www.aclweb.org/anthology/N16-1098.

Rémi Munos, Tom Stepleton, Anna Harutyunyan, and Marc G. Bellemare. Safe and efficient off-policy reinforcement learning. In Daniel D. Lee, Masashi Sugiyama, Ulrike von Luxburg, Isabelle Guyon, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, pp. 1046–1054, 2016. URL https://proceedings.neurips.cc/paper/2016/hash/c3992e9a68c5ae12bd18488bc579b30d-Abstract.html.

Tri Nguyen, Mir Rosenberg, Xia Song, Jianfeng Gao, Saurabh Tiwary, Rangan Majumder, and Li Deng. Ms marco: A human generated machine reading comprehension dataset. In *CoCo@NIPS*, 2016. URL http://ceur-ws.org/Vol-1773/CoCoNIPS_2016_paper9.pdf.

Kyosuke Nishida, Itsumi Saito, Kosuke Nishida, Kazutoshi Shinoda, Atsushi Otsuka, Hisako Asano, and Junji Tomita. Multi-style generative reading comprehension. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 2273–2284, Florence, Italy, 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1220. URL https://www.aclweb.org/anthology/P19-1220.

Richard Yuanzhe Pang and He He. Text generation by learning from demonstrations. *arXiv preprint arXiv:2009.07839*, 2020. URL https://arxiv.org/pdf/2009.07839.pdf.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics*, pp. 311–318, Philadelphia, Pennsylvania, USA, July 2002. Association for Computational Linguistics. doi: 10.3115/1073083.1073135. URL https://www.aclweb.org/anthology/P02-1040.

Romain Paulus, Caiming Xiong, and Richard Socher. A deep reinforced model for abstractive summarization. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL https://openreview.net/forum?id=HkAClQgA-.

Ben Peters, Vlad Niculae, and André F. T. Martins. Sparse sequence-to-sequence models. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 1504–1519, Florence, Italy, 2019a. Association for Computational Linguistics. doi: 10.18653/v1/P19-1146. URL https://www.aclweb.org/anthology/P19-1146.

Matthew E. Peters, Mark Neumann, Robert Logan, Roy Schwartz, Vidur Joshi, Sameer Singh, and Noah A. Smith. Knowledge enhanced contextual word representations. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 43–54, Hong Kong, China, 2019b. Association for Computational Linguistics. doi: 10.18653/v1/D19-1005. URL https://www.aclweb.org/anthology/D19-1005.

Fabio Petroni, Tim Rocktäschel, Sebastian Riedel, Patrick Lewis, Anton Bakhtin, Yuxiang Wu, and Alexander Miller. Language models as knowledge bases? In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 2463–2473, Hong Kong, China, 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1250. URL https://www.aclweb.org/anthology/D19-1250.

Fabio Petroni, Aleksandra Piktus, Angela Fan, Patrick Lewis, Majid Yazdani, Nicola De Cao, James Thorne, Yacine Jernite, Vladimir Karpukhin, Jean Maillard, Vassilis Plachouras, Tim Rocktäschel, and Sebastian Riedel. KILT: a benchmark for knowledge intensive language tasks. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 2523–2544, Online, June 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.naacl-main.200. URL https://aclanthology.org/2021.naacl-main.200.

Lianhui Qin, Vered Shwartz, Peter West, Chandra Bhagavatula, Jena D. Hwang, Ronan Le Bras, Antoine Bosselut, and Yejin Choi. Back to the future: Unsupervised backprop-based decoding for counterfactual and abductive commonsense reasoning. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 794–805, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.58. URL https://www.aclweb.org/anthology/2020.emnlp-main.58.

Lianhui Qin, Aditya Gupta, Shyam Upadhyay, Luheng He, Yejin Choi, and Manaal Faruqui. TIME-DIAL: Temporal commonsense reasoning in dialog. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 7066–7076, Online, August 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.acl-long.549. URL https://aclanthology.org/2021.acl-long.549.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. *OpenAI Blog*, 1(8):9, 2019. URL https://d4mucfpksywv.cloudfront.net/better-language-models/language-models.pdf.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *arXiv preprint arXiv:1910.10683*, 2019.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 21(140):1–67, 2020. URL https://www.jmlr.org/papers/volume21/20-074/20-074.pdf.

Marc'Aurelio Ranzato, Sumit Chopra, Michael Auli, and Wojciech Zaremba. Sequence level training with recurrent neural networks. In Yoshua Bengio and Yann LeCun (eds.), *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*, 2016. URL http://arxiv.org/abs/1511.06732.

Adam Roberts, Colin Raffel, and Noam Shazeer. How much knowledge can you pack into the parameters of a language model? In *Proceedings of the 2020 Conference on Empirical*

*Methods in Natural Language Processing (EMNLP)*, pp. 5418–5426, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.437. URL https://www.aclweb.org/anthology/2020.emnlp-main.437.

Stephen Roller, Emily Dinan, Naman Goyal, Da Ju, Mary Williamson, Yinhan Liu, Jing Xu, Myle Ott, Eric Michael Smith, Y-Lan Boureau, and Jason Weston. Recipes for building an open-domain chatbot. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pp. 300–325, Online, 2021. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/2021.eacl-main.24.

Maarten Sap, Ronan Le Bras, Emily Allaway, Chandra Bhagavatula, Nicholas Lourie, Hannah Rashkin, Brendan Roof, Noah A. Smith, and Yejin Choi. ATOMIC: an atlas of machine commonsense for if-then reasoning. In *The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI 2019, The Thirty-First Innovative Applications of Artificial Intelligence Conference, IAAI 2019, The Ninth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2019, Honolulu, Hawaii, USA, January 27 - February 1, 2019*, pp. 3027–3035. AAAI Press, 2019. doi: 10.1609/aaai.v33i01.33013027. URL https://doi.org/10.1609/aaai.v33i01.33013027.

John Schulman, Sergey Levine, Pieter Abbeel, Michael I. Jordan, and Philipp Moritz. Trust region policy optimization. In Francis R. Bach and David M. Blei (eds.), *Proceedings of the 32nd International Conference on Machine Learning, ICML 2015, Lille, France, 6-11 July 2015*, volume 37 of *JMLR Workshop and Conference Proceedings*, pp. 1889–1897. JMLR.org, 2015. URL http://proceedings.mlr.press/v37/schulman15.html.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Yuanlong Shao, Stephan Gouws, Denny Britz, Anna Goldie, Brian Strope, and Ray Kurzweil. Generating high-quality and informative conversation responses with sequence-to-sequence models. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pp. 2210–2219, Copenhagen, Denmark, 2017. Association for Computational Linguistics. doi: 10.18653/v1/D17-1235. URL https://www.aclweb.org/anthology/D17-1235.

Robyn Speer, Joshua Chin, and Catherine Havasi. Conceptnet 5.5: An open multilingual graph of general knowledge. In Satinder P. Singh and Shaul Markovitch (eds.), *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence, February 4-9, 2017, San Francisco, California, USA*, pp. 4444–4451. AAAI Press, 2017. URL http://aaai.org/ocs/index.php/AAAI/AAAI17/paper/view/14972.

Gabriel Stanovsky, Julian Michael, Luke Zettlemoyer, and Ido Dagan. Supervised open information extraction. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 885–895, New Orleans, Louisiana, 2018. Association for Computational Linguistics. doi: 10.18653/v1/N18-1081. URL https://www.aclweb.org/anthology/N18-1081.

Yu Sun, Shuohuan Wang, Yukun Li, Shikun Feng, Hao Tian, Hua Wu, and Haifeng Wang. Ernie 2.0: A continual pre-training framework for language understanding. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 8968–8975, 2020.

Alon Talmor, Yanai Elazar, Yoav Goldberg, and Jonathan Berant. oLMpics-on what language model pre-training captures. *Transactions of the Association for Computational Linguistics*, 8:743–758, 2020. doi: 10.1162/tacl_a_00342. URL https://www.aclweb.org/anthology/2020.tacl-1.48.

Sean Welleck, Ilia Kulikov, Jaedeok Kim, Richard Yuanzhe Pang, and Kyunghyun Cho. Consistency of a recurrent language model with respect to incomplete decoding. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 5553–5568, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.448. URL https://www.aclweb.org/anthology/2020.emnlp-main.448.

Peter West, Ximing Lu, Ari Holtzman, Chandra Bhagavatula, Jena D. Hwang, and Yejin Choi. Reflective decoding: Beyond unidirectional generation with off-the-shelf language models. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pp. 1435–1450, Online, August 2021. Association for Computational Linguistics. doi: 10.18653/ v1/2021.acl-long.114. URL https://aclanthology.org/2021.acl-long.114.

Ledell Wu, Fabio Petroni, Martin Josifoski, Sebastian Riedel, and Luke Zettlemoyer. Scalable zero-shot entity linking with dense entity retrieval. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 6397–6407, Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.519. URL https: //www.aclweb.org/anthology/2020.emnlp-main.519.

Chen Xing, Wei Wu, Yu Wu, Jie Liu, Yalou Huang, Ming Zhou, and Wei-Ying Ma. Topic aware neural response generation. In Satinder P. Singh and Shaul Markovitch (eds.), *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence, February 4-9, 2017, San Francisco, California, USA*, pp. 3351–3357. AAAI Press, 2017. URL http://aaai.org/ocs/index. php/AAAI/AAAI17/paper/view/14563.

Wenhan Xiong, Jingfei Du, William Yang Wang, and Veselin Stoyanov. Pretrained encyclopedia: Weakly supervised knowledge-pretrained language model. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=BJlzm64tDH.

Michihiro Yasunaga, Hongyu Ren, Antoine Bosselut, Percy Liang, and Jure Leskovec. QA-GNN: Reasoning with language models and knowledge graphs for question answering. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 535–546, Online, 2021. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/2021.naacl-main.45.

Houyu Zhang, Zhenghao Liu, Chenyan Xiong, and Zhiyuan Liu. Grounded conversation generation as guided traverses in commonsense knowledge graphs. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 2031–2043, Online, 2020a. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.184. URL https://www. aclweb.org/anthology/2020.acl-main.184.

Jingqing Zhang, Yao Zhao, Mohammad Saleh, and Peter Liu. Pegasus: Pre-training with extracted gap-sentences for abstractive summarization. In *International Conference on Machine Learning*, pp. 11328–11339. PMLR, 2020b.

Saizheng Zhang, Emily Dinan, Jack Urbanek, Arthur Szlam, Douwe Kiela, and Jason Weston. Personalizing dialogue agents: I have a dog, do you have pets too? In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2204–2213, Melbourne, Australia, 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1205. URL https://www.aclweb.org/anthology/P18-1205.

Yizhe Zhang, Siqi Sun, Michel Galley, Yen-Chun Chen, Chris Brockett, Xiang Gao, Jianfeng Gao, Jingjing Liu, and Bill Dolan. DIALOGPT : Large-scale generative pre-training for conversational response generation. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics: System Demonstrations*, pp. 270–278, Online, 2020c. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-demos.30. URL https: //www.aclweb.org/anthology/2020.acl-demos.30.

Zhengyan Zhang, Xu Han, Zhiyuan Liu, Xin Jiang, Maosong Sun, and Qun Liu. ERNIE: Enhanced language representation with informative entities. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 1441–1451, Florence, Italy, 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1139. URL https://www.aclweb. org/anthology/P19-1139.

Xueliang Zhao, Wei Wu, Can Xu, Chongyang Tao, Dongyan Zhao, and Rui Yan. Knowledge-grounded dialogue generation with pre-trained language models. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 3377–3390,

Online, 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.272. URL https://www.aclweb.org/anthology/2020.emnlp-main.272.

Wangchunshu Zhou, Dong-Ho Lee, Ravi Kiran Selvam, Seyeon Lee, and Xiang Ren. Pre-training text-to-text transformers for concept-centric common sense. In *International Conference on Learning Representations*, 2020.