Few-shot Text Adversarial Attack for Black-box Multi-task Learning

Abstract

Current multi-task adversarial text attacks rely on white-box access to shared internal features and assumption of homogeneous multi-task learning framework. As a result, these attacks are less effective against practical scenarios involving black-box feedback APIs and multi-model multi-task learning. To bridge this gap, we introduce **C**luster and **E**nsemble **M**util-task Text Adversarial **A**ttack (**CEMA**), an effective black-box attack that exploits the transferability of adversarial texts. Specifically, we initially employ cluster-oriented substitute model training, as a plug-and-play framework, to simplify complex multi-task scenarios into more manageable text classification attacks and train the substitute model. Next, we generate multiple adversarial candidate examples by applying various adversarial text classification methods. Finally, we select the adversarial example that attacks the most substitute models as the final attack output. CEMA is evaluated on two primary multi-task objectives: text classification and translation. In the classification task, CEMA achieves attack success rates that exceed 60% while reducing the total number of queries to 100. For the text translation task, the BLEU scores of both victim texts and adversarial examples decrease to below 0.36 with 100 queries even including the commercial translation APIs, such as Baidu Translate and Ali Translate.

1 Introduction

A multi-task textual adversarial attack misleads multiple tasks simultaneously through small perturbations, increasing attack efficiency and impact. It poses significant risks to safety-critical systems, leading to wrong decisions. Defending against such attacks is challenging due to the need for multi-task robustness, making it a key issue in AI security (Liu et al., 2017; Lin et al., 2022).

Research on text multi-task adversarial examples typically concentrates on tasks of the same type, particularly classification tasks (Liu et al., 2017). However, in real-world applications, multi-task learning often involves tasks of different types. Existing adversarial attack methods generally assume that attackers have access to the model architecture and shared layer information within a unified model (Guo et al., 2020). However, most commercial and application-based models are proprietary, with their architecture and parameters hidden from external attackers. Additionally, current multi-task adversarial attack strategies primarily target models that employ a shared parameter approach for managing multiple tasks. In contrast, multi-model multi-task learning approaches (Aoki et al., 2022) handle each task with a separate model, without direct parameter sharing. As a result, most existing adversarial methods, designed to attack shared parameter models, are ineffective against these systems because of the absence of a common layer to target.

Our goal is to perform multi-task textual adversarial attacks in realistic scenarios. Based on the previous analysis, such a scenario should encompass a variety of tasks, with black-box model feedback being more reflective of real-world conditions. Moreover, both parameter-sharing multi-task learning systems and multi-model multi-task learning systems must be considered. Additionally, limiting the number of queries is essential to conserve resources and reduce the risk of detection, making it a key aspect of practical attack scenarios. Therefore, this paper is driven by the following research questions(RQ):

> **RQ1**: Can attackers craft the adversarial examples with a **black-box** multi-task learning model that encompasses a variety of tasks?
> **RQ2**: How to craft the adversarial examples in **multi-model multi-task learning** model?
> **RQ3**: How to craft the adversarial examples in **few-shot** queries?
> **RQ3**: How to craft the adversarial examples in the mutil-task learning systems that **encompass a variety of tasks**?

In limited-access scenarios, a straightforward strategy is the transfer attack, which crafts adversarial examples in a substitute model. Training effective substitute models becomes challenging in the absence of a well-trained substitute model, particularly in multi-task learning, where limited access to input-output pairs and poor transferability between tasks in multi-model settings pose significant difficulties. Rather than mimicking the entire multi-task model, we propose focusing on building a substitute model with **strong discriminability**. This approach allows a single substitute model to generate adversarial examples that target all tasks simultaneously, even when trained with limited data.

We propose CEMA (**C**luster and **E**nsemble **M**ulti-task Text **A**dversarial Attack), a framework that leverages a small set of auxiliary texts sharing characteristics with the victim's texts. Using a pre-trained model, we vectorize texts and their outputs, perform clustering, and train substitute models on these auxiliary texts and cluster labels. This converts the multi-task attack into a single-task text classification problem. Repeating this process, we can obtain multiple substitute models. During the adversarial example generation phase for victim texts, for each victim text, adversarial candidates are generated for each victim text. The final adversarial example is selected based on its success across the most substitute models.

Although the substitute model trained by CEMA differs from the victim model trained through multi-task learning, our substitute model, demonstrates **strong discriminative capability**. For task A, if an adversarial attack on the substitute model f^{sub} successfully changes the cluster label of text x_i from 0 to 1, the label y_i^A shifts accordingly, indicating a successful attack on task A. We derive and demonstrate that adversarial examples based on cluster labels, when effective against multiple substitute models, can also transfer effectively to other tasks $B, C, \ldots, N$.

During the experiment, we focus on text classification and translation within a multi-task learning framework. For the text classification task, CEMA achieves an attack success rate (ASR) of over 60% with only 100 queries. In the text translation task, CEMA reaches a BLEU score of 0.14. Even with limited auxiliary data that differs significantly from the training dataset, CEMA maintains an ASR of up to 66.40% for classification tasks and a BLEU score of 0.27 for translation tasks. The primary **contributions** are summarized as follows: ❶ To the best of our knowledge, we are the first to extend text adversarial attacks to the multi-task setting by training cluster-oriented substitute models and employing transferability-oriented adversarial example selection. The proposed CEMA method generates high-quality adversarial examples for multiple tasks simultaneously with **very few queries** in black-box and multi-model multi-task learning scenarios. ❷ We present the first *plug-and-play framework* that converts a multi-task attack into a single-task attack, enabling traditional methods to be easily adapted to multi-task scenarios. Furthermore, our approach overcomes the limitations of existing multi-task attack methods, which depend on shared layers in multi-task models. CEMA effectively handles multi-task scenarios with multi-models, whether they involve related or independent tasks. Additionally, we derive a theoretical lower bound for CEMA's success rate, showing that the probability of success increases with the number of substitute models used. ❸ We demonstrate the effectiveness of CEMA through rigorous mathematical derivations, as well as comprehensive experiments. The experimental results show the proposed CEMA achieves an attack success rate (ASR) of over 60% in text classification tasks and a BLEU score of less than 0.15 in translation tasks, indicating effective adversarial attack performance in both cases.

2 PRELIMINARY

2.1 TRANSFERABILITY AND TRANSFER ATTACKS

Transfer attacks leverage adversarial examples to target different models without requiring direct access, posing a significant security threat in black-box scenarios (Szegedy et al., 2014; Papernot

et al., 2017; Dong et al., 2018; Tramèr et al., 2017). **Transferability** refers to the phenomenon where adversarial examples crafted for one model can successfully compromise other models as well (Zhang et al., 2020). Notably, several existing studies increase the amount of data available to attackers (Mahmood et al., 2021a) or generate synthetic data (Zhou et al., 2020), significantly advancing the development of transfer attacks. Meanwhile, Mahmood et al. (2021b) improve the transferability and robustness of Vision Transformers to adversarial examples

2.2 Multi-Task Learning and Multi-Model Multi-Task Learning

Multi-Task Learning (MTL) involves simultaneously training multiple related tasks, enabling models to share knowledge and improve generalization, particularly when data is limited. MTL has been extensively applied in fields such as natural language processing and computer vision, resulting in more robust models. However, challenges such as task interference and balancing shared information across tasks remain. Recent advancements seek to mitigate these challenges and enhance MTL's overall effectiveness. **Multi-Model Multi-Task Learning** extends the traditional MTL framework by utilizing separate models for each task, providing greater flexibility and better handling of task heterogeneity. This approach minimizes negative transfer and allows for task-specific optimizations. However, it also increases computational complexity and the difficulty of integrating outputs from different models. Current research focuses on hybrid methods that balance task specialization with shared learning, aiming to optimize model architectures and enhance resource efficiency.

3 Threat Model

❶Victim Model: In this paper, we explore a more practical scenario of Multi-Model Multi-Task Learnin, focusing on the tasks of text classification and translation. We utilize publicly available APIs from the Hugging Face platform as the victim models for our attacks. Specifically, we target the SST5 and Emotion datasets for text classification, and we select DistilBERT and RoBERTa models trained on these datasets, referred to as dis-sst5, ro-sst5, dis-emotion, and ro-emotion, respectively. For the translation task, we target the opus-mt model for English-to-Chinese translation and the t5-small model for English-to-French translation. The URLs of these models are provided in Table 8 in the Appendix. Meanwhile, to simulate a more realistic attack scenario, we employ two commercial translation APIs: Baidu Translate for English-to-French translation and Ali Translate for English-to-Chinese translation. We design three multi-task victim models using these base models. **Victim Model A** comprises two classification models and one translation model: dis-sst5, dis-emo, and opus-mt. **Victim Model B** also comprises two classification models and one translation model: ro-sst5, ro-emo, and t5-small. **Victim Model C** consists of two commercial translation APIs: Baidu Translate and Ali Translate. ❷Attacks's Goal The goal of our attack is to degrade the performance of all tasks in a multi-task model. Adversarial examples are crafted to universally disrupt multiple tasks, not just a single one. For text classification, the objective is to ensure differing output labels between the original and adversarial inputs (*i.e.*, $y_{\text{adv}} \neq y_{\text{ori}}$). For translation tasks, the aim is to induce significant semantic divergence, minimizing BLEU scores between the original and adversarial outputs (*i.e.*, $\arg\min, \text{BLEU}(y_{\text{adv}}, y_{\text{ori}})$). ❸ **Adversary Capabilities**: We analyze the adversary's capabilities from three perspectives: query access, API feedback, auxiliary data, and similarity constraint. (1) **Query Access:** Query access refers to the adversary's ability to interact with the target model before delivering the final adversarial input. We assume the attacker has up to 100 opportunities to query the victim model, with each query generating output results for all tasks. (2) **API feedback:** In a practical multi-task text adversarial attack, the attacker has no access to the internal information of the model and can only obtain the final output results of the model. Therefore, the API feedback serves as a black-box response, providing predicted labels for the classification task and the translated text (e.g., French output for English-to-French translation). (3) **Auxiliary Data:** From the perspective of data quantity, we assume that the attacker can acquire only a limited amount of Auxiliary Data, specifically 100 unlabeled texts. Regarding data distribution, we explore two scenarios: (a) The 100 unlabeled texts are sampled from the same distribution as the victim's texts, such as the 100 unlabeled texts in the validation dataset. (b) The 100 unlabeled texts and the victim's texts come from datasets of the same nature but with different distributions. (4) **Similarity Constraint:** To enhance the stealthiness of attacks, textual adversarial samples are constrained to maintain high similarity to the original text, ensuring semantic and structural coherence. This approach balances modification

Figure 1: **The Overview of CEMA.** ❶ CEMA assigns cluster labels to auxiliary texts through a clustering method. These text-label pairs are then used to train the substitute model. This process allows CEMA to efficiently transform a multi-task scenario into a single-task text classification scenario, with only 100 queries to the black-box multi-task model. ❷ To improve attack effectiveness, CEMA applies multiple attack methods to the substitute models, generating candidate adversarial examples to refine the selection process. CEMA also trains several substitute models, selecting the final adversarial example based on its success across the majority of them.

extent with attack effectiveness, preserving fluency and alignment with the original texts. In this study, we enforce a similarity threshold of 0.85, computed using the Universal Sentence Encoder (USE), a widely adopted method for reliable similarity measurement in text adversarial tasks.

4 METHOD

As shown in Figure 1, our method, CEMA, consists of the following steps: ❶ **Representation Learning** (Section 4.1). We convert the auxiliary texts and their outputs from multiple tasks into vector form using representation learning. ❷ **Clustering to Generate cluster labels** (Section 4.2). After determining the optimal number of clusters, we apply a clustering algorithm to the vector representations of the auxiliary texts and their outputs, assigning a cluster label to each auxiliary text. ❸ **Training Substitute Models** (Section 4.3). We train substitute models f^{sub} using auxiliary texts as input and their corresponding cluster labels as output. ❹ **Generation of Adversarial Candidates** (Section 4.4). We apply various text adversarial attack methods to the substitute model f^{sub} to generate multiple adversarial candidates. ❺ **Final Adversarial Example Selection** (Section 4.5). By repeating steps ❶, ❷, and ❸, we can train multiple substitute models, $f_1^{\text{sub}}, f_2^{\text{sub}}, \ldots, f_M^{\text{sub}}$. We select the adversarial candidate that successfully attacks the most substitute models as the final adversarial example.

4.1 REPRESENTATION LEARNING

In a multi-task model, both the input text and output labels need to be appropriately vectorized to effectively capture the relevant information. This section details the specific approach used for learning the representations of input text and output labels. Pre-trained models are extensively utilized in NLP for textual feature extraction (Tabassum & Patil, 2020; Han et al., 2021). These models are highly effective as they are trained on large-scale datasets, enabling them to learn general language patterns and representations. Furthermore, concatenating multiple text representations allows for the simultaneous encoding of multiple texts (Devlin et al., 2019). Accordingly, we leverage a pre-trained model to vectorize both the input text and output labels, generating their respective embeddings. These embeddings are subsequently concatenated to form a unified representation that captures the information from both the input text and the output labels.

Algorithm 1: The substitute model Training Process

Input: The dataset to be attacked $\boldsymbol{D} = \{x_1, x_2, \cdots, x_n\}$, where x_i is the input text; embedding function f_E; clustering function f_c; number of clusters k; training epoch $e_{\max}$; targeted model f_t

Output: The substitute model f^{sub}

1 **for** $i = 1$ to n **do**
2     $y_i^A, y_i^B, \ldots, y_i^N = f_t(x_i)$ ▶ Input x_i to the targeted model f_t to obtain the corresponding label $\boldsymbol{y_i^t}$
3     $\boldsymbol{E}(x_i) = f_E(x_i)$; $\boldsymbol{E}_{y_i^J} = f_{\text{pre}}(y_i^J)$
4     $\boldsymbol{E}_i = \text{Concat}(\boldsymbol{E}_{x_i}, \boldsymbol{E}_{y_i^A}, \ldots, \boldsymbol{E}_{y_i^N})$
5 $\boldsymbol{E}_{\text{all}} = [\boldsymbol{E}_1, \boldsymbol{E}_2, \cdots, \boldsymbol{E}_n]$ ▶ Representation learning
6 Perform a cluster analysis on $\boldsymbol{E}_{\text{all}}$ and refine the internal parameters of the clustering model f_c
7 **for** $i = 1$ to n **do**
8   Input $\boldsymbol{E}_i$ into the clustering algorithm to generate the corresponding pseudolabel $y_i^{\text{pse}} = f_c(\boldsymbol{E}_i)$ ▶ Obtaining cluster labels and pseudo labels
9 The victim text cluster label pairs data: $\boldsymbol{PD} = \{(x_1, y_1^{\text{pse}}), (x_2, y_2^{\text{pse}}), \cdots, (x_n, y_n^{\text{pse}})\}$
10 **for** $i = 1$ to $e_{\max}$ **do**
11   Train the substitute model f^{sub} on $\boldsymbol{PD}$ to adjust the parameters $\theta_{f^{\text{sub}}}$: $\theta_{f^{\text{sub}}} \leftarrow \text{train}(f^{\text{sub}}, \boldsymbol{PD})$ ▶ Train substitute model
12 **return** The substitute model $f^{\text{sub}} = f^{\text{sub}}(\boldsymbol{PD}; \theta_{f^{\text{sub}}})$

As outlined in lines 1-5 of Algorithm 1, we begin by querying the multi-task model to retrieve the output text for each task. Next, auxiliary text with corresponding output results are vectorized by pre-trained models to extract relevant features for subsequent clustering process. We define the multi-task model as f_v, which deals with the set of tasks $A, B, \ldots, N$. The pre-trained model is defined as f_{pre}. The attacker is assumed to have access to a small set of auxiliary texts $\boldsymbol{X}$, which share the same distribution as the victim texts. For each auxiliary text x_i in $\boldsymbol{X}$, we query f_v to obtain the corresponding outputs $y_i^A, y_i^B, \ldots, y_i^N$. Next, we use the pre-trained model f_{pre} to vectorize x_i and $\{y_i^A, y_i^B, \ldots, y_i^N\}$, resulting in the vectors $\{\boldsymbol{E}_{x_i}, \boldsymbol{E}_{y_i^A}, \ldots, \boldsymbol{E}_{y_i^N}\}$. These vectors are concatenated to form the final vector $\boldsymbol{E}_i$, representing x_i and its outputs $y_i^A, y_i^B, \ldots, y_i^N$. Thus, $\boldsymbol{E}_i$ is defined as follows:

$$\boldsymbol{E}_{x_i} = f_{\text{pre}}(x_i), \boldsymbol{E}_{y_i^J} = f_{\text{pre}}(y_i^J), \boldsymbol{E}_i = Concat(\boldsymbol{E}_{x_i}, \boldsymbol{E}_{y_i^A}, \ldots, \boldsymbol{E}_{y_i^N}), \tag{1}$$

where the $Concat$ indicates the concatenation of $\{\boldsymbol{E}_{x_i}, \boldsymbol{E}_{y_i^A}, \ldots, \boldsymbol{E}_{y_i^N}\}$.

4.2 CLUSTER NUMBER AND CLUSTER LABELS

In Section 4.1, we obtain the representations for each text input and output. We then perform a clustering analysis on these representations, with the number of clusters being a crucial parameter. Before clustering, we determine the optimal number of clusters by selecting the value that maximizes strong discriminative capability for each cluster group. When the number of clusters is 2, the two clusters can be interpreted as class C_A and $\overline{C_A}$. (Boongoen & Iam-On, 2018). Therefore, we set the number of clusters to 2. After determining the number of clusters to be 2, we perform clustering analysis on the 100 vectors using the Spectral clustering method (Zhang et al., 1996). For each vector $\boldsymbol{E}_i$, we derive its corresponding cluster label y_i^{clu}, which is later assigned as the pseudolabel for x_i.

4.3 SUBSTITUTE MODEL TRAINING

Once the cluster labels are obtained, we employ the auxiliary texts paired with their respective cluster labels to train a substitute model. This approach effectively converts the multi-task text adversarial attack scenario into a conventional text classification adversarial attack scenario. The substitute model f^{sub} is trained with the auxiliary texts serving as input data and the cluster labels as the corresponding output labels. The process is shown in lines 10-12 of Algorithm 1. More details about the substitute model architecture and substitute model training are presented in Appendix C.

4.4 Candidate adversarial example Generation

Once the substitute model is generated, we apply several adversarial text attack methods to f^{sub}. These methods produce multiple adversarial examples. We then define criteria to select the final adversarial examples from the candidates generated. In this section, we begin by explaining the importance of generating multiple adversarial candidate examples. We assume that m adversarial text attack methods are used to generate m adversarial examples on the substitute model f_1^{sub}. These adversarial examples are denoted as $x_i^{*1}, x_i^{*2}, \ldots, x_i^{*m}$. Each example has a corresponding probability of successfully attacking the victim model, denoted as $p_i^{*1}, p_i^{*2}, \ldots, p_i^{*m}$. The minimum probability among these is denoted as $p_{\min}^*$, where $p_{\min}^* = \min(p_i^{*1}, p_i^{*2}, \ldots, p_i^{*m})$. We calculate the probability, p_s, that at least one of these adversarial examples successfully attacks the victim model as follows:

$$p_s = 1 - (1 - p_i^{*1})(1 - p_i^{*2}) \cdots (1 - p_i^{*m}) = 1 - \prod_{j=1}^{m}(1 - p_i^{*j}) \qquad (2)$$

We analyze the trend of p_s as the number of adversarial examples, m, increases.

$$\begin{aligned} p_s &= 1 - (1 - p_i^{*1})(1 - p_i^{*2}) \cdots (1 - p_i^{*m}) \\ &\geq 1 - (1 - p_{\min}^*)(1 - p_{\min}^*) \cdots (1 - p_{\min}^*) = 1 - (1 - p_{\min}^*)^m \end{aligned} \qquad (3)$$

As m increases, the probability $(1 - p_{\min}^*)^m$ decreases and approaches 0. Conversely, the probability $1 - (1 - p_{\min}^*)^m$ increases and approaches 1. Since p_s is a probability, it must satisfy $0 \leq p_s \leq 1$ (Kolmogoroff, 1933). Combining this result with equation (3), we derive the following formula:

$$1 - (1 - p_{\min}^*)^m \leq p_s \leq 1 \qquad (4)$$

As m increases towards infinity, equation (4) undergoes the following changes:

$$\lim_{m \to \infty} 1 - (1 - p_{\min}^*)^m = 1, \text{ then } 1 \leq p_s \leq 1, \text{ which means } p_s = 1. \qquad (5)$$

Equation (5) demonstrates that as m approaches infinity, the probability of a successful attack reaches 100%. In contrast, (3) illustrates that the attack success rate increases gradually with the growth of m. These findings emphasize the necessity and importance of generating multiple adversarial candidate examples.

4.5 Transferability-Oriented Adversarial Example Selection

In Section 4.4, we demonstrate that generating additional adversarial candidate examples increases the likelihood of finding a successful adversarial example, which can then effectively attack the victim model. This section focuses on the process of selecting the most likely successful adversarial example from the generated candidates. We explore the criteria and methods used to identify the most effective example.

We first select the adversarial candidate with the highest transferability as the final example. To evaluate transferability, we train multiple substitute models and count the number of successful attacks against them. Ultimately, we choose the adversarial candidate that successfully attacks the most substitute models as the final adversarial example. The detailed steps are presented as follows: ❶ **Training Multiple Substitute Models:** We randomly sample 80% of the 100 auxiliary text-cluster label pairs to form the training set for a new substitute model. This process is repeated w times, yielding w substitute models, denoted as $f_1^{\text{sub}}, f_2^{\text{sub}}, \ldots, f_w^{\text{sub}}$. ❷ **Calculating the Transferability Score:** For each victim text x_k, we generate m adversarial candidate examples, denoted as $\{x_k^{*1}, x_k^{*2}, \ldots, x_k^{*m})$. The transferability score for x_k^{*j} is calculated as follows:

$$I_{kij} = \begin{cases} 1, & f_i^{\text{sub}}\left(x_k^{*j}\right) \neq f_i^{\text{sub}}(x_k); \\ 0, & f_i^{\text{sub}}\left(x_k^{*j}\right) = f_i^{\text{sub}}(x_k); \end{cases} \qquad I_{kj} = \sum_{i=1}^{w} I_{kij} \quad j = \arg\max_{j} I_{kj}. \qquad (6)$$

where $f_i^{\text{sub}}\left(x_k^{*j}\right)$ represents the output label of x_k^{*j} is produced by the substitute model f_i^{sub}. Similarly, $f_i^{\text{sub}}(x_k)$ is the output label of x_k generated by the same model. If $f_i^{\text{sub}}\left(x_k^{*j}\right) \neq f_i^{\text{sub}}(x_k)$, then x_k^{*j} successfully attacks the substitute model f_i^{sub}. Therefore, I_{kj} measures the number of substitute models that x_k^{*j} successfully attacks. The adversarial example that successfully attacks the largest number of substitute models is then selected as the final adversarial example. In other words, adversarial examples capable of attacking multiple substitute models demonstrate greater transferability and higher probability of successfully attacking the victim model f_v.

5 EXPERIMENT

5.1 EXPERIMENT SETUP

Dataset: We evaluate the effectiveness of our method using the **SST5** and **Emotion** datasets. The **Emotion** dataset, containing six emotions, is sourced from Twitter. The **SST5** dataset, used for sentiment analysis, includes five categories from movie reviews. Detailed statistics are provided in Appendix E, Table 7. **Baselines:** Since no prior black-box text adversarial attack focuses on multi-task scenarios, we select traditional textual attack methods. For text classification, we use BAE (Garg & Ramakrishnan, 2020), FD (Papernot et al., 2016), Hotflip (Ebrahimi et al., 2018b), SememePSO (Zang et al., 2020), and TextBugger (Ren et al., 2019). For text translation, we select Hotflip (Trans) (Ebrahimi et al., 2018b), kNN (Michel et al., 2019), Morphin (Tan et al., 2020), RA (Zou et al., 2019), Seq2Sick (Cheng et al., 2020), and TransFool (Sadrizadeh et al., 2023). CEMA operates with substantially fewer queries. For a fair comparison, we limit all baseline methods to 30 final queries when attacking the target text. Preliminary details about these methods are listed in Tables 9a and 9b in Appendix G. **Metrics:** We use the following metrics to evaluate our method: ❶ **ASR (Attack Success Rate):** A higher ASR indicates a more effective attack. ❷ **Average Query**: Fewer queries suggest a better attack method. ❸ **BLEU (Bilingual Evaluation Understudy)**: A lower BLEU score signifies a more successful disruption of translation quality.

5.2 COMPARISON OF RESULTS BETWEEN CEMA AND BASELINES

Given the absence of multi-task adversarial methods for black-box outputs in translation tasks, we compare the CEMA method with existing adversarial techniques for text translation and classification. The results, presented in Table 1 and Table 2, demonstrate that CEMA achieves state-of-the-art (SOTA) performance in the SST5 and Emotion datasets across the victim models A, B, and C. **For each dataset,** 100 **queries are made per task, with SST5 containing** $2,210$ **texts and Emotion** $2,000$**, averaging** 0.045 **and** 0.05 **queries per task, respectively.** Remarkably, in this black-box, low-access scenario, CEMA achieved an ASR of over 59% on classification tasks, with a maximum of 80.80%. Furthermore, in translation tasks, CEMA's BLEU score was below 0.16, outperforming the second-best method by a considerable margin. CEMA also achieved SOTA results against the victim model C (Baidu and Ali Translate) using only 100 auxiliary texts. As commercial translators are closed-source, we compared the black-box attack algorithms Morphin and TransFool. CEMA consistently outperformed the second-best attack algorithm, with BLEU scores below 0.35, using just 100 queries.

5.3 THE IMPACT OF CLUSTER NUMBER

In CEMA, we use two clusters. To assess the impact of increasing the number of clusters, we also conducted experiments with three and four clusters. As illustrated in Figure 2, increasing the number of clusters reduces attack performance. When the number of clusters increased from 2 to 4, the average ASR decreased from 58.83% and 64.55% to 46.20% and 52.10%, respectively, while the average BLEU score increased from 0.16 and 0.18 to 0.41 and 0.32. Clearly, the best attack performance is achieved when using two clusters. As discussed in Section 4.2, *two clusters provide the highest discriminative ability and optimal attack performance in the binary-class substitute model.*

5.4 THE IMPACT OF CANDIDATE ADVERSARIAL EXAMPLE NUMBER

CEMA utilizes three attack methods: DWB, FD, and Textbugger. Each method generates three adversarial examples for each victim text. To assess the impact of reducing the number of examples, we conducted experiments using only Textbugger. As shown in Table 3, attack performance declines as the number of adversarial examples decreases. This reduction occurs because a smaller adversarial space leads to lower ASR and higher BLEU scores, consistent with the analysis in Appendix C. When the number of attack algorithms increases from one to three, the average ASR rises by 30.39%, while the average BLEU score decreases by 0.16. These results suggest that increasing the number of attack algorithms enhances overall attack performance.

Table 1: The attack performance of CEMA. Text classification tasks use the ASR(%)↑ metric, while text translation tasks use the BLEU↓ metric. Other adversarial attack methods can only be applied to their specific tasks, whereas CEMA simultaneously attacks all tasks.

Dataset	SST5				Emotion			
Victim Model	Victim Model A		Victim Model B		Victim Model A		Victim Model B	
Text Classification	dis-sst5 (A)		ro-sst5 (B)		dis-sst5 (A)		ro-sst5 (B)	
Metric	ASR(%)↑	Queries↓	ASR(%)↑	Queries↓	ASR(%)↑	Queries↓	ASR(%)↑	Queries↓
Bae	42.71	21.43	39.14	21.48	31.55	26.98	28.50	25.31
FD	25.20	12.56	22.30	9.71	47.10	29.88	20.75	12.09
Hotflip	41.50	11.52	29.03	11.74	46.85	9.80	41.65	10.14
PSO	45.14	11.04	41.50	12.38	46.05	8.92	44.95	8.94
TextBugger	30.36	31.46	20.85	30.32	35.10	11.41	29.40	11.37
Leap	32.55	9.75	30.07	9.54	26.30	7.01	15.50	6.93
CT-GAT	29.37	20.92	24.80	37.54	25.90	21.42	26.75	21.33
HQA	46.11	29.35	39.64	29.08	37.35	29.74	35.85	21.47
CEMA	**73.57**	**0.045**	**75.66**	**0.045**	**80.80**	**0.05**	**60.40**	**0.05**
Text Classification	dis-emotion (A)		ro-emotion (B)		dis-emotion (A)		ro-emotion (B)	
Metric	ASR(%)↑	Queries↓	ASR(%)↑	Queries↓	ASR(%)↑	Queries↓	ASR(%)↑	Queries↓
Bae	39.81	27.33	14.65	28.06	32.25	21.84	32.95	21.83
FD	35.43	29.22	9.55	16.54	22.30	12.81	17.50	18.43
Hotflip	33.39	10.86	22.80	12.28	29.00	14.28	28.05	14.40
PSO	41.90	9.02	35.25	9.45	39.50	11.83	37.65	12.10
TextBugger	30.00	11.35	40.95	11.35	20.85	30.32	21.45	30.33
Leap	21.00	6.93	26.00	7.01	40.58	9.73	37.65	9.78
CT-GAT	39.32	21.36	33.45	21.49	28.10	26.06	30.85	25.34
HQA	37.76	21.44	31.95	29.44	37.40	22.44	36.40	23.16
CEMA	**62.27**	**0.05**	**64.01**	**0.045**	**65.40**	**0.05**	**59.6**	**0.05**
Text Translation	opus-mt(en-zh) (A)		t5-small(en-fr) (B)		opus-mt(en-zh) (A)		t5-small(en-fr) (B)	
Metric	BLEU↓	Queries↓	BLEU↓	Queries↓	BLEU↓	Queries↓	BLEU↓	Queries↓
Hot-trans	0.24	9.76	0.24	9.45	0.20	9.36	0.19	9.81
KNN	0.31	6.19	0.31	6.19	0.61	13.34	0.28	6.08
Morphin	0.30	6.79	0.37	11.1	0.27	5.06	0.22	3.84
RA	0.25	3.18	0.19	4.26	0.23	2.79	0.21	2.11
Seq2sick	0.38	4.45	0.46	6.05	0.62	7.09	0.29	4.05
TransFool	0.77	3.32	0.44	3.91	0.81	3.89	0.67	3.58
CEMA	**0.14**	**0.05**	**0.18**	**0.05**	**0.15**	**0.05**	**0.23**	**0.05**

Table 2: Attack performance of different methods on victim model C. Victim model C consists of two commercial closed-source translation models, namely Alibaba Translate and Baidu Translate.

Data	Victim Model C	Baidu Translate (en-fr) (C)		Ali Translate (en-zh) (C)	
	Methods	BLEU↓	Queries↓	BLEU↓	Queries↓
SST5	Morphin	0.54	40.48	0.60	48.45
	TransFool	0.51	23.53	0.59	31.20
	CEMA	**0.29**	**0.045**	**0.15**	**0.045**
Emotion	Morphin	0.40	27.79	0.55	12.70
	TransFool	0.36	12.70	0.49	30.91
	CEMA	**0.35**	**0.05**	**0.29**	**0.05**

Table 3: Performance of CEMA under different number setting of candidate adversarial examples.

Data	Example Number	Victim Model A			Victim Model B		
		dis-sst5 (A)	dis-emoton (A)	opumt(en-zh) (A)	ro-sst5 (B)	ro-emotion (B)	t5-small(en-fr) (B)
		ASR(%)↑	ASR(%)↑	BLEU↓	ASR(%)↑	ASR(%)↑	BLEU↓
SST5	3	73.57	62.27	0.14	75.66	64.01	0.18
	1	50.42	29.23	0.30	43.79	24.73	0.35
Emotion	3	80.80	65.40	0.15	60.40	59.60	0.23
	1	29.20	34.80	0.31	39.20	47.20	0.39

5.5 THE IMPACT OF CLUSTERING METHODS

In CEMA, we use spectral clustering as the primary method. To assess the impact of different

Table 4: Performance of CEMA under various clustering methods.

Data	Clustering Method	Victim Model A			Victim Model B			victiom Model C	
		dis-sst5	dis-emotion	opus-mt (en-zh)	ro-sst5	ro-emotion	t5-small (en-fr)	Baidu Translate (en-fr)	Ali Translate (en-zh)
		ASR(%)↑	ASR(%)↑	BLEU↓	ASR(%)↑	ASR(%)↑	BLEU↓	BLEU↓	BLEU↓
SST5	Spectral	73.57	62.27	0.14	75.66	64.01	0.18	0.29	0.13
	Kmeans	72.97	61.17	0.12	74.96	63.63	0.17	0.32	0.11
	BIRCH	74.27	62.77	0.09	73.26	60.57	0.15	0.23	0.16
Emotion	Spectral	80.80	65.40	0.15	60.40	59.60	0.23	0.35	0.21
	Kmeans	77.20	50.80	0.18	59.30	61.65	0.23	0.37	0.15
	BIRCH	76.35	52.65	0.13	64.01	56.55	0.27	0.43	0.21

Table 5: Performance of CEMA under various vectorization methods.

Data	Vectorization Method	Victim Model A			Victim Model B			Victim Model C	
		dis-sst5	dis-emotion	opus-mt (en-zh)	ro-sst5	ro-emotion	t5-small (en-fr)	Baidu Translate (en-fr)	Ali Translate (en-zh)
		ASR(%)↑	ASR(%)↑	BLEU↓	ASR(%)↑	ASR(%)↑	BLEU↓	BLEU↓	BLEU↓
SST5	mT5	73.57	62.27	0.14	75.66	64.01	0.18	0.29	0.13
	XLM-R	73.55	61.09	0.17	74.90	63.44	0.19	0.38	0.11
	one-hot	73.57	61.24	0.11	75.09	62.90	0.13	0.23	0.15
Emotion	mT5	80.80	65.40	0.15	60.40	59.60	0.23	0.35	0.21
	XLM-R	81.05	64.95	0.19	53.80	53.75	0.19	0.37	0.16
	one-hot	81.05	65.65	0.18	62.35	59.90	0.27	0.43	0.25

clustering techniques on experimental results, we also implement K-means (Krishna & Murty, 1999) and BIRCH clustering (Zhang et al., 1996). As shown in Figure 3 and Table 4, the ASR in the classification task exhibits only slight variations between different clustering methods. These changes remain minimal. In contrast, in the translation task, the BLEU score fluctuates more significantly depending on the clustering method used. Although these fluctuations are more pronounced, no consistent pattern emerges. No single clustering method consistently achieves SOTA attack performance across all scenarios. The average ASR for the Spectral, KMeans, and BIRCH clustering methods is 67.71%, 65.21%, and 65.05%, re-

Figure 2: The average ASR and BLUE of different numbers of clusters. Fewer clusters result in better attack performance.

spectively, while the corresponding average BLEU scores are 0.21, 0.20, and 0.21. Therefore, we conclude that *while clustering methods do influence attack performance, their impact is largely random and does not consistently favor one method over another.*

5.6 THE IMPACT OF VECTORIZATION METHODS

Given that our multi-task framework includes a translation task, we use the multilingual mT5 (Xue, 2020) for text vectorization, along with the XLM-R (Conneau, 2019) model and one-hot encoding (Rodríguez et al., 2018). One-hot encoding converts categorical data into binary vectors, where each category is represented by a unique vector with a single 1 and all other elements set to 0. To mitigate data leakage, we limit one-hot encoding to 100 samples from the additional dataset. As shown in Figure 3 and Table 5, different vectorization methods have no significant impact on attack performance in the classification task. In the translation task, while vectorization methods cause fluctuations in attack results, these variations are irregular, and no single method consistently achieves SOTA performance across all datasets and victim models. Specifically, the average ASR for the mT5, XLM-R, and one-hot vectorization methods is 67.71%, 65.81%, and 67.72%, respectively, while the average BLEU scores are 0.21, 0.22, and 0.22, respectively. Therefore, we conclude that *vectorization methods do not substantially influence attack performance.*

Figure 3: The average ASR and BLUE of CEMA under various clustering methods and vectorization methods.

Table 6: Zero-shot attack performance of CEMA. In a zero-shot scenario, attackers do not have access to auxiliary data with the same distribution as the victim texts. When the victim texts are SST5 data, attackers only need to recognize that they are sentiment-related, allowing them to collect 100 unlabeled texts from sentiment-related datasets, such as the Emotion dataset, as auxiliary texts.

| | | Victim Model A | | | Victim Model B | | | Victim Model C | |
| | | dis-sst5 | dis-emotion | opus-mt (en-zh) (A) | ro-sst5 (A) | ro-emotion (A) | t5-small (en-fr) | Baidu Translate (en-fr) | Ali Translate (en-zh) |
Victim Data	Access Data	ASR(%)↑	ASR(%)↑	BLEU↓	ASR(%)↑	ASR(%)↑	BLEU↓	BLEU↓	BLEU↓
SST5	SST5	**73.57**	**62.27**	0.14	**75.66**	**64.01**	0.18	**0.29**	**0.15**
	Emotion	64.00	60.80	**0.18**	59.20	52.00	0.22	0.36	0.27
Emotion	Emotion	**80.80**	**65.40**	**0.15**	**60.40**	**59.60**	0.23	**0.35**	**0.29**
	SST5	66.40	36.00	0.21	48.80	46.40	0.36	0.44	0.42

5.7 ZERO-SHOT ATTACK OF CEMA

In this section, we evaluate CEMA's effectiveness under more stringent conditions, where the attacker can only access data related to the training set. For example, both the SST5 and Emotion datasets are related to sentiment analysis, but their label spaces and distributions differ significantly. To test this, we used 100 unlabeled texts from the Emotion validation set as auxiliary data for the SST5 attack, and vice versa. The experimental results, presented in Table 6, show that even with limited auxiliary data and significant differences between the auxiliary data and victim texts, CEMA achieves an attack success rate of 66.40% and a BLEU score of 0.27. The findings indicate that an attacker requires only partial knowledge of the training dataset and gathers the relevant data from the Internet. Utilizing CEMA, they can execute a substantial attack on the multi-task system.

6 CONCLUSION

In this paper, we present a more practical multi-task learning scenario where attackers can only access final black-box outputs through limited queries. To address this challenge, we propose the CEMA method, which achieves state-of-the-art (SOTA) performance in experimental evaluations with just 100 queries and black-box outputs. Furthermore, CEMA can incorporate any text classification attack algorithm, and its performance improves as the number of attack algorithms increases. In the future, we aim to extend CEMA to multi-task models across other modalities.

REFERENCES

Raquel Aoki, Frederick Tung, and Gabriel L Oliveira. Heterogeneous multi-task learning with expert diversity. IEEE/ACM Transactions on Computational Biology and Bioinformatics, 19(6): 3093–3102, 2022.

Dzmitry Bahdanau. Neural machine translation by jointly learning to align and translate. arXiv preprint arXiv:1409.0473, 2014.

Yonatan Belinkov and Yonatan Bisk. Synthetic and natural noise both break neural machine translation. arXiv preprint arXiv:1711.02173, 2017.

Tossapon Boongoen and Natthakan Iam-On. Cluster ensembles: A survey of approaches with recent extensions and applications. Computer Science Review, 28:1–25, 2018.

Minhao Cheng, Jinfeng Yi, Pin-Yu Chen, Huan Zhang, and Cho-Jui Hsieh. Seq2sick: Evaluating the robustness of sequence-to-sequence models with adversarial examples. In Proceedings of the AAAI conference on artificial intelligence, volume 34, pp. 3601–3608, 2020.

Yong Cheng, Lu Jiang, and Wolfgang Macherey. Robust neural machine translation with doubly adversarial inputs. In ACL, pp. 4324–4333, 2019.

A Conneau. Unsupervised cross-lingual representation learning at scale. arXiv preprint arXiv:1911.02116, 2019.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pp. 4171–4186, 2019.

Yinpeng Dong, Fangzhou Liao, Tianyu Pang, Hang Su, Jun Zhu, Xiaolin Hu, and Jianguo Li. Boosting adversarial attacks with momentum. In CVPR, pp. 9185–9193, 2018.

Javid Ebrahimi, Daniel Lowd, and Dejing Dou. On adversarial examples for character-level neural machine translation. In COLING, pp. 653–663, 2018a.

Javid Ebrahimi, Anyi Rao, Daniel Lowd, and Dejing Dou. Hotflip: White-box adversarial examples for text classification. In ACL, pp. 31–36, 2018b.

Ji Gao, Jack Lanchantin, Mary Lou Soffa, and Yanjun Qi. Black-box generation of adversarial text sequences to evade deep learning classifiers. In SPW, pp. 50–56, 2018.

Siddhant Garg and Goutham Ramakrishnan. Bae: Bert-based adversarial examples for text classification. In EMNLP, pp. 6174–6181, 2020.

Salah Ghamizi, Maxime Cordy, Mike Papadakis, and Yves Le Traon. Adversarial robustness in multi-task learning: Promises and illusions. Proceedings of the AAAI Conference on Artificial Intelligence, 36(1):697–705, Jun. 2022. doi: 10.1609/aaai.v36i1.19950. URL https://ojs.aaai.org/index.php/AAAI/article/view/19950.

Yotam Gil, Yoav Chai, Or Gorodissky, and Jonathan Berant. White-to-black: Efficient distillation of black-box adversarial attacks. In NAACL-HLT, pp. 1373–1379, 2019.

Chuan Guo, Alexandre Sablayrolles, Hervé Jégou, and Douwe Kiela. Gradient-based adversarial attacks against text transformers. In EMNLP, pp. 5747–5757, 2021.

Pengxin Guo, Yuancheng Xu, Baijiong Lin, and Yu Zhang. Multi-task adversarial attack. arXiv preprint arXiv:2011.09824, 2020.

Xu Han, Zhengyan Zhang, Ning Ding, Yuxian Gu, Xiao Liu, Yuqi Huo, Jiezhong Qiu, Yuan Yao, Ao Zhang, Liang Zhang, et al. Pre-trained models: Past, present and future. AI Open, 2:225–250, 2021.

Xu Han, Qiang Li, Hongbo Cao, Lei Han, Bin Wang, Xuhua Bao, Yufei Han, and Wei Wang. Bfs2adv: Black-box adversarial attack towards hard-to-attack short texts. CS, pp. 103817, 2024.

Xiaoxue Hu, Geling Liu, Baolin Zheng, Lingchen Zhao, Qian Wang, Yufei Zhang, and Minxin Du. Fasttextdodger: Decision-based adversarial attack against black-box nlp models with extremely high efficiency. TIFS, 2024.

Zhaoxin Huan, Yulong Wang, Xiaolu Zhang, Lin Shang, Chilin Fu, and Jun Zhou. Data-free adversarial perturbations for practical black-box attack. In PAKDD, pp. 127–138. Springer, 2020.

Di Jin, Zhijing Jin, Joey Tianyi Zhou, and Peter Szolovits. Is bert really robust? a strong baseline for natural language attack on text classification and entailment. In AAAI, pp. 8018–8025, 2020.

Yan Kang, Jianjun Zhao, Xuekun Yang, Baochen Fan, and Wentao Xie. A hybrid style transfer with whale optimization algorithm model for textual adversarial attack. NCA, 36:4263–4280, 2024.

Andrey Kolmogoroff. Grundbegriffe der wahrscheinlichkeitsrechnung. 1933.

K Krishna and M Narasimha Murty. Genetic k-means algorithm. IEEE Transactions on Systems, Man, and Cybernetics, Part B (Cybernetics), 29(3):433–439, 1999.

Deokjae Lee, Seungyong Moon, Junhyeok Lee, and Hyun Oh Song. Query-efficient and scalable black-box adversarial attacks on discrete sequential data via bayesian optimization. In ICML, pp. 12478–12497, 2022.

J Li, S Ji, T Du, B Li, and T Wang. Textbugger: Generating adversarial text against real-world applications. In 26th Annual Network and Distributed System Security Symposium, 2019.

Linyang Li, Ruotian Ma, Qipeng Guo, Xiangyang Xue, and Xipeng Qiu. Bert-attack: Adversarial attack against bert using bert. arXiv e-prints, pp. arXiv–2004, 2020a.

Maosen Li, Cheng Deng, Tengjiao Li, Junchi Yan, Xinbo Gao, and Heng Huang. Towards transferable targeted attack. In CVPR, pp. 638–646. IEEE, 2020b.

Qizhang Li, Yiwen Guo, and Hao Chen. Practical no-box adversarial attacks against dnns. NeurIPS, 33:12849–12860, 2020c.

Nankai Lin, Sihui Fu, Xiaotian Lin, and Lianxi Wang. Multi-label emotion classification based on adversarial multi-task learning. Information Processing & Management, 59(6):103097, 2022.

Han Liu, Zhi Xu, Xiaotong Zhang, Xiaoming Xu, Feng Zhang, Fenglong Ma, Hongyang Chen, Hong Yu, and Xianchao Zhang. Sspattack: a simple and sweet paradigm for black-box hard-label textual adversarial attack. In AAAI, volume 37, pp. 13228–13235, 2023.

Han Liu, Zhi Xu, Xiaotong Zhang, Feng Zhang, Fenglong Ma, Hongyang Chen, Hong Yu, and Xianchao Zhang. Hqa-attack: Toward high quality black-box hard-label adversarial attack on text. NeurIPS, 36, 2024.

Pengfei Liu, Xipeng Qiu, and Xuan-Jing Huang. Adversarial multi-task learning for text classification. In Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pp. 1–10, 2017.

Rishabh Maheshwary, Saket Maheshwary, and Vikram Pudi. Generating natural language attacks in a hard label black box setting. In AAAI, pp. 13525–13533, 2021a.

Rishabh Maheshwary, Saket Maheshwary, and Vikram Pudi. A strong baseline for query efficient attacks in a black box setting. In EMNLP, pp. 8396–8409, 2021b.

Kaleel Mahmood, Deniz Gurevin, Marten van Dijk, and Phuoung Ha Nguyen. Beware the black-box: On the robustness of recent defenses to adversarial examples. Entropy, 23(10):1359, 2021a.

Kaleel Mahmood, Rigel Mahmood, and Marten Van Dijk. On the robustness of vision transformers to adversarial examples. In Proceedings of the IEEE/CVF international conference on computer vision, pp. 7838–7847, 2021b.

Zhao Meng and Roger Wattenhofer. A geometry-inspired attack for generating natural language adversarial examples. In ACL, pp. 6679–6689, 2020.

Paul Michel, Xian Li, Graham Neubig, and Juan Miguel Pino. On evaluation of adversarial perturbations for sequence-to-sequence models. arXiv preprint arXiv:1903.06620, 2019.

Muhammad Muzammal Naseer, Salman H Khan, Muhammad Haris Khan, Fahad Shahbaz Khan, and Fatih Porikli. Cross-domain transferability of adversarial perturbations. In NeurIPS, volume 32, 2019.

Nicolas Papernot, Patrick McDaniel, Ananthram Swami, and Richard Harang. Crafting adversarial input sequences for recurrent neural networks. In MILCOM, pp. 49–54, 2016.

Nicolas Papernot, Patrick McDaniel, Ian Goodfellow, Somesh Jha, Z Berkay Celik, and Ananthram Swami. Practical black-box attacks against machine learning. In CCS, pp. 506–519, 2017.

Shuhuai Ren, Yihe Deng, Kun He, and Wanxiang Che. Generating natural language adversarial examples through probability weighted word saliency. In ACL, pp. 1085–1097, 2019.

Luke E Richards, André Nguyen, Ryan Capps, Steven Forsyth, Cynthia Matuszek, and Edward Raff. Adversarial transfer attacks with unknown data and class overlap. In ACM, pp. 13–24, 2021.

Pau Rodríguez, Miguel A Bautista, Jordi Gonzalez, and Sergio Escalera. Beyond one-hot encoding: Lower dimensional target embedding. Image and Vision Computing, 75:21–31, 2018.

Sahar Sadrizadeh, Ljiljana Dolamic, and Pascal Frossard. Transfool: An adversarial attack against neural machine translation models. arXiv preprint arXiv:2302.00944, 2023.

Motoki Sato, Jun Suzuki, Hiroyuki Shindo, and Yuji Matsumoto. Interpretable adversarial perturbation in input embedding space for text. In IJCAI, pp. 4323–4330, 2018.

Ibrahim Sobh, Ahmed Hamed, Varun Ravi Kumar, and Senthil Yogamani. Adversarial attacks on multi-task visual perception for autonomous driving. arXiv preprint arXiv:2107.07449, 2021.

Chenghao Sun, Yonggang Zhang, Wan Chaoqun, Qizhou Wang, Ya Li, Tongliang Liu, Bo Han, and Xinmei Tian. Towards lightweight black-box attack against deep neural networks. NeurIPS, 35: 19319–19331, 2022.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In ICLR, 2014.

Ayisha Tabassum and Rajendra R Patil. A survey on text pre-processing & feature extraction techniques in natural language processing. International Research Journal of Engineering and Technology (IRJET), 7(06):4864–4867, 2020.

Samson Tan, Shafiq Joty, Min-Yen Kan, and Richard Socher. It's morphin'time! combating linguistic discrimination with inflectional perturbations. arXiv preprint arXiv:2005.04364, 2020.

Florian Tramèr, Nicolas Papernot, Ian Goodfellow, Dan Boneh, and Patrick McDaniel. The space of transferable adversarial examples. arXiv preprint arXiv:1704.03453, 2017.

A Vaswani. Attention is all you need. Advances in Neural Information Processing Systems, 2017.

Hetvi Waghela, Sneha Rakshit, and Jaydip Sen. A modified word saliency-based adversarial attack on text classification models. arXiv preprint arXiv:2403.11297, 2024.

Boxin Wang, Chejian Xu, Xiangyu Liu, Yu Cheng, and Bo Li. Semattack: Natural textual attacks via different semantic spaces. In NAACL, pp. 176–205, 2022.

Hanrui Wang, Shuo Wang, Cunjian Chen, Massimo Tistarelli, and Zhe Jin. A multi-task adversarial attack against face authentication. arXiv preprint arXiv:2408.08205, 2024.

Wenqiang Wang, Chongyang Du, Tao Wang, Kaihao Zhang, Wenhan Luo, Lin Ma, Wei Liu, and Xiaochun Cao. Punctuation-level attack: Single-shot and single punctuation can fool text models. In NeurIPS, 2023.

Yuxuan Wang, Wanxiang Che, Ivan Titov, Shay B Cohen, Zhilin Lei, and Ting Liu. A closer look into the robustness of neural dependency parsers using better adversarial examples. In ACL, pp. 2344–2354, 2021a.

Zhibo Wang, Hengchang Guo, Zhifei Zhang, Wenxin Liu, Zhan Qin, and Kui Ren. Feature importance-aware transferable adversarial attacks. In ICCV, pp. 7619–7628. IEEE, 2021b.

Wang Xiaosen, Kangheng Tong, and Kun He. Rethinking the backward propagation for adversarial transferability. NeurIPS, 36:1905–1922, 2023.

L Xue. mt5: A massively multilingual pre-trained text-to-text transformer. arXiv preprint arXiv:2010.11934, 2020.

Zhewei Yao, Amir Gholami, Sheng Shen, Mustafa Mustafa, Kurt Keutzer, and Michael Mahoney. Adahessian: An adaptive second order optimizer for machine learning. In proceedings of the AAAI conference on artificial intelligence, volume 35, pp. 10665–10673, 2021.

Zheng Yuan, Jie Zhang, Yunpei Jia, Chuanqi Tan, Tao Xue, and Shiguang Shan. Meta gradient adversarial attack. In ICCV, pp. 7728–7737. IEEE, 2021.

Yuan Zang, Fanchao Qi, Chenghao Yang, Zhiyuan Liu, Meng Zhang, Qun Liu, and Maosong Sun. Word-level textual adversarial attacking as combinatorial optimization. In ACL, pp. 6066–6080, 2020.

Tian Zhang, Raghu Ramakrishnan, and Miron Livny. Birch: an efficient data clustering method for very large databases. ACM sigmod record, 25(2):103–114, 1996.

Yinghua Zhang, Yangqiu Song, Jian Liang, Kun Bai, and Qiang Yang. Two sides of the same coin: White-box and black-box attacks for transfer learning. In SIGKDD, pp. 2989–2997, 2020.

Mingyi Zhou, Jing Wu, Yipeng Liu, Shuaicheng Liu, and Ce Zhu. Dast: Data-free substitute training for adversarial attacks. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 234–243, 2020.

Hai Zhu, Qingyang Zhao, Weiwei Shang, Yuren Wu, and Kai Liu. Limeattack: Local explainable method for textual hard-label adversarial attack. In AAAI, volume 38, pp. 19759–19767, 2024.

Wei Zou, Shujian Huang, Jun Xie, Xinyu Dai, and Jiajun Chen. A reinforced generation of adversarial examples for neural machine translation. arXiv preprint arXiv:1911.03677, 2019.

This appendix includes our supplementary materials as follows:

- Related Work in Section A.

- Derivation of the maximum entropy distribution in Section B

- More detail of substitute model architecture in Section C

- More detail of Data in Section E

- Url of the data and model used in Section F

- Details of Baselines in Section G

A RELATED WORK

A.1 TEXT CLASSIFICATION ADVERSARIAL ATTACK

In historical textual adversarial research, the predominant methods revolve around scenarios with singular output results (Waghela et al., 2024; Han et al., 2024; Zhu et al., 2024; Kang et al., 2024). These studies focus on the techniques for morphing the original text into adversarial counterparts, including the manipulation of pivotal chars (Ebrahimi et al., 2018b; Gil et al., 2019; Ebrahimi et al., 2018a; Gao et al., 2018; Ren et al., 2019; Jin et al., 2020; Li et al., 2019), words (Wang et al., 2022; Guo et al., 2021; Meng & Wattenhofer, 2020; Sato et al., 2018; Cheng et al., 2019; Lee et al., 2022; Li et al., 2020a; Hu et al., 2024; Liu et al., 2024; 2023; Li et al., 2019) and sentence. These methods are segmented into three distinct categories based on the response from the target model, encompassing white-box attacks, soft-label black-box attacks, and hard-label black-box attacks. In white-box attacks, adversaries gain full access to all relevant information about the target model. The Hotflip (Ebrahimi et al., 2018b) sequentially replaces crucial words based on their calculated importance scores. The FD method (Papernot et al., 2016) constructs adversarial examples depending on the model's gradient information. In soft-label black-box attacks, numerous methods are geared towards disturbing the words in accordance with output probabilities (Lee et al., 2022; Maheshwary et al., 2021b; Wang et al., 2021a; Li et al., 2020a). Bert-ATTACK (Li et al., 2020a) focuses on word attacks using a refined Bert model. SememePSO (Zang et al., 2020) enhances the search landscape to construct adversarial examples. Bae (Garg & Ramakrishnan, 2020) is an attack strategy centered on BERT to replace words. Simultaneously, the DeepWordBug (DWB) method (Gao et al., 2018) prioritizes the words for assault based on the output probabilities. Hard-label adversarial attacks present a more realistic scenario. HLGA (Maheshwary et al., 2021a) employs stochastic starting words and employs a genetic algorithm to craft adversarial examples. HQA-attack (Liu et al., 2024) starts by maximally restoring original words, reducing disruption. It then uses synonyms of remaining altered words to enhance the adversarial example.

A.2 NEURAL MACHINE TRANSLATION ADVERSARIAL ATTACK

Neural Machine Translation (NMT) models, which automatically convert input sentences into translated output, have achieved remarkable results by employing deep neural networks like Transformers (Bahdanau, 2014; Vaswani, 2017). These models are now extensively used across various applications due to their high performance. However, erroneous outputs generated by NMT models can lead to significant risks, particularly in security-sensitive contexts. Recent research has explored adversarial attacks targeting NMT models to address these concerns. Character-level NMT models are highly vulnerable to character manipulations such as typos in a block-box setting (Belinkov & Bisk, 2017; Ebrahimi et al., 2018a). as well as pushing/removing words from the translation. However, character manipulations and typos are easily detected by humans or review strategies. Hence, most adversarial attacks against NLP and NMT systems use a word replacement strategy instead. Seq2sick (Cheng et al., 2020) proposes a projected gradient method combined with group lasso and gradient regularization, conducting non-overlapping attacks and targeted keyword attacks. Similarly, Transfool (Sadrizadeh et al., 2023) also uses the gradient projection method, defining a new optimization problem and linguistic constraints to compute semantic-preserving and fluent attacks against NMT models. Morphin (Tan et al., 2020) generates plausible and semantically similar adversaries by perturbing the inflections in clean examples to investigate the robustness of NLP models to inflectional perturbation. kNN (Michel et al., 2019)is a white-box untargeted attack against

NMT models that substitutes some words with their neighbors in the embedding space. RG (Zou et al., 2019)investigates the issue by generating adversarial examples through a new paradigm based on reinforcement learning, which generates more reasonable tokens and secures semantic constraints.

A.3 MUTIL-TASK ADVERSARIAL ATTACK

A Multi-task Adversarial Attack is an adversarial machine learning strategy designed to generate examples that deceive multiple models or systems simultaneously (Guo et al., 2020; Ghamizi et al., 2022), rather than just one. As far as we know, there is currently no related work on multi-task adversarial attacks in the field of text. In other fields, MTA (Guo et al., 2020) is designed to generate adversarial perturbations for all three pre-trained classifiers simultaneously by leveraging shared knowledge among tasks. There is an attack method (Sobh et al., 2021) that targets visual perception in autonomous driving, which is applied in a wide variety of multi-task visual perception deep networks in distance estimation, semantic segmentation, motion detection, and object detection. MTADV (Wang et al., 2024) is a multitask adversarial attack against facial authentication, which is effective against various facial data sets.

A.4 TRANSFER ATTACK

Transfer attacks leverage adversarial examples to target different models without requiring direct access, posing a significant security threat in black-box scenarios (Papernot et al., 2017; Dong et al., 2018). Then, in the absence of a substitute model, several studies demonstrate that auxiliary data can also facilitate successful attacks through training a substitute model and leveraging transfer attacks (Li et al., 2020c; Sun et al., 2022). Additionally, more effective loss functions have been proposed to train substitute models (Wang et al., 2021b; Li et al., 2020b; Naseer et al., 2019; Richards et al., 2021; Huan et al., 2020), as well as techniques to refine substitute models (Xiaosen et al., 2023; Yuan et al., 2021). Notably, several existing studies increase the amount of data available to attackers (Mahmood et al., 2021a) or generate synthetic data (Zhou et al., 2020), significantly advancing the development of transfer attacks. Meanwhile, Mahmood et al. (2021b) improve the transferability and robustness of Vision Transformers to adversarial examples

B DERIVATION OF THE MAXIMUM ENTROPY DISTRIBUTION

The aim of this section is to derive the probability distribution p_i that maximizes entropy under specific constraints. This derivation follows from the Maximum Entropy Principle, which asserts that, given incomplete information, the probability distribution that best represents the current state of knowledge is the one with the maximum entropy.

B.1 DEFINITION OF ENTROPY

The Shannon entropy for a discrete probability distribution is defined as:

$$S(p) = -\sum_i p_i \log p_i \tag{7}$$

where p_i represents the probability of state i, subject to the constraint that the probabilities sum to one:

$$\sum_i p_i = 1 \tag{8}$$

B.2 CONSTRAINTS

In addition to the normalization constraint $\sum_i p_i = 1$, we consider an additional constraint on the expected value of a physical observable f, such that its expected value $\langle f \rangle$ is known. This constraint is expressed as:

$$\sum_i p_i f_i = \langle f \rangle \tag{9}$$

Thus, we aim to find a probability distribution p_i that maximizes the entropy $S(p)$, while satisfying both the normalization condition and the expectation constraint.

B.3 Application of Lagrange Multipliers

To incorporate these constraints into the maximization of entropy, we employ the method of Lagrange multipliers. The Lagrange multipliers λ_0 and λ_1 correspond to the normalization and expectation constraints, respectively. The Lagrangian is defined as:

$$\mathcal{L}(p_i, \lambda_0, \lambda_1) = -\sum_i p_i \log p_i + \lambda_0 \left(\sum_i p_i - 1 \right) + \lambda_1 \left(\sum_i p_i f_i - \langle f \rangle \right) \tag{10}$$

B.4 Maximization of the Lagrangian

To maximize the entropy, we differentiate the Lagrangian with respect to p_i, yielding:

$$\frac{\partial \mathcal{L}}{\partial p_i} = -(\log p_i + 1) + \lambda_0 + \lambda_1 f_i \tag{11}$$

Setting this derivative equal to zero to find the extremum, we obtain:

$$-(\log p_i + 1) + \lambda_0 + \lambda_1 f_i = 0 \tag{12}$$

which simplifies to:

$$\log p_i = \lambda_0 - 1 + \lambda_1 f_i \tag{13}$$

Exponentiating both sides yields the general form of the probability distribution:

$$p_i = e^{\lambda_0 - 1 + \lambda_1 f_i} \tag{14}$$

Introducing a constant $A = e^{\lambda_0 - 1}$, this becomes:

$$p_i = A e^{\lambda_1 f_i} \tag{15}$$

B.5 Normalization and Determination of A

The normalization condition $\sum_i p_i = 1$ allows us to solve for the constant A. Substituting $p_i = A e^{\lambda_1 f_i}$ into the normalization condition, we get:

$$A \sum_i e^{\lambda_1 f_i} = 1 \tag{16}$$

Hence, A is given by:

$$A = \frac{1}{\sum_i e^{\lambda_1 f_i}} \tag{17}$$

Thus, the probability distribution that maximizes entropy under the given constraints is:

$$p_i = \frac{e^{\lambda_1 f_i}}{\sum_i e^{\lambda_1 f_i}} \tag{18}$$

B.6 DETERMINATION OF λ_1

The Lagrange multiplier λ_1 is determined using the expectation constraint:

$$\sum_i p_i f_i = \langle f \rangle \tag{19}$$

Substituting $p_i = \frac{e^{\lambda_1 f_i}}{\sum_i e^{\lambda_1 f_i}}$ into this constraint yields:

$$\frac{\sum_i f_i e^{\lambda_1 f_i}}{\sum_i e^{\lambda_1 f_i}} = \langle f \rangle \tag{20}$$

This implicit equation must be solved to determine the value of λ_1. Typically, this equation requires numerical methods for its solution. The value of λ_1 ensures that the expectation constraint is satisfied.

B.7 CONCLUSION

The resulting distribution that maximizes entropy, subject to both normalization and expectation constraints, is:

$$p_i = \frac{e^{\lambda_1 f_i}}{\sum_i e^{\lambda_1 f_i}} \tag{21}$$

where the Lagrange multiplier λ_1 is determined by the equation:

$$\frac{\sum_i f_i e^{\lambda_1 f_i}}{\sum_i e^{\lambda_1 f_i}} = \langle f \rangle \tag{22}$$

This form of the probability distribution is widely used in statistical mechanics and information theory. For instance, in statistical mechanics, the Boltzmann distribution arises as a specific case of this general result. The maximum entropy principle thus provides a systematic approach to determining the most likely distribution, given incomplete information and known constraints.

C SUBSTITUTE MODEL

C.1 SUBSTITUTE MODEL ARCHITECTURE

Our substitute model comprises 12 transformer blocks, each with 768 hidden units and 12 self-attention heads. Each transformer block consists of the following substructures:

- **Self-Attention Layer:** The hidden size of the self-attention layer is 768.
- **Position-wise Feed-Forward Network:** The network first projects the output of the attention layer to a 3072-dimensional space using a fully connected layer, followed by a ReLU activation for non-linearity, and finally projects the 3072-dimensional space back to a 768-dimensional space via another fully connected layer.
- **Layer Normalization and Residual Connection:**
  - **Layer Normalization:** Applied to the output of each sub-layer to stabilize training.
  - **Residual Connection:** Adds the normalized output to the input of the sub-layer.

C.2 SUBSTITUTE MODEL TRAINING

We provide a detailed description of the training of the substitute model with the transformer-based architecture. This substitute model consists of 12 hidden layers with a dimensionality of 768. The activation function "GELU" is used, The dropout rate is 0.4. The training process is optimized with the AdamW optimizer (Yao et al., 2021), with batch size set to 64 and learning rate set to $6e-3$, over 5 epochs.

D COMPUTATION OVERHEAD OF THE SUBSTITUTE MODEL TRAINING

We train five substitute models on a server equipped with a 24 GB NVIDIA 3090 GPU. Each model is trained over two epochs using a dataset containing 100 samples. The training time for a single model is approximately 4 minutes, and the size of each trained model is 418 MB.

E DETAILS OF DATA

Table 7: The statistics of datasets.

Dataset	Train	Test	classes	Labels name
SST5	8544	2210	5	Very positive, Positive, Neutral, Negative, Very negative
Emotion	16000	2000	6	Sadness, Joy, Love, Anger, Fear, Surprise

F THE URL OF THE VICTIM MODELS

Table 8: The URL of the Victim Models

Model	Url
dis-sst5(A)	https://huggingface.co/SetFit/distilbert-base-uncased__sst5__all-train
dis-emotion(A)	https://huggingface.co/bhadresh-savani/distilbert-base-uncased-emotion
opus-mt(en-zh)(A)	https://huggingface.co/Helsinki-NLP/opus-mt-en-zh
ro-sst5(B)	https://huggingface.co/Unso/roberta-large-finetuned-sst5
ro-emotion(B)	https://huggingface.co/SamLowe/roberta-base-go_emotions
t5-small(en-fr)(B)	https://huggingface.co/Alexle/T5-small-en-fr
Baidu Translate (en-fr) (C)	https://api.fanyi.baidu.com/
Ali Translate (en-zh) (C)	https://translate.alibaba.com/

G   DETAILS OF BASELINES

Table 9: The details of the methods employed in the baseline comparisons. The Perturbed Level indicates the target of the attack methods, where "word" denotes the specific words targeted for perturbation, and "char" refers to the characters within a word that are altered by the attack method.

(a) Information on the classification attack method used as the baseline.

Methods	Perturbed Level	Gradient	Soft-labels	Hard-labels	Knowledge
Bae	Word	✗	✔	✔	black-box
FD	Char	✔	✔	✔	white-box
Hotflip	Char	✔	✔	✔	white-box
PSO	Word	✗	✔	✔	black-box
TextBugger	Char+Word	✔	✔	✔	white-box
Leap	Word	✗	✔	✔	black-box
CT-GAT	Word	✗	✔	✔	black-box
HQA	Word	✗	✔	✔	black-box
CEMA	Char+Word	✗	✗	✔	black-box

(b) Information on the translation attack method used as the baseline.

Methods	Perturbed Level	Gradient	Soft-labels	Hard-labels	Knowledge
Hot-trans	Char	✔	✗	✗	white-box
kNN	Word	✔	✗	✗	white-box
Morphin	Word	✗	✗	✔	black-box
RA	Word	✔	✗	✗	white-box
Seq2Sick	Word	✔	✗	✔	white-box
TransFool	Word	✗	✗	✔	black-box
CEMA	Char+Word	✗	✗	✔	black-box

H   THE RESULTS OF SIX TASKS

Table 10: The results of six tasks

	ASR(%)				BLEU	
Data	dis-emotion	ro-emotion	dis-sst5	ro-sst5	opus-mt	t5-small
SST5	75.91	74.90	67.04	62.82	0.18	0.22
Emotion	83.25	66.85	71.35	68.40	0.17	0.27

We increase the number of tasks to six downstream tasks, consisting of four classification tasks and two translation tasks, with the corresponding experimental results presented in Table 10. The victim models include dis-emotion, ro-emotion, dis-sst5, ro-sst5, opus-mt, and t5-small. We observe that CEMA achieves an ASR of over 60% on both the SST5 and Emotion datasets, with all BLEU scores below 0.3. These results suggest that the CEMA method can be effectively extended to multi-task learning systems with a broader range of tasks.

I   THE RESULTS OF SUMMARY AND TEXT TO IMAGE

Table 11: The results of translation, summary, and text to image tasks.

Data	Task	Metric	Score
Pokemon	Translation	BLEU	0.24
	Summary	ROUGE Drop Percentage	47%
	Text to Image	CLIP Drop Percentage	56%

We use the Pokemon dataset as the victim text, with the downstream tasks being translation, summarization, and text-to-image generation. The corresponding victim models are t5-small, distilbart-cnn, and Stable Diffusion V2, respectively. BLEU, ROUGE Drop Percentage, and CLIP Drop Percentage are selected as evaluation metrics for the attack. The experimental results, presented in Table **??**, indicate that CEMA demonstrates effective attack performance across all tasks, including translation, summarization, and text-to-image generation. These results suggest that CEMA can be effectively extended to other tasks.

J   THE RESULTS OF FEW-SHOT AND ADDITIONAL QUERIES

We set the number of queries and the amount of available training data to 10, 50, 100, 1000, and 2000, respectively. The experimental results are presented in Table 12. Our findings indicate that the attack effectiveness increases with the number of queries. Notably, even with just 10 queries, CEMA achieves an attack success rate exceeding 30%.

Table 12: The results of few-shot and additional queries

Victim Model	Data		2000	1000	100	50	10
Victim A	SST5	dis-sst5	87.56	83.04	73.57	63.71	38.38
		dis-emotion	83.27	76.76	62.27	45.64	32.06
		opus-mt	0.1	0.11	0.14	0.15	0.19
	Emotion	dis-sst5	91.7	88.25	80.8	71.05	43.35
		dis-emotion	81.45	76.15	65.4	53.55	37.7
		opus-mt	0.1	0.12	0.15	0.18	0.21
Victim B	SST5	ro-sst5	86.46	84.16	75.66	71.69	59.28
		ro-emotion	78.47	73.49	64.01	59.38	46.51
		t5-small	0.15	0.16	0.18	0.19	0.21
	Emotion	ro-sst5	67.45	66.35	60.4	58.65	46.15
		ro-emotion	69.55	67.05	59.6	57.9	41.75
		t5-small	0.16	0.17	0.23	0.24	0.27

K   REVISIT THE TRANSFER ATTACK

Transfer attacks involve an attacker generating adversarial examples using a substitute model, which are then successfully applied to attack multiple target models. These target models may differ in architecture or training data from the substitute model. This type of attack exploits the shared characteristics of adversarial examples across models, allowing these samples to transfer and affect multiple models. The success of a transfer attack typically depends on the degree of similarity between the substitute model and the target model. Consequently, even if the attacker cannot access the internal information of the target model, they can still use adversarial examples generated from the substitute model to successfully attack the target model.

L THE RESULTS OF SIMILARITY AND TOTAL NUMBER OF QUERIES

Table 13: The results of similarity and total number of queries in victim model A and B

Dataset	SST5				Emotion			
Victim Model	Victim Model A		Victim Model B		Victim Model A		Victim Model B	
Text Classification	dis-sst5 (A)		ro-sst5 (B)		dis-sst5 (A)		ro-sst5 (B)	
Metric	Sim↑	Total_Qry↓	Sim↑	Total_Qry↓	Sim↑	Total_Qry↓	Sim↑	Total_Qry↓
Bae	0.888	47360	0.887	47471	0.925	59626	0.924	55935
FD	0.939	27758	0.982	21459	0.948	66035	0.979	26719
Hotflip	0.951	25459	0.951	25945	0.942	21658	0.952	22409
PSO	0.954	24398	0.954	27360	0.945	19713	0.964	19757
TextBugger	0.978	69527	0.978	67007	0.981	25216	0.981	25128
Leap	0.953	21548	0.944	21083	0.934	15492	0.939	15315
CT-GAT	0.939	46233	0.926	82963	0.916	47338	0.927	47139
HQA	0.936	64864	0.929	64267	0.934	65725	0.925	47449
CEMA	0.934	100	0.927	100	0.926	100	0.931	100
Text Classification	dis-emotion (A)		ro-emotion (B)		dis-emotion (A)		ro-emotion (B)	
Metric	Sim↑	Total_Qry↓	Sim↑	Total_Qry↓	Sim↑	Total_Qry↓	Sim↑	Total_Qry↓
Bae	0.894	60399	0.896	62013	0.926	48266	0.923	48244
FD	0.921	64576	0.934	36553	0.932	28310	0.982	40730
Hotflip	0.943	24001	0.946	27139	0.949	31559	0.949	31824
PSO	0.968	19934	0.940	20885	0.952	26144	0.951	26741
TextBugger	0.972	25084	0.986	25084	0.978	67007	0.978	67029
Leap	0.968	15315	0.947	15492	0.926	21503	0.911	21614
CT-GAT	0.927	47206	0.924	47493	0.904	57593	0.906	56001
HQA	0.945	47382	0.931	65062	0.912	49592	0.911	51184
CEMA	0.934	100	0.927	100	0.926	100	0.931	100
Text Translation	opus-mt(en-zh) (A)		t5-small(en-fr) (B)		opus-mt(en-zh) (A)		t5-small(en-fr) (B)	
Metric	Sim↑	Total_Qry↓	Sim↑	Total_Qry↓	Sim↑	Total_Qry↓	Sim↑	Total_Qry↓
Hot-trans	0.846	21570	0.842	20885	0.859	20686	0.854	21680
KNN	0.873	13680	0.883	13680	0.935	29481	0.906	13437
Morphin	0.894	15006	0.907	24531	0.869	11183	0.887	8486
RA	0.872	7028	0.865	9415	0.852	6166	0.865	4663
Seq2sick	0.881	9835	0.926	13371	0.945	15669	0.892	8951
TransFool	0.949	7337	0.894	8641	0.962	8597	0.924	7912
CEMA	0.934	100	0.927	100	0.926	100	0.931	100

Table 14: table2-2metrics

Data	Victim Model C	Baidu Translate (en-fr) (C)		Ali Translate (en-zh) (C)	
	Methods	Sim↑	Total_Qry↓	Sim↑	Total_Qry↓
SST5	Morphin	0.904	89461	0.931	107075
	TransFool	0.921	52001	0.928	68952
	CEMA	0.913	100	0.913	100
Emotion	Morphin	0.897	61416	0.915	28067
	TransFool	0.903	28067	0.923	68311
	CEMA	0.915	100	0.915	100

M THE RESULTS OF MORE TEXT CLASSIFICATION BASELINES

We incorporate additional methods for adversarial attacks in text classification, such as FGPM, Genetic, and PWWS. The experimental results are presented in Table 15. Compared to these three methods, CEMA also achieves state-of-the-art (SOTA) attack results.

Table 15: The Results of more text classification attack methods

Data	Method	dis-sst5		ro-sst5		dis-emotion		ro-emotion	
		ASR(%)↑	Query	ASR(%)↑	Query	ASR(%)↑	Query	ASR(%)↑	Query
SST5	FGPM	30.57	29.31	29.52	30.95	36.49	31.56	30.56	30.54
	Genetic	38.46	20.35	32.31	17.50	28.53	16.49	23.58	24.24
	PWWS	33.49	18.93	31.27	23.17	34.53	21.30	42.94	28.36
	CEMA	**73.57**	**0.045**	**75.66**	**0.045**	**62.27**	**0.045**	**64.01**	**0.045**
Emotion	FGPM	30.57	29.31	29.52	30.95	36.49	31.56	30.56	30.54
	Genetic	38.46	20.35	32.31	17.50	28.53	16.49	23.58	24.24
	PWWS	33.49	18.93	31.27	23.17	34.53	21.30	42.94	28.36
	CEMA	**80.80**	**0.05**	**60.40**	**0.05**	**65.40**	**0.05**	**59.60**	**0.05**

N   COMPARISON WITH TRANSFER ATTACKS

Table 16: The results of transfer attack and CEMA

Dataset	SST5		Emotion	
Victim Model	Victim Model A	Victim Model B	Victim Model A	Victim Model B
Text Classification	dis-sst5	ro-sst5	dis-sst5	ro-sst5
Metric	ASR(%)↑	ASR(%)↑	ASR(%)↑	ASR(%)↑
Bae	29.73	26.73	17.65	16.7
FD	8.48	12.07	12.05	9.5
Hotflip	16.66	12.31	14.85	15.65
PSO	21.88	19.16	15.55	15.9
TextBugger	19.86	12.47	22.4	8.5
Leap	14.57	27.23	15.5	9.65
CT-GAT	12.33	17.16	9.65	13.65
HQA	24.70	16.50	13.85	15.25
CEMA	**73.57**	**75.66**	**80.8**	**64.4**
Text Classification	dis-emotion	ro-emotion	dis-emotion	ro-emotion
Metric	ASR(%)↑	ASR(%)↑	ASR(%)↑	ASR(%)↑
Bae	29.49	5.77	16.75	12.05
FD	19.56	68.6	9.15	7.5
Hotflip	19.11	14.84	10.8	10.65
PSO	29.86	24.34	19.9	18.55
TextBugger	16.89	22.89	10.95	10.3
Leap	16.5	14.11	22.05	10.85
CT-GAT	19.92	24.15	13.85	7.8
HQA	17.88	18.44	18.46	17.7
CEMA	**62.27**	**64.01**	**65.40**	**59.6**
Text Translation	opus-mt	t5-samll	opus-mt	t5-samll
Metric	BLEU↓	BLEU↓	BLEU↓	BLEU↓
Hot-trans	0.32	0.35	0.36	0.33
KNN	0.43	0.40	0.81	0.44
Morphin	0.46	0.50	0.39	0.42
RA	0.40	0.32	0.56	0.47
Seq2scik	0.50	0.57	0.87	0.53
TransFoll	0.94	0.58	0.93	0.87
CEMA	**0.14**	**0.18**	**0.15**	**0.23**

We use the `sst5-setfit-model` and `bert-emotion` models as substitute models for the SST5 and Emotion datasets, respectively. The model URLs for `bert-sst5` and `bert-emotion` are https://huggingface.co/addy88/sst5-setfit-model and https://huggingface.co/bhadresh-savani/bert-base-uncased-emotion, respectively. Additionally, we select `t5-base` as the substitute model for the translation task, with the model available at https://huggingface.co/google-t5/t5-base. We apply various attack algorithms to generate adversarial samples for each model, and then use these adversarial samples to attack the target model. The experimental results, shown in Table 16, indicate that CEMA achieves state-of-the-art (SOTA) attack results compared to transfer attacks.

O   DEFENSE METHOD

We initiate an extensive exploration of defensive strategies to counter CEMA. In practical systems, we thoroughly investigate various defense mechanisms, including train-free adjustments(Preceding Language Modifier) and adversarial training.

O.1   PRECEDING LANGUAGE MODIFIER

The victim models used in our study are after-trained models sourced from the Huggingface website, Ali Translator, and Baidu Translator. Since the training details of these pre-trained models are not publicly available, re-training them using adversarial training is infeasible. Consequently, we adopt training-free defense methods. Specifically, we implement the same approach proposed by (Wang et al., 2023) and apply prompt learning techniques to large language models (LLMs) to mitigate adversarial text inputs. For this, we provide CoEdIT-XXL (a LLM used for correcting text errors). The prompt is as follows: "Please revise the text for grammatical errors, improve the spelling, grammar, clarity, concision, and overall readability." The results are presented in Table 20.

"w/o" indicates the absence of a defense method, whereas "w" denotes the use of the CoEdIT-XXL model as a modifier for defense. Even after applying defense mechanisms using large language models, CEMA's attack effectiveness decreases but still maintains a significant level of performance.

Table 17: The results of Preceding Language Modifier

Victim Model	Dataset		Metric	w/o	w
Victim A	SST5	dis-sst5	ASR(%)↑	73.57	40.52
		dis-emotion	ASR(%)↑	62.27	36.38
		opus-mt	BLEU↓	0.14	0.38
	Emotion	dis-sst5	ASR(%)↑	80.80	32.75
		dis-emotion	ASR(%)↑	65.40	30.41
		opus-mt	BLEU↓	0.15	0.41
Victim B	SST5	ro-sst5	ASR(%)↑	75.66	27.62
		ro-emotion	ASR(%)↑	64.01	28.80
		t5-small	BLEU↓	0.18	0.24
	Emotion	ro-sst5	ASR(%)↑	60.40	31.15
		ro-emotion	ASR(%)↑	59.60	33.25
		t5-small	BLEU↓	0.23	0.53
Victim C	SST5	Baidu Translate	BLEU↓	0.29	0.57
		Ali Translate	BLEU↓	0.15	0.49
	Emotion	Baidu Translate	BLEU↓	0.35	0.72
		Ali Translate	BLEU↓	0.29	0.53

O.2   ADVERSARIAL TRAINING

We train four classification models as victim models and conduct adversarial training to evaluate the impact of adversarial training on CEMA's attack effectiveness. All four models are based on the BERT architecture and are labeled Bert1, Bert2, Bert3, and Bert4. Specifically, Bert1 and Bert3 are trained on the SST5 dataset, while Bert2 and Bert4 are trained on the Emotion dataset. The results are presented in Table 18. "w/o" indicates the absence of adversarial training, while "w" represents the application of adversarial training. Although adversarial training reduces attack effectiveness, CEMA still demonstrates considerable performance.

Table 18: The results of Preceding Language Modifier

Data	Model	W/O	W
SST5	Bert1	76.27	31.31
	Bert2	79.81	28.94
Emotion	Bert3	76.35	35.65
	Bert4	71.50	26.15

P THE RESULTS OF RANDOM SHUFFLE

We employ DWB and TextFooler as attack methods for CEMA, allowing them to shuffle between two models during querying and attack phases. The experimental results, presented in Table 19, demonstrate that Random Shuffle reduces CEMA's attack effectiveness. Nevertheless, CEMA still maintains a reasonably effective level of attack performance under the Random Shuffle defense.

Table 19: The Results of Random Shuffle

Victim Model	Dataset		Metric	w/o	w
Victim A	SST5	dis-sst5	ASR(%)↑	50.58	21.53
		dis-emotion	ASR(%)↑	43.02	21.61
		opus-mt	BLEU↓	0.17	0.28
	Emotion	dis-sst5	ASR(%)↑	68.45	37.50
		dis-emotion	ASR(%)↑	40.25	23.20
		opus-mt	BLEU↓	0.19	0.36
Victim B	SST5	ro-sst5	ASR(%)↑	58.67	32.67
		ro-emotion	ASR(%)↑	55.32	35.64
		t5-small	BLEU↓	0.23	0.44
	Emotion	ro-sst5	ASR(%)↑	55.10	39.15
		ro-emotion	ASR(%)↑	41.40	21.85
		t5-small	BLEU↓	0.28	0.51

Q DEFINITION OF TEXT CLASSIFICATION ADVERSARIAL EXAMPLES AND NMT ADVERSARIAL EXAMPLES

Q.1 DEFINITION OF NMT ADVERSARIAL EXAMPLES

We define the source language space as $\mathcal{X}$ and the target language space as $\mathcal{Y}$, examining two NMT systems: the source-to-target model $M_{x \to y}$, which maps $\mathcal{X}$ to $\mathcal{Y}$ to maximize $P(y_{\text{ref}} \mid x)$, and the target-to-source model $M_{y \to x}$, which performs the reverse mapping. After training, these models can reconstruct original sentences as $\hat{x} = g(f(x))$. We propose black-box adversarial testing for NMT using auxiliary data by selecting test sentences from $\mathcal{T} \subset \mathcal{X}$ and generating adversarial cases $\delta \in \Delta$ to perturb inputs $x' = x + \delta$ such that $f(x')$ diverges significantly from $f(x)$.

NMT Adversarial Example: An NMT adversarial example is a sentence in

$$\begin{aligned} &\mathcal{A} = \left\{ x' \in \mathcal{X} \mid \exists x \in \mathcal{T} \right\}, \\ &here \, \|x' - x\| < \epsilon \wedge S_t\left(y, y_{\text{ref}}\right) \geq \gamma \wedge S_t\left(y', y_{\text{ref}}\right) < \gamma' \end{aligned} \quad (23)$$

where function f represents the NMT model. The variables x and x' represent the original text and the adversarial test case, respectively, while y and y' stand for their respective translations. In detail, $y = f(x)$ and $y' = f(x')$. The function $S_t(\cdot, \cdot)$ gauges the similarity between two sentences. Additionally, γ and γ' denote thresholds for acceptable translation quality. Translation quality is deemed unacceptable if γ' drops below γ.

Q.2 DEFINITION OF TEXT CLASSIFICATION ADVERSARIAL EXAMPLES

Definition of Text Classification Adversarial Examples: Let $X = \{x_1, x_2, \ldots, x_n\}$ denote a set of text inputs, where each x_i is a text document (e.g., sentence or paragraph). Let $f(\cdot)$ represent a text classification model, where:

$$f : X \to Y$$

is a mapping from the input space X to the label space Y, with $Y = \{y_1, y_2, \ldots, y_m\}$ representing the set of possible class labels (e.g., positive, negative, neutral).

Given an input $x \in X$ and its corresponding true label $y_{\text{true}} = f(x)$, an *adversarial example* $\hat{x}$ is a perturbed version of the input x that is intentionally crafted to cause the model to misclassify it,

while remaining perceptually and semantically similar to the original text. Formally, an adversarial example is defined as:

$$\hat{x} = x + \delta$$

where δ is a small perturbation that satisfies:

$$\|\delta\| \leq \epsilon$$

Here, $\|\delta\|$ represents the magnitude of the perturbation (e.g., measured in terms of the number of word substitutions or sentence modifications), and ϵ is a threshold that bounds the maximum allowable perturbation.

Additionally, we impose a *semantic similarity* constraint, ensuring that the perturbation δ does not alter the meaning of the input significantly. This is formalized as:

$$\text{Sim}(x, \hat{x}) \leq \gamma$$

where $\text{Sim}(x, \hat{x})$ denotes a semantic similarity measure (such as cosine similarity) between the original input x and the adversarial example $\hat{x}$, and γ is a predefined threshold that controls the acceptable level of semantic similarity. This ensures that the adversarial example $\hat{x}$ remains semantically close to x, while still leading to a misclassification.

The adversarial example $\hat{x}$ causes the model to output a different class than the true label:

$$f(\hat{x}) \neq y_{\text{true}} \quad \text{and} \quad f(x) = y_{\text{true}}$$

$$\hat{x} = \text{argmin}_{x' \in X} \mathcal{L}(f(x'), y_{\text{true}}) \quad \text{subject to} \quad \|x' - x\| \leq \epsilon \quad \text{and} \quad \text{Sim}(x, x') \geq \gamma$$

where $\mathcal{L}(\cdot)$ is the loss function used to measure the discrepancy between the predicted label $f(x')$ and the true label y_{true}.

R THE EXPERIMENT FOR VERIFYING INDEPENDENCE

Table 20: The experimental results for verifying independence.

Method A	Method B	P(A)	P(B)	P(A)*P(B)	P(AB)	P(A)*P(B)-P(AB)
DWB	FD	52.50%	40.50%	21.26%	19.00%	2.26%
DWB	Textbugger	52.50%	72.50%	38.06%	35.50%	2.56%
DWB	Hotflip	52.50%	72.50%	38.06%	37.00%	1.06%
DWB	PSO	52.50%	76.50%	40.16%	35.00%	5.16%
FD	Textbugger	40.50%	72.50%	29.36%	31.00%	-1.64%
FD	Hotflip	40.50%	72.50%	29.36%	31.50%	-2.14%
FD	PSO	40.50%	76.50%	30.98%	30.50%	0.48%
Textbugger	Hotflip	72.50%	72.50%	52.56%	57.50%	-4.94%
Textbugger	PSO	72.50%	76.50%	55.46%	54.00%	1.46%
Hotflip	PSO	72.50%	76.50%	55.46%	58.00%	-2.54%
Average				39.07%	38.90%	0.17%

We employ the DWB, FD, TextBugger, Hotflip, and PSO methods to generate adversarial examples. Since the exact success probabilities of each method's attacks are unavailable, we estimate these probabilities based on the observed frequency of successful attacks. In the table, we report the frequency

$P(AB)$ of both methods successfully attacking, as well as the individual success frequencies $P(A)$ for Method A and $P(B)$ for Method B. Our findings indicate that $P(AB)$ closely approximates $P(A) \times P(B)$, with the average deviation $P(A) \times P(B) - P(AB)$ being just 0.17%. The detailed experimental results are provided in Table 20. Event independence is defined as the occurrence of event A having no effect on the occurrence of event B. Therefore, we assume that the success of adversarial examples generated by Method A does not influence the success of those generated by Method B.