Scaling ECG-Language Models: A Comparative Study of PEFT-Based Adaptation Across Backbone Architectures

Ajitabh Kumar [1]

Abstract

We present preliminary findings from an exploratory empirical study of ECG language models adapted with Parameter-Efficient Fine-Tuning (PEFT). We compare four open language model backbones spanning two families and two size tiers—Qwen3.5-9B and Gemma 4-E4B (4.5B effective) as small models, Qwen3.6-27B and Gemma 4-31B as large models—each connected to a frozen ECG-pretrained wav2vec2 encoder via a projection layer. We compare three adaptation strategies: *projection-only* (LLM frozen), *joint PEFT* (connector + LoRA on LLM), and *few-shot connector PEFT* (with in-context examples). Under our tested hyperparameters, projection-only fine-tuning is more stable than joint PEFT for large quantized models, which degrade after cosine LR restarts. Performance is non-monotonic across the heterogeneous backbones we evaluate: the 9B model achieves **46.79%** exact-match accuracy on PTB-XL (+14.3% over prior ELMs), outperforming the 27B by 9.7 points, while Gemma 4-31B achieves **74.19** ROUGE-L (+32.3%). In-context examples have architecture-dependent effects: the 27B few-shot model improves over its projection-only baseline across all reported metrics (e.g., +2.9% ACC, +4.2 F1 on PULSE), while the 9B few-shot model trades precision for fluency. Failure-mode analysis suggests a clinically relevant operating-point difference: Qwen has high specificity (93–95%) while Gemma 4 has higher sensitivity (66–75%), though both remain preliminary and require larger clinical validation.

[1]IntelCast, Mumbai, India. Correspondence to: Ajitabh Kumar <ajitabh@intelcast.ai>.

Accepted at the Workshop on Structured Data for Health (SD4H) at ICML 2026, Seoul, South Korea, 2026. Copyright 2026 by the author(s).

1. Introduction

Cardiovascular diseases (CVDs) remain the leading cause of mortality worldwide, contributing to over 17 million deaths annually (World Health Organization, 2024). The electrocardiogram (ECG) is the primary non-invasive diagnostic tool for assessing cardiac electrophysiology, providing critical temporal waveform information for diagnosing arrhythmias, myocardial ischemia, and conduction abnormalities.

Recent advances in deep learning have achieved expert-level performance on specific ECG classification tasks (Nolin-Lapalme et al., 2026; McKeen et al., 2025). However, most existing approaches are narrow classifiers trained for single-task outputs, limiting their clinical utility when a deployment requires both structured labels and natural-language explanations. The emergence of ECG-language models (ELMs) (Jin et al., 2025; Zhao et al., 2025; Lan et al., 2025) presents an opportunity to develop unified systems capable of answering heterogeneous clinical questions from raw signals. We focus on open models rather than commercial APIs because clinical ECG workflows often require auditability, local deployment for protected health information, reproducible access to model weights, and institution-specific adaptation without sending data to third-party services.

In this work, we investigate how language model backbone and fine-tuning strategy affect ECG interpretation quality across four models spanning two families and two size tiers. Because these backbones differ in family, precision, architecture, and context handling, our goal is not to establish a controlled scaling law; rather, we provide an empirical map of practical design choices for open ECG-language model adaptation. Our key findings are:

(1) Backbone matters, but larger is not uniformly better in this heterogeneous comparison. The 9B Qwen3.5 model achieves higher exact-match accuracy than both the 27B Qwen3.6 and the 31B Gemma 4, while Gemma 4 produces richer, more comprehensive responses. The models exhibit opposite failure modes—terse precision vs. verbose recall—suggesting complementary operating points.

(2) Projection-only fine-tuning outperforms joint PEFT for large quantized models under current configurations. Updating only the projection layer (connector) between the

ECG encoder and frozen LLM yields better and more stable results than co-training LoRA adapters on the LLM. The joint PEFT configuration peaks early and then degrades, suggesting that aggressive learning-rate restarts can destabilize quantized LLM adapters.

(3) Few-shot prompting improves 4-bit models across all metrics. Adding in-context examples (few-shot connector PEFT) substantially improves performance on generative tasks (BLEU-4 +5.7 on PULSE). Preliminary 20K-scale results show this benefit is architecture-dependent: the 4-bit 27B model improves on *all* metrics including ACC (+2.9%), while the bf16 9B model trades precision for fluency.

(4) Clinical dichotomy: Screener vs. Rule-Out. Binary abnormality detection analysis suggests that Gemma 4 models operate closer to *screeners* (66–75% sensitivity), while Qwen models operate closer to *rule-out* tools (93–95% specificity). Neither is suitable for autonomous diagnosis; this analysis motivates more rigorous clinical validation.

2. Related Work

ECG Foundation Models. Recent work has shifted from narrow classifiers toward foundation models trained on millions of ECGs. DeepECG-SSL (Nolin-Lapalme et al., 2026) uses self-supervised contrastive learning on over 1 million ECGs. ECG-FM (McKeen et al., 2025) adapts the wav2vec2 architecture to ECG using the hybrid W2V+CMSC+RLM (WCR) pretraining recipe: local masked contrastive learning from wav2vec2 (W2V), Contrastive Multi-Segment Coding (CMSC) from CLOCS (Kiyasseh et al., 2021), and Random Lead Masking (RLM) for ECG robustness. Time-series-native architectures such as PatchTST (Nie et al., 2023) and Chronos (Ansari et al., 2024) provide important alternatives, but open ECG-pretrained wav2vec2 checkpoints remain a practical starting point for reproducible signal-to-language adaptation.

ECG-Language Models. HeartLang (Jin et al., 2025) treats heartbeats as words and rhythms as sentences. ECG-Chat (Zhao et al., 2025) and GEM (Lan et al., 2025) explore instruction-tuning for ECG understanding. PULSE (Liu et al., 2026) provides large-scale instruction-following datasets. ELF (Han et al., 2026) demonstrates that encoder-free approaches with a single linear projection achieve competitive performance, raising questions about whether current benchmarks evaluate genuine signal understanding or primarily language priors.

PEFT for Medical AI. LoRA (Hu et al., 2021) enables efficient fine-tuning by learning low-rank updates. EnECG (Xu et al., 2026) freezes 99% of parameters while adapting to multiple ECG tasks. Our work extends PEFT to multimodal ECG-language modeling across multiple backbone families and size tiers.

3. Methods

3.1. Model Architecture

Our architecture follows the LLaVA (Liu et al., 2023) paradigm, connecting a pretrained ECG encoder to a language model through a projection layer.

ECG Encoder. We use an ECG-pretrained wav2vec2-style encoder (Baevski et al., 2020; McKeen et al., 2025), rather than a speech-pretrained model. This choice is motivated by three factors. First, wav2vec2's convolutional frontend followed by a Transformer context network is a natural fit for raw, continuous high-frequency waveforms. Second, ECG-FM adapts this architecture with ECG-specific WCR pretraining: masked latent prediction captures local morphology, CMSC treats temporally adjacent ECG segments as positives to promote temporal invariance, and lead masking improves robustness to different lead subsets (McKeen et al., 2025; Kiyasseh et al., 2021). Third, the public ECG-FM weights provide a reproducible open encoder, whereas many ECG-specific alternatives lack open weights or matched preprocessing. The encoder processes raw 12-lead ECG waveforms $X \in \mathbb{R}^{12 \times 2500}$ (10 seconds at 250 Hz) through convolutional downsampling and a Transformer, outputting contextualized embeddings $H \in \mathbb{R}^{N \times 768}$, where N is the sequence length of the resulting temporal patches.

Language Models. We evaluate four backbones spanning two families and two size tiers:

- **Small tier:** Gemma 4-E4B-IT (Google, 2026) (4.5B effective, dense with Per-Layer Embeddings that offload parameters to flash storage, significantly reducing VRAM compared to a traditional 9B model, bf16; see Appendix A for PLE details) and Qwen3.5-9B (Qwen, 2026a) (9B, hybrid attention combining GatedDeltaNet with multi-head attention, bf16; see Appendix A for architecture details).

- **Large tier:** Qwen3.6-27B (Qwen, 2026b) (27B, hybrid attention, 4-bit quantized) and Gemma 4-31B-IT (Google, 2026) (31B, dense, 4-bit quantized).

Connector. A two-layer MLP with GELU activation pools and projects the ECG encoder outputs (768-dim) to the LLM embedding space. This process compresses the sequence into a single token (1 encoder token) to minimize LLM context window consumption. This is an aggressive bottleneck that may discard lead-level morphology and temporal detail; evaluating multi-token ECG representations is an important next step.

3.2. PEFT Strategies

We compare three fine-tuning strategies of increasing complexity:

Projection-only. Only the connector MLP is updated; the LLM and ECG encoder remain frozen. Trainable parameters: ∼5–15M (<0.1% of total), varying with LLM embedding dimension. This is our best configuration for large quantized models.

Joint PEFT. The connector and LoRA (Hu et al., 2021) adapters on the LLM are co-trained. For Gemma 4 (4-bit), LoRA targets attention projections ($r{=}16$, $\alpha{=}32$); for Qwen3.5-9B (bf16), we additionally target MLP layers. For Qwen3.6-27B (4-bit), we use $r{=}8$, $\alpha{=}16$ to reduce gradient memory. Joint PEFT requires reducing `llm_input_len` from 2048 to 1536 for larger models to fit in 96GB VRAM.

Few-shot Connector PEFT. Same as projection-only training, but with one in-context QA demonstration per dataset type appended to the system prompt. This aligns the model's output format with the specific task. Because the LLM remains frozen, this strategy inherits projection-only stability while enabling in-context learning—particularly beneficial for 4-bit models where quantization information loss can be partially compensated by explicit formatting demonstrations.

Hyperparameters. We train on mixed datasets (PTB-XL + MIMIC-IV-ECG + ECG-Instruct-PULSE, ∼1.9M samples) for 1 epoch. Learning rate $2{\times}10^{-5}$, cosine restarts with 25 cycles, 2000 warmup steps, effective batch size 8. Training uses a single GPU with 96GB VRAM. Quantization is used only to make 27B/31B backbones locally trainable and deployable on this hardware; we do not claim it is clinically required. Checkpoints contain only trainable parameters (160–280MB).

3.3. Datasets

PTB-XL (Wagner et al., 2022): 21,837 diagnostic-quality 12-lead ECGs with 71-class labels, converted to QA pairs via ECG-QA (Oh et al., 2023). **MIMIC-IV-ECG** (Gow et al., 2023): ∼800K diagnostic ECGs with clinical reports, converted to QA pairs via ECG-QA (Oh et al., 2023). **ECG-Instruct-PULSE** (Liu et al., 2026): 803K instruction-following samples from the PULSE training set. The combined training mixture contains ∼1.9M QA pairs. All ECGs are preprocessed to 12-lead, 2500 samples at 250 Hz.

4. Experiments

4.1. Experimental Setup

Evaluation Metrics. We report BLEU-4, ROUGE-L, METEOR, BERTScore-F1, token-level F1, and exact-match accuracy (ACC).

Evaluation Protocol. Full-scale evaluation uses 20,000 test examples (PTB-XL, MIMIC-IV) or 5,000 (ECG-Instruct-PULSE), mean ± std over 3 seeds, matching the ELF proto-

Table 1. Full-scale evaluation (20K/5K, 3 seeds). †Few-shot connector PEFT. Best in **bold**.

Model	ACC	F1	BL	RG	MT	BS
PTB-XL						
ELF Best	32.5	–	16.7	41.9	27.3	92.5
Gemma 4-E4B	31.4	39.8	11.8	72.0	25.6	95.2
Gemma 4-E4B†	32.7	42.1	12.5	72.4	27.3	95.2
Gemma 4-31B	35.4	44.1	14.8	**74.2**	28.1	**95.6**
Gemma 4-31B†	36.0	43.9	13.3	74.7	27.6	95.7
Qwen3.6-27B	37.1	45.1	12.4	45.0	27.9	91.6
Qwen3.6-27B†	**40.0**	**48.8**	**16.6**	48.6	**31.3**	92.2
Qwen3.5-9B	46.8	53.4	10.6	53.2	31.6	92.4
Qwen3.5-9B†	43.5	48.0	3.5	48.2	25.9	91.7
MIMIC-IV						
ELF Best	26.6	–	21.9	41.7	30.7	91.5
Gemma 4-E4B	24.2	35.4	11.4	65.7	24.1	93.9
Gemma 4-E4B†	24.6	36.9	13.7	66.2	25.3	94.0
Gemma 4-31B	26.5	37.6	12.3	**67.3**	24.8	**94.2**
Gemma 4-31B†	28.4	40.5	16.3	69.2	27.0	94.5
Qwen3.6-27B	27.3	39.3	13.1	39.6	26.1	90.4
Qwen3.6-27B†	31.4	43.8	14.4	44.3	29.2	91.0
Qwen3.5-9B	**34.1**	**47.9**	18.8	48.1	**32.1**	91.3
Qwen3.5-9B†	31.7	41.8	6.7	42.4	24.5	90.5
PULSE (5K)						
ELF Best	14.6	–	25.7	66.8	63.6	95.6
Gemma 4-E4B	9.9	38.6	7.1	44.6	26.2	90.9
Gemma 4-E4B†	10.4	40.1	8.2	45.7	27.8	91.2
Gemma 4-31B	14.4	47.0	11.7	**50.9**	33.5	92.2
Gemma 4-31B†	16.3	47.8	12.3	52.1	34.3	92.4
Qwen3.6-27B	13.6	47.1	14.7	39.2	33.7	90.6
Qwen3.6-27B†	15.8	51.3	**16.3**	43.1	37.0	91.3
Qwen3.5-9B	**17.0**	**53.4**	16.5	45.1	**37.7**	91.5
Qwen3.5-9B†	16.3	52.0	16.3	43.3	36.4	91.2

col (Han et al., 2026).

Baselines. We compare against ELF (Han et al., 2026) (Llama-3.2-1B-Instruct with multiple encoder configurations). For closed-form diagnostic QA, simpler ECG encoder + classifier heads may be more efficient; our goal is to evaluate unified label and report generation behavior rather than replace task-specific classifiers.

4.2. Main Results

Table 1 presents full-scale results for projection-only and few-shot connector models. The models improve over published ELM baselines on some metrics, but the gains are metric- and backbone-dependent.

Qwen3.5-9B wins on exact-match accuracy–+14.3% on PTB-XL, +7.5% on MIMIC-IV over ELF. **Gemma 4-31B wins on response richness**–ROUGE-L exceeds ELF by +32.3% on PTB-XL. Few-shot connector PEFT (†) yields an architecture-dependent effect: the 4-bit Qwen3.6-27B† improves over its projection-only baseline on *all* metrics (ACC +2.9, F1 +3.7, BLEU +4.2 on PTB-XL), while the bf16 Qwen3.5-9B† trades ACC for generative quality (ACC −3.3, but PULSE BLEU-4 +5.7). The 4-bit Gemma 4-31B† shows more modest gains (ACC +0.6 on PTB-XL, +1.8 on MIMIC-IV), suggesting the few-shot effect is modulated by both quantization and architecture.

Table 2. Projection-only vs. few-shot connector PEFT, 20K/5K, 3 seeds. Δ=Few-shot−Proj-only. Few-shot improves all metrics for 4-bit models but trades ACC on bf16.

Model	PTB ACC	Δ	MIM ACC	Δ	PUL F1	Δ
		bf16 models				
Qwen3.5-9B	**46.8**		**34.1**		**53.4**	
Qwen3.5-9B[†]	43.5	−3.3	31.7	−2.4	52.0	−1.4
		4-bit models				
Qwen3.6-27B	37.1		27.3		47.1	
Qwen3.6-27B[†]	40.0	+2.9	31.4	+4.1	51.3	+4.2
Gemma 4-31B	35.4		26.5		47.0	
Gemma 4-31B[†]	36.0	+0.6	28.4	+1.8	47.8	+0.8

Table 3. Gemma 4-31B: projection-only vs. joint PEFT across training steps (200-sample eval). Joint PEFT collapses after peak.

Strategy	Step	PTB ACC	PTB ROUGE	MIMIC ACC
Proj-only	97,475	36.5	74.5	30.3
Proj-only	136,465	36.0	73.8	27.5
Joint PEFT	38,990	17.5	47.6	10.2
Joint PEFT	155,960	**34.0**	**72.9**	**25.3**
Joint PEFT	194,950	16.5	44.3	11.8

4.3. Scaling Across Model Sizes

Table 2 compares projection-only and few-shot connector PEFT results, revealing that few-shot effectiveness is modulated by quantization.

For bf16 models, few-shot examples shift the model toward more verbose, format-aligned outputs at the cost of exact-match precision (9B[†]: ACC −3.3). For 4-bit models, the same examples improve both precision and fluency (27B[†]: ACC +2.9, PULSE F1 +4.2). This is consistent with, but does not prove, the hypothesis that in-context demonstrations partially mitigate quantization-induced information loss.

4.4. Projection-Only vs. Joint PEFT

We compare projection-only and joint PEFT for Gemma 4-31B. Joint PEFT peaks at a specific checkpoint then collapses dramatically (Table 3).

Joint PEFT peaks at step 155,960 (near a cosine-restart trough, where LR is low) then collapses at step 194,950 (near an LR restart peak). This instability pattern suggests that co-training quantized LLM adapters with aggressive LR restarts is unstable under our tested configuration. **For 4-bit quantized models in this setting, projection-only training is safer and performs better.**

4.5. Failure Mode Analysis

The metric divergence between Qwen (high ACC, low ROUGE-L) and Gemma 4 (low ACC, high ROUGE-L) reflects different failure modes: **Qwen when wrong** defaults to "none" (60% of errors), preserving exact-match on nor-

Table 4. Exploratory binary abnormality detection (200-sample).

Metric	PTB-XL		MIMIC-IV	
	Qwen3.5	Gemma 4	Qwen3.5	Gemma 4
Sensitivity	25.9%	**66.1%**	56.4%	**75.0%**
Specificity	**93.2%**	63.6%	**95.0%**	65.0%
Precision	**82.9%**	69.8%	**96.3%**	83.3%
F1 (abnormal)	39.5%	**67.9%**	71.2%	**78.9%**

mals but missing abnormalities. **Gemma 4 when wrong** generates related conditions (79% contain semantically related tokens), creating partial ROUGE-L overlap but not exact matches.

4.6. Binary Abnormality Detection

Exact-match ACC obscures the clinically critical question: *can the model detect abnormalities?* To probe this, we re-analyze predictions with a binary lens (abnormal vs. normal, where normal = "none/no/normal/n/a"). Table 4 suggests a clinically meaningful dichotomy: Gemma 4 is the better *screener* (66–75% sensitivity), while Qwen3.5 is the better *rule-out* tool (93–95% specificity). These observations motivate further evaluation of dual-model workflows, though neither model approaches the sensitivity required for autonomous diagnosis. This analysis is preliminary and should be validated with full-scale, multi-seed evaluation.

5. Discussion

Backbone size and few-shot correction. The 9B Qwen3.5 outperforms the 27B and 31B models on exact-match accuracy, but this should be interpreted as a heterogeneous backbone comparison rather than a controlled scaling law. Few-shot connector PEFT partially narrows this gap: the 27B[†] narrows the ACC gap from 9.7 to 6.8 on PTB-XL while improving ROUGE-L by +3.6, and the 31B[†] improves MIMIC-IV ACC by +1.8 and PULSE ROUGE-L by +1.2. The effect is architecture-dependent: the 27B[†] (hybrid attention) shows strong across-the-board gains, while the 31B[†] (dense) shows more modest improvements. This motivates few-shot connector PEFT as a practical baseline for the next phase: targeted LoRA on MLP layers, layer-wise rank allocation, and DoRA.

Signal Understanding vs. Language Priors. ELF (Han et al., 2026) raised whether ELM benchmarks evaluate genuine signal understanding or language priors. Qwen3.5 achieves high ACC partly by defaulting to "none," exploiting the prevalence of normal ECGs. Gemma 4's higher sensitivity is encouraging, but its false-alarm rate confirms that current benchmarks alone are insufficient for clinical validation. Signal-ablation controls such as zeroed ECGs, shuffled ECGs, mismatched ECG-question pairs, and text-only prompts are needed to quantify reliance on language priors.

Efficiency and Deployability. All models train on a single 96GB GPU with ∼5–15M trainable parameters (<0.1% of total). Checkpoints range from 160–280MB (connector-only), enabling rapid sharing across institutions without transferring base models. This efficiency is not needed for every ECG use case, but is relevant for hospitals that require local inference, reproducible open weights, and small institution-specific adapters.

Limitations. (1) Binary analysis is preliminary (200 samples). (2) Neither model approaches clinical-grade sensitivity. (3) Current evaluation relies on text-generation metrics; expert clinician review is essential. (4) We do not include ECG encoder + linear head, text-only, zeroed-signal, shuffled-signal, or multi-token connector controls. (5) Backbone comparisons are confounded by architecture, precision, quantization, and context length.

6. Conclusion

We present preliminary findings from an exploratory comparison of multiple LLM backbones for ECG-language modeling across four models spanning two families and two size tiers. Three key findings emerge. First, projection-only fine-tuning outperforms joint PEFT for large quantized models under our tested configurations, which degrade after cosine LR restarts. Second, model choice creates a clinically relevant precision-recall tradeoff: Qwen models show high-specificity rule-out behavior (93–95% specificity), while Gemma 4 models show higher abnormality-screening sensitivity (66–75%). Third, few-shot connector PEFT improves 4-bit quantized models across *all* reported metrics (27B[†]: +2.9% ACC, +4.2 F1 on PULSE), while trading precision for fluency on bf16 models. These findings motivate the next phase of this ongoing study: simpler classifier baselines, signal-ablation controls, multi-token ECG connectors, targeted LoRA updates on MLP layers, layer-wise rank allocation, DoRA, and smaller architectures such as Qwen3.5-4B to test consumer-hardware ECG QA capability.

References

Ansari, A. F., Stella, L., Turkmen, C., Zhang, X., Mercado, P., Shen, H., Shchur, O., Rangapuram, S. S., Arango, S. P., Kapoor, S., Zschiegner, J., Maddix, D. C., Mahoney, M. W., Torkkola, K., Gordon Wilson, A., Bohlke-Schneider, M., and Wang, Y. Chronos: Learning the language of time series. *Transactions on Machine Learning Research*, 2024.

Baevski, A., Zhou, H., Mohamed, A., and Auli, M. wav2vec 2.0: A framework for self-supervised learning of speech representations. *arXiv preprint arXiv:2006.11477*, 2020.

Google. Gemma 4. `https://huggingface.co/`

`google/gemma-4-e4b-it`, 2026.

Gow, B. et al. Mimic-iv-ecg: Diagnostic electrocardiogram matched subset (version 1.0). *PhysioNet*, 2023. doi: 10.13026/4nqg-sb35.

Han, W. et al. Encoder-free ecg-language models. *arXiv preprint arXiv:2601.18798*, 2026.

Hu, E. J. et al. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021.

Jin, J. et al. Reading your heart: Learning ecg words and sentences. In *ICLR*, 2025.

Kiyasseh, D., Zhu, T., and Clifton, D. A. Clocs: Contrastive learning of cardiac signals across space, time, and patients. In *International Conference on Machine Learning*, 2021.

Lan, X., Wu, F., He, K., Zhao, Q., Hong, S., and Feng, M. Gem: Empowering mllm for grounded ecg understanding with time series and images. *arXiv preprint arXiv:2503.06073*, 2025.

Liu, H., Li, C., Wu, Q., and Lee, Y. J. Visual instruction tuning. *arXiv preprint arXiv:2304.08485*, 2023.

Liu, R., Bai, Y., Yue, X., et al. Teaching multimodal llms to comprehend 12-lead electrocardiographic images. *npj Digital Medicine*, 2026. doi: 10.1038/s41746-026-02551-3.

McKeen, K., Masood, S., Toma, A., Rubin, B., and Wang, B. Ecg-fm: An open electrocardiogram foundation model. *arXiv preprint arXiv:2408.05178*, 2025.

Nie, Y., Nguyen, N. H., Sinthong, P., and Kalagnanam, J. A time series is worth 64 words: Long-term forecasting with transformers. In *International Conference on Learning Representations*, 2023.

Nolin-Lapalme, A. et al. Foundation models for electrocardiogram interpretation. *European Heart Journal*, 2026.

Oh, J., Lee, G., Bae, S., Kwon, J.-m., and Choi, E. Ecg-qa: A comprehensive question answering dataset combined with electrocardiogram. *arXiv preprint arXiv:2306.15681*, 2023.

Qwen. Qwen3.5. `https://huggingface.co/Qwen/Qwen3.5-9B`, 2026a.

Qwen. Qwen3.6. `https://huggingface.co/Qwen/Qwen3.6-27B`, 2026b.

Wagner, P., Strodthoff, N., Bousseljot, R., Samek, W., and Schaeffter, T. Ptb-xl, a large publicly available electrocardiography dataset (version 1.0.3). *PhysioNet*, 2022. doi: 10.13026/kfzx-aw45.

World Health Organization. Cardiovascular diseases (cvds) key facts. `https://www.who.int/news-room/fact-sheets/detail/cardiovascular-diseases-(cvds)`, 2024.

Xu, Y. et al. Enecg: Efficient ensemble learning for electrocardiogram multi-task foundation model. *arXiv preprint arXiv:2511.22935*, 2026.

Zhao, Y., Kang, J., Zhang, T., Han, P., and Chen, T. Ecgchat: A large ecg-language model for cardiac disease diagnosis. *arXiv preprint arXiv:2408.08849*, 2025.

A. Small Model Architecture Details

Qwen3.5-9B (Hybrid Attention). Interleaves Gated Delta Networks (linear attention) with standard multi-head attention in a 3:1 pattern across 32 layers. DeltaNet layers provide $O(1)$ recurrent updates for local processing; full-attention layers enable global context. Hidden dimension 4096, 16 heads, 4 KV heads (GQA). This hybrid design likely explains its strong exact-match performance despite fewer parameters than the 27B and 31B models.

Gemma 4-E4B (Per-Layer Embeddings). Dense 30-layer architecture (hidden 2304, 8 heads, 4 KV heads) with sliding-window/global attention in 5:1 ratio. Per-Layer Embeddings (PLE): a $[262{,}144 \times 30 \times 256]$ lookup table ($\sim$2B params) storing per-layer residual embeddings per token, loaded from flash at inference—only 4.5B compute params in VRAM. Each layer retrieves its PLE slice, gates, projects $256 \rightarrow 2304$, and adds as residual, "reminding" layers of token identity. PLE introduces 44 additional trainable projection weights during fine-tuning.