# AMUSE:
## Anytime Muon with Stable Gradient Evaluation

**Jueun Kim**[*]                                                    JUEUNKIM@KAIST.AC.KR
*KAIST*

**Baekrok Shin**[*]                                                 BR.SHIN@KAIST.AC.KR
*KAIST*

**Jihun Yun**                                                        JIHUNY@KRAFTON.COM
*KRAFTON*

**Beomhan Baek**                                          BHBAEK2001@SNU.AC.KR
*Seoul National University, KRAFTON*

**Minhak Song**                                               MINHAKSONG@KAIST.AC.KR
*KAIST, KRAFTON*

**Chulhee Yun**                                              CHULHEE.YUN@KAIST.AC.KR
*KAIST*

## Abstract

Modern deep learning commonly relies on AdamW with learning rate schedules. Schedule-Free optimization and Muon challenge this standard recipe from complementary directions: the former removes the need for explicit schedules, while the latter offers an alternative to AdamW. Despite Muon's strong empirical performance, the mechanism behind its improvement remains only partially understood. We study this question through the river-valley perspective by examining how Muon updates decompose into river and valley directions. We show that Muon's orthogonalization increases the river component of its updates, which helps accelerate progress, but can also leave residual valley components that lead to oscillatory trajectories. Building on this, we propose **Anytime MUon with Stable gradient Evaluation (AMUSE)**, which integrates Muon's rapid river progress with the stabilizing effect of Schedule-Free optimizer. AMUSE initially evaluates gradients near the fast Muon sequence for rapid adaptation, then gradually shifts toward the stable averaged sequence to reduce valley-wall oscillations. As a result, AMUSE requires no learning rate schedules and supports anytime training. Across vision tasks and large language model pretraining, AMUSE consistently improves the performance-iteration Pareto frontier over (Schedule-Free) AdamW and Muon.

## 1. Introduction

Optimization remains a primary lever for improving training efficiency in deep learning. The standard recipe for Transformer-based language models has long relied on Adam(W) [18, 23] with warmup and prescribed learning rate decay, such as cosine decay [22]. Recent work challenges both parts: Schedule-Free (SF) optimization [9] removes explicit decay schedules by evaluating gradients at interpolated points between fast and averaged iterates, while Muon [16] improves the update geometry by applying momentum to matrix-valued parameters and orthogonalizing the direction.

---

*. Equal contribution.

We study this interaction through the lens of loss landscape geometry. Empirical Hessian spectra in deep networks often consist of a few large outlier eigenvalues and a broad bulk of small eigenvalues, inducing a dominant high-curvature subspace and a bulk low-curvature subspace [11, 28–30, 37, 38]. In the *river-valley landscape* view, the dominant subspace forms steep valley walls, while the bulk subspace forms the relatively flat river along which training progresses [41, 47] (see Figure 1 for illustration). This suggests that effective optimizers should take *(i)* large, consistent steps along the river while *(ii)* suppressing unnecessary motion across the valley.

We find that Muon naturally promotes the first property. Orthogonalization prevents momentum updates from being dominated by a few large singular components, producing larger bulk components than SGD or AdamW. However, this non-selective amplification can also magnify small dominant-direction noise, inducing valley-wall oscillations [14, 33, 51]. SF optimization provides a complementary stabilizing mechanism: evaluating gradients near an averaged sequence reduces high-curvature components before orthogonalization, stabilizing Muon's trajectory [42].

Figure 1: Illustration of a river-valley landscape. SGD oscillates across the valley walls and progresses slowly along the river, while Muon advances faster but remains oscillatory.

Motivated by this complementarity, we propose **Anytime MUon with Stable gradient Evaluation (AMUSE)**, which combines Muon's orthogonalized matrix updates with an SF formulation using a time-varying interpolation coefficient. AMUSE evaluates gradients near the fast Muon sequence early in training for rapid adaptation, then gradually shifts toward the averaged sequence for stable gradient evaluation. Because this schedule is independent of the training horizon and does not require learning rate decay, AMUSE naturally supports *anytime training*. Across diverse benchmarks, AMUSE improves the performance-iteration Pareto frontier over (Schedule-Free) AdamW and Muon.

## 2. A River-Valley Analysis of Muon and Schedule-Free Dynamics

In this section, we analyze Muon and Schedule-Free dynamics in controlled settings where the leading Hessian eigenspaces can be computed. We first decompose directions using the Hessian eigenspaces of the loss $\mathcal{L} : \mathbb{R}^d \to \mathbb{R}$, following Song et al. [41].

**Dominant and bulk ratios.** Let $\mathcal{S}_k(\theta)$ be the span of the top-$k$ eigenvectors of the Hessian $\nabla^2 \mathcal{L}(\theta)$, and $\boldsymbol{P}_k(\theta)$ be the corresponding projection, with $\boldsymbol{P}_k^\perp(\theta) = \boldsymbol{I} - \boldsymbol{P}_k(\theta)$. For any nonzero vector $\boldsymbol{v}$, we measure

$$r^{\mathrm{dom}}(\boldsymbol{v}; \theta) = \frac{\|\boldsymbol{P}_k(\theta)\boldsymbol{v}\|_2}{\|\boldsymbol{v}\|_2}, \qquad r^{\mathrm{bulk}}(\boldsymbol{v}; \theta) = \frac{\|\boldsymbol{P}_k^\perp(\theta)\boldsymbol{v}\|_2}{\|\boldsymbol{v}\|_2}. \qquad (1)$$

These quantities measure how strongly $\boldsymbol{v}$ is aligned with the dominant and bulk subspaces, respectively. Following Song et al. [41], we set $k$ to the number of classes throughout.

Before analyzing Muon's update decomposition, we first verify in Muon that *bulk amplification* accelerates training while *dominant amplification* destabilizes it, supporting the river-valley interpretation in our setting and motivating our dominant/bulk update-ratio analysis; see Appendix D.1.

(a) Muon vs. SGD/AdamW

(b) Momentum $m_t$ vs. Update $\Delta\theta_t \,(= \mathcal{T}(m_t))$

Figure 2: Comparison of dominant component ratios. Evaluated on a 5k MNIST subset using a 3-layer MLP. (**a**) Muon consistently produces smaller dominant updates than SGD/AdamW, and AMUSE further suppresses the dominant component. (**b**) Orthogonalization reduces Muon's dominant ratio compared to momentum $m_t$; in contrast, AMUSE maintains low dominant ratios throughout, reflecting more stable gradient dynamics. Averaged over three runs. Additional experiments on other datasets and architectures are provided in Appendix D.3.

## 2.1. Orthogonalization Makes Muon Updates More Bulk-Oriented

We first measure how Muon updates align with the dominant and bulk Hessian subspaces. Figure 2 shows that Muon has substantially smaller dominant ratios than SGD or AdamW, indicating more bulk-oriented updates. Moreover, comparing the raw momentum with the post-orthogonalized update shows that orthogonalization itself shifts Muon's update away from dominant directions and toward the bulk. This supports the view that Muon's efficiency comes from accelerating motion along the river directions. However, because this normalization is non-selective, it prevents dominant components from dying out and induces valley-wall oscillations, as in normalized-update dynamics [1]; see Appendix C for an example.

## 2.2. Schedule-Free Stabilizes Muon Trajectories

The previous subsection shows that Muon promotes bulk movement, but its orthogonalized updates can also amplify valley-wall oscillations. Since the averaged trajectory $x_t$ (defined in Eq. (4)) of SF-AdamW can follow the river with a suitable $\beta$ [42], SF averaging may mitigate this instability. Motivated by this, we use Muon as the base optimizer in the SF framework, referred to as *SF-Muon*:

$$
\begin{aligned}
Y_t &= (1 - \beta)Z_t + \beta X_t, \\
M_t &= \mu M_{t-1} + (1 - \mu)\nabla\mathcal{L}(Y_t), \\
Z_{t+1} &= Z_t - \eta\mathcal{T}(M_t), \\
X_{t+1} &= (1 - c_{t+1})X_t + c_{t+1}Z_{t+1},
\end{aligned}
\tag{2}
$$

where $\mathcal{T}(\cdot)$ denotes an orthogonalization operator, approximated via Newton-Schulz iterations [3]. Here, $Z_t$ is the Muon-updated sequence, $Y_t$ is the gradient-evaluation point, and $X_t$ is the averaged sequence used as the final model parameter, with $c_{t+1} = 1/(t + 1)$. Using the notation of Eq. (4) in Appendix A, let $x_t, y_t, z_t \in \mathbb{R}^d$ denote the flattened versions of $X_t, Y_t$, and $Z_t$, respectively. Figure 3 shows that SF-Muon makes the update $\Delta x_t := x_{t+1} - x_t$ more bulk-oriented, while the gradient evaluated at $y_t$ remains strongly aligned with the dominant subspace. This suggests that

(a) Comparison of dominant ratios

(b) Dominant ratio of gradient at $\boldsymbol{y}_t^{(\alpha)}$

Figure 3: Comparison of dominant component ratios. Settings as in Figure 2. (**a**) Dominant ratios for Muon (blue) and SF-Muon (red). The solid and dashed red lines denote the dominant components of $\Delta \boldsymbol{x}_t$ and $\nabla \mathcal{L}(\boldsymbol{y}_t)$, respectively. (**b**) Dominant ratios for gradients at $\boldsymbol{y}_t^{(\alpha)} = (1 - \alpha)\boldsymbol{z}_t + \alpha \boldsymbol{x}_t$ across varying $\alpha$, demonstrating that larger $\alpha$ values correlate with lower dominant components. Additional datasets and model architectures show consistent trends; see Appendix D.3.

averaging stabilizes the trajectory, but does not fully remove the dominant components in the gradient passed to Muon. This raises a natural question:

*Can we further reduce the dominant component before orthogonalization*
*by evaluating gradients at a point closer to the river?*

To test this hypothesis, we treat $\boldsymbol{x}_t$ as a proxy for a river point and probe virtual interpolation points $\boldsymbol{y}_t^{(\alpha)} = (1 - \alpha)\boldsymbol{z}_t + \alpha \boldsymbol{x}_t$ for $\alpha \in [0, 1]$, while keeping the actual training trajectory fixed with a constant $\beta$. At each point, we compute the gradient and measure its dominant ratio using Eq. (1). Figure 3 shows that larger $\alpha$ makes the gradient more bulk-oriented, indicating that evaluation closer to $\boldsymbol{x}_t$ suppresses valley-wall components before Muon orthogonalization.

This observation suggests evaluating gradients near the averaged sequence $\boldsymbol{x}_t$ by using a large fixed $\beta$. However, this creates an early–late trade-off: early in training, $\boldsymbol{x}_t$ may lag behind the rapidly adapting base sequence $\boldsymbol{z}_t$, so evaluating too close to $\boldsymbol{x}_t$ can slow initial progress toward the river. Conversely, a smaller $\beta$ preserves early adaptation but provides weaker late-stage stabilization.

## 3. AMUSE: Anytime MUon with Stable gradient Evaluation

To address the trade-off between early progress and later stability induced by a fixed $\beta$, we introduce **Anytime MUon with Stable gradient Evaluation (AMUSE)**. Instead of fixing the interpolation coefficient throughout training, AMUSE employs a time-varying coefficient $\beta_t$. It starts with a small $\beta_{init}$ to allow a fast early adaptation and gradually increases it, shifting the gradient-evaluation point from the fast base trajectory ($\boldsymbol{z}_t$) to the smoother averaged trajectory ($\boldsymbol{x}_t$). Formally, AMUSE uses the same update rule as Eq. (2), except the gradient is now evaluated at $\boldsymbol{Y}_t = (1 - \beta_t)\boldsymbol{Z}_t + \beta_t \boldsymbol{X}_t$.

Let $T_0$ denote the number of warmup steps. During warmup, we fix $\beta_t = \beta_{init}$. For $t \geq T_0$, we set:

$$\beta_t = 1 - \left( \frac{T_0}{t} \right)^{\rho} (1 - \beta_{init}), \tag{3}$$

where $\rho \in [0, 1]$ controls how quickly $\beta_t$ increases toward 1. When $\rho = 0$, AMUSE reduces to the fixed-$\beta$ SF-Muon with $\beta_t = \beta_{init}$; a larger $\rho$ moves the gradient-evaluation point toward $\boldsymbol{x}_t$ more

Figure 4: **Comparison of fixed-$\beta$ SF-Muon with different $\beta$ values and AMUSE in the 124M Llama pretraining on FineWeb.** Solid lines show fixed-$\beta$ SF-Muon, and dashed lines show AMUSE with $\beta_{init} = 0.6$ and $\rho = 0.8$.

rapidly. The detailed rationale and derivation for Eq. (3) are deferred to Appendix E.4. Notably, *this time-varying $\beta_t$ is independent of the total number of training steps*, gradually approaching 1 as training progresses. Furthermore, AMUSE does not require any learning rate schedule. See Algorithm 1 for details.

We compare AMUSE with fixed-$\beta$ SF-Muon variants on 124M Llama. In Figure 4, fixed-$\beta$ SF-Muon exhibits an early–late trade-off: smaller $\beta$ values improve early perplexity but saturate later, while larger $\beta$ values improve late-stage stability at the cost of slower early progress. AMUSE avoids this trade-off by gradually increasing $\beta_t$, achieving lower validation perplexity while maintaining a larger averaged-update norm $\|\Delta x_t\|$. This suggests that AMUSE preserves faster progress along the river while stabilizing the gradient-evaluation point over training. Additional comparisons in Appendix H.6 further confirm that fixed-$\beta$ SF-Muon variants do not match AMUSE's performance throughout training.

Furthermore, following Song et al. [42], we use Exponential Weight Averaging (EWA) and learning rate decay to test whether AMUSE already follows the river. Neither yields meaningful additional improvement, suggesting that AMUSE already stays near the river; see Appendix E.2.

## 4. Experiments

We evaluate AMUSE across a diverse set of benchmarks covering standard image classification, segmentation, and large language model (LLM) pretraining. As baselines, we use SGD and SF-SGD for most image-domain experiments, and AdamW and SF-AdamW for MAE fine-tuning and LLM pretraining. Across all settings, we additionally include Muon as a shared baseline. For SGD, AdamW and Muon, we employ cosine learning rate schedules.

### 4.1. Image Domain Experiments

**Experimental Setup.** Following the setup of Defazio et al. [9], we evaluate AMUSE on diverse datasets and architectures: Wide-ResNet-16-8 on CIFAR-10 [19, 50], DenseNet on CIFAR-100 [15], ResNet-3-96 on SVHN [12, 27], and ResNet-50 on ImageNet-1k [36]. We further evaluate two additional settings: U-Net on ISIC 2018 for image segmentation [4, 34], and MAE fine-tuning with a ViT-B/16 on ImageNet [13]. Hyperparameter tuning details are provided in Appendix F.1.

**Experimental Results.** As illustrated in Figure 5, AMUSE consistently achieves the best performance among the compared optimizers across all evaluated datasets, tasks, and architectures, demonstrating *superior anytime performance*.

Figure 5: Test accuracy across image domain experiments. Averaged over five random seeds.

Figure 6: Validation perplexity on FineWeb pretraining across Llama model scales.

## 4.2. Large Language Model Pretraining

**Experimental Setup.** We follow the Llama-style Transformer setup of Semenov et al. [39]. We train the 124M and 720M models on FineWeb-100B [31] for 16k iterations (≈2.1B and ≈16.3B tokens, respectively), and 1.3B model is trained for 24.8k iterations (≈26B tokens). We further provide longer training results for both 124M and 720M models in Appendix H.3. Hyperparameter details are provided in Appendix G.2.

**Experimental Results.** Figure 6 shows that AMUSE achieves better performance than all baselines across diverse scales. AMUSE also maintains its advantage under extended 124M training and against additional recent optimizers, improving the performance-iteration Pareto frontier (Appendices H.3 and H.1). Extended training results across both the 124M and 720M model scales further show that AMUSE remains effective beyond the standard training horizon (Figure 19 in Appendix H.3). Moreover, Muon with EWA or decay still falls short of AMUSE, suggesting that AMUSE provides more than external averaging or learning rate decay (Appendix H.2).

# References

[1] Sanjeev Arora, Zhiyuan Li, and Abhishek Panigrahi. Understanding gradient descent on the edge of stability in deep learning. In *International Conference on Machine Learning*, pages 948–1024. PMLR, 2022.

[2] Annalisa Belloni, Lorenzo Noci, and Antonio Orvieto. Universal dynamics of warmup stable decay: understanding WSD beyond transformers. In *High-dimensional Learning Dynamics 2025*, 2025. URL https://openreview.net/forum?id=QJfH0lBZ8d.

[3] Jeremy Bernstein and Laker Newhouse. Old optimizer, new norm: An anthology. In *OPT 2024: Optimization for Machine Learning*, 2024. URL https://openreview.net/forum?id=ux18f5nOpD.

[4] Noel Codella, Veronica Rotemberg, Philipp Tschandl, M Emre Celebi, Stephen Dusza, David Gutman, Brian Helba, Aadi Kalloo, Konstantinos Liopyris, Michael Marchetti, et al. Skin lesion analysis toward melanoma detection 2018: A challenge hosted by the international skin imaging collaboration (isic). *arXiv preprint arXiv:1902.03368*, 2019.

[5] Jeremy Cohen, Simran Kaur, Yuanzhi Li, J Zico Kolter, and Ameet Talwalkar. Gradient descent on neural networks typically occurs at the edge of stability. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=jh-rTtvkGeM.

[6] Jeremy Cohen, Alex Damian, Ameet Talwalkar, J Zico Kolter, and Jason D. Lee. Understanding optimization in deep learning with central flows. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=sIE2rI3ZPs.

[7] George E Dahl, Frank Schneider, Zachary Nado, Naman Agarwal, Chandramouli Shama Sastry, Philipp Hennig, Sourabh Medapati, Runa Eschenhagen, Priya Kasimbeg, Daniel Suo, et al. Benchmarking neural network training algorithms. *arXiv preprint arXiv:2306.07179*, 2023.

[8] Alex Damian, Eshaan Nichani, and Jason D Lee. Self-stabilization: The implicit bias of gradient descent at the edge of stability. *arXiv preprint arXiv:2209.15594*, 2022.

[9] Aaron Defazio, Xingyu Alice Yang, Ahmed Khaled, Konstantin Mishchenko, Harsh Mehta, and Ashok Cutkosky. The road less scheduled. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL https://openreview.net/forum?id=0XeNkkENuI.

[10] Shenyang Deng, Boyao Liao, Zhuoli Ouyang, Tianyu Pang, Minhak Song, and Yaoqing Yang. Suspicious alignment of SGD:a fine-grained step size condition analysis. In *Proceedings of The 37th International Conference on Algorithmic Learning Theory*, volume 313 of *Proceedings of Machine Learning Research*, pages 1–66, 2026.

[11] Behrooz Ghorbani, Shankar Krishnan, and Ying Xiao. An investigation into neural net optimization via hessian eigenvalue density. In *International Conference on Machine Learning*, pages 2232–2241. PMLR, 2019.

[12] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2016.

[13] Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 16000–16009, 2022.

[14] Wei He, Kai Han, Hang Zhou, Hanting Chen, Zhicheng Liu, Xinghao Chen, and Yunhe Wang. Root: Robust orthogonalized optimizer for neural network training. *arXiv preprint arXiv:2511.20626*, 2025.

[15] Gao Huang, Zhuang Liu, Laurens van der Maaten, and Kilian Q. Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, July 2017.

[16] Keller Jordan, Yuchen Jin, Vlado Boza, Jiacheng You, Franz Cesista, Laker Newhouse, and Jeremy Bernstein. Muon: An optimizer for hidden layers in neural networks, 2024. URL https://kellerjordan.github.io/posts/muon/.

[17] Changmin Kang, Jihun Yun, Baekrok Shin, Yeseul Cho, and Chulhee Yun. Uniform spectral growth and convergence of muon in lora-style matrix factorization. *arXiv preprint arXiv:2602.06385*, 2026.

[18] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *3rd International Conference on Learning Representations*, 2015.

[19] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

[20] Jingyuan Liu, Jianlin Su, Xingcheng Yao, Zhejun Jiang, Guokun Lai, Yulun Du, Yidao Qin, Weixin Xu, Enzhe Lu, Junjie Yan, et al. Muon is scalable for LLM training. *arXiv preprint arXiv:2502.16982*, 2025.

[21] Yizhou Liu, Ziming Liu, and Jeff Gore. Focus: First order concentrated updating scheme. *arXiv preprint arXiv:2501.12243*, 2025.

[22] Ilya Loshchilov and Frank Hutter. SGDR: Stochastic gradient descent with warm restarts. In *International Conference on Learning Representations*, 2017. URL https://openreview.net/forum?id=Skq89Scxx.

[23] Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019.

[24] Kairong Luo, Zhenbo Sun, Haodong Wen, Xinyu Shi, Jiarui Cui, Chenyi Dang, Kaifeng Lyu, and Wenguang Chen. How learning rate decay wastes your best data in curriculum-based LLM pretraining. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=T5wkZJqzkz.

[25] Jianhao Ma, Yu Huang, Yuejie Chi, and Yuxin Chen. Preconditioning benefits of spectral orthogonalization in muon. *arXiv preprint arXiv:2601.13474*, 2026.

[26] Yurii Nesterov. Primal-dual subgradient methods for convex problems. *Mathematical programming*, 120(1):221–259, 2009.

[27] Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Baolin Wu, Andrew Y Ng, et al. Reading digits in natural images with unsupervised feature learning. In *NIPS workshop on deep learning and unsupervised feature learning*, volume 2011, page 4. Granada, 2011.

[28] Vardan Papyan. The full spectrum of deepnet hessians at scale: Dynamics with sgd training and sample size. *arXiv preprint arXiv:1811.07062*, 2018.

[29] Vardan Papyan. Measurements of three-level hierarchical structure in the outliers in the spectrum of deepnet hessians. In *International Conference on Machine Learning*, pages 5012–5021. PMLR, 2019.

[30] Vardan Papyan. Traces of class/cross-class structure pervade deep learning spectra. *Journal of Machine Learning Research*, 21(252):1–64, 2020. URL http://jmlr.org/papers/v21/20-933.html.

[31] Guilherme Penedo, Hynek Kydlíček, Loubna Ben allal, Anton Lozhkov, Margaret Mitchell, Colin Raffel, Leandro Von Werra, and Thomas Wolf. The fineweb datasets: Decanting the web for the finest text data at scale. In *The Thirty-eight Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2024. URL https://openreview.net/forum?id=n6SCkn2QaG.

[32] Boris T Polyak and Anatoli B Juditsky. Acceleration of stochastic approximation by averaging. *SIAM journal on control and optimization*, 30(4):838–855, 1992.

[33] Xianbiao Qi, Marco Chen, Jiaquan Ye, Yelin He, and Rong Xiao. Delving into muon and beyond: Deep analysis and extensions. *arXiv preprint arXiv:2602.04669*, 2026.

[34] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pages 234–241. Springer, 2015.

[35] David Ruppert. Efficient estimations from a slowly convergent robbins-monro process. Technical report, Cornell University Operations Research and Industrial Engineering, 1988.

[36] Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *International journal of computer vision*, 115(3):211–252, 2015.

[37] Levent Sagun, Leon Bottou, and Yann LeCun. Eigenvalues of the hessian in deep learning: Singularity and beyond. *arXiv preprint arXiv:1611.07476*, 2016.

[38] Levent Sagun, Utku Evci, V Ugur Guney, Yann Dauphin, and Leon Bottou. Empirical analysis of the hessian of over-parametrized neural networks. *arXiv preprint arXiv:1706.04454*, 2017.

[39] Andrei Semenov, Matteo Pagliardini, and Martin Jaggi. Benchmarking optimizers for large language model pretraining, 2026. URL https://openreview.net/forum?id=Jw7khYzYzl.

[40] Wei Shen, Ruichuan Huang, Minhui Huang, Cong Shen, and Jiawei Zhang. On the convergence analysis of muon. *arXiv preprint arXiv:2505.23737*, 2025.

[41] Minhak Song, Kwangjun Ahn, and Chulhee Yun. Does SGD really happen in tiny subspaces? In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=v6iLQBoIJw.

[42] Minhak Song, Beomhan Baek, Kwangjun Ahn, and Chulhee Yun. Through the river: Understanding the benefit of schedule-free methods for language model training. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025. URL https://openreview.net/forum?id=CGx4XU9rCA.

[43] Wei Tao, Zhisong Pan, Gaowei Wu, and Qing Tao. Primal averaging: A new gradient evaluation step to attain the optimal individual convergence. *IEEE transactions on cybernetics*, 50(2): 835–845, 2018.

[44] Bhavya Vasudeva, Puneesh Deora, Yize Zhao, Vatsal Sharan, and Christos Thrampoulidis. How muon's spectral design benefits generalization: A study on imbalanced data. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=YzjS4jcfmS.

[45] Jinbo Wang, Mingze Wang, Zhanpeng Zhou, Junchi Yan, Weinan E, and Lei Wu. The sharpness disparity principle in transformers for accelerating language model pre-training. In *Forty-second International Conference on Machine Learning*, 2025. URL https://openreview.net/forum?id=DZ6iFdVDrx.

[46] Mingze Wang, Jinbo Wang, Haotian He, Zilin Wang, Guanhua Huang, Feiyu Xiong, Zhiyu li, Weinan E, and Lei Wu. Improving generalization and convergence by enhancing implicit regularization. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL https://openreview.net/forum?id=cjM2bhLOiC.

[47] Kaiyue Wen, Zhiyuan Li, Jason S. Wang, David Leo Wright Hall, Percy Liang, and Tengyu Ma. Understanding warmup-stable-decay learning rates: A river valley loss landscape view. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=m51BgoqvbP.

[48] Yuxin Wu and Justin Johnson. Rethinking "batch" in batchnorm. *arXiv preprint arXiv:2105.07576*, 2021.

[49] Zhewei Yao, Amir Gholami, Kurt Keutzer, and Michael W Mahoney. Pyhessian: Neural networks through the lens of the hessian. In *2020 IEEE international conference on big data (Big data)*, pages 581–590. IEEE, 2020.

[50] Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *CoRR*, abs/1605.07146, 2016. URL http://arxiv.org/abs/1605.07146.

[51] Minxin Zhang, Yuxuan Liu, and Hayden Schaeffer. Adam improves muon: Adaptive moment estimation with orthogonalized momentum. *arXiv preprint arXiv:2602.17080*, 2026.

[52] Yechen Zhang, Shuhao Xing, Junhao Huang, Kai Lv, Yunhua Zhou, Xipeng Qiu, Qipeng Guo, and Kai Chen. Mousse: Rectifying the geometry of muon with curvature-aware preconditioning. *arXiv preprint arXiv:2603.09697*, 2026.

[53] Wenjie Zhou, Bohan Wang, Wei Chen, and Xueqi Cheng. Bsfa: Leveraging the subspace dichotomy to accelerate neural network training. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 18845–18860, 2025.

[54] Shuchen Zhu, Rizhen Hu, Mingze Wang, Mou Sun, Xue Wang, Kun Yuan, and Zaiwen Wen. Accelerating llm pre-training through flat-direction dynamics enhancement. *arXiv preprint arXiv:2602.22681*, 2026.

# Contents

## Appendix A. Related Works

### A.1. River-Valley Loss Landscape

Previous studies have characterized neural network training through a low-rank Hessian structure, consisting of a few high-curvature directions and a much broader bulk component [11, 28–30, 37, 38, 49]. Recent work further interprets this geometry through the river-valley landscape (see Figure 1 for illustration), where dominant directions form steep valley walls while the bulk defines the flatter river floor where most useful progress occurs [2, 6, 10, 41, 45–47, 53].

Wen et al. [47] use this geometry to explain the success of Warmup-Stable-Decay (WSD) schedules in large language model pretraining: the stable phase facilitates rapid traversal along the river, while the decay phase helps the iterate settle onto the valley floor. Extending this perspective, Belloni et al. [2] show that a similar geometry also arises in convolutional networks trained on image classification tasks. Song et al. [41] show that projecting updates only onto the dominant subspace is insufficient to reduce training loss, while updates projected onto the bulk subspace remain effective. Recently, several works have leveraged the river-valley landscape to design optimizers that either amplify updates along river directions or stabilize oscillations along valley directions [21, 24, 52, 54].

### A.2. Schedule-Free Optimizer

Defazio et al. [9] introduce the schedule-free (SF) optimizer as an interpolation between Polyak–Ruppert (PR) averaging [32, 35] and primal averaging [26, 43]. Its update is given by

$$
\begin{aligned}
\boldsymbol{y}_t &= (1-\beta)\boldsymbol{z}_t + \beta\boldsymbol{x}_t, \\
\boldsymbol{z}_{t+1} &= \boldsymbol{z}_t - \eta\Delta_t, \\
\boldsymbol{x}_{t+1} &= (1 - c_{t+1})\,\boldsymbol{x}_t + c_{t+1}\boldsymbol{z}_{t+1},
\end{aligned}
\tag{4}
$$

where $\eta$ is the learning rate, $\Delta_t$ is the base optimizer update computed from the gradient at $\boldsymbol{y}_t$, $c_{t+1} = 1/(t+1)$, and the initialization satisfies $\boldsymbol{z}_1 = \boldsymbol{x}_1$. The framework can be combined with different base optimizers through the choice of $\Delta_t$. For example, defining $\Delta_t$ as a stochastic gradient at $\boldsymbol{y}_t$ gives SF-SGD, whereas computing $\Delta_t$ using an RMSProp update with decoupled weight decay gives SF-AdamW.

The three sequences play distinct roles: $\boldsymbol{y}_t$ is the gradient evaluation point, $\boldsymbol{z}_t$ is the primary iterate that follows the base optimizer update, and $\boldsymbol{x}_t$ is the averaged sequence used for inference. The interpolation parameter $\beta$ controls whether gradient evaluation tracks the fast-moving base trajectory ($\boldsymbol{z}_t$) or the more stable averaged trajectory ($\boldsymbol{x}_t$), thereby balancing rapid adaptation and stability. Under this formulation, SF optimizers are known to achieve a performance–time Pareto frontier, as evidenced by winning the Self-Tuning track of the 2024 AlgoPerf Challenge [7].

Song et al. [42] later connect the empirical success of SF optimization to the river-valley landscape, showing that, with an appropriate choice of $\beta$, the inference trajectory $\boldsymbol{x}_t$ of SF-AdamW follows the river throughout training. Their findings suggest that the implicit averaging in SF optimizer filters out high-curvature fluctuations from the valley walls. As a result, SF optimizer can remain near the river without requiring an explicit decay phase or an additional average of the model parameters.

### A.3. Muon Optimizer

Muon [16] is a recently introduced optimizer that leverages matrix structure by orthogonalizing matrix-valued updates. At each iteration $t$, given a matrix $\boldsymbol{W}_t$ and its gradient $\boldsymbol{G}_t$, the updates are

defined as:

$$\begin{aligned} \boldsymbol{M}_t &= \mu \boldsymbol{M}_{t-1} + (1-\mu)\boldsymbol{G}_t, \\ \boldsymbol{W}_{t+1} &= \boldsymbol{W}_t - \eta \mathcal{T}(\boldsymbol{M}_t), \end{aligned} \tag{5}$$

where $\eta$ is the learning rate, $\mu$ is the momentum coefficient, and $\mathcal{T}$ denotes an orthogonalization operator, which is approximated using a Newton-Schulz iteration [3] for computational efficiency. For non-matrix-valued parameters, including embeddings and classification heads, updates are instead performed using standard optimizers such as SGD or Adam(W).

Recent theoretical studies have begun to explain Muon's rapid convergence through the normalization effect of its matrix-wise orthogonalization, especially in ill-conditioned settings. Shen et al. [40] show that Muon can be advantageous when neural network Hessians exhibit low-rank or structured spectral geometry, while Ma et al. [25] show that its orthogonalization can act as an effective preconditioner, yielding condition-number-free linear convergence in matrix factorization and linear transformer settings. Other recent studies further show that Muon's orthogonalized updates induce balanced component learning [17], improving minority-group performance in imbalanced settings [44]. However, this same mechanism can also strengthen noisy components, potentially leading to less stable dynamics [33, 52].

## Appendix B.  Conclusion

We introduce AMUSE, an optimization algorithm designed to stabilize Muon via SF method and a time-varying interpolation parameter $\beta_t$. We observe that Muon's orthogonalization operator promotes training by leveraging large bulk components, but also induces oscillations along valley walls, thereby contributing to its inherent instability. AMUSE adopts a SF framework, a principled approach that controls where the gradient is evaluated and stabilizes training by keeping the optimization trajectory close to the river geometry. With a carefully designed schedule for the interpolation parameter $\beta_t$, AMUSE outperforms conventional learning-rate-scheduled Adam(W) or Muon optimizers across a wide range of deep learning tasks. Our results highlight how a systematic understanding of training dynamics and the loss landscape provides a principled approach to optimizer design.

Despite the superior performance of AMUSE compared with various optimizers including Muon, it requires additional memory overhead relative to vanilla Muon. Developing an optimization strategy that enhances updates along the river direction and suppresses valley-wall oscillations without incurring such overhead is a promising direction for future investigation.

## Appendix C. A Quadratic Example of Bouncing in Matrix-Normalized Updates

We compare standard gradient descent (GD) with an idealized matrix-normalized update on a two-dimensional matrix quadratic objective. This example is not intended to model the full momentum dynamics of Muon, but rather isolates the magnitude-removing effect of polar normalization. We use an anisotropic setting to show that matrix normalization removes gradient magnitude information, which can cause bouncing of small nonzero components near the optimum.

Let $\boldsymbol{W} \in \mathbb{R}^{2 \times 2}$ be the parameter matrix, and let $\boldsymbol{A} \in \mathbb{R}^{2 \times 2}$ be a symmetric positive definite matrix with an anisotropic spectrum:

$$\boldsymbol{A} = \boldsymbol{Q} \boldsymbol{\Lambda} \boldsymbol{Q}^\top, \qquad \boldsymbol{\Lambda} = \begin{pmatrix} \lambda & 0 \\ 0 & 1 \end{pmatrix},$$

where $\boldsymbol{Q}$ is an orthogonal matrix, and $\lambda \gg 1$ controls the curvature gap between the first and second principal directions. We consider the quadratic objective

$$f(\boldsymbol{W}) = \frac{1}{2} \operatorname{tr}(\boldsymbol{W}^\top \boldsymbol{A} \boldsymbol{W}),$$

where the gradient is $\nabla f(\boldsymbol{W}) = \boldsymbol{A} \boldsymbol{W}$. To analyze the dynamics, we project the parameters into the eigenbasis of $\boldsymbol{A}$ by defining $\boldsymbol{V}_t = \boldsymbol{Q}^\top \boldsymbol{W}_t$. Consider a diagonal iterate in this eigenbasis:

$$\boldsymbol{V}_t = \begin{pmatrix} a_t & 0 \\ 0 & b_t \end{pmatrix}.$$

Then, $\boldsymbol{W}_t = \boldsymbol{Q} \boldsymbol{V}_t$, and the gradient is:

$$\nabla f(\boldsymbol{W}_t) = \boldsymbol{A} \boldsymbol{W}_t = (\boldsymbol{Q} \boldsymbol{\Lambda} \boldsymbol{Q}^\top)(\boldsymbol{Q} \boldsymbol{V}_t) = \boldsymbol{Q} \boldsymbol{\Lambda} \boldsymbol{V}_t = \boldsymbol{Q} \begin{pmatrix} \lambda a_t & 0 \\ 0 & b_t \end{pmatrix}.$$

**Gradient Descent Dynamics.** GD with step size $\eta$ gives $\boldsymbol{W}_{t+1}^{\mathrm{GD}} = \boldsymbol{W}_t - \eta \nabla f(\boldsymbol{W}_t)$. Projecting this update into the eigenbasis yields:

$$\boldsymbol{V}_{t+1}^{\mathrm{GD}} = \boldsymbol{V}_t - \eta \boldsymbol{\Lambda} \boldsymbol{V}_t.$$

For the first coordinate, we have $a_{t+1}^{\mathrm{GD}} = (1 - \eta \lambda) a_t$.

If $0 < \eta < 1/\lambda$, then $0 < 1 - \eta \lambda < 1$, so

$$|a_{t+1}^{\mathrm{GD}}| < |a_t|, \qquad \operatorname{sign}(a_{t+1}^{\mathrm{GD}}) = \operatorname{sign}(a_t).$$

The update magnitude in the first coordinate is $|\Delta a_t^{\mathrm{GD}}| = \eta \lambda |a_t|$, which goes to zero as $a_t \to 0$.

**Matrix-Normalized Dynamics.** Now consider a matrix-normalized update, which idealizes the normalization effect of Muon. For a full-rank matrix $\boldsymbol{G}$, define its polar factor as:

$$\operatorname{Polar}(\boldsymbol{G}) = \boldsymbol{G}(\boldsymbol{G}^\top \boldsymbol{G})^{-1/2}.$$

We apply this to the gradient $\boldsymbol{G}_t = \nabla f(\boldsymbol{W}_t) = \boldsymbol{Q} \boldsymbol{\Lambda} \boldsymbol{V}_t$. When $a_t \neq 0$ and $b_t \neq 0$, we have:

$$\boldsymbol{G}_t^\top \boldsymbol{G}_t = \boldsymbol{V}_t^\top \boldsymbol{\Lambda}^\top \boldsymbol{Q}^\top \boldsymbol{Q} \boldsymbol{\Lambda} \boldsymbol{V}_t = \begin{pmatrix} (\lambda a_t)^2 & 0 \\ 0 & b_t^2 \end{pmatrix}.$$

The inverse square root is $\mathrm{diag}(|\lambda a_t|^{-1}, |b_t|^{-1})$. Therefore,

$$\mathrm{Polar}(\boldsymbol{G}_t) = \boldsymbol{Q} \begin{pmatrix} \lambda a_t & 0 \\ 0 & b_t \end{pmatrix} \begin{pmatrix} |\lambda a_t|^{-1} & 0 \\ 0 & |b_t|^{-1} \end{pmatrix} = \boldsymbol{Q} \begin{pmatrix} \mathrm{sign}(a_t) & 0 \\ 0 & \mathrm{sign}(b_t) \end{pmatrix}.$$

The matrix-normalized update is $\boldsymbol{W}_{t+1}^{\mathrm{MN}} = \boldsymbol{W}_t - \eta \, \mathrm{Polar}(\nabla f(\boldsymbol{W}_t))$. Projecting this back into the eigenbasis ($\boldsymbol{V}_{t+1}^{\mathrm{MN}} = \boldsymbol{Q}^\top \boldsymbol{W}_{t+1}^{\mathrm{MN}}$) gives $a_{t+1}^{\mathrm{MN}} = a_t - \eta \, \mathrm{sign}(a_t)$.

The contrast is therefore clear. GD preserves the magnitude information of the gradient, while the matrix-normalized update removes it through polar decomposition. For every nonzero $a_t$ in this full-rank regime, the matrix-normalized step magnitude remains constant:

$$|\Delta a_t^{\mathrm{MN}}| = \eta.$$

If $0 < |a_t| < \eta$, then

$$a_t a_{t+1}^{\mathrm{MN}} < 0,$$

so the first coordinate changes sign in one step. Moreover, if $0 < a_t < \eta$, then $a_{t+2}^{\mathrm{MN}} = a_t$, so the dynamics forms a two-cycle along this coordinate. Thus, unlike GD, the matrix-normalized update does not shrink as the component becomes arbitrarily small but nonzero. A small residual component can therefore receive a constant update and bounce across zero.

## Appendix D. Additional Results and Experimental Details for Section 2

In this section we provide additional experimental details and results for the analysis in Section 2. We include experimental setups and additional results that were omitted from the main text due to space constraints.

### D.1. Dominant Updates Can Cause Instability, while Bulk Updates Accelerate Training

In this subsection, we empirically show that updates along the dominant directions can cause training instability, while amplifying the bulk component can accelerate Muon training. Following Zhou et al. [53], we do this by decomposing each Muon update into its dominant and bulk components and scaling them separately.

We conduct experiments on three classification datasets: MNIST, CIFAR-10, and SST-2. Detailed experimental settings, including dataset construction and model architectures, are provided in Section D.2; hyperparameters are reported in the corresponding figure captions.

We use the dominant and bulk subspaces defined in Section 2. That is, for the Hessian $\nabla^2 \mathcal{L}(\theta_t)$, the dominant subspace $\mathcal{S}_k(\theta_t)$ is spanned by the top-$k$ eigenvectors, and the bulk subspace is its orthogonal complement $\mathcal{S}_k^\perp(\theta_t)$. Following the observation that the Hessian spectrum of classification models contains a small number of outlier eigenvalues related to the number of classes, we set $k$ to the number of classes: $k = 10$ for MNIST-5k and CIFAR-10-5k, and $k = 2$ for SST-2-1k.

Let $M_t$ denote the matrix-valued Muon momentum and define the flattened post-orthogonalized update direction as $u_t := \text{vec}(\mathcal{T}(M_t))$. Using the subspace projection matrices from Eq. (1), we decompose $u_t$ into dominant and bulk components as $P_k(\theta_t)u_t$ and $P_k^\perp(\theta_t)u_t$, respectively. We then rescale the two components separately:

$$\widetilde{u}_t = \alpha P_k(\theta_t)u_t + \gamma P_k^\perp(\theta_t)u_t,$$

where $\alpha$ and $\gamma$ are multiplicative scaling factors for the dominant and bulk components, respectively. For example, when $\alpha = \gamma = 1$, this recovers the original Muon update. The parameter is updated by

$$\theta_{t+1} = \theta_t - \eta \widetilde{u}_t.$$

As shown in Figure 7, larger $\alpha$ leads to more unstable training, indicating that dominant-subspace components can induce valley-wall oscillations. In contrast, larger $\gamma$ improves training speed and leads to more stable convergence, suggesting that bulk directions are responsible for useful optimization progress. These results suggest that reducing dominant components before orthogonalization is important for training stability, while preserving Muon's strong bulk-oriented updates is important for fast training.

### D.2. Experimental Details

We follow the experimental setup of Cohen et al. [5], Song et al. [41] for all experiments in Appendix D.3. For experiments in Appendix D.1, we use the same experimental setup except for introducing scaling factors following Zhou et al. [53].

#### D.2.1. ARCHITECTURE DETAILS

We consider three model architectures, chosen according to the input modality. For fully connected image classification, we use a three-layer MLP with width 200 and Tanh activations, following Cohen

Figure 7: **Scaling Dominant ($\alpha$) and Bulk ($\gamma$) components of Muon update.** We apply subspace-wise scaling to Muon updates starting at step 500. For CIFAR-10-5k and MNIST-5k, Muon is combined with SGD for non-Muon parameters, using momentum $0.9$ and learning rate $5 \times 10^{-4}$. For SST-2-1k, Muon is combined with AdamW for non-Muon parameters, using Muon momentum $0.9$, AdamW coefficients $(0.9, 0.99)$, and learning rate $1 \times 10^{-4}$.

et al. [5], Song et al. [41]. For convolutional image classification, we use a three-layer CNN with width 32 and ReLU activations, following Cohen et al. [5], Song et al. [41]. For text classification, we use a two-layer Transformer with hidden dimension 64 and 8 attention heads, following Damian et al. [8], Song et al. [41].

### D.2.2. DATASETS

We use three small-scale classification benchmarks constructed from MNIST, CIFAR-10, and SST-2. For MNIST and CIFAR-10, we use the first 5,000 training examples, each with 10 classes. For SST-2, we use the first 1,000 examples for binary sentiment classification. The main text reports the MNIST-5k experiment with MLP architecture in Section 2.

### D.2.3. EXPERIMENTAL SETUP

In all experiments in this section, including those in Section 2, we use cross-entropy loss with batch size 50. We use a constant learning rate for all optimizers: SGD, AdamW, Muon, and SF-Muon. For Muon and SF-Muon, non-hidden matrix layers are optimized with SGD in the CIFAR-10-5k and MNIST-5k experiments, and with AdamW (and its SF variant in SF-Muon) in the SST-2-1k experiment.

The hyperparameters for each experiment are reported in Tables 2, 1, and 3. Unless otherwise specified, each figure uses the hyperparameters corresponding to its dataset. For figures requiring additional hyperparameters, we use the following settings:

- Figure 2, Figure 3, and Figure 8: MNIST hyperparameters in Table 1.

- Figure 8, Figure 9, and Figure 11: CIFAR-10 hyperparameters in Table 2.

- Figure 8, Figure 10, and Figure 12: SST-2 hyperparameters in Table 3.

- Figure 2: AMUSE with learning rate $0.01$, $\beta_{init} = 0.8$, and $\rho = 0.6$.

- Figure 9: AMUSE with learning rate $0.02$, $\beta_{init} = 0.8$, and $\rho = 0.6$.

- Figure 10: AMUSE with learning rate $0.02$, $\beta_{init} = 0.8$, and $\rho = 0.6$.

Table 1: **Hyperparameters for MNIST-5k Experiments.**

| Optimizer | Learning rate | Momentum |
|---|---|---|
| SGD | 1e-2 | – |
| AdamW | 5e-4 | (0.9,0.99) |
| Muon | 1e-3 | 0.9 |
| SF-Muon ($\beta = 0.9$) | 2e-3 | 0.95 |

Table 2: **Hyperparameters for CIFAR10-5k Experiments.**

| Optimizer | Learning rate | Momentum |
|---|---|---|
| SGD | 1e-2 | – |
| AdamW | 5e-4 | (0.9,0.99) |
| Muon | 2e-3 | 0.9 |
| SF-Muon ($\beta = 0.8$) | 2e-3 | 0.9 |

Table 3: **Hyperparameters for SST2-1k Experiments.**

| Optimizer | Learning rate | AdamW Momentum | Muon momentum |
|---|---|---|---|
| AdamW | 5e-4 | (0.9,0.99) | – |
| Muon | 2e-3 | (0.9,0.99) | 0.9 |
| SF-Muon ($\beta = 0.8$) | 1e-4 | (–,0.99) | 0.9 |

### D.3. Additional Experimental Results

In this section, we provide additional results for the analysis in Section 2. We organize the results into three parts: Hessian eigenspectra, Muon bulk-ratio behavior, and SF-Muon dynamics.

**Hessian eigenspectrum.** We first examine the loss Hessian eigenspectrum across datasets and architectures. Figure 8 shows that the Hessian spectrum consistently contains a small number of large outlier eigenvalues, while the remaining eigenvalues are much smaller. This separation supports the dominant/bulk decomposition used in the main text.

**Bulk-oriented updates of Muon.** We next verify that the bulk-oriented behavior of Muon extends beyond the main setting. Figures 9 and 10 show that Muon produces substantially smaller dominant-ratio updates than SGD or AdamW across CIFAR-10 with a CNN and SST-2 with a Transformer. The same figures also compare the pre- and post-orthogonalized Muon updates, showing that the orthogonalization step itself increases the bulk component of the update. These results reinforce the explanation that Muon accelerates training by promoting movement in bulk directions, as mentioned in Section D.1.

**Schedule-Free Muon dynamics.** Finally, we repeat the SF-Muon analysis from the main text (Figure 3) on additional settings. Figures 11 and 12 compare the dominant/bulk components of Muon and SF-Muon, and also gradients at multiple virtual interpolation points $\boldsymbol{y}_t^{(\alpha)} = (1 - \alpha)\boldsymbol{z}_t + \alpha\boldsymbol{x}_t$. In both settings, the averaged SF-Muon trajectory has a much smaller dominant component than vanilla

Muon, and gradients evaluated closer to $x_t$ become more bulk-oriented. These results further support the claim that evaluating gradient near averaged iterate can suppress valley-wall contributions before the Muon orthogonalization step, as mentioned in Section 2.2.

(a) MNIST with MLP

(b) CIFAR-10 with CNN

(c) SST-2 with Transformer

Figure 8: **Eigenspectra of the loss Hessian across optimizers, datasets, and architectures.** Across all cases, a small number of top-$k$ eigenvalues, where $k$ corresponds to the number of classes, form clear outliers, while the remaining eigenvalues are significantly smaller. This separation highlights a low-dimensional dominant subspace and a high-dimensional bulk subspace.

(a) Muon vs. SGD/AdamW

(b) Momentum $\boldsymbol{m}_t$ vs. Update $\Delta\theta_t(=\mathcal{T}(\boldsymbol{m}_t))$

Figure 9: **Comparison of dominant component ratios on CIFAR-10 with CNN.** Metrics are measured on a CIFAR-10 5k subset using a CNN architecture. (**a**) Muon consistently produces substantially smaller dominant component updates than SGD and AdamW, and AMUSE further suppresses the dominant component. (**b**) Orthogonalization reduces Muon's dominant ratio compared to momentum $\boldsymbol{m}_t$; in contrast, AMUSE maintains low dominant ratios throughout, reflecting more stable gradient dynamics. Results are averaged over three runs.

(a) Muon vs. AdamW

(b) Momentum $\boldsymbol{m}_t$ vs. Update $\Delta\theta_t(=\mathcal{T}(\boldsymbol{m}_t))$

Figure 10: **Comparison of dominant component ratios on SST-2 with Transformer.** Metrics are measured on SST-2 using a Transformer architecture. (**a**) Muon consistently produces substantially smaller dominant component updates than AdamW, and AMUSE further suppresses the dominant component. (**b**) Orthogonalization reduces Muon's dominant ratio compared to momentum $\boldsymbol{m}_t$; in contrast, AMUSE maintains low dominant ratios throughout, reflecting more stable gradient dynamics. Results are averaged over three runs.

(a) Comparison of dominant ratios

(b) Dominant ratio of gradient at $\boldsymbol{y}_t^{(\alpha)}$

Figure 11: **Comparison of dominant component ratios on CIFAR-10 with CNN.** (**a**) Dominant ratios for Muon (blue) and SF-Muon (red). The solid and dashed red lines denote the dominant components of $\Delta\boldsymbol{x}_t$ and $\nabla\mathcal{L}(\boldsymbol{y}_t)$, respectively. (**b**) Dominant ratios for gradients at $\boldsymbol{y}_t^{(\alpha)} = (1 - \alpha)\boldsymbol{z}_t + \alpha\boldsymbol{x}_t$ across varying $\alpha$, demonstrating that larger $\alpha$ values correlate with lower dominant components.

(a) Comparison of dominant ratios

(b) Dominant ratio of gradient at $\boldsymbol{y}_t^{(\alpha)}$

Figure 12: **Comparison of dominant component ratios on SST-2 with Transformer.** (**a**) Dominant ratios for Muon (blue) and SF-Muon (red). The solid and dashed red lines denote the dominant components of $\Delta\boldsymbol{x}_t$ and $\nabla\mathcal{L}(\boldsymbol{y}_t)$, respectively. (**b**) Dominant ratios for gradients at $\boldsymbol{y}_t^{(\alpha)} = (1 - \alpha)\boldsymbol{z}_t + \alpha\boldsymbol{x}_t$ across varying $\alpha$, demonstrating that larger $\alpha$ values correlate with lower dominant components.

## Appendix E. Details for AMUSE

### E.1. Algorithmic Description of AMUSE

In this section, we present the full procedure of AMUSE, summarized in Algorithm 1.

---

**Algorithm 1** AMUSE: Anytime Muon with Stable Gradient Evaluation

---

**Require:** learning rate $\eta$, weight decay $\lambda$, AMUSE $\beta_{\text{init}}$, AMUSE $\rho$, Muon momentum $\mu$, AdamW second-moment coefficient $\beta_2$, numerical constant $\epsilon$, Muon scaling factor $s_{\text{NS}}$, warmup step $T_0$

1: Initialize $\boldsymbol{X}_1 \leftarrow \boldsymbol{Z}_1$, $\boldsymbol{M}_0 \leftarrow \boldsymbol{0}$, $\boldsymbol{V}_0 \leftarrow \boldsymbol{0}$
2: **for** $t = 1, 2, \ldots, T$ **do**
3:     $\eta_t \leftarrow \eta \cdot \min(1, t/T_0)$
4:     $c_{t+1} \leftarrow \frac{\eta_t^2}{\sum_{i=1}^{t} \eta_i^2}$
5:     **if** $t = T_0$ **then**
6:         $c_{\text{warm}} \leftarrow c_{t+1}$
7:     **end if**
8:     **if** $t \leq T_0$ **then**
9:         $\beta_t \leftarrow \beta_{\text{init}}$
10:     **else**
11:         $\beta_t \leftarrow 1 - \left( \frac{c_{t+1}(1 - c_{\text{warm}})}{c_{\text{warm}}(1 - c_{t+1})} \right)^{\rho} (1 - \beta_{\text{init}})$
12:     **end if**
13:     $\boldsymbol{Y}_t \leftarrow (1 - \beta_t)\boldsymbol{Z}_t + \beta_t \boldsymbol{X}_t$
14:     $\boldsymbol{G}_t \leftarrow \nabla \mathcal{L}(\boldsymbol{Y}_t)$
15:     **if** the parameter group uses Muon **then**
16:         $\boldsymbol{M}_t \leftarrow \mu \boldsymbol{M}_{t-1} + (1 - \mu)\boldsymbol{G}_t$
17:         $\boldsymbol{O}_t \leftarrow s_{\text{NS}} \cdot \text{Newton-Schulz}(\boldsymbol{M}_t)$
18:         $\boldsymbol{Z}_{t+1} \leftarrow (1 - \eta_t \lambda)\boldsymbol{Z}_t - \eta_t \boldsymbol{O}_t$
19:     **else if** the parameter group uses AdamW **then**
20:         $\boldsymbol{V}_t \leftarrow \beta_2 \boldsymbol{V}_{t-1} + (1 - \beta_2)(\boldsymbol{G}_t \odot \boldsymbol{G}_t)$
21:         $\widehat{\boldsymbol{V}}_t \leftarrow \boldsymbol{V}_t / (1 - \beta_2^t)$
22:         $\boldsymbol{U}_t \leftarrow \boldsymbol{G}_t \oslash \left( \sqrt{\widehat{\boldsymbol{V}}_t} + \epsilon \right)$
23:         $\boldsymbol{Z}_{t+1} \leftarrow (1 - \eta_t \lambda)\boldsymbol{Z}_t - \eta_t \boldsymbol{U}_t$
24:     **else if** the parameter group uses SGD **then**
25:         $\boldsymbol{Z}_{t+1} \leftarrow (1 - \eta_t \lambda)\boldsymbol{Z}_t - \eta_t \boldsymbol{G}_t$
26:     **end if**
27:     $\boldsymbol{X}_{t+1} \leftarrow (1 - c_{t+1})\boldsymbol{X}_t + c_{t+1}\boldsymbol{Z}_{t+1}$
28: **end for**
29: **return** $\boldsymbol{X}_{T+1}$

---

Figure 13: **Comparison between constant learning rate Muon and AMUSE in the 124M LLaMA setting**. **The left panel** shows the effect of EWA, where solid lines represent the original training trajectories and dotted lines represent their corresponding EWA trajectories. **The middle panel** shows the effect of learning rate decay, where after warmup we linearly decay the learning rate from $10^{-4}$ to 0 at selected iterations using Muon optimizer; solid lines denote the original trajectories, while dotted lines show the corresponding decay-phase trajectories. **The right panel** shows cosine similarity between consecutive updates, plotting $\cos(\Delta \boldsymbol{x}_t, \Delta \boldsymbol{x}_{t+1})$ for AMUSE and $\cos(\Delta \theta_t, \Delta \theta_{t+1})$ for Muon.

### E.2. AMUSE Follows the River

Following Song et al. [42], we test whether AMUSE already follows the river using two post-hoc evaluations: Exponential Weight Averaging (EWA) and an additional learning rate decay phase. If the optimizer still oscillates across valley walls, these procedures should substantially reduce the loss by moving the iterate closer to the river; if it already tracks the river, they should offer little benefit.

As shown in Figure 13, constant learning rate Muon benefits significantly from both EWA and learning rate decay, indicating strong valley-wall oscillation. In contrast, AMUSE shows little improvement from either procedure, suggesting it already stays near the river. This stable progress is further confirmed by AMUSE's high cosine similarity between consecutive updates of $\boldsymbol{x}_t$.

### E.3. Muon Momentum and Averaging After Orthogonalization

In this section, we justify why AMUSE retains the Muon momentum buffer $M_t$. Defazio et al. [9] observe that Schedule-Free SGD and AdamW do not require an explicit first-moment momentum buffer, since the displacement of the averaged sequence itself induces a momentum-like update. In particular, for uniform averaging and constant $\beta$, Theorem 4 in Defazio et al. [9] gives

$$\Delta X_t = \frac{t-1}{t+1}\Delta X_{t-1} + \frac{1}{t+1}\Delta Z_t, \tag{6}$$

$$\Delta Y_t = \beta \Delta X_t + (1-\beta)\Delta Z_t, \tag{7}$$

where $\Delta X_t := X_{t+1} - X_t$, $\Delta Y_t := Y_{t+1} - Y_t$, and $\Delta Z_t := Z_{t+1} - Z_t$. Thus, $\Delta X_t$ acts as an implicit momentum term that stabilizes the movement of the gradient-evaluation sequence $Y_t$.

For AMUSE, however, this implicit Schedule-Free momentum does not replace the Muon momentum buffer. Muon's momentum $M_t$ serves a distinct role: it accumulates recent gradients before the orthogonalization step, thereby determining the direction to which the Muon update is applied. Therefore, AMUSE retains $M_t$ while using the Schedule-Free interpolation to stabilize the point at which gradients are evaluated.

We next derive a closed-form expression for the update of the averaged sequence. Recall that

$$Z_{t+1} = Z_t - \eta \mathcal{T}(M_t), \qquad X_{t+1} = (1 - c_{t+1})\,X_t + c_{t+1}Z_{t+1}, \tag{8}$$

with initialization $Z_1 = X_1$. Since $c_{t+1} = 1/(t+1)$, $X_t$ is the uniform average of the $Z_t$ iterates, i.e., $X_t = \frac{1}{t}\sum_{i=1}^t Z_i$.

Each base iterate can be written as $Z_i = Z_1 - \eta \sum_{j=1}^{i-1} \mathcal{T}(M_j)$. Substituting this expression into the uniform average gives

$$X_t = \frac{1}{t}\sum_{i=1}^t \left( Z_1 - \eta \sum_{j=1}^{i-1} \mathcal{T}(M_j) \right) \tag{9}$$

$$= Z_1 - \frac{\eta}{t}\sum_{i=1}^t \sum_{j=1}^{i-1} \mathcal{T}(M_j) \tag{10}$$

$$= Z_1 - \frac{\eta}{t}\sum_{j=1}^{t-1} (t-j)\mathcal{T}(M_j). \tag{11}$$

We now derive the averaged-sequence update $\Delta X_t$ using the expression above:

$$\Delta X_t = -\frac{\eta}{t+1}\sum_{j=1}^t (t+1-j)\mathcal{T}(M_j) + \frac{\eta}{t}\sum_{j=1}^{t-1} (t-j)\mathcal{T}(M_j). \tag{12}$$

For $j = 1, \ldots, t-1$, the coefficient of $\mathcal{T}(M_j)$ is

$$\eta\left( \frac{t-j}{t} - \frac{t+1-j}{t+1} \right) = -\frac{\eta j}{t(t+1)}. \tag{13}$$

For $j = t$, only the first sum contributes, giving $-\frac{\eta}{t+1} = -\frac{\eta t}{t(t+1)}$. Combining both cases, we obtain

$$\Delta \boldsymbol{X}_t = -\frac{\eta}{t(t+1)} \sum_{j=1}^{t} j\mathcal{T}(\boldsymbol{M}_j). \tag{14}$$

Therefore, the averaged sequence in AMUSE averages a trajectory after orthogonalized Muon updates have already been applied, and $\Delta \boldsymbol{X}_t$ becomes a weighted average of previous orthogonalized updates. This is distinct from Muon momentum: the momentum buffer $\boldsymbol{M}_t$ smooths gradients before orthogonalization, whereas the averaged sequence $\boldsymbol{X}_t$ averages the trajectory induced by the already orthogonalized updates. Empirically, we also find that removing the Muon momentum buffer substantially degrades performance compared to the full AMUSE and SF-Muon update, as shown in Figure 25 in Appendix H.6.

### E.4. Derivation of the $\beta_t$ Schedule

In designing the schedule for $\beta_t$ in AMUSE, one might initially consider a monotonically increasing schedule toward 1. However, following the derivation by Song et al. [42], a closer inspection of the schedule-free (SF) update reveals that the $\boldsymbol{x}_t$ iterates perform an implicit averaging of the $\boldsymbol{y}_t$ iterates. To see this, first consider the fixed-$\beta$ case. Recall the updates from Eq. (4):

$$\boldsymbol{y}_t = (1 - \beta)\boldsymbol{z}_t + \beta\boldsymbol{x}_t, \tag{15}$$

$$\boldsymbol{z}_{t+1} = \boldsymbol{z}_t - \eta\Delta_t, \tag{16}$$

$$\boldsymbol{x}_{t+1} = (1 - c_{t+1})\,\boldsymbol{x}_t + c_{t+1}\boldsymbol{z}_{t+1}. \tag{17}$$

From the definition of $\boldsymbol{y}_{t+1}$, we have

$$\boldsymbol{z}_{t+1} = \frac{\boldsymbol{y}_{t+1} - \beta\boldsymbol{x}_{t+1}}{1 - \beta}. \tag{18}$$

Substituting this expression into the update of $\boldsymbol{x}_{t+1}$ gives

$$\boldsymbol{x}_{t+1} = (1 - c_{t+1})\boldsymbol{x}_t + c_{t+1}\frac{\boldsymbol{y}_{t+1} - \beta\boldsymbol{x}_{t+1}}{1 - \beta}. \tag{19}$$

Rearranging the terms involving $\boldsymbol{x}_{t+1}$ yields

$$((1 - \beta) + \beta c_{t+1})\,\boldsymbol{x}_{t+1} = (1 - c_{t+1})(1 - \beta)\boldsymbol{x}_t + c_{t+1}\boldsymbol{y}_{t+1}. \tag{20}$$

Equivalently,

$$\boldsymbol{x}_{t+1} = \frac{(1 - c_{t+1})(1 - \beta)}{(1 - c_{t+1})(1 - \beta) + c_{t+1}}\boldsymbol{x}_t + \frac{c_{t+1}}{(1 - c_{t+1})(1 - \beta) + c_{t+1}}\boldsymbol{y}_{t+1}. \tag{21}$$

Defining

$$\omega_{t+1} := \frac{c_{t+1}}{(1 - c_{t+1})(1 - \beta) + c_{t+1}}, \tag{22}$$

we obtain the recursion

$$\boldsymbol{x}_{t+1} = (1 - \omega_{t+1})\boldsymbol{x}_t + \omega_{t+1}\boldsymbol{y}_{t+1}. \tag{23}$$

Thus, $\boldsymbol{x}_{t+1}$ is an implicit weighted average of the evaluation points $\boldsymbol{y}_s$, with time-varying averaging coefficient $\omega_{t+1}$. If $c_{t+1} = 1/(t+1)$, the effective weight $\omega_{t+1}$ simplifies to

$$\omega_{t+1} = \frac{1}{t(1-\beta)+1}. \tag{24}$$

This expression suggests that, when designing a time-varying schedule, replacing $\beta$ by $\beta_t$ makes the effective averaging coefficient controlled by $t(1-\beta_t)$. If $\beta_t$ increases too rapidly toward 1, the term $1-\beta_t$ vanishes, causing $t(1-\beta_t)$ to decrease and thereby increasing the effective weight. An increasing effective weight implies that the implicit averaging window actually *shrinks*. From an optimization perspective, shrinking the averaging window at later stages of training is undesirable, since it reduces the stabilizing effect of the averaged sequence. Therefore, the schedule for $\beta_t$ should be chosen so that $t(1-\beta_t)$ does not decay too rapidly, preventing the implicit averaging window from collapsing.

Based on this observation, we define the upper boundary by considering the fastest schedule that still maintains the implicit averaging window after a given step $T_0$. Using the $\beta_t$ notation, the effective averaging coefficient is controlled by

$$\widetilde{\omega}_{t+1} := \frac{c_{t+1}}{(1-c_{t+1})(1-\beta_t)+c_{t+1}}. \tag{25}$$

Since the window size is inversely related to $\widetilde{\omega}_{t+1}$, keeping the window size fixed amounts to keeping $\widetilde{\omega}_{t+1}$ constant. Setting $\widetilde{\omega}_{t+1} = \widetilde{\omega}_{T_0+1}$ for $t \geq T_0$, we obtain

$$\widetilde{\omega}_{t+1} = \frac{c_{t+1}}{(1-c_{t+1})(1-\beta_t)+c_{t+1}} \tag{26}$$

$$= \frac{c_{T_0+1}}{(1-c_{T_0+1})(1-\beta_{T_0})+c_{T_0+1}} = \widetilde{\omega}_{T_0+1}. \tag{27}$$

Solving this equality for $\beta_t$ gives the constant-window boundary

$$\beta_t = 1 - \frac{c_{t+1}(1-c_{T_0+1})}{c_{T_0+1}(1-c_{t+1})}(1-\beta_{T_0}). \tag{28}$$

Building on this boundary condition, we introduce an interpolation parameter $\rho$ to control how quickly $\beta_t$ approaches this boundary. Taking $\beta_{T_0} = \beta_{\text{init}}$, we define, for $t \geq T_0$,

$$\beta_t = 1 - \left(\frac{c_{t+1}(1-c_{T_0+1})}{c_{T_0+1}(1-c_{t+1})}\right)^{\rho}(1-\beta_{\text{init}}). \tag{29}$$

This schedule interpolates between the standard fixed-$\beta$ schedule and the constant-window boundary: when $\rho = 0$, we recover $\beta_t = \beta_{\text{init}}$, while when $\rho = 1$, we recover the boundary that keeps $\widetilde{\omega}_t$ constant. By restricting $\rho \in [0,1]$, we ensure that the implicit averaging window is allowed to grow for $0 \leq \rho < 1$ and remains constant at the boundary when $\rho = 1$. Thus, the schedule prevents the averaging window from shrinking while still allowing $\beta_t$ to increase over training.

**Visualization of Averaging Window Size and $\beta_t$.** To better understand the impact of our proposed schedule on the averaging dynamics, we visualize both the effective averaging window and the trajectory of $\beta_t$. By unrolling the recursive schedule-free update, the final averaged parameter $\boldsymbol{x}_T$

Figure 14: **Effect of $\rho$ on effective weights $\alpha_t$.** Histograms of $\alpha_t$ across varying sequence lengths $T$. For $T > T_0 = 2000$, lower $\rho$ values allow the effective averaging window to continuously grow, whereas $\rho = 1$ strictly fixes the window to its size at $T_0$.

can be explicitly expressed as a weighted sum of all past iterates $\boldsymbol{y}_t$, i.e., $\boldsymbol{x}_T = \sum_{t=1}^{T} \alpha_t \boldsymbol{y}_t$, where the global effective weight $\alpha_t$ assigned to each step $t$ is defined as:

$$\alpha_t \triangleq \frac{c_t}{(1 - c_t)(1 - \beta_{t-1}) + c_t} \prod_{s=t+1}^{T} \left[ \frac{(1 - c_s)(1 - \beta_{s-1})}{(1 - c_s)(1 - \beta_{s-1}) + c_s} \right].$$

This weight $\alpha_t$ directly dictates the size and shape of the effective averaging window. In Figure 14, we plot the histogram of these weights $\alpha_t$ (initialized with $\beta_{\text{init}} = 0.8$) to illustrate how much "memory" the final model retains from past steps. The exact shape of this distribution is governed by the interpolation parameter $\rho$. Specifically, when $\rho = 0$, the schedule allows the averaging window size to grow approximately linearly throughout training. In contrast, setting $\rho = 1$ strictly fixes the window size after the initial warmup phase ($T_0 = 2000$). For any intermediate value ($0 < \rho < 1$), the schedule smoothly interpolates between these two extremes, providing a controlled, sub-linear growth of the memory window. Furthermore, we visualize the actual evolution of $\beta_t$ over time in Figure 15.

Figure 15: **Evolution of $\beta_t$ controlled by $\rho$.** After the initial warmup phase ($T_0 = 2000$, dotted vertical line), $\rho$ smoothly interpolates between a constant $\beta$ baseline ($\rho = 0$) and the strict constant-window upper bound ($\rho = 1$).

### E.5. Implementation Details

**Averaging Coefficient.** In the main text, we use the simplified intuition $c_t = 1/t$. In the implementation, we follow the learning-rate-weighted averaging rule used in Defazio et al. [9]. Let $\eta_t$ denote the effective learning rate at step $t$, including linear warmup. Rather than using a uniform average during warmup, we set

$$c_{t+1} = \frac{\eta_t^2}{\sum_{i=1}^{t} \eta_i^2}.$$

This prevents very early iterations, where the learning rate is small, from being overweighted in the averaged sequence. After warmup, $\eta_t$ becomes constant and the coefficient recovers the usual $1/t$-type decay.

**Batch Normalization.** Averaging methods, including Schedule-Free [9], require special care for models with BatchNorm. During training, gradients are evaluated at the interpolated sequence $\boldsymbol{Y}_t$, so BatchNorm running statistics are accumulated for the training-time parameter state. During evaluation, however, the returned model is the averaged sequence $\boldsymbol{X}_t$. Therefore, the stored BatchNorm running statistics may not match the parameters used for evaluation.

For models with BatchNorm, we first convert the optimizer/model to the $\boldsymbol{X}_t$-state and then refresh BatchNorm statistics by forwarding a small number of training batches without gradient updates. This is analogous to PreciseBN-style recalibration [48]. No such step is needed for normalization layers that do not maintain batch-dependent running statistics, such as LayerNorm or RMSNorm, which are used in our language model experiments.

**Weight Decay.** Following Defazio et al. [9], weight decay may be applied either to the gradient-evaluation sequence $\boldsymbol{y}_t$ or to the base sequence $\boldsymbol{z}_t$. In our implementation, we apply the standard weight-decay term to $\boldsymbol{z}_t$. We keep decay at $\boldsymbol{y}_t$ as a separate optional variant, but do not use it unless explicitly stated.

**Computational Resources.** We use up to 8 NVIDIA RTX A6000 GPUs for the image-domain experiments and the 124M Llama experiments. For experiments at the 720M scale and above, we use up to 8 NVIDIA A100 GPUs with data-parallel training.

## Appendix F. Image Domain Experiments

### F.1. Experimental Details

For the image-domain experiments, we mostly follow the experimental setup of Defazio et al. [9]. We additionally include Muon as a new baseline and add the ISIC 2018 image segmentation task.

  We follow the standard Muon hybrid setup [16]: Muon is applied to hidden matrix-valued layers, while SGD with momentum is used for non-Muon parameters. Only for MAE fine-tuning in image domain experiments, we instead use the Muon+AdamW hybrid setup commonly used for Transformer models [16, 20]: Muon is applied to the hidden-layer weight matrices of the ViT backbone, while AdamW is used for the classifier head and all one-dimensional parameters, including biases and LayerNorm parameters.

  When available, we use the tuned hyperparameters reported by Defazio et al. [9] for SGD, SF-SGD, AdamW, and SF-AdamW. For Muon and AMUSE, we tune the learning rate, and weight decay following the same tuning protocol. For vanilla Muon, we also tune the learning rate of the auxiliary SGD optimizer separately, since using the same learning rate for Muon and SGD led to poor performance.

  For AMUSE, we fix the Muon momentum to $0.95$ and use the same learning rate for the auxiliary SGD optimizer, reducing the number of tuned hyperparameters. In the Muon+SGD image-domain setting, AMUSE uses SGD without momentum for the non-Muon parameters (SF-SGD update for non-Muon parameters). For MAE fine-tuning, we use Muon with AdamW for non-Muon parameters, AMUSE uses AdamW without first momentum and we fix the second-moment coefficient to $\beta_2 = 0.999$ (SF-AdamW update for non-Muon parameters). Thus, beyond the base learning rate and weight decay, AMUSE only additionally adjusts the AMUSE-specific parameters $\beta_{init}$ and $\rho$.

**CIFAR-10.**    We train a Wide-ResNet-16-8 architecture [50] on the CIFAR-10 image classification [19] dataset. We use a batch size of 128 and train for 300 epochs.

Table 4: **Hyperparameters for CIFAR-10.**

| SGD and SF-SGD | | | | Muon and AMUSE | | |
|---|---|---|---|---|---|---|
| **Hyperparameter** | **SGD** | **SF-SGD** | | **Hyperparameter** | **Muon** | **AMUSE** |
| Epochs | 300 | | | Epochs | 300 | |
| Batch size | 128 | | | Batch size | 128 | |
| Warmup ratio | 0.05 | | | Warmup ratio | 0.05 | |
| Seeds | 5 | | | Seeds | 5 | |
| Learning Rate | 0.2 | 10.0 | | Muon LR | 0.05 | 0.2 |
| Weight decay | 0.0001 | 0.0001 | | SGD LR | 0.0001 | 0.2 |
| SGD momentum $\beta$ | 0.9 | – | | Weight decay | 0.01 | 0.02 |
| SF-SGD $\beta_1$ | – | 0.9 | | Muon momentum $\mu$ | 0.9 | 0.95 |
| LR decay scheduler | cosine | – | | SGD momentum $\beta$ | 0.9 | – |
| | | | | AMUSE $\beta_{init}$ | – | 0.8 |
| | | | | AMUSE $\rho$ | – | 0.3 |
| | | | | LR decay scheduler | cosine | – |

**CIFAR-100.** We train a DenseNet architecture [15] in the CIFAR-100 image classification dataset. We use a batch size of 64 and train for 300 epochs.

Table 5: **Hyperparameters for CIFAR-100.**

| SGD and SF-SGD | | | Muon and AMUSE | | |
|---|---|---|---|---|---|
| **Hyperparameter** | **SGD** | **SF-SGD** | **Hyperparameter** | **Muon** | **AMUSE** |
| Epochs | | 300 | Epochs | | 300 |
| Batch size | | 64 | Batch size | | 64 |
| Warmup ratio | | 0.05 | Warmup ratio | | 0.05 |
| Seeds | | 5 | Seeds | | 5 |
| Learning Rate | 0.05 | 5.0 | Muon LR | 0.05 | 0.5 |
| Weight decay | 0.0002 | 0.0002 | SGD LR | 0.001 | 0.5 |
| SGD momentum $\beta$ | 0.9 | – | Weight decay | 0.005 | 0.002 |
| SF-SGD $\beta_1$ | – | 0.9 | Muon momentum $\mu$ | 0.9 | 0.95 |
| LR decay scheduler | cosine | – | SGD momentum $\beta$ | 0.9 | – |
| | | | AMUSE $\beta_{init}$ | – | 0.7 |
| | | | AMUSE $\rho$ | – | 0.4 |
| | | | LR decay scheduler | cosine | – |

**SVHN.** We train a ResNet-3-96 architecture [12] on the Street View House Numbers (SVHN) dataset [27]. We use a batch size of 32 and train for 300 epochs.

Table 6: **Hyperparameters for SVHN.**

| SGD and SF-SGD | | | Muon and AMUSE | | |
|---|---|---|---|---|---|
| **Hyperparameter** | **SGD** | **SF-SGD** | **Hyperparameter** | **Muon** | **AMUSE** |
| Epochs | | 300 | Epochs | | 300 |
| Batch size | | 32 | Batch size | | 32 |
| Warmup ratio | | 0.05 | Warmup ratio | | 0.05 |
| Seeds | | 5 | Seeds | | 5 |
| Learning Rate | 0.1 | 1.0 | Muon LR | 0.05 | 0.05 |
| Weight decay | 0.0001 | 0.0002 | SGD LR | 0.001 | 0.05 |
| SGD momentum $\beta$ | 0.9 | – | Weight decay | 0.002 | 0.01 |
| SF-SGD $\beta_1$ | – | 0.9 | Muon momentum $\mu$ | 0.9 | 0.95 |
| LR decay scheduler | cosine | – | SGD momentum $\beta$ | 0.9 | – |
| | | | AMUSE $\beta_{init}$ | – | 0.8 |
| | | | AMUSE $\rho$ | – | 0.2 |
| | | | LR decay scheduler | cosine | – |

**ImageNet-1k.** We train a ResNet-50 architecture [12] on the ILSVRC 2012 [36] ImageNet-1k classification dataset. We use a batch size of 256 and train for 100 epochs.

Table 7: **Hyperparameters for ImageNet-1k.**

| **SGD and SF-SGD** | | | | **Muon and AMUSE** | | |
|---|---|---|---|---|---|---|
| **Hyperparameter** | **SGD** | **SF-SGD** | | **Hyperparameter** | **Muon** | **AMUSE** |
| Epochs | 100 | | | Epochs | 100 | |
| Batch size | 256 | | | Batch size | 256 | |
| Warmup ratio | 0.05 | | | Warmup ratio | 0.05 | |
| Seeds | 5 | | | Seeds | 5 | |
| Learning Rate | 0.05 | 1.5 | | Muon LR | 0.1 | 0.5 |
| Weight decay | 0.0001 | 0.00005 | | SGD LR | 0.00001 | 0.5 |
| SGD momentum $\beta$ | 0.9 | – | | Weight decay | 0.001 | 0.0005 |
| SF-SGD $\beta_1$ | – | 0.9 | | Muon momentum $\mu$ | 0.9 | 0.95 |
| LR decay scheduler | cosine | – | | SGD momentum $\beta$ | 0.9 | – |
| | | | | AMUSE $\beta_{init}$ | – | 0.5 |
| | | | | AMUSE $\rho$ | – | 0.8 |
| | | | | LR decay scheduler | cosine | – |

**ISIC2018.** We train a base U-Net architecture [34] on the ISIC 2018 dataset [4] for binary medical image segmentation. We use a batch size of 8 and train for 50 epochs. Our implementation is based on the U-Bench codebase[*].

Since this setup is newly added in our paper, we extensively tune the learning rate, weight decay, and momentum for each baseline. For vanilla Muon, we additionally tune the auxiliary SGD learning rate used for non-Muon parameters.

Table 8: **Hyperparameters for ISIC2018.**

| **SGD and SF-SGD** | | | | **Muon and AMUSE** | | |
|---|---|---|---|---|---|---|
| **Hyperparameter** | **SGD** | **SF-SGD** | | **Hyperparameter** | **Muon** | **AMUSE** |
| Epochs | 50 | | | Epochs | 50 | |
| Batch size | 8 | | | Batch size | 8 | |
| Warmup ratio | 0.05 | | | Warmup ratio | 0.05 | |
| Seeds | 5 | | | Seeds | 5 | |
| Learning Rate | 0.02 | 2e-3 | | Muon LR | 0.01 | 0.2 |
| Weight decay | 0.0005 | 0.01 | | SGD LR | 0.001 | 0.2 |
| SGD momentum $\beta$ | 0.9 | – | | Weight decay | 0.001 | 0.05 |
| SF-SGD $\beta_1$ | – | 0.9 | | Muon momentum $\mu$ | 0.9 | 0.95 |
| LR decay scheduler | cosine | – | | SGD momentum $\beta$ | 0.9 | – |
| | | | | AMUSE $\beta_{init}$ | – | 0.6 |
| | | | | AMUSE $\rho$ | – | 0.2 |
| | | | | LR decay scheduler | cosine | – |

**MAE.** We fine-tune a pretrained MAE ViT-Base model (`vit_base_patch16`) on ImageNet-1K for 100 epochs. The model uses $16 \times 16$ patches and the standard ViT-Base architecture with 12 transformer blocks, hidden size 768, and 12 attention heads.

All runs use the same AdamW-pretrained MAE pretrained initialization and differ only in optimizer-specific hyperparameters. Since MAE fine-tuning starts from an AdamW-pretrained checkpoint, we carefully tune the initial interpolation value $\beta_{init}$ for AMUSE. We use smaller $\beta_{init}$

---

[*]. https://github.com/FengheTan9/U-Bench

values than in the other experiments to avoid a large early discrepancy between the base sequence and the averaged sequence, allowing the base trajectory to adapt smoothly to the fine-tuning objective. Our implementation uses the official mae code[*].

Table 9: **Hyperparameters for MAE fine-tuning.**

**AdamW and SF-AdamW**

| Hyperparameter | AdamW | SF-AdamW |
|---|---|---|
| Epochs | | 100 |
| Batch size | | 256 |
| Warmup ratio | | 0.05 |
| Learning rate | 5e-4 | 2e-3 |
| Weight decay | 0.05 | 0.05 |
| AdamW $\beta_1$ | 0.9 | – |
| SF-AdamW $\beta_1$ | – | 0.9 |
| AdamW $\beta_2$ | 0.999 | 0.999 |
| LR decay scheduler | cosine | – |
| Drop Path | | 0.1 |
| Reprob | | 0.25 |
| Mixup | | 0.8 |
| Cutmix | | 1.0 |

**Muon and AMUSE**

| Hyperparameter | Muon | AMUSE |
|---|---|---|
| Epochs | | 100 |
| Batch size | | 256 |
| Warmup ratio | | 0.05 |
| Learning rate | 2e-4 | 2e-3 |
| Weight decay | 0.01 | 0.05 |
| Muon momentum | 0.95 | 0.95 |
| AdamW $\beta_1$ | 0.9 | – |
| AMUSE $\beta_{init}$ | – | 0.4 |
| AdamW $\beta_2$ | 0.999 | 0.999 |
| AMUSE $\rho$ | – | 0.3 |
| LR decay scheduler | cosine | – |
| Drop Path | | 0.1 |
| Reprob | | 0.25 |
| Mixup | | 0.8 |
| Cutmix | | 1.0 |

---

[*]. https://github.com/facebookresearch/mae

## Appendix G. Large Language Model Experiments

### G.1. Architecture Details

Our experimental setup follows Semenov et al. [39], using the codebase at `https://github.com/epfml/llm-optimizer-benchmark`. We use three decoder-only Llama-style models with approximately 124M, 720M, and 1.3B parameters. Across all model sizes, we use a sequence length of 512, the GPT-2 tokenizer with vocabulary size 50,304, RMSNorm with $\epsilon = 10^{-5}$, bias-free projections, SwiGLU MLPs with `multiple_of=256`, no dropout, and bfloat16 training. Table 10 summarizes the model-specific dimensions.

Table 10: **Model configurations for LLM experiments.**

| Model size | Layers | Attention heads | Hidden size |
|------------|--------|-----------------|-------------|
| 124M | 12 | 12 | 768 |
| 720M | 12 | 16 | 2048 |
| 1.3B | 24 | 32 | 2048 |

### G.2. Hyperparameter Tuning

For AdamW, D-Muon, and SF-AdamW baselines, we use the tuned hyperparameters reported by Semenov et al. [39]. At the 124M scale, their tuning includes learning rate, warmup steps, weight decay, learning-rate scheduler, gradient clipping, and optimizer-specific momentum parameters. For AdamW, the searched optimizer-specific parameters are $\beta_1$ and $\beta_2$. For Muon (D-Muon), the search includes learning rate, Muon momentum, AdamW hyperparameters for one-dimensional parameters, and whether to use Nesterov momentum. For SF-AdamW, the search includes learning rate, warmup length, weight decay, gradient clipping, and the Schedule-Free AdamW parameters $\beta_1$ and $\beta_2$, without a learning-rate decay schedule.

For AMUSE, we do not introduce additional tuning of the underlying optimizer momentums. We fix the Muon momentum to $0.95$, and keep the AdamW momentum parameters for non-Muon parameters fixed to $0.999$ to avoid additional hyperparameter tuning. We tune hyperparameters introduced by AMUSE: the initial interpolation value $\beta_{init}$ and $\rho$. Specifically, we sweep $\beta_{init} \in \{0.4, 0.6\}$ and $\rho \in \{0.6, 0.8\}$. Across our experiments, $\rho = 0.8$ consistently performs well.

Since Semenov et al. [39] report experiments only up to the 720M scale, we additionally evaluate a 1.3B model to test whether the observed results persist at a larger scale. For this setting, we initialize each optimizer from its corresponding 720M hyperparameter configuration and perform a learning-rate sweep for all methods, including AMUSE. See Tables 11–14 for the selected hyperparameters, and Table 15 for the AMUSE hyperparameter search grid.

### G.2.1. HYPERPARAMETERS FOR 124M PARAMETERS MODEL

Table 11: **Selected hyperparameters at the 124M scale.**

**AdamW and Muon (D-Muon)**

| Hyperparameter | AdamW | Muon |
|---|---|---|
| Learning rate | 0.001 | 0.002 |
| Batch size | 256 | 256 |
| Sequence length | 512 | 512 |
| Warmup steps | 2000 | 2000 |
| Weight decay | 0.1 | 0.1 |
| Gradient clipping | 0.5 | 0.5 |
| AdamW $\beta_1$ | 0.8 | 0.8 |
| AdamW $\beta_2$ | 0.999 | 0.999 |
| Muon momentum | – | 0.95 |
| LR decay scheduler | cosine | cosine |

**SF-AdamW and AMUSE**

| Hyperparameter | SF-AdamW | AMUSE |
|---|---|---|
| Learning rate | 0.002 | 0.01 |
| Batch size | 256 | 256 |
| Sequence length | 512 | 512 |
| Warmup steps | 8000 | 6000 |
| Weight decay | 0.1 | 0.05 |
| Gradient clipping | 0.5 | 0.5 |
| AMUSE $\beta_{init}$ | – | 0.6 |
| AMUSE $\rho$ | – | 0.8 |
| SF-AdamW $\beta_1$ | 0.9 | – |
| AdamW $\beta_2$ | 0.9999 | 0.999 |
| Muon momentum | – | 0.95 |
| LR decay scheduler | – | – |

### G.2.2. HYPERPARAMETERS FOR 720M PARAMETERS MODEL

Table 12: **Selected hyperparameters at the 720M scale.**

**AdamW and Muon (D-Muon)**

| Hyperparameter | AdamW | Muon |
|---|---|---|
| Learning rate | 0.001 | 0.001 |
| Batch size | 1984 | 1984 |
| Sequence length | 512 | 512 |
| Warmup steps | 2000 | 2000 |
| Weight decay | 0.1 | 0.1 |
| Gradient clipping | 0.1 | 0.1 |
| AdamW $\beta_1$ | 0.9 | 0.9 |
| AdamW $\beta_2$ | 0.999 | 0.99 |
| Muon momentum | – | 0.95 |
| LR decay scheduler | cosine | cosine |

**SF-AdamW and AMUSE**

| Hyperparameter | SF-AdamW | AMUSE |
|---|---|---|
| Learning rate | 0.001 | 0.01 |
| Batch size | 1984 | 1984 |
| Sequence length | 512 | 512 |
| Warmup steps | 8000 | 2000 |
| Weight decay | 0.1 | 0.1 |
| Gradient clipping | 0.1 | 0.1 |
| AMUSE $\beta_{init}$ | – | 0.4 |
| AMUSE $\rho$ | – | 0.8 |
| SF-AdamW $\beta_1$ | 0.9 | – |
| AdamW $\beta_2$ | 0.9999 | 0.999 |
| Muon momentum | – | 0.95 |
| LR decay scheduler | – | – |

### G.2.3. HYPERPARAMETERS FOR 1.3B PARAMETERS MODEL

Table 13: **Selected hyperparameters for AdamW and Muon (D-Muon) at the 1.3B scale.** We initialize from the 720M configuration and sweep the learning rate. Bold values indicate the selected learning rate.

| Hyperparameter | AdamW | Muon |
|---|---|---|
| Learning rate | 0.0005, **0.001**, 0.002 | 0.0005, 0.001, **0.002** |
| Batch size | 2048 | 2048 |
| Sequence length | 512 | 512 |
| Warmup steps | 2000 | 2000 |
| Weight decay | 0.1 | 0.1 |
| Gradient clipping | 0.1 | 0.1 |
| AdamW $\beta_1$ | 0.9 | 0.9 |
| AdamW $\beta_2$ | 0.999 | 0.99 |
| Muon momentum | – | 0.95 |
| LR decay scheduler | cosine | cosine |

Table 14: **Selected hyperparameters for SF-AdamW and AMUSE at the 1.3B scale.** We initialize from the 720M configuration and sweep the learning rate. Bold values indicate the selected learning rate.

| Hyperparameter | SF-AdamW | AMUSE |
|---|---|---|
| Learning rate | 0.0005, 0.001, **0.002** | 0.005, **0.01**, 0.02 |
| Batch size | 2048 | 2048 |
| Sequence length | 512 | 512 |
| Warmup steps | 8000 | 2000 |
| Weight decay | 0.1 | 0.1 |
| Gradient clipping | 0.1 | 0.1 |
| AMUSE $\beta_{init}$ | – | 0.4 |
| AMUSE $\rho$ | – | 0.8 |
| SF-AdamW $\beta_1$ | 0.9 | – |
| AdamW $\beta_2$ | 0.9999 | 0.999 |
| Muon momentum | – | 0.95 |
| LR decay scheduler | – | – |

### G.2.4. SEARCH GRID TABLE FOR AMUSE

For AdamW, SF-AdamW, and Muon (D-Muon), we use the best reported hyperparameters from the LLM optimizer benchmark of Semenov et al. [39]. Their full search spaces are provided in the original benchmark and are substantially larger than ours. For example, the Muon search for the 124M Llama model sweeps over more than 2,000 hyperparameter configurations. We report the AMUSE search grid below.

Table 15: **AMUSE hyperparameter search grid for LLM pretraining.** Selected values are shown in bold.

| Scale | Hyperparameter | Search grid |
|---|---|---|
| | Learning rate | 0.002, 0.005, **0.01**, 0.02 |
| | Batch size | 256 |
| | Sequence length | 512 |
| 124M | Warmup steps | 2000, 4000, **6000** |
| | Weight decay | 0.01, **0.05**, 0.1 |
| | Gradient clipping | **0.5** |
| | AMUSE $\beta_{\mathrm{init}}$ | 0.4, **0.6** |
| | AMUSE $\rho$ | 0.6, **0.8** |
| | Learning rate | 0.002, 0.005, **0.01**, 0.02 |
| | Batch size | 1984 |
| | Sequence length | 512 |
| 720M | Warmup steps | **2000** |
| | Weight decay | **0.1** |
| | Gradient clipping | **0.1** |
| | AMUSE $\beta_{\mathrm{init}}$ | **0.4**, 0.6 |
| | AMUSE $\rho$ | **0.8** |
| | Learning rate | 0.005, **0.01**, 0.02 |
| | Batch size | 2048 |
| | Sequence length | 512 |
| 1.3B | Warmup steps | **2000** |
| | Weight decay | **0.1** |
| | Gradient clipping | **0.1** |
| | AMUSE $\beta_{\mathrm{init}}$ | **0.4** |
| | AMUSE $\rho$ | **0.8** |

*Fixed across sweeps:* AdamW $\beta_2 = 0.999$, Muon momentum 0.95, no LR decay.

## Appendix H.  Additional Experiments

### H.1.  Comparison with Additional Optimizer Baselines

We first compare AMUSE with other strong optimizer baselines for 124M Llama pretraining. In addition to AdamW, Muon, and SF-AdamW, we include AdEMAMix, ADOPT, Signum, Prodigy, MARS, Lion, Sophia, and SOAP, using the tuned hyperparameters reported by Semenov et al. [39]. As shown in Figure 16, AMUSE achieves the best validation perplexity among these optimizers, indicating that its advantage is not limited to the main baselines considered in the paper.

Figure 16: **Comparison with Other Baselines on Llama 124M model.**

### H.2.  Comparison with Muon with EWA and WSD

We further compare AMUSE with Muon equipped with exponential weight averaging (EWA) and warmup-stable-decay (WSD). These baselines test whether the gains of AMUSE can be matched by adding an external averaging mechanism or an explicit decay phase to constant-LR Muon.

For the 124M Llama experiment, we tune constant-LR Muon over learning rate, warmup steps, and weight decay, while keeping the momentum parameters the same as in the cosine-decay Muon baseline. The best constant-LR Muon setting uses learning rate $10^{-3}$, weight decay 0.05, and 1000 warmup steps. We apply EWA with multiple averaging coefficients ($\alpha = 0.99, 0.999, 0.9995$) to this tuned constant-LR Muon trajectory, and also run WSD-style decay phases for 2k iterations starting from multiple Muon checkpoints.

As shown in Figure 17, both EWA and WSD improve constant-LR Muon. EWA gives better validation perplexity with stronger averaging, and applying a 2k-step decay phase from Muon checkpoints substantially lowers perplexity. However, none of the EWA variants or WSD decay runs matches the performance of AMUSE, and AMUSE remains better throughout training. This suggests that AMUSE does not merely imitate post-hoc averaging or learning-rate decay, but instead maintains a more stable trajectory during training while preserving fast progress.

For ImageNet, we additionally evaluate Muon with EWA using the same EWA coefficient grid. In this experiment, we use the optimal hyperparameters of the cosine-scheduled Muon baseline and apply EWA. As shown in Figure 18, Muon+EWA does not outperform AMUSE for any averaging

coefficient. This suggests that AMUSE does not merely behave like an external weight average or a learning-rate decay, but instead maintains a more stable trajectory during training.

(a) Muon with multiple EWA coefficients

(b) Muon with WSD decay

Figure 17: **Comparison with Muon+EWA and Muon+WSD on 124M Llama pretraining.** Left: we apply exponential weight averaging (EWA) with multiple averaging coefficients to the tuned constant-LR Muon trajectory. Right: we apply 2k-step WSD-style decay phases starting from multiple Muon checkpoints. Both EWA and WSD improve constant-LR Muon, but none of these variants matches AMUSE.

Figure 18: **Comparison with Muon with EWA on ImageNet.**

### H.3. Longer Training Results

We further train AMUSE and the main baselines on 124M and 720M Llama models for extended horizons, corresponding to approximately $3.4\times$ and $4.5\times$ the Chinchilla token budget, respectively. Following Semenov et al. [39], we use the best hyperparameters tuned at 16,000 iterations and keep them fixed for the longer training run. As shown in Figure 19, AMUSE achieves the lowest validation perplexity on the 124M model at all evaluated steps except the final 64k step. On the 720M model, AMUSE outperforms all baselines by a large margin throughout training, without additional hyperparameter tuning. Notably, unlike cosine-scheduled baselines whose learning-rate schedules must be specified for a predefined training horizon, AMUSE requires only a single run with no explicit decay schedule. This *single AMUSE trajectory* performs strongly across different training horizons, suggesting that its averaged trajectory remains effective beyond the standard training budget.

(a) 124M Longer-horizon Training          (b) 720M Longer-horizon Training

Figure 19: **Longer-horizon language model pretraining on FineWeb.** We train AMUSE and the main baselines on 124M and 720M Llama models for approximately $3.4\times$ and $4.5\times$ the Chinchilla token budget, respectively. AMUSE remains highly competitive throughout the extended training horizon, often achieving the best validation perplexity without explicit learning-rate decay schedule. Notably, unlike cosine-scheduled baselines that require a predefined training horizon, a single AMUSE trajectory performs strongly across training horizons, highlighting its anytime training capability.

### H.4. Hyperparameter Sensitivity

**Language Model Pretraining (FineWeb with 124M Llama).** Figure 20 and Table 16 show the sensitivity of AMUSE to $\beta_{\text{init}}$ and $\rho$ in the 124M Llama setting. AMUSE shows only mild variation in validation perplexity across the tested ranges. Moreover, every swept configuration achieves lower perplexity than the tuned Muon baseline with cosine learning-rate decay.

(a) $\beta_{\text{init}}$ Sweep Results

(b) $\rho$ Sweep Results

Figure 20: **Hyperparameter sensitivity varying $\beta_{\text{init}}$ and $\rho$ on Llama-124M training.** AMUSE remains robust to both $\beta_{\text{init}}$ and $\rho$, exhibiting stable learning curves across the tested configurations.

Table 16: **Hyperparameter sensitivity of AMUSE on 124M Llama pretraining.**

| Sweep | Hyperparameter value | Validation perplexity |
|---|---|---|
| $\beta_{\text{init}}$ sweep, $\rho = 0.8$ | 0.4 | 28.81 |
| | 0.5 | 28.70 |
| | 0.6 | 28.61 |
| | 0.7 | 28.73 |
| $\rho$ sweep, $\beta_{\text{init}} = 0.6$ | 0.6 | 28.79 |
| | 0.7 | 28.68 |
| | 0.8 | 28.61 |
| | 0.9 | 28.63 |
| Muon with cosine decay | – | 29.21 |

**Image Classification (ImageNet with ResNet-50).** Figure 21 and Table 17 show analogous results in the image-domain setting, using ImageNet with ResNet-50. AMUSE is similarly robust to both $\beta_{\text{init}}$ and $\rho$: its learning curves remain stable across the tested ranges, and nearly all configurations outperform the tuned Muon baseline with cosine learning-rate decay.

(a) $\beta_{\text{init}}$ Sweep Results

(b) $\rho$ Sweep Results

Figure 21: **Hyperparameter sensitivity varying $\beta_{\text{init}}$ and $\rho$ on ImageNet training.** AMUSE exhibits stable performance across a range of hyperparameter choices. Results are averaged over five runs.

Table 17: **Hyperparameter sensitivity of AMUSE using ImageNet with ResNet-50.**

| Sweep | Hyperparameter value | Test Accuracy (%) |
|---|---|---|
| | 0.4 | 77.24 |
| $\beta_{init}$ sweep, $\rho = 0.8$ | 0.5 | 77.17 |
| | 0.6 | 77.03 |
| | 0.7 | 77.23 |
| $\rho$ sweep, $\beta_{init} = 0.5$ | 0.8 | 77.17 |
| | 0.9 | 76.89 |
| Muon with cosine decay | – | 76.97 |

## H.5. Wall-clock Time Comparison

We compare the per-iteration wall-clock time of different optimizers in the 124M Llama pretraining setting. Following common practice in optimizer runtime comparisons, we report the average training iteration time, including forward pass, backward pass, and optimizer update. All optimizers are evaluated with the same model, sequence length, global batch size, precision, hardware, and distributed training configuration. AMUSE has a per-iteration cost similar to Muon, while SF-AdamW has a per-iteration cost similar to AdamW. The main runtime difference between these two groups comes from the Newton–Schulz iterations used to orthogonalize Muon updates, which are also used by AMUSE for Muon-updated layers.

Table 18: **Wall-clock time comparison on 124M Llama pretraining.** We report average iteration time after discarding warmup iterations. Each iteration processes $256 \times 512$ tokens. Relative time is normalized by AdamW.

| Optimizer | Iter. time (s) | Relative time | Throughput (tokens/s) |
|---|---|---|---|
| AdamW | 0.674 | 1.000 | 194,469 |
| SF-AdamW | 0.684 | 1.015 | 191,626 |
| Muon | 0.706 | 1.047 | 185,654 |
| AMUSE | 0.719 | 1.067 | 182,298 |

### H.6. Ablation Studies

**Comparison with SF-Muon.** We compare AMUSE with fixed-$\beta$ SF-Muon. SF-Muon is tuned over the same hyperparameter grid, including multiple fixed $\beta$ values. As shown in Figures 22 and 23, fixed-$\beta$ SF-Muon does not outperform AMUSE in either setting. In particular, its improvement becomes limited in the later stage of training, suggesting that a fixed gradient-evaluation point cannot maintain the same trade-off between early speed and late-stage stability. By gradually increasing $\beta_t$, AMUSE continues to make progress later in training while preserving stable optimization.

Figure 22: **Comparison between AMUSE and fixed-$\beta$ SF-Muon on 124M Llama pretraining.** We compare AMUSE with SF-Muon using the best fixed interpolation value, $\beta = 0.95$. Fixed-$\beta$ SF-Muon makes progress early in training but its improvement becomes limited in the later stage. In contrast, AMUSE continues to improve by gradually moving the gradient-evaluation point toward the averaged trajectory.

Figure 23: **Comparison between AMUSE and fixed-$\beta$ SF-Muon on Image domain experiments.** We compare AMUSE with SF-Muon in image classification benchmarks.

**Can We Stop Increasing $\beta_t$ After It Becomes Large?** We further test whether AMUSE's improvement comes only from reaching a specific large interpolation value. To do so, we use the best hyperparameter for AMUSE, $\beta_{\text{init}} = 0.6$ and $\rho = 0.8$, but cap $\beta_t$ at the best fixed value used by SF-Muon, $\beta = 0.95$. That is, after $\beta_t$ reaches 0.95, we keep it fixed instead of allowing it to continue increasing toward 1.

As shown in Figure 24, the clipped schedule performs worse than AMUSE, and the gap increases later in training. This indicates that AMUSE benefits not only from using a large $\beta_t$, but also from continuously shifting the evaluation point toward the averaged trajectory.

Figure 24: **Effect of stopping the increase of $\beta_t$ in AMUSE. (Left)** Validation perplexity on 124M Llama pretraining. The clipped variant underperforms AMUSE, with the gap widening later in training. (**Right**) Evolution of $\beta_t$. While both methods reach similar large values, AMUSE continues to increase $\beta_t$, whereas the clipped variant saturates to 0.95.

**AMUSE without Muon Momentum.** To examine the role of Muon momentum in AMUSE and SF-Muon, we remove the momentum buffer used before the orthogonalization step. As shown in Figure 25, removing Muon momentum causes a large performance drop for both methods. This indicates that momentum is crucial before orthogonalization: it smooths stochastic gradient noise before orthogonalization and accumulates a more reliable update direction, including useful bulk components.

(a) AMUSE w/o Muon momentum        (b) SF-Muon w/o Muon momentum

Figure 25: **Momentum ablation on 124M Llama pretraining.** Removing momentum in Muon substantially degrades both AMUSE and SF-Muon, showing that momentum is essential for stability.

**Applying $\beta_t$ Scheduling and Momentum to SF-AdamW.** We investigate whether the modified $\beta_t$ schedule introduced in Eq. (3) can also improve the performance of SF-AdamW. As shown in Figure 26, applying only the $\beta_t$ schedule does not improve performance over the original SF-AdamW. In contrast, when combined with AdamW's first-moment ($\beta_1 = 0.9$), the $\beta_t$ schedule consistently improves performance throughout training, yielding lower validation perplexity in both the early and late stages.

Interestingly, neither the $\beta_t$ schedule nor first-moment alone improves performance over the original SF-AdamW. In contrast, applying both together consistently improves validation perplexity throughout training, indicating that the two components are effective only when used in combination.

However, incorporating first-moment in AdamW into SF-AdamW requires maintaining an additional momentum buffer, resulting in higher memory consumption than either AdamW or AMUSE.

Figure 26: **Effect of $\beta_t$ scheduling and momentum in SF-AdamW.** We evaluate whether the modified $\beta_t$ schedule used in AMUSE can improve SF-AdamW in 124M Llama pretraining. Applying only the $\beta_t$ schedule ($\beta_{\text{init}} = 0.6$, $\rho = 0.6$) degrades performance relative to the original SF-AdamW. Combining AdamW's first-moment ($\beta_1 = 0.9$) with the $\beta_t$ schedule improves validation perplexity throughout training, benefiting both the early and late training stages. Hyperparameters were tuned separately for the schedule variant.