Does GNN Pretraining Help Molecular Representation?

Abstract

Extracting informative representations of molecules using Graph neural networks
(GNNs) is crucial in AI-driven drug discovery. Recently, the graph research
community has been trying to replicate the success of self-supervised pretraining in
natural language processing, with several successes claimed. However, we find the
benefit brought by self-supervised pretraining on molecular data can be negligible in
many cases. We conduct thorough ablation studies on the key components of GNN
pretraining, including pretraining objectives, data splitting methods, input features,
pretraining dataset scales, and GNN architectures, in deciding the accuracy of the
downstream tasks. Our first important finding is, self-supervised graph pretraining
do not have statistically significant advantages over non-pretraining methods in
many settings. Second, although improvement can be observed with additional
supervised pretraining, the improvement may diminish with richer features or
more balanced data splits. Third, experimental hyper-parameters have a larger
impact on accuracy of downstream tasks than the choice of pretraining tasks. We
hypothesize the complexity of pretraining on molecules is insufficient, leading to
less transferable knowledge for downstream tasks.

1 Introduction

Graph neural networks (GNNs) , due to their effectiveness, have been adopted to model a wide
range of structured data, such as social networks, road graphs, citation networks, etc. Among
those applications, molecule modeling is probably one of the most important, as it serves as the
foundation of biomedical area, nurtuing techniques like novel drug discovery. However, since
biomedical labeling are usually time-consuming and expensive, task-specific labels are extremely
inadequate in this domain, posing a big challenge to this field. Recently, inspired by the remarkable
success of self-supervised pretraining from natural language processing [4, 2, 23] and computer
vision domains [9, 3], researchers start trying to apply the pretrain-finetune paradigm to molecule
modeling with GNN, hoping to boost the performance of various molecular tasks by pretraining the
model on the enormous unlabeled data. For instance, many GNN pretraining methods have been
proposed [26, 24] and many of them claim significant performance improvement by pretraining on
large scale datasets [10, 18, 29, 30, 31]. Despite of the promising results, we find that reproducing the
outstanding gain due to graph pretraining is non-trivial, and sometimes the improvement largely relies
on the experiment setup (data splits, etc) and the extensive hyper-parameter tuning of downstream
tasks, instead of the designs of pretraining objectives. These observations motivate us to rethink the
effectiveness of graph pretraining (mainly unsupervised and self-supervised) and investigate what
factors really influence the effectiveness of self-supervised graph pretraining.

In this paper, we perform systematic studies to assess the performance of popular graph pretraining
objectives on different types of datasets, and exploit various confounding components in experimental
setup in deciding the performance of downstream tasks with or without pretraining. Here, we restrict

Figure 1: A typical pipeline for graph pretraining and deployment for downstream applications.

our studies to molecular graphs, as opposed to other application domains, such as social networks or citation graphs. The key insights and take-aways of this paper are:

- Regardless of the design of the pretraining tasks, applying self-supervised pretraining alone does not provide statistically significant improvements over non-pretrained methods on downstream tasks.

- Only when additional supervised pretraining step is conducted after self-supervised pretraining, we might observe statistically significant improvements. However, the gain becomes marginal on some specific data splits or diminishes if richer features are introduced.

- Beyond data splits and hand-crafted features, the usefulness of graph pretraining is also sensitive to the experimental hyperparameters, such as learning rates and number of study repeats. Different setups can lead to opposite conclusions.

- In conclusion, different from the previous works, we do not observe clear and unconditional gains achieved by graph pretraining on molecular representation, indicating it is still too early to conclude graph pretraining is effective for molecular domain.

- We investigate the reason of above and hypothesize that the complexity of pretraining on molecules is insufficient, leading to less transferable knowledge for downstream tasks.

Below we first introduce the background about GNN and its pretraining in Section 2, and our experimental design and results in Section 3 and Section 4, respectively. Finally we conclude with our findings and the limitations in Section 5 and Section 7.

2 Preliminary

Table 1: Summary of Experiments. Table 12 and Table 13 are deferred to appendix due to space limit.

	Pretrain Objective		Graph Features		Downstream Splits		GNN Arch		Pretrain Dataset	
	Self-Supervise	Supervise	Rich	Basic	Balanced	Scaffold	GIN	GraphSage	ZINC15	SAVI
Table 2	✔		✔		✔		✔		✔	
Table 3		✔	✔		✔		✔		✔	
Table 4	✔		✔			✔	✔		✔	
Table 5		✔	✔			✔	✔		✔	
Table 6	✔			✔	✔		✔		✔	
Table 7		✔		✔	✔		✔		✔	
Table 8	✔			✔		✔	✔		✔	
Table 9		✔		✔		✔	✔		✔	
Table 10	✔	✔	✔		✔		✔			✔
Table 11	✔	✔	✔			✔	✔			✔
Table 12	✔	✔	✔		✔			✔	✔	
Table 13	✔	✔	✔			✔		✔	✔	

Graph Neural Networks (GNNs). Let $G = \{V, E\}$ denotes a molecule graph with V as node set and E as edge set. Given the node features X_i, GNNs learn an embedding representation h_i for every node $i \in V$ by aggregating representations from connected nodes and edges, denoted as graph convolution. These procedure repeats for K times with the update equation as follows:

$$h_i^k = \text{UPDATE}(h_i^{k-1}, \text{AGGREGATE}(\{h_i^{k-1}, h_j^{k-1}, e_{ij}\} : \forall j \in N(i)))$$

where $\mathcal{N}(i)$ is the set of neighbor nodes of i and $h_i^0 = X_i$. The representation for entire graph G is then obtained by permutation-invariant transformation on node representation, $h_G = \text{READOUT}(h_i^K | i \in V)$.

Finetune. After the pretraining, the pretrained model is used to finetune on the downstream tasks. For molecule property prediction tasks, the graph-level representation obtained from the pretrained model is connected to linear classifiers to predict downstream task labels. The fine-tuning is performed on the end-to-end model, including pretrained GNN models and linear classifiers.

Graph pretraining objectives. The primary goal of pretraining is to learn representations with robust transferable knowledge of graphs from the abundant pretraining data and then generalize to downstream tasks with usually different supervision signals. Generally the pretraining objectives can be categorized into self-supervised and supervised ones. We present a brief overview of some representative objectives in the following sections.

2.1 Self-supervised (unsupervised) pretraining

In self-supervised pretraining, the pretraining objective is designed to learn self-generated targets from the structure of the molecules, such as the type of nodes and edges, prediction of local context, graph partition, node clustering, occurrence of some functional groups, and etc. The predictive target can be node/edge level or entire graph level. We present some representative ones below:

2.1.1 Node Prediction

Node prediction is a node-level classification task given the masked context of entire graph. Similar with Devlin et al. [4], some proportion of node attributes are masked and replaced with mask-specified indicators in the node input feature. After graph convolution, the embedding output from GNN is used to predict the true attribute of the node, e.g. atom type in molecular graphs, through a linear classifier on top of the node embedding.

2.1.2 Context Prediction

Context prediction task is a sub-graph level task aiming at learning embedding that can represent the local subgraph surrounding a node. Generally it can be viewed as a masked task for substructure. Since it is essentially a structured prediction which can be difficult in general, Hu et al. [10] leverages the adversarial learning to teach the model distinguish from the positive sub-graph embedding and negative sub-graph embeddings. Rong et al. [18] instead builds a dictionary of structures that captures the property of sub-graphs (e.g. type and quantity of neighbour nodes and bonds), and turns it into a multi-class classification problem.

2.1.3 Motif Prediction

Motif prediction [18] is to predict the existence of functional groups, such as benzene ring or hydroxyl. The motifs are extracted automatically from RDKit [12] . The motif task is formulated as a graph-level multi-label binary classification task, where graph embedding is used to jointly predict the occurrence of these semantic functional motifs.

2.1.4 Contrastive learning

Graph contrastive learning is to maximize the agreement of two augmented views of the same graph, and minimize the agreement of different graphs. The optimization is conducted using contrastive loss in the latent embedding space [29, 8, 31, 24]. The augmentation function needs to transform graphs into realistic and novel augmentations without affecting semantic labels of the graphs. For example, the transformation can be small perturbations or modifications on node/edge embedding, drop of a few nodes or edges, and so on. These transformations enforce an underlying prior for contrastive learning, that is, local transformation does not change semantic meaning of a graph.

2.2 Supervised pretraining

Supervised pretraining aims to learn domain-specific graph-level knowledge from specific designed pretraining tasks. For molecular application, the supervised labels are generated from a diverse set of functional studies, such as biochemical assays. The pretrainning task is to perform multiple binary classification and jointly learn the supervised labels. Although pretraining mainly refer to

Table 2: **Self-supervised** + Rich feature + Balanced Scaffold Split. No pretrain has an average value of 78.0% over all 5 datasets.

Methods	BBBP	BACE	TOX21	TOXCAST	SIDER	AVE GAIN
No pretrain	92.23($\pm$3.07)	87.43($\pm$1.63)	79.20($\pm$1.99)	69.13($\pm$0.55)	61.92($\pm$0.89)	0($\pm$1.626)
Node Prediction	92.24($\pm$2.76)	87.32($\pm$1.67)	79.57($\pm$2.03)	69.77($\pm$0.13)	61.62($\pm$1.12)	0.122($\pm$1.542)
Context Prediction	92.68($\pm$1.19)	86.98($\pm$1.26)	79.05($\pm$2.51)	70.18($\pm$0.44)	61.65($\pm$0.77)	0.126($\pm$1.234)
Motif Prediction	92.63($\pm$1.19)	87.16($\pm$1.66)	79.22($\pm$2.38)	69.09($\pm$0.07)	62.45($\pm$1.25)	0.128($\pm$1.310)
Contrastive learning	92.31($\pm$1.58)	86.67($\pm$2.40)	78.45($\pm$2.44)	68.37($\pm$0.80)	61.22($\pm$1.20)	-0.578($\pm$1.684)

unsupervised or self-supervised methods as they are not limited by the need of labels, supervised pretraining is still a great source to investigate graph pretraining.

Table 3: **Supervised** + Rich feature + Balanced Scaffold. No pretrain has an average AUC of 78.0%.

Methods	BBBP	BACE	TOX21	TOXCAST	SIDER	AVE GAIN
No pretrain	92.23($\pm$3.07)	87.43($\pm$1.63)	79.2($\pm$1.99)	69.13($\pm$0.55)	61.92($\pm$0.89)	0($\pm$1.626)
Supervised	91.65($\pm$2.11)	86.91($\pm$1.86)	81.13($\pm$2.39)	71.64($\pm$0.46)	62.14($\pm$1.13)	0.712($\pm$1.590)
Masking Node + Supervised	**93.43($\pm$2.50)**	86.90($\pm$2.04)	**81.93($\pm$1.79)**	71.66($\pm$0.73)	62.68($\pm$1.82)	1.338($\pm$1.776)
Context Prediction + Supervised	92.27($\pm$1.57)	**88.72($\pm$1.68)**	81.71($\pm$1.79)	**72.19($\pm$0.79)**	**63.21($\pm$1.49)**	1.638($\pm$1.464)

3 Experiment framework

To investigate pretraining on graphs for molecule representations, we first revisit the typical pretraining-finetuning pipeline used in the literature. Figure 1 shows the overall procedure of deployment, with several design choices presented at each stage of the pipeline. Since different choices at each stage can lead to different outcomes of the performance on the downstream tasks, we investigate them one at a time and keep others the same. The design principle of our experiment framework is to analyze the effect of *every* stage in this pipeline as comprehensive as possible.

3.1 Design choices

We consider the design choices for the four pretraining objectives.

Pretraining objective In Section 2 we have provided a brief literature review over the pretraining methods for molecule representation. Here we categorize those pretraining by different principles, and present one well-recognized representative of each category. The representatives are selected because they have more desired properties, such as better performance, compared with their counterparts.

- **Masking.** We leverage the node prediction objective, which randomly masks 15% of the nodes' feature and then ask GNN to make prediction on the node attributes of the masked ones. This strategy resembles the BERT pretraining [4] in natural language processing.
- **Structured.** Unlike text data where the topology is a sequence, the graph has rich structure information. Following Hu et al. [10], we use context prediction objective, which masks out the context from k_1-hops to k_2-hops and leverages adversarial training to predict the true context embeddings from the random context embeddings.
- **Graph-level self-supervised.** Following [18], GNN is asked to predict whether a motif is contained in a molecule. The motif can be extracted from the molecule with RDKit [12]. The motifs are 85 motifs [1] for multi-label classification.
- **Contrastive.** We leverage the contrastive learning approach in [29], where we corrupt the input node features with Gaussian noise to generate different views of the same graph, and maximize the consistency between positive pairs (same graph) and minimize that between negative pairs (different graphs).
- **Graph-level supervised.** Finally when applicable, we use the ChEMBL dataset with graph-level labels for graph-level supervised pretraining as Hu et al. [10].

The above are the design choices for pretraining objectives. Next, we consider other factors that influence graph-pretraining performance.

Graph Features Each molecule is represented by a graph with atoms as nodes and bonds as edges. In this paper we mainly consider the graph representations without the 3D information. For each molecule graph, chemical properties of nodes and edges are extracted to serve as node and edge features for the graph neural networks. Depending on how rich the features are, we categorize the design choice into two categories:

---

[1] http://rdkit.org/docs/source/rdkit.Chem.Fragments.html

Table 4: Self-supervised + Rich feature + **Scaffold**. No pretrain has an average ROC-AUC of 71.8% over all benckmark datasets.

Methods	BBBP	BACE	TOX21	TOXCAST	SIDER	AVE GAIN
No pretrain	74.83($\pm$0.73)	80.10($\pm$0.42)	75.86($\pm$0.58)	65.95($\pm$0.15)	62.30($\pm$1.14)	0($\pm$0.579)
Node Prediction	73.45($\pm$0.27)	83.66($\pm$0.75)	75.30($\pm$0.37)	66.50($\pm$0.06)	65.08($\pm$0.12)	0.990($\pm$0.323)
Context Prediction	74.10($\pm$0.22)	81.87($\pm$0.49)	75.37($\pm$0.11)	66.86($\pm$0.07)	62.84($\pm$0.46)	0.400($\pm$0.280)
Motif Prediction	73.65($\pm$0.36)	80.58($\pm$2.04)	74.55($\pm$0.79)	65.63($\pm$0.07)	64.05($\pm$0.23)	-0.116($\pm$0.766)
Contrastive learning	73.32($\pm$2.38)	80.51($\pm$0.80)	74.55($\pm$0.22)	65.70($\pm$0.09)	64.39($\pm$0.63)	-0.114($\pm$0.513)

Table 5: Supervised + Self-supervised + Rich feature + **Scaffold**. No pretrain get 71.8% average ROC-AUC.

Methods	BBBP	BACE	TOX21	TOXCAST	SIDER	AVE GAIN
No pretrain	**74.83**($\pm$**0.73**)	80.10($\pm$0.42)	75.86($\pm$0.58)	65.95($\pm$0.15)	62.30($\pm$1.14)	0($\pm$0.604)
Supervised	72.79($\pm$0.7)	83.23($\pm$0.67)	77.66($\pm$0.08)	67.72($\pm$0.13)	65.34($\pm$0.17)	1.540($\pm$0.350)
Masking Node + Supervised	73.38($\pm$0.55)	**84.42**($\pm$**0.27**)	**77.85**($\pm$**0.24**)	**67.14**($\pm$**0.28**)	64.06($\pm$0.28)	1.562($\pm$0.324)
Context Prediction + Supervised	73.81($\pm$0.52)	84.35($\pm$0.93)	77.11($\pm$0.14)	67.87($\pm$0.08)	**65.19**($\pm$**0.17**)	1.858($\pm$0.368)

- **Basic features.** The basic set of features are the ones used in Hu et al. [10]. Specifically, the node features contain the atom type and the derived features, such as formal charge list, chirality list, etc. The edge features contain the bond types and the bond directions. These features are categorical, and thus will be encoded in a one-hot vector individually and then concatenated together to form the feature vector for node/edge representation.

- **Rich features.** The rich feature set is a superset of the basic features. In addition to the basic ones mentioned above, it comes with the additional node features such as hydrogen acceptor match, acidic match and bond features such as ring information. This set of features are used in Rong et al. [18]. Additionally and importantly, we follow their setting to incorporate additional 2d normalized rdNormalizedDescriptors features [2], which is used in the downstream tasks (but not used in pretraining).

Please refer to the original papers for the full set of basic [10] and rich [18] features, respectively.

GNN Backbone The GNN architecture also plays a role in graph pretraining. In Hu et al. [10], the results show that pretraining on GNN variants like GIN [27] would improve the performance on downstream tasks, while the performance with architectures like GAT [22] would actually get worse performance with pretraining. As the GNNs based on 1-Weisfeiler-Lehman (WL) test have similar representation power [27] bounded by the Weisfeiler-Lehman isomorphism check [19], we consider the two representative GNN architectures, namely the **GIN** [27] and **GraphSage** [7]. They have shown benefits with graph pretraining in Hu et al. [10].

Pretraining dataset In natural language pretraining, researchers observed a significant performance boost due to self-supervised pretraining on large-scale data, that is, the larger the pretraining dataset is, the better the downstream performance it is [16]. Inspired by this success in natural language processing, we test the algorithms on two different-scale unlabeled pretraining datasets.

- **ZINC15 [21]** ZINC15 contains 2 million molecules. This dataset was preprocessed following Hu et al. [10].
- **SAVI [15]** The SAVI dataset contains about 1 billion molecules, which are significantly larger than ZINC15. To the best of our knowledge, it hasn't been used for pretraining tasks. This dataset contains drug-like molecules synthesized by computer simulated reactions.

Additionaly, we used **ChEMBL [6]** as the supervised datasets. Different from the above ZINC15 and SAVI dataset which is only used for self-supervised pretraining, this dataset contains 500k drug-able molecules with 1,310 prediction target labels from bio-activity assays for drug discovery. Thus like in Hu et al. [10] we only leverage it for *supervised* pretraining.

Data split on downstream tasks The downstream tasks for molecular domain we used are 5 benchmark datasets from MoleculeNet [25]. See Appendix A.3 for more details. The train/valid/test sets are split with ratio 8:1:1. For molecule domain, the random split is not the most meaningful way to assess the performance, because the real-world senarios often require generalization ability on out-of-distribution samples. So we consider the following ways to split the data:

- **Scaffold Split [10, 17]** This strategy first sorts the molecules according to the scaffold (e.g. molecule structure), and then partition the sorted list into train/valid/test splits consecutively. Therefore, the molecules in train and test sets are most different ones according to their molecule structure. Note this strategy would yield deterministic data splits.

---

[2] https://github.com/bp-kelley/descriptastorus for the feature descriptor.

Table 6: Self-supervised + **Basic feature** + Balanced Scaffold. No pretrain has an average AUC of 76.7% over all 5 datasets.

Methods	BBBP	BACE	TOX21	TOXCAST	SIDER	AVE GAIN
No pretrain	91.46($\pm$ 0.85)	84.29($\pm$ 3.80)	78.35($\pm$ 0.95)	68.31($\pm$ 1.61)	61.15($\pm$ 2.46)	0($\pm$1.934)
Node Prediction	91.23($\pm$ 1.51)	84.97($\pm$ 1.55)	77.77($\pm$ 1.23)	68.98($\pm$ 1.11)	61.20($\pm$ 0.41)	0.118($\pm$1.162)
Context Prediction	92.13($\pm$ 1.04)	84.83($\pm$ 3.19)	78.79($\pm$ 2.52)	68.29($\pm$ 1.23)	62.32($\pm$ 2.99)	0.560($\pm$2.194)

Table 7: Supervised + Self-supervised + **Basic feature** + Balanced Scaffold. No pretrain has an average AUC of 76.7%.

Methods	BBBP	BACE	TOX21	TOXCAST	SIDER	AVE GAIN
No pretrain	91.46($\pm$ 0.85)	84.29($\pm$ 3.80)	78.35($\pm$ 0.95)	68.31($\pm$ 1.61)	61.15($\pm$ 2.46)	0($\pm$ 1.934)
Supervised	90.70($\pm$ 0.74)	84.22($\pm$ 2.69)	80.45($\pm$ 1.47)	69.47($\pm$ 1.06)	**63.38($\pm$ 1.44)**	0.932($\pm$ 1.480)
Masking Node + Supervised	91.10($\pm$ 2.88)	85.54($\pm$ 4.57)	**81.49($\pm$ 1.52)**	70.77($\pm$ 1.00)	62.81($\pm$ 2.61)	1.630($\pm$ 2.516)
Context Prediction + Supervised	**91.54($\pm$ 3.52)**	**85.71($\pm$ 2.92)**	81.23($\pm$ 1.94)	**71.36($\pm$ 1.05)**	62.75($\pm$ 2.27)	1.806($\pm$ 2.340)

- **Balanced Scaffold Split [1, 18]** This strategy introduces the randomness in the sorting and splitting stages above, thus one can run on splits with different random seeds and report the average performance to lower the evaluation variance.

We choose balanced scaffold as our major evaluation configuration, because it allows us to evaluate the algorithm on multiple data splits while maintaining the ability to evaluate out of distribution samples (e.g. assess generalization ability). Evaluating on one single split (such as scaffold split) can be subject to bias due to one specific split, leading to higher variance in evaluation.

3.2 Experiment protocol

As the total number of configurations for the entire pipeline can be combinatorially large which is not practical for us to exhaustively experiment with all of them, we design our protocol with a pairwise comparison principle. Specifically, we first anchor a *vanilla configuration* with a certain design choice combination for each stage. To study the effect of each stage on the pretraining effectiveness, we vary the design choice one stage a time compared to the *vanilla configuration*.

For all these experiments, to assess the effectiveness of graph pretraining, we report the **ROC-AUC** on downstream tasks as well as the relative **average gain** over all downstream datasets with and without pretraining. For each setting we will report the mean and standard deviation (in parenthesis) over three runs with different random seeds. We tune the model on downstream tasks with the validation set, and report the evaluation metric on the test set using the model with best validation performance. For each setup, we report the average performance obtained with three random seeds. We tune the learning rate in $\{1e^{-4}, 5e^{-4}, 1e^{-3}, 5e^{-3}, 1e^{-2}, 5e^{-2}, 1e^{-1}\}$ for each setup *individually* and select the one with best validation performance. For GNNs we fix the hidden dimension to 300 and number of layers to 5.

4 Results

In this section, we present the results and discussions for a set of experiments designed with the protocols in Section 3.2. Table 1 summarizes the experimental configurations for each table. We will elaborate on them in the following sections. Due to space limit, we defer our investigation on different GNN architectures to appendix Section A.1.

4.1 Vanilla configuration

We choose the *vanilla configuration* with the settings from existing works [10, 18]. Specifically, we use the **rich feature** with **GIN** backbone, pretrained on **ZINC15** when pretraining is applied, and evaluate on the **Balanced Scaffold Split** for downstream tasks. One important baseline is without pretraining. For comparison convenience, we include the results without pretraining in each table.

4.2 Self-supervised pretraining objectives

We compare the results pretrained with different self-supervised pretraining objectives. As is presented in Section 3.1, we consider four representative types of pretraining objectives. For the ease of comparing the performance, we only consider one objective at a time, instead of mixing different pretraining objectives to obtain a multi-task pretrained model. Table 2 shows the performance on downstream molecule property prediction benchmarks with models initialized from different pretraining objectives. The relative average gain compared to the one without pretraining is not statistically significant, e.g. not larger than the standard deviations of multiple runs. All the four different objectives obtained similar gains/loses regardless of very different designs. To fully understand the effect

Table 8: Unsupervised + **Basic feature + Scaffold**. No pretrain has an average accuracy of 68.7% over all benckmark datasets.

Methods	BBBP	BACE	TOX21	TOXCAST	SIDER	AVE GAIN
No pretrain	69.62($\pm$ 1.05)	75.77($\pm$4.29)	75.52($\pm$0.67)	63.67($\pm$0.32)	59.07($\pm$1.13)	0($\pm$1.492)
Node Prediction	68.70($\pm$2.16)	76.95($\pm$0.12)	75.88($\pm$0.60)	64.11($\pm$0.38)	61.29($\pm$0.87)	0.656($\pm$0.826)
Context Prediction	69.41($\pm$1.44)	**81.96**($\pm$0.72)	75.49($\pm$0.75)	63.48($\pm$0.31)	**62.27**($\pm$**0.90**)	1.792($\pm$0.824)

Table 9: Supervised + **Basic feature + Scaffold**. No pretrain has an average accuracy of 68.7% over all benckmark datasets.

Methods	BBBP	BACE	TOX21	TOXCAST	SIDER	AVE GAIN
No pretrain	69.62($\pm$ 1.05)	75.77($\pm$4.29)	75.52($\pm$0.67)	63.67($\pm$0.32)	59.07($\pm$1.13)	0($\pm$1.492)
Supervised	68.96($\pm$0.64)	76.30($\pm$1.30)	76.64($\pm$0.39)	66.07($\pm$0.22)	61.97($\pm$0.96)	1.258($\pm$0.702)
Masking Node + Supervised	**71.41**($\pm$0.67)	84.59($\pm$0.35)	**79.13**($\pm$**0.29**)	65.32($\pm$0.37)	62.12($\pm$0.19)	3.784($\pm$0.374)
Context Prediction + Supervised	69.63($\pm$0.25)	**83.34**($\pm$**0.67**)	78.11($\pm$0.28)	**66.15**($\pm$**0.48**)	**63.48**($\pm$**0.43**)	3.412($\pm$0.422)

of self-supervised pretraining on molecule representation, we further investigate the performance of different pretraining objectives in combination with other factors, such as input features or data splits, described in the following sections.

4.3 Supervised pretraining objectives

In addition to the self-supervised objectives, we study the potential benefits with supervised pretraining. Unlike the self-supervised setting where the molecule graphs themselves are used for pretraining, the supervised pretraining requires extra cost of data labeling, and thus is not scalable for large scale pretraining. In this paper, we present the results with supervised pretraining alone, as well as the joint pretraining. e.g. pretrain with self-supervised objective and followed by supervised pretraining, in Table 3. We can see with the supervised pretraining, one can improve the downstream performance, which aligns with the observation from Hu et al. [10]. Our hypothesis is that, supervised pretraining is helpful when the pretraining tasks are closely aligned with the downstream tasks. In particular, the bio-activity labels provided by ChEMBL is highly related to the drug discovery purpose and drug discovery properties are the major topics evaluated in the downstream tasks. Therefore, the positive correlation between the pretraining supervision and downstream tasks contribute the most to the performance improvement of downstream tasks.

4.4 Data split on downstream tasks

Molecular data is usually diverse and limited, so chemists are particularly interested in the generalization ability of GNNs on out of distribution data. Also due to the same reason (e.g. limited and diverse data), the variance in performance of different splits is significant, which imposes challenges on robust evaluation. In *vanilla configuration* we use the balanced scaffold split, and here we show additional results with the **scaffold** split, which is a deterministic data split that makes the train/valid/test set differ from each other the most. Table 4 and Table 5 present the results using scaffold split with self-supervised without or with additional supervised pretraining. Compared with Table 2 and Table 3, it is clear to see that Table 4 and Table 5 have significantly lower ROC-AUC. Specifically the AUC drops 6.2% on average for all benchmarks without pretraining. On the other hand, we can see if we compare Table 4 with Table 2, or Table 5 with Table 3 respectively, the gain of pretraining is more significant on the **scaffold** split. We speculate the reason for the improvement of scaffold split is that the initialization of neural network parameters (e.g. from pretraining) are typically critical for the out-of-distribution generalization (e.g. scaffold split). Similar observations have also been studied in the meta-learning literature [5]. Although the gain with supervised pretraining is significant in Table 5, the effect of self-supervised pretraining is mixed in Table 4. This indicates the effectiveness of self-supervised pretraining on scaffold split is not significant enough to claim "very helpful".

4.5 Graph features

So far we have presented the results with rich features. Here we want to see how those basic features used in Hu et al. [10] affect the outcome. Table 6 and Table 7 show the test ROC-AUC (%) performance with *basic features* on the balanced scaffold splits using self-supervised or supervised pretraining objectives, respectively. Table 8 and Table 9 show the same results but on scaffold split.

Compared with basic features, rich features have an average gain of 1.3% and 3.1% without pretraining over all the benchmarks experiments using balanced scaffold split and scaffold split, respectively. Specifically, it achieves 76.7% vs 78.0% for balanced scaffold split, and 68.7% vs 71.8% on scaffold split. The gain brought by the rich features are more significant than the ones with different self-supervised pretraining objectives. Table 6 to Table 9 show that pretraining has more positive

Table 10: **Large scale pretraining data** with balanced scaffold split. No pretraining gets an average AUC of 78.0%.

Methods	BBBP	BACE	TOX21	TOXCAST	SIDER	AVE GAIN
No pretrain	92.23(±3.07)	87.43(±1.63)	79.2(±1.99)	69.13(±0.55)	61.92(±0.89)	0(±1.626)
Node Prediction	92.33(±2.08)	87.22(±1.79)	79.12(±1.62)	69.47(±0.65)	61.24(±1.94)	-0.106(±1.616)
Context Prediction	93.32(±0.53)	87.77(±2.94)	79.18(±2.48)	70.13(±0.56)	62.24(±2.65)	0.546(±1.832)
Masking Node + Supervised	93.23(±3.02)	86.39(±1.67)	81.89(±1.58)	71.77(±0.50)	63.73(±2.20)	1.420(±1.794)
Context Prediction + Supervised	92.55(±2.93)	87.76(±1.87)	82.19(±1.58)	72.91(±0.71)	62.44(±0.45)	1.588(±1.508)

Table 11: **Large scale pretraining** data with scaffold split. No pretraining gets an average AUC of 71.8%.

Methods	BBBP	BACE	TOX21	TOXCAST	SIDER	AVE GAIN
No pretrain	74.83(±0.73)	80.10(±0.42)	75.86(±0.58)	65.95(±0.15)	62.30(±1.14)	0(±0.604)
Node Prediction	73.81(±1.82)	81.90(±1.59)	74.94(±0.05)	66.95(±0.12)	62.93(±0.34)	0.298(±0.784)
Context Prediction	74.32(±0.85)	83.93(±0.24)	74.42(±0.19)	67.01(±0.29)	64.83(±0.45)	1.094(±0.404)
Masking Node + Supervised	73.32(±0.60)	83.38(±1.05)	78.59(±0.09)	67.01(±0.18)	65.40(±0.12)	1.732(±0.408)
Context Prediction + Supervised	74.38(±0.93)	86.33(±0.16)	78.16(±0.25)	68.71(±0.07)	62.22(±0.48)	2.152(±0.378)

impact when basic features are used. In particular, the self-pretraining with context prediction shows significant gains especially in the scaffold split setting. However, the gain diminishes when careful feature engineering are applied to the downstream tasks (use rich feature in *vanilla configuration*). The supervised pretraining continues the significant gain under these settings, which shows the consistency and reliability of the situation with the labeled and downstream-task-aligned supervisions.

4.6 Pretraining datasets

As observed in natural language processing domain, more text pretraining data lead to better downstream performance. Intuitively this can be true for molecule representation domain as well, so we run a new set of experiments with the model pretrained on SAVI dataset, which is about 500 times larger than the ZINC15 dataset we used in the above result sections. We present the results pretrained on SAVI dataset using balanced scaffold split or scaffold split in Table 10 and Table 11, respectively. Other configurations are the same as the *vanilla configuration*.

Compared with the performance on ZINC15, the SAVI pretraining data does not have a significant improvement either on balanced scaffold split (Table 2 vs Table 10) or scaffold split (Table 4 or Table 11). Also similarly, the self-supervised pretraining objectives lead to negligible gain on downstream task performance, while the supervised one still achieves a clear gain.

As the result is counterintuitive, we further investigate the reason behind it by inspecting the pretaining performances with different training objectives on both ZINC15 and SAVI datasets. We plot the curve of accuracy growth with the number of training steps iterated. We can see from Figure 2 that in all settings the pretraining accuracy grows above 90% quickly after only 0.1 to 0.2M steps and also converges quickly. Given that the model gets very high accuracy without even going through 1 epoch of the SAVI dataset, it is expected that the larger training data like SAVI may not provide more learning signals for the model, and partially explains why more molecules wouldn't help significantly in this case. Furthermore, these figures might suggest several reasons of why the self-supervised pretraining may not be very effective in some situations:

- **Tasks are easy.** Some of the self-pretraining tasks for molecules might be easy, so that model learns less useful information from pretraining. For example in the masked node prediction case, the model is expected to predict the atomic number from a vocabulary with less than 100 candidate atoms. Furthermore, due to the valence constraints, the graph topology may already exclude most of the wrong atoms. As a comparison, the vocabulary size for text pretraining may be 100k or even higher. Some structured prediction tasks like context prediction might be hard, but due to the difficulty of structured prediction itself and the proposal for high quality negative examples for contrastive learning, it can still be challenging for downstream task improvements. Other strategies like motif prediction can be achieved by subgraph matching, which can be easy for GNN that intrinsically does the graph isomorphism test.

- **Data lacks diversity.** Due to biophysical and functional requirements, molecules share many common sub-structures, e.g., functional motifs. Hence, molecules are not as diversified as text data. This is why the model learns to generalize quickly within the training distribution.

- **2D Structure is not enough to infer functionality.** Some important biophysical properties (such as 3D structure, chirality) are barely reflected in the 2D-feature-based pretraining (i.e. using smiles or 2D graph features). For example, the molecules with the same chemical formula and 2D feature, can have very different chirality, which leads to quite different toxicity [20] (e.g. flipped toxicity labels). This is not captured in the current GNN pretraining frameworks that we considered.

4.7 Hyper-parameters for downstream tasks

We also find that hyper-parameters for downstream tasks are critical for the their performance that their choice may totally change the conclusion of the effectiveness of pretraining. We can take the learning rate as an example. As the models initialized from scratch and pretraining may have different scales, the most suitable learning rate required for downstream tasks may also be different. Without tuning learning rate extensively, we may reach a misleading conclusion. In particular, when we adopt the default learning rate for reproducing the existing success of pretraining in Table 14 of Appendix A.2, we indeed observe the advantage of pretraining. However, if we follow our procedures (e.g. extensive search learning rate and averaging over three splits), the resulting Table 2 and Table 3 indicate no performance gain by pretraining. So we suspect the previous success of pretraining may largely due to lack of hyper-parameter tuning and not averaging over different splits.

Figure 2: Pretraining accuracy on ZINC15 or SAVI datasets with node prediction or context prediction objectives.

5 Summary and takeaways

Based on our experiments in Section 4, we present our takeaways by (empirically) summarizing when the pretraining would/would not help the molecular representation learning.

When pretraining helps?   It helps 1) if we can have the supervised pretraining with target labels that are aligned with the downstream tasks. However, getting large amount of high-quality and relevant supervision is not always feasible; 2) if the high quality hand-crafted features are absent. However, it seems that the gain obtained by self-supervised pretraining is not as significant as these high quality hand-crafted features; 3) if the downstream train, valid and test dataset distributions are substantially different.

When the gain diminishes?   Pretraining may not help 1) if we have the high quality hand-crafted features (e.g. rich features described in Section 3.1) ; 2) if we don't have the highly relevant supervisions. As shown in Section 4.6, many self-supervised pretraining tasks might be too easy for the model to learn meaningful embedding; 3) if the downstream data splits are balanced; 4) if the self-supervised learning dataset is simply enlarged.

6 Discussion

Why pretraining does not help? Inspired by the success in NLP, we pretrained a GNN on a much larger dataset (SAVI), which is 500 times larger, to obtain the maximum possible gain of pretraining. However, we do not obtain the expected gain. The pretraining accuracy curve (Figure 2) provides insights of why pretraining may not work: The pretraining accuracy curve grows above $95\%+$ quickly and converges fast, unlike pretraining in NLP which keeps growing to 70% and hardly plateaus. This indicates molecular pretraining is easy (e.g., vocabulary size is small) and therefore contains less transferable knowledge for downstream tasks.

7 Limitations of current study

Although we have tried our best to design a comprehensive study on the effectiveness of graph pretraining for molecular representation, there are still limitations we want to point out to prevent the over-generalization of our conclusion. First, our study focuses on pretraining for small molecule graph inductive representation learning. Recently there are works on pretraining transductive representation learning [30] on large graphs [11], where our conclusion cannot be directly extended to these cases. Second, although we've shown results on two representative 1-WL graph neural networks, it can be possible that the latest advances of deep GNN [14] and another Transformer-based GNN [28] (e.g. Graphormer) might yield different results, as these architectures go beyond the 1-WL check.

References

[1] Guy W Bemis and Mark A Murcko. The properties of known drugs. 1. molecular frameworks. *Journal of medicinal chemistry*, 39(15):2887–2893, 1996.

[2] Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

[3] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pages 1597–1607. PMLR, 2020.

[4] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

[5] Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International Conference on Machine Learning*, pages 1126–1135. PMLR, 2017.

[6] Anna Gaulton, Louisa J Bellis, A Patricia Bento, Jon Chambers, Mark Davies, Anne Hersey, Yvonne Light, Shaun McGlinchey, David Michalovich, Bissan Al-Lazikani, et al. Chembl: a large-scale bioactivity database for drug discovery. *Nucleic acids research*, 40(D1):D1100–D1107, 2012.

[7] William L Hamilton, Rex Ying, and Jure Leskovec. Representation learning on graphs: Methods and applications. *arXiv preprint arXiv:1709.05584*, 2017.

[8] Kaveh Hassani and Amir Hosein Khasahmadi. Contrastive multi-view representation learning on graphs. In *International Conference on Machine Learning*, pages 4116–4126. PMLR, 2020.

[9] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross B. Girshick. Momentum contrast for unsupervised visual representation learning. In *CVPR*, pages 9726–9735, 2020.

[10] Weihua Hu, Bowen Liu, Joseph Gomes, Marinka Zitnik, Percy Liang, Vijay Pande, and Jure Leskovec. Strategies for pre-training graph neural networks. *arXiv preprint arXiv:1905.12265*, 2019.

[11] Ziniu Hu, Yuxiao Dong, Kuansan Wang, Kai-Wei Chang, and Yizhou Sun. Gpt-gnn: Generative pre-training of graph neural networks. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 1857–1867, 2020.

[12] G Landrum. Rdkit: Open-source cheminformatics software, 2016.

[13] P. Langley. Crafting papers on machine learning. In Pat Langley, editor, *Proceedings of the 17th International Conference on Machine Learning (ICML 2000)*, pages 1207–1216, Stanford, CA, 2000. Morgan Kaufmann.

[14] Meng Liu, Hongyang Gao, and Shuiwang Ji. Towards deeper graph neural networks. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 338–348, 2020.

[15] Hitesh Patel, Wolf Ihlenfeldt, Philip Judson, Yurii S Moroz, Yuri Pevzner, Megan Peach, Nadya Tarasova, and Marc Nicklaus. Synthetically accessible virtual inventory (savi). 2020.

[16] Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *arXiv preprint arXiv:1910.10683*, 2019.

[17] Bharath Ramsundar, Peter Eastman, Patrick Walters, and Vijay Pande. *Deep learning for the life sciences: applying deep learning to genomics, microscopy, drug discovery, and more*. " O'Reilly Media, Inc.", 2019.

[18] Yu Rong, Yatao Bian, Tingyang Xu, Weiyang Xie, Ying Wei, Wenbing Huang, and Junzhou Huang. Self-supervised graph transformer on large-scale molecular data. *arXiv preprint arXiv:2007.02835*, 2020.

[19] Nino Shervashidze, Pascal Schweitzer, Erik Jan Van Leeuwen, Kurt Mehlhorn, and Karsten M Borgwardt. Weisfeiler-lehman graph kernels. *Journal of Machine Learning Research*, 12(9), 2011.

[20] Silas W Smith. Chiral toxicology: it's the same thing... only different. *Toxicological sciences*, 110(1):4–30, 2009.

[21] Teague Sterling and John J Irwin. Zinc 15–ligand discovery for everyone. *Journal of chemical information and modeling*, 55(11):2324–2337, 2015.

[22] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. *arXiv preprint arXiv:1710.10903*, 2017.

[23] Jason Wei, Maarten Bosma, Vincent Y Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M Dai, and Quoc V Le. Finetuned language models are zero-shot learners. *arXiv preprint arXiv:2109.01652*, 2021.

[24] Lirong Wu, Haitao Lin, Zhangyang Gao, Cheng Tan, Stan Li, et al. Self-supervised on graphs: Contrastive, generative, or predictive. *arXiv preprint arXiv:2105.07342*, 2021.

[25] Zhenqin Wu, Bharath Ramsundar, Evan N Feinberg, Joseph Gomes, Caleb Geniesse, Aneesh S Pappu, Karl Leswing, and Vijay Pande. Moleculenet: a benchmark for molecular machine learning. *Chemical science*, 9(2):513–530, 2018.

[26] Yaochen Xie, Zhao Xu, Jingtun Zhang, Zhengyang Wang, and Shuiwang Ji. Self-supervised learning of graph neural networks: A unified review. *arXiv preprint arXiv:2102.10757*, 2021.

[27] Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? *arXiv preprint arXiv:1810.00826*, 2018.

[28] Chengxuan Ying, Tianle Cai, Shengjie Luo, Shuxin Zheng, Guolin Ke, Di He, Yanming Shen, and Tie-Yan Liu. Do transformers really perform bad for graph representation? *arXiv preprint arXiv:2106.05234*, 2021.

[29] Yuning You, Tianlong Chen, Yongduo Sui, Ting Chen, Zhangyang Wang, and Yang Shen. Graph contrastive learning with augmentations. *Advances in Neural Information Processing Systems*, 33:5812–5823, 2020.

[30] Yuning You, Tianlong Chen, Zhangyang Wang, and Yang Shen. When does self-supervision help graph convolutional networks? In *International Conference on Machine Learning*, pages 10871–10880. PMLR, 2020.

[31] Yanqiao Zhu, Yichen Xu, Feng Yu, Qiang Liu, Shu Wu, and Liang Wang. Graph contrastive learning with adaptive augmentation. In *Proceedings of the Web Conference 2021*, pages 2069–2080, 2021.