Skill Acquisition by Instruction Augmentation on Offline Datasets

Abstract

In recent years, much progress has been made in learning robotic manipulation policies that follow natural language instructions. Commonly, such methods learn from a corpora of robot-language data that was either collected with specific tasks in mind or expensively re-labelled by humans with rich language descriptions in hindsight. Recently, large-scale pretrained vision-language models like CLIP have been applied to robotics in the form of learning representations and planners. Can these pretrained models also be used to cheaply impart internet-scale knowledge onto offline datasets, providing access to skills that were not reflected in ground truth labels? To accomplish this, we introduce **D**ata-driven **I**nstruction **A**ugmentation for **L**anguage-conditioned control (DIAL): we utilize semi-supervised language labels leveraging the semantic understanding of CLIP to propagate knowledge onto large datasets of unlabelled demonstration data and then train language-conditioned policies on the augmented datasets. This method enables cheaper acquisition of useful language descriptions compared to expensive human labels, allowing for more efficient label coverage of large-scale datasets. We apply DIAL to a challenging real-world robotic manipulation domain, enabling imitation learning policies to acquire new capabilities and generalize to 80 novel instructions unseen in the original dataset.

1 Introduction

Recent advances in decision making have combined data-driven policies with language models to enable control policies that respond to natural language instructions, an important capability for practical adoption of general robots in the real world. A popular method used to accomplish such language-controlled policies is behavioral cloning (BC) [17, 23, 1], which commonly acquires language labels in two ways: i) using a pre-defined tasks where the task description was provided at the time of data collection or ii) using rich language labels provided by humans in hindsight. Both of these options have major drawbacks, it is difficult to come up with a very diverse set of language instructions upfront which limits the diversity of the dataset and hindsight relabelling is expensive when applied to large datasets.

On the other hand, large-scale pretrained language models (LLMs) and vision-language models (VLMs) have seen increased adoption due to their ability to leverage internet-scale data to augment or even replace traditionally engineered parts of robot control systems, such as representation for perception [27, 31], as task representation for language [21, 17], or as planners [16, 1]. We seek to apply pretrained VLMs to the datasets themselves: can we use VLMs for *instruction augmentation*, where we relabel existing offline trajectory datasets with additional language instructions?

In this work, we provide an analysis of using instruction augmentation with VLMs to weakly relabel offline control datasets. We demonstrate this method on a challenging real-world robotic control

Figure 1: DIAL consists of three steps: (1) Contrastive fine-tuning of a vision-language model (VLM) such as CLIP [29] on small dataset of robot manipulation trajectories with crowd-sourced natural language annotation, (2) using the fine-tuned VLM (in dashed outline) to score and rank the relevance of crowd-sourced annotations against a larger dataset of trajectories to produce novel instruction labels, and (3) training a language-conditioned policy using behavior cloning on the original and relabeled dataset. See Section 2 for more details.

domain, showing that instruction augmentation allows policies to acquire understanding of skills not contained in the original task labels, enabling generalization to 80 novel task instructions.

Our core contributions are as follows:

- We introduce **D**ata-driven **I**nstruction **A**ugmentation for **L**anguage-conditioned control (DIAL) by using CLIP to label offline demonstrations for policy learning

- We study the sensitivity of policies performance to increasing instruction label noise

- We show the benefits of combining instruction augmentation predictions with existing labels

- We demonstrate the scalability of the method to a challenging real-world robotic task

2 Method

In this section, we describe DIAL consisting of three stages: (1) finetuning a VLM's vision and language representation on a small offline dataset of trajectories with crowd sourced episode-level natural language description, (2) generating alternative instructions for a larger offline dataset of trajectories with the VLM, and (3) learning a language-conditioned policy via behavior-cloning on this augmented offline data.

Stage 1: Finetuning Vision-Language Model Representations on Offline Dataset   Given an offline dataset $\mathcal{D}_A = [\tau_1, \ldots, \tau_N]$ of N trajectories $\tau_n = ([(s_0^n, a_0^n), (s_1^n, a_1^n), \ldots, (s_T^n)])$, we collect a corresponding natural language description l^n for the n-th episode describing what the robot agent did in the episode via crowd-sourcing. The crowd-sourced evaluators observe only the first frame, s_0, and last frame, s_T, when producing these descriptions. We refer these instructions as *hindsight instructions*. Our method then fine-tunes a vision and language model representation on this dataset. Given promising results of CLIP in robotics in prior works [31, 24], our instantiation of DIAL uses CLIP [29] as the VLM fine-tuned using the same contrastive loss. See Appendix A.2 for details.

Stage 2: Instruction Augmentation on Offline Datasets   We are also given a much larger offline dataset of trajectories $\mathcal{D}_B = [\hat{\tau}_1, \ldots, \hat{\tau}_M]$ of N trajectories $\hat{\tau}_m =$

Instruction Augmented Dataset Properties			Evaluation on Novel Instructions			
Episodes w/ GT	Episodes w/ IA	IA Accuracy	Spatial	Rephrased	Semantic	Overall
5600	0	N/A	24.1%	41.7%	0.0%	25.7%
5600	80k ($k = 1$)	68.0%	46.9%	58.3%	33.3%	44.3%
5600	240k ($k = 3$)	65.3%	46.3%	41.7%	33.3%	45.7%
5600	800k ($k = 10$)	57.0%	35.2%	41.7%	16.7%	35.7%

Table 1: Training on groundtruth crowd-sourced hindsight instructions (GT) compared with utilizing increasing the amount k of instruction augmentation on unlabeled data (IA), with a corresponding decrease in label accuracy. IA accuracy is estimated by sampling batches of relabeled episodes.

$([(\hat{s}_0^m, \hat{a}_0^m), (\hat{s}_1^m, \hat{a}_1^m), \ldots, (\hat{s}_T^m)], \hat{l}^m)$ consisting of $M \gg N$ trajectories. The instructions $\hat{l}^m$ associated with these trajectories may be: (1) *foresight instructions*, arising from a fixed set of tasks chosen before performing the demonstration, or (2) absent, such as episodes collected from unstructured play data [22]. We use the fine-tuned VLM model to propose novel natural language instructions $\tilde{l}^m$ for the trajectory $\hat{\tau}_m$ to augment the foresight/absent instructions for the robotic trajectories in $\mathcal{D}_B$. We source the candidate natural language instructions from the crowd-sourced hindsight instructions from the first stage, i.e. $\tilde{l}^m \in \{l^1, \ldots, l^N\} \sim \mathcal{D}_A$. [1] We use CLIP cosine similarity to rank the top-k most similar crowd-compute instruction to the episode. See Appendix A.3 for more details.

Stage 3: Learning Language Conditioned Policies with Behaviour Cloning   Given a dataset of robot trajectories and corresponding augmented language instructions, we can train a language-conditioned control policy with Behavior Cloning (BC). While instruction augmented offline datasets can be used by any downstream language-conditioned policy learning method such as offline RL or BC, we limit our work to the conceptually simpler BC in order to focus our analysis on the importance of instruction augmentation.

3   Experimental Setup

We implement DIAL in a challenging real-world robotic manipulation in real kitchen setting similar to SayCan [1]. We focus on the practically-motivated setting where a dataset of teleoperated demonstrations is available, collected for downstream imitation learning [17, 1]. For a details on the robot system, environment, and datasets please see Appendix A.4. After finetuning a CLIP model and utilizing it for instruction augmentation on unlabeled demonstration datasets, we train a vision-based language-conditioned behavior cloning policy similar to the formulation in BC-Z [17]. In contrast to prior works, we focus strictly on novel evaluation instructions unseen during training, which we categorize as "Spatial", "Rephrased", and "Semantic" tasks. For more details on policy training and the evaluation setting, please see Appendix A.5.

4   Experimental Results

4.1   Are hindsight instructions proposed by a VLM useful for policy learning?

We hope to study whether policies can successfully learn from instruction augmented datasets, even when some relabeled instructions are potentially inaccurate. Starting with a dataset of 5,600 trajectories with crowd-sourced hindsight labels, we apply different amounts of instruction augmentation onto a dataset of 89,000 trajectories that do not have any hindsight language labels. We find that training on the relabeled trajectories increases performance on a set of 80 sampled novel instructions not seen in the original hindsight label set, as shown in Table 1.

---

[1]Alternatively, candidate instructions can also be generated by having a large language model (LLM) such as GPT [5] or PaLM [10] to propose plausible new skills, given a few seen examples.

Instruction Augmented Dataset Properties			Evaluation on Novel Instructions			
Episodes w/ FS	Episodes w/ GT	Episodes w/ IA	Spatial	Rephrased	Semantic	Overall
80k	0	0	35.2%	58.3%	16.7%	38.6%
80k	5600	0	42.6%	83.3%	16.7%	48.6%
80k	5600	80k ($k = 1$)	53.1%	66.7%	33.3%	52.9%
80k	5600	240k ($k = 3$)	55.6%	33.3%	33.3%	51.4%
80k	5600	800k ($k = 10$)	40.8%	40.0%	16.7%	35.7%

Table 2: Combining episodes with foresight labels of the structured tasks attempted during data collection (FS) with groundtruth crowd-sourced hindsight instructions (GT) with an increasing amount k of instruction augmentation (IA). DIAL performs the best at challenging "Spatial" tasks.

		Evaluation on Novel Instructions			
Model	Task Instruction Encoder	Spatial	Rephrased	Semantic	Overall
GT Only	USE	16.7%	40.0%	0.0%	18.6%
GT Only	FT CLIP	24.1%	50.0%	0.0%	25.7%
FS + GT	Pretrained CLIP	42.6%	66.7%	0.00%	44.3%
FS + GT	FT CLIP	42.6%	83.3%	16.7%	48.6%
FS + GT + IA, $k = 1$	USE	44.9%	33.3%	33.3%	41.4%
FS + GT + IA, $k = 1$	FT CLIP	53.1%	50.0%	33.3%	52.9%

Table 3: Comparing downstream policy performance when improving the task representation from USE [6] to Pretrained CLIP [29] to Finetuned CLIP (FT CLIP) (Section 2. We find that the FT CLIP representation is the best task representation in all dataset settings.

4.2 Can hindsight relabelling by a VLM complement foresight task labels?

To test whether instruction augmentation is complementary to prior structured knowledge about demonstration datasets, we compare combining foresight labels with ground-truth hindsight labels and instruction augmentation, as seen in Table 2. Additional baselines we consider in Table 5 include methods that perform instruction augmentation without visual context. We find that only instruction augmentation using CLIP is able to perform well at novel "Spatial" tasks that require visual understanding.

4.3 Is a VLM good at relabeling also a good task representation?

We study whether a VLM fine-tuned for instruction augmentation can also act as a better task representation for policy learning in the form of a more powerful language embedding. Across the various groundtruth and relabeled datasets we focus on, we find that Finetuned CLIP is the most effective task representation, as seen in Table 3.

5 Conclusion

In this work, we introduced DIAL, a method that uses VLMs to label offline datasets for language-conditioned policy learning. We show that control policies are able to utilize relabeled demonstrations even when some labels are inaccurate, suggesting that DIAL is able to provide a cheap and automated option to extract additional semantic knowledge from offline control datasets. As the performance of internet-scale VLMs improve, we expect that DIAL might work increasingly better on even richer control settings.

References

[1] M. Ahn, A. Brohan, N. Brown, Y. Chebotar, O. Cortes, B. David, C. Finn, K. Gopalakrishnan, K. Hausman, A. Herzog, D. Ho, J. Hsu, J. Ibarz, B. Ichter, A. Irpan, E. Jang, R. J. Ruano, K. Jeffrey, S. Jesmonth, N. Joshi, R. Julian, D. Kalashnikov, Y. Kuang, K.-H. Lee, S. Levine, Y. Lu, L. Luu, C. Parada, P. Pastor, J. Quiambao, K. Rao, J. Rettinghouse, D. Reyes, P. Sermanet, N. Sievers, C. Tan, A. Toshev, V. Vanhoucke, F. Xia, T. Xiao, P. Xu, S. Xu, and M. Yan. Do as i can and not as i say: Grounding language in robotic affordances. In *arXiv preprint arXiv:2204.01691*, 2022.

[2] M. Andrychowicz, F. Wolski, A. Ray, J. Schneider, R. Fong, P. Welinder, B. McGrew, J. Tobin, O. Pieter Abbeel, and W. Zaremba. Hindsight experience replay. *Advances in neural information processing systems*, 30, 2017.

[3] D. Bahdanau, F. Hill, J. Leike, E. Hughes, A. Hosseini, P. Kohli, and E. Grefenstette. Learning to understand goal specifications by modelling reward. *arXiv preprint arXiv:1806.01946*, 2018.

[4] B. Baker, I. Akkaya, P. Zhokhov, J. Huizinga, J. Tang, A. Ecoffet, B. Houghton, R. Sampedro, and J. Clune. Video pretraining (vpt): Learning to act by watching unlabeled online videos. *arXiv preprint arXiv:2206.11795*, 2022.

[5] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

[6] D. Cer, Y. Yang, S.-y. Kong, N. Hua, N. Limtiaco, R. S. John, N. Constant, M. Guajardo-Cespedes, S. Yuan, C. Tar, et al. Universal sentence encoder. *arXiv preprint arXiv:1803.11175*, 2018.

[7] H. Chan, Y. Wu, J. Kiros, S. Fidler, and J. Ba. Actrce: Augmenting experience via teacher's advice for multi-goal reinforcement learning. *arXiv preprint arXiv:1902.04546*, 2019.

[8] Y. Chebotar, K. Hausman, Y. Lu, T. Xiao, D. Kalashnikov, J. Varley, A. Irpan, B. Eysenbach, R. Julian, C. Finn, et al. Actionable models: Unsupervised offline reinforcement learning of robotic skills. *arXiv preprint arXiv:2104.07749*, 2021.

[9] A. S. Chen, S. Nair, and C. Finn. Learning generalizable robotic reward functions from" in-the-wild" human videos. *arXiv preprint arXiv:2103.16817*, 2021.

[10] A. Chowdhery, S. Narang, J. Devlin, M. Bosma, G. Mishra, A. Roberts, P. Barham, H. W. Chung, C. Sutton, S. Gehrmann, et al. Palm: Scaling language modeling with pathways. *arXiv preprint arXiv:2204.02311*, 2022.

[11] G. Cideron, M. Seurin, F. Strub, and O. Pietquin. Self-educated language agent with hindsight experience replay for instruction following. 2019.

[12] A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

[13] L. Fan, G. Wang, Y. Jiang, A. Mandlekar, Y. Yang, H. Zhu, A. Tang, D.-A. Huang, Y. Zhu, and A. Anandkumar. Minedojo: Building open-ended embodied agents with internet-scale knowledge. *arXiv preprint arXiv:2206.08853*, 2022.

[14] E. Fix and J. L. Hodges. Discriminatory analysis. nonparametric discrimination: Consistency properties. *International Statistical Review/Revue Internationale de Statistique*, 57(3):238–247, 1989.

[15] J. Fu, A. Korattikara, S. Levine, and S. Guadarrama. From language to goals: Inverse reinforcement learning for vision-based instruction following. *arXiv preprint arXiv:1902.07742*, 2019.

[16] W. Huang, P. Abbeel, D. Pathak, and I. Mordatch. Language models as zero-shot planners: Extracting actionable knowledge for embodied agents. *arXiv preprint arXiv:2201.07207*, 2022.

[17] E. Jang, A. Irpan, M. Khansari, D. Kappler, F. Ebert, C. Lynch, S. Levine, and C. Finn. Bc-z: Zero-shot task generalization with robotic imitation learning. In *Conference on Robot Learning*, pages 991–1002. PMLR, 2022.

[18] Y. Jiang, S. S. Gu, K. P. Murphy, and C. Finn. Language as an abstraction for hierarchical deep reinforcement learning. *Advances in Neural Information Processing Systems*, 32, 2019.

[19] D. Kalashnikov, J. Varley, Y. Chebotar, B. Swanson, R. Jonschkowski, C. Finn, S. Levine, and K. Hausman. Mt-opt: Continuous multi-task robotic reinforcement learning at scale. *arXiv preprint arXiv:2104.08212*, 2021.

[20] J. Luketina, N. Nardelli, G. Farquhar, J. Foerster, J. Andreas, E. Grefenstette, S. Whiteson, and T. Rocktäschel. A survey of reinforcement learning informed by natural language. *arXiv preprint arXiv:1906.03926*, 2019.

[21] C. Lynch and P. Sermanet. Language conditioned imitation learning over unstructured data. *arXiv preprint arXiv:2005.07648*, 2020.

[22] C. Lynch, M. Khansari, T. Xiao, V. Kumar, J. Tompson, S. Levine, and P. Sermanet. Learning latent plans from play. In *Conference on robot learning*, pages 1113–1132. PMLR, 2020.

[23] A. Mandlekar, D. Xu, J. Wong, S. Nasiriany, C. Wang, R. Kulkarni, L. Fei-Fei, S. Savarese, Y. Zhu, and R. Martín-Martín. What matters in learning from offline human demonstrations for robot manipulation. *arXiv preprint arXiv:2108.03298*, 2021.

[24] O. Mees, L. Hermann, and W. Burgard. What matters in language conditioned robotic imitation learning. *arXiv preprint arXiv:2204.06252*, 2022.

[25] O. Mees, L. Hermann, E. Rosete-Beas, and W. Burgard. Calvin: A benchmark for language-conditioned policy learning for long-horizon robot manipulation tasks. *IEEE Robotics and Automation Letters*, 2022.

[26] S. Nair, E. Mitchell, K. Chen, S. Savarese, C. Finn, et al. Learning language-conditioned robot behavior from offline data and crowd-sourced annotation. In *Conference on Robot Learning*, pages 1303–1315. PMLR, 2022.

[27] S. Nair, A. Rajeswaran, V. Kumar, C. Finn, and A. Gupta. R3m: A universal visual representation for robot manipulation. *arXiv preprint arXiv:2203.12601*, 2022.

[28] M. Plappert, M. Andrychowicz, A. Ray, B. McGrew, B. Baker, G. Powell, J. Schneider, J. Tobin, M. Chociej, P. Welinder, et al. Multi-goal reinforcement learning: Challenging robotics environments and request for research. *arXiv preprint arXiv:1802.09464*, 2018.

[29] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pages 8748–8763. PMLR, 2021.

[30] V. Sanh, L. Debut, J. Chaumond, and T. Wolf. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. *arXiv preprint arXiv:1910.01108*, 2019.

[31] M. Shridhar, L. Manuelli, and D. Fox. Cliport: What and where pathways for robotic manipulation. In *Conference on Robot Learning*, pages 894–906. PMLR, 2022.

[32] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

[33] X Development, LLC. Everyday Robots. http://www.everydayrobots.com, 2022. Accessed: 2022-06-15.

[34] T. Xiao, E. Jang, D. Kalashnikov, S. Levine, J. Ibarz, K. Hausman, and A. Herzog. Thinking while moving: Deep reinforcement learning with concurrent control. *arXiv preprint arXiv:2004.06089*, 2020.

A Appendix

A.1 Related Work

Language-instruction following in Robotics   Language-instruction following agents have been extensively explored in the reinforcement learning setting [20]. Recent advances in deep learning with large amounts of data has led to works following natural language for robotic manipulations. Latent Motor Control (LMP) [22] learns hierarchical goal-conditioned policies. Subsequent Language from Play (LfP) [21] uses language goals provided by large dataset of hindsight human labels on robotic play data. In contrast, our method does not rely on crowd-sourced language labels at scale, but instead focuses on collecting just a modest amount of language labels and then using a learned model to provide weak hindsight labeling of the rest of the data.

Learned Language-conditioned reward function   Prior works have investigated using demonstrations with language annotations to learn a language-conditioned reward functions and subsequently optimize against it in a downstream online [3, 15, 13] or offline RL [26, 9] approach. The complexity of the language instructions range from templated language in small-scale environment to crowd-sourced language annotations in real robotics or open-ended environments such as Minecraft. LOReL [26] learns a reward function from offline datasets of robot interactions with crowd sourced annotations using a convolutional neural network trained from scratch combined with a pretraind DistilBERT sentence embedding [30] using the binary cross entropy. MineCLIP [13] fine-tunes CLIP [29] encoders using contrastive loss on a large offline dataset of Minecraft videos and optimizes a language-conditioned through online RL. While their learned reward function can be used to train agents specifically on novel task instructions, it requires an expensive and sample-inefficient stage of online RL, which is not tractable in the real world. A frozen CLIP vision and text encoders has also been used as a baseline method for imitation learning in [24] in the simulated robotic manipulation CALVIN benchmark [25]. Our approach fine-tunes CLIP on our *real* robot offline dataset and is used for instruction augmentation for a behavior cloning agent, instead of directly using the CLIP model as a reward model and optimizing an RL agent.

Hindsight Relabeling for Goal-conditioned Reinforcement Learning   The relabeling approach for goal-conditioned reinforcement learning [28] originates from Hindsight Experience Replay (HER) [2], which relabels the desired goals in a trajectory with achieved goals (hindsight goal) in the same trajectories to generate positive examples in a sparse reward setting. Relabeling approach has later been applied to environments where the goals are images [8], task IDs [19], and language instructions [18, 7, 11]. Early works with templated language goals rely on environment simulator to provide hindsight labels [18, 7], and more recently uses a learned model [11]. Our work further applies the relabeling strategy with a learned model for real robot environment.

Semi-supervised imitation / offline reinforcement learning   Prior works in semi-supervised imitation learning focuses on labeling missing actions from demonstrations. The approach of using a small curated dataset to train a model to then label a larger dataset has been explored in Video PreTraining (VPT) [4]. While VPT uses the small curated dataset to train an inverse dynamics model (IDM) to label actions, we fine-tuned CLIP [29] on our small dataset with crowd-sourced natural language annotation in order to relabel the language instructions for a larger dataset of robot trajectories. While LOReL [26] also applies instruction relabeling to an instruction from another episode, the relabeling is used to create more *negative* examples for the reward model to train on. In contrast, our approach creates new *positive* instruction labels for a given trajectory by leveraging an already fine-tuned VLM, which is used to train a behaviour cloned policy.

A.2 Details on Finetuning Vision-Language Model Representations on Offline Dataset

Given a batch of B initial state s_0, final state s_T, and hindsight instruction l tuple, the model is trained to predict which of the B^2 (initial-final state, hindsight instruction) pairs co-occurred. We use CLIP's Transformer-based text encoder T_{enc} to embed the crowd-sourced instruction to a latent space $z_l^n = T_{enc}(l^n)/\|T_{enc}(l^n)\| \in \mathbb{R}^d$ and CLIP's Vision Transformer-based (ViT) [12] image encoder I_{enc} to embed the initial and final state, and further concatenate these two embeddings and pass through fully connected neural network f_θ, producing the vision embedding $z_s^n = f_\theta([I_{enc}(s_0^n); I_{enc}(s_T^n)])/\|f_\theta([I_{enc}(s_0^n); I_{enc}(s_T^n)])\| \in \mathbb{R}^d$. B^2 similarity logits are formed

Figure 2: (a) A mobile manipulator robot performs a variety of manipulation tasks with various objects and cabinet drawers in an office kitchen environment. (b) An example of some of the kitchen objects found in the demonstration dataset. (c) The mobile manipulator robot receives RGB images from an over-the-shoulder camera and uses a 7 DoF arm with parallel-jaw grippers.

by applying dot product across all state-instruction pairs, and a symmetric cross entropy loss term is calculated by applying softmax normalization with temperature α across the states and across the text:

$$\mathcal{L}_{CLIP} = -\left[\sum_{n=1}^{B} \log \left(\frac{e^{z_l^n \cdot z_s^n / \alpha}}{\sum_{k=1}^{B} e^{z_l^k \cdot z_s^n / \alpha}} \right) + \sum_{n=1}^{B} \log \left(\frac{e^{z_l^n \cdot z_s^n / \alpha}}{\sum_{k=1}^{B} e^{z_l^n \cdot z_s^k / \alpha}} \right) \right] \tag{1}$$

A.3 Details on Instruction Augmentation on Offline Datasets

We use the fine-tuned text encoder to independently embed these language instructions and store them: $\{z_l^1, \ldots, z_l^N\} = \{T_{enc}(l^1), \ldots, T_{enc}(l^N)\}$. Similarly, we use the fine-tuned image encoder and MLP fusion to embed the initial and final observations from the second dataset: $\{\hat{z}_s^1, \ldots, \hat{z}_s^M\} = \{f_\theta([I_{enc}(\hat{s}_0^1); I_{enc}(\hat{s}_T^1)]), \ldots, f_\theta([I_{enc}(\hat{s}_0^M); I_{enc}(\hat{s}_T^M)])\}$. With these embeddings pre-computed, we can retrieve the most likely candidates using k-Nearest Neighbors [14] with cosine similarity between the vision-language embedding pairs $d(z_l^n, \hat{z}_s^m) = \frac{z_l^n \cdot \hat{z}_s^m}{\|z_l^n \cdot \hat{z}_s^m\|}$ as the metric. The resulting top-k candidate instructions $\{\tilde{l}_1^m, \ldots, \tilde{l}_k^m\}, \tilde{l}_i \in L$ for each trajectory is used to construct the *relabeled* dataset $\mathcal{D}_C = [\tilde{\tau}_1, \ldots, \tilde{\tau}_M]$, where $\tilde{\tau}_m = ([(\hat{s}_0^m, \hat{a}_0^m), (\hat{s}_1^m, \hat{a}_1^m), \ldots, (\hat{s}_T^m)], [\tilde{l}_1^m, \ldots, \tilde{l}_k^m])$. The hyperparameter k trades off precision and recall of the relabeled dataset. A smaller k will return mostly relevant candidate instructions, while a larger k value can recall a broader spectrum of potential hindsight descriptions for the episode at the expense of introducing irrelevant instructions. We will investigate the effects of k in Section 4 on the downstream policy performance.

A.4 Environment, Robot, and Datasets

An Everyday Robots robot [33], a mobile manipulator with RGB observations, is placed in an office kitchen to interact with common objects using concurrent [34] continuous closed-loop control from pixels, as shown in Figure 2. The robot uses parallel-jaw grippers, an over-the-shoulder RGB camera, and a 7 DoF arm. We collect a large-scale dataset of over 89,000 robot trajectories via human teleoperation, focusing on demonstrations of 551 unique tasks motivated by common manipulation skills and objects in a kitchen environment [1]. Afterwards, we leverage crowd-sourced human annotators to label 2,800 robot trajectories with two possible hindsight instructions each, resulting in a total of 5,600 unique episodes with crowdsourced captions. Human annotators are shown the

first and last frame of the episode and asked to provide a free-form text description describing how a robot should be commanded to go from the start to the end.

A.5   Policy Training and Evaluation

Following the language-conditioned behavior cloning formulation in BC-Z [17], we train a vision-based policy network conditioned on natural language embeddings to imitate teleoperated actions. Compared to BC-Z, we use a larger Transformer [32] based backbone instead of ResNet18 and use a CLIP language encoder instead of a Universal Sentence Encoder [6]. Nonetheless, we treat the behavior cloning policy as an independent component of our method and focus on studying instruction augmentation methods; we do not explore different policy architectures or losses in this work. The behavior cloning policy trains on robot trajectory datasets that are potentially relabeled with instruction augmentations, as described in Section 2.

To evaluate policy performance on novel instructions, we sample a list of 80 instructions that were explicitly not contained in the instruction augmentation process in Section 2 nor contained in the original set of 551 foresight tasks in Section A.4. To source these novel instructions, we crowd-source instructions from a different set of humans than the original dataset labelers and filter out any instructions already contained in the training set. While these novel evaluation instructions were not curated with specific properties in mind, after sourcing these instructions we split them up into various semantic categories to allow for more detailed analysis. Specifically, we study: "Spatial" tasks which focus on instructions involving reasoning about Spatial relationships, "Rephrased" tasks which are linguistic rephrasings of the original 551 foresight tasks, and "Semantic" tasks which encompass concepts that aren't present in the original corpus of hindsight labels. Some examples of these instructions are shown in Table 4.

Category	Instruction Samples
Spatial	['lift the apple which is on the right side of the table', 'raise the left most can', 'raise bottle which is to the left of the can']
Rephrased	['grab and lift up the green bag', 'pick up the apple fruit', 'move green packet near the red apple']
Semantic	['move the lonely object to the others', 'finish the row', 'move the green bag away from the others']

Table 4: Sample novel instructions in each evaluation category. Spatial tasks focus on tasks involving Spatial relationships, Rephrased tasks contain tasks that directly map to a foresight skill, and Semantic tasks describe semantic concepts not contained in the relabeled or original datasets. In total, there are 80 instructions across the three categories.

A.6   Additional Experiments

While our proposed method utilizes instruction augmentation with pretrained visual-language models, we can also attempt to increase the diversity of task instructions with non-visual methods. Two potential methods to do this are madlibs-style augmentations that replace words in the foresight instructions with synonyms and with Gaussian Noise augmentations that add noise with variance=0.05 to the text embeddings of foresight instructions. In Table 5, we compare relabeling methods in a setting similar to Section 4.2, where we apply relabeling to ground-truth labels from 80,000 episodes with foresight tasks and 5,600 episodes with groundtruth tasks. We note that while our dataset allows the baseline methods to relabel starting from the ground-truth foresight labels, "IA with CLIP" is able to relabel potentially unlabeled episodes, a setting that is not possible for the baseline methods.

	Evaluation on Novel Instructions			
Relabeling Method	Spatial	Rephrased	Semantic	Overall
No relabeling	35.2%	37.5%	16.7%	38.6%
Madlibs Text Augmentation	33.3%	75.0%	0.0%	38.6%
Gaussian Noise	31.4%	66.7%	0.0%	30.0%
IA with CLIP, $k = 1$	53.1%	66.7%	33.3%	52.9%
IA with CLIP, $k = 3$	55.6%	33.3%	33.3%	51.4%

Table 5: Comparing instruction augmentation with CLIP (IA) with non-visually grounded ways of relabeling the foresight tasks. We try Madlibs-style text augmentation as well as adding task embedding Gaussian noise. Policies train on foresight labels, groundtruth hindsight labels, and the additional relabeled episodes. While these improve performance on "Rephrased" tasks, they fail to improve performance on other task categories.