CURVALID: A GEOMETRICALLY-GUIDED ADVERSARIAL PROMPT DETECTION

ABSTRACT

Adversarial prompts that can jailbreak large language models (LLMs) and lead to undesirable behaviours pose a significant challenge to the safe deployment of LLMs. Existing defenses, such as input perturbation and adversarial training, depend on activating LLMs' defense mechanisms or fine-tuning LLMs individually, resulting in inconsistent performance across different prompts and LLMs. To address this, we propose CurvaLID, an algorithm that classifies benign and adversarial prompts by leveraging two complementary geometric measures: Local Intrinsic Dimensionality (LID) and curvature. LID provides an analysis of geometric differences at the prompt level, while curvature captures the degree of curvature in the manifolds and the semantic shifts at the word level. Together, these tools capture both prompt-level and word-level geometric properties, enhancing adversarial prompt detection. Unlike traditional approaches that rely on token-level LID, we introduce PromptLID, which calculates LID at the prompt level to better capture the geometric properties of text prompts within the adversarial subspace. Additionally, we propose TextCurv to further analyze the local geometric structure of prompt manifolds by calculating the curvature in text prompts. CurvaLID achieves over 0.99 detection accuracy, effectively reducing the attack success rate of advanced adversarial prompts to zero or nearly zero. Importantly, CurvaLID provides a unified detection framework across different adversarial prompts and LLMs, as it achieves consistent performance regardless of the specific LLM targeted.

1 INTRODUCTION

The safety of Large Language Models (LLMs) has gained significant attention due to their deployment in many real-world applications. Research into adversarial prompts that threaten LLM safety has grown, along with the development of defenses. Adversarial training and prompt engineering have been adapted to defend LLMs. Input perturbation techniques, such as IntentionAnalysis (Zhang et al., 2024a) and SmoothLLM (Robey et al., 2023), depend on how the prompt appears after perturbation and whether the modified prompt can successfully trigger the self-defense mechanisms of the targeted LLM. The effectiveness of these techniques varies depending on the extent of the perturbation and the LLM being targeted. Adversarial training methods require fine-tuning of each model. Moreover, they often face limitations when scaling to larger models. For example, Latent Adversarial Training (LAT) is limited to LLMs with fewer than 10 billion parameters (Sheshadri et al., 2024). Both adversarial training and prompt engineering defenses are dependent on the targeted LLMs. As a result, they fail to guarantee robust protection across different adversarial prompts and models.

An alternative defense method is adversarial prompt detection, which is both efficient and practical. In this approach, practitioners can reject queries that contain adversarial prompts. Adversarial input detection has been extensively studied in the context of image classification tasks (Dong et al., 2020; Machado et al., 2021; Bajaj & Vishwakarma, 2024; Liu et al., 2024). For instance, Ma et al. (2018) demonstrated that Local Intrinsic Dimensionality (LID) can effectively characterize an adversarial subspace and enable efficient adversarial input detection. They leveraged image-level representation vectors to estimate LID and distinguish adversarial examples from clean inputs. However, a fundamental difference in LLMs lies in the fact that inputs are represented as sequences of words. To the best of our knowledge, no prior work has investigated LID in the context of adversarial prompt detection for LLMs. Yin et al. (2024) explored using LID to assess the truthfulness of LLM responses

by estimating LID with token-level representations. We demonstrate that token-level LID is ineffective for adversarial prompt detection because LID values for benign and adversarial prompts often overlap significantly, primarily due to shared nearest neighbors being dominated by stop words and punctuation. Even after removing stop words and punctuation, which reduces the standard deviations, the average LID values for benign and adversarial prompts remain similar, making token-level LID still ineffective for distinguishing between them.

To address these limitations, we introduce CurvaLID, an algorithm designed to classify benign and adversarial prompts by leveraging two complementary geometric measures: LID and curvature. Instead of using token-level representations, CurvaLID utilizes PromptLID, a prompt-level LID analysis that quantifies and characterizes the distinct local subspace where adversarial prompts reside. We train a simple convolutional neural network (CNN) on clean prompts to extract these prompt-level representations, enabling the distinct LID of adversarial prompts to be identified during testing. Unlike previous work (Ma et al., 2018), which relies on the specific victim model for detection, CurvaLID detects adversarial prompts across different LLMs using a separate CNN for prompt representation extraction. This independence from specific LLMs ensures broader applicability and allows CurvaLID to provide consistent and universal defense across different LLMs. Furthermore, we introduce TextCurv, a novel mathematical framework that captures the geometric properties of text prompts through curvature analysis, focusing on the degree of curvature in the manifolds and the semantic shifts at the word level. Together, PromptLID and TextCurv provide complementary information—PromptLID captures prompt-level geometric differences, while TextCurv reveals local structural differences at the word level. While PromptLID achieves great accuracy, when combined with TextCurv, CurvaLID surpasses 0.99 classification accuracy, significantly outperforming state-of-the-art (SOTA) defenses on various adversarial prompts, including PAIR (Chao et al., 2023), RandomSearch (Andriushchenko et al., 2024), and AmpleGCG (Liao & Sun, 2024). CurvaLID consistently performs across all LLMs by detecting adversarial prompts independently, without depending on specific model architectures as many SOTA defenses do. CurvaLID is highly efficient, requiring only 15 minutes of training on a single Nvidia H100 GPU, compared to SOTA adversarial training methods that can take up to 16 hours on an 8-node A100 setup (Mazeika et al., 2024) or nearly 12 hours on a single A100 or H100 GPU (Sheshadri et al., 2024).

Our main contributions can be summarized as follows:

- We devise PromptLID, a prompt-level LID estimation method that enhances adversarial prompt detection, and effectively addresses the limitations of conventional token-level LID estimation. By leveraging prompt-level representations learned by a simple CNN, we can effectively capture the distinct characteristics of clean and adversarial prompts in their local intrinsic dimension.

- We propose TextCurv, a novel method for calculating curvature in text prompts. TextCurv captures local geometric properties by focusing on the semantic shift between consecutive words and the magnitude of this change. It effectively distinguishes between harmless and adversarial prompts, providing a robust classification capability.

- We introduce CurvaLID that utilizes both PromptLID and TextCurv to distinguish benign and adversarial prompts. Its performance is independent of the underlying LLM and offers consistent and efficient adversarial detection.

2 RELATED WORK

This section reviews prior research on adversarial attacks and defense mechanisms for LLMs, highlighting their objectives, underlying logic, and key characteristics.

Adversarial attacks on LLM. Adversarial attacks on LLMs involve crafted inputs designed to manipulate models into generating harmful content, like offensive language or dangerous instructions (Zou et al., 2023). These attacks range from a single input (zero-shot) to more complex, continuous dialogue scenarios (multi-shot) (Shen et al., 2023; Dong et al., 2023; Wang et al., 2023). This research focuses on zero-shot text prompt attacks, including techniques like text perturbation that adds gibberish or subtly alters input wording and social-engineered prompts that trick LLMs into harmful behavior (Zou et al., 2023; Schwinn et al., 2023; Chu et al., 2024).

Adversarial defenses for LLM. There are three primary defenses against adversarial attacks on LLMs: input preprocessing, prompt engineering, and adversarial training. Input preprocessing perturbs inputs to disrupt adversarial prompts but may also affect benign ones, with its effectiveness varying depending on the extent of the perturbation and the targeted LLM(Cao et al., 2023; Robey et al., 2023; Yung et al., 2024). Prompt engineering enhances the LLM's self-defensive capabilities by adding prompts that help expose harmful intent, though its effectiveness varies with different models (Zhang et al., 2024a; Phute et al., 2023; Zhang et al., 2024b). Finally, adversarial training strengthens the LLM's ability to reject harmful prompts by exposing it to adversarial scenarios during training (Xu et al., 2024b; Jain et al., 2023). However, this approach requires fine-tuning the LLM, making its success dependent on the specific model being protected, with most adversarial training methods confined to white-box models. Moreover, these methods generally exhibit varying effectiveness across different adversarial prompts and LLMs (Sheshadri et al., 2024; Ziegler et al., 2022; Ganguli et al., 2022). Note that our paper belongs to the field of adversarial prompt detection. In contrast to our approach, existing methods, such as perplexity filtering, rely on LLMs for next-token probability predictions (Hu et al., 2023).

3 BACKGROUND AND TERMINOLOGY

This section provides a brief overview of the mathematical definitions of LID and curvature, as well as how they are estimated and utilized in practice.

3.1 LOCAL INTRINSIC DIMENSION

Local Intrinsic Dimensionality (LID) measures the intrinsic dimensionality of the local neighborhood around a reference sample (Houle, 2017). Compared to Global Intrinsic Dimension (GID), which measures the degree of the d-dimension of the global manifold of a data subset, LID focuses on the local neighborhood of given points. Thus, LID is particularly useful in analyzing high-dimensional data with varying dimensionality across the dataset.

Definition 3.1 (Intrinsic Dimension). (Houle, 2017) Let F be a real-valued function that is non-zero over some open interval containing $r \in \mathbb{R}$, $r \neq 0$.

The intrinsic dimensionality of F at r is defined as follows, whenever the limit exists:

$$\text{IntrDim}_F(r) \triangleq \lim_{\epsilon \to 0} \frac{\ln\left(F((1+\epsilon)r)/F(r)\right)}{\ln((1+\epsilon)r/r)}.$$

Definition 3.2 (Local Intrinsic Dimension (LID)). (Houle, 2017) LID is mathematically defined as:

$$\text{LID}_F(r) = \frac{r \cdot F'(r)}{F(r)} = \text{IntrDim}_F(r),$$

where the last equality follows by applying L'Hôpital's rule to the limits. We are interested in a function F that satisfies the conditions of a cumulative distribution function (CDF) and is continuously differentiable at r. The local intrinsic dimension at x is in turn defined as the limit, when the radius r tends to zero:

$$\text{LID}_F^* \triangleq \lim_{r \to 0^+} \text{LID}_F(r).$$

We refer to the LID of a function F, or of a point $\mathbf{x}$, whose induced distance distribution has F as its CDF. For simplicity, we use the term 'LID' to refer to the quantity LID_F^*.

LID_F^* is the theoretical definition, and in practice, this quantity needs to be estimated (Levina & Bickel, 2004; Tempczyk et al., 2022). In this work, we use the Method of Moments (MoM) (Amsaleg et al., 2015) due to its simplicity. LID has been applied in many machine learning applications (Gong et al., 2019; Ansuini et al., 2019; Pope et al., 2021; Huang et al., 2024; Zhou et al., 2024a). It is important to note that applying LID estimation in machine learning requires both a distance measure and a set of reference points to select nearest neighbors (NN). In this work, we follow existing works that use the Euclidian distance. The representation of a data point, along with the chosen reference points, significantly influences how LID is interpreted. In adversarial prompt detection, the representation and neighborhood definition directly affect the ability to distinguish between clean and adversarial prompts.

3.2 CURVATURE

The intuition of curvature is how quickly a curve changes direction. In geometry, we can visualize curvature through an osculating circle. Curvature can be measured at a given point by fitting a circle to the curve on which the point resides (Kline, 1998). The formal definition is as follows:

Definition 3.3. [Curvature measured by osculating circle](Kline, 1998)

The osculating circle for some point P on a curve is defined as the circle tangent to P and passing each other point on the curve. We denote the radius of the osculating circle as R. Thus, the curvature κ is defined as:

$$\kappa = \frac{1}{R}.$$

For an arbitrary curve, one can extend the concept of curvature to the rate of tangential angular change with respect to arc length, which is known as the Whewell equation (Whewell, 1849). The tangential angular change refers to the change of angle of inclination of tangent at the given point.

Definition 3.4. [Curvature by Whewell equation](Whewell, 1849)

Let s be the arc length and tangential angle ϕ be the angle between the tangent to point P and the x-axis, for a given point P on a curve. The curvature κ is defined as:

$$\kappa = \frac{d\phi}{ds}.$$

Furthermore, in differential geometry, the curvature can be defined as the change of the unit tangent vector with respect to arc length (Shifrin, 2015; O'neill, 2006).

Definition 3.5. [Curvature in differential geometry](Shifrin, 2015) Suppose the curve α is parametrized by arc length s and $\mathbf{T}(s)$ is the unit tangent vector to the curve. We define curvature as

$$\kappa(s) = \|\mathbf{T}'(s)\| = \left\|\frac{d\mathbf{T}}{ds}\right\|.$$

Curvature is also defined and utilized in physics. The Frenet-Serret formulas relate curvature to torsion, tangent, normal, and binormal unit vectors (Frenet, 1852). In the Frenet-Serret formulas, the curvature describes the rotational speed along a curve, which is relevant in kinetics and trajectory applications (Huang et al., 2023). Its application extends to autonomous driving, robotics, and quantum computing (Hallgarten et al., 2024; Alsing & Cafaro, 2023; Shabana, 2023).

4 GEOMETRIC ANALYSIS AND CURVALID FRAMEWORK

In this work, we aim to develop geometric measures that can effectively characterize benign and adversarial prompts at both the prompt and word levels, and utilize these measurements for adversarial prompt detection. We specifically define our problem statement as follows:

Let $\mathcal{D} = \{(x^i, y^i)\}_{i=1}^n$ be a labeled dataset comprising n i.i.d. samples $x^{(i)}$, where each sample is associated with a label y^i. In this context, each input x^i represents a text prompt, with the corresponding label $y^i \in \{0, 1\}$ indicating whether the prompt is benign ($y^i = 0$), or adversarial ($y^i = 1$). Let $\mathcal{M}(x)$ denote the geometric measure applied to a prompt x, where $\mathcal{M}(x)$ is composed of two complementary components: the prompt-level measure PromptLID(x) and the word-level measure TextCurv(x). These measures are then utilized within an adversarial prompt detection algorithm, formalized as a classification problem where the objective is to minimize the empirical error between the ground-truth labels and the predictions:

$$\arg\min_\theta \mathbb{E}_{(x,y)\in\mathcal{D}}[\ell(h(\mathcal{M}(x)), y)],$$

where $\ell(\cdot)$ denotes the cross-entropy loss function, and $h(\mathcal{M}(x))$ is the classifier applied to the geometric measures $\mathcal{M}(x) = (\text{PromptLID}(x), \text{TextCurv}(x))$.

Next, we formally define PromptLID and TextCurv, detailing how they explore the geometric properties of prompts at the prompt and word levels, respectively. Finally, we provide an overview of CurvaLID, our adversarial prompt detection model.

4.1 PromptLID: LID estimation at the prompt-level

To characterize the prompt-level geometric properties of benign and adversarial prompts, we propose PromptLID, an LID estimation based on prompt representations obtained from a trained CNN. We first train a model g (CNN) to perform prompt classification. Classification involves learning a function $g : \mathcal{B} \to \mathcal{Q}$ that maps the input space to the label space $\mathcal{Q}$. In our setup, $\mathcal{Q}$ consists of four distinct labels $\{q_1, q_2, q_3, q_4\}$, each corresponding to one of the four benign datasets we use, namely Orca, MMLU, AlpacaEval, and TQA. For a benign prompt dataset $\mathcal{B} = \{(\boldsymbol{b}, q)^i\}_{i=1}^n$, where $\boldsymbol{b}$ is the benign prompt and q is the corresponding dataset label, the model aims to identify which benign dataset each prompt belongs to. The objective function used is categorical cross-entropy, as the task involves multi-class classification. The representation $\boldsymbol{z}_1$, derived from the penultimate dense layer, encodes the prompt as a single vector, which is then used to calculate the PromptLID. The PromptLID is calculated based on the MoM estimation (Amsaleg et al., 2015) of LID on the prompts' representation in $\boldsymbol{z}_1$.

Definition 4.1 (PromptLID). The PromptLID of a given prompt $\boldsymbol{x}$ is defined as:

$$PromptLID = -k \cdot \frac{\mu_k}{\mu_k - w^k},$$

where k is a locality hyperparameter representing the number of nearest neighbors, μ_k is the averaged distance from the prompt representation $\boldsymbol{z}_1$ of $\boldsymbol{x}$ to its k-nearest neighbors, w^k is the distance to the k-th nearest neighbor.

Additionally, we extract the outputs of the convolutional layers, $\boldsymbol{z}_2$ and $\boldsymbol{z}_3$, to calculate TextCurv, a method introduced in the next section, which captures the word-level geometric properties of prompts.

4.2 TextCurv: Curvature at the word-level

To characterize the word-level geometric properties of benign and adversarial prompts, we analyze the curvature of word connections. The aim is to have curvature complement PromptLID by analyzing the word-level geometric properties of prompts, effectively identifying nearly all adversarial prompts. Specifically, curvature captures the relationships between words, revealing subtle semantic shifts based on word order, and uncovering local geometric differences between benign and adversarial prompts.

Previous research indicates that CNN activation creates a curved manifold, evidenced by the significantly higher intrinsic dimension estimated by Principal Component Analysis (PCA) compared to the GID estimated by TwoNN on activation data (Abdi & Williams, 2010; Facco et al., 2017; Ansuini et al., 2019). However, there is a lack of findings on the curvature of benign versus adversarial prompts. Therefore, we investigate the curvature differences between these prompts in CNN convolution layers as potential classification features.

Our goal is to establish a definition of text curvature based on existing mathematical definitions, with the curvature capturing semantic shifts according to word sequence and the strength of these shifts. Word sequence plays a crucial role in semantic analysis, helping to accurately capture the local geometric properties of prompts. We focus on the representations of prompts in the convolutional layers of the model g as mentioned in Section 4.1, where the prompt data remains unflattened and in stacked lists of vectors at this stage, which can be viewed as word-level representation. Specifically, we extract the representations $\boldsymbol{z}_2$ and $\boldsymbol{z}_3$ from these convolutional layers for further analysis. This stage is critical, as it is where feature spaces are curved, according to prior research (Ansuini et al., 2019).

To capture semantic shifts between consecutive words in a prompt, we draw on Whewell's equation, where the rate of directional change of a curve is represented by the tangential angular change. In NLP, this angular change is connected to the dot-product formula and cosine similarity, which indicate the semantic similarity or difference between two words (Mikolov, 2013; Levy et al., 2015). We assume that this theory also applies to modern word embeddings like GPT-2 and RoBERTa, and therefore, we define the rate of angular change in text curvature accordingly:

Figure 1: Illustrative diagram for CurvaLID, which classifies benign and adversarial prompts using PromptLID and TextCurv.

Definition 4.2. [Text Curvature: Rate of angular change]

For any two consecutive word embeddings, denoted by $\vec{u}$ and $\vec{v}$, the rate of angular change, $d\theta$, is defined as:

$$d\theta = \arccos\left(\frac{\vec{u} \cdot \vec{v}}{\|\vec{u}\|\|\vec{v}\|}\right).$$

However, the rate of angular change alone does not fully capture the semantic shift between words, as it overlooks the magnitude of the shift. In differential geometry, curvature is defined by the rate of change in the tangent vector's direction relative to the change in arc length. When two curves exhibit the same directional change, the curve achieving this change over a shorter arc length has a higher curvature. Similarly, in text curvature, given the same semantic shift as measured by our rate of angular change, the curvature should increase when the semantic change is more substantial.

We focus on word vector magnitudes to capture the degree of semantic shift. Previous research suggests that magnitude reflects the semantic weight carried by each word and the tokenizers' understanding of that word within its context (Schakel & Wilson, 2015; Reif et al., 2019). For example, common words tend to have smaller magnitudes due to their frequent use and limited semantic significance (Schakel & Wilson, 2015). Instead of summing vector norms to measure distance changes in curvature—which may seem intuitive and consistent with geometric principles—we sum the inverses of the vector norms. This approach is driven by the hypothesis that larger vector norms signify greater semantic importance, meaning that curvature should be inversely proportional to vector norms, capturing the larger semantic shifts between words.

Definition 4.3. [Text Curvature] For any two consecutive word embeddings, denoted by $\vec{u}$ and $\vec{v}$, the text curvature, denote by TextCurv is defined as:

$$TextCurv = \frac{d\theta}{\frac{1}{\|\vec{u}\|} + \frac{1}{\|\vec{v}\|}}.$$

The supplementary mathematical proof can be found in A.1.2.

4.3 CURVALID: ADVERSARIAL PROMPT CLASSIFICATION BY CURVATURE AND LID

CurvaLID classifies and filters adversarial prompts before they reach LLMs, thus ensuring their security. Since CurvaLID operates independently of LLMs, it provides a unified defensive performance across all LLMs. This differentiates it from existing SOTA defenses like input perturbation, prompt engineering, and adversarial training, which show varying performance across different adversarial prompts and LLMs. Moreover, CurvaLID's evaluation is straightforward and standardized, avoiding the need for subjective human assessments or reliance on LLM judgments, which can raise robustness concerns (Chen et al., 2024; Raina et al., 2024).

CurvaLID involves four steps (see Figure 1, pseudo code in Appendix A.1.1). In the first step, we use our trained model g (defined in Section 4.1) to classify different types of benign prompts, deriving the normal feature manifold. This is essential for amplifying the geometric and dimensional distinctions between benign and adversarial prompts in subsequent steps. In the second step, we extract the representations of both benign and adversarial prompts from z_1, z_2, and z_3. In the third step, we compute PromptLID and TextCurv. Then in the final step, we train a Multilayer Perceptron (MLP) to classify benign and adversarial prompts using the two mean TextCurv values, and the PromptLID as inputs. The MLP performs binary classification and filters out adversarial prompts before they reach to LLMs. Details on the MLP architecture are included in Appendix A.1.6.

5 EXPERIMENTS

This section highlights CurvaLID's performance in classifying benign and adversarial prompts. We demonstrate the limitations of word-level LID due to stop words and punctuation. Lastly, we analyze TextCurv, emphasizing the difference between benign and adversarial prompts. Unless explicitly specified, the general experimental setup is as follows: we use a total of 2,519 testing prompts, comprising 1,200 benign prompts and 1,319 adversarial prompts. For the benign prompts, we randomly sampled 300 prompts from each of the Orca (Lian et al., 2023), MMLU (Hendrycks et al., 2020), AlpacaEval (Li et al., 2023b), and TruthfulQA (TQA) (Lin et al., 2021) datasets. Similarly, for the adversarial prompts, approximately 300 were randomly sampled from each of SAP (Deng et al., 2023a), DAN (Shen et al., 2023), MathAttack (Zhou et al., 2024b), and GCG (Zou et al., 2023).

We have included ablation studies and comparisons to other defenses in Appendix A.2 and A.4 respectively. It is important to note that SOTA defenses, such as input perturbation and adversarial training, are highly dependent on the specific adversarial prompts used and the particular LLMs targeted. In contrast, CurvaLID operates independently of the LLMs, providing consistent defensive performance across various models. This fundamental difference makes direct comparisons with SOTA defenses challenging. Nonetheless, we have attempted to summarize the performance of SOTA defenses and provide a comparative analysis with our method in Appendix A.4.

5.1 ADVERSARIAL PROMPT CLASSIFICATION BY CURVALID

This section explores CurvaLID's performance in classifying adversarial prompts, assessing its ability to identify mixed benign and adversarial inputs in real-world conditions. We also compare CurvaLID's detection capabilities with existing defenses to demonstrate its effectiveness.

5.1.1 CLASSIFICATION ON ADVERSARIAL PROMPTS

In this subsection, we demonstrate CurvaLID's effectiveness in accurately classifying benign and adversarial prompts, including both English and non-English adversarial prompts. We compared a total of eight datasets for our experiment, consisting of four benign datasets, namely Orca, MMLU, AlpacaEval, and TQA, and four adversarial datasets, namely SAP, DAN, MathAttack, and GCG. These datasets are the popular and SOTA English prompt datasets for testing the robustness of LLMs. From each dataset, we randomly selected at least 300 prompts, resulting in over 2,500 prompts for our classification experiment. We evaluated the ability of CurvaLID to distinguish between benign and adversarial prompts. Further details about the datasets are in Appendix A.1.7.

CurvaLID on English adversarial prompts. The experimental results, summarized in Table 1, demonstrate CurvaLID's high performance. The model achieved an overall accuracy of 0.992, with perfect accuracy of 1.00 (i.e., 100%) in identifying adversarial prompts and 0.984 accuracy in identifying benign prompts. This indicates that CurvaLID effectively reduced the attack success rate of adversarial prompts to zero.

In addition to evaluating CurvaLID on the four main adversarial datasets, which contain a substantial number of prompts, we extended our experiments to include other datasets like RandomSearch, AmpleGCG, Persuasive Attack, AutoDAN, and DrAttack (Chao et al., 2023; Andriushchenko et al., 2024; Liao & Sun, 2024; Zeng et al., 2024; Liu et al., 2023; Li et al., 2024). These datasets often contain prompts that are highly similar to each other or are variants of those in the datasets used in our main experiment. Due to computational constraints and the limited scope of their original

Table 1: Performance metrics for CurvaLID on benign and adversarial datasets.

Data class	Accuracy by dataset				Accuracy by class	Overall accuracy	F1 score
Benign	**Orca**	**MMLU**	**AlpacaEval**	**TQA**	**0.984**	**0.992**	**0.992**
	0.968	1.000	0.983	0.986			
Adversarial	**SAP**	**DAN**	**MathAttack**	**GCG**	**1.000**		
	1.000	1.000	1.000	1.000			

Table 2: Performance metrics for CurvaLID on non-English adversarial datasets.

Adv. Dataset	zh	it	vi	ar	ko	th	bn	sw	jv	Avg
Benign Acc.	0.975	1	1	1	1	1	1	0.975	1.0	0.994
Adv. Acc.	1	0.984	0.984	1	1	1	0.984	1	0.984	0.993
Overall Acc.	0.988	0.994	0.994	1	1	1	0.994	0.988	0.994	0.994
F1 Score	0.987	0.994	0.994	1	1	1	0.994	0.987	0.994	0.994

research, we used 100-200 prompts from each dataset. Despite the reduced number of prompts, CurvaLID effectively identified all adversarial attacks with around 0.99 accuracy. Detailed results of these experiments are provided in Appendix A.2.1.

CurvaLID on non-English adversarial prompts. We analyzed CurvaLID's effectiveness in detecting non-English adversarial prompts by testing it on nine languages from the MultiJail dataset (Deng et al., 2023b). We randomly sampled 300 prompts from each of the 9 languages in the MultiJail dataset and tested them individually against 400 benign prompts, adjusted to avoid class imbalance. We gathered 100 prompts from each of four benign datasets randomly. Notably, retraining with benign prompts in different languages was unnecessary to maintain high accuracy. As shown in Table 2, CurvaLID achieved an overall accuracy and F1 score of 0.994, highlighting its robust ability to detect adversarial prompts across languages.

5.1.2 DETAILED ANALYSIS ON CURVALID

We conducted an extensive analysis of CurvaLID's performance, including experiments with reduced training prompt sizes and training without adversarial prompts.

Impact of number of prompts on CurvaLID. We studied the impact of reducing the number of prompts on CurvaLID's performance. We decreased the number of prompts in each dataset to 150 (from 300). Despite this reduction, CurvaLID maintained an overall accuracy of 0.988 and an F1 score of 0.988. Further details of the experimental results can be found in Appendix A.2.2.

Using CurvaLID in one-class classification problems. We experimented at modifying step 4 of CurvaLID by replacing the supervised MLP with unsupervised outlier detection methods such as the local outlier factor (LOF) or isolation forest, which do not require training on adversarial prompts. This was done to explore the performance of the model in a one-class classification scenario, where only benign prompts are used for training. Despite the absence of adversarial examples during training, the LOF and isolation forest methods achieved a comparable detection accuracy of around 0.9. Therefore, our framework is task-independent and can be applied to various problem settings. Further details are provided in Appendix A.2.3.

5.2 ANALYSIS OF LOCAL AND GLOBAL ID ON BENIGN AND ADVERSARIAL PROMPTS

This subsection addresses the limitations associated with using token-level LID, for classifying benign and adversarial prompts. Adversarial prompts manipulate rarely encountered areas of the feature space using complex words and irregular combinations (Wallace et al., 2019; Ilyas et al., 2019; Ren et al., 2019). Existing work has shown that adversarial perturbation leads the representation to a subspace with distinct local dimensional properties (high LID) (Ma et al., 2018). As a result, we hypothesize that each word in adversarial prompts could lead to a representation with high LID. By utilizing token-level representations and aggregating the LIDs for each prompt by taking the average, it is possible to detect adversarial prompts.

(a) Avg token-level LID (b) Average NN-distances (c) Average PromptLID (d) Avg length and GID

Figure 2: (a) Comparison of average token-level LID for benign and adversarial prompts. The blue bars show the average LID of prompts in their original form, while the red bars show the average token-level LID after removing stopwords and punctuation. (b) Average Nearest Neighbor distances for benign and adversarial datasets. The blue bars represent the average nearest neighbour distances for the benign datasets, while the red bars represent the adversarial dataset. (c) Average PromptLID for benign and adversarial prompts. The benign datasets are in blue while the adversarial datasets are in red. (d) Comparison of average length and average GID across datasets.

Table 3: Top 10 most common nearest neighbors for each dataset. The angle brackets (<>) are used to specify punctuation and newline characters in the tokenizer. The visible space symbol (␣) represents a space preceding a word or punctuation.

Dataset	Top 10 most common nearest neighbors
SAP	␣to, ␣and, ␣the, <.>, ␣a, ␣of, <,>, ␣<">, ␣that, ␣your
DAN	<,>, <.>, <newline>, ␣the, ␣and, ␣to, ␣you, ␣will, ␣not, ␣is
MathAttack	␣the, <,>, ␣of, ␣he, <.>, ␣to, ␣and, ␣she, ␣is, ␣a
GCG	␣text, tto, use, ized, <}>, ␣mar, dt, ␣a, <'>, ␣Guide
Orca	␣the, <,>, <.>, <newline>, ␣and, ␣a, ␣of, ␣to, ␣is, ␣in
MMLU	␣the, <,>, <.>, ␣of, ␣a, ␣to, ␣that, ␣and, ␣in, ␣was
AlpacaEval	␣the, ␣a, ␣to, <,>, ␣of, ␣and, ␣I, <.>, ␣for, <?>
TQA	␣the, <?>, ␣a, ␣you, ␣is, ␣of, ␣that, ␣to, ␣if, ␣in

Effectiveness of token-level LID values in separating benign and adversarial prompts. Our analysis revealed a significant overlap in token-level LID values between benign and adversarial prompts. We examined the average LID at the word level, treating each word representation as a data point with its neighborhood defined by the prompt. This approach mirrors standard natural language processing (NLP) practices, where words are tokenized and converted to embeddings, similar to how pixels are treated as data points in image analysis. Using RoBERTa embeddings, we calculated word-level average LID. As shown in Figure 2a and Appendix A.3.2, the average token-level LID for most datasets are similar and hovers around 10, making it difficult to differentiate between benign and adversarial prompts. The standard deviations of the token-level LID values are also notably high, with AlpacaEval exceeding 100 and DAN surpassing 200. This indicates substantial variability, leading to significant overlap in LID values for benign and adversarial prompts, which diminishes the effectiveness of token-level LID in distinguishing between them.

Investigating similarity benign and adversarial token-level LIDs. Next, we investigated the underlying reasons for the similarity in average token-level LID between benign and adversarial prompts. We focused on the average of the first 5 nearest-neighbor distances (NN-distance), which, as shown in Figure 2b, appear similar for both benign and adversarial datasets. We present the top 10 most common nearest-neighbors for different prompts in different datasets in Table 3. It shows that common nearest-neighbors in the representation space were mostly stop words and punctuation. This suggests that word-level LID overlooks the sequential order of text and often relies on conjunctions, articles, and punctuation. These findings suggest that word-level LID is ineffective for detecting adversarial prompts.

Effectiveness of token-level LID after removing stop words and punctuation. To explore the significance of stop words and punctuation on the effectiveness of LID, we recalculated word-level

Table 4: Average TextCurv of benign and adversarial datasets across word embedding and CNN layers. Percentages in parentheses represent the increase in TextCurv for adversarial prompts compared to benign prompts.

Word Embedding	Convolution Layer 1		Convolution Layer 2	
	Benign	Adversarial	Benign	Adversarial
RoBERTa	0.626	0.881 (+40.7%)	0.325	0.446 (+37.2%)
GPT-2	0.805	1.11 (+37.9%)	0.389	0.546 (+40.4%)
BERT	0.428	0.590 (+37.9%)	0.199	0.264 (+32.7%)
XLNet	0.296	0.431 (+45.6%)	0.199	0.264 (+32.7%)
DistilBERT	0.386	0.557 (+44.3%)	0.225	0.322 (+43.1%)

LID after excluding these elements. As shown in Figure 2a and Appendix A.3.2, this modification significantly reduces the standard deviation, with a maximum of 2.26, indicating more consistent LID values that are less influenced by stop words and punctuation. However, the difference between the benign and adversarial prompts' LID is not sufficient to discriminate them.

Analysis on PromptLID. We analyze PromptLID across benign and adversarial datasets. As shown in Figure 2c, adversarial prompts have a significantly higher average PromptLID (19.472) compared to benign prompts (3.509), highlighting its effectiveness in distinguishing adversarial prompts.

Effectiveness of global intrinsic dimension in adversarial prompt detection. Global intrinsic dimension (GID) is another plausible approach for the word-level representation. It can avoid aggregating the LID for each word by assessing the GID for each word within the prompt and output a single value. We use the MLE-based estimate from Tulchinskii et al. (Tulchinskii et al., 2024). However, as shown in Figure 2d, there is no clear difference between benign and adversarial datasets. Instead, GID appears to correlate strongly with prompt length, showing Pearson and Spearman correlation coefficients of 0.92 and 0.98, respectively. We also experimented with the prompt's GID after removing stop words and punctuation, but the results remained similar, with a Pearson correlation coefficient of 0.9, indicating the limitations of GID in effectively detecting adversarial prompts.

5.3 CURVATURE ANALYSIS ON BENIGN AND ADVERSARIAL PROMPTS

We analyzed the average TextCurv of adversarial prompts in CurvaLID Step 2. To ensure TextCurv is independent of the embedding model, we conducted curvature analysis using various embeddings, including GPT-2, BERT, XLNet, and DistilBERT (Radford et al., 2019; Devlin, 2018; Yang, 2019; Sanh, 2019). As shown in Table 4, adversarial prompts consistently showed at least 30% higher curvature than benign prompts across all embeddings. This result supports our hypothesis that words in adversarial prompts tend to be more irregular and complex than those in benign prompts.

We also demonstrated that CNN activation significantly amplifies the TextCurv differences between benign and adversarial prompts. Specifically, the mean TextCurv of adversarial prompts is at least 30% higher than that of benign prompts in the representations of both CNN layers. In contrast, when considering only the word embedding, the TextCurv for benign prompts based solely on word embedding is 4.91, compared to 5.42 for adversarial prompts. The difference in TextCurv is much smaller—just 13%, which is less than half of the difference observed in the CNN layers.

6 CONCLUSION

In this paper, we introduce CurvaLID, a framework that uses LID and curvature to distinguish benign and adversarial prompts. CurvaLID achieves over 0.99 accuracy and reduces the ASR of the tested adversarial prompts to near zero. Unlike conventional SOTA defenses, such as prompt engineering and input perturbation, CurvaLID operates independently of LLMs, providing consistent performance across all models. We also demonstrate the limitations of word-level LID due to stop words and punctuation. We address this by introducing PromptLID and TextCurv, which respectively explore the geometric properties of prompts at the prompt-level and word-level in text data. Future directions for this work include expanding CurvaLID to spam detection, adding a human feedback system to CurvaLID for optimisation, and testing CuravLID with noisy prompts.

REPRODUCIBILITY STATEMENT

Details of all hyperparameters and experimental settings are given in Appendix A.1.4, A.1.5, A.1.6, A.1.7, A.2. Pseudo code for LID estimated by Method of Moments can be found in Appendix A.3.1. The experiments were performed on a system equipped with a single Nvidia H100 GPU, 8 CPU cores, and 128 GB of RAM. We provide source code for reproducing the experiments in this paper, which can be accessed here: https://anonymous.4open.science/r/CurvaLID-8DE0/README.md

REFERENCES

Hervé Abdi and Lynne J Williams. Principal component analysis. *Wiley interdisciplinary reviews: computational statistics*, 2(4):433–459, 2010.

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.

AI@Meta. Llama 3 model card. 2024. URL `https://github.com/meta-llama/llama3/blob/main/MODEL_CARD.md`.

Paul M Alsing and Carlo Cafaro. From the classical frenet-serret apparatus to the curvature and torsion of quantum-mechanical evolutions. part i. stationary hamiltonians. *arXiv preprint arXiv:2311.18458*, 2023.

Laurent Amsaleg, Oussama Chelly, Teddy Furon, Stéphane Girard, Michael E Houle, Ken-ichi Kawarabayashi, and Michael Nett. Estimating local intrinsic dimensionality. In *Proceedings of the 21th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 29–38, 2015.

Maksym Andriushchenko, Francesco Croce, and Nicolas Flammarion. Jailbreaking leading safety-aligned llms with simple adaptive attacks. *arXiv preprint arXiv:2404.02151*, 2024.

Cem Anil, Esin Durmus, Mrinank Sharma, Joe Benton, Sandipan Kundu, Joshua Batson, Nina Rimsky, Meg Tong, Jesse Mu, Daniel Ford, et al. Many-shot jailbreaking. *Anthropic, April*, 2024.

Rohan Anil, Andrew M Dai, Orhan Firat, Melvin Johnson, Dmitry Lepikhin, Alexandre Passos, Siamak Shakeri, Emanuel Taropa, Paige Bailey, Zhifeng Chen, et al. Palm 2 technical report. *arXiv preprint arXiv:2305.10403*, 2023.

Alessio Ansuini, Alessandro Laio, Jakob H Macke, and Davide Zoccolan. Intrinsic dimension of data representations in deep neural networks. *Advances in Neural Information Processing Systems*, 32, 2019.

Anthropic. Claude-1, 2023a. URL `https://www.anthropic.com`. Large Language Model.

Anthropic. Claude-2, 2023b. URL `https://www.anthropic.com`. Large Language Model.

Ashish Bajaj and Dinesh Kumar Vishwakarma. A state-of-the-art review on adversarial machine learning in image classification. *Multimedia Tools and Applications*, 83(3):9351–9416, 2024.

Xiao Bi, Deli Chen, Guanting Chen, Shanhuang Chen, Damai Dai, Chengqi Deng, Honghui Ding, Kai Dong, Qiushi Du, Zhe Fu, et al. Deepseek llm: Scaling open-source language models with longtermism. *arXiv preprint arXiv:2401.02954*, 2024.

Tom B Brown. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Bochuan Cao, Yuanpu Cao, Lu Lin, and Jinghui Chen. Defending against alignment-breaking attacks via robustly aligned llm. *arXiv preprint arXiv:2309.14348*, 2023.

Zhiyuan Chang, Mingyang Li, Yi Liu, Junjie Wang, Qing Wang, and Yang Liu. Play guessing game with llm: Indirect jailbreak attack with implicit clues. *arXiv preprint arXiv:2402.09091*, 2024.

Patrick Chao, Alexander Robey, Edgar Dobriban, Hamed Hassani, George J Pappas, and Eric Wong. Jailbreaking black box large language models in twenty queries. *arXiv preprint arXiv:2310.08419*, 2023.

Guiming Hardy Chen, Shunian Chen, Ziche Liu, Feng Jiang, and Benyou Wang. Humans or llms as the judge? a study on judgement biases. *arXiv preprint arXiv:2402.10669*, 2024.

Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E Gonzalez, et al. Vicuna: An open-source chatbot impressing gpt-4 with 90%* chatgpt quality. *See https://vicuna. lmsys. org (accessed 14 April 2023)*, 2(3):6, 2023.

Junjie Chu, Yugeng Liu, Ziqing Yang, Xinyue Shen, Michael Backes, and Yang Zhang. Comprehensive assessment of jailbreak attacks against llms. *arXiv preprint arXiv:2402.05668*, 2024.

Boyi Deng, Wenjie Wang, Fuli Feng, Yang Deng, Qifan Wang, and Xiangnan He. Attack prompt generation for red teaming and defending large language models. *arXiv preprint arXiv:2310.12505*, 2023a.

Yue Deng, Wenxuan Zhang, Sinno Jialin Pan, and Lidong Bing. Multilingual jailbreak challenges in large language models. *arXiv preprint arXiv:2310.06474*, 2023b.

Jacob Devlin. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Yinpeng Dong, Qi-An Fu, Xiao Yang, Tianyu Pang, Hang Su, Zihao Xiao, and Jun Zhu. Benchmarking adversarial robustness on image classification. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 321–331, 2020.

Yinpeng Dong, Huanran Chen, Jiawei Chen, Zhengwei Fang, Xiao Yang, Yichi Zhang, Yu Tian, Hang Su, and Jun Zhu. How robust is google's bard to adversarial image attacks? *arXiv preprint arXiv:2309.11751*, 2023.

Elena Facco, Maria d'Errico, Alex Rodriguez, and Alessandro Laio. Estimating the intrinsic dimension of datasets by a minimal neighborhood information. *Scientific reports*, 7(1):12140, 2017.

F Frenet. Sur les courbes à double courbure. *Journal de mathématiques pures et appliquées*, 17: 437–447, 1852.

Deep Ganguli, Liane Lovitt, Jackson Kernion, Amanda Askell, Yuntao Bai, Saurav Kadavath, Ben Mann, Ethan Perez, Nicholas Schiefer, Kamal Ndousse, et al. Red teaming language models to reduce harms: Methods, scaling behaviors, and lessons learned. *arXiv preprint arXiv:2209.07858*, 2022.

Sixue Gong, Vishnu Naresh Boddeti, and Anil K Jain. On the intrinsic dimensionality of image representations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3987–3996, 2019.

Haizelabs. Haizelabs/llama3-jailbreak: A trivial programmatic llama 3 jailbreak. sorry zuck!, 2023. URL https://github.com/haizelabs/llama3-jailbreak?v=2. Version 2.

Marcel Hallgarten, Ismail Kisa, Martin Stoll, and Andreas Zell. Stay on track: A frenet wrapper to overcome off-road trajectories in vehicle motion prediction. In *Proceedings of the IEEE Intelligent Vehicles Symposium (IV)*, pp. 795–802. IEEE, 2024.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. *arXiv preprint arXiv:2009.03300*, 2020.

Michael E Houle. Local intrinsic dimensionality i: an extreme-value-theoretic foundation for similarity applications. In *Proceedings of the Similarity Search and Applications: 10th International Conference, SISAP 2017, Munich, Germany, October 4-6, 2017, Proceedings 10*, pp. 64–79. Springer, 2017.

Xiaomeng Hu, Pin-Yu Chen, and Tsung-Yi Ho. Gradient cuff: Detecting jailbreak attacks on large language models by exploring refusal loss landscapes. *arXiv preprint arXiv:2403.00867*, 2024.

Zhengmian Hu, Gang Wu, Saayan Mitra, Ruiyi Zhang, Tong Sun, Heng Huang, and Vishy Swaminathan. Token-level adversarial prompt detection based on perplexity measures and contextual information. *arXiv preprint arXiv:2311.11509*, 2023.

Hanxun Huang, Ricardo JGB Campello, Sarah Monazam Erfani, Xingjun Ma, Michael E Houle, and James Bailey. Ldreg: Local dimensionality regularized self-supervised learning. *arXiv preprint arXiv:2401.10474*, 2024.

Jianyu Huang, Zuguang He, Yutaka Arakawa, and Billy Dawton. Trajectory planning in frenet frame via multi-objective optimization. *IEEE Access*, 2023.

Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Logan Engstrom, Brandon Tran, and Aleksander Madry. Adversarial examples are not bugs, they are features. *Advances in neural information processing systems*, 32, 2019.

Neel Jain, Avi Schwarzschild, Yuxin Wen, Gowthami Somepalli, John Kirchenbauer, Ping-yeh Chiang, Micah Goldblum, Aniruddha Saha, Jonas Geiping, and Tom Goldstein. Baseline defenses for adversarial attacks against aligned language models. *arXiv preprint arXiv:2309.00614*, 2023.

Morris Kline. *Calculus: an intuitive and physical approach*. Courier Corporation, 1998.

Elizaveta Levina and Peter Bickel. Maximum likelihood estimation of intrinsic dimension. *Advances in neural information processing systems*, 17, 2004.

Omer Levy, Yoav Goldberg, and Ido Dagan. Improving distributional similarity with lessons learned from word embeddings. *Transactions of the association for computational linguistics*, 3:211–225, 2015.

Xirui Li, Ruochen Wang, Minhao Cheng, Tianyi Zhou, and Cho-Jui Hsieh. Drattack: Prompt decomposition and reconstruction makes powerful llm jailbreakers. *arXiv preprint arXiv:2402.16914*, 2024.

Xuan Li, Zhanke Zhou, Jianing Zhu, Jiangchao Yao, Tongliang Liu, and Bo Han. Deepinception: Hypnotize large language model to be jailbreaker. *arXiv preprint arXiv:2311.03191*, 2023a.

Xuechen Li, Tianyi Zhang, Yann Dubois, Rohan Taori, Ishaan Gulrajani, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. Alpacaeval: An automatic evaluator of instruction-following models. `https://github.com/tatsu-lab/alpaca_eval`, 5 2023b.

Wing Lian, Bleys Goodson, Eugene Pentland, Austin Cook, Chanvichet Vong, and "Teknium". Openorca: An open dataset of gpt augmented flan reasoning traces. `https://https://huggingface.co/Open-Orca/OpenOrca`, 2023.

Zeyi Liao and Huan Sun. Amplegcg: Learning a universal and transferable generative model of adversarial suffixes for jailbreaking both open and closed llms. *arXiv preprint arXiv:2404.07921*, 2024.

Stephanie Lin, Jacob Hilton, and Owain Evans. Truthfulqa: Measuring how models mimic human falsehoods. *arXiv preprint arXiv:2109.07958*, 2021.

Chang Liu, Yinpeng Dong, Wenzhao Xiang, Xiao Yang, Hang Su, Jun Zhu, Yuefeng Chen, Yuan He, Hui Xue, and Shibao Zheng. A comprehensive study on robustness of image classification models: Benchmarking and rethinking. *International Journal of Computer Vision*, pp. 1–23, 2024.

Xiaogeng Liu, Nan Xu, Muhao Chen, and Chaowei Xiao. Autodan: Generating stealthy jailbreak prompts on aligned large language models. *arXiv preprint arXiv:2310.04451*, 2023.

Xingjun Ma, Bo Li, Yisen Wang, Sarah M Erfani, Sudanthi Wijewickrema, Grant Schoenebeck, Dawn Song, Michael E Houle, and James Bailey. Characterizing adversarial subspaces using local intrinsic dimensionality. *arXiv preprint arXiv:1801.02613*, 2018.

Gabriel Resende Machado, Eugênio Silva, and Ronaldo Ribeiro Goldschmidt. Adversarial machine learning in image classification: A survey toward the defender's perspective. *ACM Computing Surveys (CSUR)*, 55(1):1–38, 2021.

Mantas Mazeika, Long Phan, Xuwang Yin, Andy Zou, Zifan Wang, Norman Mu, Elham Sakhaee, Nathaniel Li, Steven Basart, Bo Li, et al. Harmbench: A standardized evaluation framework for automated red teaming and robust refusal. *arXiv preprint arXiv:2402.04249*, 2024.

Anay Mehrotra, Manolis Zampetakis, Paul Kassianik, Blaine Nelson, Hyrum Anderson, Yaron Singer, and Amin Karbasi. Tree of attacks: Jailbreaking black-box llms automatically. *arXiv preprint arXiv:2312.02119*, 2023.

Tomas Mikolov. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*, 2013.

Barrett O'neill. *Elementary differential geometry*. Elsevier, 2006.

Mansi Phute, Alec Helbling, Matthew Hull, ShengYun Peng, Sebastian Szyller, Cory Cornelius, and Duen Horng Chau. Llm self defense: By self examination, llms know they are being tricked. *arXiv preprint arXiv:2308.07308*, 2023.

Phil Pope, Chen Zhu, Ahmed Abdelkader, Micah Goldblum, and Tom Goldstein. The intrinsic dimension of images and its impact on learning. In *Proceedings of the International Conference on Learning Representations*, 2021.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Vyas Raina, Adian Liusie, and Mark Gales. Is llm-as-a-judge robust? investigating universal adversarial attacks on zero-shot llm assessment. *arXiv preprint arXiv:2402.14016*, 2024.

Emily Reif, Ann Yuan, Martin Wattenberg, Fernanda B Viegas, Andy Coenen, Adam Pearce, and Been Kim. Visualizing and measuring the geometry of bert. *Advances in neural information processing systems*, 32, 2019.

Shuhuai Ren, Yihe Deng, Kun He, and Wanxiang Che. Generating natural language adversarial examples through probability weighted word saliency. In *Proceedings of the 57th annual meeting of the association for computational linguistics*, pp. 1085–1097, 2019.

Alexander Robey, Eric Wong, Hamed Hassani, and George J Pappas. Smoothllm: Defending large language models against jailbreaking attacks. *arXiv preprint arXiv:2310.03684*, 2023.

V Sanh. Distilbert, a distilled version of bert: Smaller, faster, cheaper and lighter. *arXiv preprint arXiv:1910.01108*, 2019.

Adriaan MJ Schakel and Benjamin J Wilson. Measuring word significance using distributed representations of words. *arXiv preprint arXiv:1508.02297*, 2015.

Leo Schwinn, David Dobre, Stephan Günnemann, and Gauthier Gidel. Adversarial attacks and defenses in large language models: Old and new threats. In *Proceedings of the NeurIPS 2023 Workshops, Proceedings on Machine Learning Research*, pp. 103–117. PMLR, 2023.

Ahmed A Shabana. Instantaneous motion plane and zero-force axis and their relationship to frenet geometry. *Nonlinear Dynamics*, 111(17):15737–15748, 2023.

Xinyue Shen, Zeyuan Chen, Michael Backes, Yun Shen, and Yang Zhang. " do anything now": Characterizing and evaluating in-the-wild jailbreak prompts on large language models. *arXiv preprint arXiv:2308.03825*, 2023.

Abhay Sheshadri, Aidan Ewart, Phillip Guo, Aengus Lynch, Cindy Wu, Vivek Hebbar, Henry Sleight, Asa Cooper Stickland, Ethan Perez, Dylan Hadfield-Menell, et al. Targeted latent adversarial training improves robustness to persistent harmful behaviors in llms. *arXiv preprint arXiv:2407.15549*, 2024.

Theodore Shifrin. Differential geometry: a first course in curves and surfaces. *University of Georgia*, pp. 24, 2015.

MosaicML NLP Team. Introducing mpt-30b: Raising the bar for open-source foundation models, 2023. URL www.mosaicml.com/blog/mpt-30b. Accessed: 2023-06-22.

Piotr Tempczyk, Rafał Michaluk, Lukasz Garncarek, Przemysław Spurek, Jacek Tabor, and Adam Golinski. Lidl: Local intrinsic dimension estimation using approximate likelihood. In *Proceedings of the International Conference on Machine Learning*, pp. 21205–21231. PMLR, 2022.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023.

Eduard Tulchinskii, Kristian Kuznetsov, Laida Kushnareva, Daniil Cherniavskii, Sergey Nikolenko, Evgeny Burnaev, Serguei Barannikov, and Irina Piontkovskaya. Intrinsic dimension estimation for robust detection of ai-generated texts. *Advances in Neural Information Processing Systems*, 36, 2024.

Eric Wallace, Shi Feng, Nikhil Kandpal, Matt Gardner, and Sameer Singh. Universal adversarial triggers for attacking and analyzing nlp. *arXiv preprint arXiv:1908.07125*, 2019.

Jiongxiao Wang, Zichen Liu, Keun Hee Park, Zhuojun Jiang, Zhaoheng Zheng, Zhuofeng Wu, Muhao Chen, and Chaowei Xiao. Adversarial demonstration attacks on large language models. *arXiv preprint arXiv:2305.14950*, 2023.

Xunguang Wang, Daoyuan Wu, Zhenlan Ji, Zongjie Li, Pingchuan Ma, Shuai Wang, Yingjiu Li, Yang Liu, Ning Liu, and Juergen Rahmel. Selfdefend: Llms can defend themselves against jailbreaking in a practical manner. *arXiv preprint arXiv:2406.05498*, 2024.

Alexander Wei, Nika Haghtalab, and Jacob Steinhardt. Jailbroken: How does llm safety training fail? *Advances in Neural Information Processing Systems*, 36, 2024.

William Whewell. *On the intrinsic equation of a curve, and its application*. Printed at the Pitt Press by JW Parker, 1849.

Zhangchen Xu, Fengqing Jiang, Luyao Niu, Jinyuan Jia, Bill Yuchen Lin, and Radha Poovendran. Safedecoding: Defending against jailbreak attacks via safety-aware decoding. *arXiv preprint arXiv:2402.08983*, 2024a.

Zihao Xu, Yi Liu, Gelei Deng, Yuekang Li, and Stjepan Picek. A comprehensive study of jailbreak attack versus defense for large language models. In *Proceedings of the Findings of the Association for Computational Linguistics ACL 2024*, pp. 7432–7449, 2024b.

Zhilin Yang. Xlnet: Generalized autoregressive pretraining for language understanding. *arXiv preprint arXiv:1906.08237*, 2019.

Fan Yin, Jayanth Srinivasa, and Kai-Wei Chang. Characterizing truthfulness in large language model generations with local intrinsic dimension. In *Proceedings of the International Conference on Machine Learning*, 2024.

Zheng-Xin Yong, Cristina Menghini, and Stephen H Bach. Low-resource languages jailbreak gpt-4. *arXiv preprint arXiv:2310.02446*, 2023.

Jiahao Yu, Xingwei Lin, Zheng Yu, and Xinyu Xing. Gptfuzzer: Red teaming large language models with auto-generated jailbreak prompts. *arXiv preprint arXiv:2309.10253*, 2023.

Canaan Yung, Hadi Mohaghegh Dolatabadi, Sarah Erfani, and Christopher Leckie. Round trip translation defence against large language model jailbreaking attacks. *arXiv preprint arXiv:2402.13517*, 2024.

Aohan Zeng, Xiao Liu, Zhengxiao Du, Zihan Wang, Hanyu Lai, Ming Ding, Zhuoyi Yang, Yifan Xu, Wendi Zheng, Xiao Xia, et al. Glm-130b: An open bilingual pre-trained model. *arXiv preprint arXiv:2210.02414*, 2022.

Yi Zeng, Hongpeng Lin, Jingwen Zhang, Diyi Yang, Ruoxi Jia, and Weiyan Shi. How johnny can persuade llms to jailbreak them: Rethinking persuasion to challenge ai safety by humanizing llms. *arXiv preprint arXiv:2401.06373*, 2024.

Yuqi Zhang, Liang Ding, Lefei Zhang, and Dacheng Tao. Intention analysis prompting makes large language models a good jailbreak defender. *arXiv preprint arXiv:2401.06561*, 2024a.

Ziyang Zhang, Qizhen Zhang, and Jakob Foerster. Parden, can you repeat that? defending against jailbreaks via repetition. *arXiv preprint arXiv:2405.07932*, 2024b.

Yuning Zhou, Henry Badgery, Matthew Read, James Bailey, and Catherine Davey. Dda: Dimensionality driven augmentation search for contrastive learning in laparoscopic surgery. In *Medical Imaging with Deep Learning*, 2024a.

Zihao Zhou, Qiufeng Wang, Mingyu Jin, Jie Yao, Jianan Ye, Wei Liu, Wei Wang, Xiaowei Huang, and Kaizhu Huang. Mathattack: Attacking large language models towards math solving ability. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pp. 19750–19758, 2024b.

Daniel Ziegler, Seraphina Nix, Lawrence Chan, Tim Bauman, Peter Schmidt-Nielsen, Tao Lin, Adam Scherlis, Noa Nabeshima, Benjamin Weinstein-Raun, Daniel de Haas, et al. Adversarial training for high-stakes reliability. *Advances in Neural Information Processing Systems*, 35: 9274–9286, 2022.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*, 2023.

A APPENDIX

The appendix is organized into four sections. A.1 provides supplementary information about CurvaLID, offering additional details and mathematical proofs. A.2 focuses on ablation studies, presenting experiments to analyze various aspects of CurvaLID's performance. A.3 presents supplementary information on LID analysis. Finally, A.4 evaluates the performance of other SOTA defenses, comparing them to CurvaLID.

A.1 SUPPLEMENTARY INFORMATION ABOUT CURVALID

This section includes supplementary mathematical proofs for CurvaLID, detailed parameter specifications, and an analysis of its time and space complexity.

A.1.1 PSEUDOCODE FOR CURVALID

Algorithm A.1 presents the pseudocode for CurvaLID.

Algorithm A.1 CurvaLID

Require: Datasets $\mathcal{D}_b$, $\mathcal{D}_a$ (benign and adversarial prompts)
 1: **Step 1: Data Preparation**
 2:     Load datasets $\mathcal{D}_b$ and $\mathcal{D}_a$
 3:     Compute word embeddings E_b and E_a for $\mathcal{D}_b$ and $\mathcal{D}_a$
 4: **Step 2: Preprocessing**
 5:     Pad sequences to uniform length $L_{\max}$
 6:     Standardize embeddings to zero mean and unit variance
 7: **Step 3: Train CNN for Benign Classification**
 8:     Train a CNN $\mathcal{G}$ on $\mathcal{D}_b$ to extract prompt-level representations z_1
 9: **Step 4: Compute PromptLID and TextCurv**
10:     Calculate PromptLID on z_1
11:     Extract intermediate layer outputs z_2, z_3 and calculate TextCurv
12: **Step 5: Train the Detection Model**
13:     Combine PromptLID and TextCurv as features
14:     Train an MLP $\mathcal{H}$ for binary classification of benign vs adversarial prompts

---

A.1.2 THEORETICAL FOUNDATIONS AND MATHEMATICAL JUSTIFICATION OF TEXTCURV

We will begin by discussing how embedding angles relate to tangential angles to address the reference of TextCurv to Whewell's equation. Our goal is to show that the angle between two word embedding vectors corresponds to the difference in their tangential angles (i.e., the numerator in Whewell's equation). We start by examining the 2D Euclidean plane, where the vector space is two-dimensional. The following proof demonstrates that, in 2D space, the angle between two vectors is equivalent to the difference in their tangential angles.

Proof: The angle between two vectors is equivalent to the difference in their tangential angles in 2D

Let $\vec{u}$ and $\vec{v}$ be two vectors in a 2D space, with tangential angles ϕ_u and ϕ_v relative to the x-axis. Without loss of generosity, we consider the positive x-axis represented by the vector $(1, 0)$. We aim to prove that the angle θ between $\vec{u}$ and $\vec{v}$ is equal to the difference in their tangential angles.

Step 1: Angle between two vectors $\vec{u}$ and $\vec{v}$

The angle θ between two vectors $\vec{u}$ and $\vec{v}$ in Euclidean space is defined by the dot product formula:

$$\theta = \arccos\left(\frac{\vec{u} \cdot \vec{v}}{||\vec{u}|| \, ||\vec{v}||}\right).$$

Step 2: Define tangential angles for each vector with respect to x-axis

Consider the positive x-axis, represented by the unit vector $\vec{e}_x = (1, 0)$ in 2D space.

- The **tangential angle** ϕ_u of $\vec{u}$ with respect to $\vec{e}_x$ is:

$$\phi_u = \arccos\left(\frac{\vec{u} \cdot \vec{e}_x}{||\vec{u}||}\right).$$

- The **tangential angle** ϕ_v of $\vec{v}$ with respect to $\vec{e}_x$ is:

$$\phi_v = \arccos\left(\frac{\vec{v} \cdot \vec{e}_x}{||\vec{v}||}\right).$$

Step 3: Express $\vec{u}$ and $\vec{v}$ in terms of their tangential angles

Using their tangential angles with respect to $\vec{e}_x$, we can write:

$$\vec{u} = ||\vec{u}|| \begin{pmatrix} \cos\phi_u \\ \sin\phi_u \end{pmatrix}, \quad \vec{v} = ||\vec{v}|| \begin{pmatrix} \cos\phi_v \\ \sin\phi_v \end{pmatrix}.$$

Step 4: Compute the dot product $\vec{u} \cdot \vec{v}$

Substitute these expressions into the dot product formula:

$$\vec{u} \cdot \vec{v} = ||\vec{u}|| \, ||\vec{v}|| \left(\cos\phi_u \cos\phi_v + \sin\phi_u \sin\phi_v\right).$$

Using the trigonometric identity $\cos(\phi_v - \phi_u) = \cos\phi_u \cos\phi_v + \sin\phi_u \sin\phi_v$, we have:

$$\vec{u} \cdot \vec{v} = ||\vec{u}|| \, ||\vec{v}|| \cos(\phi_v - \phi_u).$$

Step 5: Prove the equivalency

Substitute the result in step 4 back into the formula for θ gives:

$$\theta = \arccos\left(\frac{\vec{u} \cdot \vec{v}}{||\vec{u}|| \, ||\vec{v}||}\right) = \arccos\left(\cos(\phi_v - \phi_u)\right).$$

Since $\arccos(\cos x) = |x|$ for any angle x, we have:

$$\theta = |\phi_v - \phi_u|.$$

We acknowledge that word embedding vectors exist in high-dimensional space, not in 2D. In higher dimensions, defining tangential angles introduces new challenges, as specifying a vector's direction in n-dimensional space requires n-1 angles. However, to explore changes in tangential angles within a text data setting, and given that the angle between two vectors in 2D is equivalent to the difference in their tangential angles, we postulate that for word vectors of consecutive words in text, the angle between their embedding vectors can approximate the change in tangential angle. This approach also allows us to capture semantic shifts effectively even within the limitations of high-dimensional space.

Now we investigate the relationship between word embedding vector norms and the change of arc length.

Relationship between word embedding vector norms and the change of arc length: To relate the word embedding vector norms and the change of arc length, we rely on an intuitive proportional relationship that aligns with the definitions in Whewell's equation. We start by considering the relationship between the change in arc length and curvature in the context of Whewell's equation.

Let s denote the arc length along a curve and κ denote the curvature at a given point on the curve. According to Whewell's equation, the change in arc length Δs is inversely proportional to the curvature κ for a fixed change in the tangential angle. Mathematically, this implies:

$$\Delta s \propto \frac{1}{\kappa}.$$

Intuitively, this means that, for the same change in tangential angle, a smaller arc length Δs corresponds to a sharper turn on the curve, which implies a higher curvature κ.

Postulating arc length in the context of semantic shift: In the context of semantic shift, we interpret the change in arc length Δs as the progression of words within a text. To capture the semantic shift from one word to the next, we approximate Δs by measuring the magnitude of the word embedding vectors for consecutive words. Specifically, we denote the magnitudes of two consecutive word embeddings as $||\vec{u}||$ and $||\vec{v}||$, where $\vec{u}$ and $\vec{v}$ are the embeddings of consecutive words. The use of consecutive words aligns with our approach for evaluating changes in tangential angle, ensuring consistency.

Relating arc length change to curvature: Since the change in arc length is approximated by the magnitude of word embedding vectors, we initially consider $||\vec{u}|| + ||\vec{v}||$ as a measure of Δs. However, directly using $||\vec{u}|| + ||\vec{v}||$ in the denominator would contradict the inverse proportionality between Δs and curvature κ. To resolve this, we reinterpret the role of vector magnitudes in the semantic context.

The magnitude of each word embedding vector reflects the semantic "weight" of each word within its context, capturing the tokenizer's understanding of the word's significance. Consequently, a larger sum $||\vec{u}|| + ||\vec{v}||$ suggests a more substantial semantic shift between consecutive words, indicating a sharper change in meaning and thus a higher curvature. Therefore, we assert:

$$\kappa \propto ||\vec{u}|| + ||\vec{v}||.$$

To satisfy the inverse relationship between arc length and curvature, we incorporate the **inverse of the sum of the word vector magnitudes** in our curvature formula. Thus, in our proposed TextCurv metric, we define:

$$\text{TextCurv} = \frac{\Delta\theta}{\frac{1}{||\vec{u}||+||\vec{v}||}},$$

where $\Delta\theta$ represents the change in angle between the consecutive word embeddings $\vec{u}$ and $\vec{v}$, as mentioned above.

A.1.3 TIME AND SPACE COMPLEXITY OF CURVALID

The time complexity for PromptLID is $\mathcal{O}(np)$, where n is the number of prompts and p is the dimensionality of the prompt embeddings. In our implementation, we use the representation layer of the CNN to obtain the embeddings. For TextCurv, the time complexity is $\mathcal{O}(nmd)$, where m is the number of words in a prompt and d is the word embedding dimensionality. In our case, we use RoBERTa embeddings for word representations. Therefore, the overall time complexity is $\mathcal{O}(n(p + md))$.

The space complexity for PromptLID is $\mathcal{O}(np)$, as we store n prompts, each with p dimensions. For TextCurv, the space complexity is $\mathcal{O}(nz)$, where z represents the dimensionality of the trained CNN layers used in our computations. Consequently, the space complexity is $\mathcal{O}(n(p + z))$.

A.1.4 CNN HYPERPARAMETER SELECTION

We conducted a preliminary study for the CNN hyperparameter selection to determine the optimal architecture based on overall CurvaLID detection accuracy, training time, and stability. Stability was evaluated by measuring the average CurvaLID accuracy across 10 random seeds. The study involved experimenting with the following parameters:

Number of convolutional layers: Tested configurations with 1 to 5 layers.
Activation functions: Evaluated ReLU, ELU, tanh, sigmoid, and softplus.
Kernel sizes: Tested kernel sizes ranging from 2 to 5.
Number of parameters: Adjusted the dense layer sizes to 64, 128, and 256 units.
Epochs: Tested training with 10, 20, 30, 40, 50 epochs.
Batch sizes: Evaluated sizes of 16, 32, 64, and 128.
Optimizers: Compared Adam and SGD.

The experiment result is shown in Table 5.

Table 5: Performance metrics for CNN hyperparameter selection.

Hyperparameter	Overall Accuracy	Time (min)
No. of Conv. Layers		
1	0.962	13.2
2	0.992	14.6
3	0.992	14.6
4	0.974	15.8
5	0.993	15.7
Activation Function		
ReLU	0.992	14.8
ELU	0.993	15.1
tanh	0.977	15.1
Sigmoid	0.975	14.5
Softplus	0.991	14.8
Kernel Size		
2	0.942	14.8
3	0.992	14.9
4	0.988	14.8
5	0.982	15.0
Dense Layer Size		
64	0.958	14.8
128	0.990	15.2
256	0.992	15.6
Epochs		
10	0.943	14.2
20	0.991	14.9
30	0.989	15.3
40	0.990	15.5
50	0.988	15.3
Batch Size		
16	0.990	15.6
32	0.991	14.8
64	0.988	14.7
128	0.982	14.2
Optimizer		
Adam	0.990	15.2
SGD	0.981	15.8

A.1.5 DETAILED PARAMETERS AND SPECIFICS OF THE CNN ARCHITECTURE FOR CLASSIFYING BENIGN PROMPTS IN CURVALID STEP 1

The CNN architecture consists of an input layer and two 1D convolutional layers. The first Conv1D layer applies 32 filters with a kernel size of 3 and a ReLU activation function, while the second Conv1D layer increases the number of filters to 64, again using a kernel size of 3 and ReLU activation. The output from the convolutional layers is flattened before passing through a fully connected layer with 128 units and ReLU activation. Finally, the network includes an output layer with four units and a softmax activation to classify the input into four distinct categories: Orca, MMLU, AlphEval, and TQA. The model is compiled using the Adam optimizer, categorical cross-entropy

loss, and accuracy as the evaluation metric. Training is conducted over 20 epochs with a batch size of 32 and a validation split of 20%.

A.1.6 DETAILED PARAMETERS AND SPECIFICS OF THE MLP ARCHITECTURE FOR CLASSIFYING BENIGN AND ADVERSARIAL PROMPTS IN CURVALID STEP 4

The MLP architecture consists of two fully connected layers and an output layer. The first layer contains 256 neurons with ReLU activation, followed by a batch normalization and dropout layer with a rate of 0.5 to prevent overfitting. A second layer, with 128 neurons and ReLU activation, is followed by another batch normalization and dropout layer. The final output layer uses softmax activation with two units corresponding to the binary classification of benign and adversarial prompts. The model is compiled using the Adam optimizer, a learning rate of 0.001, and categorical cross-entropy as the loss function, and it is trained over 150 epochs with early stopping to prevent overfitting.

A.1.7 EXPERIMENT SETTING FOR SECTION 5.1

We gathered 2519 prompts in total, with 1200 benign prompts and 1319 adversarial prompts. For benign prompts, we randomly sampled 300 prompts from each of Orca, MMLU, AlphacaEval and TruthfulQA. Besides, we gathered 320 SAP200 prompts, which is randomly selected 40 prompts from 8 adversarial goals. For DAN, we randomly sampled 350 prompts from the adversarial prompts uploaded on their Github, roughly half of their total number of prompts. For MathAttack, we used all 300 adversarial prompts uploaded to their Github. For GCG, we used their default parameter setting: learning rate = 0.01, batch size = 512, top-k = 256, and temperature = 1, and created a universal adversarial suffix. The targetted model is Vicuna-7B-v1.5. We used all 349 adversarial behaviors as listed in their Github.

A.2 ABLATION STUDIES

This section presents ablation studies for CurvaLID, including its performance across various adversarial prompts and its effectiveness under different training conditions and parameter settings.

A.2.1 PERFORMANCE METRICS FOR CURVALID IN RANDOMSEARCH, AMPLEGCG, PERSUASIVE ATTACK, AUTODAN, AND DRATTACK

Table 6 shows the Performance metrics for CurvaLID in PAIR, RandomSearch, AmpleGCG, Persuassive Attack, AutoDAN, and DrAttack. Note that due to the abundance of each dataset, we are testing these adversarial datasets against benign datasets individually, i.e., four benign datasets against each adversarial dataset.

We obtained 100 data from each of the four benign datasets. For PAIR, we sampled 171 adversarial prompts by generating PAIR adversarial prompts targeting Palm2, GPT4, Vicuna-7B, and Llama-2-13b-chat-hf. This is because PAIR's code focuses on 50 adversarial goals for each LLM, and PAIR does not always find an adversarial prompt for each goal in its default setting. For RandomSearch, we obtain the adversarial prompts from their GitHub directly. We gathered the datasets from attacking vicuna-13B-v1.5, R2D2, Nemotron-4-340b, Llama-2-70b, Llama-2-13B, GPT4_Turbo, GPT3.5_Turbo, and Gemma-7B. We randomly selected 200 unique adversarial prompts, as we observed that some adversarial prompts are the same when attacking different LLMs. For AmpleGCG, we obtained permission to access their adversarial prompts directly. We randomly sampled 200 prompts from the attack to Vicuna-7B on AdvBench. For Persuasive Attack, we included 150 adversarial prompts uploaded by the authors on HuggingFace. For AutoDAN, we included 150 AutoDAN prompts generated by following the setting from their Github, with 50 prompts each targeting Vicuna-7b-v1.5, Llama2-7b, and GPT-4-0613. For DrAttack, we tested 150 adversarial prompts generated by following the setting from their Github, with 50 prompts targeting each of Vicuna-7B, LLaMA-2-7B-Chat, and GPT-3.5-turbo.

A.2.2 ACCURACY OF CURVALID WITH LESS DATA

Table 7 shows the performance of CurvaLID when trained with less data. We training and tested CurvaLID with 150 data from each dataset, halving the number of data used from the main result. All other parameters remained the same.

Table 6: Performance metrics for CurvaLID in PAIR, RandomSearch, AmpleGCG, Persuasive Attack, AutoDAN, and DrAttack.

Adv. Dataset	PAIR	RandomSearch	AmpleGCG	Persuasive Attack	AutoDAN	DrAttack	Avg.
Benign Acc.	0.973	1	0.975	0.952	0.973	0.975	0.975
Adv. Acc.	1	1	0.976	1	1	1	0.996
Overall Acc.	0.983	1	0.975	0.962	0.978	0.980	0.986
F1 Score	0.986	1	0.987	0.974	0.986	0.987	0.985

Table 7: Classification Accuracy and Performance Metrics for CurvaLID on Benign and Adversarial Datasets with 150 Data from Each Dataset.

Data Class	Accuracy by Dataset				Accuracy by Class	Accuracy	F1
Benign	Orca	MMLU	AlpacaEval	TQA	0.992	0.988	0.988
	0.9565	1.000	1.000	1.000			
Adversarial	SAP	DAN	MathAttack	GCG	0.983		
	1.000	0.966	1.000	0.969			

Table 8: Performance metrics for CurvaLID with replacing MLP by local outlier factor

Metric	Benign	Adversarial	Overall
Accuracy	0.953	0.840	0.909
F1 Score	0.927	0.878	0.903

Table 9: Performance metrics for CurvaLID with replacing MLP by isolation forest

Metric	Benign	Adversarial	Overall
Accuracy	0.910	0.902	0.907
F1 Score	0.953	0.833	0.903

A.2.3 PERFORMANCE METRICS FOR CURVALID WITH REPLACING MLP BY LOCAL OUTLIER FACTOR OR ISOLATION FOREST

The parameters of the local outlier factor is as follows:n_neighbors=30, metric='chebyshev', leaf_size=10, and p=1.

For isolation forest, the contamination is set as auto.

We are testing 1900 prompts in total, with 100 prompts randomly sampled from each of SAP, DAN, MathAttack, GCG, PAIR, AmpleGCG and RandomSearch, and 300 prompts from each of Orca, MMLU, AlphacaEval and TruthfulQA. The experimental results are shown in Tables 8 and 9

A.2.4 CURVALID WITH PROMPTLID OR TEXTCURV ONLY

We demonstrate that both PromptLID and TextCurv are essential for achieving optimal performance in CurvaLID. When using only PromptLID as the input feature, the model reaches 0.95 accuracy. However, by combining PromptLID and TextCurv, we achieve an accuracy of over 0.99.

Table 10 illustrated the performance of CurvaLID if we only use LID or TextCurv as our features.

Table 10: Ablation study comparing LID and TextCurv for benign and adversarial prompt classification.

	PromptLID	TextCurv (1st Conv. Layer)	TextCurv (2nd Conv. Layer)	TextCurv (Both Conv. Layers)
Benign Acc.	0.987	0.690	0.738	0.960
Adv. Acc.	0.932	0.833	0.809	0.884
Overall Acc.	0.958	0.783	0.783	0.777
F1 Score	0.958	0.781	0.782	0.776

A.2.5 ACCURACY OF CURVALID IN DIFFERENT EMBEDDING

We tested CurvaLID using different word embeddings, including popular ones like GPT-2, BERT, XLNet, and DistilBERT. The experimental results show that CurvaLID performs similarly with around 0.99 overall accuracy, regardless of the word embedding used. Therefore, CurvaLID's classification performance is independent of the word embedding used.

Table 11 shows the accuracy of CurvaLID in different embedding. The experimental result shows that CurvaLID maintains a high classification accuracy under different word embeddings.

Table 11: Performance of CurvaLID with Different Word Embeddings. The table summarizes the classification accuracy and F1 scores for benign and adversarial prompts using various word embeddings.

Word embedding	Benign Prompt Accuracy	Adv. Prompt Accuracy	Overall Accuracy	F1
RoBERTa	0.984	1.000	0.992	0.992
GPT-2	0.973	1.000	0.986	0.986
BERT	0.987	1.000	0.994	0.993
XLNet	0.991	0.989	0.990	0.990
DistilBERT	0.970	0.992	0.982	0.980

A.2.6 CURVALID IN DEFENDING VICUNA-7B-V1.5

We measured the reduction in ASR after CurvaLID identified and filtered out the adversarial attacks in Vicuna-7B-v1.5, using the same settings specified in the respective original adversarial prompt papers. As shown in Table 12, CurvaLID successfully reduced the ASR of most attacks to zero, outperforming the studied SOTA defenses.

A.2.7 REPLACEMENT OF CNN IN CURVALID STEP 1 WITH TRANSFORMER AND RNN MODELS

We experimented with replacing the CNN architecture (Step 1 of CurvaLID) with Transformer and RNN models. The experimental results are shown in Table 13. While both Transformer and RNN achieved comparable detection accuracy (0.98 versus CNN's 0.992), they required almost two to three times longer training times. Details of the Transformer and RNN configurations are provided below:

Transformer The transformer has an input layer, a multi-head attention layer with 4 heads and a key dimension of 64, followed by layer normalization, a dense layer with 128 units, dropout (rate of 0.1), and a final layer normalization. The model then flattens the output, adds another dense layer with 128 units, and concludes with a softmax output layer for classification into 4 classes.

RNN: The RNN model begins with an input layer, followed by two stacked LSTM layers with 64 units each (the first LSTM layer returns sequences, while the second does not). After the LSTM layers, there is a dense layer with 128 units and a ReLU activation, followed by a softmax output layer

Table 12: Attack success rates (ASR) in percentage after CurvaLID in vicuna-7b-v1.5.

	SAP	DAN	MathAttack	GCG	PAIR	RandomSearch	AmpleGCG
Vanilla	69	41	56	95	98	95	97.5
CurvaLID	0	0	0	0	0	0	2.4

Table 13: Comparison of CurvaLID Architectures

Metric	CNN (Original Setting)	Transformer	RNN
Detection accuracy	0.992	0.984	0.989
Overall training time (min)	14.58	39.01	25.10

Data class	Accuracy by dataset				Accuracy by class	Overall accuracy	F1 score
Benign	Orca	MMLU	AlpacaEval	TQA	0.981	0.984	0.984
	0.993	0.983	0.973	0.973			
Adversarial	SAP	DAN	MathAttack	GCG	0.987		
	0.983	0.963	1.000	1.000			

Table 14: Performance metrics for CurvaLID on adversarial prompts with reordered word sequences.

Data class	Accuracy by dataset				Accuracy by class	Overall accuracy	F1 score
Benign	AlpacaEval		TQA		0.9412	0.982	0.98
	0.963		0.9194				
Adversarial	SAP	DAN	MathAttack	GCG	1		
	1	1	1	1			

Table 15: CurvaLID with different training and testing benign datasets

for classification into 4 classes. The model is compiled with the Adam optimizer and categorical cross-entropy loss.

A.2.8   PERFORMANCE OF CURVALID ON ADVERSARIAL PROMPTS WITH REORDERED WORD SEQUENCES

We utilized GPT-4-o to reorder the words in every sentence of the adversarial prompts while preserving their semantic meaning. The experimental results, presented in Table 14, demonstrate that CurvaLID maintains robust performance, achieving an overall accuracy of 0.984 in detecting these adversarial prompts with altered word order. It is important to note, however, that reordering the words in adversarial prompts may potentially disrupt their effectiveness as attacks, as the content and intent of the original prompts could be compromised.

A.2.9   CURVALID WITH SEPARATED BENIGN TRAINING AND TESTING DATA

We conducted an ablation study by training CurvaLID on two benign datasets and testing it on the remaining two. Specifically, we trained CurvaLID using only Orca and MMLU as benign data and evaluated it on AlpacaEval and TQA. The results, shown in Table 15, demonstrate an overall detection accuracy of 0.982, just one percentage point lower than when trained on all four benign datasets. These findings indicate that CurvaLID's performance remains robust and is not overly optimistic, even when tested on unseen benign datasets.

A.2.10   CURVALID WITH LONG TEXT LENGTH BENIGN PROMPTS

We conducted an additional experiment to evaluate CurvaLID's performance on benign prompts with longer text lengths. Specifically, we calculated the median text length of benign prompts (106 characters in our experiment), removed all benign prompts with fewer than the median, and reevaluated CurvaLID's performance as outlined in Section 5.1 (Page 7, Line 351). The results, presented in Table 16 below, show that this adjustment had minimal effect on detection accuracy. The overall

Data class	Accuracy by dataset				Accuracy by class	Overall accuracy	F1 score
Benign	**Orca**	**MMLU**	**AlpacaEval**	**TQA**	**0.981**	**0.990**	**0.990**
	0.922	1.000	1.000	1.000			
Adversarial	**SAP**	**DAN**	**MathAttack**	**GCG**	**1.000**		
	1.000	1.000	1.000	1.000			

Table 16: CurvaLID on benign prompts over 106 characters

Data class	Accuracy by dataset				Accuracy by class	Overall accuracy	F1 score
Benign	**Orca**	**MMLU**	**AlpacaEval**	**TQA**	**0.985**	**0.990**	**0.990**
	0.957	0.983	1.000	1.000			
Adversarial	**SAP**	**DAN**	**MathAttack**	**GCG**	**0.995**		
	0.990	0.990	1.000	1.000			

Table 17: CurvaLID on benign prompts with spelling errors

accuracy was 0.990, compared to 0.992 when all benign prompts (without filtering by text length) were included. This confirms that text length does not materially impact CurvaLID's performance.

A.2.11 CURVALID WITH NON-STANDARD BENIGN PROMPTS

We conducted an experiment to evaluate CurvaLID's performance on non-standard benign samples. Specifically, we utilized GPT-4-o to introduce spelling errors by replacing one word in each sentence of all benign prompts with a misspelled variant. The experimental results are presented in Table 17 below.

Our findings reveal that the detection accuracy by dataset exhibited minimal changes, and the overall accuracy remained almost identical to the original experiment , which involved benign prompts without spelling errors. These results demonstrate that introducing spelling errors has a negligible impact on CurvaLID's performance, reaffirming its robustness in handling non-standard text inputs.

A.3 LID ANALYSIS

This section includes supplementary information on LID analysis.

A.3.1 LID ESTIMATION USING METHOD OF MOMENTS

This section provides the pseudo code for estimating LID by the Method of Moments, see Algorithm A.3.1.

Algorithm A.2 LID Estimation using Method of Moments

Require: Dataset, Reference points, Number of neighbors k
1: **For each data point in Dataset:**
2:     Compute pairwise distances r between the data point and all points in Reference
3:     Sort distances in ascending order and store them as a
4:     Compute the mean of the first $k - 1$ nearest distances: $m = \frac{1}{k-1}\sum_{i=1}^{k-1} a_i$
5:     Estimate LID for the data point: $\text{LID} = \frac{m}{a_k - m}$
6: **Return** LID for all data points

A.3.2 AVERAGE LID AND STANDARD DEVIATION OF PROMPTS WITH AND WITHOUT STOP WORDS AND PUNCTUATION

Table 18 shows the average LID and standard deviation of prompts with and without stop words and punctuation.

Table 18: Comparison of Average LID and Standard Deviation (SD) of Prompts with and without Stop Words and Punctuation

Data Type	Dataset	With Stop Words and Punctuation		Without Stop Words and Punctuation	
		Avg. LID	SD	Avg. LID	SD
Benign	Orca	9.77	2.52	6.08	1.91
	MMLU	9.23	2.86	5.64	1.76
	AlpacaEval	13.14	104.58	4.07	2.26
	TQA	6.29	3.40	3.93	0.65
Adversarial	SAP	12.10	0.55	7.27	0.46
	DAN	24.52	244.72	7.18	1.18
	MWP	8.98	1.44	4.14	1.28
	GCG	8.35	0.40	6.18	0.41

A.3.3 TOP 10 MOST COMMON NEAREST NEIGHBOR WORDS AFTER REMOVING STOP WORDS AND PUNCTUATION

Table 19 shows the top 10 most common Nearest Neighbor words after removing stop words and punctuation. The experimental result demonstrates that word-level LID is insufficient for distinguishing between benign and adversarial prompts, even after the removal of stop words and punctuation.

Table 19: Top 10 Most Common Nearest Neighbor Words for each dataset after removing stop words and punctuation. The symbol ␣represents a space preceding a word or punctuation.

Dataset	Top 10 Most Common Nearest Neighbor Words after removing stop words and punctuation
SAP	␣Remember, ␣write, ␣goal, ␣mission, ␣act, ␣suicide, ␣Use, ␣phrases, ␣use, ␣refer
DAN	PT, ␣D, G, AN, ␣Chat, ␣answer, ␣AI, ␣responses, ␣response, ␣respond
MathAttack	␣many, ␣much, ␣would, ␣apples, ␣money, ␣20, ␣sold, ␣5, ␣bought, ␣day
GCG	use, ␣mar, ␣text, dt, end, ate, c, package, ized, ␣t
Orca	␣answer, à, °, ␣question, à¦, ␣one, ␣following, ␣said, s, ␣Answer
MMLU	␣mortgage, acre, ␣state, ␣contract, ␣deed, ␣would, ␣question, ␣statute, ␣action, s
AlpacaEval	␣drinks, ␣gathering, ␣interested, ␣give, ␣time, ␣home, br, ␣trying, ␣dishes, ␣guests
TQA	␣say, ks, ␣Oz, ␣established, ␣famous, ␣primed, ␣mirror, es, ␣principle, ␣power

A.4 PERFORMANCE OF OTHER SOTA DEFENSES

We summarize the performance of various defenses across different LLMs, focusing on their ability to reduce the ASR of adversarial prompts and compare this to CurvaLID's unified performance. CurvaLID outperforms the studied defenses and maintains consistent performance across all LLMs. While we primarily compare four key defenses in this subsection—SmoothLLM (Robey et al., 2023), IntentionAnalysis (Zhang et al., 2024a), RTT3d(Yung et al., 2024), and LAT(Sheshadri et al., 2024)—which are considered SOTA or represent some of the most recent developments, we also experimented with other defenses like Gradient Cuff(Hu et al., 2024), SELFDEFEND(Wang et al., 2024), and SafeDecoding(Xu et al., 2024a).

Given the computational and time constraints associated with replicating results and testing across multiple LLMs, we have cited the performance figures for these defenses from their respective papers. This approach ensures fairness, as different studies report varying results for these defenses

when replicating them against different adversarial prompts and across different models. Therefore, we rely on the original reported performances to provide a balanced and consistent comparison. Note that since the results for these defenses are primarily based on English adversarial prompts in their respective papers, our analysis here is focused solely on English prompts.

Defenses based on input perturbation demonstrate mixed results depending on the LLM and the nature of the adversarial attack. For instance, IntentionAnalysis reduces the ASR to between 0.03% and 8.34%, but it struggles with models like Vicuna-7B and MPT-30B-Chat, where the ASR for the SAP attack can reach nearly 20%. Similarly, while SmoothLLM can reduce the ASR to nearly 0% in various LLMs, it fails against PAIR attacks, showing ASRs of 46% in Vicuna-13B and 24% in GPT-4. RTT3d, as the first defense against MathAttack, managed to mitigate 40% of MathAttack in GPT4, but it failed to reduce the ASR to under 10%. LAT achieves near-zero ASR for models like Llama2-7B-Chat and Llama3-8B-Instruct. However, its reliance on a white-box setting and its testing on models with fewer than 10 billion parameters limit its broader applicability.

In the remainder of this subsection, we present the defensive performance of the SOTA defenses. The performance figures for all defenses are directly cited from their original papers due to the computational and time constraints involved in replicating results and testing across various LLMs. This approach ensures consistency and fairness in comparison, as the results reported by different studies often vary when replicating these defenses on different adversarial prompts and models. By relying on the figures from the original sources, we aim to provide an accurate and balanced reflection of each defense's performance.

We first compared the defenses using a common LLM, LLaMA-2-7B-Chat, as all the studied defenses employ this model. Table 20 presents the ASR comparison between CurvaLID and seven other defenses, showcasing CurvaLID's exceptional performance in mitigating various adversarial prompts.

Table 20: ASR comparison of CurvaLID with other defenses against different adversarial prompts on LLaMA-2-7B-Chat. A dash (-) indicates that experiments were not conducted for this setting in the original paper.

LLM	defense	Adversarial Prompt						
		GCG	PAIR	DAN	AmpleGCG	SAP	MathAttack	RandomSearch
LLaMA-2-7B-Chat	SmoothLLM	0.1	8	-	0	-	-	0
	LAT	0.007	0.025	-	-	-	-	-
	Gradient Cuff	0.012	0.23	-	-	-	-	-
	IntentionAnalysis	0	-	0.13	-	0	-	-
	SELFDEFEND	0.09	0.21	0.242	-	-	-	-
	RTT3d	0.17	0.043	-	-	-	-	-
	SafeDecoding	0	0.04	-	-	-	-	-
	CurvaLID (ours)	0	0	0	0.025	0	0	0

The following are the experimental settings and performances of the seven defenses we studied. Note that it includes various LLMs, namely Vicuna (Chiang et al., 2023), Llama-2(Touvron et al., 2023), Llama-3(AI@Meta, 2024), GPT-3.5(Brown, 2020), GPT-4(Achiam et al., 2023), (Anil et al., 2023), Claude-1(Anthropic, 2023a), Claude-2(Anthropic, 2023b), ChatGLM-6B(Zeng et al., 2022), MPT-30B-Chat(Team, 2023), DeepSeek-67B-Chatand(Bi et al., 2024). It also includes various adversarial prompts, namely, GCG(Zou et al., 2023), PAIR(Chao et al., 2023), DAN(Shen et al., 2023), AmpleGCG(Liao & Sun, 2024), SAP(Deng et al., 2023a), MathAttack(Zhou et al., 2024b), RandomSearch(Andriushchenko et al., 2024), Prefill(Haizelabs, 2023), Many-Shot(Anil et al., 2024), AutoDAN(Liu et al., 2023), (Mehrotra et al., 2023), (Wei et al., 2024), LRL(Yong et al., 2023), DrAttack(Li et al., 2024), (Chang et al., 2024), (Deng et al., 2023b), DeepInception(Li et al., 2023a), and Template(Yu et al., 2023).

SmoothLLM Detailed experimental settings are referred to (Robey et al., 2023). The experimental results are shown in Table 21.

Table 21: ASR comparison of different LLMs against adversarial prompts under SmoothLLM defense. A dash (-) indicates that experiments were not conducted for this setting in the original paper.

LLM	Adversarial Prompt			
	GCG	PAIR	RandomSearch	AmpleGCG
Vicuna-13B-v1.5	0.8	46	44	2
Llama-2-7B-chat	0.1	8	0	0
GPT-3.5	0.8	2	0	0
GPT-4	0.8	24	0	0
PaLM-2	0.9	-	-	-
Claude-1	0.3	-	-	-
Claude-2	0.3	-	-	-

Latent Adversarial Training Detailed experimental settings are referred to (Sheshadri et al., 2024). The experimental results are shown in Table 22.

Table 22: ASR comparison of different LLMs against adversarial prompts under LAT defense.

LLM	Adversarial Prompt				
	PAIR	Prefill	AutoPrompt	GCG	Many-Shot
Llama2-7B-chat	0.025	0.029	0.006	0.007	0
Llama3-8B-instruct	0.0033	0.0068	0	0.009	0

Gradient Cuff Detailed experimental settings are referred to (Hu et al., 2024). The experimental results are shown in Table 23.

Table 23: ASR comparison of different LLMs against adversarial prompts under Gradient Cuff defense.

LLM	Adversarial Prompt					
	GCG	AutoDAN	PAIR	TAP	Base64	LRL
Llama2-7B-chat	0.012	0.158	0.23	0.05	0.198	0.054
Vicuna-7B-v1.5	0.108	0.508	0.306	0.354	0	0.189

IntentionAnalysis Detailed experimental settings are referred to (Zhang et al., 2024a). The experimental results are shown in Table 24.

SELFDEFEND Detailed experimental settings are referred to (Wang et al., 2024). The experimental results are shown in Table 25.

RTT3d Detailed experimental settings are referred to (Yung et al., 2024). The experimental results are shown in Table 26.

SafeDecoding Detailed experimental settings are referred to (Xu et al., 2024a). The experimental results are shown in Table 27.

Table 24: ASR comparison of different LLMs against adversarial prompts under IntentionAnalysis defense. A dash (-) indicates that experiments were not conducted for this setting in the original paper.

LLM	Adversarial Prompt				
	DAN	SAP200	DeepInception	GCG	AutoDAN
ChatGLM-6B	5.48	6.12	0	1	2
LLaMA2-7B-Chat	0.13	0	0	0	0
Vicuna-7B-v1.1	3.42	0.31	0	0	10.5
Vicuna-13B-v1.1	0.94	1.12	0	0	3.5
MPT-30B-Chat	5.38	19.2	4.78	4	-
DeepSeek-67B-Chat	3.78	1.56	7.57	2	-
GPT-3.5	0.64	0	0	0	-

Table 25: ASR comparison of different LLMs against adversarial prompts under SELFDEFEND defense.

LLM	Adversarial Prompt							
	DAN	GCG	AutoDAN	PAIR	TAP	DrAttack	Puzzler	MultiJail
GPT-3.5	0.007	0.18	0.31	0.29	0.02	0.71	0.22	0.203
GPT-4	0.002	0	0.01	0.1	0.08	0.04	0.26	0.012

Table 26: ASR comparison of different LLMs against adversarial prompts under RTT3d defense. A dash (-) indicates that experiments were not conducted for this setting in the original paper.

LLM	Adversarial Prompt			
	PAIR	GCG	SAP	MathAttack
GPT-3.5	-	-	0.06	9.8
GPT-4	0.265	-	-	-
Llama-2-13B-Chat	0.043	0.17	-	-
Vicuna-13B-v1.5	0.26	0.15	-	-
PaLM-2	0.13	-	-	-

Table 27: ASR comparison of different LLMs against adversarial prompts under SafeDecoding defense.

LLM	Adversarial Prompt					
	GCG	AutoDAN	PAIR	DeepInception	SAP30	Template
Vicuna-7B	0.04	0	0.04	0	0.09	0.05
Llama2-7B-Chat	0	0	0.04	0	0	0