SSD: A Unified Framework for Self-Supervised Outlier Detection

Abstract

We ask the following question: what training information is required to design an effective outlier / out-of-distribution (OOD) detector, i.e, detecting samples that lie far away from training distribution? Since unlabeled data is easily accessible for many applications, the most compelling approach is to develop detectors based on only unlabeled in-distribution data. However, we observe that existing detectors based on unlabeled data perform poorly, often equivalent to a random prediction. In contrast, existing state-of-the-art OOD detectors achieve impressive performance but require access to fine-grained data labels for supervised training. We propose SSD, an outlier detector based on only unlabeled training data. We use self-supervised representation learning followed by a Mahalanobis distance based detection in the feature space. We demonstrate that SSD outperforms existing detectors based on unlabeled data by a large margin. Additionally, SSD achieves performance on par, and sometimes even better, with supervised training based detectors. Finally, we expand our detection framework with two key extensions. First, we formulate *few-shot OOD detection*, in which the detector has access to only one to five samples from the targeted OOD dataset. Second, we extend our framework to incorporate training data labels, if available. We find that our novel detection framework based on SSD displays enhanced performance with these extensions, and achieves state-of-the-art performance.

1 Introduction

Deep neural networks are at the cornerstone of multiple safety-critical applications, ranging from autonomous driving (Ramanagopal et al., 2018) to biometric authentication (Masi et al., 2018; Günther et al., 2017). When trained on a particular data distribution, referred to as in-distribution data, deep neural networks are known to fail against test inputs that lie far away from training distribution, commonly referred to as outliers or out-of-distribution (OOD) samples (Grubbs, 1969; Hendrycks & Gimpel, 2016). This vulnerability motivates the use of an outlier detector before feeding the input sample to the downstream neural network modules. However, a key question is to understand what training information is *crucial* for effective outlier detection? Will the detector require fine-grained annotation of training data labels or even access to a set of outliers in the training process?

Figure 1: Detection performance with CIFAR-10 as in-distribution and CIFAR-100 as OOD dataset. SSD performs significantly better than existing detectors for unlabeled data and on par with supervised learning based detectors.

Since neither data labels nor outliers are ubiquitous, the most compelling option is to design outlier detector based on only *unlabeled* in-distribution data. However, we observe that existing outlier detectors based on unlabeled data fail to scale up to complex data modalities, such as images (Figure 1). For example, autoencoder (Hawkins et al., 2002) based outlier detectors have achieved success in applications such as intrusion detection (Mirsky et al., 2018), and fraud detection (Schreyer et al., 2017). However, this approach achieves close to random chance performance on image datasets. Similarly, density modeling based methods, such as PixelCNN++ (Salimans et al., 2017),

and Glow (Kingma & Dhariwal, 2018) are known to even assign a higher likelihood to outliers in comparison to in-distribution data (Nalisnick et al., 2019).

In contrast, existing state-of-the-art detectors achieve high success on image datasets but assume the availability of fine-grained labels for in-distribution samples (Hendrycks & Gimpel, 2016; Bendale & Boult, 2015; Liang et al., 2017; Dhamija et al., 2018; Winkens et al., 2020). This is a strong assumption since labels, in-particular fine-grained labels, can be very costly to collect in some applications (Google AI, 2020), which further motivates the use of unlabeled data. The inability of supervised detectors to use unlabeled data and poor performance of existing unsupervised approaches naturally give rise to the following question.

> *Can we design an effective outlier detector with access to only unlabeled data*
> *from training distribution?*

A framework for outlier detection with unlabeled data involves two key steps: 1) Learning a good feature representation with unsupervised training methods 2) Modeling features of in-distribution data without requiring class labels. For example, autoencoders attempt to learn the representation with a bottleneck layer, under the expectation that successful reconstruction requires learning an efficient set of representations. Though useful for tasks such as dimensionality reduction, we find that these representations are not good enough to sufficiently distinguish in-distribution data and outliers. We argue that if unsupervised training can learn a rich understanding of key semantics in in-distribution data then absence of such semantics in outliers can cause them to lie far in the feature space, thus making it easy to detect them. Recently, self-supervised representation learning methods have made large progress, commonly measured by accuracy achieved on a downstream classification task (Chen et al., 2020; He et al., 2020; Oord et al., 2018; Misra & Maaten, 2020; Tian et al., 2020). We leverage these representations in our proposed cluster-conditioned framework based on the Mahalanobis distance (Mahalanobis, 1936). Our key result is that self-supervised representations are highly effective for the task of outlier detection in our self-supervised outlier detection (SSD) framework where they not only perform far better than previous unsupervised training methods but also perform on par, and sometimes even better, than supervised representations (Figure 1).

What if access to a fraction of OOD data or training data labels is available? How do we move past a detector based on unlabeled data and design a framework which can take advantage of such information? Though access to outliers during training is a strong assumption, it may be feasible to obtain a few prior instances of such outliers (Görnitz et al., 2013). We characterize this setting as *few-shot OOD detection*, where we assume access to very few, often one to five, samples from the targeted set of outliers. While earlier approaches (Liang et al., 2017; Lee et al., 2018b) mostly use such data to calibrate the detector, we find that access to just one outlier can bring an additional boost in the performance of our detector. Crucial to this success is a reliable estimation of first and second order statistics of OOD data with just a very few samples in the high dimensional feature space.

Finally, if class labels are available in the training phase, how can we incorporate them in the SSD framework for outlier detection? Recent works have proposed the addition of the supervised cross-entropy and self-supervised learning loss with a tunable parameter, which may require tuning for optimal parameter setting for each dataset. We demonstrate that incorporating labels directly in the contrastive loss achieves 1) a parameter-free detector, and 2) state-of-the-art performance.

1.1 KEY CONTRIBUTIONS

SSD for unlabeled data. We propose SSD, an unsupervised framework for outlier detection based on unlabeled in-distribution data. We demonstrate that SSD outperforms existing unsupervised outlier detectors by a large margin while also performing on par, and sometimes even better than supervised detection methods. We validate our observation across four different datasets: CIFAR-10, CIFAR-100, STL-10, and ImageNet.

Extensions of SSD. We provide multiple extensions of SSD to further improve its performance. We formulate *few-shot OOD detection* and propose detection methods which can achieve a significantly large gain in performance with access to only a few targeted OOD samples. Next, we extend SSD, without using any tuning parameter, to also incorporate training data labels and achieve state-of-the-art performance.

2 SSD: SELF-SUPERVISED OOD DETECTION

In this section, we first provide the necessary background on OOD detection and then present the underlying formulation of our self-supervised detector (SSD) that relies on unlabeled in-distribution data. Finally, we describe multiple extensions of SSD to (optionally) incorporate access to target OOD samples and training data labels (if available).

Notation. We represent the input space by $\mathcal{X}$ and corresponding label space as $\mathcal{Y}$. We assume in-distribution data is sample from $\mathbb{P}^{in}_{X \times Y}$. In the absence of data labels, it is sampled from marginal distribution $\mathbb{P}^{in}_X$. We sample out-of-distribution data from $\mathbb{P}^{ood}_X$. We denote the feature extractor by $f : \mathcal{X} \rightarrow \mathcal{Z}$, where $\mathcal{Z} \subset \mathbb{R}^d$, a function which maps a sample from the input space to the d-dimensional feature space ($\mathcal{Z}$). The feature extractor is often parameterized by a deep neural network. In supervised learning, we obtain output confidence for each class by $g \circ f : \mathcal{X} \rightarrow \mathbb{R}^c$. In most cases, g is parameterized by a shallow neural network, generally a linear classifier.

Problem Formulation: Outlier / Out-of-distribution (OOD) detection. Given a collection of samples from $\mathbb{P}^{in}_X \times \mathbb{P}^{ood}_X$, the objective is to correctly identify the source distribution, i.e., $\mathbb{P}^{in}_X$ or $\mathbb{P}^{ood}_X$, for each sample. We use the term *supervised OOD detectors* for detectors which use in-distribution data labels, i.e., train the neural network ($f \circ g$) on $\mathbb{P}_{\mathcal{X} \times \mathcal{Y}}$ using supervised training techniques. *Unsupervised OOD detectors* aim to solve the aforementioned OOD detection tasks, with access to only $\mathbb{P}^{in}_{\mathcal{X}}$. In this work, we focus on developing effective unsupervised OOD detectors.

Background: Contrastive self-supervised representation learning. Given unlabelled training data, it aims to train a feature extractor, by discriminating between individual instances from data, to learn a good set of representations. Using image transformations, it first generates multiple transformations/views of an image, commonly referred to as positives. Next, it optimizes to pull each instance close to the other positives while pushing away from other negatives. Assuming that (x_i, x_j) are positive pairs for an image and $h(.)$ is a projection header, τ is the temperature, contrastive training minimizes the following loss, referred to as Normalized temperature-scaled cross-entropy (*NT-Xent*), over each batch.

$$\mathcal{L}_{batch} = \sum_{i=1}^{2N} -log \frac{e^{u_i^T u_j / \tau}}{\sum_{k=1}^{2N} \mathbb{1}(k \neq i) e^{u_i^T u_k / \tau}} \; ; \qquad u_i = \frac{h(f(x_i))}{\|h(f(x_i))\|_2} \tag{1}$$

2.1 UNSUPERVISED OUTLIER DETECTION WITH SSD

Leveraging contrastive self-supervised training. In the absence of data labels, SSD consists of two steps: 1) Training a feature extractor using unsupervised representation learning. 2) Developing an effective OOD detector based on hidden features which isn't conditioned on data labels.

We leverage contrastive self-supervised training for representation learning in our outlier detection framework, particularly due to its state-of-the-art performance. We will discuss the effect of different representation learning methods later in Section 3.2.

Cluster-conditioned detection. We develop an *cluster-conditioned* detection method in the feature space. We first partition the features for in-distribution training data in m clusters. We represent features for each cluster as $\mathcal{Z}_m$. We use k-means clustering method, due to its effectiveness and low computation cost. Next, we model features in each cluster independently, and calculate the following *membership score* $(s_x) = \min_m \mathcal{D}(x, \mathcal{Z}_m)$ for each test input x, where $\mathcal{D}(.,.)$ is a distance metric in the feature space. We use the membership scores for the test set of the in-distribution dataset and OOD dataset to discriminate between them. We discuss the choice of the number of clusters in Section 3.2.

Figure 2: AUROC along every individual principle eigenvector with CIFAR-10 as in-distribution and CIFAR-100 as OOD. Higher eigenvalues dominates euclidean distance, but are least helpful for outlier detection. Mahalnobis distance avoid this bias with appropriate scaling and performs better.

Choice of distance metric: Mahalanobis distance. We use Mahalanobis distance to calculate the membership score as follows:

$$s_x = \min_m (z_x - \mu_m)^T \Sigma_m^{-1}(z_x - \mu_m) \tag{2}$$

where μ_m and Σ_m are the estimated mean and covariance for features ($\mathcal{Z}$) of the in-distribution training data. We justify this choice with quantitative results in Figure 2. With eigendecomposition of sample covariance ($\Sigma_m = Q_m \Lambda_m Q_m^{-1}$), $s_x = \min_m \left(Q^T(z_x - \mu_m)\right)^T \Lambda_m^{-1}\left(Q^T(z_x - \mu_m)\right)$ which is equivalent to euclidean distance scaled with eigenvalues. We discriminate between in-distribution (CIFAR10) and OOD (CIFAR100) data along each principal eigenvector (using AUROC, higher the better). With euclidean distance, i.e, in absence of scaling, component with higher eigenvlaues weight most but provide least discriminative power. Scaling with eigenvalues remove the bias, making Mahalnobis distance effective for outlier detection in the feature space.

2.2 FEW-SHOT OOD DETECTION (SSD_k)

In this extension of the SSD framework, we consider the scenario where access to a few samples from the OOD dataset of interest is available at the time of training. We focus on *one-shot* and *five-shot* detection, which refers to access to only one and fives samples, from each class of targeted OOD dataset, respectively. Our hypothesis is that in-distribution samples and OOD samples will be closer to other inputs from their respective distribution *in the feature space*, while lying further away from each other. We incorporate this hypothesis by using the following formulation of membership score.

$$s_x = (z_x - \mu_{in})^T \Sigma_{in}^{-1}(z_x - \mu_{in}) - (z_x - \mu_{ood})^T \Sigma_{ood}^{-1}(z_x - \mu_{ood}) \tag{3}$$

where μ_{in}, Σ_{in} and μ_{ood}, Σ_{ood} are the estimated sample mean and covariance in the feature space for in-distribution and OOD data, respectively.

Challenge. The key challenge is to reliably estimate the statistics for OOD data, with access to only a few samples. Sample covariance is not an accurate estimator of covariance when the number of samples is less than the dimension of feature space (Stein, 1975), which is often in the order of thousands for deep neural networks.

Shrunk covariance estimators and data augmentation. We overcome this challenge by using the following two techniques: 1) we use shrunk covariance estimators (Ledoit & Wolf, 2004), and 2) we create more OOD samples using data augmentation. We use shrunk covariance estimators due to their ability to estimate covariance better than sample covariance, especially when the number of samples is even less than the feature dimension. To further improve the estimation we increase the number of samples using data augmentation at the input stage. We use common image transformations, such as geometric and photometric changes to create multiple different images from a single source image. Thus given a set of k OOD samples $\{u_1, u_2, \ldots, u_k\}$, we first create a set of $k \times n$ samples using data augmentation, $\mathcal{U} = \{u_1^1, \ldots, u_1^n, \ldots u_k^1, \ldots, u_k^n\}$. Using this set, we calculate the membership score for a test sample in the following manner.

$$s_x = (z_x - \mu_{in})^T \Sigma_{in}^{-1}(z_x - \mu_{in}) - (z_x - \mu_U)^T S_U^{-1}(z_x - \mu_U) \tag{4}$$

where μ_U and S_U is the mean and shrunk covariance estimator for the set $\mathcal{U}$, respectively.

2.3 HOW TO BEST USE DATA LABELS ($SSD+$).

If fine-grained labels for in-distribution data are available, an immediate question is how to incorporate them in training to enhance performance in the detection of OOD samples.

Conventional approach: additive self-supervised and supervised training loss. A common theme in earlier work (Hendrycks et al. 2019b; Winkens et al. 2020) is to add self-supervised (L_{ssl}) and supervised (L_{sup}) training loss functions, i.e., $L_{training} = L_{sup} + \alpha L_{ssl}$, where the hyper-parameter α is chosen for best performance on OOD detection. A common loss function for supervised training is cross-entropy.

Our approach: incorporating labels in contrastive self-supervised training. As we show in Section 3.2, even without labels, contrasting between instances using self-supervised learning is highly successful for outlier detection. We argue for a similar instance-based contrastive training, where labels can also be incorporated to further improve the learned representations. To this end, we

use the recently proposed supervised contrastive training loss function (Khosla et al., 2020), which uses labels for a more effective selection of positive and negative instances for each image. We minimize the following loss function.

$$\mathcal{L}_{batch} = \sum_{i=1}^{2N} -log \frac{\sum_{k=1}^{2N} \mathbb{1}(k \neq i)\mathbb{1}(y_k = y_i)e^{u_i^T u_k/\tau}}{\sum_{k=1}^{2N} \mathbb{1}(k \neq i)e^{u_i^T u_k/\tau}} \tag{5}$$

In comparison to contrastive NT-Xent loss (Equation 1), now we use images with identical labels in each batch as positives. We will show the superior performance of this approach compared to earlier approaches, and note that it is also a parameter-free approach which doesn't require additional OOD data to tune parameters. We further use the proposed cluster-conditioned framework, with Mahalnobis distance, as we find it results in better performance than using data labels. We further summarize our framework in Algorithm 1.

Algorithm 1: Self-supervised outlier detection framework (SSD)

Input : $\mathcal{X}_{in}$, $\mathcal{X}_{test}$, feature extractor (f), projection head (h), Required True-positive rate (T),
   Optional: $\mathcal{X}_{ood}, \mathcal{Y}_{in}$ # $\mathcal{X}_{in} \in \mathbb{P}_X^{in}, \mathcal{X}_{test} \in \mathbb{P}_{X \times Y}^{in}, \mathcal{X}_{ood} \in \mathbb{P}_X^{ood}$
Output : Is outlier or not? $\forall x \in \mathcal{X}_{test}$
Function *getFeatures($\mathcal{X}$): return* $\{f(x_i)/\|f(x_i)\|_2 \mid x_i \in \mathcal{X}\}$;
Function *SSDScore($\mathcal{Z}, \mu, \Sigma$): return* $\{(z-\mu)^T \Sigma^{-1}(z-\mu) \mid x_i \in \mathcal{X}\}$;
Function *SSDkScore($\mathcal{Z}, \mu_{in}, \Sigma_{in}, \mu_{ood}, \Sigma_{ood}$):*
 | return $(z-\mu_{in})^T \Sigma_{in}^{-1}(z-\mu_{in}) - (z-\mu_{ood})^T \Sigma_{ood}^{-1}(z-\mu_{ood})$;
end
Parition $\mathcal{X}_{in}$ in training set ($\mathcal{X}_{train}$) and calibration set ($\mathcal{X}_{cal}$);
if $\mathcal{Y}_{in}$ *is available* **then**
 | $\mathcal{L}_{batch} = \sum_{i=1}^{2N} -log \frac{e^{u_i^T u_j/\tau}}{\sum_{k=1}^{2N} \mathbb{1}(k \neq i)e^{u_i^T u_k/\tau}}; u_i = \frac{h(f(x_i))}{\|h(f(x_i))\|_2};$ # Train feature extractor
else
 | $\mathcal{L}_{batch} = \sum_{i=1}^{2N} -log \frac{\sum_{k=1}^{2N} \mathbb{1}(k \neq i)\mathbb{1}(y_k = y_i)e^{u_i^T u_k/\tau}}{\sum_{k=1}^{2N} \mathbb{1}(k \neq i)e^{u_i^T u_k/\tau}};$
end
$\mathcal{Z}_{train} = \text{getFeatures}(\mathcal{X}_{train})$, $\mathcal{Z}_{cal} = \text{getFeatures}(\mathcal{X}_{cal})$
$\mathcal{Z}_{test} = \text{getFeatures}(\mathcal{X}_{test})$, **if** $\mathcal{X}_{ood}$ *is available*: $\mathcal{Z}_{ood} = \text{getFeatures}(\mathcal{X}_{ood})$;
if $\mathcal{X}_{ood}$ *is not available* **then**
 | $s_{cal} = \text{SSDScore}(\mathcal{Z}_{cal}, \mu_{train}, \Sigma_{train})$; # Sample mean and convariance of $\mathcal{Z}_{train}$
 | $s_{test} = \text{SSDScore}(\mathcal{Z}_{test}, \mu_{train}, \Sigma_{train})$ # membership score;
else
 | # Using estimation techniques from Section 2.2 for $\mathcal{Z}_{ood}$
 | $s_{cal} = \text{SSDkScore}(\mathcal{Z}_{cal}, \mu_{train}, \Sigma_{train}, \mu_{ood}, \Sigma_{ood})$;
 | $s_{test} = \text{SSDkScore}(\mathcal{Z}_{test}, \mu_{train}, \Sigma_{train}, \mu_{ood}, \Sigma_{ood})$;
end
$x_i \in \mathcal{X}_{test}$ is an outlier if $s_{test}^i > (s_{cal}$ threshold at TPR = T);

---

3 EXPERIMENTAL RESULTS

3.1 COMMON SETUP ACROSS ALL EXPERIMENTS

We use recently proposed NT-Xent loss from SimCLR (Chen et al., 2020) method for self-supervised training. We use the ResNet-50 network in all key experiments but also provide ablation with ResNet-18, ResNet-34, and ResNet-101 network architecture. We train each network, for both supervised and self-supervised training, with stochastic gradient descent for 500 epochs, 0.5 starting learning rate with cosine decay, weight decay, and batch size set to 1e-4, and 512, respectively. We set the temperature parameter to 0.5 in the NT-Xent loss. We evaluate our detector with three performance metrics, namely FPR (at TPR=95%), AUROC, and AUPR. For the supervised training baseline, we use identical training budget as SSD while also using the Mahalanobis distance based detection in the feature space. Due to space constraints, we present results with AUROC, which refers to area under the receiver operating characteristic curve, in the main paper and provide detailed results with other performance metrics in Appendix B.5. Our setup incorporates six image datasets along with some

other synthetic datasets based on random noise. We report the average results over three independent runs in most experiments.

Number of clusters. We find the choice of the number of clusters dependent on which layer we extract the features from in the Residual neural networks. While for the first three blocks, we find an increase in AUROC with the number of clusters, the trend is reversed for the last block (Appendix B.2). Since the last block features achieve the highest detection performance, we model the in-distribution features as a single cluster.

Table 1: Comparison of SSD with different outlier detectors using only unlabeled training data.

In-distribution (Out-of-distribution)	CIFAR-10 (SVHN)	CIFAR-10 (CIFAR-100)	CIFAR-100 (SVHN)	CIFAR-100 (CIFAR-10)	Average
Autoencoder (Hawkins et al., 2002)	2.5	51.3	3.0	51.4	27.0
VAE (Kingma & Welling, 2014)	2.4	52.8	2.6	47.1	26.2
PixelCNN++ (Salimans et al., 2017)	15.8	52.4	–	–	–
Deep-SVDD (Ruff et al., 2018b)	14.5	52.1	16.3	51.4	33.5
Rotation-loss(Gidaris et al., 2018)	97.9	81.2	94.4	50.1	80.9
SSD	**99.6**	**90.6**	**94.9**	**69.6**	**88.7**
SSD_k ($k=5$)	**99.7**	**93.1**	**99.1**	**78.2**	**92.5**

3.2 PERFORMANCE OF SSD

Comparison with unsupervised detectors. We present this comparison in Table 1. We find that our SSD approach achieves more than 55% higher average AUROC compared to standard outlier detectors based on Density modeling (PixelCNN++ (Salimans et al., 2017)), input reconstruction (Auto-encoder (Hawkins et al., 2002), Variational Auto-encoder (Kingma & Welling, 2014)), and One-class classification (Deep-SVDD Ruff et al. (2018b)). A common limitation of each of these three detectors is to find images from the SVHN dataset as more in-distribution when trained on CIFAR-10 or CIFAR-100 dataset. We also experiment with Rotation-loss Gidaris et al. (2018), a non-contrastive self-supervised training objective. We find that SSD with SimCLR achieves 7.8% higher average AUROC compare to using Rotation-loss.

Ablation studies We ablate along individual parameters in self-supervised training with CIFAR-10 as in-distribution data (Figure 3). While architecture doesn't have a large effect on AUROC for any OOD dataset, we find that number of epochs and batch-size plays a key role in detecting outliers from the CIFAR-100 dataset, which is hardest to detect among the four OOD datasets. We find an increase in the size of training data helpful in the detection of all four OOD datasets.

(a) Model size.	(b) Number of epochs.	(c) Batch-size.	(d) Size of training set.

Figure 3: SSD performance when ablating across different training parameters under following setup: In-distribution dataset = CIFAR-10, OOD dataset = CIFAR100, Epoch = 500, Batch-size = 512.

Comparison with supervised representations. We earlier asked the question *whether data labels are even necessary to learn representations crucial for OOD detection?* To answer it, we compare SSD with a supervised network, trained with an identical budget as SSD while also using Mahalanobis distance in the feature space, across sixteen different pairs of in-distribution and out-of-distribution datasets, and report our results in Table 2. We observe that self-supervised representation even achieve better performance than supervised representation for 56% of the tasks in Table 2.

3.3 FEW-SHOT OOD DETECTION (SSD_k)

Setup. We focus on one-shot and five-shot OOD detection, i.e, set k to 1 or 5 in Equation 4, with Ledoit-Wolf (Ledoit & Wolf, 2004) estimator and ten transformation of each sample. To avoid a bias on selected samples, We report average results over 25 random trials.

Table 2: Comparison of OOD detection with self-supervised (SSD) and supervised representations. We also provide results for few-shot OOD detection for comparison with SSD.

In-distribution	OOD	SSD	Supervised	SSD_k k=1	k=5	In-distribution	OOD	SSD	Superivsed	SSD_k k=1	k=5
CIFAR-10	CIFAR-100	90.6	90.6	91.7	93.0	STL-10	CIFAR-100	**94.8**	84.0	90.1	90.0
	SVHN	99.6	99.6	99.9	99.7		SVHN	**98.7**	95.7	98.7	99.4
	Texture	97.6	**97.8**	98.9	99.4		Texture	**85.8**	75.5	85.7	84.5
	Blobs	98.8	**99.9**	99.7	100.0		Blobs	**96.4**	88.6	96.5	99.9
CIFAR-100	CIFAR-10	**69.6**	55.3	74.8	78.3	ImageNet	SVHN	99.1	**99.4**	99.7	100.0
	SVHN	**94.9**	94.5	99.5	99.1		Texture	**95.4**	85.1	94.7	97.3
	Texture	82.9	98.8	96.8	94.2		Blobs	**99.5**	98.4	100.0	100.0
	Blobs	**98.1**	57.3	98.1	100.0		Gaussian Noise	100.0	100.0	100.0	100.0

Results. Compared to baseline SSD detection, one-shot and five-shot settings improves the average AUROC, across all OOD datasets, by 1.6 and 2.1, respectively (Table 1,2). In particular, we observe the large gain with CIFAR100 as in-distribution and CIFAR-10 as OOD where five-shot detection improves the AUROC from 69.6 to 78.3. We find the use of shrunk covariance estimator most critical in the success of our estimator. Use of shrunk covariance estimation itself improves the AUROC from 69.6 to 77.1. Then data augmentation further improves it 78.3 for the five-shot detection. With an increasing number of transformed copies of each sample, we also observe improvement in ROC, though it later plateaus close to ten copies (Appendix B.3).

What if additional OOD images are available Note that earlier works, such as (Liang et al., 2017), assume that 1000 OOD inputs are available for tuning the detector. We find that with access to this large amount of data, SSD_k can improve the state-of-the-art by an even larger margin. With CIFAR100 as in-distribution and CIFAR10 as out-distribution, we achieve 89.4 AUROC, which is 11 percentage points higher than the current state-of-the-art (Winkens et al., 2020).

3.4 Success when using data labels ($SSD+$)

Now we integrate labels of training data in our framework and compare it with existing state-of-the-art detectors. We report our results in Table 3. Our approach improves the average AUROC by 0.8% over the previous state-of-the-art detector. Our approach also achieves equal or better performance across individual pairs of in and out-distribution dataset. For example, using labels in our framework improves the AUROC of Mahalanobis detector from 55.5 to 72.1 for CIFAR-100 as in-distribution and CIFAR-10 as the OOD dataset. Using the simple softmax probabilities, training a two-layer MLP on learned representations further improves the AUROC to 78.3. Combining $SSD+$ with a five-shot OOD detection method further brings a gain of 1.4% in the average AUROC.

Table 3: Comparison of $SSD+$, i.e., incorporating labels in the SSD detector, with state-of-the-art detectors based on supervised training.

In-distribution (Out-of-distribution)	CIFAR-10 (CIFAR-100)	CIFAR-10 (SVHN)	CIFAR-100 (CIFAR-10)	CIFAR-100 (SVHN)	Average
Softmax-probs (Hendrycks & Gimpel, 2016)	89.8	95.9	78.0	78.9	85.6
ODIN(Liang et al., 2017)[†]	89.6	96.4	77.9	60.9	81.2
Mahalanobis (Lee et al., 2018b)[†]	90.5	99.4	55.3	94.5	84.8
Residual Flows (Zisselman & Tamar, 2020)[†]	89.4	99.1	77.1	97.5	90.7
Gram Matrix (Sastry & Oore, 2019)	79.0	99.5	67.9	96.0	85.6
Outlier exposure (Hendrycks et al., 2019a)	93.3	98.4	75.7	86.9	88.6
Rotation-loss + Supervised (Hendrycks et al., 2019c)	90.9	98.9	–	–	–
Contrastive + Supervised (Winkens et al., 2020)[*]	92.9	99.5	**78.3**	95.6	91.6
$SSD+$	**93.4**	**99.9**	78.3	**98.2**	**92.4**
SSD_k+ ($k = 5$)	**94.1**	99.6	**84.1**	97.4	**93.8**

[*] Uses $4\times$ wider ResNet-50 network, [†] Requires additional out-of-distribution data for tuning.

4 Related work

OOD detection with unsupervised detectors. Interest in unsupervised outlier detection goes back to Grubbs (1969). We categorize these approaches in three groups 1) Reconstruction-error-based detection using Auto-encoders (Hawkins et al., 2002; Mirsky et al., 2018; Schreyer et al., 2017), Variational auto-encoders (Abati et al., 2018; An & Cho, 2015) 2) Classification based, such as Deep-SVDD (Ruff et al., 2018b;a; El-Yaniv & Wiener, 2010; Geifman & El-Yaniv, 2017) and 3) Probabilistic detectors, such as density models like Glow, PixelCNN++ (Ren et al., 2019; Nalisnick

et al., 2019; Salimans et al., 2017; Kingma & Dhariwal, 2018). We compare with detectors from each category and find that SSD outperforms them by a wide margin.

OOD detection with supervised learning. Supervised detectors have been most successful with complex input modalities, such as images and language (Chalapathy et al., 2018; DeVries & Taylor, 2018; Dhamija et al., 2018; Jiang et al., 2018; Yoshihashi et al., 2018; Lee et al., 2018a). Most of these approaches model features of in-distribution data at output (Liang et al., 2017; Hendrycks & Gimpel, 2016; Dhamija et al., 2018) or in the feature space (Lee et al., 2018b; Winkens et al., 2020) for detection. We show that SSD can achieve performance on par with these supervised detectors, without using data labels. A subset of these detectors also leverages generic OOD data to boost performance (Hendrycks et al., 2019a; Mohseni et al., 2020).

Access to OOD data at training time. Some recent detectors also require OOD samples for hyperparameter tuning (Liang et al., 2017; Lee et al., 2018b; Zisselman & Tamar, 2020). We extend SSD to this setting but assume access to only a few OOD samples, referred to as few-shot OOD detection, which our frameworks can efficiently utilize to bring large gains in performance.

In conjunction with supervised training. Vyas et al. (2018) use ensemble of leave-one-out classifier, Winkens et al. (2020) uses contrastive self-supervised training, Hendrycks et al. (2019c) uses rotation based self-supervised loss, in conjunction with supervised cross-entropy loss to achieve state-of-the-art performance in OOD detection. Here we extend SSD, to incorporate data labels, when available, and achieve *better* performance than existing state-of-the-art.

5 DISCUSSION AND CONCLUSION

SSD is a parameter free detector. In designing SSD, we aimed to avoid introducing parameters which would requires additional OOD data for tuning. We use a standard set of parameters for self-supervised training and model the learned features with a single-cluster. When incorporating labels, we combine them with existing contrastive loss without requiring additional parameters.

Why contrastive self-supervised learning is effective in the SSD framework? We focus on the NT-Xent loss function, which is parameterized by a temperature variable (τ). Its objective to pull positive instances, i.e., different transformations of an image, together while pushing away from other instances. Earlier works have shown that such contrastive training forces the network to learn a good set of feature representations. However, a smaller value of temperature quickly saturates the loss, discouraging it to improve the feature representation. We find that the

Table 4: Test Accuracy and AUROC with different temperature values in *NT-Xent* (Equation 1) loss. Using CIFAR-10 as in-distribution and CIFAR-100 as OOD dataset.

Temperature	0.001	0.01	0.1	0.5
Test -Accuracy	70.8	76.7	86.9	90.5
AUROC	66.7	71.6	85.5	89.5

performance of SSD also degrades with lower temperature, suggesting the necessity of learning a good set of feature representation for effective outlier detection (Table 4).

How discriminative ability of feature representations evolves over the course of training. We analyze this effect in Figure 4 where we compare both SSD and supervised training based detector over the course of training. While discriminative ability of self-supervised training in SSD is lower at the start, it quickly catches up with supervised representation after half of the training epochs.

Performance of SSD improves with the amount of available unlabelled data. A compelling advantage of unsupervised learning is to learn from unlabeled data, which can be easily collected. As presented in Figure 3, we find that performance of SSD increases with the size of training. We conduct another experiment with the STL-10 dataset, where in addition to the 5k training images, we also use additional 10k images from the unlabeled set. This improves the AUROC from 94.7 to 99.4 for CIFAR-100 as the OOD dataset, further demonstrating the success of SSD in leveraging unlabeled data (Appendix B.4). In conclusion, our framework provides an effective & flexible approach for outlier detection using unlabeled data.

Figure 4: AUROC over the course of training with CIFAR-10 as in-distribution and CIFAR-100 as OOD set.

REFERENCES

Davide Abati, Angelo Porrello, Simone Calderara, and Rita Cucchiara. And: Autoregressive novelty detectors. *arXiv preprint arXiv:1807.01653*, 2018.

Jinwon An and Sungzoon Cho. Variational autoencoder based anomaly detection using reconstruction probability. *Special Lecture on IE*, 2:1–18, 2015.

A. Bendale and T. Boult. Towards Open Set Deep Networks. *ArXiv e-prints*, November 2015.

Raghavendra Chalapathy, Aditya Krishna Menon, and Sanjay Chawla. Anomaly detection using one-class neural networks. *arXiv preprint arXiv:1802.06360*, 2018.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. *arXiv preprint arXiv:2002.05709*, 2020.

M. Cimpoi, S. Maji, I. Kokkinos, S. Mohamed, , and A. Vedaldi. Describing textures in the wild. In *Proceedings of the IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2014.

Adam Coates, Andrew Ng, and Honglak Lee. An analysis of single-layer networks in unsupervised feature learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pp. 215–223, 2011.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *Computer Vision and Pattern Recognition, 2009. CVPR 2009. IEEE Conference on*, pp. 248–255. Ieee, 2009.

Terrance DeVries and Graham W Taylor. Learning confidence for out-of-distribution detection in neural networks. *arXiv preprint arXiv:1802.04865*, 2018.

Akshay Raj Dhamija, Manuel Günther, and Terrance Boult. Reducing network agnostophobia. In *Advances in Neural Information Processing Systems*, pp. 9175–9186, 2018.

Ran El-Yaniv and Yair Wiener. On the foundations of noise-free selective classification. *Journal of Machine Learning Research*, 11(May):1605–1641, 2010.

Yonatan Geifman and Ran El-Yaniv. Selective classification for deep neural networks. In *Advances in neural information processing systems*, pp. 4878–4887, 2017.

Spyros Gidaris, Praveer Singh, and Nikos Komodakis. Unsupervised representation learning by predicting image rotations. *arXiv preprint arXiv:1803.07728*, 2018.

API Google AI. *Data Labelling Pricing - Google AI Platform*, 2020. URL https://cloud.google.com/ai-platform/data-labeling/pricing.

Nico Görnitz, Marius Kloft, Konrad Rieck, and Ulf Brefeld. Toward supervised anomaly detection. *Journal of Artificial Intelligence Research*, 46:235–262, 2013.

Frank E Grubbs. Procedures for detecting outlying observations in samples. *Technometrics*, 11(1): 1–21, 1969.

Manuel Günther, Steve Cruz, Ethan M Rudd, and Terrance E Boult. Toward open-set face recognition. In *Conference on Computer Vision and Pattern Recognition (CVPR) Workshops. IEEE*, 2017.

Simon Hawkins, Hongxing He, Graham Williams, and Rohan Baxter. Outlier detection using replicator neural networks. In *International Conference on Data Warehousing and Knowledge Discovery*, pp. 170–180. Springer, 2002.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9729–9738, 2020.

Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. *arXiv preprint arXiv:1610.02136*, 2016.

Dan Hendrycks, Mantas Mazeika, and Thomas Dietterich. Deep anomaly detection with outlier exposure. In *International Conference on Learning Representations*, 2019a. URL `https://openreview.net/forum?id=HyxCxhRcY7`.

Dan Hendrycks, Mantas Mazeika, Saurav Kadavath, and Dawn Song. Using self-supervised learning can improve model robustness and uncertainty. In *Advances in Neural Information Processing Systems*, pp. 15663–15674, 2019b.

Dan Hendrycks, Mantas Mazeika, Saurav Kadavath, and Dawn Song. Using self-supervised learning can improve model robustness and uncertainty. In *Advances in Neural Information Processing Systems*, pp. 15663–15674, 2019c.

Heinrich Jiang, Been Kim, Melody Guan, and Maya Gupta. To trust or not to trust a classifier. In *Advances in Neural Information Processing Systems*, pp. 5546–5557, 2018.

Prannay Khosla, Piotr Teterwak, Chen Wang, Aaron Sarna, Yonglong Tian, Phillip Isola, Aaron Maschinot, Ce Liu, and Dilip Krishnan. Supervised contrastive learning. *arXiv preprint arXiv:2004.11362*, 2020.

Diederik P. Kingma and Max Welling. Auto-encoding variational bayes. In Yoshua Bengio and Yann LeCun (eds.), *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, 2014. URL `http://arxiv.org/abs/1312.6114`.

Durk P Kingma and Prafulla Dhariwal. Glow: Generative flow with invertible 1x1 convolutions. In *Advances in neural information processing systems*, pp. 10215–10224, 2018.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Olivier Ledoit and Michael Wolf. Honey, i shrunk the sample covariance matrix. *The Journal of Portfolio Management*, 30(4):110–119, 2004.

Kimin Lee, Honglak Lee, Kibok Lee, and Jinwoo Shin. Training confidence-calibrated classifiers for detecting out-of-distribution samples. In *International Conference on Learning Representations*, 2018a.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In *Advances in Neural Information Processing Systems*, pp. 7167–7177, 2018b.

Shiyu Liang, Yixuan Li, and Rayadurgam Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. *arXiv preprint arXiv:1706.02690*, 2017.

Prasanta Chandra Mahalanobis. On the generalized distance in statistics. National Institute of Science of India, 1936.

Iacopo Masi, Yue Wu, Tal Hassner, and Prem Natarajan. Deep face recognition: A survey. In *2018 31st SIBGRAPI conference on graphics, patterns and images (SIBGRAPI)*, pp. 471–478. IEEE, 2018.

Yisroel Mirsky, Tomer Doitshman, Yuval Elovici, and Asaf Shabtai. Kitsune: an ensemble of autoencoders for online network intrusion detection. *arXiv preprint arXiv:1802.09089*, 2018.

Ishan Misra and Laurens van der Maaten. Self-supervised learning of pretext-invariant representations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 6707–6717, 2020.

Sina Mohseni, Mandar Pitale, JBS Yadawa, and Zhangyang Wang. Self-supervised learning for generalizable out-of-distribution detection. In *AAAI*, pp. 5216–5223, 2020.

Eric Nalisnick, Akihiro Matsukawa, Yee Whye Teh, Dilan Gorur, and Balaji Lakshminarayanan. Do deep generative models know what they don't know? In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=H1xwNhCcYm`.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y Ng. Reading digits in natural images with unsupervised feature learning. In *NIPS workshop on deep learning and unsupervised feature learning*, volume 2011, pp. 5, 2011.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Manikandasriram Srinivasan Ramanagopal, Cyrus Anderson, Ram Vasudevan, and Matthew Johnson-Roberson. Failing to learn: autonomously identifying perception failures for self-driving cars. *IEEE Robotics and Automation Letters*, 3(4):3860–3867, 2018.

Jie Ren, Peter J Liu, Emily Fertig, Jasper Snoek, Ryan Poplin, Mark Depristo, Joshua Dillon, and Balaji Lakshminarayanan. Likelihood ratios for out-of-distribution detection. In *Advances in Neural Information Processing Systems*, pp. 14707–14718, 2019.

Lukas Ruff, Robert Vandermeulen, Nico Goernitz, Lucas Deecke, Shoaib Ahmed Siddiqui, Alexander Binder, Emmanuel Müller, and Marius Kloft. Deep one-class classification. In *Proceedings of the 35th International Conference on Machine Learning*, pp. 4393–4402, 2018a. URL http://proceedings.mlr.press/v80/ruff18a.html.

Lukas Ruff, Robert A. Vandermeulen, Nico Görnitz, Lucas Deecke, Shoaib A. Siddiqui, Alexander Binder, Emmanuel Müller, and Marius Kloft. Deep one-class classification. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80, pp. 4393–4402, 2018b.

Tim Salimans, Andrej Karpathy, Xi Chen, and Diederik P Kingma. Pixelcnn++: Improving the pixelcnn with discretized logistic mixture likelihood and other modifications. *arXiv preprint arXiv:1701.05517*, 2017.

Chandramouli Shama Sastry and Sageev Oore. Detecting out-of-distribution examples with in-distribution examples and gram matrices. *arXiv preprint arXiv:1912.12510*, 2019.

Marco Schreyer, Timur Sattarov, Damian Borth, Andreas Dengel, and Bernd Reimer. Detection of anomalies in large scale accounting data using deep autoencoder networks. *arXiv preprint arXiv:1709.05254*, 2017.

C. Stein. Estimation of a covariance matrix. *39th Annual Meeting IMS, Atlanta, GA, 1975*, 1975. URL https://ci.nii.ac.jp/naid/10020185297/en/.

Yonglong Tian, Chen Sun, Ben Poole, Dilip Krishnan, Cordelia Schmid, and Phillip Isola. What makes for good views for contrastive learning. *arXiv preprint arXiv:2005.10243*, 2020.

Apoorv Vyas, Nataraj Jammalamadaka, Xia Zhu, Dipankar Das, Bharat Kaul, and Theodore L Willke. Out-of-distribution detection using an ensemble of self supervised leave-out classifiers. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 550–564, 2018.

Jim Winkens, Rudy Bunel, Abhijit Guha Roy, Robert Stanforth, Vivek Natarajan, Joseph R. Ledsam, Patricia MacWilliams, Pushmeet Kohli, Alan Karthikesalingam, Simon Kohl, taylan. cemgil, S. M. Ali Eslami, and Olaf Ronneberger. Contrastive training for improved out-of-distribution detection. 2020.

Ryota Yoshihashi, Wen Shao, Rei Kawakami, Shaodi You, Makoto Iida, and Takeshi Naemura. Classification-reconstruction learning for open-set recognition. *arXiv preprint arXiv:1812.04246*, 2018.

Ev Zisselman and Aviv Tamar. Deep residual flow for novelty detection. *arXiv preprint arXiv:2001.05419*, 2020.

A   ADDITIONAL DETAILS ON EXPERIMENTAL SETUP

A.1   TRAINING AND EVALUATION SETUP FOR DEEP NEURAL NETWORKS.

We use ResNet-50 architecture for all our major experiments and ResNet-18 for ablation studies. We also provide results with ResNet-34 and ResNet-101 architecture. We use a two-layer fully connected network as the projection header ($h(.)$). To contrast with a large number of negatives, $NT - Xent$ loss requires a much larger batch size compared to the supervised cross-entropy loss function. We train it using a batch size of 512. When evaluating self-supervised models, even when we incorporate labels in SSD, we achieve the best performance when modeling in-distribution features with only a single cluster. However, for supervised training, which refers to the supervised baseline in the paper, we find that increasing the number of clusters helps. For the latter, we report the best of the results obtained from cluster indexes or using true labels of the data. For each dataset, we use the images from the test set, if it exists, as the OOD dataset. For consistent comparison, we re-implement Softmax-probabilities (Hendrycks & Gimpel, 2016), ODIN (Liang et al., 2017), and Mahalanobis detector (Lee et al., 2018b) and evaluate their performance on the same network, trained with supervised training for 500 epochs. We set the perturbation budget to 0.0014 and temperature to 1000 for ODIN, since these are the most successful set of parameters reported in the original paper (Liang et al., 2017). We primarily focus on one-shot and five-shot OOD detection, i.e, set k to 1 or 5. With CIFAR10 as the OOD dataset, it means access to one and five images, respectively, from each class. We create 10 randomly transformed samples from each available OOD image. To avoid any hyperparameter selection, we use the image augmentation technique to be the same as the one used in training. Finally, we use the Ledoit-Wolf (Ledoit & Wolf, 2004) estimator to estimate the covariance.

A.2   PERFORMANCE METRICS FOR OUTLIER DETECTORS

We use the following performance metrics to evaluate the outlier detectors.

- **FPR at TPR=95%** It refers to the False positive rate (= FP / (FP+TN)), when True positive rate (= TP / (TP + FN)) is equal to 95%. Effectively, its goal is to measure what fraction of outliers go undetected when it is desirable to have a True positive rate of 95%.

- **AUROC.** It refers to the area under the receiver operating characteristic curve. We measure it by calculating the area under the curve when we plot TPR against FPR.

- **AUPR.** It refers to the area under the precision-recall curve, where precision = TP / (TP+FP) and recall = TP / (TP+FN). Similar to AUROC, AUPR is also a threshold independent metric.

A.3   DATASETS USED IN THIS WORK

We use the following datasets in this work. Whenever there is a mismatch between the resolution of images in in-distribution and out-of-distribution (OOD) data, we appropriately scale the OOD images with bilinear scaling. When there is an overlap between the classes of the in-distribution and OOD dataset, we remove the common classes from the OOD dataset.

- **CIFAR-10 (Krizhevsky et al., 2009)**. It consists of 50,000 training images and 10,000 test images from 10 different classes. Each image is 32×32 pixels size.

- **CIFAR-100 (Krizhevsky et al., 2009)**. CIFAR-100 also has 50,000 training images and 10,000 test images. However, it has 100 classes which are further organized in 20 sub-classes. Note that its classes aren't identical to the CIFAR-10 dataset, with a slight exception with class "truck" in CIFAR-10 and "pickup truck" in CIFAR-100. However, their classes share multiple similar semantics, making it hard to catch outlier samples from the other dataset.

- **SVHN (Netzer et al., 2011)**. SVHN is a real-world street-view housing number dataset. It has 73257 digits available for training, and 26032 digits for testing. Similar to the CIFAR-10/100 dataset, it also has 32×32 size images.

- **STL-10 (Coates et al., 2011)**. STL-10 has identical classes as the CIFAR-10 dataset but focuses on the unsupervised training task. It has 5,000 training images, 8,000 test images,

and a set of 100,000 unlabeled images. Unlike the previous three datasets, it has 96×96 size images.

- **DTD (Cimpoi et al., 2014)**. Describable Textures Dataset (DTD) is a collection of textural images in the wild. It includes a total of 5,640 images, split equally between 47 categories where the size of images range between 300×300 and 640×640 pixels.

- **ImageNet[1] (Deng et al., 2009)**. ImageNet is a large scale dataset of 1,000 categories with 1.2 Million training images and 50,000 validation images. It has high diversity in both inter- and intra-class images and is known to have strong generalization properties to other datasets.

- **Blobs.** Similar to Hendrycks et al. (2019a), we algorithmically generate these amorphous shapes with definite edges.

- **Gaussian Noise.** We generate images with Gaussian noise using a mean of 0.5 and a standard deviation of 0.25. We clip the pixel value to the valid [0, 1] pixel range.

- **Uniform Noise.** It refers to images where each pixel value is uniformly sampled from the [0, 1] range.

B   ADDITIONAL EXPERIMENTAL RESULTS

B.1   LIMITATIONS OF OUTLIER DETECTORS BASED ON SUPERVISED TRAINING

Existing supervised training based detector assumes that fine-grained data labels are available. What happens to the performance of current detectors if we relax this assumption by assuming that only coarse labels are present. We simulate this setup by combining consecutive classes from the CIFAR-10 dataset into two groups, referred to as CIFAR-2, or five groups referred to as CIFAR-5. We use CIFAR-100 as the out-of-distribution dataset. We find that the performance of existing detectors degrades significantly when only coarse labels are present (Figure 5).

Figure 5: Existing supervised detector requires fine-grained labels. In contrast, SSD can achieve similar performance with only unlabelled data.

Figure 6: Relationship of AU-ROC with clusters depends on which layer we use as feature extractor.

Figure 7: Using extra unla-belled training data can help to further improve the perfor-mance of SSD.

B.2   ON CHOICE OF NUMBER OF CLUSTERS

We find the choice of optimal number of clusters dependent on which layer we extract the features from in a Residual Neural networks. We demonstrate this trend in Figure 6, with CIFAR-10 as in-distribution dataset and CIFAR-100 as out-of-distribution dataset. While for the first three blocks, we find an increase in AUROC with number of clusters, the trend is reversed for the last block (Figure 6). Since last block features achieve highest detection performance, we model in the in-distribution features as a single cluster.

B.3   ABLATION STUDY FOR FEW-SHOT OOD DETECTION

For a few shot OOD detection, we ablate along the number of transformations used for each sample. We choose CIFAR100 as in-distribution and CIFAR-10 as OOD dataset with SSD_k, k set to five and Resnet-18 network. When increasing number of transformations from 1, 5, 10, 20, 50 the AUROC of

---

[1]We refer to the commonly used ILSVRC 2012 release of ImageNet dataset.

detector is 74.3, 75.7, 76.1, 76.3, 76.7. To achieve a balance between performance and computational cost, we use 10 transformations for each sample in our final experiments.

B.4 Performance of SSD improves with amount of unlabeled data

With easy access to unlabeled data, it is compelling to develop detectors that can benefit from the increasing amount of such data. We earlier demonstrated this ability of SSD for the CIFAR-10 dataset in Figure 3. Now we present similar results with the STL-10 dataset. We first train a self-supervised network, and an equivalent supervised network with 5,000 training images from the STL-10 dataset. We refer to these networks by SSD-5k and Sup-5k, respectively. Next, we include additional 10,000 images from the available 100k unlabeled images in the dataset. As we show in Figure 7, SSD is able to achieve large gains in performance with access to the additional unlabeled training data.

B.5 Results with different performance metrics

We provide our experimental results for each component in SSD framework with three different performance metrics in Table 5, 6.

Table 5: Experimental results of SSD detector with multiple metrics with CIFAR-10, CIFAR100, and STL-10 dataset.

In-distribution	OOD	FPR (TPR = 95%) ↓							AUROC ↑							AUPR ↑						
		SSD	Supervised	SSD_k		$SSD+$	SSD_k+		SSD	Superivsed	SSD_k		$SSD+$	SSD_k+		SSD	Supervised	SSD_k		$SSD+$	SSD_k+	
				k=1	k=5		k=1	k=5			k=1	k=5		k=1	k=5			k=1	k=5		k=1	k=5
CIFAR-10	CIFAR-100	50.7	47.4	44.7	39.4	38.5	36.3	34.6	90.6	90.6	91.7	93.0	93.4	93.4	94.0	89.2	89.5	90.5	91.9	92.3	92.5	92.9
	SVHN	2.0	1.6	0.2	1.0	0.2	0.5	1.9	99.6	99.6	99.9	99.7	99.9	99.9	99.6	99.8	99.8	100.0	100.0	99.9	100.0	99.8
	Texture	14.6	12.4	5.1	2.7	7.7	6.4	3.6	97.6	97.8	98.9	99.4	98.5	98.6	99.2	95.6	96.7	98.4	99.0	97.3	98.1	98.9
	Blobs	4.3	0.0	4.4	0.0	0.0	0.0	0.0	98.8	99.9	99.7	100.0	100.0	100.0	100.0	98.4	99.9	99.4	100.0	100.0	100.0	100.0
CIFAR-100	CIFAR-10	89.4	96.4	85.3	69.4	89.5	72.1	65.2	69.6	55.3	74.8	78.3	71.0	78.2	84.0	64.5	51.8	69.3	77.2	65.3	76.2	81.7
	SVHN	20.9	28.4	2.7	4.5	7.9	11.3	11.9	94.9	94.5	99.5	99.1	98.2	97.3	97.4	98.1	97.5	99.8	99.6	99.3	99.1	99.0
	Texture	65.8	2.3	16.4	25.1	68.1	24.3	23.8	82.9	98.8	96.8	94.2	81.2	93.8	94.5	72.9	97.9	95.0	91.9	70.7	91.6	92.2
	Blobs	1.2	95.6	1.1	0.0	3.6	0.0	0.0	98.1	57.3	98.1	100.0	98.8	100.0	100.0	97.8	47.6	97.8	100.0	98.2	100.0	100.0
STL-10	CIFAR-100	29.9	73.2	32.9	32.3	40.0	8.6	14.1	94.8	84.0	90.1	90.0	92.4	98.4	97.8	95.1	82.5	92.6	92.3	93.3	98.7	98.0
	SVHN	6.6	26.2	5.8	2.4	18.6	0.4	0.3	98.7	95.7	98.7	99.4	96.9	99.8	99.9	99.5	97.6	99.5	99.7	98.9	100.0	100.0
	Texture	53.0	69.4	50.0	39.5	51.8	46.2	43.8	85.8	75.5	85.7	84.5	85.8	90.4	91.0	82.6	69.3	84.1	84.3	83.7	87.1	87.7
	Blobs	16.3	88.9	14.6	0.0	67.8	0.1	0.0	96.4	88.6	96.5	99.9	92.9	99.7	99.8	92.1	81.3	92.2	99.9	86.7	99.5	99.7

Table 6: Experimental results of SSD detector with multiple metrics with ImageNet dataset.

In-distribution	OOD	FPR (TPR = 95%) ↓				AUROC ↑				AUPR ↑			
		SSD	Supervised	SSD_k		SSD	Supervised	SSD_k		SSD	Supervised	SSD_k	
				k=1	k=5			k=1	k=5			k=1	k=5
ImageNet	SVHN	1.3	0.6	0.0	0.0	99.4	99.1	100.0	100.0	98.4	96.6	100.0	100.0
	Texture	57.2	23.2	20.1	11.4	85.4	95.4	95.4	97.4	41.7	75.8	78.6	84.2
	Blobs	0.0	0.0	0.0	0.0	98.4	99.5	100.0	100.0	81.1	91.6	100.0	100.0
	Gaussian noise	0.0	0.0	0.0	0.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
	Uniform noise	0.0	0.0	0.0	0.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0