# Do Language Models Reason Across Languages?

## Abstract

Real-world information sources are inherently multilingual, which raises the question *whether* language models can synthesize information across languages. In this paper, we introduce a simple two-hop question answering setting, where answering a question requires making inferences over two documents in different languages. We find that language models are more sensitive to language variation in answer-span documents than in those providing bridging information, despite the equal importance of both documents for answering a question. Under a step-by-step sub-question evaluation, we further show that in up to 33% of multilingual cases, models fail to infer the bridging information in the first step yet still answer the overall question correctly. This indicates that reasoning in language models, especially in multilingual settings, does not follow a faithful step-by-step decomposition. Moreover, language models also struggle to compose intermediate results: in around 18% of cases, they answer both sub-questions correctly but fail to derive the correct final answer. To examine whether explicit decomposition can help, we evaluate a three-stage SUBQ prompting setup that provides the relevant intermediate sub-questions during inference. This improves final two-hop QA accuracy, from 10.1% to 66.5%.

## 1 Introduction

Reasoning is a central aspect of human cognition and refers to the process of drawing new conclusions by combining multiple pieces of evidence through logical inference (Kurtz et al., 1999). Large language models (LLMs) have demonstrated strong reasoning performance across pieces of evidence within the same language, which almost exclusively is English (Liu et al., 2025). However, real-world information is inherently multilingual and therefore distributed across languages. Enhancing multilingual reasoning is thus essential for building globally reliable AI systems. This requires models not only to comprehend information in multiple languages but also to integrate and chain knowledge across them to derive correct answers (Ghosh et al., 2025).

Recent works (Qin et al., 2023; Huang et al., 2023; Chai et al., 2024; Wang et al., 2025) explore multilingual reasoning in non-linguistic domains such as mathematics and coding, which inherently require multi-step reasoning. However, their evaluation is solely based on final performance, e.g., accuracy, which cannot truly capture whether language models perform inference across multiple multilingual sources or instead rely on shortcut heuristics. In this work, we focus on a decomposed two-hop question answering task that requires integrating information across two contexts to answer a question. The simplicity and controlled decomposition of this task enable fine-grained multilingual evaluation, allowing for the assessment of a faithful step-by-step reasoning process.

To this end, we extend a decomposed English-language HotpotQA dataset (Tang et al., 2021) by four diverse and high-resource languages: French, Russian, Arabic, and Chinese.[1] This extension broadens the reasoning evaluation across languages but also bridges the gap between English-centric two-hop reasoning and multilingual NLP. Take Figure 1 as an example. To answer a two-hop question: '*What government position was held by the woman who portrayed Corliss Archer in the film Kiss and Tell?*', it requires two reasoning steps to infer the final answer: First, identifying the bridge entity Shirley Temple as the woman who portrayed the film from an English first-hop document. Second, connecting Shirley Temple with the government position chief of protocol in a French second-hop document. This setup provides a clear testbed to

---

[1]We will release the dataset publicly to support reproducibility and further research.

Figure 1: Example of *multilingual two-hop QA*. In Section 2, we evaluate multilingual two-step reasoning performance with the two-hop question and the corresponding Hop-1 and Hop-2 document. In Section 3, we conduct a sub-question evaluation to disentangle the two-step reasoning mechanism: SubQ1 infers the bridge entity and SubQ2 links the bridge entity to the final answer.

examine whether models perform reasoning across contexts in varying languages and whether they reason in a step-by-step manner, commonly analogous to how humans solve problems via sub-questions.

From a controlled evaluation of multilingual large language models (including Gemma-3, Qwen-3, and Llama-3.1) on this benchmark, we observe a degradation in two-hop QA performance when varying languages for each document (see Section 2). In particular, changing the language of the answer-span (second-hop) documents leads to larger performance drops than changing the language of the bridging (first-hop) documents. This discrepancy raises the question of whether the first step of multilingual reasoning is intrinsically easier than the second, or whether models rely on other mechanisms that bypass faithful reasoning.

Subsequently, we conduct a step-level evaluation on decomposed sub-questions (see Section 3). We observe a relatively high unfaithfulness ratio (up to 33%) in multilingual scenarios where language models correctly answer a two-hop question but fail to answer the first step's sub-question. To further probe how models arrive at the correct answer despite failing to identify bridging information, we conduct a context attribution analysis. The results reveal that the bridging documents still play a critical role in answer generation, with at least one-third of the attribution scores. Moreover, the performance of unfaithful two-hop cases drops sharply when distractors with topically related bridging information are introduced. This shows that language models perform multilingual two-hop reasoning,

but this reasoning does not indicate explicit step-by-step sub-question answering.

On the other hand, we show that faithful step-by-step sub-question answering does not necessarily ensure correct multilingual two-hop reasoning. Following Press et al. (2023), we refer to this phenomenon as compositional failure, and observe up to 18% of cases where the model correctly answers each sub-question but fails to integrate the intermediate information into the final two-hop answer. Next, we examine the impact of presenting explicit reasoning information on resolving this issue. We first show the existing chain-of-thought prompting (Wei et al., 2022), which requests models to "think step-by-step", only partially alleviates compositional failure. With the given decomposed sub-questions, we naturally introduce a three-stage SUBQ prompting method, where each sub-question is explicitly provided to guide the final answer generation. This approach substantially reduces compositional failures, improving accuracy from 10.1% to 66.56%. These results highlight question decomposition as a promising direction for enhancing multilingual multi-step reasoning.

## 2   Multilingual Two-Hop QA

The multilingual two-hop question answering (QA) task requires language models to reason with information from two gold documents in different languages to generate the answer. In this task, the models' inputs are: (i) a two-hop question to answer and (ii) two gold documents. We denote Hop-1 as first-hop documents containing bridge

| Settings | Document Languages | | Query Languages ($L_q$) | | | | | Avg. |
|---|---|---|---|---|---|---|---|---|
| | Hop-1 | Hop-2 | En | Fr | Ru | Ar | Zh | |
| **Monolingual** | $= L_q$ | $= L_q$ | 56.08 | 49.04 | 43.48 | 43.70 | 32.25 | 44.91 |
| **Multilingual** | $\neq L_q$ | $= L_q$ | 55.49 | 49.19 | 43.12 | 42.92 | 35.41 | 45.22 |
| | $= L_q$ | $\neq L_q$ | 48.58 | 45.67 | 40.01 | 40.19 | 36.13 | 42.12 |
| | $\neq L_q$ | $\neq L_q$ | 48.16 | 44.64 | 41.37 | 40.50 | 40.33 | 43.00 |

Table 1: Multilingual two-hop QA performance for Gemma-3-27B-Instruct. We report the F1 token score. $= L_q/\neq L_q$ denotes whether the languages of documents are the same/different from the query language. For non-matching documents, we report the average across the four non-query languages. Full results are in Appendix E.2. Results for additional models, including Llama-3.1 and Qwen-3, are reported in Appendix E.4.

entities and Hop-2 as second-hop documents with target answers. In particular, a bridge entity must first be identified to infer the final answer in the second-hop documents. This task evaluates models' multilingual understanding and reasoning ability to integrate information across different languages.

## 2.1 Experimental Setup

**Datasets.** We evaluate on the extended decomposed HOTPOTQA dataset (Tang et al., 2021), derived from (Yang et al., 2018), which comprises 1,000 English two-hop questions with corresponding decomposed sub-questions; we use SubQ1 and SubQ2 to denote the first and second single-hop sub-questions. To probe multi-hop reasoning at varying depths, we additionally use MUSIQUE (Trivedi et al., 2022), whose dev set contains 2,417 compositional questions spanning 2-, 3-, and 4-hop reasoning chains.

**Dataset Filter.** To ensure models rely on compositional reasoning rather than memorized pre-training knowledge, we filter both datasets as follows. For a $k$-hop question with gold documents $\{d_{\text{hop}_1}, \ldots, d_{\text{hop}_k}\}$, we discard any instance that the experimental models can answer correctly from any *strict* subset of these documents, i.e., any combination omitting at least one hop, including the closed-book setting. Data entry is retained only if every strict-subset query fails, ensuring that the answer requires the full $k$-document chain. After filtering, the evaluation corpus contains 1,318 examples: 809 two-hop, 327 three-hop, and 182 four-hop.

**Dataset Translation.** We automatically translate the filtered English datasets into four high-resource languages with varying language families and written scripts: French (Fr), Russian (Ru), Arabic (Ar), and Chinese (Zh). We use GPT-4o-mini to translate the filtered English multi-hop datasets into four selected target languages. To ensure translation quality, we conducted human evaluations on a subset of translation examples (see Appendix B).

**Models.** We experiment with the Gemma-3-Instruct (Kamath et al., 2025) model of size 27B due to its strong multilingual ability, which supports over 140 languages. To show the generalisability of our findings, we report results from additional multilingual models, including Qwen-3 and Llama-3.1, in Appendix E.4. Following (Modarressi et al., 2025), we adopt greedy decoding for question answering tasks. For the prompts, we put the two-hop question *before* and *after* the provided documents to reduce the effect of query-aware contextualization (Liu et al., 2023). The standard prompt templates are in Appendix D.1.

## 2.2 Results

**Cross-lingual degradation is across reasoning hops.** Table 1 reports multilingual two-hop QA performance under different query languages. Across Gemma-3, Qwen-3, and Llama-3.1, performance decreases when the query language differs from the document language. This degradation is not limited to two-hop reasoning: Figure 9 in Appendix E.1 shows that cross-lingual settings consistently underperform monolingual settings as the number of reasoning hops increases.

**Failure modes vary by query language.** We provide a small-scale error analysis of cross-lingual failures in Appendix E.5, which shows that cross-lingual degradation arises from different failure modes across query languages. English and French queries have more reasoning errors, Arabic and Chinese queries show language-following failures, and

| Correlation | En | | Fr | | Ru | | Ar | | Zh | |
|---|---|---|---|---|---|---|---|---|---|---|
| | Hop-1 | Hop-2 | Hop-1 | Hop-2 | Hop-1 | Hop-2 | Hop-1 | Hop-2 | Hop-1 | Hop-2 |
| **Pearson** | 0.01 | 0.89 | 0.06 | 0.66 | 0.20 | 0.78 | 0.20 | 0.70 | 0.12 | 0.69 |
| **Spearman** | 0.09 | 0.70 | 0.01 | 0.60 | 0.09 | 0.60 | 0.12 | 0.50 | 0.01 | 0.50 |

Table 2: Pearson/Spearman correlations between two-hop QA performance and the linguistic similarity for Gemma-3-27B-Instruct. Overall, linguistic similarity between two-hop questions and Hop-2 documents has a strong correlation with the performance.

Russian queries are more sensitive to the evaluation metric. These results suggest that cross-lingual reasoning degradation reflects multiple failure sources, rather than reasoning errors alone.

**Hop-2 language matters more than Hop-1.** Performance is more sensitive to the language of the answer-span document (Hop-2) than the bridging document (Hop-1). Changing languages in Hop-2 leads to a larger degradation than changing them in Hop-1 (6.84% vs. −0.83% across models). To examine whether this degradation relates to linguistic similarity, we compute Pearson and Spearman correlations between QA accuracy and the linguistic distance between the question and each document.[2] Table 2 shows that final performance has a strong correlation with the linguistic distance between the question and the Hop-2 document.

## 3 Multilingual Reasoning Decomposition

In this section, we disentangle the two-hop reasoning process by two single steps through our translated subset of decomposed sub-questions from HOTPOTQA. This explicit step-wise evaluation facilitates a more fine-grained understanding of multilingual two-hop reasoning behavior.

### 3.1 Setup

We denote SubQ1 as the first-step sub-questions that extract bridge entities from Hop-1 documents, and SubQ2 as the second-step sub-questions that retrieve final answers from Hop-2 documents; see also Figure 1. Based on the decomposed evaluation, we examine whether multilingual multi-hop reasoning follows a faithful step-by-step decomposition. We further identify two distinct failure modes following the definition in previous works, i.e., *unfaithfulness* (Lyu et al., 2023) and *compositional failure* (Press et al., 2023), illustrated in Appendix Figure E.3.

**Unfaithfulness.** Models correctly answer a two-hop question while failing to answer its sub-questions, i.e., SubQ1 or SubQ2. The unfaithfulness ratio is calculated as the percentage of total unfaithful cases over all correctly answered two-hop questions. This ratio reflects whether models are faithful to step-by-step sub-question reasoning.

**Compositional Failure.** Models incorrectly answer two-hop questions while succeeding in both SubQ1 and SubQ2. The composition failure ratio is calculated as the percentage of total composition failure cases over all incorrectly answered two-hop questions. This ratio reflects the limitation of language models' compositional reasoning.

### 3.2 Unfaithfulness

**Overall Results.** Table 3a shows that the model is more likely to be unfaithful to the first-step sub-question for both monolingual and multilingual settings. Consistent with Tang et al. (2021), we show that explicitly identifying the bridge entity is not required for the model to answer two-hop questions correctly in monolingual English settings. Furthermore, we find that multilingual settings yield higher unfaithfulness ratios than monolingual ones. In particular, Arabic and Chinese two-hop questions yield notably high unfaithfulness rates of 25% and 33%, respectively. To further probe how language models are still able to generate correct answers in unfaithful cases, we conduct a context utilization analysis to examine the role of both hop documents, especially for bridging documents. Specifically, we only focus on unfaithful cases that fail at the first sub-question, as they constitute the majority.

### 3.2.1 Context Attribution Analysis

Here, we aim to implicitly analyze how language models use different hop documents to generate the answers. We follow input attribution methods to measure how much each document contributes to generating the answers (Lundberg and Lee, 2017; Covert et al., 2021).

---

[2]Details of the linguistic similarity calculation are provided in Appendix C.

| Setting | Answer Correctness | | | Query Languages | | | | |
|---|---|---|---|---|---|---|---|---|
| | Two-HopQ | SubQ1 | SubQ2 | En | Fr | Ru | Ar | Zh |
| Monolingual | ✓ | ✗ | ✓ | 0.07 | 0.19 | 0.12 | 0.10 | 0.16 |
| | ✓ | ✓ | ✗ | 0.02 | 0.00 | 0.00 | 0.05 | 0.04 |
| | ✓ | ✗ | ✗ | 0.03 | 0.00 | 0.02 | 0.00 | 0.00 |
| Multilingual | ✓ | ✗ | ✓ | 0.12 | 0.23 | 0.15 | 0.25 | 0.33 |
| | ✓ | ✓ | ✗ | 0.03 | 0.03 | 0.03 | 0.05 | 0.04 |
| | ✓ | ✗ | ✗ | 0.01 | 0.00 | 0.03 | 0.03 | 0.02 |

(a) Unfaithfulness Ratio

| Setting | Two-HopQ | SubQ1 | SubQ2 | En | Fr | Ru | Ar | Zh |
|---|---|---|---|---|---|---|---|---|
| Monolingual | ✗ | ✓ | ✓ | 0.14 | 0.16 | 0.03 | 0.17 | 0.18 |
| Multilingual | ✗ | ✓ | ✓ | 0.11 | 0.10 | 0.05 | 0.10 | 0.08 |

(b) Compositional Failure Ratio

Table 3: The decomposed sub-questions evaluation for Gemma-3-27B-Instruct. We report the average ratio for multilingual settings. The full results are shown in Appendix E.2.

**Setup.** We use the input-erasure attribution method (Li et al., 2016) to measure the contribution of each hop's document on the correct answer generation. Input erasure quantifies the contribution of an input component (typically a token) by measuring the change in the model's probability on the ground truth when that component is removed. In our experiments, we compute token-level attributions with respect to producing the correct answer. A document's attribution is obtained by summing the contributions of its tokens, after which we calculate its percentage attribution relative to the combined attribution of the two documents, i.e., Hop-1 and Hop-2. Finally, we report the average percentage attribution for each document across the entire data. To ensure a fair comparison, we examine the context attribution scores in unfaithful cases on the first sub-question against fully faithful ones[3] to show shifts in context attribution.

**Results.** Figure 2 presents Hop-1 attribution scores for faithful and unfaithful cases in English two-hop questions. In general, we surprisingly notice that most unfaithful cases exhibit relatively higher Hop-1 attribution scores compared to faithful cases. Although the model fails to explicitly infer bridge entities from Hop-1 documents for unfaithful cases, Hop-1 documents still implicitly contribute to the correct two-hop target answer generation. The relatively high Hop-1 attribution scores for unfaithful cases indicate the model relies on a more nuanced intrinsic reasoning mechanism that

---
[3]Two-hop, SubQ1, and SubQ2 all correct

Figure 2: Context attribution scores for faithful and unfaithful cases. The two-hop query is in English, and Lang1-Lang2 (e.g., EN-ZH) indicates the languages of Hop-1 and Hop-2 documents.

extends beyond what can be revealed through explicit step-level evaluation. Moreover, we notice that multilingual Hop-1 documents have higher attributions than English ones for both cases. Taken together with the observation in Section 3.2 that multilingual settings exhibit higher unfaithfulness, this suggests that while the models attend to the multilingual Hop-1 documents, they struggle to answer the sub-question on them correctly.

### 3.2.2 Context Distractor Analysis

The context attribution analysis shows the importance of Hop-1 documents on intrinsic multilingual reasoning for unfaithful cases. To further investigate whether the reliance on Hop-1 documents reflects robust reasoning rather than shortcutting

Figure 3: The impact of inserting relevant and irrelevant distractors between Hop-1 and Hop-2 documents. A distance of $d$ corresponds to $(|d| - 1)$ distractors between the two hops. Positive $d$ means Hop-1 precedes Hop-2, while a negative sign means the reverse. We report the average $F1$ token scores for every unfaithful multilingual case for each query language.

spurious cues, we perform a controlled context perturbation analysis on unfaithful cases inspired by prior works by distractors (Hengle et al., 2025) and context orders (Yu et al., 2025).

**Setup.** We gradually insert an increasing number of distractor documents between Hop-1 and Hop-2 documents. The language of the distractors is the same as the two-hop question. We use distance $d$ to denote the position differences between Hop-1 and Hop-2, and it corresponds to $(|d| - 1)$ distractors between the two hops. The sign of $d$ specifies their order: a positive value means Hop-1 precedes Hop-2, while a negative value means the reverse. In particular, we control distractor relevance with the bridging Hop-1 documents. Relevant distractors contain topics similar to the original bridging Hop-1 documents from the dataset, whereas irrelevant distractors are randomly sampled from unrelated training examples.

**Results.** Figure 3 shows that inserting distractors between Hop-1 and Hop-2 degrades multilingual two-hop reasoning, consistent with monolingual findings by Modarressi et al. (2025). Topic-relevant distractors result in larger drops than irrelevant ones, underscoring the difficulty of models to discriminate true bridging evidence from semantically proximate noise and highlighting the central role of Hop-1 in two-step reasoning. Moreover, changing the document order further degrades performance: presenting the Hop-1 and Hop-2 documents in reverse order is consistently worse than the original sequence, echoing premise-order effects in LLMs (Chen et al., 2024; Yu et al., 2025). This indicates

a positional sensitivity of intermediate bridge information, suggesting that the model relies on order-dependent reasoning rather than fully order-robust multi-hop composition.

### 3.3 Compositional Failure

The previous section 3.2 analyzes the unfaithfulness cases and shows that correct intrinsic reasoning does not necessarily follow faithful step-by-step sub-question answering. Here, we examine the second failure mode, i.e., compositional failure, where the model answers sub-questions correctly but fails to answer the overall two-hop question. Table 3b shows composition failure rates up to 18%, showing that solving both sub-questions does not guarantee correct two-hop composition. Motivated by evidence that prompting with explicit intermediate reasoning can improve performance (Wei et al., 2022), we aim to examine whether guiding language models with (i) self-generated chain-of-thoughts or (ii) decomposed step-by-step sub-questions, can reduce composition failure.

#### 3.3.1 Step-by-Step Prompting

The setup details and results are shown below.

**Zero-shot CoT.** Following (Wei et al., 2022), we instruct the model to "*Think Step-by-Step*" and generate its own reasoning chains for answering two-hop questions. Prompt templates are in Appendix Figure 7. The language of zero-shot instruction is aligned with the two-hop question, and we do not control the reasoning languages here.

> **SubQ Prompting**
>
> **{Instruction}**
> **Question:** {Two-Hop Question}
> **Articles:** {Hop-1 Document} {Hop-2 Document}
> Based on your answers for the decomposed sub-questions to answer the two-hop question:
>
> **SubQ1**: {Sub-question for bridge entity}
> **Prediction:** {Bridge entity from step-1 output}
>
> **SubQ2**: {Sub-question for target answer with bridge entity}
> **Prediction:** {Target answer from step-2 output}
> **Answer:**

Figure 4: Three-step of SubQ Prompting. The first and second step prompt templates are in Appendix Figure 8.

**SUBQ Prompt.** We introduce a three-stage, step-by-step prompting technique with decomposed sub-questions. As illustrated in Figure 4, prompting consists of three steps: First step, prompting the model to answer the SubQ1 question about the bridge entity; Second step, using the first step output for the bridge entity inserted with SubQ2 to ask for the target answer; Third step, presenting both sub-questions and the previous steps' outputs together to ask for the final two-hop answer. For a fair comparison, we also use the ground-truth answers for each step's sub-question to guide reasoning.

**Results.** Figure 5 shows the average multilingual two-hop QA performance for each query language with different prompting techniques. First, SUBQ prompting yields substantial gains over zero-shot CoT on both the compositional failure cases and the full evaluation set. These improvements suggest that explicitly decomposing the query into sub-questions helps the model integrate information step-wise. One plausible explanation for the weaker zero-shot CoT results is that the model uses its own internal representations to generate explanations, which might diverge from the task's true decomposition. This, in turn, leads to errors in the reasoning process.

Second, SUBQ prompting shows a larger performance gap between model-generated predictions and ground-truth answers for sub-questions on the full evaluation set compared to the compositional failure cases. This is expected, as the model predicts sub-questions correctly in compositional failure cases, resulting in performance close to that of the ground truth. For the full set, despite potential errors in predicted answers of sub-questions,

SUBQ prompting still leads to substantial performance gains across all query languages. Overall, these results highlight the effectiveness of question decomposition in enhancing LLM performance on multilingual multi-hop reasoning tasks.

## 4 Related Work

In this section, we review prior work relevant to our study, focusing on multilingual capability and reasoning capability.

**Multilingual Reasoning.** This line of research has examined multilingual reasoning in mathematical tasks (Shi et al., 2023; Qin et al., 2023; Chen et al., 2023; Ghosh et al., 2025). Although mathematical problems also probe multi-step reasoning, these studies primarily focus on reasoning over numerical computation rather than general linguistic information. Another line of work has often noted linguistic benchmarks such as XCOPA (Ponti et al., 2020) or translated versions of MMLU (Hendrycks et al., 2021) as multilingual reasoning (Chua et al., 2024). However, XCOPA typically involves one-step inferences, and MMLU lacks explicit control over reasoning steps. In contrast, our work introduces a controlled setting for multilingual multi-hop question answering, where we disentangle each step of reasoning across languages to directly assess whether models perform genuine multilingual linguistic reasoning.

**Intrinsic Reasoning.** Intrinsic reasoning investigates whether LLMs are capable of reasoning without explicit prompting (Wang and Zhou, 2024). For instance, Yang et al. (2024) reveals latent two-hop reasoning paths by constructing questions that require retrieving factual bridging information from

Figure 5: F1 token accuracy for multilingual two-hop QA for different prompting strategies, evaluated on composition failure cases and the full dataset. Red dashed lines above the SubQ Prompt bars show the performance when using ground-truth answers for sub-questions.

pre-trained knowledge. Similarly, Guo et al. (2025) trains a three-layer transformer model from scratch to examine how two-hop reasoning occurs by analyzing attention logits for bridge and target entities. In contrast, our work evaluates reasoning explicitly through decomposed sub-questions, allowing us to assess whether multilingual reasoning aligns with a step-by-step sub-question answering process.

**Failure Modes of Reasoning.** This work is also related to several modes of reasoning failure in LLMs, including unfaithfulness (Lyu et al., 2023; Arcuschin et al., 2025), premise order effects (Chen et al., 2024; Yu et al., 2025), distractibility (Guo et al., 2025; Qi et al., 2025), and the limited capacity for long-context reasoning (Liu et al., 2023; Modarressi et al., 2025; Hengle et al., 2025). Specifically, Lyu et al. (2023) shows that chain-of-thought prompting on mathematical tasks often produces answers that do not faithfully follow the intermediate reasoning steps. Our work extends to multi-hop reasoning by showing the unfaithful outputs for decomposed sub-questions. Modarressi et al. (2025) reveals that increasing the context length of the two-hop associated reasoning QA task leads to performance degradation, while we show that this difficulty is further amplified when long-context reasoning is combined with multilinguality, exposing another limitation of current LLMs.

**Effectiveness of Reasoning Decomposition.** Reasoning decomposition has been widely adopted in prompting techniques across various downstream tasks. For example, chain-of-thought prompting decomposes mathematical problems into intermediate steps, encouraging models to follow a step-by-step reasoning strategy (Wei et al.,

2022). In machine translation, Briakou et al. (2024); He et al. (2024) decompose the task into multiple stages, showing that multi-turn refinements can improve translation quality. In our work, we explore multi-hop question decomposition. While the decomposed sub-questions need to be additionally acquired, they provide a potential way of enhancing reasoning across languages.

## 5 Conclusion

In this paper, we introduce a controlled setting for multilingual two-hop reasoning to broaden multilingual evaluation. Building on this task, we present a comprehensive analysis that exposes the limitations of current strong multilingual language models in two-step reasoning when information is distributed across languages. Specifically, we find that language models are more sensitive to cross-lingual variation in answer-span documents than in bridging documents, despite both being equally essential for deriving the final answer. Through both explicit and implicit analyses, we show models rely on more nuanced intrinsic reasoning mechanisms that extend beyond what can be revealed by explicit step-by-step evaluation. On the other hand, this work demonstrates the benefits of explicit step-by-step prompting with structured sub-questions in multilingual multi-hop tasks, particularly for mitigating compositional failures. Although the model is capable of reasoning without predefined structures, our findings show that such guidance enhances its robustness. These insights open promising directions for future work on incorporating reasoning decomposition into both training objectives and prompting strategies to improve multilingual multi-hop reasoning.

## Limitations

We acknowledge several limitations in our work. First, this paper primarily focuses on analyzing how language models reason across languages. Although we propose a new method, SUBQ, our main objective is to examine whether LLMs benefit from structured, human-like step-by-step reasoning, rather than to compete with existing methods for overall effectiveness. Second, our translated dataset focuses on four high-resource languages and does not include low-resource languages. This design choice aims to mitigate the impact of training data scarcity on models' cross-lingual reasoning performance. Although these four high-resource languages still have less pre-training data compared to English, we believe they provide a sufficiently controlled setting to analyze cross-lingual reasoning without the extreme data imbalance in low-resource languages.

## References

Iv'an Arcuschin, Jett Janiak, Robert Krzyzanowski, Senthooran Rajamanoharan, Neel Nanda, and Arthur Conmy. 2025. Chain-of-thought reasoning in the wild is not always faithful. *ArXiv*, abs/2503.08679.

Eleftheria Briakou, Jiaming Luo, Colin Cherry, and Markus Freitag. 2024. Translating step-by-step: Decomposing the translation process for improved translation quality of long-form texts. In *Proceedings of the Ninth Conference on Machine Translation*, pages 1301–1317, Miami, Florida, USA. Association for Computational Linguistics.

Linzheng Chai, Jian Yang, Tao Sun, Hongcheng Guo, Jiaheng Liu, Bing Wang, Xiannian Liang, Jiaqi Bai, Tongliang Li, Qiyao Peng, and Zhoujun Li. 2024. xcot: Cross-lingual instruction tuning for cross-lingual chain-of-thought reasoning. In *AAAI Conference on Artificial Intelligence*.

Nuo Chen, Zinan Zheng, Ning Wu, Linjun Shou, Ming Gong, Yangqiu Song, Dongmei Zhang, and Jia Li. 2023. Breaking language barriers in multilingual mathematical reasoning: Insights and observations. *Preprint*, arXiv:2310.20246.

Xinyun Chen, Ryan A. Chi, Xuezhi Wang, and Denny Zhou. 2024. Premise order matters in reasoning with large language models. *ArXiv*, abs/2402.08939.

Lynn Chua, Badih Ghazi, Yangsibo Huang, Pritish Kamath, Ravi Kumar, Pasin Manurangsi, Amer Sinha, Chulin Xie, and Chiyuan Zhang. 2024. Crosslingual capabilities and knowledge barriers in multilingual large language models. *ArXiv*, abs/2406.16135.

Ian Covert, Scott M. Lundberg, and Su-In Lee. 2021. Explaining by removing: A unified framework for model explanation. *J. Mach. Learn. Res.*, 22:209:1–209:90.

Akash Ghosh, Debayan Datta, Sriparna Saha, and Chirag Agarwal. 2025. The multilingual mind : A survey of multilingual reasoning in language models. *ArXiv*, abs/2502.09457.

Tianyu Guo, Hanlin Zhu, Ruiqi Zhang, Jiantao Jiao, Song Mei, Michael I. Jordan, and Stuart Russell. 2025. How do llms perform two-hop reasoning in context? *ArXiv*, abs/2502.13913.

Zhiwei He, Tian Liang, Wenxiang Jiao, Zhuosheng Zhang, Yujiu Yang, Rui Wang, Zhaopeng Tu, Shuming Shi, and Xing Wang. 2024. Exploring human-like translation strategy with large language models. *Transactions of the Association for Computational Linguistics*, 12:229–246.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021. Measuring massive multitask language understanding. In *International Conference on Learning Representations*.

Amey Hengle, Prasoon Bajpai, Soham Dan, and Tanmoy Chakraborty. 2025. Multilingual needle in a haystack: Investigating long-context behavior of multilingual large language models. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 5165–5180, Albuquerque, New Mexico. Association for Computational Linguistics.

Haoyang Huang, Tianyi Tang, Dongdong Zhang, Xin Zhao, Ting Song, Yan Xia, and Furu Wei. 2023. Not all languages are created equal in LLMs: Improving multilingual capability by cross-lingual-thought prompting. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 12365–12394, Singapore. Association for Computational Linguistics.

Gemma Team Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ram'e, Morgane Rivière, Louis Rouillard, Thomas Mesnard, Geoffrey Cideron, Jean-Bastien Grill, Sabela Ramos, Edouard Yvinec, Michelle Casbon, Etienne Pot, Ivo Penchev, Gael Liu, and 191 others. 2025. Gemma 3 technical report. *ArXiv*, abs/2503.19786.

Kenneth J. Kurtz, Dedre Gentner, and Virginia Gunn. 1999. Chapter 4 - reasoning1. In Benjamin Martin Bly and David E. Rumelhart, editors, *Cognitive Science*, pages 145–200. Academic Press, San Diego.

Jiwei Li, Will Monroe, and Dan Jurafsky. 2016. Understanding neural networks through representation erasure. *CoRR*, abs/1612.08220.

Hanmeng Liu, Zhizhang Fu, Mengru Ding, Ruoxi Ning, Chaoli Zhang, Xiaozhang Liu, and Yue Zhang. 2025. Logical reasoning in large language models: A survey. *Preprint*, arXiv:2502.09100.

Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. 2023. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12:157–173.

Scott M. Lundberg and Su-In Lee. 2017. A unified approach to interpreting model predictions. In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pages 4765–4774.

Qing Lyu, Shreya Havaldar, Adam Stein, Li Zhang, Delip Rao, Eric Wong, Marianna Apidianaki, and Chris Callison-Burch. 2023. Faithful chain-of-thought reasoning. In *Proceedings of the 13th International Joint Conference on Natural Language Processing and the 3rd Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 305–329, Nusa Dua, Bali. Association for Computational Linguistics.

Ali Modarressi, Hanieh Deilamsalehy, Franck Dernoncourt, Trung Bui, Ryan A. Rossi, Seunghyun Yoon, and Hinrich Schütze. 2025. Nolima: Long-context evaluation beyond literal matching. In *Forty-second International Conference on Machine Learning*.

Edoardo M. Ponti, Goran Glavaš, Olga Majewska, Qianchu Liu, Ivan Vulić, and Anna Korhonen. 2020. XCOPA: A multilingual dataset for causal commonsense reasoning. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.

Ofir Press, Muru Zhang, Sewon Min, Ludwig Schmidt, Noah Smith, and Mike Lewis. 2023. Measuring and narrowing the compositionality gap in language models. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 5687–5711, Singapore. Association for Computational Linguistics.

Jirui Qi, Raquel Fern'andez, and Arianna Bisazza. 2025. On the consistency of multilingual context utilization in retrieval-augmented generation. *ArXiv*, abs/2504.00597.

Libo Qin, Qiguang Chen, Fuxuan Wei, Shijue Huang, and Wanxiang Che. 2023. Cross-lingual prompting: Improving zero-shot chain-of-thought reasoning across languages. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 2695–2709, Singapore. Association for Computational Linguistics.

Ricardo Rei, Craig Stewart, Ana C Farinha, and Alon Lavie. 2020. COMET: A neural framework for MT evaluation. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 2685–2702, Online. Association for Computational Linguistics.

Freda Shi, Mirac Suzgun, Markus Freitag, Xuezhi Wang, Suraj Srivats, Soroush Vosoughi, Hyung Won Chung, Yi Tay, Sebastian Ruder, Denny Zhou, Dipanjan Das, and Jason Wei. 2023. Language models are multilingual chain-of-thought reasoners. In *The Eleventh International Conference on Learning Representations*.

Yixuan Tang, Hwee Tou Ng, and Anthony Tung. 2021. Do multi-hop question answering systems know how to answer the single-hop sub-questions? In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pages 3244–3249, Online. Association for Computational Linguistics.

Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. 2022. MuSiQue: Multihop questions via single-hop question composition. *Transactions of the Association for Computational Linguistics*, 10:539–554.

Qihan Wang, Shidong Pan, Tal Linzen, and Emily Black. 2025. Multilingual prompting for improving llm generation diversity. *ArXiv*, abs/2505.15229.

Xuezhi Wang and Denny Zhou. 2024. Chain-of-thought reasoning without prompting. *ArXiv*, abs/2402.10200.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Ed H. Chi, F. Xia, Quoc Le, and Denny Zhou. 2022. Chain of thought prompting elicits reasoning in large language models. *ArXiv*, abs/2201.11903.

Sohee Yang, Elena Gribovskaya, Nora Kassner, Mor Geva, and Sebastian Riedel. 2024. Do large language models latently perform multi-hop reasoning? In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 10210–10229, Bangkok, Thailand. Association for Computational Linguistics.

Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. 2018. HotpotQA: A dataset for diverse, explainable multi-hop question answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 2369–2380, Brussels, Belgium. Association for Computational Linguistics.

Sangwon Yu, Ik-hwan Kim, Jongyoon Song, Saehyung Lee, Junsung Park, and Sungroh Yoon. 2025. Unleashing multi-hop reasoning potential in large language models through repetition of misordered context. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 6435–6455, Albuquerque, New Mexico. Association for Computational Linguistics.

## A  Appendix

## A  Use of Large Language Models

We use large language models (LLMs) in two limited ways. First, we use GPT-4o-mini to translate the dataset into the target languages. Second, we use ChatGPT only for grammar-level polishing of the manuscript. We do not use LLMs for research ideation, experimental design, analysis, or generating substantive scientific content.

## B  Translation Quality Evaluation

We evaluate translation quality using both automatic and human evaluation. For automatic evaluation, we report reference-free COMET-22[4] scores (Rei et al., 2020). For human evaluation, we randomly sample 20% of the translated dataset for each language. Native speakers of French, Chinese, Arabic, and Russian rate each translation using the four-point scale below.

- **3**: The translation preserves the full meaning of the English source and contains no grammatical errors.

- **2**: The translation preserves most of the meaning of the English source, with only minor grammatical errors.

- **1**: The translation preserves only part of the source meaning and may contain fluency or grammatical issues.

- **0**: The translation preserves little or none of the source meaning and is difficult to understand.

## C  Linguistic Similarity Calculation

We compute linguistic similarity using subword vocabulary overlap on the NTREX multi-parallel corpus[5], following Qi et al. (2025). NTREX covers 128 languages and provides parallel text for estimating vocabulary overlap across languages. For two languages $l_1$ and $l_2$, we define the overlap score as:

$$\text{Overlap}(l_1, l_2) = \frac{|V_1 \cap V_2|}{|V_1 \cup V_2|}, \qquad (1)$$

where $V_1$ and $V_2$ denote the subword vocabularies induced from languages $l_1$ and $l_2$, respectively.

[4]https://huggingface.co/Unbabel/wmt22-cometkiwi-da

[5]https://github.com/MicrosoftTranslator/NTREX

## D  Prompt Templates

### D.1  Default Prompting

Figure 6 shows the default prompt templates used for monolingual and cross-lingual two-hop QA. For all prompts, the instruction language matches the query language. Native speakers of each target language, who are also proficient in English, translate the instructions.

### D.2  Reasoning Prompting

Figures 7 and 8 show the prompting variants used in Section 3.3.1. Zero-shot CoT asks the model to generate its own reasoning chain, while SUBQ prompting explicitly decomposes the task into intermediate sub-questions.

## E  Additional Experimental Results

### E.1  Impact of Reasoning Depth

We evaluate how reasoning depth affects Gemma-3-27B performance in Figure 9. We report results for English queries under monolingual and cross-lingual evidence settings. The cross-lingual score is computed by averaging over settings in which the evidence documents are written in languages different from the query language.

### E.2  Full Multilingual Two-hop QA Results

Figure 10 presents the full multilingual two-hop QA results for Gemma-3-27B-Instruct across five query languages: English, French, Russian, Arabic, and Chinese. Each heatmap varies the language of the Hop-1 and Hop-2 documents while holding the query language fixed.

### E.3  Failure Mode Examples

Figure 11 illustrates two failure modes observed in Gemma-3-27B-Instruct: unfaithfulness and composition failure. In unfaithful reasoning, the model produces the correct final two-hop answer despite failing the intermediate bridge step. In composition failure, the model answers both decomposed sub-questions correctly but fails to compose them into the correct final answer.

### E.4  Additional Model Results

Tables 8 and 9 report additional results for Qwen-3-8B and Llama-3.1-8B-Instruct.

### E.5  Error Analysis

To understand how cross-lingual multi-hop reasoning fails, we conduct a qualitative error analysis on

| Metric | French (Fr) | Russian (Ru) | Chinese (Zh) | Arabic (Ar) |
|--------|-------------|--------------|--------------|-------------|
| COMET-22 | 86.14 | 83.42 | 82.89 | 80.43 |
| Human | 2.60 | 2.40 | 2.50 | 2.60 |

Table 4: Translation quality of the multilingual two-hop QA dataset. We report reference-free COMET-22 scores and average human ratings on a 0–3 scale. Both automatic and human evaluations indicate that the translations largely preserve the meaning of the English source questions and documents.

Gemma-3-27B-Instruct. We sample 50 predictions per query language for (i) each single-hop sub-question and (ii) the composed two-hop question—750 predictions in total ($50 \times 5 \times 3$)—and classify each prediction into one of four mutually exclusive categories by Claude-Opus-4.6:

- **Correct (C):** F1=1.0 and exact-match true with golden answers.

- **Wrong Language (WL):** the prediction is fluent and (sometimes) factually correct, but its script or language does not match the query language. We treat this as an instruction-following failure rather than a reasoning failure.

- **Factual Failure (FF):** the prediction is in the correct language but factually incorrect, or the model declines to answer. This captures genuine reasoning or retrieval errors.

- **Imprecise Answer (IA):** The model retrieves the correct information but its surface form does not match the gold span.

Tables 5, 6 and 7 report the category distribution for each query language. Across the three settings, three qualitatively different failure modes dominate in different languages.

**Instruction-following Failure (Arabic, Chinese)** For Arabic and Chinese queries, Wrong Language accounts for 26–36% of predictions across all three tasks, while Factual Failure stays at or below 4% for Arabic and reaches 14–22% for Chinese. The model retrieves the right facts but answers in a high-resource script (i.e., English), suggesting that the cross-lingual penalty in these languages is driven by instruction following rather than reasoning.

**Reasoning deficit (English, French).** For English and French, WL drops to 4–10% while FF rises sharply between the single-hop and two-hop settings (12→30% for English; 12→38% for French). The model has no trouble producing output in the target language but increasingly fails to

chain the two hops together, indicating that the cross-lingual penalty in higher-resource European languages is a multi-hop reasoning bottleneck.

**Metric sensitivity (Russian).** For Russian, IA dominates (70–84% across the three tables) while FF remains near 0%. Manual inspection shows that the model typically returns the correct entity in an inflected form that fails exact-match evaluation. Russian performance is underestimated by token-level metrics; this is a property of the metric, not of the model's underlying capability.

| Language | C% | WL% | FF% | IA% |
|----------|------|------|------|------|
| Arabic | 14.0 | 34.0 | 0.0 | 52.0 |
| Chinese | 20.0 | 36.0 | 14.0 | 30.0 |
| English | 50.0 | 4.0 | 12.0 | 34.0 |
| French | 38.0 | 10.0 | 12.0 | 40.0 |
| Russian | 20.0 | 10.0 | 0.0 | 70.0 |
| **All** | **28.4** | **18.8** | **7.6** | **45.2** |

Table 5: Error distribution on Sub-Question 1 ($N$=50 per language).

| Language | C% | WL% | FF% | IA% |
|----------|------|------|------|------|
| Arabic | 10.0 | 26.0 | 0.0 | 64.0 |
| Chinese | 12.0 | 24.0 | 22.0 | 42.0 |
| English | 28.0 | 4.0 | 26.0 | 42.0 |
| French | 18.0 | 4.0 | 24.0 | 54.0 |
| Russian | 4.0 | 8.0 | 4.0 | 84.0 |
| **All** | **14.4** | **13.2** | **15.2** | **57.2** |

Table 6: Error distribution on Sub-Question 2 ($N$=50 per language).

| Language | C% | WL% | FF% | IA% |
|----------|------|------|------|------|
| Arabic | 10.0 | 30.0 | 4.0 | 56.0 |
| Chinese | 18.0 | 26.0 | 20.0 | 36.0 |
| English | 20.0 | 4.0 | 30.0 | 46.0 |
| French | 6.0 | 4.0 | 38.0 | 52.0 |
| Russian | 6.0 | 8.0 | 4.0 | 82.0 |
| **All** | **12.0** | **14.4** | **19.2** | **54.4** |

Table 7: Error distribution on the composed two-hop question ($N$=50 per language).

---
**Multilingual Two-Hop Prompting**
---

You are given an article and a question. Answer the question based on the given article as concisely as you can, using a single phrase or sentence if possible. Do not provide any explanation.

Question: What government position was held by the woman who portrayed Corliss Archer in the film Kiss and Tell?

Article:
Hop-1 Doc: Kiss and Tell is a 1945 American comedy film starring then 17-year-old Shirley Temple as Corliss Archer….
Hop-2 Doc: Shirley Temple Black was an American actress….She was named United States ambassador to Ghana and to Czechoslovakia and also served as Chief of Protocol of the United States.

Question: What government position was held by the woman who portrayed Corliss Archer in the film Kiss and Tell?

Answer:

(a) Monolingual setting: English query, English Hop-1 document, and English Hop-2 document.

---
**Multilingual Two-Hop Prompting**
---

您将收到一篇文章和一个问题。请根据给定的文章尽可能简洁地回答问题，尽可能使用一个短语或句子。请勿提供任何解释。

问题：在电影《吻与告白》中饰演科尔利斯·阿彻的女性担任了什么政府职位？

文章：
Hop-1 Doc: Kiss and Tell est une comédie américaine de 1945 mettant en vedette Shirley Temple…
Hop-2 Doc:وكانت  شيرلي تيمبل بلاك (23 أبريل 1928 - 10 فبراير 2014) كانت ممثلة أمريكية، راقصة، مغنية، سيدة أعمال،ودبلوماسية
الرقم واحد في شباك التذاكر في هوليوود كممثلة أطفال من 1935 إلى 1938.
كبالغة، تم تعيينها سفيرة الولايات المتحدة لدى غانا وتشيكوسلوفاكيا وكذلك خدمت كرئيسة للبروتوكول في الولايات المتحدة.

问题：在电影《吻与告白》中饰演科尔利斯·阿彻的女性担任了什么政府职位？

答案：

(b) Cross-lingual setting: Chinese query, French Hop-1 document, and Arabic Hop-2 document.

Figure 6: Default multilingual two-hop QA prompt templates. The labels Hop-1 Doc and Hop-2 Doc are shown only for illustration and are not included in the actual prompt.

**Zero-shot CoT**

You are given an article and a question. Think step-by-step and then give a final concise answer.

Question: {TwoHopQ}
Article:{Hop-1}{Hop-2}
Question:{TwoHopQ}

Reasoning:

Answer:

(a) English two-hop question.

**Zero-shot CoT**

你将获得一篇文章和一个问题。请逐步思考，然后给出最终的简洁答案。

问题：{TwoHopQ}
文章：{Hop-1}{Hop-2}
问题：{TwoHopQ}

推理：

答案：

(b) Chinese two-hop question.

Figure 7: Zero-shot CoT prompt templates. We append "think step-by-step" to encourage the model to generate an intermediate reasoning chain before answering.

**Step 1 CoT**

You are given an article and a question. Answer the question based on the given article as concisely as you can, using a single phrase or sentence if possible. Do not provide any explanation.

**Question**: {Sub-question for bridge entity}
**Answer**:

**Step 2 CoT**

You are given an article and a question. Answer the question based on the given article as concisely as you can, using a single phrase or sentence if possible. Do not provide any explanation.

**Question**: {Sub-question for target answer with Step 1's predicted bridge entity}
**Answer**:

Figure 8: The first two stages of SUBQ prompting. The first stage answers the first sub-question to identify the bridge entity. The second stage uses the predicted bridge entity to answer the second sub-question. The final stage, shown in Figure 4 in the main text, combines both intermediate steps to generate the final two-hop answer.

Figure 9: Gemma-3-27B performance under monolingual and cross-lingual settings as the number of reasoning hops increases. Cross-lingual evidence consistently underperforms monolingual evidence, and the performance gap persists as reasoning depth increases.

Figure 10: Full multilingual two-hop QA performance for Gemma-3-27B-Instruct across query languages. Each panel fixes the query language and varies the languages of the Hop-1 and Hop-2 evidence documents.

**Two-hopQ:** Lou Cutell 出现在 CBS 情景喜剧第 九季第三集，这一集在总体上是第几集？
**Model Prediction:** 187 (**correct**)
**Ground-Truth:** 187

**Two-hopQ:** Katherine Ann Dettwyler wasn't rehired after she commented on the death of the student who was arrested in North Korea in what month and year?
**Model Prediction:** June 2017 (**wrong**)
**Ground-Truth:** January 2016

**SubQ1:** Lou Cutell 出现在哪一集？
**Model Prediction:** 螺旋形杰瑞 (**wrong**)
**Ground-Truth:** 最后一次在纽约

**SubQ2:** 最后一次在纽约是总体的第几集？
**Model Prediction:** 187 (**correct**)
**Ground-Truth:** 187

**SubQ1:** Katherine Ann Dettwyler wasn't rehired after she commented on the death of which student?
**Model Prediction:** Otto Warmbier (**correct**)
**Ground-Truth:** Otto Warmbier

**SubQ2:** Otto Warmbier was arrested in North Korea in what month and year?
**Model Prediction:** January 2016 (**correct**)
**Ground-Truth:** January 2016

Figure 11: Examples of two reasoning failure modes in Gemma-3-27B-Instruct. **Left**: unfaithfulness, where the model reaches the correct final answer despite an incorrect intermediate step. **Right**: composition failure, where the model answers both sub-questions correctly but fails to produce the correct final two-hop answer.

| Setting | Document Languages | | Query Languages ($L_q$) | | | | | Avg. |
|---|---|---|---|---|---|---|---|---|
| | Hop-1 | Hop-2 | En | Fr | Ru | Ar | Zh | |
| **Monolingual** | $= L_q$ | $= L_q$ | 52.59 | 45.64 | 38.62 | 37.73 | 27.47 | 40.41 |
| **Cross-lingual** | $\neq L_q$ | $= L_q$ | 52.99 | 44.56 | 38.63 | 37.23 | 25.84 | 39.85 |
| | $= L_q$ | $\neq L_q$ | 41.80 | 36.30 | 29.19 | 27.25 | 23.89 | 31.69 |
| | $\neq L_q$ | $\neq L_q$ | 39.78 | 34.79 | 28.40 | 26.89 | 24.12 | 30.80 |

Table 8: Multilingual two-hop QA performance for Qwen-3-8B. We report token-level F1. $= L_q$ and $\neq L_q$ indicate whether the document language matches or differs from the query language. For non-matching documents, we report the average across the four non-query languages.

| Setting | Document Languages | | Query Languages ($L_q$) | | | | | Avg. |
|---|---|---|---|---|---|---|---|---|
| | Hop-1 | Hop-2 | En | Fr | Ru | Ar | Zh | |
| **Monolingual** | $= L_q$ | $= L_q$ | 46.64 | 39.07 | 29.24 | 28.30 | 23.24 | 33.30 |
| **Cross-lingual** | $\neq L_q$ | $= L_q$ | 43.91 | 36.21 | 28.60 | 24.62 | 21.90 | 31.05 |
| | $= L_q$ | $\neq L_q$ | 35.49 | 30.55 | 22.10 | 18.64 | 14.67 | 24.29 |
| | $\neq L_q$ | $\neq L_q$ | 30.10 | 28.57 | 22.27 | 18.86 | 16.47 | 23.25 |

Table 9: Multilingual two-hop QA performance for Llama-3.1-8B-Instruct. We report token-level F1. $= L_q$ and $\neq L_q$ indicate whether the document language matches or differs from the query language. For non-matching documents, we report the average across the four non-query languages.

Figure 12: Full unfaithfulness ratios across query languages. Unfaithfulness refers to cases where the final two-hop answer is correct, SUBQ1 is incorrect, and SUBQ2 is correct.

Figure 13: Full composition failure ratios across query languages. Composition failure refers to cases where both SUBQ1 and SUBQ2 are correct, but the final two-hop answer is incorrect.