Fitting Regularized Population Dynamics with Neural Differential Equations

Abstract

Neural differential equations (neural DEs) are yet to see success in its application as interpretable autoencoders/descriptors, where they directly model a population of signals with the learned vector field. In this manuscript, we show that there is a threshold to which these models capture the dynamics of a population of signals produced under the same monitoring protocol. This threshold is computed by taking the derivative at each time point and analyzing the variance of its dynamics. In addition, we show that this can be tackled by projecting a highly-variant population to a lower dynamically variant space, where the model is able to capture dynamics, and similarly project the modelled signal back to the original space.

1 Introduction

The question we are asking is if the solution retrieved by a DE solver can be used to directly perform regression. By verifying empirically that this is not true for the current neural DE learning settings, we go further and ask if such can be done in a latent space, where the dynamics are simpler, but still informative to represent a complex population. To validate it, experiments are ran on:

- synthetic data with parametrizable complexity and variance (see Section 3);
- neuroimaging data associated with complex and noisy observations (see Section 4).

In particular, neural ordinary differential equations (neural ODEs) [1] are able to model signals and therefore extract vector fields that represent dynamics [2]. However, empirical observations show that neural ODEs are unable to capture dynamics of a population with a significative dynamical variance. Nonetheless, if one regularizes a latent space to have low variant dynamics, as illustrated in Figure 1, neural ODEs are able to capture that information. To this end, we introduce the concept of dynamical variance, which

Figure 1: Variance regularization example. Consider each line to be an instance signal in a population. The plot on the left shows the population projected in its original feature space. The plot on the right shows the same population projected in a space with low dynamical variance.

refers to how much the derivative of a signal deviates from a population mean. It is hypothesized that the minimization of the dynamical variance enables the neural ODE to solve accurately a population set. The latter implies that the vectorfield of the neural ODE incorporates the dynamics of the whole population, separating instances using the initial value [3] and estimated derivatives [1].

The contributions of our work are: (1) a novel loss function that allows a neural DE to learn dynamics of a population; (2) ability to reduce dynamical variance while retaining the important dynamics of the signal, that enable the separation of different representations through the initial value and

35 estimated derivatives; (3) experiment analysis, of the modelling capacity of a neural ODE under
36 paramatrizable variance and complexity data, was performed, unravelling that it only thrives on low
37 varying dynamical spaces and it gets better as the dynamical variance decreases; (4) show how one
38 can use neural DEs to extract brain dynamics.

2 Methods

40 **Autoencoder network.** We propose the use of a neural ODE in a latent space, which is characterized
41 by a smaller variance of dynamics relative to the original space. To this end, an encoder decoder
42 architecture is defined, where the encoder performs the mapping between the original space, $\vec{x}$,
43 that has representations of the raw signal, and the latent space, $\vec{z}$, that has representations with low
44 complexity. The decoder, on the other hand, maps $\vec{z}$ to $\hat{\vec{x}}$. The encoder, $E(.|\theta_E)$, consists of an
45 attention [4, 5] mechanism with 2 heads. The decoder, $D(.|\theta_D)$, is composed of a fully connected
46 neural network. The encoder and decoder are parametrized by θ_E and θ_D, respectively.

47 **Derivative estimation.** The encoder outputs a representation with the estimated derivatives for a
48 function f. The derivative is given to the ODE solver by a dense neural network with parameters θ_f,

$$f(\vec{z}, t|\theta_f) = \left(\frac{\hat{dz}}{dt}\right). \tag{1}$$

49 **Ordinary differential equations.** With the derivative given by a neural network, then a differential
50 equation of the form $\frac{d\mathbf{\bar{z}_t}}{dt} = f(\vec{z}_t, t)$ can be solved using the adjoint solver [6] (initial value problem
51 solver) as done in [1]. The solution to this equation is the signal being modelled.

52 **Bounded complexity loss (BCL).** As for the encoder, we propose a loss that converges the dynamical
53 complexity, $\hat{c}(\vec{z})$, of the latent representation, $\vec{z}$, to an interval defined by $[c_l, c_u]$, with $c_l, c_u \in \mathbb{R}^+$.
54 The dynamical complexity is defined in Equation 2 and consists on taking the discrete analog of the
55 derivative, $\Delta_t \vec{z} = \vec{z}_t - \vec{z}_{t-1}$, and subtracting with the next observed derivative, i.e. a discrete analog
56 of the second derivative. This is done for all the observed points, $\vec{z} = \{z_1, \ldots, z_T\}$,

$$\hat{c}(\vec{z}) = \frac{1}{T-2} \sum_{t=2}^{T-1} |\Delta_t \vec{z} - \Delta_{t+1} \vec{z}|. \tag{2}$$

57 After computing the dynamical complexity, $\hat{c}(\vec{z})$, let $c_l, c_u \in \mathbb{R}^+ : c_l < c_u$ be predefined constants
58 (hyperparameters), then by minimizing,

$$m(\vec{z}; c_l) = \frac{c_l}{\min(c_l, \hat{c}(\vec{z}))} - 1, \tag{3}$$

59 the complexity of the signal will converge to be higher than c_l, i.e., $\hat{c}(\vec{z}) \geq c_l$.

60 As the dynamical complexity of the latent representation approaches c_l, the penalization is higher,
61 i.e., the gradient has a higher magnitude. However, no penalty is given if $\hat{c}(\vec{z}) \geq c_l$ and if in its turn
62 $\hat{c}(\vec{z}) \ll c_l$, a gradient with low magnitude is computed.

63 The upper bound component,

$$M(\vec{z}; c_u) = \frac{\max(c_u, \hat{c}(\vec{z}))}{c_u} - 1 \tag{4}$$

64 has a similar behaviour as the hinge loss [7]. It gives higher penalizations than the minimum bound
65 component for values that are distant (higher) from (than) the defined constant, c_u.

66 The two expressions, $m(\vec{z}; c_l)$ and $M(\vec{z}; c_u)$, are joined by addition in a global loss,

$$\mathcal{L}_{\text{BCL}}(\vec{z}; c_l, c_u) = m(\vec{z}; c_l) + M(\vec{z}; c_u), \tag{5}$$

67 formalizing the BCL loss. Its minimization implies that the complexity of the signal will converge
68 to be between the two constants, c_l and c_u, i.e., $\hat{c}(\vec{z}) \rightarrow [c_l, c_u]$. Please refer to the supplementary
69 material, where you can find the plots of how these components change. The BCL loss is used to
70 optimize θ_E.

The proposed computational methodology starts with the original signal being represented at a hidden space, $E(\vec{x}; \theta_E)$, through means of a projection made by the encoder, E, then the latent representation of the signal, $\vec{z}$, is used to model a ordinary differential equation problem as an initial value problem. The derivative is computed using the initial value, $\vec{z}_0$, of the hidden signal representation. Using the estimated derivatives, $f(\vec{z}_0, \theta_f)$, the adjoint solver [1] models the hidden signal, $\hat{\vec{z}}$. Finally, the modelled hidden signal is transformed by a decoder to the original signal space, $D(\hat{\vec{z}}; \theta_D)$. The gradients for θ_E, θ_D and θ_f are computed according to $\nabla_{\theta_E} \mathcal{L}_{\text{BCL}}(z; c_l, c_u) + ||\theta_E||_1$, $\nabla_{\theta_D} \mathcal{L}_{\text{MSE}}(\hat{\vec{x}}, \vec{x}) + ||\theta_D||_1$, $\nabla_{\theta_f} \mathcal{L}_{\text{MSE}}(\hat{\vec{z}}, \vec{z}) + ||\theta_f||_1$.

Dynamical variance. A metric, that measures the success of $\mathcal{L}_{\text{BCL}}$, is now described. Note that this metric computes the variance of the first derivative, while the $\mathcal{L}_{\text{BCL}}$ loss uses the second derivative. This metric focuses on the dynamical variance of the population, i.e., given the mean dynamical complexity of all instances, $\mu_{\Delta \vec{z}}$, how much do all instances deviate from it (standard deviation). Figure 1 illustrates this phenomena. Consider a population with N individuals/instances. To compute the dynamical variance of the population, a different notation will be used for the complexity of an instance, i, which is regarded as $\Delta \vec{z}_i$. The Dynamical Variance is computed as

$$\text{Var}[\Delta \vec{z}] = \frac{1}{N} \sum_i^N (\Delta \vec{z}_i - \mu_{\Delta \vec{z}})^2. \tag{6}$$

3 Synthetic data

The algorithm that generates the synthetic data is explained in Appendix B.1. From Figure 2, we show that a neural ODE is unable to capture the dynamics of a population with a high variance of dynamics. It is observed that the neural ODE that operates directly on the raw signal improves as the variance, $\text{Var}[\Delta x]$, increases, which is counter intuitive. This is due to the model not adapting to the changes of the signal and ignoring them by only minimizing the error for the population set with a linear function line, similar to a linear regression. On the other hand, the neural ODE, regularized by E, is consistent

Figure 2: RMSE for the neural ODE in the latent space versus the neural ODE operating in the raw signal. In this figure, one can see the impact that the regularization of variance done by the encoder, E, has on modelling the true signal space.

for all the values that affect the complexity of the signal. This means the encoder performs a projection that helps modelling dynamics, which are complex enough to be retrieved from the latent to the original space representation.

4 Case Study: Neuroimaging data

Here we report results of the proposed methodology applied to neuroimaging data, specifically functional magnetic resonance imaging (fMRI). The feature extraction that provides the x-axis, y-axis, z-axis and temporal settings are described in Appendix B.2. Starting by analyz-

Table 1: Dynamical Variance comparison of the original space, $\vec{x}$, and the dynamics simplified space, $\vec{z}$.

	x-axis	y-axis	z-axis	temporal
$\text{Var}[\Delta \vec{x}]$	$6.1e-3$	$5.4e-3$	$1.1e-2$	$6.4e-3$
$\text{Var}[\Delta \vec{z}]$	$6.3e-4$	$2.5e-6$	$1.2e-3$	$2.6e-3$

ing the impact of the $\mathcal{L}_{\text{BCL}}$ loss, on the $\text{Var}[\Delta \vec{x}]$, when projecting $\vec{x}$ to $\vec{z}$, $\text{Var}[\Delta \vec{z}] < \text{Var}[\Delta \vec{x}]$ for all settings. Therefore, the minimization of $\mathcal{L}_{\text{BCL}}$ equates in a lower dynamical variance in the latent space. It is also worth noting that z-axis and temporal settings have the highest variance in the latent space, $\vec{z}$.

RMSE and Cosine dissimilarity metrics are presented in Table 2. For all settings, the differences, of the residuals from the autoencoder (AE) [8] and latent long-short term memory network (HRNN) [9] against neuralODE(z) [1], are all statistically significant with the maximum p-value being $4.13e-28$. Regarding the RMSE metric, by analyzing Table 2, the neuralODE($\vec{z}$) and neuralSDE($\vec{z}$) [10] both achieved values lower than their respective peers that operated in a space where the dynamical

119 complexity was not regularized, namely neuralODE($\vec{x}$) and neuralSDE($\vec{x}$). The latter, validates what
120 was already empirically proved in the previous section, using synthetic data.

121 The AE and HRNN baselines were outperformed with statistical significance, except for HRNN
122 in the y-axis setting (p-value 0.1201). Their misperformance may be due to the vanishing gradient
123 problem, because the neuralODE($\vec{z}$) and neuralSDE($\vec{z}$) both have gradients being introduced in f and
124 E independently, whereas the AE and HRNN gradients for E are backpropagated using the chain
125 rule. Nonetheless, the minimization of $\mathcal{L}_{\text{BCL}}$ proved to retain information from the original space,
126 as the decoder was able to retrieve the original signal, $\vec{x}$. It was also observed that the RMSE in the
127 z-axis and temporal settings was higher than the values for x-axis and y-axis settings. This might be
128 due to more complex dynamics being present in this dimension of the fMRI signal. Nonetheless, this
129 also correlates with z-axis and temporal settings having higher dynamical variance, $\text{Var}[\Delta \vec{z}]$, in the
130 latent space, whereas x-axis and y-axis have lower magnitudes of dynamical variance. Consequently,
131 the minimization of $\mathcal{L}_{\text{BCL}}$ not only gives $\text{Var}[\Delta \vec{z}] < \text{Var}[\Delta \vec{z}]$, but also leads to better results in a
132 auto-encoding regression task.

Table 2: RMSE and Cosine dissimilarity metrics in the test set.

| | RMSE | | | | Cosine dissimilarity | | | |
	x-axis	y-axis	z-axis	temporal	x-axis	y-axis	z-axis	temporal
AE	0.1542	0.1528	0.2149	0.2289	0.3477	0.3894	0.3425	0.2620
HRNN	0.1464	0.1201	0.1961	0.2135	0.3254	0.2528	0.2924	0.2338
neuralODE($\vec{x}$)	0.1186	0.1279	0.1804	0.1822	0.2268	0.2920	0.2446	0.1795
neuralODE($\vec{z}$)	0.1135	0.1184	0.1633	0.1815	0.2115	0.2399	0.2068	0.1767
neuralSDE($\vec{x}$)	0.1202	0.1273	0.1869	0.1811	0.2273	0.2801	0.2533	0.1752
neuralSDE($\vec{z}$)	0.1130	0.1190	0.1631	0.1789	0.2075	0.2444	0.2172	0.1708

133 The Cosine Distance was computed, in order to check if the observations taken from Table 2 differ
134 when computing a metric that looks at the pattern similarity. One observes that both metrics are
135 in agreement. The baselines AE and HRNN perform worse than the neuralODE and neuralSDE
136 models. The projection to the simplified latent space also improves the performance measured by this
137 metric. Similarly, z-axis and temporal settings also perform worse, due to the mentioned failure of
138 minimizing the dynamical variance.

139 The learned vector fields are shown in Figure 3. The z-axis and temporal settings have inherently
140 more complex space, correlated with higher dynamical variance. As for the x-axis and y-axis, one
141 observes less complex dynamics, with the x-axis being the space with less variability along the line.

(a) x-axis lines. (b) y-axis lines. (c) z-axis lines. (d) temporal lines.

Figure 3: Learned vector fields of each fMRI setting. Each describes the dynamics captured in the latent space, projected from the original space by E.

5   Conclusion

143 Neural ODEs are not currently seen, by the research community, as a method capable of extracting
144 dynamics from a population. Indeed, neural ODEs cannot fit the dynamics of populations with high
145 dynamical variance, whereas they are able to represent low dynamical variance populations with
146 success. In accordance, we hypothesize, that the minimization of the dynamical complexity of a space
147 enables a neural ODE model to capture the dynamics of a population, and validate this hypothesis.
148 A novel loss, $\mathcal{L}_{\text{BCL}}$, is introduced in order to project a highly complex dynamical space to a lower
149 complex one. The minimization of this loss is empirically shown to also minimize the dynamical
150 variance of a space. The encoder targeted a space that had representations with no discontinuities and
151 low derivative variance, as inspired by the NLP technique of preserving context [11]. Furthermore,
152 experiments were also done over a neuroimaging data (fMRI) modality, showing the possibility of
153 using shallow neural models to capture brain dynamics.

References

[1] Ricky TQ Chen, Yulia Rubanova, Jesse Bettencourt, and David K Duvenaud. Neural ordinary differential equations. In *Advances in neural information processing systems*, pages 6571–6583, 2018.

[2] Luca Falorsi and Patrick Forré. Neural ordinary differential equations on manifolds. *arXiv preprint arXiv:2006.06663*, 2020.

[3] Lawrence F Shampine. Computer solution of ordinary differential equations. *The Initial Value Problem*, 1975.

[4] Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. *arXiv preprint arXiv:1409.0473*, 2014.

[5] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. *arXiv preprint arXiv:1706.03762*, 2017.

[6] Yang Cao, Shengtai Li, Linda Petzold, and Radu Serban. Adjoint sensitivity analysis for differential-algebraic equations: The adjoint dae system and its numerical solution. *SIAM journal on scientific computing*, 24(3):1076–1089, 2003.

[7] Jason Weston, Chris Watkins, et al. Support vector machines for multi-class pattern recognition. In *Esann*, volume 99, pages 219–224, 1999.

[8] Geoffrey E Hinton and Ruslan R Salakhutdinov. Reducing the dimensionality of data with neural networks. *science*, 313(5786):504–507, 2006.

[9] Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

[10] Xuechen Li, Ting-Kam Leonard Wong, Ricky TQ Chen, and David Duvenaud. Scalable gradients for stochastic differential equations. In *International Conference on Artificial Intelligence and Statistics*, pages 3870–3882. PMLR, 2020.

[11] Tao Lei, Regina Barzilay, and Tommi Jaakkola. Rationalizing neural predictions. *arXiv preprint arXiv:1606.04155*, 2016.

[12] Jalil Taghia, Weidong Cai, Srikanth Ryali, John Kochalka, Jonathan Nicholas, Tianwen Chen, and Vinod Menon. Uncovering hidden brain state dynamics that regulate performance and decision-making during cognition. *Nature communications*, 9(1):1–19, 2018.

[13] Zirui Huang, Jun Zhang, Jinsong Wu, George A Mashour, and Anthony G Hudetz. Temporal circuit of macroscale dynamic brain activity supports human consciousness. *Science advances*, 6(11):eaaz0087, 2020.

[14] Douglas N Greve and Bruce Fischl. Accurate and robust brain image alignment using boundary-based registration. *Neuroimage*, 48(1):63–72, 2009.

[15] Fani Deligianni, Maria Centeno, David W Carmichael, and Jonathan D Clayden. Relating resting-state fmri and eeg whole-brain connectomes across frequency bands. *Frontiers in neuroscience*, 8:258, 2014.

[16] Fani Deligianni, David W Carmichael, Gary H Zhang, Chris A Clark, and Jonathan D Clayden. Noddi and tensor-based microstructural indices as predictors of functional connectivity. *PLoS One*, 11(4):e0153404, 2016.

[17] Xavier Glorot, Antoine Bordes, and Yoshua Bengio. Deep sparse rectifier neural networks. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pages 315–323, 2011.

[18] Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pages 249–256, 2010.

[19] Diganta Misra. Mish: A self regularized non-monotonic neural activation function. *arXiv preprint arXiv:1908.08681*, 2019.

[20] Prajit Ramachandran, Barret Zoph, and Quoc V Le. Searching for activation functions. *arXiv preprint arXiv:1710.05941*, 2017.

[21] Emilien Dupont, Arnaud Doucet, and Yee Whye Teh. Augmented neural odes. In *Advances in Neural Information Processing Systems*, pages 3140–3150, 2019.

[22] James Bergstra and Yoshua Bengio. Random search for hyper-parameter optimization. *The Journal of Machine Learning Research*, 13(1):281–305, 2012.

[23] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

A BCL Components

(a) Complexity bound with a lower bound, c_l. As the dynamical complexity of the latent representation approaches c_l, the penalization is higher, i.e., the gradient has a higher magnitude. No penalty is given if $\hat{c}(z) \geq c_l$ and if $\hat{c}(z) \ll c_l$, the gradient does not force linearly the representation to approach c_l.

(b) Complexity bound with a upper bound, c_u. This loss has the same behaviour as the hinge loss [7], but instead centered at $\hat{c}(z)$. This loss, $M(z; c_u)$, has higher penalizations than the minimum bound component for values that are distant from the defined constant.

Figure 4: BCL lower and upper bound components.

B Materials

In this Section, we provide a description of the materials used to validate the hypotheses drawn in the beginning of the manuscript. First, a description of the synthetic data is given. Then, a case study using real world neuroimaging data to extract brain dynamics is presented. Finally the validation setup is described.

B.1 Synthetic data

To address the impact that the derivative variance has on the performance of a neural ODE, a set of synthetic lines, l_s, are sampled according to derivative changes $\Delta l_s \sim \mathcal{N}(\mu_\Delta, \sigma_\Delta^2)$, for all t steps, and initial values $l_{s_0} \sim \mathcal{N}(\mu_0, \sigma_0^2)$, for each instance. The experiments were ran with:

- $\mu_{l_s} \in \{0.1, 0.2, 0.5, 1.0, 2.0\}$
- $\mathrm{Var}[\Delta l_s] \in \{0.01, 0.02, 0.05, 0.1, 0.2, 0.5, 1.0\}$

A total of 10000 lines were synthesized and a split of 60% and 40% was done for training and test data, respectively.

B.2 Case study: Neuroimaging data

In this work, to extract vector fields, two perspectives are introduced: spatial and temporal. In a spatial perspective, dynamics refer to how a signal changes through space, given a referential axis/vector. In a temporal perspective, dynamics refer to how a signal changes through time. We hypothesize that there are techniques available, due to advances in machine learning [1], which allow the direct modelling of complex systems in its raw form.

The blood flow of the brain can be captured in a functional magnetic resonance imaging (fMRI) recording session. Known as the haemodynamical activity, this modality is used to extract and uncover dynamics associated with brain functions [12, 13]. An fMRI instance $\in \mathbb{R}^{X \times Y \times Z \times T}$ is characterized by: the spatial dimension X representing the x-axis voxels, the spatial dimension Y representing the y-axis voxels, the spatial dimension Z representing the z-axis voxels, and the temporal dimension T defining the number of time points (also referred as number of volumes). All dimensions are discrete, with a fixed value used as separation/period. X, Y and Z each have a slice separation of size v_x, v_y and v_z, respectively, and T has a well-defined period given by Time

Response (TR) of the fMRI recording. The terms separation and period are used for spatial and temporal dimensions, respectively.

Temporal lines extraction. Consider a voxel characterized by the tuple $w = (w_x, w_y, w_z) \in (X, Y, Z)$, a location in space. Gathering all values of w along the temporal axis provides a time series, w, of length T. To avoid the problem of individual's brain misalignment [14], a commmon sub-region of coordinates is extracted among all individuals. The coordinates were computed as a set of adjacent spirals with the center at the center point of the volume. The radius of these spirals was set to a low value, as the number of line instances increases with it. The volumes of each individual were partitioned into 30 equal sized partitions.

Spatial lines extraction. Consider lines that traverse a volume, a volume on time point t of an fMRI is defined by three different directions: x-axis direction represented by $l_x = (w_y, w_z)$, y-axis direction represented by $l_y = (w_x, w_z)$ and z-axis direction represented by $l_z = (w_x, w_y)$. Gathering all values of l_a, with $a \in X \bigcup Y \bigcup Z$, creates a vector, $\vec{l_a}$, with length S. Lines were extracted with a fixed size of 8 voxels. From all individuals, each volume was used to extract *x*-axis, *y*-axis and *z*-axis lines. Similarly to the temporal line extraction, all lines are adjacent in its plane (either x, y or z plane), with the extracted voxels being the ones that intersect the path of the mentioned spiral, centered with the volume.

The proposed pipeline (Section 2) is tested in four different fMRI settings: temporal, *x*-axis line, *y*-axis line and *z*-axis line modelling. For the sake of completeness, each setting is subject to a hyperparameter search.

NODDI Dataset. The dataset [15, 16] contains 17 individuals (11 males, 6 females) with average age 32.84 ± 8.13 years, out of which only 10 are considered, as the remaining contain corrupted views. The simultaneous Electroencephalography-fMRI recordings were done in a resting state with eyes open setting. The subjects stayed still on a vaccum cushion during scanning. The fMRI imaging was acquired based on a T2-weighted gradient-echo EPI sequence with: 300 volumes, TR of 2160 milliseconds (ms), TE of 30 ms, 30 slices with 3.0 millimeters (mm) (1 mm gap), voxel size of $3.3 \times 3.3 \times 4.0$ mm and a field of view of $210 \times 210 \times 120$ mm.For more details please refer to [15, 16]. The dataset described is used to validate the approach proposed.For more details please refer to [15, 16]. The dataset described is used to validate the approach proposed.

B.3 Validation

For the sake of completeness, an hyperparameter search is ran with the search space defined as:

- learning rate, $lr \in \{1e-1, 1e-2, 1e-3, 1e-4, 1e-5\}$
- batch size, $b \in \{16, 32, 64, 128\}$
- activation functions , $\sigma \in \{\text{ReLU } [17], \text{softsign } [18], \text{hardtanh, leakyrelu } [17], \text{mish } [19], \text{selu } [17], \text{swish } [20]\}$
- L1 regularization term, $\lambda \in \{1e-1, 1e-2, 1e-3, 1e-4, 1e-5, 0.0\}$
- hidden size, $h_N \in \{10, 20, 30\}$
- number of layers, $N_L \in \{1, 2, 3\}$
- augmented dimensions [21], $a \in \{0, 1, 2, 3, 4, 8, 16\}$
- upper bound of BCL, $c_u \in \{0.2, 0.5, 1.0, 1.5, 2.0\}$

The following hyperparameters are set independently for the encoder, decoder and derivative estimator networks: activation functions, L1 regularization. In addition, the hidden size and number of layers are also set for the decoder and derivative estimator. Because the search space has a complexity of $\mathcal{O}(\Sigma^P)$, being Σ the size of the parameter space and P the number of parameters, a grid search is not feasible in time. To avoid this, a random search is implemented (it is efficient in limited time [22] and it has a high payoff for its simplicity).

In the NODDI dataset, the partitions for the train and test sets were set to 0.60 (6 individuals) and 0.40 (4 individuals), respectively. The hyperparameter search is ran with 200 iterations for each setting. At each iteration a 5-fold cross validation is performed in the train set and the set of hyperparameters that has the lowest average loss in the validation set of the 5 folds is chosen as the optimal hyperparameter

set. The L1 regularization is optimized independently for each component (encoder, E, decoder, D, and derivative estimator, f). Additionally, activation function, hidden size and the number of layers are also independently optimized for D and f. The lower bound of BCL is set to $c_l = 0.1$. For the sake of comparison, a vanilla autoencoder and an autoencoder with a recurrent layer at the latent space are implemented. The vanilla autoencoder is composed of the encoder, E, and the decoder, D. Since hyperparameters are shared with the proposed approach, the ones obtained from the hyperparameter search are recycled for these baselines. The autoencoder with a recurrent layer (LSTM [9]) at the latent space, which has the same components, E and D, also uses the optimized hyperparameters. The neural differential equation based models are referred to as:

- neuralODE($\vec{x}$), a neural ODE operating in the original space representation, $\vec{x}$;

- neuralODE($\vec{z}$), a neural ODE operating in the latent space, $\vec{z}$;

- neuralSDE($\vec{x}$), a neural stochastic differential equation (SDE) operating in the original space representation, $\vec{x}$;

- neuralSDE($\vec{z}$), a neural SDE operating in the latent space, $\vec{z}$;

Table 3: Optimal hyperparameters obtained by the random hyperparameter search. Adam [23] was used for the training of each setting. Since the multi head attention mechanism, explained in Section 2, was used as the encoder, the activation function (linear), number of layers and hidden size are not defined for E.

	lr	b	σ_D	σ_f	λ_E	λ_D	λ_f	h_{N_D}	h_{N_f}	N_{L_D}	N_{L_f}	a	c_u
x-axis	0.01	128	mish	softsign	0.0001	$1e-5$	0.001	30	30	2	2	8	2.0
y-axis	0.1	16	relu	relu	$1e-5$	$1e-5$	0.001	30	10	3	3	8	1.0
z-axis	0.001	64	leakyrelu	swish	0.0001	0.0	$1e-5$	30	20	3	1	3	1.5
temporal	0.001	128	leakyrelu	leakyrelu	$1e-5$	0.0	0.001	20	10	1	3	2	0.5