TCHV: Type-Conditioned Hypothesis Verification for Multimodal Named Entity Recognition

Abstract

Multimodal Named Entity Recognition (MNER) uses supplementary images to resolve ambiguity in entity mentions in noisy, short-form social-media text. Prevailing approaches typically fuse text with visually aligned features, but such cues often lack sufficient discriminative power and may support conflicting entity-type hypotheses. To address this issue, we propose TCHV, a lightweight framework driven by a hypothesis-testing perspective. By formulating each span-type pair as a distinct hypothesis during inference, TCHV predicts the latent feature evidence expected under each hypothesis and validates it against observed multimodal representations through bidirectional text-image matching, using a visual relevance gate to suppress uninformative images. Verification scores serve as surrogate evidence statistics; evaluations on Twitter-2015/2017 show consistent gains over established MNER baselines, while extensions to grounded and fine-grained settings demonstrate broader generalizability. Anonymous code: https://anonymous.4open.science/r/ImaginE-7DE0.

1 Introduction

Multimodal Named Entity Recognition (MNER) aims to identify entity mentions in text-image social posts and assign them semantic types such as PER, LOC, ORG, and MISC (Moon et al., 2018; Lu et al., 2018; Zhang et al., 2018). Compared with text-only NER, MNER reflects a common social-media setting in which names, hashtags, abbreviations, and images jointly signal the entity being discussed, supporting applications such as event monitoring, opinion analysis, information extraction, and multimodal search (Ritter et al., 2011; Moon et al., 2018; Lu et al., 2018). Visual cues are useful because social-media texts are often short, noisy, and context-limited, making many mentions ambiguous from text alone (Ritter et al.,

Figure 1: Motivation for TCHV. Visually related cues may support competing entity-type hypotheses. In the *Harry Potter* example, TCHV verifies whether observed multimodal evidence supports each candidate type rather than relying on visual relatedness alone. Scores are schematic.

2011; Moon et al., 2018; Lu et al., 2018; Chen et al., 2021; Ushio et al., 2022).

Existing MNER methods usually follow a relevance-oriented *encode-align-fuse* paradigm: they first retrieve visually related evidence and then map the fused representation to an entity type (Xu et al., 2022; Wang et al., 2022; Chen et al., 2022; Zhou et al., 2022; Xu et al., 2024). However, visual relatedness is not equivalent to type-discriminative evidence. Because cross-modal alignment is learned from training-time co-occurrence statistics and representation-level compatibility, it may over-emphasize visually salient or historically frequent cues that are related to a mention but insufficient for resolving its current entity type.

Figure 1 illustrates this distinction with the mention "*Harry Potter*" in the post "*Harry Potter and the box office.*" For example, in "*Harry Potter and the box office,*" character faces are clearly related to the Harry Potter universe and may induce a PER-like visual expectation. Yet the current context points to a movie-franchise interpretation, where movie posters, release years, revenue statistics, and the textual cue "*box office*" provide

stronger evidence for MISC. This reveals a mismatch between relevance-oriented alignment and type-specific decision making: *the model should not only ask whether an image is related to a mention, but whether the observed multimodal evidence supports a particular candidate type.*

To address this mismatch, we reformulate MNER as *type-conditioned hypothesis verification*. Instead of treating entity type only as a final classification label, we regard each span-type pair as a competing hypothesis. For each hypothesis, TCHV predicts the latent evidence expected under the given span and candidate type, and verifies this expectation against observed multimodal representations through bidirectional text-image matching. This turns visual information from a general relevance cue into type-specific evidence, enabling the model to compare competing hypotheses rather than rely on a single type-agnostic alignment prior. Here, latent prediction denotes compact evidence prediction for discriminative verification, not image reconstruction or a general-purpose world model (LeCun, 2022; Assran et al., 2023; Bardes et al., 2024; Garrido et al., 2024).

Our contributions are summarized as follows:

- We propose TCHV, a lightweight type-conditioned hypothesis verification framework that evaluates each span-type hypothesis by comparing expected latent evidence with observed multimodal evidence through bidirectional verification and a visual relevance gate.

- We provide a hypothesis-testing view that interprets verification scores as surrogate evidence statistics and explains how contrastive verification and bidirectional score separation support type-specific decisions.

- Experiments on Twitter-2015 and Twitter-2017 demonstrate consistent improvements over established MNER baselines, while extensions to grounded and fine-grained MNER further show the applicability of the verification formulation.

2 Preliminaries

Span-based MNER. Let $\mathbf{x} = (x_1, \ldots, x_n)$ denote a sentence paired with an image $\mathbf{I}$. Following span-based MNER formulations (Sohrab and Miwa, 2018; Zhou et al., 2022; Xu et al., 2024), we enumerate candidate spans $\mathcal{S}(\mathbf{x}) = \{(i, j) \mid$ $1 \leq i \leq j \leq n, \ j - i + 1 \leq L\}$ and assign each span a label $y \in \mathcal{Y} = \{y_0\} \cup \mathcal{Y}^+$, where y_0 is the non-entity class O and $\mathcal{Y}^+$ contains entity types such as PER, LOC, ORG, and MISC. Evaluation follows the strict span-level protocol: a prediction is correct only when both its boundary and non-O type match the gold annotation.

Latent verification intuition. Latent predictive models learn to predict target representations in latent space rather than reconstruct raw observations (LeCun, 2022; Assran et al., 2023; Bardes et al., 2024). TCHV adapts this idea for MNER: for each span-type hypothesis, it predicts the latent evidence expected under that hypothesis and verifies the prediction against observed multimodal evidence. The prediction is not used to generate images; it serves as a type-conditioned evidence expectation for hypothesis verification. Appendix B gives the detailed mapping from latent prediction to TCHV.

3 Our Method: TCHV

3.1 Overview

Inspired by statistical hypothesis testing, TCHV treats each candidate span-type pair as a hypothesis and uses type-conditioned verification scores as evidence statistics; Section 3.8 provides the formal interpretation and explanatory results.

TCHV operationalizes type-conditioned hypothesis verification through two latent prediction paths. The forward path evaluates whether the image contains evidence expected under a span-type hypothesis, while the reverse path evaluates whether visually grounded evidence remains consistent with the textual mention under the same type hypothesis. TCHV is not designed to replace cross-modal alignment; instead, it adds a type-conditioned verification layer on top of latent span and image representations, where relevance-oriented alignment retrieves potentially related evidence and verification tests which type hypothesis the evidence supports. Figure 2 illustrates the full architecture. The pipeline has five stages: **(1)** Backbone encoders produce span representations $\mathbf{z}_{\text{span}} \in \mathbb{R}^d$, patch features $\mathbf{Z}_v \in \mathbb{R}^{N \times d}$, and a global visual vector $\mathbf{z}_{v,\text{cls}} \in \mathbb{R}^d$. **(2)** The forward path generates type-conditioned latent visual evidence expectations and scores each expectation against the observed image, yielding $\mathbf{s}^{\text{fwd}} \in \mathbb{R}^K$. **(3)** The reverse path predicts type-conditioned textual evidence expectations from visual features and scores each against

Figure 2: Architecture of TCHV. **(Left)** Backbone encoders produce span and visual representations. **(Center)** The forward path generates type-conditioned latent visual evidence expectations and compares them with observed image features. **(Right)** The reverse path predicts type-conditioned textual evidence expectations from span-relevant visual features and compares them with the real span, gated by visual relevance.

the real span, yielding $\mathbf{s}^{\text{rev}} \in \mathbb{R}^K$. **(4)** A Visual Relevance Gate produces a scalar $g \in [0, 1]$ to downweight reverse scores when the image is noisy, irrelevant, or weakly associated with the span. **(5)** An entity classifier fuses all signals to predict entity types.

3.2 Backbone Encoders

Text encoder. We encode the input sentence with RoBERTa (Liu et al., 2019), obtaining token-level representations $\mathbf{H}_t = (\mathbf{h}_1, \ldots, \mathbf{h}_n) \in \mathbb{R}^{n \times d_t}$. For each candidate span (i, j), we construct a span representation via the triple encoding scheme:

$$\mathbf{h}_{(i,j)} = \big[\text{AvgPool}(\mathbf{h}_i{:}\mathbf{h}_j) \,;\, \mathbf{h}_j - \mathbf{h}_i \,;\, \mathbf{h}_i \odot \mathbf{h}_j\big],$$

where $\text{AvgPool}(\mathbf{h}_i{:}\mathbf{h}_j) = \frac{1}{j-i+1} \sum_{\ell=i}^{j} \mathbf{h}_\ell$, $[\,;\,]$ denotes concatenation, and $\odot$ is the Hadamard product. The resulting $\mathbf{h}_{(i,j)} \in \mathbb{R}^{3d_t}$ is projected to the shared latent space:

$$\mathbf{z}_{\text{span}} = \pi_t(\mathbf{h}_{(i,j)}) \in \mathbb{R}^d, \quad \pi_t : \mathbb{R}^{3d_t} \to \mathbb{R}^d.$$

Image encoder. We encode image $\mathbf{I}$ with a Vision Transformer (Dosovitskiy et al., 2021), yielding patch representations $\mathbf{X}_v \in \mathbb{R}^{(N+1) \times d_v}$ including the [CLS] token. These are projected to the shared space:

$$\mathbf{Z}_v = \pi_v(\mathbf{X}_{v,1:N}) \in \mathbb{R}^{N \times d},$$

$$\mathbf{z}_{v,\text{cls}} = \pi_v(\mathbf{x}_{v,0}) \in \mathbb{R}^d,$$

where $\mathbf{X}_{v,1:N}$ denotes the N patch representations excluding the [CLS] token $\mathbf{x}_{v,0}$, and $\pi_v : \mathbb{R}^{d_v} \to \mathbb{R}^d$

applies layer normalization followed by a linear projection. The RoBERTa and ViT backbone encoders are frozen in all experiments. We train the projection layers and the task-specific latent predictors, comparators, gate, and classifier modules.

3.3 Forward Latent Evidence Prediction: Text-to-Image Verification

The forward path is the main mechanism for type-evidence verification. Instead of directly attending from a span to visual patches in a type-agnostic manner, it first uses each type hypothesis to generate a latent visual evidence expectation and then verifies this expectation against the observed image. It consists of a *Type-Conditioned Latent Evidence Predictor* that generates type-specific visual evidence expectations, and an *Evidence-Reality Comparator* that scores each expectation against the observed image.

Type-conditioned latent evidence predictor. We maintain a learnable type embedding table $\mathbf{E}_{\text{type}} = \{\mathbf{e}_0, \ldots, \mathbf{e}_{K-1}\} \subset \mathbb{R}^{d_e}$, where $\mathbf{e}_0$ encodes the O/null hypothesis and each $\mathbf{e}_k$ encodes one type or null hypothesis. The null hypothesis supports non-entity rejection in classification, but it is not treated as a semantic entity type with concrete visual or textual evidence for auxiliary evidence-prediction supervision. The predictor is a mapping $f_\theta : \mathbb{R}^d \times \mathbb{R}^{d_e} \to \mathbb{R}^d$:

$$\hat{\mathbf{z}}_k^v = f_\theta(\mathbf{z}_{\text{span}}, \mathbf{e}_k), \quad k = 0, \ldots, K{-}1.$$

We implement f_θ as an AdaLN-conditioned predictor with an input projection, M type-conditioned blocks, and an output projection. The type embedding modulates hidden states through adaptive affine parameters, allowing the same span representation to produce different latent evidence expectations under different type hypotheses. Appendix B gives the full block equations and initialization details.

Evidence-reality comparator. For each type hypothesis k, the comparator attends from the expected visual evidence $\hat{\mathbf{z}}_k^v$ to the observed image patches $\mathbf{Z}_v$:

$$\boldsymbol{\alpha}_k = \text{softmax}\left(\frac{\hat{\mathbf{z}}_k^v \mathbf{Z}_v^\top}{\sqrt{d}}\right) \in \mathbb{R}^N,$$

$$\mathbf{z}_k^{v,\text{att}} = \boldsymbol{\alpha}_k \mathbf{Z}_v \in \mathbb{R}^d.$$

A scoring MLP produces a scalar compatibility score using common attend-and-compare matching features (Parikh et al., 2016; Chen et al., 2017). Let $\mathbf{a} = \hat{\mathbf{z}}_k^v$ and $\mathbf{b} = \mathbf{z}_k^{v,\text{att}}$:

$$s_k^{\text{fwd}} = \text{MLP}_s([\mathbf{a}; \mathbf{b}; \mathbf{a}-\mathbf{b}; \mathbf{a}\odot\mathbf{b}]), \quad (1)$$

where $\text{MLP}_s : \mathbb{R}^{4d} \to \mathbb{R}$. The forward scores $\mathbf{s}^{\text{fwd}} = (s_0^{\text{fwd}}, \ldots, s_{K-1}^{\text{fwd}})$ indicate how well each type-specific visual expectation matches the observed image.

3.4 Reverse Consistency Verification: Visual-to-Text

The reverse path provides a complementary visual-to-text consistency verification signal. Given span-relevant visual evidence, it predicts the textual evidence expected under each type hypothesis and compares it with the actual span representation.

Span-visual attention. We extract a span-relevant visual representation via cross-attention with learned projections $\mathbf{W}_q, \mathbf{W}_k \in \mathbb{R}^{d\times d}$: The span representation serves as the query, while projected image patches serve as keys, so the attention distribution is conditioned on the current mention rather than on the image alone. This mention-level grounding is important for the reverse path because different spans in the same post may rely on different visual regions or may require suppressing the image entirely.

$$\mathbf{q} = \mathbf{z}_{\text{span}}\mathbf{W}_q, \quad \mathbf{K}_v = \mathbf{Z}_v\mathbf{W}_k,$$

$$\boldsymbol{\beta} = \text{softmax}\left(\frac{\mathbf{q}\mathbf{K}_v^\top}{\sqrt{d}}\right), \quad \mathbf{z}_{v,\text{span}} = \boldsymbol{\beta}\,\mathbf{Z}_v.$$

This lets each span attend to the image regions most relevant to it.

Reverse latent evidence predictor. A reverse predictor $r_\phi : \mathbb{R}^d \times \mathbb{R}^{d_e} \to \mathbb{R}^d$, architecturally identical to the forward predictor, takes $\mathbf{z}_{v,\text{span}}$ as input and generates an expected textual representation for each type:

$$\hat{\mathbf{z}}_k^t = r_\phi(\mathbf{z}_{v,\text{span}}, \mathbf{e}_k), \ k = 0, \ldots, K-1.$$

To enforce consistent type semantics across both directions, the forward and reverse predictors *share the type embedding table* $\mathbf{E}_{\text{type}}$.

Reverse evidence comparator. The reverse comparator scores each $\hat{\mathbf{z}}_k^t$ against the real span $\mathbf{z}_{\text{span}}$ using the same four-way feature combination as Eq. (1):

$$s_k^{\text{rev}} = \text{MLP}_r([\hat{\mathbf{z}}_k^t; \mathbf{z}_{\text{span}}; \hat{\mathbf{z}}_k^t - \mathbf{z}_{\text{span}}; \hat{\mathbf{z}}_k^t \odot \mathbf{z}_{\text{span}}]),$$

where $\text{MLP}_r : \mathbb{R}^{4d} \to \mathbb{R}$. The reverse scores $\mathbf{s}^{\text{rev}}$ reflect complementary type evidence from visual-to-text consistency verification.

The two branches are complementary. The forward branch evaluates whether the image contains evidence expected under a span-type hypothesis, while the reverse branch evaluates whether visually grounded evidence remains consistent with the textual mention. The gate prevents the reverse branch from amplifying noise when the image is weakly related or irrelevant.

3.5 Visual Relevance Gate

Not every image is informative for entity typing; social media images may be irrelevant or even introduce visual bias/noise (Chen et al., 2021, 2022; Zhang et al., 2023). To prevent unreliable visual evidence from dominating the reverse path, we use a learned gate that estimates whether visual evidence is reliable enough to contribute to reverse verification. Let $\mathbf{u} = [\mathbf{z}_{\text{span}}; \mathbf{z}_{v,\text{cls}}; \mathbf{z}_{\text{span}} \odot \mathbf{z}_{v,\text{cls}}] \in \mathbb{R}^{3d}$:

$$g = \sigma(\text{MLP}_g(\mathbf{u})) \in [0, 1], \quad (2)$$

where σ is the sigmoid function and $\text{MLP}_g : \mathbb{R}^{3d} \to \mathbb{R}$. The bias of the final layer is initialized to 2, so that $\sigma(2) \approx 0.88$: the gate defaults to "on" and learns to reduce the contribution of reverse scores when the image is irrelevant, noisy, or weakly associated with the span. The gated reverse scores are $\tilde{s}_k^{\text{rev}} = g \cdot s_k^{\text{rev}}$.

3.6 Entity Classifier

The classifier fuses five groups of features: $\mathbf{z}_{\text{span}}$, $\mathbf{z}_{v,\text{cls}}$, $\mathbf{s}^{\text{fwd}}$, $\tilde{\mathbf{s}}^{\text{rev}}$, and a span width embedding $\mathbf{w} \in \mathbb{R}^{d_w}$ indexed by span length. Let $\mathbf{c} = [\mathbf{z}_{\text{span}}; \mathbf{z}_{v,\text{cls}}; \mathbf{s}^{\text{fwd}}; \tilde{\mathbf{s}}^{\text{rev}}; \mathbf{w}] \in \mathbb{R}^{2d+2K+d_w}$:

$$\mathbf{h}_{\text{fuse}} = \text{MLP}_{\text{fuse}}(\mathbf{c}) \in \mathbb{R}^{d_c},$$
$$\mathbf{o} = \mathbf{W}_{\text{cls}} \mathbf{h}_{\text{fuse}} \in \mathbb{R}^K,$$
$$\hat{\mathbf{y}} = \text{softmax}(\mathbf{o}) \in \mathbb{R}^K,$$

where MLP_{fuse} is a two-layer network with GELU and dropout, $\mathbf{o}$ denotes pre-softmax logits, and $\hat{\mathbf{y}}$ denotes probabilities. At inference, we retain non-O spans whose best entity-type logit exceeds the O logit by a tuned margin, and greedily resolve overlapping predictions by confidence; Appendix F gives the decoding details.

3.7 Training Objective

The total loss combines a span classification loss, three forward verification losses, and their reverse counterparts:

$$\mathcal{L} = \mathcal{L}_{\text{task}} + \alpha\mathcal{L}_{\text{ira}} + \beta\mathcal{L}_{\text{ico}} + \gamma\mathcal{L}_{\text{sig}}$$
$$+ \alpha'\mathcal{L}'_{\text{ira},g} + \beta'\mathcal{L}'_{\text{ico},g} + \gamma'\mathcal{L}'_{\text{sig},g},$$

where $\mathcal{L}_{\text{task}}$ is weighted span-level cross-entropy; $\mathcal{L}_{\text{ira}}$, $\mathcal{L}_{\text{ico}}$, and $\mathcal{L}_{\text{sig}}$ denote evidence-reality alignment, type-contrastive verification, and anti-collapse regularization, respectively; primed symbols denote reverse counterparts. The subscript g indicates that reverse alignment and contrastive losses are weighted by the stopped-gradient visual relevance gate. Auxiliary verification losses are computed only on gold non-O entity spans because non-entity spans do not have well-defined type-specific evidence; batches without gold entity spans optimize only $\mathcal{L}_{\text{task}}$. Appendix B gives the full objective definitions.

3.8 A Hypothesis-Testing View

Interpretation. For a candidate span u and a non-O type k, MNER can be viewed as testing whether the available multimodal evidence supports the span-type hypothesis against the composite null:

$$H_0^{u,k} : Y_u \neq k \qquad \text{vs.} \qquad H_1^{u,k} : Y_u = k.$$

TCHV constructs type-conditioned verification scores for these hypotheses. Let $F_{u,k} = s_{u,k}^{\text{fwd}}$ and $R_{u,k} = s_{u,k}^{\text{rev}}$. The forward score evaluates whether the observed image contains the visual evidence expected under (u, k), while the reverse score evaluates whether span-relevant visual evidence remains consistent with the textual span under the same type hypothesis. With the visual relevance gate $g_u \in [0, 1]$, a reliability-weighted verification statistic can be abstracted as

$$T_{u,k} = F_{u,k} + \rho g_u R_{u,k}, \qquad (3)$$

where $\rho \geq 0$ controls the contribution of reverse verification. The implemented classifier uses the full fused representation rather than this scalar statistic alone; Eq. (3) is an analytical abstraction showing how forward verification, reverse consistency, and reliability gating jointly support type-specific decisions. This perspective also clarifies why conditioning on the candidate type is necessary. Without type conditioning, visually related evidence for different labels is compared only after fusion, so evidence that is salient for one type can obscure weaker but more appropriate evidence for another. By constructing a separate statistic for each span-type hypothesis, TCHV makes the evidence comparison label-aware before the final classifier combines the signals.

Contrastive verification as a soft evidence-ratio surrogate. The forward contrastive loss encourages the gold type to dominate competing hypotheses. For a gold entity span u with type $y \in \mathcal{Y}^+$ and $K = |\mathcal{Y}|$, define

$$\bar{Z}_{u,y} = \frac{1}{K-1} \sum_{\ell \in \mathcal{Y} \setminus \{y\}} \exp\left(\frac{F_{u,\ell}}{\tau}\right),$$
$$\Lambda_{u,y}^{\text{fwd}} = \frac{F_{u,y}}{\tau} - \log \bar{Z}_{u,y}.$$

This quantity compares support for the correct type against a smooth aggregate of all competing labels, including the O/null class.

Proposition 1 (Contrastive loss as evidence-ratio margin). *For each gold entity span u with type $y \in \mathcal{Y}^+$, the instance-wise forward contrastive loss satisfies*

$$\ell_u^{\text{fwd}} = -\log \frac{\exp(F_{u,y}/\tau)}{\sum_{k \in \mathcal{Y}} \exp(F_{u,k}/\tau)}$$
$$= \log\left(1 + (K-1)\exp(-\Lambda_{u,y}^{\text{fwd}})\right). \qquad (4)$$

Therefore, the instance-wise contrastive loss is a strictly decreasing function of $\Lambda_{u,y}^{\text{fwd}}$: smaller evidence-ratio margins are monotonically penalized, and minimizing the loss encourages larger

support for the gold type relative to the composite null.

Proposition 1 shows that the contrastive objective is not only increasing the absolute gold-type score; it monotonically rewards a larger soft evidence margin between the gold type and the composite set of competing hypotheses. Additional score-separation analysis is provided in Appendix C.

Bidirectional verification as combining two tests. Let $G_{u,k} = g_u R_{u,k}$ be the gated reverse statistic and define

$$\Delta_f = \mathbb{E}[F_{u,k} \mid H_1^{u,k}] - \mathbb{E}[F_{u,k} \mid H_0^{u,k}],$$
$$\Delta_g = \mathbb{E}[G_{u,k} \mid H_1^{u,k}] - \mathbb{E}[G_{u,k} \mid H_0^{u,k}].$$

Proposition 2 (Bidirectional verification improves separation). *Assume $F_{u,k}$ and $G_{u,k} = g_u R_{u,k}$ are independent sub-Gaussian statistics under both hypotheses, with variance proxies σ_f^2 and σ_g^2. If the forward statistic is discriminative, $\Delta_f > 0$, and the gated reverse statistic provides positive additional separation, $\Delta_g > 0$, then there exists a sufficiently small $\rho > 0$ such that*

$$\frac{(\Delta_f + \rho\Delta_g)^2}{\sigma_f^2 + \rho^2\sigma_g^2} > \frac{\Delta_f^2}{\sigma_f^2}.$$

Proposition 2 gives a testing-theoretic explanation of bidirectional complementarity: reverse verification is useful when it supplies additional separation beyond the forward score, but it can add variance when the image is unreliable. The visual relevance gate therefore acts as a reliability controller, allowing reverse evidence to contribute when informative and suppressing it when visual evidence is weak or noisy.

4 Experiments

4.1 Experimental Setup

Datasets and metrics. We evaluate standard MNER on Twitter-2015 and Twitter-2017, two multimodal social media benchmarks annotated with PER, LOC, ORG, and MISC entities (Lu et al., 2018; Zhang et al., 2018). Following standard protocol, we report Precision (P), Recall (R), F1, and per-type F1 under strict span-level matching; dataset statistics and extension benchmark details are provided in Appendix F.

Implementation details. The default TCHV uses frozen RoBERTa-base (Liu et al., 2019) and ViT-Base/16 (Dosovitskiy et al., 2021) encoders, and trains only the task-specific projection, latent verification, gate, and classifier modules. TCHV-BERT replaces only RoBERTa-base with BERT-base (Devlin et al., 2019); otherwise the visual encoder, trainable modules, training protocol, and decoding settings are unchanged. Full hyperparameters, preprocessing, decoding, and computing environment details are provided in Appendix F.

Baselines. We compare against three groups of methods: (1) *Text-only*: BiLSTM-CRF (Huang et al., 2015) and BERT-CRF (Devlin et al., 2019); (2) *Multimodal MNER*: AdaCoAtt (Zhang et al., 2018), MAF (Xu et al., 2022), HVPNeT (Chen et al., 2022), MNER-QG (Jia et al., 2023), De-Bias (Zhang et al., 2023), SMNER (Zhou et al., 2022), VEC-MNER (Wei et al., 2024), and SEPA (Ding et al., 2025); (3) *VLLM-based*: Llama3.2-11B-Vision (Meta AI, 2024), Qwen2.5-VL-7B (Bai et al., 2025), DeepSeek-VL-7B (Lu et al., 2024), and PGIM (Li et al., 2023).

4.2 Main Results

Table 1 presents the main comparison. We organize baselines by methodology and report both per-type F1 and overall P/R/F1 on each dataset.

The results show that type-conditioned verification provides evidence beyond relevance-oriented alignment: TCHV improves overall F1 over text-only and multimodal baselines on both datasets. With VLLM-enhanced evidence, TCHV† further improves Twitter-2017 and remains competitive with PGIM on Twitter-2015. Per-type gains are strongest on MISC, where visual relatedness often fails to determine a single canonical entity type. This pattern is consistent with our motivation: MISC contains events, products, competitions, and media titles, so visually related cues can easily point to people, organizations, or locations unless they are checked under the candidate type. The TCHV-BERT variant also outperforms previous non-VLLM multimodal systems, suggesting that the improvement is not solely due to using a stronger text encoder. Meanwhile, direct zero-shot or few-shot VLLM prompting remains weaker than task-specific MNER models, indicating that large vision-language models still benefit from span-level supervision and explicit type verification in this setting.

Table 1: Performance on Twitter-2015 and Twitter-2017. Per-type F1 and overall P, R, F1 (%). Best results are in **bold** and second best results are underlined, marked separately for non-VLLM and VLLM-based methods. The dagger denotes VLLM-enhanced results.

Method	Twitter-2015							Twitter-2017						
	PER	LOC	ORG	MISC	P	R	F1	PER	LOC	ORG	MISC	P	R	F1
Text-only methods														
BiLSTM-CRF	76.77	72.56	41.33	26.80	68.14	61.09	64.42	85.12	72.68	72.50	52.56	79.42	73.43	76.31
BERT-CRF	84.74	80.51	60.27	37.29	69.22	74.59	71.81	90.25	83.05	81.13	62.21	83.32	83.57	83.44
Multimodal MNER methods														
AdaCoAtt	81.98	78.95	53.07	34.02	72.75	68.74	70.69	89.63	77.64	79.24	62.77	84.16	80.24	82.15
MAF	84.67	81.18	63.35	41.82	71.86	75.10	73.42	91.51	85.80	85.10	68.79	86.13	86.38	86.25
HVPNeT	86.62	81.89	60.22	41.70	73.87	76.82	75.32	92.87	84.75	83.24	69.35	85.84	87.93	86.87
MNER-QG	85.31	81.65	63.41	41.32	77.43	72.15	74.70	92.29	86.19	84.52	71.67	88.26	85.65	86.94
De-Bias	85.97	81.84	64.02	43.38	74.45	76.13	75.28	93.46	84.15	84.42	67.88	87.59	86.11	86.84
SMNER	85.98	81.26	64.53	43.26	75.34	76.81	76.06	92.63	85.62	85.68	71.71	88.15	87.47	87.81
VEC-MNER	86.11	81.03	62.86	40.60	74.56	75.23	74.89	93.88	81.27	85.49	73.40	87.42	87.61	87.51
SEPA	86.49	83.33	62.90	43.80	74.71	76.84	75.76	93.18	86.27	85.39	69.08	87.50	87.05	87.27
TCHV-BERT (Ours)	87.53	83.15	67.34	48.50	77.72	77.33	77.53	**95.31**	84.57	86.99	73.38	89.84	88.54	89.19
TCHV (Ours)	**87.71**	**83.57**	**68.16**	**50.25**	78.35	78.09	78.22	94.85	**87.03**	**88.18**	**79.44**	**90.64**	**89.76**	**90.20**
VLLM-based methods														
Llama3.2-11B-Vision (zero-shot)	75.43	68.98	36.52	26.05	49.29	70.72	58.09	85.48	63.37	61.05	24.36	58.78	71.77	64.63
Llama3.2-11B-Vision (4-shot)	76.98	68.23	37.57	24.15	50.35	70.20	58.64	87.28	65.91	66.41	30.15	64.19	74.83	69.10
Qwen2.5-VL-7B (zero-shot)	67.57	58.68	34.20	18.25	51.76	51.81	51.78	77.72	53.87	51.90	18.60	63.31	55.79	59.31
Qwen2.5-VL-7B (4-shot)	67.83	59.26	36.89	20.78	55.42	58.30	56.82	79.08	55.71	53.67	19.14	65.48	59.75	62.48
DeepSeek-VL-7B (zero-shot)	52.74	27.92	16.37	6.71	21.44	27.87	24.23	63.14	29.29	15.79	11.91	33.21	33.61	33.41
DeepSeek-VL-7B (4-shot)	57.04	28.01	18.83	9.13	26.48	31.51	28.78	64.27	47.92	38.01	12.99	35.33	49.89	41.36
PGIM	**88.34**	**84.22**	70.15	52.34	79.21	79.45	79.33	96.46	**89.89**	89.03	79.62	90.86	92.01	91.43
TCHV[†] (Ours)	88.16	83.39	**70.42**	**52.75**	78.50	79.29	78.89	**96.88**	88.63	**90.00**	**79.86**	91.02	92.90	91.95

Pat celebrating her 90th birthday with Emily Roux in Chez Roux at the Newmarket Guineas Festival. #weare350

(1) Pat:PER
(2) Emily Roux:PER
(3) Chez Roux:LOC
(4) Newmarket Guineas Festival:MISC
MAF: (1) ✓ (2) ✓
  (3) × **Roux:MISC** (4) ✓
UMT: (1) ✓ (2) ✓
  (3) × **Chez Roux:MISC** (4) ✓
TCHV: (1) ✓ (2) ✓ (3) ✓ (4) ✓

David Beckham sends message to Zinedine Zidane following Real Madrid's UCL win. Class!

(1) David Beckham:PER
(2) Zinedine Zidane:PER
(3) Real Madrid:ORG
(4) UCL:MISC
MAF: (1) ✓ (2) ✓
  (3) ✓ (4) × **UCL:ORG**
UMT: (1) ✓ (2) ✓
  (3) ✓ (4) × **UCL:ORG**
TCHV: (1) ✓ (2) ✓ (3) ✓ (4) ✓

Figure 3: Case study. TCHV resolves type ambiguity by verifying candidate entity-type hypotheses.

Table 2: Ablation study on Twitter-2017 (F1, %). Δ is the change from the full TCHV model.

Variant	F1	Δ
Full TCHV	90.20	–
Architecture ablations		
w/o Forward Prediction	89.14	-1.06
w/o Reverse Verification	89.41	-0.79
w/o Visual Relevance Gate	89.07	-1.13
w/o AdaLN (type concat.)	88.98	-1.22
Replace Latent Pred. with Cross-Attn	89.67	-0.53
Loss ablations		
w/o $\mathcal{L}_{ira}$ (alignment)	89.46	-0.74
w/o $\mathcal{L}_{ico}$ (contrastive)	89.10	-1.10
w/o $\mathcal{L}_{sig}$ (anti-collapse)	89.30	-0.90
w/o Stop-Gradient in $\mathcal{L}_{ira}$	89.91	-0.29

4.3 Ablation Study

Table 2 reports ablation results on Twitter-2017. Ablations test the forward and reverse branches, visual gate, type conditioning, and auxiliary objectives. Removing these modules, or replacing latent prediction with cross-attention, reduces F1, indicating that gains come from type-conditioned verification rather than simply adding another interaction layer. The largest drops come from type conditioning, the gate, and contrastive verification, which jointly separate competing type hypotheses and control unreliable visual evidence. The forward branch contributes by asking whether the image contains evidence expected by a span-type hypothesis, while the reverse branch checks whether the

visual evidence remains compatible with the textual span under that type. The visual gate is important because reverse verification can otherwise amplify irrelevant or noisy images; its removal causes a larger drop than removing the reverse branch alone.

Overall, the ablations show that TCHV gains from verifying type-compatible visual evidence before fusion.

4.4 Scalability to GMNER and FMNERG

TCHV extends to grounded and fine-grained settings by replacing patch-level visual evidence with detected proposal-level evidence and adding a lightweight region pointer. These experiments evaluate extensibility; full protocols and P/R/F1 breakdowns are in Appendix E. The gains over

Text: The Best Daytime Looks from the 2016 Cannes Film Festival | Entity: Cannes Film Festival | Gold/Pred: MISC -> MISC   Evidence strength: Low ▬▬▬ High

Figure 4: Type-evidence visualization. For the same image and mention, different entity-type hypotheses attend to different visual evidence, illustrating how type-conditioned verification separates plausible but competing type interpretations.

Table 3: Compact extension results. We report main-task F1 (%); full results are in Appendix E.

Method	GMNER	FMNERG
H-Index (Yu et al., 2023)	56.41	46.55
TIGER (Wang et al., 2023)	–	47.20
TCHV + Extension	**59.73**	**50.64**

Table 4: Parameter count and per-epoch runtime of TCHV. Trainable parameters exclude frozen backbone encoders.

Parameter count		
Trainable task-specific params	∼15M	
Setting	**Train only (s/epoch)**	**Train+Eval (s/epoch)**
Twitter-2015	35.8	51.8
Twitter-2017	30.5	43.6
GMNER	136.1	152.8
FMNERG	431.2	469.0

H-Index on GMNER and TIGER on FMNERG show that the same hypothesis-verification interface can be reused when the visual evidence becomes region-level or the label space becomes finer grained. This is useful because the span encoder and type-hypothesis scoring mechanism remain unchanged; only the visual evidence source and the optional grounding head are adapted.

4.5 Case Study

Figure 3 shows complementary failure modes: visual scenes can bias entity types, and visually related context can make event-like mentions resemble organizations. In both cases, useful but potentially misleading visual context must be interpreted under the correct candidate type rather than transferred directly into the final label. In the first example, "Chez Roux" contains the surname-like token "Roux" and appears in a social-event context, but the span-type hypothesis LOC expects venue evidence and separates the restaurant mention from nearby person mentions. In the second example, football imagery and the team name make "UCL" visually close to an organization, while hypothesis

verification favors the competition/event interpretation MISC.

Type-Evidence Visualization. Figure 4 shows that red-carpet context is visually related to people, but the model still verifies whether the event-oriented MISC hypothesis is better supported. The visualization supports the qualitative claim that type conditioning changes which visual regions are treated as evidence, rather than simply increasing attention to the whole image.

4.6 Efficiency Analysis

Table 4 reports parameter count and per-epoch runtime. TCHV freezes the pretrained encoders and trains only lightweight verification modules; the extra runtime mainly comes from scoring a small set of entity-type hypotheses. The "Train only" and "Train+Eval" measurements separate optimization cost from evaluation overhead, showing that the verification heads add modest cost while preserving the efficiency benefits of frozen backbones. Runtime increases in GMNER and FMNERG mainly reflect larger inputs and additional region-level evaluation, whereas the trainable parameter count stays about ∼15M because the verification modules are shared across datasets.

5 Conclusion

This paper proposes TCHV, a lightweight hypothesis-testing framework that formulates each span-type pair as a distinct hypothesis and verifies it through bidirectional text-image matching with a visual relevance gate. Extensive experiments on Twitter-2015 and Twitter-2017 demonstrate that TCHV consistently outperforms established MNER baselines. Further extensions to grounded and fine-grained settings confirm its generalizability. These results validate that explicit type-conditioned verification offers a more reliable way to leverage visual information than conventional relevance-oriented fusion.

6 Limitations

TCHV still depends on frozen textual and visual encoders, so its verification quality is bounded by the representations provided by these pretrained backbones. Extremely noisy, irrelevant, misleading, or underspecified images may still provide unreliable evidence, especially when the decisive cue is a small region, embedded text, or a subtle visual relation that is not well captured by global image features. The current design mainly verifies latent global or span-level evidence; finer region-level verification, explicit OCR-aware reasoning, and end-to-end grounding remain underexplored. Our extensions to grounded and fine-grained settings also depend on external proposal quality and predefined label inventories. More broadly, TCHV assumes a relatively small set of candidate entity types can be enumerated during inference, and scaling the same verification idea to open or very large type ontologies may require candidate retrieval, pruning, or calibration mechanisms. Generalization to other languages, platforms, domains, and distribution shifts therefore requires further study. Finally, the hypothesis-testing view is a surrogate-level explanation of verification scores, not a calibrated statistical test with finite-sample guarantees; future work should examine uncertainty estimation and reliability under stronger out-of-domain shifts.

7 Ethical Considerations

This work uses existing public multimodal NER benchmarks and does not collect new data or involve human participants. Since these benchmarks are derived from social-media posts, they may contain user-generated text, named entities, and images of real individuals, which raises privacy and consent concerns. We therefore intend our model and released code for research use only, and users should follow the licenses and terms of the original datasets.

TCHV may inherit biases from pretrained encoders and benchmark data, and its predictions may be unreliable for underrepresented groups, languages, platforms, or visually ambiguous cases. Misuse in surveillance, profiling, content moderation, or other high-stakes settings could cause harm. We discourage such deployment without additional privacy review, bias evaluation, and human oversight. To reduce computational cost, TCHV freezes large backbone encoders and trains only lightweight task-specific modules, but reproducing the experiments still requires GPU resources.

References

Mahmoud Assran, Quentin Duval, Ishan Misra, Piotr Bojanowski, Pascal Vincent, Michael Rabbat, Yann LeCun, and Nicolas Ballas. 2023. Self-supervised learning from images with a joint-embedding predictive architecture. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 15619–15629.

Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E. Hinton. 2016. Layer normalization. *arXiv preprint arXiv:1607.06450*.

Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, Jiabo Ye, Xi Zhang, Tianbao Xie, Zesen Cheng, Hang Zhang, Zhibo Yang, Haiyang Xu, and Junyang Lin. 2025. Qwen2.5-VL technical report. *arXiv preprint arXiv:2502.13923*.

Adrien Bardes, Quentin Garrido, Jean Ponce, Xinlei Chen, Michael Rabbat, Yann LeCun, Mahmoud Assran, and Nicolas Ballas. 2024. Revisiting feature prediction for learning visual representations from video. *arXiv preprint arXiv:2404.08471*.

Adrien Bardes, Jean Ponce, and Yann LeCun. 2022. VICReg: Variance-invariance-covariance regularization for self-supervised learning. In *International Conference on Learning Representations*.

Qian Chen, Xiaodan Zhu, Zhen-Hua Ling, Si Wei, Hui Jiang, and Diana Inkpen. 2017. Enhanced LSTM for natural language inference. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1657–1668, Vancouver, Canada. Association for Computational Linguistics.

Shuguang Chen, Gustavo Aguilar, Leonardo Neves, and Thamar Solorio. 2021. Can images help recognize entities? a study of the role of images for multimodal NER. In *Proceedings of the Seventh Workshop on Noisy User-generated Text (W-NUT 2021)*, pages 87–96, Online. Association for Computational Linguistics.

Xiang Chen, Ningyu Zhang, Lei Li, Yunzhi Yao, Shumin Deng, Chuanqi Tan, Fei Huang, Luo Si, and Huajun Chen. 2022. Good visual guidance make a better extractor: Hierarchical visual prefix for multimodal entity and relation extraction. In *Findings of the Association for Computational Linguistics: NAACL 2022*, pages 1607–1618, Seattle, United States. Association for Computational Linguistics.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1 (long and short papers)*, pages 4171–4186.

Guohui Ding, Yushuo Kong, and Xinlei Li. 2025. Sepa: An semantic projection alignment framework for multimodal named entity recognition. In *Proceedings of the 2025 International Conference on Multimedia Retrieval*, pages 202–210. Association for Computing Machinery.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. 2021. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*.

Quentin Garrido, Mahmoud Assran, Nicolas Ballas, Adrien Bardes, Laurent Najman, and Yann LeCun. 2024. Learning and leveraging world models in visual representation learning. *arXiv preprint arXiv:2403.00504*.

Zhiheng Huang, Wei Xu, and Kai Yu. 2015. Bidirectional lstm-crf models for sequence tagging. *arXiv preprint arXiv:1508.01991*.

Meihuizi Jia, Lei Shen, Xin Shen, Lejian Liao, Meng Chen, Xiaodong He, Zhendong Chen, and Jiaqi Li. 2023. MNER-QG: An end-to-end MRC framework for multimodal named entity recognition with query grounding. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 37, pages 8032–8040.

Yann LeCun. 2022. A path towards autonomous machine intelligence. *OpenReview preprint*.

Jinyuan Li, Han Li, Zhuo Pan, Di Sun, Jiahao Wang, Wenkun Zhang, and Gang Pan. 2023. Prompting chatgpt in mner: Enhanced multimodal named entity recognition with auxiliary refined knowledge. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 2787–2802.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. RoBERTa: A robustly optimized BERT pretraining approach. *arXiv preprint arXiv:1907.11692*.

Di Lu, Leonardo Neves, Vitor Carvalho, Ning Zhang, and Heng Ji. 2018. Visual attention model for name tagging in multimodal social media. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1990–1999, Melbourne, Australia. Association for Computational Linguistics.

Haoyu Lu, Wen Liu, Bo Zhang, Bingxuan Wang, Kai Dong, Bo Liu, Jingxiang Sun, Tongzheng Ren, Zhuoshu Li, Hao Yang, et al. 2024. Deepseek-vl: towards real-world vision-language understanding. *arXiv preprint arXiv:2403.05525*.

Meta AI. 2024. Llama 3.2 Vision Model Card.

Seungwhan Moon, Leonardo Neves, and Vitor Carvalho. 2018. Multimodal named entity recognition for short social media posts. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 852–860, New Orleans, Louisiana. Association for Computational Linguistics.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. 2018. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*.

Ankur Parikh, Oscar Täckström, Dipanjan Das, and Jakob Uszkoreit. 2016. A decomposable attention model for natural language inference. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 2249–2255, Austin, Texas. Association for Computational Linguistics.

William Peebles and Saining Xie. 2023. Scalable diffusion models with transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 4195–4205.

Ethan Perez, Florian Strub, Harm de Vries, Vincent Dumoulin, and Aaron Courville. 2018. FiLM: Visual reasoning with a general conditioning layer. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32.

Alan Ritter, Sam Clark, Mausam, and Oren Etzioni. 2011. Named entity recognition in tweets: An experimental study. In *Proceedings of the 2011 Conference on Empirical Methods in Natural Language Processing*, pages 1524–1534, Edinburgh, Scotland, UK. Association for Computational Linguistics.

Mohammad Golam Sohrab and Makoto Miwa. 2018. Deep exhaustive model for nested named entity recognition. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 2843–2849, Brussels, Belgium. Association for Computational Linguistics.

Asahi Ushio, Francesco Barbieri, Vitor Sousa, Leonardo Neves, and Jose Camacho-Collados. 2022. Named entity recognition in twitter: A dataset and analysis on short-term temporal shifts. In *Proceedings of the 2nd Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics and the 12th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 309–319, Online only. Association for Computational Linguistics.

Jieming Wang, Ziyan Li, Jianfei Yu, Li Yang, and Rui Xia. 2023. Fine-grained multimodal named entity

recognition and grounding with a generative framework. In *Proceedings of the 31st ACM International Conference on Multimedia*, MM '23, pages 3934–3943, New York, NY, USA. Association for Computing Machinery.

Xinyu Wang, Min Gui, Yong Jiang, Zixia Jia, Nguyen Bach, Tao Wang, Zhongqiang Huang, and Kewei Tu. 2022. ITA: Image-text alignments for multi-modal named entity recognition. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 3176–3189, Seattle, United States. Association for Computational Linguistics.

Ziqi Wang, Chen Zhu, Zhi Zheng, Xinhang Li, Tong Xu, Yongyi He, Qi Liu, Ying Yu, and Enhong Chen. 2024. Granular entity mapper: Advancing fine-grained multimodal named entity recognition and grounding. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 3211–3226, Miami, Florida, USA. Association for Computational Linguistics.

Pengfei Wei, Hongjun Ouyang, Qintai Hu, Bi Zeng, Guang Feng, and Qingpeng Wen. 2024. VEC-MNER: Hybrid transformer with visual-enhanced cross-modal multi-level interaction for multimodal NER. In *Proceedings of the 2024 International Conference on Multimedia Retrieval*, pages 469–477. Association for Computing Machinery.

Bo Xu, Shizhou Huang, Chaofeng Sha, and Hongya Wang. 2022. MAF: A general matching and alignment framework for multimodal named entity recognition. In *Proceedings of the Fifteenth ACM International Conference on Web Search and Data Mining*, WSDM '22, pages 1215–1223, New York, NY, USA. Association for Computing Machinery.

Yongxiu Xu, Hao Xu, Heyan Huang, Shiyao Cui, Minghao Tang, Longzheng Wang, and Hongbo Xu. 2024. An effective span-based multimodal named entity recognition with consistent cross-modal alignment. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 1063–1072, Torino, Italia. ELRA and ICCL.

Jianfei Yu, Jing Jiang, Li Yang, and Rui Xia. 2020. Improving multimodal named entity recognition via entity span detection with unified multimodal transformer. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 3342–3352, Online. Association for Computational Linguistics.

Jianfei Yu, Ziyan Li, Jieming Wang, and Rui Xia. 2023. Grounded multimodal named entity recognition on social media. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 9141–9154, Toronto, Canada. Association for Computational Linguistics.

Pengchuan Zhang, Xiujun Li, Xiaowei Hu, Jianwei Yang, Lei Zhang, Lijuan Wang, Yejin Choi, and Jianfeng Gao. 2021. VinVL: Revisiting visual representations in vision-language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 5579–5588.

Qi Zhang, Jinlan Fu, Xiaoyu Liu, and Xuanjing Huang. 2018. Adaptive co-attention network for named entity recognition in tweets. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 32.

Xin Zhang, Jingling Yuan, Lin Li, and Jianquan Liu. 2023. Reducing the bias of visual objects in multimodal named entity recognition. In *Proceedings of the Sixteenth ACM International Conference on Web Search and Data Mining*, WSDM '23, New York, NY, USA. Association for Computing Machinery.

Baohang Zhou, Ying Zhang, Kehui Song, Wenya Guo, Guoqing Zhao, Hongbin Wang, and Xiaojie Yuan. 2022. A span-based multimodal variational autoencoder for semi-supervised multimodal named entity recognition. In *Proceedings of the 2022 conference on empirical methods in natural language processing*, pages 6293–6302.

Appendix

A Related Work

Multimodal named entity recognition. Early MNER work studied multimodal social-media entity recognition and attention-based visual integration (Moon et al., 2018; Lu et al., 2018; Zhang et al., 2018). Later methods improved cross-modal interaction through unified multimodal transformers (Yu et al., 2020), matching and alignment frameworks (Xu et al., 2022; Wang et al., 2022), visual-context analysis and hierarchical visual prefixes (Chen et al., 2021, 2022), machine reading comprehension with query grounding (Jia et al., 2023), and debiasing strategies (Zhang et al., 2023). Recent span-level approaches include semi-supervised span-based MNER (Zhou et al., 2022), cross-modal span alignment (Xu et al., 2024), and semantic projection (Ding et al., 2025). Prior MNER studies mainly focus on improving how visual and textual representations interact, including cross-modal attention, alignment, fusion, prompt-based conditioning, and noise-aware visual filtering. These methods are effective at retrieving and incorporating visually related information. However, they typically do not explicitly ask whether the retrieved visual evidence supports one candidate entity type over another. TCHV is complementary to this line of work: it turns visual information from a relevance signal into a type-conditioned verification signal.

Latent prediction and JEPA. JEPA-style models predict target latent representations rather than reconstructing pixels (LeCun, 2022; Assran et al., 2023; Bardes et al., 2024). Recent work further studies latent world models and anti-collapse regularization (Garrido et al., 2024; Bardes et al., 2022). Our type-conditioned predictor uses adaptive conditioning related to FiLM and adaptive layer normalization (Perez et al., 2018; Peebles and Xie, 2023). Our work uses latent prediction in a task-specific sense: it predicts expected evidence under an entity-type hypothesis rather than generating images or modeling general environment dynamics.

B Additional Method Details

Table 5 summarizes how TCHV adapts latent predictive modeling to type-conditioned entity verification.

Table 5: Mapping from JEPA-style latent prediction to entity-type verification in TCHV.

JEPA-style Prediction	TCHV (Ours)
Context repr. $\mathbf{z}_{\text{ctx}}$	Span representation
Conditioning $\mathbf{c}$	Entity-type or null hypothesis
Predicted target $\hat{\mathbf{z}}_{\text{tar}}$	Expected visual evidence
Encoded target $\mathbf{z}_{\text{tar}}$	Observed visual evidence
Prediction loss	Evidence-reality alignment $\mathcal{L}_{\text{ira}}$
Anti-collapse reg.	Variance/covariance regularizer $\mathcal{L}_{\text{sig}}$

B.1 Predictor Architecture

The type-conditioned latent evidence predictor consists of an input projection, M AdaLN blocks, and an output projection. The input projection maps $\mathbf{z}_{\text{span}}$ into an intermediate space:

$$\mathbf{h}^{(0)} = \sigma(\mathbf{W}_{\text{in}}\mathbf{z}_{\text{span}} + \mathbf{b}_{\text{in}}) \in \mathbb{R}^{d_p},$$

where σ is GELU. Each AdaLN block $\ell \in \{1, \ldots, M\}$ performs:

$$(\boldsymbol{\gamma}_\ell, \boldsymbol{\beta}_\ell) = \text{MLP}_\ell(\mathbf{e}_k), \tag{5}$$
$$\bar{\mathbf{h}}^{(\ell)} = (1 + \boldsymbol{\gamma}_\ell) \odot \text{LN}(\mathbf{h}^{(\ell-1)}) + \boldsymbol{\beta}_\ell,$$
$$\tilde{\mathbf{h}}^{(\ell)} = \mathbf{h}^{(\ell-1)} + \mathbf{W}_\ell^{\text{mix}}\bar{\mathbf{h}}^{(\ell)}, \tag{6}$$
$$\mathbf{h}^{(\ell)} = \tilde{\mathbf{h}}^{(\ell)} + \text{FFN}\big(\text{LN}(\tilde{\mathbf{h}}^{(\ell)})\big),$$

where LN is Layer Normalization (Ba et al., 2016); the type-conditioned affine modulation is related to feature-wise conditioning and adaptive layer normalization (Perez et al., 2018; Peebles and Xie, 2023). Here, $\boldsymbol{\gamma}_\ell, \boldsymbol{\beta}_\ell \in \mathbb{R}^{d_p}$ are affine parameters generated from type hypothesis $\mathbf{e}_k$, $\mathbf{W}_\ell^{\text{mix}} \in \mathbb{R}^{d_p \times d_p}$ is a linear mixing layer, and FFN is a two-layer network with GELU and expansion factor 2. The output projection yields $\hat{\mathbf{z}}_k^v = \mathbf{W}_{\text{out}}\text{LN}(\mathbf{h}^{(M)}) \in \mathbb{R}^d$.

The last linear layer of the conditioning MLP in Eq. (5) is zero-initialized, following adaptive conditioning practice in Diffusion Transformers (Peebles and Xie, 2023), so that type conditioning takes effect progressively. Since each predictor input is a single vector, self-attention provides no token-mixing benefit; we replace it with the linear mixing layer in Eq. (6).

B.2 Training Objective Details

Let $\mathcal{Y} = \{y_0\} \cup \mathcal{Y}^+$, where y_0 is O and $\mathcal{Y}^+$ denotes the set of entity types. Let $\mathcal{E} = \{s = (i, j) \in \mathcal{S}(\mathbf{x}) : y_s \in \mathcal{Y}^+\}$ be the set of gold entity spans. The task classification loss is computed over all

candidate spans and the full label set:

$$\mathcal{L}_{\text{task}} = -\frac{1}{|\mathcal{S}|} \sum_{(i,j)\in\mathcal{S}} \sum_{k=0}^{K-1} w_k \, \tilde{y}_k^{(i,j)} \log \hat{y}_k^{(i,j)},$$

where $\tilde{y}_k^{(i,j)}$ is the label-smoothed target and $w_0 < 1$ down-weights the dominant non-entity class.

For non-O entity spans, the evidence-reality alignment loss aligns the predicted visual evidence expectation of the ground-truth entity type with the attended real visual evidence:

$$\mathcal{L}_{\text{ira}} = \frac{1}{|\mathcal{E}|} \sum_{(i,j)\in\mathcal{E}} \left\| \hat{\mathbf{z}}_{y_{(i,j)}}^{v} - \text{sg}(\mathbf{z}_{y_{(i,j)}}^{v,\text{att}}) \right\|_2^2, \quad (7)$$

where $\text{sg}(\cdot)$ stops gradient flow through its argument. The evidence contrastive loss is an InfoNCE-style objective (Oord et al., 2018):

$$\mathcal{L}_{\text{ico}} = -\frac{1}{|\mathcal{E}|} \sum_{(i,j)\in\mathcal{E}} \log \frac{\exp\!\left(s_{y_{(i,j)}}^{\text{fwd}}/\tau\right)}{\sum_{k=0}^{K-1} \exp\!\left(s_k^{\text{fwd}}/\tau\right)},$$

where $\tau > 0$ is a temperature hyperparameter.

We use a VICReg-style variance-covariance regularizer to prevent predicted latent evidence representations from collapsing (Bardes et al., 2022):

$$\mathcal{L}_{\text{sig}} = \frac{1}{d} \sum_{j=1}^{d} \max\!\left(0, \, 1 - \text{std}_j(\hat{\mathbf{Z}}^v)\right)^2$$
$$+ \frac{1}{d(d-1)} \sum_{i\neq j} \mathbf{C}_{ij}^2, \quad (8)$$

where $\hat{\mathbf{Z}}^v = \{\hat{\mathbf{z}}_{s,k}^v \mid s \in \mathcal{E}, \, k \in \mathcal{Y}\}$ collects all type hypotheses for gold entity spans, including the null hypothesis but excluding O spans; std_j is the per-dimension standard deviation, and $\mathbf{C}_{ij}$ is the (i,j)-th entry of the sample covariance matrix $\mathbf{C}$. The first term penalizes dimensional collapse through a squared hinge, and the second decorrelates dimensions.

The gate-weighted reverse alignment loss mirrors Eq. (7):

$$\mathcal{L}'_{\text{ira},g} = \frac{1}{|\mathcal{E}|} \sum_{s\in\mathcal{E}} \text{sg}(g_s) \left\| \hat{\mathbf{z}}_{s,y_s}^{t} - \text{sg}(\mathbf{z}_{\text{span},s}) \right\|_2^2.$$

We stop gradients through g_s in auxiliary reverse losses so that the gate cannot reduce these losses by simply closing the reverse path. The gate-weighted reverse contrastive loss is

$$\mathcal{L}'_{\text{ico},g} = -\frac{1}{|\mathcal{E}|} \sum_{s\in\mathcal{E}} \text{sg}(g_s) \log \frac{\exp\!\left(s_{s,y_s}^{\text{rev}}/\tau\right)}{\sum_{k\in\mathcal{Y}} \exp\!\left(s_{s,k}^{\text{rev}}/\tau\right)}.$$

The reverse anti-collapse loss $\mathcal{L}'_{\text{sig}}$ follows Eq. (8) applied to predicted textual evidence representations $\hat{\mathbf{Z}}^t = \{\hat{\mathbf{z}}_{s,k}^t \mid s \in \mathcal{E}, \, k \in \mathcal{Y}\}$. Because anti-collapse regularization prevents predictor collapse rather than supervising evidence matching, we do not gate the reverse anti-collapse term. If a mini-batch contains no gold entity spans, we skip the auxiliary verification losses and optimize only $\mathcal{L}_{\text{task}}$.

C Additional Statistical Interpretation

Hypothesis-testing setup. Let $\mathcal{Y} = \{y_0\} \cup \mathcal{Y}^+$, where y_0 denotes the O/null class and $\mathcal{Y}^+$ denotes non-O entity types. For a candidate span u, let $Y_u \in \mathcal{Y}$ be its gold label. For each non-O type $k \in \mathcal{Y}^+$, MNER can be interpreted as a binary hypothesis test:

$$H_0^{u,k} : Y_u \neq k, \qquad H_1^{u,k} : Y_u = k.$$

The null hypothesis is composite: the span may be a non-entity, or it may be an entity of another type. The O label therefore acts as the non-entity null class in final classification, while non-O labels correspond to type-specific alternatives.

Information-theoretic implication. Let $Y^\star$ denote the gold non-O entity type for spans in the gold entity set $\mathcal{E}$, and let $\mathbf{F} = \mathbf{s}^{\text{fwd}}$. The forward contrastive objective implies

$$I(Y^\star; \mathbf{F}) \geq H(Y^\star) - \mathcal{L}_{\text{ico}}.$$

Under a uniform prior over non-O entity types,

$$I(Y^\star; \mathbf{F}) \geq \log |\mathcal{Y}^+| - \mathcal{L}_{\text{ico}}.$$

Thus, reducing $\mathcal{L}_{\text{ico}}$ both increases the soft evidence-ratio margin in Proposition 1 and makes the forward verification scores more informative about the entity type.

Score separation and testing error. For a threshold c_k, define the analytical test

$$\varphi_{u,k} = \mathbf{1}[T_{u,k} > c_k].$$

The type-I and type-II errors are

$$\alpha_k = \Pr_{H_0^{u,k}} (T_{u,k} > c_k),$$
$$\beta_k = \Pr_{H_1^{u,k}} (T_{u,k} \leq c_k).$$

Let $\mu_{0,k} = \mathbb{E}[T_{u,k} \mid H_0^{u,k}]$, $\mu_{1,k} = \mathbb{E}[T_{u,k} \mid H_1^{u,k}]$, and $\Delta_k = \mu_{1,k} - \mu_{0,k}$. A larger Δ_k means that the verification statistic is better separated under the alternative and the null.

Proposition 3 (Score separation reduces testing error). *Suppose $T_{u,k}$ is sub-Gaussian with variance proxy σ^2 under both $H_0^{u,k}$ and $H_1^{u,k}$, and suppose $\Delta_k > 0$. If an oracle midpoint threshold is chosen as*

$$c_k = \frac{\mu_{0,k} + \mu_{1,k}}{2}, \qquad (9)$$

then

$$\alpha_k \le \exp\left(-\frac{\Delta_k^2}{8\sigma^2}\right), \qquad \beta_k \le \exp\left(-\frac{\Delta_k^2}{8\sigma^2}\right).$$

This proposition is an analytical concentration result, not a claim that TCHV implements calibrated p-values or uses the oracle threshold in Eq. (9). It shows that, under the sub-Gaussian assumption, any achieved increase in Δ_k improves the error exponent. The contrastive loss $\mathcal{L}_{\text{ico}}$ promotes relative score separation, $\mathcal{L}_{\text{ira}}$ encourages predicted evidence to match observed evidence, and $\mathcal{L}_{\text{sig}}$ reduces degenerate cases in which type-conditioned evidence predictions become indistinguishable.

Multiple span-type tests and decoding. MNER requires many simultaneous span-type decisions:

$$\mathcal{H} = \{H_0^{u,k} : u \in \mathcal{S}(\mathbf{x}),\ k \in \mathcal{Y}^+\}.$$

At inference, the implementation selects the best non-O type $k_u^\star = \arg\max_{k \in \mathcal{Y}^+} o_{u,k}$ and retains span u only if the entity-vs-null margin $m_u = o_{u,k_u^\star} - o_{u,0}$ exceeds a development-tuned threshold δ. Overlapping predicted spans are then resolved greedily by confidence. This margin is a practical empirical rejection threshold rather than formal false-discovery control. Future work could add calibration data to convert one-vs-rest verification statistics into empirical or conformal p-values under the composite null.

D Proofs

D.1 Proof of Proposition 1

For a gold entity span u with label $y \in \mathcal{Y}^+$, the forward contrastive loss is

$$\ell_u^{\text{fwd}} = -\log \frac{\exp(F_{u,y}/\tau)}{\sum_{k\in\mathcal{Y}} \exp(F_{u,k}/\tau)}.$$

Let

$$a_k = \frac{F_{u,k}}{\tau}.$$

Then

$$\ell_u^{\text{fwd}} = -\log \frac{\exp(a_y)}{\exp(a_y) + \sum_{\ell\in\mathcal{Y}\setminus\{y\}} \exp(a_\ell)}.$$

Rearranging,

$$\ell_u^{\text{fwd}} = \log \left(1 + \sum_{\ell\in\mathcal{Y}\setminus\{y\}} \exp(a_\ell - a_y) \right). \tag{10}$$

By definition,

$$\Lambda_{u,y}^{\text{fwd}} = a_y - \log \frac{1}{K-1} \sum_{\ell\in\mathcal{Y}\setminus\{y\}} \exp(a_\ell). \tag{11}$$

Exponentiating the negative of Eq. (11), we obtain

$$\exp(-\Lambda_{u,y}^{\text{fwd}}) = \exp(-a_y) \cdot \frac{1}{K-1} \sum_{\ell\in\mathcal{Y}\setminus\{y\}} \exp(a_\ell).$$

Therefore,

$$\sum_{\ell\in\mathcal{Y}\setminus\{y\}} \exp(a_\ell - a_y) = (K-1)\exp(-\Lambda_{u,y}^{\text{fwd}}). \tag{12}$$

Substituting Eq. (12) into Eq. (10) gives Eq. (4). Finally, the derivative with respect to $\Lambda_{u,y}^{\text{fwd}}$ is

$$\frac{\partial \ell_u^{\text{fwd}}}{\partial \Lambda_{u,y}^{\text{fwd}}} = -\frac{(K-1)\exp(-\Lambda_{u,y}^{\text{fwd}})}{1 + (K-1)\exp(-\Lambda_{u,y}^{\text{fwd}})} < 0.$$

Thus, the instance-wise loss is strictly decreasing in $\Lambda_{u,y}^{\text{fwd}}$. This proves Proposition 1.

The evidence-ratio interpretation is surrogate-level. If $\exp(F_{u,k}/\tau)$ is treated as an unnormalized evidence likelihood for type hypothesis k, then the second term in Eq. (11) is a smooth mixture approximation of the composite null evidence over competing hypotheses. Without this modeling assumption, $\Lambda_{u,y}^{\text{fwd}}$ should be read as a logit-level evidence-ratio surrogate rather than a calibrated likelihood ratio.

D.2 Proof of the Information-Theoretic Corollary

Let $Y^\star$ denote the gold non-O entity type for spans in $\mathcal{E}$, so $Y^\star \in \mathcal{Y}^+$. Let $\mathbf{F} = \mathbf{s}^{\text{fwd}}$. Define the full softmax distribution over $\mathcal{Y}$ as

$$q_k(\mathbf{F}) = \frac{\exp(\mathbf{F}_k/\tau)}{\sum_{j\in\mathcal{Y}} \exp(\mathbf{F}_j/\tau)}.$$

The implemented evidence contrastive loss can be written as

$$\mathcal{L}_{\text{ico}} = \mathbb{E}_{Y^\star,\mathbf{F}} \left[-\log q_{Y^\star}(\mathbf{F}) \right].$$

Although the denominator includes the O/null class, the positive label is always non-O. Normalize the predictive distribution over non-O labels:

$$Q_+(\mathbf{F}) = \sum_{k\in\mathcal{Y}^+} q_k(\mathbf{F}), \qquad \bar{q}_k(\mathbf{F}) = \frac{q_k(\mathbf{F})}{Q_+(\mathbf{F})}, \quad k \in \mathcal{Y}^+.$$

Since $Q_+(\mathbf{F}) \leq 1$, for $Y^\star \in \mathcal{Y}^+$ we have

$$-\log q_{Y^\star}(\mathbf{F}) = -\log \bar{q}_{Y^\star}(\mathbf{F}) - \log Q_+(\mathbf{F}) \geq -\log \bar{q}_{Y^\star}(\mathbf{F}).$$

Taking expectations gives

$$\mathcal{L}_{\text{ico}} \geq \mathbb{E}_{Y^\star,\mathbf{F}}\left[-\log \bar{q}_{Y^\star}(\mathbf{F})\right]. \tag{13}$$

The right-hand side is the cross-entropy of the normalized non-O classifier. By the standard cross-entropy decomposition,

$$\begin{aligned}
\mathbb{E}_{Y^\star,\mathbf{F}}\left[-\log \bar{q}_{Y^\star}(\mathbf{F})\right] &= H(Y^\star \mid \mathbf{F}) \\
&\quad + \mathbb{E}_{\mathbf{F}}\left[D_{\text{KL}}\big(p(Y^\star \mid \mathbf{F}) \,\|\, \bar{q}(\cdot \mid \mathbf{F})\big)\right] \\
&\geq H(Y^\star \mid \mathbf{F}).
\end{aligned} \tag{14}$$

Combining Eq. (13) and Eq. (14),

$$H(Y^\star \mid \mathbf{F}) \leq \mathcal{L}_{\text{ico}}.$$

Therefore,

$$I(Y^\star; \mathbf{F}) = H(Y^\star) - H(Y^\star \mid \mathbf{F}) \geq H(Y^\star) - \mathcal{L}_{\text{ico}}.$$

If the non-O entity types are uniformly distributed, then

$$H(Y^\star) = \log|\mathcal{Y}^+| = \log(K-1),$$

and hence

$$I(Y^\star; \mathbf{F}) \geq \log|\mathcal{Y}^+| - \mathcal{L}_{\text{ico}}.$$

This proves the information-theoretic corollary. The same normalization argument applies to reverse scores when the corresponding reverse contrastive objective is considered without reliability weighting. The implemented $\mathcal{L}'_{\text{ico},g}$ uses stop-gradient gate weights as a reliability-aware training variant, and should not be read as changing the mutual-information identity itself.

D.3 Proof of Proposition 3

Fix a type k and omit k from the notation for clarity. Let

$$\mu_0 = \mathbb{E}[T \mid H_0], \qquad \mu_1 = \mathbb{E}[T \mid H_1], \qquad \Delta = \mu_1 - \mu_0 > 0.$$

Assume T is sub-Gaussian with variance proxy σ^2 under both hypotheses. That is, for any $t > 0$,

$$\Pr_{H_0}(T - \mu_0 \geq t) \leq \exp\left(-\frac{t^2}{2\sigma^2}\right), \tag{15}$$

and

$$\Pr_{H_1}(\mu_1 - T \geq t) \leq \exp\left(-\frac{t^2}{2\sigma^2}\right). \tag{16}$$

Choose the oracle midpoint threshold

$$c = \frac{\mu_0 + \mu_1}{2} = \mu_0 + \frac{\Delta}{2} = \mu_1 - \frac{\Delta}{2}.$$

The type-I error is

$$\alpha = \Pr_{H_0}(T > c) = \Pr_{H_0}\left(T - \mu_0 > \frac{\Delta}{2}\right).$$

By Eq. (15),

$$\alpha \leq \exp\left(-\frac{(\Delta/2)^2}{2\sigma^2}\right) = \exp\left(-\frac{\Delta^2}{8\sigma^2}\right).$$

Similarly, the type-II error is

$$\beta = \Pr_{H_1}(T \le c) = \Pr_{H_1}\left(\mu_1 - T \ge \frac{\Delta}{2}\right).$$

By Eq. (16),

$$\beta \le \exp\left(-\frac{(\Delta/2)^2}{2\sigma^2}\right) = \exp\left(-\frac{\Delta^2}{8\sigma^2}\right).$$

This proves Proposition 3.

This proof uses an oracle midpoint threshold that depends on μ_0 and μ_1. The actual implementation instead tunes an entity-vs-null margin on the development set. Therefore, Proposition 3 should be interpreted as a concentration-based analytical explanation of why larger separation is beneficial, not as a statement that the implemented decoder achieves the exact bound.

A related threshold choice gives an explicit significance-level interpretation. For a desired type-I upper bound α_0, choose

$$c_{\alpha_0} = \mu_0 + \sigma\sqrt{2\log(1/\alpha_0)}.$$

Then

$$\Pr_{H_0}(T > c_{\alpha_0}) \le \alpha_0.$$

Under H_1,

$$\beta = \Pr_{H_1}(T \le c_{\alpha_0}) = \Pr_{H_1}\left(\mu_1 - T \ge \Delta - \sigma\sqrt{2\log(1/\alpha_0)}\right).$$

If

$$\Delta > \sigma\sqrt{2\log(1/\alpha_0)},$$

then

$$\beta \le \exp\left(-\frac{\left(\Delta - \sigma\sqrt{2\log(1/\alpha_0)}\right)^2}{2\sigma^2}\right).$$

This shows that increasing the separation Δ improves power at a fixed type-I error level under the same concentration assumption.

D.4 Proof of Proposition 2

Let

$$F = F_{u,k}, \qquad G = G_{u,k} = g_u R_{u,k}.$$

The bidirectional statistic is

$$T_\rho = F + \rho G.$$

Define the forward separation and gated reverse separation as

$$\Delta_f = \mathbb{E}[F \mid H_1] - \mathbb{E}[F \mid H_0],$$
$$\Delta_g = \mathbb{E}[G \mid H_1] - \mathbb{E}[G \mid H_0].$$

The separation of the combined statistic is

$$\Delta(\rho) = \mathbb{E}[T_\rho \mid H_1] - \mathbb{E}[T_\rho \mid H_0] = \Delta_f + \rho\Delta_g.$$

Assume F and G are independent sub-Gaussian statistics under both hypotheses, with variance proxies σ_f^2 and σ_g^2. Then T_ρ is sub-Gaussian with variance proxy

$$\sigma^2(\rho) = \sigma_f^2 + \rho^2\sigma_g^2.$$

From Proposition 3, the testing error exponent is controlled by the signal-to-noise ratio

$$J(\rho) = \frac{\Delta(\rho)^2}{\sigma^2(\rho)} = \frac{(\Delta_f + \rho\Delta_g)^2}{\sigma_f^2 + \rho^2\sigma_g^2}.$$

The forward-only statistic corresponds to $\rho = 0$:

$$J(0) = \frac{\Delta_f^2}{\sigma_f^2}.$$

The derivative of $J(\rho)$ at $\rho = 0$ is

$$J'(0) = \frac{2\Delta_f\Delta_g}{\sigma_f^2}.$$

If $\Delta_f > 0$ and $\Delta_g > 0$, then $J'(0) > 0$. Therefore, there exists a sufficiently small $\rho > 0$ such that

$$J(\rho) > J(0).$$

Since the concentration bound in Proposition 3 improves as $J(\rho)$ increases, the bidirectional statistic can yield a more powerful test than the forward-only statistic when gated reverse verification provides positive additional separation. This proves the first part of Proposition 2.

Next suppose reverse evidence contributes no useful separation under unreliable visual evidence, so $\Delta_g \approx 0$. Under the same independence assumption,

$$J(\rho) \approx \frac{\Delta_f^2}{\sigma_f^2 + \rho^2\sigma_g^2} \le \frac{\Delta_f^2}{\sigma_f^2} = J(0).$$

Thus, adding uninformative reverse evidence can increase variance without improving separation. If the gate learns $g_u \approx 0$ for unreliable images, then $G = g_u R_{u,k} \approx 0$, and the statistic effectively reverts to the forward-only case. This proves the reliability-gating claim under the stated assumptions.

In practice, F and G need not be exactly independent. A more general local condition can be stated by writing the variance proxy as

$$\sigma^2(\rho) = \sigma_f^2 + 2\rho\kappa + \rho^2\sigma_g^2,$$

where κ represents a covariance proxy between F and G. Then

$$J(\rho) = \frac{(\Delta_f + \rho\Delta_g)^2}{\sigma_f^2 + 2\rho\kappa + \rho^2\sigma_g^2}.$$

A direct derivative calculation gives

$$J'(0) = \frac{2\Delta_f(\Delta_g\sigma_f^2 - \Delta_f\kappa)}{\sigma_f^4}.$$

Therefore, when $\Delta_f > 0$, a sufficient condition for small positive ρ to improve the signal-to-noise ratio is

$$\Delta_g\sigma_f^2 > \Delta_f\kappa.$$

This correlated-case condition makes explicit that reverse verification is beneficial when its additional separation is large enough to offset any covariance-induced increase in effective variance.

Table 6: Results on GMNER. We report P/R/F1 (%) for GMNER, MNER, and EEG, following H-Index ([Yu et al., 2023]). Within this table, best and second-best scores are highlighted in bold and underline, respectively.

Method	GMNER			MNER			EEG		
	P	R	F1	P	R	F1	P	R	F1
Text-only methods									
HBiLSTM-CRF-None	43.56	40.69	42.07	78.80	72.61	75.58	49.17	45.92	47.49
BERT-None	42.18	43.76	42.96	77.26	77.41	77.30	46.76	48.52	47.63
BERT-CRF-None	42.73	44.88	43.78	77.23	78.64	77.93	46.92	49.28	48.07
BARTNER-None	44.61	45.04	44.82	79.67	79.98	79.83	48.77	49.23	48.99
Text+Image methods									
GVATT-RCNN-EVG	49.36	47.80	48.57	78.21	74.39	76.26	54.19	52.48	53.32
UMT-RCNN-EVG	49.16	51.48	50.29	77.89	79.28	78.58	53.55	56.08	54.78
UMT-VinVL-EVG	50.15	52.52	51.31	77.89	79.28	78.58	54.35	56.91	55.60
UMGF-VinVL-EVG	51.62	51.72	51.67	79.02	78.64	78.83	55.68	55.80	55.74
ITA-VinVL-EVG	52.37	50.77	51.56	80.40	78.37	79.37	56.57	54.84	55.69
BARTMNER-VinVL-EVG	52.47	52.43	52.45	80.65	**80.14**	**80.39**	55.68	55.63	55.66
H-Index	56.16	56.67	56.41	79.37	80.10	79.73	60.90	61.46	61.18
TCHV + Extension	**62.23**	**57.41**	**59.73**	**83.59**	77.11	80.22	**65.64**	60.56	**63.00**

Table 7: Results on FMNERG. We report P/R/F1 (%) for FMNERG, FMNER, and EEG, following TIGER ([Wang et al., 2023]). Within this table, best and second-best scores are highlighted in bold and underline, respectively.

Method	FMNERG			FMNER			EEG		
	P	R	F1	P	R	F1	P	R	F1
Text-only methods									
HBiLSTM-CRF-None	34.86	32.38	33.57	62.31	56.55	59.29	49.25	43.27	46.07
BERT-None	33.28	34.28	33.77	58.91	60.05	59.47	46.27	47.65	46.94
BERT-CRF-None	34.41	35.51	34.95	60.06	61.38	60.72	46.93	48.44	47.67
T5-Paraphrase-None	37.38	37.29	37.33	64.83	65.32	65.07	49.03	48.91	48.97
Text+Image methods									
GVATT-VinVL-EVG	42.02	38.75	40.32	63.08	57.85	60.35	55.27	53.46	54.35
UMT-VinVL-EVG	40.67	41.99	41.32	61.24	62.01	61.63	53.58	55.32	54.43
UMGF-VinVL-EVG	41.73	42.11	41.92	61.68	61.90	61.79	54.51	55.00	54.75
ITA-VinVL-EVG	43.05	42.51	42.78	63.80	62.64	63.21	57.63	56.90	57.26
H-Index	46.83	46.28	46.55	65.25	64.45	64.84	60.82	60.10	60.46
MMT5-VinVL-EVG	45.35	45.08	45.21	66.46	**66.77**	66.61	58.35	58.01	58.18
TIGER	47.57	46.85	47.20	64.43	65.40	64.91	62.44	**61.49**	61.96
TCHV + Extension	**53.05**	**48.44**	**50.64**	**70.39**	64.22	**67.16**	**66.74**	60.93	**63.70**

E Grounded and Fine-Grained Extension Results

For GMNER and FMNERG, we follow the official evaluation protocols and report the main grounded metric together with the corresponding text-only entity recognition metric and the EEG metric. The comparisons are intended to evaluate the extensibility of TCHV rather than make leaderboard claims on grounded benchmarks.

F Experimental Details

F.1 Dataset Statistics

Table 8 summarizes the dataset statistics for standard MNER and the grounded/fine-grained extension benchmarks.

Table 8: Dataset statistics. Train/Dev/Test report text-image posts; Ent. and Grd. report total entity and groundable-entity annotations when available.

Dataset	Train	Dev	Test	Ent.	Grd.
Twitter-2015	4,000	1,000	3,257	–	–
Twitter-2017	3,373	723	723	–	–
Twitter-GMNER	7,000	1,500	1,500	16,778	6,716
Twitter-FMNERG	7,000	1,500	1,500	16,772	6,770

F.2 Hyperparameters

Table 9 lists all hyperparameters.

For TCHV-BERT, the text encoder is replaced with frozen BERT-base, while all other hyperparameters in Table 9 remain unchanged.

Table 9: Full hyperparameter configuration.

Hyperparameter	Value
Model	
Text encoder	RoBERTa-base (125M)
Image encoder	ViT-Base/16 (86M)
Shared dimension d	384
Type embedding dimension d_e	128
Predictor hidden dimension d_p	512
Predictor layers M	4
FFN expansion factor	2
Comparator hidden dimension	256
Classifier hidden dimension	256
Width embedding dimension d_w	32
Maximum span length L	4
Maximum sequence length	128
Training	
Epochs	50
Batch size	16
Encoder learning rate	0 (frozen)
New module learning rate	1×10^{-4}
Weight decay	0.01
Warmup ratio	0.06
LR scheduler	Cosine decay
Max gradient norm	1.0
Mixed precision	FP16
EMA decay	0.995
Loss	
α (forward alignment)	1.0
α' (reverse alignment)	1.0
β (forward contrastive)	0.5
β' (reverse contrastive)	0.5
γ (forward anti-collapse)	0.05
γ' (reverse anti-collapse)	0.05
Temperature τ	0.07
Label smoothing	0.02
Non-entity weight w_0	0.25

F.3 Computing Environment

All experiments were conducted on a Linux server equipped with an Intel Xeon Platinum 8580 CPU and approximately 503 GiB system memory. Model training was performed on a single NVIDIA H200 NVL GPU with about 140 GB memory. The software environment was managed with Conda. We used Python 3.11.9 and PyTorch 2.6.0+cu124. The NVIDIA driver version was 570.195.03; the CUDA Runtime version was 12.8, while PyTorch was built against CUDA 12.4. The main dependencies included Transformers 5.4.0, NumPy 1.26.4, Pillow 12.1.0, and scikit-learn 1.8.0. FP16 mixed-precision training was enabled for the standard MNER experiments, and VinVL region features were used for the GMNER/FMNERG experiments.

F.4 VLLM-Based Offline Knowledge Enhancement

For VLLM-enhanced methods such as TCHV†, we use pretrained vision-language large models to generate additional semantic cues for each text-image sample, including entity-related descriptions, visual context, and cross-modal alignment information, and inject these cues as auxiliary knowledge into the MNER model. For fair comparison, the VLLMs are used only for offline knowledge enhancement and do not participate in downstream parameter updates; all other training settings, random seeds, data splits, backbone hyperparameters, and decoding settings are kept the same as their non-enhanced counterparts.

F.5 Data Preprocessing

Sentences are tokenized with the RoBERTa tokenizer (maximum 128 sub-word tokens). We maintain a word-to-token alignment map to recover span boundaries in token space. Candidate spans are enumerated for all (i, j) pairs with $j - i + 1 \leq L$; spans extending beyond the sentence are discarded. The maximum number of candidate spans per sentence is capped at 192.

Images are resized to 224×224 pixels using the standard ViT preprocessing pipeline, yielding $N = 14 \times 14 = 196$ patch tokens plus one `[CLS]` token.

F.6 Margin Threshold Tuning

At inference, we apply a margin-based decoding strategy. For each candidate span u, we first select $k_u^{\star} = \arg\max_{k \in \mathcal{Y}+} o_{u,k}$ and compute $m_u = o_{u,k_u^{\star}} - o_{u,0}$ using the pre-softmax logits $\mathbf{o}_u$, i.e., the margin between the highest entity-type logit and the non-entity logit. A span is predicted as an entity only if $m_u > \delta$, where δ is selected on the dev set by grid search over $[0.0, 2.0]$ with step 0.01. Conflicts are resolved by greedy non-overlapping selection, preferring higher-margin spans.

F.7 Extension to GMNER and FMNERG

For GMNER and FMNERG, we keep the span-level TCHV backbone unchanged and replace image-patch visual evidence with proposal-level visual evidence because grounded prediction requires region-level outputs (Yu et al., 2023). The proposal encoder provides region features, region boxes, and region masks, which serve as the observed visual evidence for grounding (Zhang et al., 2021). The type-conditioned latent prediction and verification modules are reused to produce entity-type verification scores for each candidate span.

To support grounded prediction, we attach a lightweight region pointer on top of TCHV. The pointer scores candidate proposal regions using the

span representation and type-aware verification features. Therefore, the grounded extension can be viewed as adding a region selection branch to the same span-level hypothesis-verification architecture.

For GMNER (Yu et al., 2023), the model predicts entity-type-region triples using the standard coarse entity type space. For FMNERG (Wang et al., 2023), the type hypothesis bank and classifier are expanded to the fine-grained label space, while the same grounding head is retained. Coarse-to-fine calibration and auxiliary knowledge injection, when used, act as lightweight enhancements to fine-grained classification rather than changes to the TCHV backbone; this is consistent with recent fine-grained grounded MNERG studies (Wang et al., 2024). All grounded results are evaluated using the official protocols of the corresponding benchmarks.