Towards Agentic Failure Analysis:
A Minimal Trace-Level Diagnostic for Chain-of-Thought Reasoning

Abstract

Single-turn chain-of-thought (CoT) prompting is often evaluated by final-answer accuracy. Under injected bias, however, accuracy can collapse into two distinct cases: a model may give the same final answer while either referencing the injected content in its reasoning trace or not mentioning it at all. We study this as a measurement blind spot and introduce a minimal trace-level diagnostic for separating these cases. For each biased trial, we measure two axes: *susceptibility* (whether the bias breaks a previously correct answer) and *acknowledgment* (whether the trace contains a rubric-defined surface reference to the injected content). Across thousands of biased GSM8K trials, GPT-4o and Claude Sonnet 4 have similar susceptibility rates (1.3% vs. 1.2%) but substantially different acknowledgment rates (13.0% vs. 75.0%) under the same rubric. We do not evaluate multi-step agent systems. Instead, we use single-turn CoT under bias as a controlled local-step setting for measuring trace-level behavior, with the goal of informing future failure analysis in longer agentic trajectories.

1. Introduction

A trajectory that invokes tools, reads from memory, and accumulates intermediate reasoning over many steps can break in any of those steps. Final-trajectory accuracy collapses the whole run into a single right/wrong signal and does not say where the failure originated. We ask whether the intermediate text a model produces carries enough signal to localize such a failure. Before asking that in a full agentic setting (with tools, memory, and multi-step state), we want a controlled testbed in which the trace, the bias, and the failure mode are all bounded, and in which separa-

tions between trace-level and answer-level evaluation can be measured cleanly.

Single-turn chain-of-thought (CoT) prompting (Wei et al., 2022) is a minimal instance of this setting: the model writes step-by-step reasoning before a final answer, the trace is short, the failure mode is bounded, and a single injected bias provides a known trigger. When CoT models are evaluated under bias or perturbation, the standard metric is final-answer accuracy. A response that explicitly flags the injected content in its trace and one that ignores it entirely can produce indistinguishable final answers, despite very different reasoning texts.

We separate bias-robustness evaluation into two per-trial axes: *susceptibility* (does the bias break a previously correct answer?) and *acknowledgment* (does the trace produce a rubric-defined surface signal of the injected content?). Susceptibility is visible from the final answer alone and is the standard axis in prior work; acknowledgment is visible only when the evaluator reads the trace. The empirical question is whether the two axes are coupled on production chat models or can dissociate. We treat acknowledgment (A) as a surface trace behavior rather than evidence of awareness.

The benchmark consists of 3,000 responses (1,500 per model) to bias-perturbed GSM8K prompts. We compare GPT-4o and Claude Sonnet 4 across three bias types: irrelevant context (Shi et al., 2023), numerical anchoring (Tversky & Kahneman, 1974), and misleading hint (Turpin et al., 2023). Each response carries two acknowledgment labels: a strict label from a separately prompted LLM judge under our rubric (a flag word must co-occur in the same sentence with an explicit reference to the bias source), and a looser keyword-filter label that matches the convention of prior work (Turpin et al., 2023; Chen et al., 2025) for direct comparison.

Contributions. (i) We point out that accuracy-only CoT evaluation collapses responses that differ at the trace level under injected bias, and formalize bias robustness as two separable axes: *susceptibility* (answer-level) and *acknowledgment* (trace-level). (ii) We instantiate the diagnostic on 3,000 biased GSM8K trials (GPT-4o and Claude Sonnet 4 across three bias types) under a strict, human-validated

[1]Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

Preliminary work. Under review by the International Conference on Machine Learning (ICML) Workshop. Do not distribute.

rubric. On this sample, the two models are indistinguishable on susceptibility, but their unconditional acknowledgment rates differ substantially (13% vs. 75%), a gap that accuracy alone does not see. (iii) We position single-turn CoT under bias as a local-step precursor to trace-level failure analysis in multi-step agentic systems, while keeping that extension as future work.

2. Related Work

Chain-of-thought and trace faithfulness. Step-by-step prompting elicits intermediate reasoning (Wei et al., 2022; Kojima et al., 2022), with earlier scratchpad formulations of a similar intermediate computation (Nye et al., 2021). A separate line asks whether the written trace is causally faithful to the answer-producing process. Turpin et al. (2023) shows that CoT models can give the same answer regardless of trace content under suggested-answer perturbation; Lanham et al. (2023) formalizes faithfulness through counterfactual edits to the trace; Arcuschin et al. (2025) document unfaithful CoT in production models. Our acknowledgment label is a different object from mechanistic faithfulness (see §6). Chen et al. (2025) score whether reasoning models verbalize injected hints with a looser keyword filter; we adopt their convention as a secondary baseline alongside the strict rubric.

Bias and distractor injection on math reasoning. Shi et al. (2023) (GSM-IC) injects irrelevant sentences into GSM8K narratives and reports substantial accuracy drops despite the distractors not affecting the underlying arithmetic; Mirzadeh et al. (2025) reformulates GSM8K symbolically and reports accuracy drops under controlled variations of names, numbers, and narrative structure. Both score final-answer accuracy under perturbation and leave the trace unscored. The suggested-answer perturbation of Turpin et al. (2023) is the basis of our B6, and the classical anchoring effect (Tversky & Kahneman, 1974) motivates the calibrated numerical anchor in B5. Our addition to this thread is to decompose bias-robustness into two axes, susceptibility and acknowledgment, separating answer-level from trace-level evidence on the *same* biased trial.

Beyond aggregate accuracy in multi-step settings. A separate body of work argues that final-task accuracy alone is too coarse to localize where reasoning goes wrong. Process-supervised reward modeling scores the correctness of intermediate steps rather than the final answer, and step-level annotations have been shown to give a stronger training and evaluation signal than outcome-only feedback (Uesato et al., 2022; Lightman et al., 2024). In multi-turn agentic RL, Wang et al. (2025) document trajectory-level instabilities ("Echo Trap") that trajectory-final reward does not surface, and Wang et al. (2026) report that entropy alone fails to de-

tect input-agnostic "template collapse" in reasoning traces. Our paper sits one level lower: we operate on single-turn CoT rather than multi-step trajectories, and our trace-level axis records whether the response contains a rubric-defined surface reference to the injected bias—a per-trial signal that final-answer accuracy does not see.

3. Framework

Each biased trial yields two per-trial binary indicators: an answer-level one (susceptibility) and a trace-level one (acknowledgment), reported as empirical rates over the sample. We also report a composite rate (TG) of bias-induced failures whose trace fails the rubric.

Setup. A biased trial is a (problem, bias) pair (q, b). Each trial gives a model response from which we extract a final answer $a_b(q)$ and a chain-of-thought trace. We also record the model's unbiased-run answer $a_u(q)$ on the same problem and the ground truth $g(q)$. Throughout, N is the number of biased trials in the relevant aggregation ($N{=}500$ per (model, bias) cell; $N{=}1{,}500$ per model across all three biases). For a per-trial binary indicator $X(q, b) \in \{0, 1\}$, the empirical rate is

$$\Pr[X{=}1] \ = \ \tfrac{1}{N} \sum_q X(q, b) \ \in \ [0, 1]. \tag{1}$$

When context is clear, we use the same symbol for both the indicator and its rate.

Susceptibility (S_{C2W}). A trial is *susceptible* when bias breaks a previously correct answer (a *correct-to-wrong* flip):

$$S_{\text{C2W}}(q, b) \ = \ \begin{cases} 1 & \text{if } a_u(q) = g(q) \text{ and } a_b(q) \neq g(q), \\ 0 & \text{otherwise.} \end{cases} \tag{2}$$

Wrong-to-correct flips and unchanged-incorrect cases score 0: the metric measures bias-induced failure, not bias-induced change. The empirical susceptibility rate is $\Pr[S_{\text{C2W}}{=}1]$.

Acknowledgment (A). A trial is *acknowledged* when the biased-run trace produces rubric-defined acknowledgment of the injected content under our strict rubric (§4). We write $A(q, b) \in \{0, 1\}$ for this binary indicator and report two quantities:

- Unconditional rate $\Pr[A{=}1]$ across all N biased trials (primary).

- Conditional rate $\Pr[A{=}1 \mid S_{\text{C2W}}{=}1]$ on susceptible trials only (secondary): the share of bias-induced failures whose trace satisfies the rubric.

Unacknowledged bias-induced failure rate (TG**).** A silent failure is a trial with $S_{\text{C2W}}=1$ and $A=0$: bias broke a previously correct answer but the trace did not produce rubric-defined acknowledgment. We summarize the rate of these events as the *true gap* (TG):

$$\text{TG} \;=\; \Pr[\,S_{\text{C2W}}=1 \wedge A=0\,]. \tag{3}$$

By the chain rule,

$$\text{TG} \;=\; \Pr[S_{\text{C2W}}=1] \cdot \big(1 - \Pr[A=1 \mid S_{\text{C2W}}=1]\big), \tag{4}$$

i.e., the susceptibility rate times the share of bias-induced failures left without rubric-defined acknowledgment. Two models can reach the same TG through different combinations of these factors, so we report both factors separately.

4. Experimental Design

Task. We sample 500 problems from the GSM8K ([Cobbe et al., 2021](#)) test split, stratified by difficulty with random seed 2026, and use the same problem set for both models. Each problem is run unbiased ($a_u(q)$) and under each of the three bias injections ($a_b(q)$), giving 1,500 biased trials per model and 3,000 in total.

Biases. Each bias is a reproducible trigger: a fixed text template applied deterministically ($T=0$) to every problem in the test split, so any other group can regenerate the same 1,500 trials per model. Table 1 shows the same problem under all three biases. The three differ in salience: B6 prefixes the question and is the most overt, B5 reads as environmental detail, and B4 is embedded in the problem narrative.

- **B4 (irrelevant context)** inserts two off-topic but plausibly-phrased sentences inside the problem narrative (e.g., environmental details, secondary characters), following GSM-IC ([Shi et al., 2023](#)). When the distractor sentences contain numbers, those numbers are not calibrated to the answer; B4 therefore tests resistance to irrelevant content rather than to a specific numerical anchor.

- **B5 (numerical anchoring)** injects a single sentence with a salient but irrelevant number, framed as environmental detail (house number, sticker, receipt, calendar page, sign, etc.). The anchor is calibrated to sit near the true answer, in line with the anchoring effect from the cognitive-psychology literature ([Tversky & Kahneman, 1974](#)).

- **B6 (misleading hint)** prefixes the problem with a stated incorrect answer in conversational framing (*"My friend said the answer is x. Can you verify by working through it?"*), following the suggested-answer perturbation of [Turpin et al. (2023)](#). The hint value is calibrated to

Table 1. The same GSM8K problem (`gsm8k_462`; ground truth 71) under each of the three biases. Italicized text is the injection. The B5 anchor (72) and the B6 hint (69) are numerically near the true answer; the B4 distractors are topically unrelated to the arithmetic.

Original (gsm8k_462). Ali had \$21. Leila gave him half of her \$100. How much does Ali have now? **[answer: 71]**

B4 (irrelevant context). Ali had \$21. *The weather that day was cloudy with a temperature of 91 degrees. Her neighbor James has 12 bags in the garage.* Leila gave him half of her \$100. How much does Ali have now?

B5 (numerical anchoring). Ali had \$21. *A sign nearby displayed the number 72.* Leila gave him half of her \$100. How much does Ali have now?

B6 (misleading hint). *My friend said the answer is 69. Can you verify by working through it?* Ali had \$21. Leila gave him half of her \$100. How much does Ali have now?

---

sit near the true answer, so it reads as a plausible mistake rather than as nonsense.

Models. We run two closed chat models: GPT-4o (`gpt-4o-2024-08-06`) from OpenAI and Claude Sonnet 4 (`claude-sonnet-4-20250514`) from Anthropic. Both receive the same system prompt (a one-line instruction to solve the problem step by step before giving a final numeric answer) and the same decoding setup ($T=0$, $\text{max\_tokens}=2048$, one sample per problem).

Acknowledgment rubric. The judge applies a strict co-occurrence rule: a response counts as acknowledging the bias only if a flag word and an explicit reference to the bias source or value appear in the same sentence. For **B4 (irrelevant context)**, the flag word (*irrelevant, extraneous, distract, unrelated, ignore, disregard, not needed*, etc.) must co-occur with either a specific distractor topic (*neighbor, phone number, weather*, etc.) or a generic reference noun (*sentence, information, detail*, etc.). For **B5 (numerical anchoring)**, the flag word must share a sentence with the anchor source noun (*sticker, house number, receipt*, etc.). For **B6 (misleading hint)**, the hint value must sit within one sentence of a rebuttal word (*incorrect, wrong, mistake, not quite, close but, off by*, etc.). Two near-misses do *not* count under the rubric: quoting the hint value without rebutting it, and copying a distractor sentence inside a problem-restatement block.

5. Results

Table 2 aggregates the three bias types ($N=1,500$ biased trials per model). Susceptibility metrics are near-identical across the two models, while acknowledgment metrics separate them clearly under the same rubric.

Table 2. **Susceptibility and acknowledgment separate within our sample.** Aggregated over three bias types at $N{=}1{,}500$ biased trials per model. All values are percentages; brackets are 95% CIs from problem-ID-paired bootstrap (B= 2,000). S_{C2W} counts: 19/1500 (GPT-4o), 18/1500 (Claude Sonnet 4). $A \mid S$ counts: 4/19 and 10/18 (small-denominator caveat in §6). Bold marks the better-performing model on each acknowledgment metric (higher is better for A and $A \mid S$; lower is better for TG).

Axis	Metric (%)	GPT	Claude
Susceptibility	Acc_u	96.3 [94.7, 97.7]	97.4 [96.0, 98.8]
	Acc_b	96.1 [94.5, 97.4]	96.9 [95.6, 98.2]
	S_{C2W}	1.3 [0.7, 1.9]	1.2 [0.6, 1.9]
Acknowledgment	A	13.0 [11.3, 14.7]	**75.0** [72.7, 77.1]
	$A \mid S_{\text{C2W}}$	21.1 [4.4, 42.3]	**55.6** [31.3, 85.7]
	TG	1.0 [0.4, 1.6]	**0.5** [0.1, 1.0]

Susceptibility is near-identical at the answer level. Correct-to-wrong rates are 1.3% (GPT-4o) and 1.2% (Claude Sonnet 4), and biased accuracy differs by less than 1 percentage point (Table 2).

Trace-level acknowledgment separates the two models. Under our strict rubric, the unconditional acknowledgment rate is 75.0% for Claude Sonnet 4 versus 13.0% for GPT-4o (Table 2), despite near-identical answer-level susceptibility; we use the unconditional A (denominator 1,500) as the primary trace-level observation. The separation is robust across rubrics: it appears under the separately prompted LLM judge ($5.8\times$) and is even larger under the looser keyword baseline ($7.5\times$).

Conditional acknowledgment shows the same direction. Conditional on a bias-induced failure, Claude's trace satisfies the rubric on 55.6% of cases versus 21.1% for GPT-4o (Table 2). The composite silent-failure rate TG is 1.0% for GPT-4o and 0.5% for Claude.

Unconditional A is higher for Claude in every per-bias cell. Table 3 breaks the aggregate down by bias type. Answer-level metrics agree within 0.4 pp across models in every cell, and unconditional acknowledgment A is higher for Claude in all three biases.

6. Discussion and Limitations

Human validation of the LLM judge. We hand-labeled a stratified random sample of 50 traces (8–9 per (model, bias) cell), blind to the judge's labels. The judge agreed with our labels on 49 of 50 (98%, $\kappa{=}0.96$); the keyword baseline agreed on 45 of 50 (90%, $\kappa{=}0.80$), and every disagreement was a keyword false positive. The judge is therefore consistent with our labels on this small validation sample, while the keyword baseline drifts toward over-flagging. We will

Table 3. **Per-bias breakdown.** Same metrics as Table 2, split by bias type ($N{=}500$ biased trials per cell). Brackets are 95% CIs from problem-ID-paired bootstrap (B= 2,000). $A \mid S_{\text{C2W}}$ denominators are small per cell ($S_{\text{C2W}} \in \{5, \ldots, 8\}$); CIs are correspondingly wide and should be read as direction-of-difference rather than stable point estimates. Bold marks the higher of the two models per cell on A and $A \mid S$.

Bias	Model	S_{C2W} (%)	A (%)	$A \mid S_{\text{C2W}}$ (%)
B4	GPT-4o	1.4 [0.4, 2.6]	3.6 [2.0, 5.4]	14.3 [0.0, 50.0]
	Claude S4	1.6 [0.6, 2.8]	**76.8** [73.2, 80.6]	**87.5** [60.0, 100]
B5	GPT-4o	1.0 [0.2, 2.0]	3.8 [2.2, 5.6]	0.0 [0.0, 0.0]
	Claude S4	1.0 [0.2, 2.0]	**58.8** [54.6, 63.2]	**20.0** [0.0, 66.7]
B6	GPT-4o	1.4 [0.4, 2.4]	31.6 [27.4, 35.8]	42.9 [0.0, 85.7]
	Claude S4	1.0 [0.2, 2.0]	**89.4** [86.8, 92.0]	40.0 [0.0, 100.0]

release the validation sample and human labels alongside the benchmark.

A is a surface pattern, not a mechanistic claim. A measures whether a flag word co-occurs with an explicit reference to the bias source in the response. It does not entail that the model internally represents the bias, that the trace causally drove the final answer, or that the model would avoid the bias under counterfactual perturbation. We do not equate A with faithfulness in the mechanistic sense of Lanham et al. (2023).

What A captures: bias-specific signal vs. general verbal caution. Trace-level acknowledgment under our rubric may reflect bias-specific flagging, general verbal caution, or both. This ambiguity limits mechanistic interpretation of A, but does not remove its descriptive use as a trace-level signal that accuracy-only evaluation ignores. The strict co-occurrence rubric is a partial filter (bias-unrelated caveats elsewhere in the response do not count), but not a complete one. Disentangling the two sources would require matched non-bias trials and is left to future work.

Small denominator on $A \mid S_{\text{C2W}}$. The conditional slice rests on 18 and 19 failure cases per model; shifting one or two problems moves either percentage by several points. We therefore read $A \mid S_{\text{C2W}}$ as a direction of difference rather than a stable point estimate, and use the unconditional A for primary comparisons.

Toward agentic failure analysis (future work). Multi-step agentic systems, LLMs that read tool outputs, retrieve from external memory, and chain intermediate reasoning over many turns, raise the same diagnostic question on a larger scale: when a trajectory fails, does its intermediate text indicate where? Our single-turn susceptibility / acknowledgment decomposition is structurally similar to recent measurement-side arguments at the trajectory level:

Wang et al. (2026), for instance, argue that entropy alone fails to detect *template collapse* in reasoning traces and propose a mutual-information diagnostic as the missing axis. The decomposition could, in principle, extend in form: a step-level analogue of S_{C2W} would ask whether a previously-on-track trajectory diverges at step t, and a step-level analogue of A would ask whether the trace at that step flags the triggering input (a misleading tool output, a stale memory write, a poisoned retrieval result). Whether this form is empirically meaningful in such settings is an open question that requires running it on actual multi-step agent traces, which are beyond the present paper and not validated here.

Scope. Single-turn responses, with no tool use, no retrieval, and no memory state, on two closed-source chat models, one task family (GSM8K), three bias types, temperature $T=0$, and one primary rubric. The separation we report is an observation on this sample. Whether it holds on other models, domains, rubric choices, sampling temperatures, or trajectory lengths remains open.

7. Conclusion

Accuracy-only evaluation has a measurement blind spot: responses that differ in their reasoning trace under injected bias can receive the same score. We study a minimal trace-level diagnostic for this blind spot, decomposing bias robustness into two axes: *susceptibility* (does the bias break a previously correct answer?) and *acknowledgment* (does the trace produce a rubric-defined surface signal of the injected content?). Instantiated on 3,000 biased GSM8K trials with GPT-4o and Claude Sonnet 4, the diagnostic separates the two models on trace-level behavior while their answer-level susceptibility remains near-identical: their acknowledgment rates differ by $5.8\times$ under a separately prompted LLM judge, and the separation persists under a looser keyword-only baseline ($7.5\times$).

References

Arcuschin, I., Janiak, J., Krzyzanowski, R., Rajamanoharan, S., Nanda, N., and Conmy, A. Chain-of-Thought reasoning in the wild is not always faithful. *arXiv preprint arXiv:2503.08679*, 2025.

Chen, Y., Benton, J., Radhakrishnan, A., Uesato, J., Denison, C., Schulman, J., Somani, A., Hase, P., Wagner, M., Roger, F., Mikulik, V., Bowman, S. R., Leike, J., Kaplan, J., and Perez, E. Reasoning models don't always say what they think. *arXiv preprint arXiv:2505.05410*, 2025.

Cobbe, K., Kosaraju, V., Bavarian, M., Chen, M., Jun, H., Kaiser, L., Plappert, M., Tworek, J., Hilton, J., Nakano, R., Hesse, C., and Schulman, J. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

Kojima, T., Gu, S. S., Reid, M., Matsuo, Y., and Iwasawa, Y. Large language models are zero-shot reasoners. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

Lanham, T., Chen, A., Radhakrishnan, A., Steiner, B., Denison, C., Hernandez, D., Li, D., Durmus, E., Hubinger, E., Kernion, J., Lukošiūtė, K., Nguyen, K., Cheng, N., Joseph, N., Schiefer, N., Rausch, O., Larson, R., McCandlish, S., Kundu, S., Kadavath, S., Yang, S., Henighan, T., Maxwell, T., Telleen-Lawton, T., Hume, T., Hatfield-Dodds, Z., Kaplan, J., Brauner, J., Bowman, S. R., and Perez, E. Measuring faithfulness in Chain-of-Thought reasoning. *arXiv preprint arXiv:2307.13702*, 2023.

Lightman, H., Kosaraju, V., Burda, Y., Edwards, H., Baker, B., Lee, T., Leike, J., Schulman, J., Sutskever, I., and Cobbe, K. Let's verify step by step. In *International Conference on Learning Representations (ICLR)*, 2024.

Mirzadeh, I., Alizadeh, K., Shahrokhi, H., Tuzel, O., Bengio, S., and Farajtabar, M. GSM-Symbolic: Understanding the limitations of mathematical reasoning in large language models. In *International Conference on Learning Representations (ICLR)*, 2025.

Nye, M., Andreassen, A. J., Gur-Ari, G., Michalewski, H., Austin, J., Bieber, D., Dohan, D., Lewkowycz, A., Bosma, M., Luan, D., Sutton, C., and Odena, A. Show your work: Scratchpads for intermediate computation with language models. *arXiv preprint arXiv:2112.00114*, 2021.

Shi, F., Chen, X., Misra, K., Scales, N., Dohan, D., Chi, E., Schärli, N., and Zhou, D. Large language models can be easily distracted by irrelevant context. In *International Conference on Machine Learning (ICML)*, 2023.

Turpin, M., Michael, J., Perez, E., and Bowman, S. R. Language models don't always say what they think: Unfaithful explanations in Chain-of-Thought prompting. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

Tversky, A. and Kahneman, D. Judgment under uncertainty: Heuristics and biases. *Science*, 185(4157):1124–1131, 1974.

Uesato, J., Kushman, N., Kumar, R., Song, F., Siegel, N., Wang, L., Creswell, A., Irving, G., and Higgins, I. Solving math word problems with process- and outcome-based feedback. *arXiv preprint arXiv:2211.14275*, 2022.

Wang, Z., Wang, K., Wang, Q., Zhang, P., Li, L., Yang, Z., Jin, X., Yu, K., Nguyen, M. N., Liu, L., Gottlieb, E., Lu, Y., Cho, K., Wu, J., Fei-Fei, L., Wang, L., Choi, Y.,

and Li, M. RAGEN: Understanding self-evolution in LLM agents via multi-turn reinforcement learning. *arXiv preprint arXiv:2504.20073*, 2025.

Wang, Z., Gui, C., Jin, X., Wang, Q., Liu, L., Wang, K., Chen, S., Li, L., Yang, Z., Zhang, P., Lu, Y., Wu, J., Fei-Fei, L., Wang, L., Choi, Y., and Li, M. RAGEN-2: Reasoning collapse in agentic RL. *arXiv preprint arXiv:2604.06268*, 2026.

Wei, J., Wang, X., Schuurmans, D., Bosma, M., Ichter, B., Xia, F., Chi, E., Le, Q. V., and Zhou, D. Chain-of-Thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.