Deep Weight Factorization: Sparse Learning Through the Lens of Artificial Symmetries

Abstract

Sparse regularization techniques are well-established in machine learning, yet their application in neural networks remains challenging due to the non-differentiability of penalties like the L_1 norm, which is incompatible with stochastic gradient descent. A promising alternative is shallow weight factorization, where weights are decomposed into two factors, allowing for smooth optimization of L_1-penalized neural networks by adding differentiable L_2 regularization to the factors. In this work, we introduce deep weight factorization, extending previous shallow approaches to more than two factors. We theoretically establish equivalence of our deep factorization with non-convex sparse regularization and analyze its impact on training dynamics and optimization. Due to the limitations posed by standard training practices, we propose a tailored initialization scheme and identify important learning rate requirements necessary for training factorized networks. We demonstrate the effectiveness of our deep weight factorization through experiments on various architectures and datasets, consistently outperforming its shallow counterpart and widely used pruning methods.

1 Introduction

Making models sparse is a contemporary challenge in deep learning, currently attracting a lot of attention. Among the more prominent methods to achieve sparsity are model pruning methods (Gale et al., 2019; Blalock et al., 2020) and regularization approaches sparsifying the model during training (Hoefler et al., 2021). While in statistics and machine learning, sparse regularization approaches are well-established (see, e.g., Tian & Zhang, 2022), the non-smoothness of sparsity penalties such as the L_1 norm impedes the optimization of neural networks when using classical stochastic gradient descent (SGD) optimization. A possible solution that allows SGD-based optimization while inducing L_1 regularization is *weight factorization*. Originally proposed in statistics for linear models (Hoff, 2017), the idea of factorizing the weights $\mathbf{w} = \boldsymbol{\omega}_1 \odot \boldsymbol{\omega}_2$ to obtain a differentiable L_1 penalty on the product $\boldsymbol{\omega}_1 \odot \boldsymbol{\omega}_2$ has recently been adopted also in deep learning (see, e.g., Ziyin & Wang, 2023). This simple trick allows the integration of convex L_1-based sparsity into neural

network training while promising direct applicability of familiar SGD. As shown in Fig. 1, the obtained sparsity of differentiable L_1 remains superior to vanilla L_1 regularization. This holds even after applying additional post-hoc pruning, demonstrating that the inferior sparsity performance of vanilla L_1 is not just due to a suboptimal threshold but also the incompatibility of SGD and non-smooth penalties.

Figure 1: Sparsity-accuracy tradeoff using a vanilla L_1 penalization with SGD (blue) compared to (deep) weight factorization. Means and std. deviations over 3 random seeds are shown.

Given the success of (shallow) weight factorization, we study deep weight factorization in this work, i.e., factorizing $\mathbf{w} = \boldsymbol{\omega}_1 \odot \cdots \odot \boldsymbol{\omega}_D, D \geq 2$ (cf. Fig. 2). We investigate whether theoretical guarantees support the use of a *depth-D* factorization, whether it is beneficial for sparsity, what implications its usage has on training dynamics, and analyze other practices such as initialization.

Figure 2: Overview of the proposed method (cf. Algorithm 2). Our approach proceeds by factorizing the neural network weights and running SGD on the factors $\boldsymbol{\omega}_d$ with weight decay. Post-training, the factors are collapsed again, with the resulting sparse solutions being minimizers of the non-smooth $L_{2/D}$-regularized objective.

Our contributions In this work, we address the aforementioned challenges and close an important gap in the current literature. We first theoretically show the equivalence of factorized neural networks with sparse regularized optimization problems for depth $D \geq 2$, allowing for differentiable non-convex sparsity regularization in any neural network. We then discuss optimization strategies for these factorized networks including their initialization and appropriate learning rate schedules. We also analyze the training dynamics of such networks, showing a particularly interesting connection between the evolution of weight norms, compression, accuracy, and generalization. Conducting experiments on a range of architectures and datasets, we further substantiate our theoretical findings and demonstrate that our proposed factorized networks usually outperform the recently proposed shallow factorization and yield competitive results to commonly used pruning methods.

2 BACKGROUND AND RELATED LITERATURE

2.1 NOTATION

Let $\{(\boldsymbol{x}_i, y_i)\}_{i=1}^n$ be the training data of independent samples $(\boldsymbol{x}_i, y_i) \in \mathcal{X} \times \mathbb{R}^c$, and $n, c \in \mathbb{N}$. Let $f(\mathbf{w}, \boldsymbol{x}) : \mathcal{X} \to \mathbb{R}^c$ denote a network realization for any $\mathbf{w} \in \mathbb{R}^p$. In general, we are interested in minimizing $\ell(\cdot, \cdot) : \mathbb{R}^c \times \mathbb{R}^c \to \mathbb{R}_0^+$ denoting a continuous per-sample loss. The L_q *norm* of a vector $\mathbf{w} \in \mathbb{R}^p$ is defined as $\|\mathbf{w}\|_q = \left(\sum_{i=1}^p |\mathbf{w}_i|^q\right)^{1/q}$ for $q > 0$. Note that L_q *regularizers* are defined differently as $\|\mathbf{w}\|_q^q$ and that for $q < 1$, only a non-convex quasi-norm is defined. For two vectors $\boldsymbol{\omega}_1, \boldsymbol{\omega}_2 \in \mathbb{R}^p$, we use $\odot$ to denote their element-wise multiplication. For an optimization problem $\min_{\mathbf{w}} \mathcal{L}(\mathbf{w})$, we denote $\hat{\mathbf{w}} := \arg\min_{\mathbf{w}} \mathcal{L}(\mathbf{w})$. Finally, the *compression ratio* (CR) is defined as the ratio of original to sparse model parameters.

2.2 DIFFERENTIABLE L_1 REGULARIZATION

Weight factorizations were previously studied either to optimize regularized linear models or as toy models for deep learning theory. We briefly illustrate this using the idea of a differentiable lasso.

Differentiable lasso The original lasso objective is defined as

$$\min_{\mathbf{w} \in \mathbb{R}^p} \mathcal{L}_{\mathbf{w}, \lambda}(\mathbf{w}) := \sum_{i=1}^n \left(y_i - \boldsymbol{x}_i^\top \mathbf{w}\right)^2 + \lambda \|\mathbf{w}\|_1, \tag{1}$$

where $\lambda > 0$ promotes sparsity via the L_1 norm (Tibshirani, 1996). By factorizing $\mathbf{w}$ into $\boldsymbol{\omega}_1$ and $\boldsymbol{\omega}_2$ such that $\mathbf{w} = \boldsymbol{\omega}_1 \odot \boldsymbol{\omega}_2$, and replacing the non-differentiable L_1 penalty with an L_2 penalty on $\boldsymbol{\omega} = (\boldsymbol{\omega}_1, \boldsymbol{\omega}_2)$, we can obtain a differentiable formulation of the lasso (Hoff, 2017):

$$\min_{\boldsymbol{\omega}_1, \boldsymbol{\omega}_2 \in \mathbb{R}^p} \mathcal{L}_{\boldsymbol{\omega}, \lambda}(\boldsymbol{\omega}) := \sum_{i=1}^n \left(y_i - \boldsymbol{x}_i^\top (\boldsymbol{\omega}_1 \odot \boldsymbol{\omega}_2)\right)^2 + \frac{\lambda}{2}\left(\|\boldsymbol{\omega}_1\|_2^2 + \|\boldsymbol{\omega}_2\|_2^2\right), \tag{2}$$

The formulation Eq. (2) is equivalent to Eq. (1) in the sense that all minima of the non-convex objective in Eq. (2) are global and related to the unique lasso solution of Eq. (1) as $\hat{\omega}_1 \odot \hat{\omega}_2 = \hat{\mathbf{w}}$. Hoff (2017) proposes solving Eq. (2) via alternating ridge regression. However, this relies on the biconvexity of the problem and cannot be easily extended beyond linear models.ph[L1]Differentiable L_1 regularization in general neural networks

Recently, Ziyin & Wang (2023) proposed applying a shallow factorization to arbitrary weights of a neural network. Coupled with weight decay, this allows obtaining a differentiable formulation of the sparsity-inducing L_1 penalty that can be optimized with simple SGD. Specifically, by factorizing the weights $\mathbf{w}$ of any neural network $f_{\mathbf{w}}(\mathbf{w}, \boldsymbol{x})$ as $\mathbf{w} = \boldsymbol{\omega}_1 \odot \boldsymbol{\omega}_2$, and applying L_2 regularization to the factors, the resulting optimization problem has the same minima as the L_1 regularized vanilla network. The key insight for the equivalence with L_1 regularization is that the factorization $\mathbf{w} = \boldsymbol{\omega}_1 \odot \boldsymbol{\omega}_2$ introduces a rescaling symmetry in the (unregularized) loss $\mathcal{L}_{\boldsymbol{\omega},0}$.

Definition 1 (Rescaling Symmetry). Let the parameters of a loss function $\mathcal{L}_{\boldsymbol{\theta}}(\boldsymbol{\theta})$ be partitioned as $\boldsymbol{\theta} = (\boldsymbol{\omega}_1, \boldsymbol{\omega}_2, \boldsymbol{\theta}_0)$, with $\boldsymbol{\theta}_0$ denoting the remaining parameters. Then $\mathcal{L}_{\boldsymbol{\theta}}(\boldsymbol{\theta})$ possesses a rescaling symmetry w.r.t. arbitrary parameters $\boldsymbol{\omega}_1, \boldsymbol{\omega}_2$ belonging to $\boldsymbol{\theta} = (\boldsymbol{\omega}_1, \boldsymbol{\omega}_2, \boldsymbol{\theta}_0)$ if for any $c \neq 0$:

$$\mathcal{L}_{\boldsymbol{\theta}}(\boldsymbol{\omega}_1, \boldsymbol{\omega}_2, \boldsymbol{\theta}_0) = \mathcal{L}_{\boldsymbol{\theta}}(c \cdot \boldsymbol{\omega}_1, c^{-1} \cdot \boldsymbol{\omega}_2, \boldsymbol{\theta}_0) \ \forall \boldsymbol{\theta}.$$

Figure 3: Scalar rescaling symmetry and min-norm factorizations.

While previous works mainly studied rescaling symmetries naturally arising in, e.g., homogeneous activation functions (Neyshabur et al., 2015; Parhi & Nowak, 2023), weight factorization constitutes an *artificial* symmetry that is independent of $\mathcal{L}$, and by extension also of $\ell(\cdot, \cdot)$ and $f_{\mathbf{w}}(\cdot, \boldsymbol{x})$. This applicability to any parametric problem designates artificial symmetries as a powerful tool for constrained learning (Ziyin, 2023; Chen et al., 2024). Intuitively, the additional L_2 regularization enforces preference for min-norm factorizations $(\boldsymbol{\omega}_1^*, \boldsymbol{\omega}_2^*)$ among all feasible factorizations of a given $\mathbf{w}$ (Fig. 3). At such a min-norm factorization of $\mathbf{w}$, the L_2 penalty in Eq. (2) reduces to $\|\boldsymbol{\omega}_1^* \odot \boldsymbol{\omega}_2^*\|_1 = \|\mathbf{w}\|_1$, effectively inducing L_1 regularization on the collapsed parameter. This approach allows for implementing L_1 regularization in general networks using GD without requiring specialized algorithms to handle non-differentiable regularization.

We refer to Appendix A for additional related methods and discussion. Appendix B provides some intuition why weight factorization with L_2 regularization promotes sparse solutions based on Fig. 3.

3 THEORETICAL RESULTS

Based on a given network specification of $f(\mathbf{w}, \boldsymbol{x})$, we study its *depth-D* factorization with $D \geq 2$, which we call Deep Weight Factorization (DWF) and is defined as follows:

Definition 2 (Deep Weight Factorization). A depth-D factorization with $D \in \mathbb{N}_{\geq 2}$ of an arbitrary neural network $f_{\mathbf{w}}(\mathbf{w}, \boldsymbol{x})$, $\mathbf{w} \in \mathbb{R}^p$, is given by $f_{\mathbf{w}}(\boldsymbol{\omega}_1 \odot \ldots \odot \boldsymbol{\omega}_D, \boldsymbol{x})$ with $\boldsymbol{\omega} = (\boldsymbol{\omega}_1, \ldots, \boldsymbol{\omega}_D)$ and factors $\boldsymbol{\omega}_d = (\omega_{1,d}, \ldots, \omega_{p,d}) \in \mathbb{R}^p, d \in [D]$. The original and factorized parameters are related through $\mathbf{w} = \boldsymbol{\omega}_1 \odot \ldots \odot \boldsymbol{\omega}_D =: \boldsymbol{\varpi}$, where $\boldsymbol{\varpi}$ denotes the collapsed parameter. Further, a factorization depth is called *shallow* for $D = 2$ and otherwise *deep*.

In this work, we focus on unstructured sparsity. This means all weights and biases in $f_{\mathbf{w}}$ are factorized using DWF. In principle, however, the factorization can also be selectively applied to arbitrary subsets of the parameters $\mathbf{w}$. Importantly, while DWF does not alter the expressive capacity of the underlying network $f_{\mathbf{w}}$, it drastically alters the optimization dynamics and enables sparse learning in conjunction with L_2 regularization or weight decay. Therefore, our focus lies on examining the effects of L_2 regularization and the behavior of SGD optimization in factorized networks.

The regularized training loss with DWF and regularization strength $\lambda > 0$ is defined to be

$$\mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega}) = \frac{1}{n}\sum_{i=1}^{n} \ell\left(y_i, f_{\mathbf{w}}\left(\boldsymbol{\omega}_1 \odot \ldots \odot \boldsymbol{\omega}_D, \boldsymbol{x}_i\right)\right) + \frac{\lambda}{D}\sum_{d=1}^{D} \|\boldsymbol{\omega}_d\|_2^2. \tag{3}$$

For a given $\mathbf{w}$, applying DWF to the training objective introduces an infinite set of feasible factorizations $\{(\boldsymbol{\omega}_1, \ldots, \boldsymbol{\omega}_D) : \boldsymbol{\varpi} = \mathbf{w}\}$ that leave the network output $f_{\mathbf{w}}(\mathbf{w}, \boldsymbol{x})$ and loss invariant. Those

factorizations, however, differ in their respective norms. While the norm of individual factors can grow arbitrarily large, there exist factorizations that minimize the Euclidean norm, or equivalently, the factor L_2 penalty. L_2 regularization thus biases the optimization toward min-norm factorizations. This regularization ensures that the parameter representation strives to be evenly distributed across factors. The following result formalizes the necessary optimality conditions for the factorized objective, identifying solution candidates as those that achieve minimal norm configuration.

Lemma 1 (Necessary condition for solution and minimum L_2 penalty). *Let $\boldsymbol{\omega} = (\boldsymbol{\omega}_1, \ldots, \boldsymbol{\omega}_D) \in \mathbb{R}^{Dp}$ be a local minimizer of $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega})$. Then i) $|\omega_{j,1}| = \ldots = |\omega_{j,D}|$ for all $j \in [p]$, and ii) the factor L_2 penalty reduces to $D^{-1} \sum_{d=1}^{D} \|\boldsymbol{\omega}_d\|_2^2 = \|\boldsymbol{\varpi}\|_{2/D}^{2/D}$.*

Using the result of Lemma 1, we introduce the concept of **factor misalignment** to quantify the distance from balanced factorizations required for solutions. Specifically, the factor misalignment is defined as $M(\boldsymbol{\omega}) = D^{-1} \sum_{d=1}^{D} \|\boldsymbol{\omega}_d\|_2^2 - \|\boldsymbol{\varpi}\|_{2/D}^{2/D}$ and captures the difference between the factor L_2 penalty and that of a balanced minimum-norm factorization of the same collapsed $\boldsymbol{\varpi}$. The misalignment satisfies $M(\boldsymbol{\omega}) \geq 0$, with equality if and only if the factorization is balanced. This allows us to restrict the search for potential solutions to balanced factorizations $M(\boldsymbol{\omega}) = 0$, as required by Lemma 1. Lemma 6 in Appendix C.4 describes the remarkable implications of reaching zero misalignment for SGD dynamics, collapsing the dynamics to a constrained symmetry-induced subspace in which the parameters remain for all future iterations (cf. Fig. 20 for dynamics of $M(\boldsymbol{\omega})$).

The results from Lemmas 1 and 6 highlight the significance of factor misalignment for both the landscape of loss functions under DWF and the trajectories of SGD optimization. For balanced factorizations, the usual smooth L_2 penalty remarkably takes the equivalent form of a sparsity-inducing regularizer, with SGD dynamics being restricted to simpler symmetry-induced subspaces. Notably, both L_2 regularization and SGD noise naturally drive the dynamics towards balance (Chen et al., 2024). These observations motivate the following key result:

Theorem 1 (Equivalence of optimization problems). *The optimization problems*

$$\min_{\mathbf{w} \in \mathbb{R}^p} \mathcal{L}_{\mathbf{w},\lambda}(\mathbf{w}) := \frac{1}{n} \sum_{i=1}^{n} \ell\left(y_i, f_{\mathbf{w}}\left(\mathbf{w}, \boldsymbol{x}_i\right)\right) + \lambda \|\mathbf{w}\|_{2/D}^{2/D} \tag{4}$$

$$\min_{\boldsymbol{\omega} \in \mathbb{R}^{Dp}} \mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega}) := \frac{1}{n} \sum_{i=1}^{n} \ell\left(y_i, f_{\mathbf{w}}\left(\boldsymbol{\omega}_1 \odot \ldots \odot \boldsymbol{\omega}_D, \boldsymbol{x}_i\right)\right) + \frac{\lambda}{D} \sum_{d=1}^{D} \|\boldsymbol{\omega}_d\|_2^2 \tag{5}$$

have the same global and local minima with the respective minimizers related as $\hat{\mathbf{w}} = \hat{\boldsymbol{\omega}}_1 \odot \ldots \odot \hat{\boldsymbol{\omega}}_D$.

Practically speaking, instead of attempting to optimize the non-smooth problem in Eq. (4), we can alternatively optimize the smooth problem in Eq. (5) as every local or global solution of the DWF model will yield a corresponding local or global solution in the original model space. Hence, this allows inducing sparsity in typical deep learning applications with SGD-optimization by a simple L_2 regularization using Eq. (5). In contrast, the non-differentiability in (4) will cause the optimization to oscillate and not provide the desired sparsity (see Section 5.1 and Fig. 1). The $L_{2/D}$ penalty in Eq. (4) becomes non-convex and increasingly closer to the L_0 penalty for $D > 2$, permitting a more aggressive penalization of small weights than L_1 regularization (Frank & Friedman, 1993).

While the theoretical equivalence derived in Theorem 1 establishes correspondence of all minimizers and suggests a simple way to induce sparsity in arbitrary neural networks, the optimization of a DWF model is not straightforward and little is known about the learning dynamics of such a model. We will hence study these two aspects in the following section.

4 OPTIMIZATION AND DYNAMICS OF DEEP FACTORIZED NETWORKS

Two crucial aspects of successfully training DWF models are their initialization and the learning rate when optimizing with SGD.

4.1 INITIALIZATION

Applying DWF to a neural network factorizes each parameter into a product of D factors. However, initializations for factorized neural networks are not straightforward since the product distribution of random variables often drastically differs from the factor distribution, leading to pathological behavior, especially for deep factorizations. To retain the properties of standard initializations, defined

Figure 4: DWF initialization strategies. **Left**: factor densities with variance matching and truncation. **Middle**: product densities for $D = 4$ illustrating kurtosis explosion without truncation. **Right**: sparsity-accuracy curves for different initializations and D, showing the failure of standard initialization.

in Appendix C, adjustments to the factor initializations need to be implemented.

Our exposition focuses on the simplest case $w_j^{(l)} \sim \mathcal{N}(0, 1/n_{\text{in}}^{(l)})$, where $n_{\text{in}}^{(l)}$ is the number of input units to the l-th layer (LeCun et al., 2002), but similar arguments can be made for other approaches. While Ziyin & Wang (2023) use standard initialization for shallow factorizations with good results, this consistently fails for $D > 2$ in our experiments and only works in few cases for $D = 2$ (cf. Figs. 4 and 13). The following result shows that initializing a factorized neural network using a standard scheme leads to deteriorating initialization quality and vanishing activation variance:

Lemma 2 (Standard initializations in factorized networks). *Consider a factorized neural network with L layers and factorization depth $D \geq 2$, where $\mathbf{w}^{(l)} = \boldsymbol{\omega}_1^{(l)} \odot \ldots \odot \boldsymbol{\omega}_D^{(l)}$ and the scalar factors $\omega_{j,d}^{(l)}$ are initialized using a standard scheme. Then **i)** the collapsed weights $\varpi_j^{(l)} = \prod_{d=1}^{D} \omega_{j,d}^{(l)} \xrightarrow{p} 0$ as D grows, and **ii)** for any $D \geq 2$, the variance of the activations vanishes in both n_{in} and L.*

Rectifying the failure of standard initializations in DWF   Given a standard initialization $w \sim \mathcal{P}(w)$ with variance σ_w^2, the first step is to correct the variance of the product ϖ by initializing the factors ω_d so that the variance of their product matches that of $\mathcal{P}(w)$. This variance matching of ϖ and w is achieved by setting $\text{Var}(\omega_d) = \text{Var}(w)^{1/D}$ and named *VarMatch* initialization here. However, only considering the variance overlooks the importance of higher-order moments for initialization in deep learning. For example, given a factor initialization $\omega_d \sim \mathcal{N}(0, \sigma^2)$, we have $\mathbb{E}[(\varpi)^2] = \sigma^{2D}, \quad \mathbb{E}[(\varpi)^4] = 3^D \sigma^{4D}$, implying the kurtosis of ϖ grows exponentially as $\kappa_\varpi = 3^D$ regardless of variance matching (cf. Fig. 4). In DWF with plain variance matching, we observe a performance decline and the undesirable emergence of inactive weights (cf. Fig. 5a).[1]

Since variance matching alone does not yield satisfactory results for $D > 2$, we additionally propose a tailored interval truncation of the factor initialization outside of a certain absolute value range and name this approach *DWF Initialization* (see also Algorithm 1). This redistributes the accumulating probability mass away from 0 and prevents catastrophic initialization of dead weights. The truncation thresholds control the smallest and largest possible absolute values $\varpi_{\min}$ and $\varpi_{\max}$ of ϖ, defining the support of the product distribution. Setting the upper truncation threshold to $(2\sigma_w)^{1/D}$ to address large outliers and the lower threshold to $\varepsilon^{1/D}$, for some $\varepsilon > 0$, successfully removes pathological product initializations in our experiments.

Together, the crucial ingredients for DWF initialization are corrections for both the vanishing variance of the product distribution and its concentration around zero.

Remark 1. The factorized bias parameters should not be initialized to all zeros, as this corresponds to a saddle point from which gradient descent cannot escape by symmetry (see Lemma 6).

4.2   LEARNING RATE

Another challenge in optimizing a depth-factorized model is the choice of learning rate (LR). As shown in Fig. 5b, if the LR is chosen too small, the model cannot learn a sparse representation despite achieving the same generalization as a 99.4% sparse model trained with large LR. This closely follows previous analyses of large LRs in neural network training dynamics: Nacson et al.

---

[1]Inactive or dead weights are collapsed weights ϖ consisting of factors ω_d with vanishingly small initialization values, resulting in ϖ not changing during training.

(a) Acc. degradation and dead weights w/o truncation despite $\lambda = 0$ for ResNet-18 and $D = 10$.

(b) Sparsity only emerges with sufficiently large LR for LeNet-300-100 and $D = 4$.

Figure 5: Failure modes when optimizing factorized neural networks.

(2022) show that large LRs help transition to a sparsity-inducing regime in diagonal linear networks. In more realistic scenarios, Andriushchenko et al. (2023) observe that a piece-wise constant (step decay) LR schedule with large initial LR induces phased learning dynamics including a short initial learning phase, followed by a period of sparse feature learning and loss stabilization, and sudden generalization upon reduction of the LR. Particular to symmetries and SGD, Chen et al. (2024) demonstrate how large LRs help generalization by causing SGD to be attracted to symmetry-induced structures through stochastic collapse. We conjecture that in DWF, the introduction of D-fold artificial symmetries (cf. Definition 1) accelerates this phenomenon and thus additionally aids sparse learning. The first row of Fig. 6 shows the training dynamics of deep factorized ResNets and demonstrates the requirement of large and small LR phases for DWF training. These training dynamics are further discussed in the following section. Additionally, Appendix E includes an ablation study on different LRs and factorization depths D, suggesting optimal sparsity-accuracy tradeoffs for initial LRs slightly below a critical threshold where training becomes unstable (Fig. 11).

Figure 6: Factorized ResNet-18 on CIFAR10 with $D = 4$. Dashed lines indicate phase transitions. **Top**: Different LR schedules with same initial LR and λ. **Left**: cosine LR learns sparse and generalizing solutions. **Mid**: a const. large LR causes sparsification but no generalization. **Right**: step-decay LR displays sharply distinct sparsification and generalization phases in large and small LR phases. **Bottom**: For cosine LR, the three distinct learning phases occur at all sparsity levels, with sharper contracted dynamics for high sparsity.

4.3 LEARNING DYNAMICS AND DELAYED GENERALIZATION

The learning dynamics of DWF with cosine annealing exhibit three distinct phases, characterized by changes in accuracy, sparsity, and L_2 norm of the collapsed weights (Fig. 6, second row): In an **initial phase**, SGD learns easy-to-fit patterns without overfitting while the L_2 norm decreases. The **reorganization phase** is characterized by temporary drops in accuracy and an increase in weight norm, hinting at a period of representational restructuring to accommodate sparsity constraints. Sparsity emerges during or at the end of this phase. The final **mixed sparsification and generalization phase** shows improvements in training and validation accuracy as sparsification continues at a decreasing rate. The mixed nature of the final phase, contrasting the sharply separated sparsifi-

cation and generalization with step decay, is owed to gradual reduction in cosine annealing. Notably, with increasing regularization λ, the dynamics contract, and the phases occur in closer succession. This phased behavior shows that the more contracted the reorganization phase is, the higher compression and more severe the delayed generalization will be. This is reminiscent of the "grokking" phenomenon (Power et al., 2022) shown to be tightly linked to L_2 regularization (Liu et al., 2023).

4.4 IMPACT OF REGULARIZATION AND EVOLUTION OF LAYER-WISE METRICS

To investigate dynamics in more detail, we analyze the effect of D and λ on the sparsity and training trajectories (Fig. 7). Similar results for different architectures/datasets are included in Appendix F.

Figure 7: Impact of regularization λ on compression (**top**), training, and validation accuracy (**bottom**) for factorized ResNet-18 and $D \in \{2, 3, 4\}$. For large λ severely delayed generalization and extreme compression emerges simultaneously. Colors indicate the same λ in both rows.

As expected, increasing λ leads to higher compression ratios across all depths. Moreover, greater D enables higher compression ratios for the same λ. During the initial phase, the regularized training curves coincide with the unregularized trajectory until their departure at the onset of the reorganization phase. This departure occurs earlier the stronger the regularization. For greater factorization depths, the same λ values induce higher sparsity at the cost of reduced generalization performance, indicating a stronger regularizing effect[2]. The relationship between sparsity, λ, and the collapsed weight norm is further discussed in Appendix E.3. Appendix F.3 presents the layer-wise evolution of sparsity and weight norms, providing more detailed insights into the effects of DWF across the network topology for different architectures (e.g., Fig. 18a). Two key observations can be made: the first and last layers exhibit less sparsity, owed to their increased importance for the prediction. For the intermediate layers, there is a general trend toward higher compression for later layers. Secondly, the non-monotonic dynamics of the collapsed weight norm seem to be almost entirely driven by the first few and the last layer, while the intermediate layers behave homogeneously. Finally, the evolution of factor misalignment and its relation to the onset of sparsity is discussed in Appendix F.4.

5 PERFORMANCE EVALUATION

In this section, we evaluate the performance of DWF. In Appendices F and G, we provide further results and details on the experimental setup, including hyperparameters and training protocols.

5.1 FAILURE OF VANILLA L_1 OPTIMIZATION WITH SGD

The failure of SGD with vanilla L_1 regularization to achieve inherent sparsity has been previously observed by Ziyin & Wang (2023); Kolb et al. (2023). It is natural to ask whether this limitation is merely a benign optimization artifact or if it degrades the prunability of the regularized models. We, therefore, train a LeNet-300-100 on Fashion-MNIST with vanilla L_1 regularization as well as with DWF and $D = 2, 3$, inducing differentiable L_1 and non-convex $L_{2/3}$ regularization.

---

[2]Note that this does not imply worse performance in general, but a different optimal λ for different D.

Results The left plot in Fig. 1 (page 1) shows the tradeoff between performance and inherent sparsity (before pruning) for 100 logarithmically spaced λ values, confirming prior findings on the limitations of vanilla L_1 optimization. In contrast, differentiable L_1 regularization using DWF achieves a compression ratio of about 350 at 80% test accuracy. In addition, our DWF network with $D = 3$ is four times sparser than $D = 2$ at the same accuracy, underscoring the advantages of deeper factorizations. In the right plot of Fig. 1, we subsequently apply post-hoc magnitude pruning to each of the models at increasing compression ratios (without fine-tuning) until reaching random chance performance and use the best-performing pruned model at each fixed compression ratio to obtain the pruning curves. Results indicate that differentiable sparse training with factorized networks provides better tradeoffs than vanilla L_1 optimization, even after accounting for the numerical inaccuracies of using SGD for vanilla L_1. At 80% test accuracy, vanilla L_1 plus pruning requires twice as many parameters as its DWF counterpart, and three times as many as DWF ($D = 3$). This suggests SGD with L_1 struggles to find similarly well-prunable structures, while DWF yields much sparser models.

5.2 RUN TIMES

The perceptive reader might be concerned about the computational overhead induced by training deep factorized networks. Our experiments show this concern to be unwarranted, as the effect of the factorization depth is rather unimportant compared to batch size for both time per sample and memory cost. Appendix I.2 illustrates this for WRN-16-8 (Zagoruyko & Komodakis, 2016) and VGG-19 (Simonyan & Zisserman, 2014). For both models, the impact of factorization depth on computation time and memory usage becomes negligible as batch size increases. These findings suggest that practitioners can leverage deeper factorized networks without incurring substantial additional computational costs, particularly at typical batch sizes used in modern deep learning.

5.3 COMPRESSION BENCHMARK

We now evaluate DWF for factorization depths $D \in \{2, 3, 4\}$ against various pruning methods concerning test accuracy vs. compression, as well as the layer-wise allocation of the remaining weights.
Architectures and datasets: Our experiments cover commonly used computer vision benchmarks: LeNet-300-100 and LeNet-5 (LeCun et al., 1998) on MNIST, Fashion-MNIST, and Kuzushiji-MNIST, VGG-16 and VGG-19 (Simonyan & Zisserman, 2014) on CIFAR10 and CIFAR100, and ResNet-18 (He et al., 2016) on CIFAR10 and Tiny ImageNet.
Methods: We compare our method against Global magnitude pruning (**GMP**) after training (Han et al., 2015), a simple pruning method that removes the smallest weights across all layers and is surprisingly competitive, especially at low sparsities (Gale et al., 2019; Frankle et al., 2020); Single-shot Network Pruning (**SNIP**) (Lee et al., 2019), a pruning-at-initialization technique, showing competitive performance against other recent pruning methods (Wang et al., 2020); **SynFlow** (Tanaka et al., 2020), considered a state-of-the-art method for high sparsity regimes; **Random pruning**, serving as a naive baseline that removes weights uniformly at random; a shallow factorized network ($D = 2$) which is our variant of the **spred** algorithm (Ziyin & Wang, 2023) with improved initialization.
Tuning: For comparison methods, we use the established training configurations in Lee et al. (2019); Wang et al. (2020); Frankle et al. (2020) when available, and otherwise ensure comparability by using the same configuration for all methods. All models are trained with SGD and cosine learning rate annealing (Loshchilov & Hutter, 2016). For our method, **no** post-hoc pruning or fine-tuning is required and all layers are regularized equally. Further details are given in Appendix G.

Results Fig. 8 shows results for the fully-connected and convolutional LeNet-300-100 and LeNet-5 architectures on MNIST, F-MNIST, and K-MNIST. Across all datasets and models, our proposed DWF consistently outperforms existing pruning techniques, particularly at higher compression ratios. For LeNet-300-100 on MNIST, DWF with $D = 3, 4$ remains within 5% of the dense performance even above a compression ratio of 500, significantly surpassing other methods. On F-MNIST and K-MNIST, a similar performance gain is observed. LeNet-5 exhibits similar trends, with DWF maintaining high accuracy at compression ratios where other techniques, especially random pruning and SNIP, have collapsed. Notably, DWF sustains performance up to a compression ratio of 100 on K-MNIST, while competitors rapidly decline. SynFlow and GMP generally outperform random pruning and SNIP, but still fall short of DWF. When comparing shallow and deep factorizations, we see that $D > 2$ retains performance and delays model collapse much longer than $D = 2$. The

Figure 8: Accuracy vs. sparsity tradeoffs for LeNet architectures on MNIST and replacements of varying difficulty. Lines depict median test accuracies and shaded areas the minimum over three random initializations.

results demonstrate that DWF offers substantial gains in compression capability. Further, the clear separation between DWF and other methods in the high-sparsity regime indicates that our approach captures aspects of the model's representational power that are missed by the other techniques. These findings underscore the potential of DWF, particularly under severe parameter constraints.

For larger architectures and more complex datasets (Fig. 9), DWF continues to demonstrate superior performance, albeit less pronounced. We observe that the $D = 2$ factorization excels in the medium sparsity regime below a compression ratio of 100, while $D > 2$ shows enhanced resilience to performance degradation and delayed model collapse at more extreme sparsity levels.

Figure 9: Accuracy vs. sparsity for larger ResNet and VGG architectures on CIFAR and TinyImageNet.

Table 1 showcases the sparsest models achieved by each method while maintaining performance within 5% or 10% of the dense model accuracy. These tolerance levels are suitable for testing the medium to high sparsity regimes we focus on. Other levels can be read from Fig. 9. Of the 10 presented scenarios, DWF with $D = 3, 4$ achieves the highest compression in 9 cases, demonstrating the robustness of DWF in preserving model performance under extreme sparsity requirements. The best-ranked DWF model achieves 2 to 5 times the compression ratio of the best pruning method, and surpasses shallow factorization in all but one setting, albeit with smaller improvements ranging from 8% to 298%. For example, DWF with $D = 3$ reaches a compression ratio of 1014 (1456) for VGG-19 on CIFAR100 (ResNet-18 on CIFAR10) at 10% tolerance, improving by 8% (25%) over $D = 2$ and by 381% (102%) over the best pruning method SynFlow.

Allocation of layer-wise sparsity Finally, we investigate the reasons for model collapse in SNIP and GMP in the high sparsity regime by plotting the layer-wise remaining ratio (1/CR) for ResNet-18 and VGG-16 on CIFAR10 in the medium and extreme compression regimes, as shown in Fig. 10. At high compression, for both ResNet-18 and VGG-16, we observe that GMP and SNIP catastrophically prune entire layers. In contrast, SynFlow and DWF automatically learn adaptive layer-wise sparsity budgets which helps in avoiding such issues. While SynFlow does prune some layers entirely in ResNet-18, these correspond to skip connections that can be removed without interrupting

Table 1: Compression ratios (sparsities) of sparsest model within ε_{acc} percentage points of the dense model test accuracy. Random pruning is left out for clarity.

CR (↑)	ε_{acc}	LeNet-300-100	LeNet-5	ResNet-18	VGG-19	ResNet-18
		F-MNIST	K-MNIST	CIFAR10	CIFAR100	Tiny ImageNet
Depth 2	5%	141 (99.29%)	52 (98.08%)	466 (99.79%)	**484** (99.79%)	60 (98.34%)
	10%	362 (99.72%)	78 (98.71%)	1169 (99.91%)	939 (99.89%)	99 (98.99%)
Depth 3	5%	**506** (99.80%)	**75** (98.67%)	**573** (99.83%)	440 (99.77%)	**67** (98.51%)
	10%	1422 (99.93%)	134 (99.25%)	**1456** (99.93%)	**1014** (99.90%)	**161** (99.38%)
Depth 4	5%	486 (99.79%)	**75** (98.67%)	445 (99.78%)	215 (99.53%)	13 (92.39%)
	10%	**1442** (99.93%)	**139** (99.28%)	1161 (99.91%)	675 (99.85%)	113 (99.12%)
GMP	5%	156 (99.36%)	22 (95.37%)	211 (99.53%)	37 (97.27%)	60 (98.33%)
	10%	235 (99.58%)	32 (96.84%)	484 (99.79%)	68 (98.52%)	133 (99.25%)
SNIP	5%	76 (98.69%)	17 (94.10%)	140 (99.29%)	28 (96.47%)	18 (94.34%)
	10%	146 (99.32%)	24 (95.91%)	339 (99.70%)	42 (97.59%)	41 (97.56%)
Synflow	5%	141 (99.29%)	21 (95.23%)	210 (99.52%)	46 (97.81%)	24 (95.84%)
	10%	302 (99.67%)	37 (97.30%)	721 (99.86%)	218 (99.54%)	71 (98.60%)

the synaptic flow. Comparing SynFlow and DWF, we observe that DWF produces higher sparsity in the first and last layers across all settings. This is a particularly desirable property, as it leads to greater computational savings for a given overall sparsity level. Moreover, as opposed to removing the skip connections, DWF allocates less sparsity to these structures, suggesting a qualitatively distinct underlying structure optimization mechanism.

Figure 10: Allocation of layer-wise sparsity for different methods. SNIP and GMP show catastrophic pruning of whole layers (collapse) for high sparsities, whereas DWF, like SynFlow, finds adaptive sparsity allocations.

6 CONCLUSION

This paper introduces deep weight factorization (DWF), an extension of a previously proposed differentiable L_1 regularization to induce sparsity in general neural networks. By factorizing weights not only into two, but $D \geq 3$ parts, our method provably induces differentiable $L_{2/D}$ regularization that can be incorporated in any neural network. We analyze various properties and propose optimization strategies such as an initialization avoiding "bad" starting values and a sparsity-promoting learning rate scheme. We also identify three phases that describe the learning dynamics and (delayed) generalization behavior of DWF. Experiments demonstrate that DWF is usually superior to shallow factorization and outperforms dominant pruning techniques.

Limitations and future work In this work, we primarily focused on $D \in \{2, 3, 4\}$. While not incurring significant computational overhead (cf. Fig. 26), we found that increasing the factorization depth beyond four did not yield further sparsity improvements and introduced optimization challenges (cf. Fig. 15). Additionally, a limitation of our work is that we exclusively focused on DWF approaches resulting in unstructured sparsity regularization. Hence, an interesting potential direction for future research is to extend our factorization to structured sparsity problems.

REFERENCES

Maksym Andriushchenko, Aditya Vardhan Varre, Loucas Pillaud-Vivien, and Nicolas Flammarion. Sgd with large step sizes learns sparse features. In *International Conference on Machine Learning*, pp. 903–925. PMLR, 2023.

Sanjeev Arora, Nadav Cohen, Wei Hu, and Yuping Luo. Implicit regularization in deep matrix factorization. *Advances in Neural Information Processing Systems*, 32, 2019.

Francis Bach, Rodolphe Jenatton, Julien Mairal, Guillaume Obozinski, et al. Optimization with sparsity-inducing penalties. *Foundations and Trends in Machine Learning*, 4(1):1–106, 2012.

Marek Balcerzak, Ehrhard Behrends, and Filip Strobin. On certain uniformly open multilinear mappings. *Banach Journal of Mathematical Analysis*, 10(3):482–494, 2016.

Kartikeya Bhardwaj, Milos Milosavljevic, Liam O'Neil, Dibakar Gope, Ramon Matas, Alex Chalfin, Naveen Suda, Lingchuan Meng, and Danny Loh. Collapsible linear blocks for super-efficient super resolution. *Proceedings of Machine Learning and Systems*, 4:529–547, 2022.

Davis Blalock, Jose Javier Gonzalez Ortiz, Jonathan Frankle, and John Guttag. What is the state of neural network pruning? *Proceedings of machine learning and systems*, 2:129–146, 2020.

Kevin Bui, Fredrick Park, Shuai Zhang, Yingyong Qi, and Jack Xin. Improving network slimming with nonconvex regularization. *IEEE Access*, 9:115292–115314, 2021.

Feng Chen, Daniel Kunin, Atsushi Yamamura, and Surya Ganguli. Stochastic collapse: How gradient noise attracts sgd dynamics towards simpler subnetworks. *Advances in Neural Information Processing Systems*, 36, 2024.

Hongrong Cheng, Miao Zhang, and Javen Qinfeng Shi. A survey on deep neural network pruning: Taxonomy, comparison, analysis, and recommendations. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2024.

Zhen Dai, Mina Karzand, and Nathan Srebro. Representation costs of linear neural networks: Analysis and design. *Advances in Neural Information Processing Systems*, 34, 2021.

Tristan Deleu and Yoshua Bengio. Structured sparsity inducing adaptive optimizers for deep learning. *arXiv preprint arXiv:2102.03869*, 2021.

Rayen Dhahri, Alexander Immer, Bertrand Charpentier, Stephan Günnemann, and Vincent Fortuin. Shaving weights with occam's razor: Bayesian sparsification for neural networks using the marginal likelihood. In *Sixth Symposium on Advances in Approximate Bayesian Inference-Non Archival Track*, 2024.

Utku Evci, Trevor Gale, Jacob Menick, Pablo Samuel Castro, and Erich Elsen. Rigging the lottery: Making all tickets winners. In *International conference on machine learning*, pp. 2943–2952. PMLR, 2020.

Jianqing Fan and Runze Li. Variable selection via nonconcave penalized likelihood and its oracle properties. *Journal of the American Statistical Association*, 96(456):1348–1360, 2001.

L. E. Frank and Jerome H Friedman. A statistical view of some chemometrics regression tools. *Technometrics*, 35(2):109–135, 1993.

Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. In *International Conference on Learning Representations*, 2019.

Jonathan Frankle, Gintare Karolina Dziugaite, Daniel M Roy, and Michael Carbin. Pruning neural networks at initialization: Why are we missing the mark? *arXiv preprint arXiv:2009.08576*, 2020.

Jerome Friedman, Trevor Hastie, and Rob Tibshirani. Regularization paths for generalized linear models via coordinate descent. *Journal of Statistical Software*, 33(1):1, 2010.

Trevor Gale, Erich Elsen, and Sara Hooker. The state of sparsity in deep neural networks. *arXiv preprint arXiv:1902.09574*, 2019.

Daniel Gissin, Shai Shalev-Shwartz, and Amit Daniely. The implicit bias of depth: How incremental learning drives generalization. In *International Conference on Learning Representations*, 2019.

Patrick Glandorf, Timo Kaiser, and Bodo Rosenhahn. Hypersparse neural networks: Shifting exploration to exploitation through adaptive regularization. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 1234–1243, 2023.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pp. 249–256. JMLR Workshop and Conference Proceedings, 2010.

Yves Grandvalet. Least absolute shrinkage is equivalent to quadratic penalization. In *ICANN 98: Proceedings of the 8th International Conference on Artificial Neural Networks, Skövde, Sweden, 2–4 September 1998 8*, pp. 201–206. Springer, 1998.

Suriya Gunasekar, Jason D Lee, Daniel Soudry, and Nati Srebro. Implicit bias of gradient descent on linear convolutional networks. *Advances in Neural Information Processing Systems*, 31, 2018.

Shuxuan Guo, Jose M Alvarez, and Mathieu Salzmann. Expandnets: Linear over-parameterization to train compact convolutional networks. *Advances in Neural Information Processing Systems*, 33:1298–1310, 2020.

Song Han, Jeff Pool, John Tran, and William Dally. Learning both weights and connections for efficient neural network. *Advances in neural information processing systems*, 28, 2015.

Trevor Hastie, Rahul Mazumder, Jason D Lee, and Reza Zadeh. Matrix completion and low-rank svd via fast alternating least squares. *The Journal of Machine Learning Research*, 16(1):3367–3402, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 1026–1034, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Yang He and Lingao Xiao. Structured pruning for deep convolutional neural networks: A survey. *IEEE transactions on pattern analysis and machine intelligence*, 2023.

Yihui He, Xiangyu Zhang, and Jian Sun. Channel pruning for accelerating very deep neural networks. In *Proceedings of the IEEE international conference on computer vision*, pp. 1389–1397, 2017.

Torsten Hoefler, Dan Alistarh, Tal Ben-Nun, Nikoli Dryden, and Alexandra Peste. Sparsity in deep learning: Pruning and growth for efficient inference and training in neural networks. *Journal of Machine Learning Research*, 22(241):1–124, 2021.

Peter D Hoff. Lasso, fractional norm and structured sparse estimation using a hadamard product parametrization. *Computational Statistics & Data Analysis*, 115:186–198, 2017.

Yaohua Hu, Chong Li, Kaiwen Meng, Jing Qin, and Xiaoqi Yang. Group sparse optimization via $\ell_{p,q}$ regularization. *The Journal of Machine Learning Research*, 18(1):960–1011, 2017.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International Conference on Machine Learning*, pp. 448–456. pmlr, 2015.

Arthur Jacot. Implicit bias of large depth networks: a notion of rank for nonlinear functions. In *The Eleventh International Conference on Learning Representations*, 2023.

Li Jing, Jure Zbontar, et al. Implicit rank-minimizing autoencoder. *Advances in Neural Information Processing Systems*, 33:14736–14746, 2020.

Chris Kolb, Christian L Müller, Bernd Bischl, and David Rügamer. Smoothing the edges: a general framework for smooth optimization in sparse regularization using hadamard overparametrization. *arXiv preprint arXiv:2307.03571*, 2023.

Daniel Kunin, Javier Sagastuy-Brena, Surya Ganguli, Daniel LK Yamins, and Hidenori Tanaka. Neural mechanics: Symmetry and broken conservation laws in deep learning dynamics. *arXiv preprint arXiv:2012.04728*, 2020.

Aditya Kusupati, Vivek Ramanujan, Raghav Somani, Mitchell Wortsman, Prateek Jain, Sham Kakade, and Ali Farhadi. Soft threshold weight reparameterization for learnable sparsity. In *International Conference on Machine Learning*, pp. 5544–5555. PMLR, 2020.

Thien Le and Stefanie Jegelka. Training invariances and the low-rank phenomenon: beyond linear networks. *arXiv preprint arXiv:2201.11968*, 2022.

Yann LeCun, John Denker, and Sara Solla. Optimal brain damage. *Advances in neural information processing systems*, 2, 1989.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Yann LeCun, Léon Bottou, Genevieve B Orr, and Klaus-Robert Müller. Efficient backprop. In *Neural networks: Tricks of the trade*, pp. 9–50. Springer, 2002.

N Lee, T Ajanthan, and P Torr. Snip: single-shot network pruning based on connection sensitivity. In *International Conference on Learning Representations*. Open Review, 2019.

Eitan Levin, Joe Kileel, and Nicolas Boumal. The effect of smooth parametrizations on nonconvex optimization landscapes. *Mathematical Programming*, pp. 1–49, 2024.

Hao Li, Asim Kadav, Igor Durdanovic, Hanan Samet, and Hans Peter Graf. Pruning filters for efficient convnets. In *International Conference on Learning Representations*, 2022.

Jiangyuan Li, Thanh Nguyen, Chinmay Hegde, and Ka Wai Wong. Implicit sparse regularization: The impact of depth and early stopping. *Advances in Neural Information Processing Systems*, 34, 2021.

Yicheng Li and Qian Lin. Improving adaptivity via over-parameterization in sequence models. *arXiv preprint arXiv:2409.00894*, 2024.

Zhiyuan Li, Kaifeng Lyu, and Sanjeev Arora. Reconciling modern deep learning with traditional optimization analyses: The intrinsic learning rate. *Advances in Neural Information Processing Systems*, 33:14544–14555, 2020.

Junjie Liu, Zhe Xu, Runbin Shi, Ray CC Cheung, and Hayden KH So. Dynamic sparse training: Find efficient sparse network from scratch with trainable masked layers. *arXiv preprint arXiv:2005.06870*, 2020.

Zhuang Liu, Jianguo Li, Zhiqiang Shen, Gao Huang, Shoumeng Yan, and Changshui Zhang. Learning efficient convolutional networks through network slimming. In *Proceedings of the IEEE international conference on computer vision*, pp. 2736–2744, 2017.

Ziming Liu, Eric J Michaud, and Max Tegmark. Omnigrok: Grokking beyond algorithmic data. In *The Eleventh International Conference on Learning Representations*, 2023.

Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. *arXiv preprint arXiv:1608.03983*, 2016.

Christos Louizos, Max Welling, and Diederik P. Kingma. Learning sparse neural networks through l_0 regularization. In *International Conference on Learning Representations*, 2018.

Rahul Mazumder, Trevor Hastie, and Robert Tibshirani. Spectral regularization algorithms for learning large incomplete matrices. *The Journal of Machine Learning Research*, 11:2287–2322, 2010.

Nicolai Meinshausen and Peter Bühlmann. High-dimensional graphs and variable selection with the lasso. *The Annals of Statistics*, 34(3):1436–1462, 2006.

Mor Shpigel Nacson, Kavya Ravichandran, Nathan Srebro, and Daniel Soudry. Implicit bias of the step size in linear diagonal neural networks. In *International Conference on Machine Learning*, pp. 16270–16295. PMLR, 2022.

Behnam Neyshabur, Ryota Tomioka, and Nathan Srebro. In search of the real inductive bias: On the role of implicit regularization in deep learning. In *ICLR (Workshop)*, 2015.

Nadav Joseph Outmezguine and Noam Levi. Decoupled weight decay for any p norm. *arXiv preprint arXiv:2404.10824*, 2024.

Wenqing Ouyang, Yuncheng Liu, Ting Kei Pong, and Hao Wang. Kurdyka-lojasiewicz exponent via hadamard parametrization. *arXiv preprint arXiv:2402.00377*, 2024.

Rahul Parhi and Robert D Nowak. Deep learning meets sparse regularization: A signal processing perspective. *arXiv preprint arXiv:2301.09554*, 2023.

Scott Pesme, Loucas Pillaud-Vivien, and Nicolas Flammarion. Implicit bias of sgd for diagonal linear networks: a provable benefit of stochasticity. *Advances in Neural Information Processing Systems*, 34:29218–29230, 2021.

Clarice Poon and Gabriel Peyré. Smooth bilevel programming for sparse regularization. *Advances in Neural Information Processing Systems*, 34, 2021.

Clarice Poon and Gabriel Peyré. Smooth over-parameterized solvers for non-smooth structured optimization. *Mathematical Programming*, pp. 1–56, 2023.

Alethea Power, Yuri Burda, Harri Edwards, Igor Babuschkin, and Vedant Misra. Grokking: Generalization beyond overfitting on small algorithmic datasets. *arXiv preprint arXiv:2201.02177*, 2022.

Pedro Savarese, Hugo Silva, and Michael Maire. Winning the lottery with continuous sparsification. *Advances in neural information processing systems*, 33:11380–11390, 2020.

Simone Scardapane, Danilo Comminiello, Amir Hussain, and Aurelio Uncini. Group sparse regularization for deep neural networks. *Neurocomputing*, 241:81–89, 2017.

Jonathan Schwarz, Siddhant Jayakumar, Razvan Pascanu, Peter Latham, and Yee Teh. Powerpropagation: A sparsity inducing weight reparameterisation. *Advances in Neural Information Processing Systems*, 34, 2021.

Fanhua Shang, Yuanyuan Liu, Fanjie Shang, Hongying Liu, Lin Kong, and Licheng Jiao. A unified scalable equivalent formulation for schatten quasi-norms. *Mathematics*, 8(8):1325, 2020.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Berfin Simsek, François Ged, Arthur Jacot, Francesco Spadaro, Clément Hongler, Wulfram Gerstner, and Johanni Brea. Geometry of the loss landscape in overparameterized neural networks: Symmetries and invariances. In *International Conference on Machine Learning*, pp. 9722–9732. PMLR, 2021.

Melvin Dale Springer. *The algebra of random variables*. New York: Wiley,, 1979.

Melvin Dale Springer and WE Thompson. The distribution of products of independent random variables. *SIAM Journal on Applied Mathematics*, 14(3):511–526, 1966.

Nathan Srebro, Jason D. M. Rennie, and Tommi S. Jaakkola. Maximum-margin matrix factorization. In *Proceedings of the 17th International Conference on Neural Information Processing Systems*, NIPS'04, pp. 1329–1336, Cambridge, MA, USA, 2004. MIT Press.

Hidenori Tanaka, Daniel Kunin, Daniel L Yamins, and Surya Ganguli. Pruning neural networks without any data by iteratively conserving synaptic flow. *Advances in neural information processing systems*, 33:6377–6389, 2020.

Yingjie Tian and Yuqi Zhang. A comprehensive survey on regularization strategies in machine learning. *Information Fusion*, 80:146–166, 2022.

Robert Tibshirani. Regression shrinkage and selection via the lasso. *Journal of the Royal Statistical Society: Series B (Methodological)*, 58(1):267–288, 1996.

Ryan Tibshirani. Equivalences between sparse models and neural networks. *Working Notes*, 2021.

Tomas Vaskevicius, Varun Kanade, and Patrick Rebeschini. Implicit regularization for optimal sparse recovery. *Advances in Neural Information Processing Systems*, 32, 2019.

Chaoqi Wang, Guodong Zhang, and Roger Grosse. Picking winning tickets before training by preserving gradient flow. *arXiv preprint arXiv:2002.07376*, 2020.

Huan Wang, Can Qin, Yue Bai, and Yun Fu. Why is the state of neural network pruning so confusing? on the fairness, comparison setup, and trainability in network pruning. *arXiv preprint arXiv:2301.05219*, 2023.

Sifan Wang, Hanwen Wang, Jacob H Seidman, and Paris Perdikaris. Random weight factorization improves the training of continuous neural representations. *arXiv preprint arXiv:2210.01274*, 2022.

Wei Wen, Chunpeng Wu, Yandan Wang, Yiran Chen, and Hai Li. Learning structured sparsity in deep neural networks. In *Advances in Neural Information Processing Systems*, volume 29, 2016.

Blake Woodworth, Suriya Gunasekar, Jason D Lee, Edward Moroshko, Pedro Savarese, Itay Golan, Daniel Soudry, and Nathan Srebro. Kernel and rich regimes in overparametrized models. In *Conference on Learning Theory*, pp. 3635–3673. PMLR, 2020.

Zongben Xu, Hai Zhang, Yao Wang, XiangYu Chang, and Yong Liang. L1/2 regularization. *Science China Information Sciences*, 53(6):1159–1169, 2010.

Yang Yang, Yaxiong Yuan, Avraam Chatzimichailidis, Ruud JG van Sloun, Lei Lei, and Symeon Chatzinotas. Proxsgd: Training structured neural networks under regularization and constraints. In *International Conference on Learning Representations (ICLR) 2020*, 2020.

Sergey Zagoruyko. 92.45% on cifar-10 in torch. https://torch.ch/blog/2015/07/30/cifar.html, 2015. Torch Blog.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. In *British Machine Vision Conference 2016*. British Machine Vision Association, 2016.

Cun-Hui Zhang. Nearly unbiased variable selection under minimax concave penalty. *The Annals of Statistics*, 38(2):894–942, 2010.

Cun-Hui Zhang and Jian Huang. The sparsity and bias of the lasso selection in high-dimensional linear regression. *The Annals of Statistics*, 36(4):1567–1594, 2008.

Qiaozhe Zhang, Ruijie ZHANG, Jun Sun, and Yingzhuang Liu. How sparse can we prune a deep network: A fundamental limit perspective. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024.

Peng Zhao, Yun Yang, and Qiao-Chu He. High-dimensional linear regression via implicit regularization. *Biometrika*, 2022.

Xiao Zhou, Weizhong Zhang, Hang Xu, and Tong Zhang. Effective sparsification of neural networks with global sparsity constraint. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 3599–3608, 2021.

Liu Ziyin. Symmetry induces structure and constraint of learning. In *Forty-first International Conference on Machine Learning*, 2023.

Liu Ziyin and Zihao Wang. spred: Solving l1 penalty with sgd. In *International Conference on Machine Learning*, pp. 43407–43422. PMLR, 2023.

Liu Ziyin, Botao Li, Tomer Galanti, and Masahito Ueda. The probabilistic stability of stochastic gradient descent. *arXiv preprint arXiv:2303.13093*, 2023.

Appendices

A   FURTHER RELATED LITERATURE

Convex and Non-convex sparse regularization   Convex and non-convex regularization for sparsity-inducing effects has a long history as it is well-understood with strong theoretical underpinnings. Notable works in this direction include Tibshirani (1996); Fan & Li (2001); Meinshausen & Bühlmann (2006); Zhang & Huang (2008) for convex norm-based sparse regularization and Friedman et al. (2010); Fan & Li (2001); Zhang (2010); Xu et al. (2010) studying its non-convex extensions. While mathematically rigorous, they see limited application in deep learning due to their non-differentiability exactly where sparsity is achieved, requiring the implementation of non-smooth optimization routines that are often inflexible and do not scale well. While some works exist on proximal-type optimization routines in deep learning (Yang et al., 2020; Deleu & Bengio, 2021), their popularity remains far behind pruning and other approaches, with these methods being rarely applied, used as comparisons, or given much if any attention in surveys (Hoefler et al., 2021; Gale et al., 2019). Nevertheless, the use of L_1 or structured $L_{2,1}$ regularization is ubiquitous in sparse deep learning (Han et al., 2015; He et al., 2017; Liu et al., 2017; Li et al., 2022). These sparsity regularization pruning methods (Cheng et al., 2024) use sparse regularization to shrink weights before applying a subsequent pruning step for actual sparsity. However, the conceptual framework underlying these heuristic-based methods remains poorly understood.

Weight factorization without and with explicit regularization   Weight factorizations, also studied under the names diagonal linear networks (Woodworth et al., 2020), redundant parameterization (Ziyin & Wang, 2023), or Hadamard product parameterization (Hoff, 2017; Tibshirani, 2021; Kolb et al., 2023) in various contexts, can be traced back to Grandvalet (1998) and was rediscovered both in statistics (Hoff, 2017) and machine learning Neyshabur et al. (2015). Later, Tibshirani (2021); Kolb et al. (2023) and Ziyin & Wang (2023) used this approach to induce sparsity via L_2 regularization. Further works using weight factorization from the field of optimization include Poon & Peyré (2021; 2023). Ouyang et al. (2024) show that the Kurdyka-Łojasiewicz exponent at a second-order stationary point of a factorized and L_2 regularized objective can be inferred from its corresponding L_1 penalized counterpart. These works are closest to ours in spirit, namely, factorizing the weights of existing problems to achieve sparsity in the original weight space under L_2 regularization. None of these works, however, studied deeper factorizations of neural network parameters. A closely related approach to incorporate the induced non-convex L_q regularization ($q < 1$) into DNN training was recently proposed by Outmezguine & Levi (2024), who base their method on the η-trick (Bach et al., 2012) instead of the L_2 regularized weight factorization we study. This method re-parametrizes the regularization function instead of factorizing the network parameters, utilizing a different variational formulation of the L_q quasi-norm. Despite having the same effective L_q regularization, DWF incorporates additional symmetry-induced sparsity-promoting effects through weight factorization and the stochastic collapse phenomenon (Ziyin, 2023; Chen et al., 2024). Another branch of literature studies the *representation cost* of DNN architectures $f_{\mathbf{w}}$ for a specific function f, defined as $R(f) = \min_{\mathbf{w}: f_{\mathbf{w}}=f} \|\mathbf{w}\|_2^2$, showing that the L_2 cost of representing a linear function using a diagonal linear network yields the $L_{2/D}$ quasi-norm (Dai et al., 2021; Jacot, 2023).

Apart from the previous works using explicit regularization, the implicit regularization effect of weight factorization was studied by various researchers, both in statistics and deep learning, including Neyshabur et al. (2015); Gunasekar et al. (2018); Gissin et al. (2019); Vaskevicius et al. (2019); Woodworth et al. (2020); Pesme et al. (2021); Zhao et al. (2022); Li et al. (2021). However, such approaches are usually impractical for real applications, requiring vanishing initializations or specific loss functions. For example, the implicit bias of deep weight factorizations does not extend to non-convex regularizers under the squared loss (Nacson et al., 2022). Powerpropagation is a different sparsity-inducing weight transformation with implicit regularization effect and proposed by Schwarz et al. (2021) to also provide a tool for practical applications.

Various papers have also studied the factorization of weights without explicit regularization in the context of implicit acceleration caused by the factors acting as adaptive learning rates. Notable examples include Arora et al. (2019); Wang et al. (2022); Li & Lin (2024).

Pruning in neural networks   The landscape of pruning and sparse training methods is confusing due to the plethora of complex sparsification pipelines, incorporating numerous techniques at the same time, and an enormous amount of hyperparameters like pruning schedules or learning rates at

different stages. A fair comparison is further complicated by the lack of established, streamlined evaluation processes and opposing objectives in some methods. Pruning, arguably the most popular and widespread method, can be used in innumerable ways to sparsify neural networks, which makes comparisons among these particularly difficult (Wang et al., 2023). Existing pruning techniques use pruning at initialization (Lee et al., 2019; Wang et al., 2020; Tanaka et al., 2020), pruning after training by, e.g., magnitude pruning (Han et al., 2015; Gale et al., 2019), pruning during training, iterative pruning (Frankle et al., 2020), or pruning and re-growth (Evci et al., 2020). Recent surveys can be found in Blalock et al. (2020); Hoefler et al. (2021); Cheng et al. (2024). Prominent examples include the lottery ticket hypothesis (Frankle & Carbin, 2019), proposing that many networks contain equally performant, but much smaller subnetworks that can be found at initialization. A Bayesian pruning version is suggested in Dhahri et al. (2024). Another approach related to pruning is soft thresholding reparameterization (Kusupati et al., 2020), a sparse training method incorporating a soft-thresholding step into its network. Despite its success, however, it was shown to be outperformed by the differentiable L_1 approach, i.e., DWF with $D = 2$ (Ziyin & Wang, 2023). Recently, Zhang et al. (2024) establish theoretical bounds on network prunability using convex geometry, showing that the fundamental one-shot pruning limit without sacrificing performance is determined by weight magnitudes and the sharpness of the loss landscape, providing a unified framework to help explain the effectiveness of magnitude-based pruning. They empirically show that L_1 regularized post-hoc magnitude pruning approximately matches the derived pruning limit before performance degrades significantly.

Sparsity-inducing regularization in neural networks Apart from pruning, the application of norm-based regularizers is also common on deep learning (Scardapane et al., 2017; Wen et al., 2016; Han et al., 2015; Bui et al., 2021). This includes L_0-type reguarlization methods (Louizos et al., 2018; Zhou et al., 2021; Savarese et al., 2020). Some of these such as Louizos et al. (2018) were however found to not work well due to the stochastic sampling in their training procedure. Other approaches include adaptive regularization (Glandorf et al., 2023) or dynamic masking (Liu et al., 2020).

Sparsity based on structural constraints While we focus on unstructured pruning in this paper, there exist various approaches for structured pruning including Wen et al. (2016); Li et al. (2022); Bui et al. (2021); Liu et al. (2017). For a recent survey, see He & Xiao (2023). A link also made in our paper is the connection between sparsity and symmetries. Using structures of symmetries can guide the sparsification of neural networks. Papers studying this link include the works of Kunin et al. (2020); Simsek et al. (2021); Le & Jegelka (2022), but also some various recent work such Ziyin (2023); Ziyin et al. (2023); Chen et al. (2024).

Matrix factorization related induced regularization In Srebro et al. (2004); Mazumder et al. (2010); Shang et al. (2020); Hastie et al. (2015) different matrix factorization regularization schemes are proposed to, e.g., learn incomplete matrices (Mazumder et al., 2010; Hastie et al., 2015) or for better generalization (Srebro et al., 2004). There are also neural architectures implementing some sort of matrix factorization to achieve better performance or acceleration (Guo et al., 2020; Jing et al., 2020; Bhardwaj et al., 2022). Although not directly related to our factorization, we will briefly explain their idea to contrast it with our approach. For example, Guo et al. (2020) note a beneficial effect of applying L_2 regularization on the (matrix) factors in the form of $\|W_1\|_2^2 + \|W_2\|_2^2$ as opposed to the L_2 regularizer $\|W_1 W_2\|_2^2$ proposed in Arora et al. (2019). This observation can be explained by the low-rank bias induced on the product matrix, whereas the second approach is simple L_2 regularization on the product.

B   INTUITION FOR SPARSITY VIA L_2 REGULARIZED WEIGHT FACTORIZATION

Deep Weight Factorization introduces overparameterization by decomposing each original weight w multiplicatively into $D \geq 2$ factors $\omega_1, \ldots, \omega_D$. Without additional L_2 regularization, this induces artificial rescaling symmetries (Definition 1), resulting in infinitely many possible factorizations for each weight, all producing the same collapsed network and thus leaving the loss function unchanged. However, when L_2 regularization is applied, it influences the choice among these factorizations by preferring those with minimal Euclidean norm. With L_2 regularization, only minimum-norm (bal-

anced) factorizations can be optimal, as otherwise, we could always decrease the L_2 penalty by picking a more balanced factorization while leaving the unregularized loss unchanged (cf. Lemma 1).

To provide some geometric intuition using a more concrete example, consider the simplest case of factorizing a scalar weight $w \in \mathbb{R}$ into two factors, $w = \omega_1 \cdot \omega_2$, as illustrated in Fig. 3 for $w \in \{0, 0.25\}$. The set of all possible factorizations $\{(\omega_1, \omega_2) \in \mathbb{R}^2 : \omega_1\omega_2 = w\}$ is given by the points on the coordinate axes for $w = 0$ and forms a rectangular hyperbola in the (ω_1, ω_2) plane for non-zero w (cf. Fig. 3). Among these, the factorizations with minimal L_2 norm (i.e., minimal distance to the origin) are located at the vertices of the hyperbola. These minimum-norm factorizations are balanced, meaning the factors are equal in magnitude, as the vertices of a rectangular hyperbola always lie either on the diagonal $\omega_2 = \omega_1$ or $\omega_2 = -\omega_1$. Specifically, the two vertices of the resulting hyperbola are given by $(\sqrt{|w|}, \sqrt{|w|})$ and $(-\sqrt{|w|}, -\sqrt{|w|})$ for positive w, and $(\sqrt{|w|}, -\sqrt{|w|})$ and $(-\sqrt{|w|}, \sqrt{|w|})$ for negative w. Combined with the case $w = 0$, the minimum-norm factorizations (ω_1^*, ω_2^*) for any w are obtained as

$$(\omega_1^*, \omega_2^*) = \begin{cases} \left(\sqrt{|w|}, \sqrt{|w|}\right) \text{ or } \left(-\sqrt{|w|}, -\sqrt{|w|}\right) & , w > 0 \\ (0, 0) & , w = 0 \\ \left(\sqrt{|w|}, -\sqrt{|w|}\right) \text{ or } \left(-\sqrt{|w|}, \sqrt{|w|}\right) & , w < 0. \end{cases} \quad (6)$$

At these points, the L_2 penalty evaluates to $2|w|$, effectively turning into an L_1 penalty on the collapsed weight w scaled by a factor of 2.

For deeper factorizations involving more than two factors the same line of reasoning applies, but visualizing the set of possible factorizations as in Fig. 3 for $D = 2$ becomes challenging. The minimum L_2 penalty at balanced factorizations reduces to a non-convex sparsity-inducing $L_{2/D}$ penalty on the collapsed weight. This serves as a lower bound of the L_2 penalty for every fixed value of w. Once the factors reach this balanced state, which is an "absorbing state" under (S)GD, the optimization process locks in this configuration for all future iterations by symmetry (cf. Lemma 6). Thus, the combination of DWF and L_2 regularization induces sparsity in the collapsed weights by promoting balanced factorizations, at which the L_2 penalty reduces to a lower-degree quasi-norm penalty on w.

C   FURTHER RESULTS AND MISSING PROOFS

C.1   PROOF OF LEMMA 1

Proof. Let $\boldsymbol{\omega} = (\boldsymbol{\omega}_1, \dots, \boldsymbol{\omega}_D) \in \mathbb{R}^{Dp}$ be a local minimizer of $\mathcal{L}_{\boldsymbol{\omega}, \lambda}(\boldsymbol{\omega})$. As the factorization is applied independently to each parameter, it suffices to treat the scalar case: We will prove that $|\omega_{j,1}| = \dots = |\omega_{j,D}|$ for all $j \in [p]$.

The rescaling symmetries of DWF ensures that $\mathcal{L}_{\boldsymbol{\omega}, 0}$ (the factorized loss without regularization) is constant over all possible factorizations of a collapsed parameter $\boldsymbol{\varpi}$. However, the L_2 regularization term $\lambda D^{-1} \sum_{d=1}^{D} \|\boldsymbol{\omega}_d\|_2^2$ enforces a preference for min-norm factorization. For each scalar weight indexed by $j \in [p]$, consider its factors $\omega_{j,1}, \dots, \omega_{j,D}$. Applying the AM-GM inequality to the L_2 penalty of the DWF loss yields

$$D^{-1} \sum_{d=1}^{D} \omega_{j,d}^2 \geq \left(\prod_{d=1}^{D} (\omega_{j,d})^2 \right)^{1/D} = |\omega_{j,1} \cdots \omega_{j,D}|^{2/D} = |\varpi_j|^{2/D} \quad \forall j \in [p] \quad (7)$$

This shows the balancedness requirement for the minimizers of $\mathcal{L}_{\boldsymbol{\omega}, \lambda}(\boldsymbol{\omega})$, as the AM-GM inequality holds tight if and only if all terms are equal, i.e., $|\omega_{j,1}| = \dots = |\omega_{j,D}|$.

Summing over the factorizations of all weights yields the non-convex $L_{2/D}$ regularizer $\|\boldsymbol{\varpi}\|_{2/D}^{2/D}$ as the minimum L_2 penalty for a given collapsed weight $\boldsymbol{\varpi} \in \mathbb{R}^p$. □

C.2   PROOF OF LEMMA 2

Definition 3 (Standard Weight Initialization). A standard weight initialization scheme for a neural network layer with n_{in} input units and n_{out} output units is a probability distribution with mean 0 and variance σ^2, where $\sigma^2 = \frac{cg^2}{n_{\text{mode}}}$. Here, g is a gain factor depending on the activation function, c is a constant, and n_{mode} is either n_{in}, n_{out} or their sum. Common examples include the Kaiming ($\sigma^2 = \frac{2}{n_{\text{in}}}$) (He et al., 2015), Glorot ($\sigma^2 = \frac{2}{n_{\text{in}} + n_{\text{out}}}$) (Glorot & Bengio, 2010), or LeCun initialization ($\sigma^2 = \frac{1}{n_{\text{in}}}$) (LeCun et al., 2002).

Proof. Recall that using a standard initialization (cf. Definition 3), each factor is initialized as $\omega_{j,d}^{(l)} \sim \mathcal{N}(0, \sigma_l^2)$, where $\sigma_l^2 = 1/n_{in}^{(l)} < 1$ in the case of LeCun initialization (LeCun et al., 2002). For clarity, we assume the width $n_{in}^{(l)}$ to be constant across layers $l \in [L]$.

To prove the first statement, we note that $\mathbb{E}[\varpi_j^{(l)}] = 0$ and $\text{Var}\left(\varpi_j^{(l)}\right) = \prod_{d=1}^{D} \text{Var}\left(\omega_{j,d}^{(l)}\right) = \sigma^{2D}$. Applying Chebyshev's inequality, we get for any $\varepsilon > 0$

$$\mathbb{P}\left(\left|\varpi_j^{(l)} - \mathbb{E}\left[\varpi_j^{(l)}\right]\right| \geq \varepsilon\right) = \mathbb{P}(|\varpi_j^{(l)}| \geq \varepsilon) \leq \frac{\text{Var}\left(\varpi_j^{(l)}\right)}{\varepsilon^2} = \frac{\sigma^{2D}}{\varepsilon^2}. \quad (8)$$

Finally, we have $0 \leq \lim_{D \to \infty} \mathbb{P}(|\varpi_j^{(l)}| \geq \varepsilon) \leq \lim_{D \to \infty} \frac{\sigma^{2D}}{\varepsilon^2} = 0$, and thus, by the squeeze theorem: $\lim_{D \to \infty} \mathbb{P}(|\varpi_j^{(l)}| \geq \varepsilon) = 0$. This shows that $\varpi_j^{(l)} \xrightarrow{P} 0$ as $D \to \infty$.

For the second point, we denote the pre-activation of neuron k in layer l as

$$y_k^{(l)} = \sum_{i=1}^{n_{\text{in}}} \text{w}_{k_i}^{(l)} \phi\left(y_i^{(l-1)}\right) = \sum_{i=1}^{n_{\text{in}}} \left(\prod_{d=1}^{D} \omega_{k_i, d}^{(l)} \right) \phi\left(y_i^{(l-1)}\right), \quad (9)$$

where $\omega_{k_i, d}^{(l)}$ is the d-th scalar factor of the weight $\text{w}_{k_i}^{(l)}$ associated with input i of neuron k in layer l. The activation $\phi\left(y_i^{(l-1)}\right)$ is the activation function ϕ applied to the pre-activations from layer $l - 1$. To simplify calculations, we assume that the activation function is approximately linear

around the origin, implying $\text{Var}\left(\phi\left(y_i^{(l-1)}\right)\right) \approx \text{Var}\left(y_i^{(l-1)}\right)$ and allowing us to ignore the gain factor, as valid for, e.g., tanh activation. Using that the factors $\omega_{k_i,d}^{(l)}$ and activations $\phi\left(y_i^{(l-1)}\right)$ are independent and identically distributed, respectively, the variance of $y_k^{(l)}$ is given by:

$$\text{Var}\left(y_k^{(l)}\right) = \sum_{i=1}^{n_{\text{in}}} \text{Var}\left(\prod_{d=1}^{D} \omega_{k_i,d}^{(l)} \cdot \phi\left(y_i^{(l-1)}\right)\right) = \sum_{i=1}^{n_{\text{in}}} \text{Var}\left(\phi\left(y_i^{(l-1)}\right)\right) \cdot \prod_{d=1}^{D} \text{Var}\left(\omega_{k_i,d}^{(l)}\right). \quad (10)$$

Since the factors are initialized with $\text{Var}\left(\omega_{k_i,d}^{(l)}\right) = \sigma_l^2 = \frac{1}{n_{\text{in}}}$, the variance of $y_k^{(l)}$ is:

$$\text{Var}\left(y_k^{(l)}\right) = \sum_{i=1}^{n_{\text{in}}} \text{Var}\left(y_i^{(l-1)}\right)\left(\frac{1}{n_{\text{in}}}\right)^D = n_{\text{in}} \cdot \frac{\text{Var}\left(y^{(l-1)}\right)}{n_{\text{in}}^D} = \frac{\text{Var}\left(y^{(l-1)}\right)}{n_{\text{in}}^{D-1}} \quad (11)$$

In non-factorized layers, the n_{in} in Eq. (11) cancel out, resulting in equal activation variances across layers. In contrast, standard initializations in factorized layers do not account for the exponent D appearing in the variance of the collapsed weight $\varpi_{k_i}^{(l)}$, and thus result in a variance reduction in each subsequent layer as a function of input units and factorization depth D. Applying the above relationship recursively, we see that the variance at layer L is

$$\text{Var}(y_k^{(L)}) = \text{Var}(y^{(1)}) \cdot \left(\frac{1}{n_{\text{in}}}\right)^{(D-1)(L-1)} \quad (12)$$

To avoid reducing or amplifying the magnitudes of input signals exponentially, a proper initialization requires $\text{Var}(y_k^{(L)})$ to equal some constant, typically set to unity (He et al., 2015). In factorized networks with $D \geq 2$, however, standard initialization causes strong dependence on n_{in}, D, and L.

$\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad\square$

C.3 PROOF OF THEOREM 1

Before proving the theorem, we introduce some required notations and auxiliary results. Our strategy is to first show equivalence between the the $L_{2/D}$-regularized objective $\mathcal{L}_{\mathbf{w},\lambda}(\mathbf{w})$ and an intermediate objective $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega}) := \mathcal{L}_{\mathbf{w},\lambda}(\boldsymbol{\omega}_1 \odot \ldots \odot \boldsymbol{\omega}_D)$ that still contains the regularizer $\|\boldsymbol{\omega}_1 \odot \ldots \odot \boldsymbol{\omega}_D\|_{2/D}^{2/D}$ instead of the L_2 regularization in the DWF loss. In a second step, we show the equivalence of $\tilde{\mathcal{L}}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega})$ and the DWF objective $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega})$. We define the inverse factorization function as $\mathcal{K} : \mathbb{R}^{Dp} \to \mathbb{R}^p, \boldsymbol{\omega} \mapsto \boldsymbol{\omega}_1 \odot \ldots \odot \boldsymbol{\omega}_D = \boldsymbol{\varpi}$, and remark that it is a smooth surjection. To show the correspondence of minimizers between both objectives, we require $\mathcal{K}$ to be locally open at each minimizer (Levin et al., 2024).

Definition 4 (Local openness). *A mapping $\mathcal{K} : \mathbb{R}^{Dp} \to \mathbb{R}^p, \boldsymbol{\omega} \mapsto \mathcal{K}(\boldsymbol{\omega})$ is locally open at $\boldsymbol{\omega}$ if for every $\varepsilon > 0$ we can find $\delta > 0$ such that $B(\mathcal{K}(\boldsymbol{\omega}), \delta) \subseteq \mathcal{K}(B(\boldsymbol{\omega}, \varepsilon))$, where $B(\boldsymbol{\omega}, \varepsilon)$ denotes an ε-ball around $\boldsymbol{\omega}$. Further $\mathcal{K}$ is called globally open if it is locally open at all $\boldsymbol{\omega} \in \mathbb{R}^{Dp}$.*

Using the same notation, continuity can be defined as $\forall \varepsilon > 0 \,\exists \delta > 0 : \mathcal{K}(B(\boldsymbol{\omega}, \delta)) \subseteq B(\mathcal{K}(\boldsymbol{\omega}), \varepsilon)$. For DWF, global openness can be established using the following result extending a result for scalar-valued factorizations in Balcerzak et al. (2016):

Proposition 1 (Kolb et al. (2023), Lemma 5.3). *The inverse weight factorization $\mathcal{K} : \mathbb{R}^{Dp} \to \mathbb{R}^p, (\boldsymbol{\omega}_1, \ldots, \boldsymbol{\omega}_D) \mapsto \boldsymbol{\omega}_1 \odot \ldots \odot \boldsymbol{\omega}_D$ is globally open.*

Proof. Let $\mathcal{L}_{\mathbf{w},\lambda}(\mathbf{w})$ be the penalized objective function using $\mathbf{w} \in \mathbb{R}^p$, and $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega}) = \mathcal{L}_{\mathbf{w},\lambda}(\mathcal{K}(\boldsymbol{\omega}))$ be the intermediary objective defined on $\boldsymbol{\omega} \in \mathbb{R}^{Dp}$.

Lemma 3. *If $\hat{\mathbf{w}}$ is a local minimizer of $\mathcal{L}_{\mathbf{w},\lambda}(\mathbf{w})$, then any $\hat{\boldsymbol{\omega}}$ such that $\hat{\boldsymbol{\omega}} \in \mathcal{K}^{-1}(\hat{\mathbf{w}}) = \{\boldsymbol{\omega} : \mathcal{K}(\boldsymbol{\omega}) = \hat{\mathbf{w}}\}$ is a local minimizer of $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega})$ with $\mathcal{L}_{\mathbf{w},\lambda}(\hat{\mathbf{w}}) = \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\hat{\boldsymbol{\omega}})$.*

Proof. Assume $\hat{\mathbf{w}}$ is a local minimizer of $\mathcal{L}_{\mathbf{w},\lambda}(\mathbf{w})$, then $\exists \varepsilon > 0 : \forall \mathbf{w}' \in B(\hat{\mathbf{w}}, \varepsilon) : \mathcal{L}_{\mathbf{w},\lambda}(\hat{\mathbf{w}}) \leq \mathcal{L}_{\mathbf{w},\lambda}(\mathbf{w}')$. Since $\mathcal{K}(\boldsymbol{\omega})$ is surjective, choose any $\hat{\boldsymbol{\omega}} \in \mathcal{K}^{-1}(\hat{\mathbf{w}}) = \{\boldsymbol{\omega} : \mathcal{K}(\boldsymbol{\omega}) = \hat{\mathbf{w}}\}$. By continuity of $\mathcal{K}$, there $\exists \delta > 0 : \mathcal{K}(B(\hat{\boldsymbol{\omega}}, \delta)) \subseteq B(\mathcal{K}(\hat{\boldsymbol{\omega}}), \varepsilon) = B(\hat{\mathbf{w}}, \varepsilon)$. This means $\forall \boldsymbol{\omega}' \in B(\hat{\boldsymbol{\omega}}, \delta) : \mathcal{K}(\boldsymbol{\omega}') = \mathbf{w}' \in B(\hat{\mathbf{w}}, \varepsilon)$. Since by assumption, $\mathcal{L}_{\mathbf{w},\lambda}(\hat{\mathbf{w}}) \leq \mathcal{L}_{\mathbf{w},\lambda}(\mathbf{w}')$ for all $\mathbf{w}' \in B(\hat{\mathbf{w}}, \varepsilon)$, and by continuity all $\boldsymbol{\omega}' \in B(\hat{\boldsymbol{\omega}}, \delta)$ map to some $\mathbf{w}'$ in $B(\hat{\mathbf{w}}, \varepsilon)$ under $\mathcal{K}$, we conclude that

$$\forall \boldsymbol{\omega}' \in B(\hat{\boldsymbol{\omega}}, \delta) : \mathcal{L}_{\mathbf{w},\lambda}(\mathcal{K}(\hat{\boldsymbol{\omega}})) = \mathcal{L}_{\mathbf{w},\lambda}(\hat{\mathbf{w}}) \leq \mathcal{L}_{\mathbf{w},\lambda}(\mathbf{w}') = \mathcal{L}_{\mathbf{w},\lambda}(\mathcal{K}(\boldsymbol{\omega}')) = \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\hat{\boldsymbol{\omega}}).$$

Therefore, if $\hat{\mathbf{w}}$ is a local minimizer of $\mathcal{L}_{\mathbf{w},\lambda}(\mathbf{w})$, then any $\hat{\boldsymbol{\omega}} \in \mathcal{K}^{-1}(\hat{\mathbf{w}})$ is a local minimizer of $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega}) = \mathcal{L}_{\mathbf{w},\lambda}(\mathcal{K}(\boldsymbol{\omega}))$ with equivalent local minima $\mathcal{L}_{\mathbf{w},\lambda}(\hat{\mathbf{w}}) = \mathcal{L}_{\mathbf{w},\lambda}(\mathcal{K}(\hat{\boldsymbol{\omega}}))$. $\qquad\square$

Lemma 4. *If $\hat{\boldsymbol{\omega}}$ is a local minimizer of $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega}) = \mathcal{L}_{\mathbf{w},\lambda}(\mathcal{K}(\boldsymbol{\omega}))$, then $\mathcal{K}(\hat{\boldsymbol{\omega}}) = \hat{\mathbf{w}}$ is a local minimizer of $\mathcal{L}_{\mathbf{w},\lambda}(\mathbf{w})$ with $\mathcal{L}_{\mathbf{w},\lambda}(\hat{\mathbf{w}}) = \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\hat{\boldsymbol{\omega}})$.*

Proof. Assume $\hat{\boldsymbol{\omega}}$ is a local minimizer of $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega})$, then $\exists \varepsilon > 0 : \forall \boldsymbol{\omega}' \in B(\hat{\boldsymbol{\omega}}, \varepsilon) : \mathcal{L}_{\mathbf{w},\lambda}(\mathcal{K}(\hat{\boldsymbol{\omega}})) \leq \mathcal{L}_{\mathbf{w},\lambda}(\mathcal{K}(\boldsymbol{\omega}'))$. Since $\mathcal{K}(\boldsymbol{\omega})$ is open at $\hat{\boldsymbol{\omega}}$, there is $\delta > 0$ such that $B(\mathcal{K}(\hat{\boldsymbol{\omega}}), \delta) \subseteq \mathcal{K}(B(\hat{\boldsymbol{\omega}}, \varepsilon))$. Thus, $\forall \mathbf{w}' \in B(\mathcal{K}(\hat{\boldsymbol{\omega}}), \delta) : \exists \boldsymbol{\omega}' \in B(\hat{\boldsymbol{\omega}}, \varepsilon)$ such that $\mathcal{K}(\boldsymbol{\omega}') = \mathbf{w}'$. But since we have by assumption that $\forall \boldsymbol{\omega}' \in B(\hat{\boldsymbol{\omega}}, \varepsilon) : \mathcal{L}_{\mathbf{w},\lambda}(\mathcal{K}(\hat{\boldsymbol{\omega}})) \leq \mathcal{L}_{\mathbf{w},\lambda}(\mathcal{K}(\boldsymbol{\omega}'))$, and we established $\forall \mathbf{w}' \in B(\hat{\mathbf{w}}, \delta) \exists \boldsymbol{\omega}' \in B(\hat{\boldsymbol{\omega}}, \varepsilon) : \mathbf{w}' = \mathcal{K}(\boldsymbol{\omega}')$, we obtain

$$\forall \mathbf{w}' \in B(\hat{\mathbf{w}}, \delta) : \mathcal{L}_{\mathbf{w},\lambda}(\hat{\mathbf{w}}) = \mathcal{L}_{\mathbf{w},\lambda}(\mathcal{K}(\hat{\boldsymbol{\omega}})) \leq \mathcal{L}_{\mathbf{w},\lambda}(\mathcal{K}(\boldsymbol{\omega}')) = \mathcal{L}_{\mathbf{w},\lambda}(\mathbf{w}').$$

Thus, $\hat{\mathbf{w}} = \mathcal{K}(\hat{\boldsymbol{\omega}})$ is a local minimizer of $\mathcal{L}_{\mathbf{w},\lambda}(\mathbf{w})$ with corresponding local minimum $\mathcal{L}_{\mathbf{w},\lambda}(\hat{\mathbf{w}}) = \mathcal{L}_{\mathbf{w},\lambda}(\mathcal{K}(\hat{\boldsymbol{\omega}}))$. $\qquad\square$

Together, Lemma 3 and Lemma 4 establish the equivalence of all minima between $\mathcal{L}_{\mathbf{w},\lambda}(\mathbf{w})$ and the factorized intermediate objective $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega}) = \mathcal{L}_{\mathbf{w},\lambda}(\mathcal{K}(\boldsymbol{\omega}))$, both of which are non-differentiable. The following result extends the equivalence to the differentiable factorized objective with L_2 regularization.

Lemma 5. *Let $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega})$ be the factorized objective Eq. (2) with L_2 regularization and $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega}) = \mathcal{L}_{\mathbf{w},\lambda}(\mathcal{K}(\boldsymbol{\omega}))$ be the intermediate objective defined above. Then **i)** if $\hat{\boldsymbol{\omega}}$ is a local minimizer of $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega})$, then $\hat{\boldsymbol{\omega}}$ is also a local minimizer of $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega})$ with $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\hat{\boldsymbol{\omega}}) = \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\hat{\boldsymbol{\omega}})$. Further, **ii)** if $\tilde{\boldsymbol{\omega}}$ is a local minimizer of $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega})$, then there exists $\hat{\boldsymbol{\omega}}$ such that $\mathcal{K}(\hat{\boldsymbol{\omega}}) = \mathcal{K}(\tilde{\boldsymbol{\omega}})$, and $\hat{\boldsymbol{\omega}}$ is a local minimizer of $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega})$ with $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\hat{\boldsymbol{\omega}}) = \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\tilde{\boldsymbol{\omega}})$.*

Proof. We start by relating both objectives using the factor misalignment $M(\boldsymbol{\omega}) = D^{-1} \sum_{d=1}^{D} \|\boldsymbol{\omega}_d\|_2^2 - \|\boldsymbol{\varpi}\|_{2/D}^{2/D}$. The DWF objective is then $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega}) = \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega}) + \lambda M(\boldsymbol{\omega})$, where $M(\boldsymbol{\omega}) \geq 0$ attains zero if an only if $\boldsymbol{\omega}$ represents a balanced factorization (Lemma 1).

To prove the first point, we assume that $\hat{\boldsymbol{\omega}}$ is a local minimizer of $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega})$, so that $\exists \varepsilon > 0 : \forall \boldsymbol{\omega}' \in B(\hat{\boldsymbol{\omega}}, \varepsilon) : \mathcal{L}_{\boldsymbol{\omega},\lambda}(\hat{\boldsymbol{\omega}}) < \mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega}')$. By Lemma 1, only balanced factors can be solutions to $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega})$, implying $M(\hat{\boldsymbol{\omega}}) = 0$ and $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\hat{\boldsymbol{\omega}}) = \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\hat{\boldsymbol{\omega}})$. To evoke a contradiction, assume that $\hat{\boldsymbol{\omega}}$ is not a local minimizer of $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega})$, so that $\forall \varepsilon > 0 : \exists \boldsymbol{\omega}' \in B(\hat{\boldsymbol{\omega}}, \varepsilon)$ with $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega}') < \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\hat{\boldsymbol{\omega}})$.

First, note that $\boldsymbol{\omega}'$ can not result in the same collapsed weight $\mathcal{K}(\boldsymbol{\omega}')$ as $\hat{\boldsymbol{\omega}}$, since $\hat{\boldsymbol{\omega}}$ already is a balanced min-norm factorization. Hence, $\mathcal{K}(\boldsymbol{\omega}') \neq \mathcal{K}(\hat{\boldsymbol{\omega}})$. To reduce notational overload, we abbreviate $\mathcal{K}(\boldsymbol{\omega}) = \boldsymbol{\varpi}$ again. Observing that points in the neighborhood of the product $\hat{\boldsymbol{\varpi}}$ of a balanced factorization $\hat{\boldsymbol{\omega}}$ can be attained by simple rescaling of $\hat{\omega}_{j,d}$ to conserve balancedness, each balanced factor is a continuous function of the resulting $\boldsymbol{\varpi}$. Selecting an arbitrary index from the set of feasible balanced factorizations lets us define a continuous function $\mathcal{F} : \mathbb{R}^p \to \mathbb{R}^{Dp}, \boldsymbol{\varpi} \mapsto (\boldsymbol{\omega}_1, \ldots, \boldsymbol{\omega}_D)$, that maps products to a specific balanced factorization. By continuity, $\forall \varepsilon > 0 \exists \delta > 0 : \mathcal{F}(B(\boldsymbol{\varpi}, \delta)) \subseteq B(\mathcal{F}(\boldsymbol{\varpi}), \varepsilon)$. This means for every $\boldsymbol{\varpi}' \in B(\hat{\boldsymbol{\varpi}}, \delta)$ there is is a corresponding balanced factorization $\tilde{\boldsymbol{\omega}} \in B(\hat{\boldsymbol{\omega}}, \varepsilon)$ that also maps to $\boldsymbol{\varpi}'$ and thereby implies $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\tilde{\boldsymbol{\omega}}) = \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega}')$ since $M(\tilde{\boldsymbol{\omega}}) = 0$. Together, we get the following chain of inequalities:

$$\mathcal{L}_{\boldsymbol{\omega},\lambda}(\tilde{\boldsymbol{\omega}}) = \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\tilde{\boldsymbol{\omega}}) = \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega}') < \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\hat{\boldsymbol{\omega}}) = \mathcal{L}_{\boldsymbol{\omega},\lambda}(\hat{\boldsymbol{\omega}}).$$

The first and last equalities hold because $M(\tilde{\boldsymbol{\omega}}) = M(\hat{\boldsymbol{\omega}}) = 0$, and the second because $\tilde{\boldsymbol{\omega}}$ and $\boldsymbol{\omega}'$ are different factorizations of $\boldsymbol{\varpi}'$ and $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega})$ is constant over factorizations the product $\boldsymbol{\varpi}'$. Then we have found $\tilde{\boldsymbol{\omega}} \in B(\hat{\boldsymbol{\omega}}, \varepsilon)$ so that $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\tilde{\boldsymbol{\omega}}) < \mathcal{L}_{\boldsymbol{\omega},\lambda}(\hat{\boldsymbol{\omega}})$ leading to a contradiction. Therefore, if $\hat{\boldsymbol{\omega}}$ is a local minimizer of $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega})$, then $\hat{\boldsymbol{\omega}}$ is also a local minimizer of $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega})$ with equivalent minima.

For the second step, we proceed by assuming $\tilde{\boldsymbol{\omega}}$ is a local minimizer of $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega})$, so $\exists \varepsilon > 0 : \forall \boldsymbol{\omega}' \in B(\tilde{\boldsymbol{\omega}}, \varepsilon) : \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\tilde{\boldsymbol{\omega}}) \leq \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega}')$. Let $\hat{\boldsymbol{\omega}}$ be a balanced factorization of $\mathcal{K}(\tilde{\boldsymbol{\omega}})$. Then $M(\hat{\boldsymbol{\omega}}) = 0$ and $\mathcal{K}(\hat{\boldsymbol{\omega}}) = \mathcal{K}(\tilde{\boldsymbol{\omega}})$, implying $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\tilde{\boldsymbol{\omega}}) = \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\hat{\boldsymbol{\omega}}) = \mathcal{L}_{\boldsymbol{\omega},\lambda}(\hat{\boldsymbol{\omega}})$.
By continuity of $\mathcal{K}$, $\exists \delta > 0 : \forall \boldsymbol{\omega}' \in B(\hat{\boldsymbol{\omega}}, \delta) : \mathcal{K}(\boldsymbol{\omega}') \in B(\mathcal{K}(\hat{\boldsymbol{\omega}}), \varepsilon)$. For any $\boldsymbol{\omega}' \in B(\hat{\boldsymbol{\omega}}, \delta)$, we have $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega}') \geq \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\tilde{\boldsymbol{\omega}})$, as $\mathcal{K}(\boldsymbol{\omega}') \in B(\mathcal{K}(\tilde{\boldsymbol{\omega}}), \varepsilon)$ and $\tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega})$ depends only on $\mathcal{K}(\boldsymbol{\omega})$.
Therefore, $\forall \boldsymbol{\omega}' \in B(\hat{\boldsymbol{\omega}}, \delta) : \mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega}') = \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\boldsymbol{\omega}') + \lambda M(\boldsymbol{\omega}') \geq \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\tilde{\boldsymbol{\omega}}) = \mathcal{L}_{\boldsymbol{\omega},\lambda}(\hat{\boldsymbol{\omega}})$, where the inequality holds as $M(\boldsymbol{\omega}') \geq 0$. Thus, $\hat{\boldsymbol{\omega}}$ is a local minimizer of $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega})$ with $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\hat{\boldsymbol{\omega}}) = \tilde{\mathcal{L}}_{\mathbf{w},\lambda}(\tilde{\boldsymbol{\omega}})$.

$\square$

The previous results transitively establish that if $\hat{\boldsymbol{\omega}}$ is a local minimizer of $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega})$, then $\hat{\boldsymbol{\varpi}} = \hat{\boldsymbol{\omega}}_1 \odot \ldots \odot \hat{\boldsymbol{\omega}}_D$ is a local minimizer of $\mathcal{L}_{\mathbf{w},\lambda}(\mathbf{w})$. Conversely, if $\hat{\mathbf{w}}$ is a minimizer of $\mathcal{L}_{\mathbf{w},\lambda}(\mathbf{w})$, then there exists a local minimizer $\hat{\boldsymbol{\omega}}$ of $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega})$ such that $\hat{\boldsymbol{\varpi}} = \hat{\mathbf{w}}$. This finishes the proof.

$\square$

C.4 BALANCED FACTORS AND ABSORBING STATES IN SGD OPTIMIZATION (LEMMA 6)

Lemma 6 (Balanced factors are absorbing states in SGD). *Consider the SGD iterates of a depth-D factorized network with parameters $\boldsymbol{\omega}^{(t)} = (\boldsymbol{\omega}_1^{(t)}, \ldots, \boldsymbol{\omega}_D^{(t)})$ at iteration $t \in \mathbb{N}$, where the j-th entry of the collapsed weight vector $\boldsymbol{\varpi}^{(t)}$ is $\varpi_j^{(t)} = \omega_{j,1}^{(t)} \cdot \ldots \cdot \omega_{j,D}^{(t)}$. Then, i) if $\varpi_j^{(t)} = 0$ and $M(\boldsymbol{\omega}_j^{(t)}) = 0$, then $\omega_{j,d}^{(t')} = 0$ for all $d \in [D]$ and $t' > t$. Further, ii) $M(\boldsymbol{\omega}_j^{(t)}) = 0$ implies $M(\boldsymbol{\omega}_j^{(t')}) = 0$ for all $t' > t$.*

In other words, a balanced factorization at 0 causes the SGD dynamics to "collapse" and the factors remain zero for all subsequent iterations, effectively reducing the expressiveness of the model.

Proof. Consider the SGD updates for the factors $\boldsymbol{\omega}_d \in \mathbb{R}^p$, $d \in [D]$, in a factorized network with L_2 regularization. Let $\mathcal{L}_{\boldsymbol{\omega},0}(\boldsymbol{\omega})$ denote the part of the loss function without regularization and assume a batch size of n without loss of generality:

$$\boldsymbol{\omega}_d^{(t+1)} = \boldsymbol{\omega}_d^{(t)} - \eta^{(t)} \big(\nabla_{\boldsymbol{\omega}_d} \mathcal{L}_{\boldsymbol{\omega},0}(\boldsymbol{\omega}^{(t)}) + 2D^{-1}\lambda \boldsymbol{\omega}_d^{(t)} \big) \tag{13}$$

Using the chain rule, the SGD updates are given by:

$$\boldsymbol{\omega}_d^{(t+1)} = \boldsymbol{\omega}_d^{(t)} - \eta^{(t)} \big(\nabla_{\boldsymbol{\varpi}} \mathcal{L}_{\boldsymbol{\omega},0}(\boldsymbol{\omega}^{(t)}) \odot \big(\textstyle\bigodot_{k \neq d} \boldsymbol{\omega}_k^{(t)} \big) + 2D^{-1}\lambda \boldsymbol{\omega}_d^{(t)} \big) \tag{14}$$

To show the collapse in the dynamics for a balanced zero factorization, consider the scalar case $\varpi_j^{(t)} = 0$ with factorization $\boldsymbol{\omega}_j^{(t)} = \{\omega_{j,d}^{(t)}\}_{d=1}^D$ such that $M(\boldsymbol{\omega}_j^{(t)}) = 0$. Then $\omega_{j,d}^{(t)} = 0$ for all $d \in [D]$, as the update becomes:

$$\omega_{j,d}^{(t+1)} = 0 - \eta^{(t)} \big([\nabla_{\boldsymbol{\varpi}} \mathcal{L}_{\boldsymbol{\omega},0}(\boldsymbol{\omega}^{(t)})]_j \cdot 0 + 2D^{-1}\lambda \cdot 0 \big) = 0 \tag{15}$$

This holds for all subsequent iterations, proving $\omega_{j,d}^{(t')} = 0$ for all $d \in [D]$ and $t' > t$. Next we show the more general case of SGD dynamics conserving balancedness, i.e., $M(\boldsymbol{\omega}_j^{(t)}) = 0$, or

equivalently, $|\omega_{j,1}^{(t)}| = \cdots = |\omega_{j,D}^{(t)}| = m_j^{(t)}$. Let $\omega_{j,d} = s_{j,d}^{(t)} m_j^{(t)}$, where $s_{j,d}^{(t)} = \text{sign}(\omega_{j,d}^{(t)})$ and $s_{\varpi_j}^{(t)} = \text{sign}(\prod_{d=1}^{D} s_{j,d}^{(t)})$. We investigate the scalar updates:

$$\omega_{j,d}^{(t+1)} = s_{j,d}^{(t)} m_j^{(t)} - \eta^{(t)}\left([\nabla_{\varpi}\mathcal{L}_{\omega,0}(\boldsymbol{\omega}^{(t)})]_j \cdot (m_j^{(t)})^{D-1} \cdot \frac{s_{\varpi_j}^{(t)}}{s_{j,d}^{(t)}} + 2D^{-1}\lambda s_{j,d}^{(t)} m_j^{(t)}\right) \qquad (16)$$

Because $1/s_{j,d}^{(t)} = s_{j,d}^{(t)}$, we can factor out $s_{j,d}^{(t)}$ from all terms in the update. Hence, the resulting magnitude at iteration $t+1$ is:

$$|\omega_{j,d}^{(t+1)}| = \left|m_j^{(t)} - \eta^{(t)}\left([\nabla_{\varpi}\mathcal{L}_{\omega,0}(\boldsymbol{\omega}^{(t)})]_j \cdot (m_j^{(t)})^{D-1} \cdot s_{\varpi_j}^{(t)} + 2D^{-1}\lambda m_j^{(t)}\right)\right| \qquad (17)$$

Since the magnitude is constant over d, it is shown that $M\big(\boldsymbol{\omega}_j^{(t')}\big) = 0$ for all $t' > t$. $\qquad\square$

This "stochastic collapse" (Chen et al., 2024) is a recently investigated phenomenon where the noise in SGD dynamics drives iterates toward simpler *invariant sets* of the weight space that remain unchanged under SGD. However, the dynamics that cause this collapse are poorly understood, including how it is determined to which simpler structure the model collapses, with unclear implications for generalization in broad settings. The attractivity of these simpler structures is associated with high noise levels (Ziyin et al., 2023), providing an explanation for the generalization benefits of large initial LRs, induced by regularizing overly expressive networks via stochastic collapse. While potentially positive effects on generalization were shown, the research community is not yet certain about the broader consequences of this phenomenon.

D ALGORITHMS

In the following, we provide the algorithms for the proposed initialization (Section 4.1) of DWF networks Appendix D.1 and how to train these networks Appendix D.2.

D.1 DWF INITIALIZATION

Algorithm 1 DWF Initialization with Variance-Matching and Absolute Value Truncation

---

1: **Input:**
2:    Number L and parameter size n_l of layers, factorization depth D, minimum absolute value ε
3:    Standard initializations $\{\mathcal{P}(\mathrm{w}_j^{(l)}) \sim \mathcal{N}(0, \sigma_{\mathrm{w},l}^2)\}_{l=1}^L$
4: **for** $l = 1$ to L **do**
5:    $\sigma_l \leftarrow (\sigma_{\mathrm{w},l})^{1/D}$
6:    $\omega_{\min}^{(l)} \leftarrow \varepsilon^{1/D}$
7:    $\omega_{\max}^{(l)} \leftarrow \min\left\{1, (2\sigma_{\mathrm{w},l})^{1/D}\right\}$
8:      **for** each weight $\mathrm{w}_j^{(l)}$ in n_l **do**
9:        **for** $d = 1$ to D **do**
10:          **repeat**
11:            $\omega_{j,d}^{(l)} \sim \mathcal{N}(0, \sigma_l^2)$
12:          **until** $\omega_{\min}^{(l)} < |\omega_{j,d}^{(l)}| < \omega_{\max}^{(l)}$
13:        **end for**
14:      **end for**
15: **end for**
16: **Output:**
17:    Initialized factors $\{\omega_{j,d}^{(l)}\}_{d=1}^D$ for all weights $j \in [n_l]$ per layer and all layers $l \in [L]$.

D.2 DWF TRAINING

Algorithm 2 Training Factorized Neural Networks

1: **Input:**
2:    Dataset $\mathcal{D} = \{(\boldsymbol{x}_i, y_i)\}_{i=1}^n$, network architecture $\mathcal{A}$ with L layers and weights $\mathbf{w} \in \mathbb{R}^p$
3:    Factorization depth $D \geq 2$, factor initialization scheme `DWF-Init` (Alg. 1)
4:    Training hyperparameters $\{T, |\mathcal{B}|, \text{LRSchedule } \{\eta^{(t)}\}_{t=1}^T, \lambda\}$
5:    $\varepsilon_{\text{tiny}}$ (e.g., float32 machine epsilon $\approx 1.19 \times 10^{-7}$)
6: **Deep Weight Factorization:**
7:    Factorize the weights $\mathbf{w}$ of $\mathcal{A}$ as:
8:    $\mathbf{w} \leftarrow \boldsymbol{\omega}_1 \odot \ldots \odot \boldsymbol{\omega}_D$ and obtain $f_{\boldsymbol{\omega}}(\boldsymbol{\omega})$ from $f_{\mathrm{w}}(\mathrm{w})$
9: **Initialize weights $\boldsymbol{\omega}$ of $f_{\boldsymbol{\omega}}(\boldsymbol{\omega})$:**
10:    $\boldsymbol{\omega} \leftarrow \text{DWF-Init}(\mathcal{A}, D, \varepsilon, \text{standard init } \mathcal{P})$
11: **for** each training step $t \in \{0, \ldots, T-1\}$ **do**
12:    Sample a mini-batch $\{(\boldsymbol{x}_i, y_i)\}_{i=1}^{|\mathcal{B}|}$ from the $\mathcal{D}$
13:    Update $\boldsymbol{\omega}_d$ using SGD:
14:      $\boldsymbol{\omega}_d^{(t+1)} \leftarrow \boldsymbol{\omega}_d^{(t)} - \eta^{(t)} \nabla_{\boldsymbol{\omega}_d}\left(\mathcal{L}_{\boldsymbol{\omega},0}(\boldsymbol{\omega}^{(t)}) + \lambda D^{-1} \sum_{d=1}^D \|\boldsymbol{\omega}_d^{(t)}\|_2^2\right)$ $\forall\, d \in [D]$
15:    Update LR:
16:      $\eta^{(t+1)} \leftarrow \text{LRSchedule}(t+1)$
17: **end for**
18: **Post-training factor collapse:**
19:    Collapse factors to obtain weights for $\mathcal{A}$:
20:    $\hat{\boldsymbol{\varpi}} = \boldsymbol{\omega}_1^{(T)} \odot \ldots \odot \boldsymbol{\omega}_D^{(T)}$
21:    Apply numerical mach. epsilon threshold $\varepsilon_{\text{tiny}}$ to remove approx. 0 weights:
22:    $\hat{\varpi}_j \leftarrow 0$ if $|\hat{\varpi}_j| < \varepsilon_{\text{tiny}}$ $\forall\, j \in [p]$
23:    Transfer sparse weights $\hat{\boldsymbol{\varpi}}$ back to $\mathcal{A}$
24: **Output:**
25:    Sparse collapsed network parameters $\hat{\boldsymbol{\varpi}} = \hat{\mathbf{w}}$

E DETAILS ON OPTIMIZATION

E.1 LEARNING RATES IN FACTORIZED NETWORKS

Ablation study on overall learning rate Our goal is to determine suitable LR ranges for achieving high sparsity with good generalization in factorized networks. Additionally, we investigate how deeper factorization affects LR requirements. We train factorized LeNet-300-100 with $D \in \{2, 3, 4\}$ and our `DWF` on MNIST, using initial LRs ranging from 10^{-3} to 2. All models are trained using SGD with a cosine LR schedule. The results, displayed in Fig. 11, show excessively high LRs lead to highly variable results, especially at higher compression ratios. Similarly, too small LRs result in poor or even no sparsification. Notably, models with greater D exhibit more robustness to LR variations, maintaining performance over a wider range of compression ratios compared to shallower factorizations. Across all depths, selecting a large initial LR slightly below the edge where training becomes unstable yields the best overall results, balancing both effective training with high compression ratios. and providing evidence for the importance of a large LR phase in successfully training with DWF.

Figure 11: Sparsity-accuracy tradeoffs for a grid of learning rates, demonstrating the importance of appropriately large LRs for DWF. Left to right shows factorization depths $D \in \{2, 3, 4\}$.

Ablation on the stability of optimal LRs across the sparsity range In another ablation study, we investigate the impact of different sparsity requirements on the optimal initial LR. To do this, we train a LeNet-300-100 on MNIST for $D \in \{2, 3, 4\}$ on a large number of LR and λ combinations. For each D, we train all combinations of the learning rate η and the regularization λ, comprising 8 different LRs between 10^{-3} and 1, and a grid of 20 λ values logarithmically spaced between 10^{-6} and 10^{-1}. We obtain the Pareto frontier for each D by removing all runs that are dominated by other runs in either test accuracy or compression ratio. Fig. 12 shows the corresponding tradeoffs, with the color of the points indicating the optimal learning rate for the corresponding λ. Confirming the importance of large LRs, the result further demonstrates that the range of optimal LRs remains at a high level across sparsity requirements, except for a slight trend toward distinctly larger LRs for models with little regularization. This can be explained by the intricate relationship between LR and λ, together forming the *intrinsic* LR. When λ is reduced, this is compensated using a larger LR to recover optimal performance (Li et al., 2020).

Figure 12: Ablation on optimal LRs at different amounts of sparsity using LeNet-300-100 on MNIST. Note that none of the smaller LRs are selected as optimal.

E.2   ABLATION STUDY ON INITIALIZATIONS

In Fig. 13, we extend the experimental analysis of standard initialization and our proposed corrections on performance and sparsity in factorized networks, complementing the experiment on a fully-connected architecture (right plot of Fig. 4) by a convolutional LeNet-5 architecture. Similar to the results in Fig. 4, we observe a failure of standard initialization for $D > 2$. For $D = 2$, contrasting results for LeNet-300-100, some sparsity is indeed achieved using LeNet-5. The attainable tradeoff, however, is vastly outperformed by using the two corrections in the `DWF` initialization (Algorithm 1).

Figure 13: Comparison of different factor initializations and depths D. For $D = 2$, training with standard initialization does not completely fail, but is strongly inferior to our adjusted factor initializations. Those also retain trainability with even better tradeoffs for $D > 2$, while standard initialization causes the model to become untrainable using SGD.

E.3   RELATIONSHIP BETWEEN SPARSITY, REGULARIZATION AND WEIGHT NORMS

In Fig. 14, we present results on the relationship between sparsity (measured via the CR), regularization induced by different λ values, and L_2 weight norms of the collapsed parameter ϖ. From the first row, we see that increases in compression ratio for increasing λ values have a similar trend with all depths starting at the same regularization strength to induce sparsity. For all datasets and regularization strengths except for very large λ values for ResNet-18, the $D = 4$ model always yields a more compressed model than the $D = 3$ model, which in turn is sparser than the $D = 2$ model for given λ. In the second row and smaller models, we see a short increase in L_2 norm when increasing the regularization, followed by a drop in L_2 norm that finally goes to zero at the point where the compression ratio for the same λ stagnates. A slightly different behavior can be seen for ResNet, where the collapsed norm seems to monotonically decrease for increasing λ values (i.e., norms do not increase first and then decrease). Finally, the third row indicates smaller L_2 norms the more compressed models become, again with deeper factorizations achieving a higher compression ratios at the same L_2 norm just before model collapse.

Figure 14: Relationship between different regularization strengths and compression ratio (first row), regularization strength and L_2 norm (second row), as well as compression ratio and L_2 norm (third row) for different datasets (columns) and different factorization depths D (colors).

F   ADDITIONAL RESULTS AND ABLATION STUDIES

F.1   ABLATION STUDY ON THE FACTORIZATION DEPTH D

In our experiments, we considered deeper factorizations up to a level of $D = 4$. This cut-off is not chosen arbitrarily but follows empirical observations that non-convex L_q regularization achieves an optimal tradeoff between superior sparsity performance and difficulty of numerical optimization roughly at $q = 0.5$ (Hu et al., 2017). In an ablation study, we investigate if this also holds for the DWF approach. Fig. 15 displays the sparsity-accuracy curves attained by factorizations depths up to $D = 8$ and three different LRs in the range that performed well for $D = 4$. We use the same hyperparameter configuration as described in Appendix G. Results show that in all settings, deeper factorizations beyond $D = 4$ offer no improvements in generalization or sparsity, while their training becomes increasingly unstable.

Figure 15: Factorization depths $D > 4$ empirically do not improve performance but become unstable to train. Sparsity-accuracy curves for LeNet-300-100 on MNIST with increasing LRs shown from left to right. The results demonstrate the benefits of large LRs, particularly for little additional regularization.

F.2   COMBINED TRAINING AND VALIDATION ACCURACY

Fig. 17 contains the deferred training and compression trajectories over a range of λ values, as shown exemplary for ResNet-18 on CIFAR10 in the main text (Fig. 7). For improved clarity, we display the running mean of the validation accuracy over three iterations. In addition, Fig. 16 illustrates the change in training learning dynamics for an extended grid of λ values in the top row. Validation accuracies without moving average smoothing are displayed in the bottom row.

Figure 16: Impact of regularization λ on training (**top**) and validation accuracy (**bottom**) for VGG-19 on CIFAR100 and $D \in \{2, 3, 4\}$. The top row shows the training curves for the whole grid of λ values. Bottom row shows validation accuracies without running mean for selected λ.

F.3   EVOLUTION OF LAYER-WISE COMPRESSION AND WEIGHT NORMS

This section provides a detailed examination of the layer-wise dynamics regarding the evolution of sparsity, complementing the analysis in Section 4.4. Figure 18 illustrates the layer-wise evolution of sparsity (top) and collapsed weight norm (bottom) for different architectures and datasets, using a factorization depth $D = 3$ and increasing regularization strength λ.

The plots reveal broadly consistent patterns across different architectures. For stronger regularization, we observe a more rapid and pronounced onset of sparsity across all layers. Different layers exhibit varying rates of sparsification, with deeper layers generally achieving higher compression

(a) Convolutional LeNet-5 on K-MNIST

(b) VGG-16 on CIFAR10

(c) WRN-16-8 on CIFAR100

(d) ResNet-34 on TinyImageNet

Figure 17: Impact of regularization λ on compression (**top**), training, and validation accuracy (**bottom**) for various architectures and datasets, using $D \in \{2, 3, 4\}$.

ratios more quickly than earlier layers. The layer-wise norm trajectories show a characteristic pattern of initial increase, for the first layer, followed by a peak and gradual decrease. The deeper levels exhibit a simpler dynamic, showing an initial short decrease followed by a low plateau. Stronger regularization leads to earlier peaking and faster decay of weight norms, corresponding to faster sparsification. Notably, the first layer exhibits distinct behavior (see also Fig. 19a), often showing

the lowest compression ratio and the highest peak in weight norm. These more complex dynamics indicate stronger feature learning in earlier layers closer to the input data. Combined, these observations provide insights into how DWF affects different parts of the network during training and how this process is mediated by regularization.

(a) ResNet-18 on CIFAR10

(b) VGG-16 on CIFAR10

(c) VGG-19 on CIFAR100

Figure 18: Layer-wise evolution of sparsity (**top**) and collapsed weight norm (**bottom**) using $D = 3$ and increasing regularization λ (left to right) for different architectures and datasets.

F.4 EVOLUTION OF MISALIGNMENT AND ONSET OF SPARSITY

We investigate the empirical dynamics of the factor misalignment $M(\omega)$ and demonstrate that DWF ensures balanced factorizations for sufficiently large λ. Our analysis reveals an interesting connection between the reduction of misalignment and the onset of sparsity in the learning dynamics, both at the layer-wise and overall model levels.

(a) ResNet-18 on CIFAR10 ($D = 2$)

(b) VGG-16 on CIFAR10 ($D = 2$)

Figure 19: Evolution of the average layer-wise factor misalignment (dashed) together with layer-wise sparsity (solid) for ResNet-18 and VGG-16 on CIFAR10 and $D = 2$. Increasing values of λ shown from left to right.

Figures 19a and 19b illustrate the layer-wise evolution of sparsity and the average misalignment per layer for depth-2 factorized ResNet-18 and VGG-16 trained on CIFAR-10. The factor misalignment $M(\boldsymbol{\omega})$ is calculated at the layer level and normalized by the number of weights in each layer, providing a granular view of misalignment evolution across the network.

Figure 20: Evolution of factor misalignment $M(\boldsymbol{\omega})$ for VGG-19 on CIFAR100 with increasing λ and factorization depths $D \in \{2, 3, 4\}$ (left to right).

The results reveal a clear relationship between the elimination of misalignment and sparsity emergence. The onset of sparsity coincides almost exactly with the elimination of average misalignment per layer, providing empirical evidence for the theoretical connection discussed in Section 3. Larger values of λ lead to faster reduction in misalignment and earlier onset of sparsity, demonstrating stronger regularization favors more balanced factorizations.

Two important observations emerge from these results. First, earlier layers broadly exhibit higher initial layer-wise misalignment but decrease at a higher rate than later layers. Surprisingly, a larger initial misalignment coincides with the most rapid and pronounced onset of sparsity as the average misalignment approaches zero. Second, the final layer (yellow) displays distinctly decoupled dynamics, with sparsity emerging within the first few epochs, as opposed to the approximately simultaneous onset for the remaining layers.

We also explore if the onset of sparsity relates to the dynamics of different components of the regularized loss. Figure 21 shows the overall training loss $\mathcal{L}_{\boldsymbol{\omega},\lambda}(\boldsymbol{\omega}^{(t)})$, the data fit part $\mathcal{L}_{\boldsymbol{\omega},0}(\boldsymbol{\omega}^{(t)})$, and the (non-collapsed) factor L_2 penalty $D^{-1}\lambda\|\boldsymbol{\omega}^{(t)}\|_2^2$. The L_2 penalty is further decomposed into its minimal penalty and the excess penalty or misalignment $\lambda \cdot M(\boldsymbol{\omega}^{(t)})$, as described in Lemma 1. Early in training, the L_2 component strongly exceeds the data component. Since the data fit levels out much earlier than the L_2 penalty, they intersect at some point during training that both LR and λ influence. Notably, this point where the loss components are balanced coincides precisely with the onset of sparsity and the overall misalignment approaching zero.

Figure 21: Decomposition of loss components and sparsity evolution for ResNet-18 on CIFAR-10 with depth $D = 3$ and $\lambda = 9 \times 10^{-5}$.

F.5 POST-HOC PRUNING AND FINE-TUNING

Since DWF operates distinctly from most sparsification methods, this offers potential for integration with other pruning techniques. To demonstrate this, we combined DWF with post-hoc pruning on a ResNet-18 with $D = 2$ factorization trained on CIFAR10. The setup used an initial learning rate of 0.27 and a batch size of 256. Each model was trained across a range of λ values to obtain a raw sparsity-accuracy tradeoff curve. These models were then further pruned along a sequence of compression ratios and fine-tuned for 50 epochs using SGD with an LR of 0.11. Fig. 22 presents the results of this experiment. Combining DWF with post-hoc pruning led to increased sparsity at certain accuracy levels up to three times while maintaining comparable accuracy. This demonstrates the potential for integrating DWF with existing pruning techniques.

Figure 22: Additional post-hoc pruning and fine-tuning. ResNet-18 ist first trained with DWF and $D = 2$. The models are post-hoc magnitude pruned and re-trained for another 50 epochs.

F.6 ADDITIONAL SPARSITY-ACCURACY TRADEOFFS

Figure 23 presents sparsity-accuracy tradeoffs for WRN-16-8, ResNet-18, and ResNet-34 on CIFAR100 and Tiny ImageNet datasets, using factorization depths $D \in \{2, 3, 4\}$. Contrasting our training protocol for section Section 5.3, we do not tune the LRs here and set them to fixed values across datasets and architectures. The results show that DWF consistently produces a range of sparsity-accuracy tradeoffs across different architectures and datasets without incurring model collapse. Deeper factorizations generally achieve higher accuracies at extreme sparsity levels.

F.7 ADDITIONAL BENCHMARK RESULTS

The following Table 2 shows test accuracies for different compression ratios on different LeNet model specifications and different MNIST datasets. While GMP or SNIP sometimes perform best for 90% or 95% sparsity, DWF models show the highest sparsity in all medium- and high-sparsity

Figure 23: Additional experiments applying DWF to WRN-16-8 and ResNet-18. For these experiments, the LRs were not tuned for each setting but set to $\{0.2, 0.5, 0.7\}$ for $D \in \{2, 3, 4\}$ across models and datasets.

cases. In total, Synflow and SNIP each work best in 1 case, GMP in 6 cases, $D = 2$ yields the highest sparsity in 4 cases, $D = 3$ in 14 cases, and $D = 4$ in 21 cases.

Table 2: Test accuracy (%) for different compression ratios (columns), models (rows), and datasets (table sections).

Sparsity	90%	95%	98%	99%	99.5%	99.75%	99.875%	99.9%
LeNet-5								
MNIST								
Dense	99.26 ± 0.03							
Depth 2	**99.26 ± 0.04**	**99.27 ± 0.06**	**99.02 ± 0.06**	98.23 ± 0.09	66.88 ± 40.23	10.00 ± 0.00	10.00 ± 0.00	10.00 ± 0.00
Depth 3	99.10 ± 0.06	99.09 ± 0.05	**99.02 ± 0.01**	**98.79 ± 0.08**	**97.80 ± 0.10**	81.22 ± 3.14	46.63 ± 26.19	40.52 ± 21.58
Depth 4	98.95 ± 0.04	98.94 ± 0.05	98.88 ± 0.02	98.66 ± 0.10	97.76 ± 0.12	**85.57 ± 6.45**	**61.31 ± 4.48**	25.35 ± 21.71
GMP	99.00 ± 0.07	98.75 ± 0.14	97.97 ± 0.10	83.69 ± 10.07	11.35 ± 0.00	11.35 ± 0.00	11.35 ± 0.00	11.35 ± 0.00
SNIP	98.92 ± 0.21	98.63 ± 0.24	97.29 ± 0.38	64.85 ± 8.81	21.73 ± 11.19	14.34 ± 5.18	11.35 ± 0.00	11.35 ± 0.00
Synflow	99.00 ± 0.04	98.68 ± 0.09	98.18 ± 0.23	96.71 ± 0.63	91.97 ± 2.82	74.37 ± 7.80	56.60 ± 2.68	**43.68 ± 2.34**
Random	98.28 ± 0.13	97.29 ± 0.27	59.70 ± 7.65	22.61 ± 4.38	11.35 ± 0.00	11.35 ± 0.00	11.35 ± 0.00	11.35 ± 0.00
F-MNIST								
Dense	90.41 ± 0.20							
Depth 2	**91.30 ± 0.13**	**90.78 ± 0.26**	89.78 ± 0.20	88.06 ± 0.18	34.68 ± 34.91	10.00 ± 0.00	10.00 ± 0.00	10.00 ± 0.00
Depth 3	90.82 ± 0.22	90.67 ± 0.16	**90.10 ± 0.18**	88.75 ± 0.26	**85.84 ± 0.72**	**79.15 ± 0.74**	**64.87 ± 2.78**	**60.53 ± 3.17**
Depth 4	90.65 ± 0.03	90.28 ± 0.25	90.00 ± 0.19	**88.77 ± 0.11**	85.21 ± 0.36	77.76 ± 1.41	62.90 ± 0.94	56.29 ± 2.23
GMP	90.24 ± 0.14	89.71 ± 0.16	84.61 ± 0.83	25.57 ± 7.01	10.00 ± 0.00	10.00 ± 0.00	10.00 ± 0.00	10.00 ± 0.00
SNIP	90.21 ± 0.59	87.21 ± 3.00	68.27 ± 15.13	48.92 ± 16.00	10.00 ± 0.00	10.00 ± 0.00	10.00 ± 0.00	10.00 ± 0.00
Synflow	89.77 ± 0.13	89.16 ± 0.31	87.21 ± 0.12	84.86 ± 0.37	78.68 ± 2.30	66.01 ± 9.94	45.45 ± 1.90	38.97 ± 1.97
Random	89.28 ± 0.26	86.29 ± 0.11	46.32 ± 9.87	15.60 ± 6.67	10.00 ± 0.00	10.00 ± 0.00	10.00 ± 0.00	10.00 ± 0.00
K-MNIST								
Dense	95.58 ± 0.33							
Depth 2	**95.45 ± 0.24**	94.56 ± 0.25	90.52 ± 0.30	81.88 ± 0.15	10.00 ± 0.00	10.00 ± 0.00	10.00 ± 0.00	10.00 ± 0.00
Depth 3	95.17 ± 0.19	**94.91 ± 0.15**	**93.08 ± 0.10**	88.68 ± 0.59	78.02 ± 0.58	61.69 ± 0.29	21.95 ± 16.90	10.00 ± 0.00
Depth 4	94.72 ± 0.19	94.41 ± 0.22	92.91 ± 0.21	87.91 ± 0.40	**79.37 ± 0.19**	**61.75 ± 0.90**	**43.09 ± 1.87**	**27.10 ± 12.12**
GMP	93.18 ± 0.42	90.92 ± 0.40	79.28 ± 0.71	50.75 ± 11.04	20.12 ± 9.81	10.95 ± 1.64	10.00 ± 0.00	10.00 ± 0.00
SNIP	91.86 ± 0.73	89.00 ± 0.18	71.32 ± 1.48	26.25 ± 0.37	12.64 ± 4.57	10.00 ± 0.00	10.00 ± 0.00	10.00 ± 0.00
Synflow	92.21 ± 0.31	90.59 ± 0.17	82.77 ± 1.28	72.95 ± 0.46	58.95 ± 1.42	44.67 ± 3.48	27.69 ± 6.51	26.96 ± 4.16
Random	89.52 ± 0.60	82.18 ± 0.79	32.65 ± 7.40	11.20 ± 2.92	9.47 ± 0.92	10.00 ± 0.00	10.00 ± 0.00	10.00 ± 0.00
LeNet-300-100								
MNIST								
Dense	98.29 ± 0.05							
Depth 2	97.49 ± 0.10	97.30 ± 0.12	96.33 ± 0.02	94.54 ± 0.27	91.15 ± 0.13	10.00 ± 0.00	10.00 ± 0.00	10.00 ± 0.00
Depth 3	97.30 ± 0.13	97.25 ± 0.15	97.11 ± 0.21	96.79 ± 0.19	95.83 ± 0.26	93.58 ± 0.34	90.29 ± 0.24	**88.55 ± 0.63**
Depth 4	97.31 ± 0.10	97.22 ± 0.12	97.08 ± 0.15	**96.81 ± 0.15**	**96.05 ± 0.25**	**94.27 ± 0.26**	**90.62 ± 0.40**	88.49 ± 1.00
GMP	**98.34 ± 0.16**	**98.14 ± 0.32**	**97.39 ± 0.56**	96.59 ± 0.03	93.30 ± 1.75	75.38 ± 15.13	25.97 ± 9.12	19.16 ± 6.95
SNIP	98.09 ± 0.13	97.67 ± 0.19	96.25 ± 0.66	94.51 ± 0.21	86.45 ± 4.37	59.67 ± 6.41	40.38 ± 7.88	14.52 ± 2.79
Synflow	97.83 ± 0.17	97.40 ± 0.30	96.26 ± 0.59	94.03 ± 0.19	88.86 ± 0.46	75.61 ± 2.02	48.75 ± 11.40	49.49 ± 5.19
Random	97.35 ± 0.09	95.83 ± 0.35	79.32 ± 7.61	38.01 ± 10.45	14.64 ± 2.90	11.35 ± 0.00	11.35 ± 0.00	11.35 ± 0.00
F-MNIST								
Dense	89.12 ± 0.40							
Depth 2	87.95 ± 0.03	87.42 ± 0.12	86.16 ± 0.12	85.05 ± 0.09	82.80 ± 0.06	53.87 ± 31.02	41.90 ± 22.68	38.05 ± 20.10
Depth 3	87.84 ± 0.12	87.66 ± 0.10	87.34 ± 0.12	86.97 ± 0.11	86.02 ± 0.20	84.84 ± 0.35	**82.35 ± 0.11**	**81.35 ± 0.16**
Depth 4	87.68 ± 0.15	87.53 ± 0.21	**87.35 ± 0.25**	**87.15 ± 0.09**	**86.52 ± 0.16**	**84.96 ± 0.26**	82.32 ± 0.31	81.30 ± 0.40
GMP	88.22 ± 1.00	**87.95 ± 1.07**	87.10 ± 1.30	85.22 ± 2.15	79.77 ± 5.47	55.70 ± 25.45	26.55 ± 14.94	17.29 ± 6.42
SNIP	**88.61 ± 1.08**	87.68 ± 0.84	82.35 ± 5.34	83.76 ± 1.10	75.64 ± 5.02	21.69 ± 17.05	13.23 ± 5.59	10.00 ± 0.00
Synflow	88.16 ± 1.06	87.54 ± 0.74	86.57 ± 0.75	85.23 ± 0.41	82.04 ± 0.59	76.75 ± 0.33	68.29 ± 1.46	51.62 ± 13.97
Random	87.79 ± 0.12	87.14 ± 0.57	73.35 ± 8.92	29.92 ± 9.75	16.21 ± 4.80	10.16 ± 0.27	10.00 ± 0.00	10.00 ± 0.00
K-MNIST								
Dense	91.44 ± 0.24							
Depth 2	88.26 ± 0.09	86.61 ± 0.15	80.74 ± 0.24	73.23 ± 0.36	63.19 ± 0.63	10.00 ± 0.00	10.00 ± 0.00	10.00 ± 0.00
Depth 3	87.83 ± 0.20	87.49 ± 0.22	86.60 ± 0.06	83.92 ± 0.19	77.75 ± 0.22	66.56 ± 3.07	52.17 ± 1.94	48.71 ± 1.67
Depth 4	87.96 ± 0.16	87.63 ± 0.17	**86.99 ± 0.24**	**84.49 ± 0.21**	**78.85 ± 0.66**	**70.16 ± 0.51**	**55.77 ± 1.78**	**51.13 ± 2.19**
GMP	**90.43 ± 0.37**	**88.09 ± 0.43**	83.18 ± 0.34	75.34 ± 0.61	51.39 ± 0.57	21.50 ± 4.05	9.41 ± 1.02	10.00 ± 0.00
SNIP	88.51 ± 0.49	85.15 ± 0.20	79.96 ± 1.03	68.30 ± 0.79	47.25 ± 2.25	25.02 ± 3.44	10.00 ± 0.00	10.85 ± 1.47
Synflow	88.52 ± 0.32	86.05 ± 0.34	82.30 ± 0.45	77.29 ± 0.39	65.65 ± 1.26	52.01 ± 1.36	36.22 ± 1.61	37.92 ± 2.96
Random	87.02 ± 0.31	82.10 ± 0.15	57.30 ± 2.39	22.22 ± 3.61	11.96 ± 3.39	11.65 ± 2.35	10.00 ± 0.00	10.00 ± 0.00

G EXPERIMENTAL DETAILS

G.1 DESCRIPTION OF COMPARISON METHODS

In the following, we briefly describe the comparison methods used in our study, covering different approaches of network sparsification before or post-training.

SNIP (Single-shot Network Pruning): This method introduces the concept of connection sensitivity to quantify the impact of individual weights on the network's loss function, given by $\mathbf{z}^{(l)} = \left| \mathbf{g}^{(l)} \odot \mathbf{w}^{(l)} \right|$ for layer $l \in [L]$, where $\mathbf{g}^{(l)}$ is the loss gradient with respect to $\mathbf{w}^{(l)}$. By computing this score for each weight at initialization, SNIP identifies and preserves the most crucial connections, enabling effective one-shot pruning prior to training. This approach has shown remarkable efficacy in maintaining network performance even at high sparsity levels (Lee et al., 2019).

SynFlow: As a data-independent pruning approach, SynFlow addresses the important issue of layer collapse in neural network pruning. It utilizes a layerwise conservation principle to ensure conservation of synaptic flow across the network, thereby maintaining high model capacity even under extreme compression ratios. SynFlow has demonstrated state-of-the-art performance at very high sparsity levels, outperforming many data-driven approaches in scenarios where over 99% of parameters are pruned (Tanaka et al., 2020).

Global Magnitude Pruning (GMP): This method is based on the assumption that the weight magnitudes are a good proxy for their importance in the network. Despite its heuristic nature, GMP has proven remarkably effective, especially at low sparsity levels. Its success has led to numerous refinements and adaptations of pruning schedules and criteria, with its lasting popularity in both research and practice highlighting its robustness and efficacy (Han et al., 2015; Blalock et al., 2020; Frankle et al., 2020).

Random Pruning: Serving as a baseline method, random pruning uniformly removes weights or structures without considering their importance, thereby helping to evaluate the effectiveness of more sophisticated pruning strategies.

G.2 DETAILS ON ARCHITECTURES, DATASETS, AND TRAINING HYPERPARAMETERS

Neural network architectures   In the following, we briefly describe the neural architectures used in our experiments.

- *LeNet-300-100*: This fully-connected network, designed for MNIST classification, consists of an input layer (784 units), two hidden layers (300 and 100 units respectively), and an output layer (10 units). All layers utilize ReLU activation functions. The architecture closely follows the original version proposed by (LeCun et al., 1989), adapted to incorporate modern activations for improved performance.

- *LeNet-5* (LeCun et al., 1998) is a small but effective convolutional network with two convolutional layers (6 and 16 filters, both 5x5), each followed by average pooling, and three fully connected layers (120, 84, and 10 units). We use ReLU activations and add batch normalization (Ioffe & Szegedy, 2015) and average pooling after each convolutional layer.

- *VGG-16* for CIFAR-10/100 consists of 13 convolutional layers and 3 fully connected layers (Simonyan & Zisserman, 2014). The convolutional part is described by 2x(64 filters), 2x(128 filters), 3x(256 filters), 3x(512 filters), 3x(512 filters), with max pooling inserted after each group. All filter sizes are 3x3. Batch normalization is applied before each ReLU activation as described by (Lee et al., 2019). *VGG-19* extends VGG-16 by adding one more convolutional layer to each of the last three convolutional blocks, resulting in 19 layers in total. Following (Zagoruyko, 2015), the two fully-connected layers before the output are reduced to a single layer layer with 512 units compared to the ImageNet version.

- *ResNet-18* is a popular residual network with 18 layers (He et al., 2016). In our implementation, the architecture is adapted following common practice for smaller image datasets (Tanaka et al., 2020). We modify the first convolutional layer to use 3x3 filters and remove the initial max pooling layer. The network consists of an initial convolutional layer, followed by 4 stages of basic blocks (2 blocks each), with filter sizes [64, 128, 256, 512]. Global average pooling is used before the fully connected output layer. Likewise, our *ResNet-34* implementation is also adapted for smaller datasets. The architecture follows a

similar pattern to ResNet-18 with more layers in each stage. As with ResNet-18, we use 3x3 filters in the first layer and omit the initial max pooling, appropriate for the image size of our experiments.

- *WideResNet* is a ResNet variant whose increased width compared to plain ResNets allows for better feature representations without the optimization difficulties that come with extremely deep networks. In our work, we implement the version with a depth of 16 and a width factor of 8 (WRN-16-8), particularly specifically suited for CIFAR-like classification tasks (Zagoruyko & Komodakis, 2016).

Table 3: Summary of datasets used in experiments.

Dataset	Training Samples	Test Samples	Classes	Input Features
MNIST	60,000	10,000	10	784 ($28\times28\times1$)
F-MNIST	60,000	10,000	10	784 ($28\times28\times1$)
K-MNIST	60,000	10,000	10	784 ($28\times28\times1$)
CIFAR-10	50,000	10,000	10	3,072 ($32\times32\times3$)
CIFAR-100	50,000	10,000	100	3,072 ($32\times32\times3$)
Tiny ImageNet	100,000	10,000	200	12,288 ($64\times64\times3$)

Datasets   In our experiment evaluation, we use several standard image classification datasets of varying size and complexity, summarized in Table 3.

MNIST, Fashion-MNIST (F-MNIST), and Kuzushiji-MNIST (K-MNIST) are grayscale image datasets, each containing 10 classes with images of 28x28 pixels. The original MNIST comprises handwritten digits, while F-MNIST contains images of clothing items, and K-MNIST has handwritten Japanese characters. These datasets combine a range of classification tasks with similar input dimensions but varying levels of difficulty.

CIFAR10 and CIFAR100 contain 32x32x3 (color) images with 10 and 100 classes respectively. These datasets present more challenging classification tasks due to their higher resolution, color information, and larger number of classes for CIFAR100.

Finally, Tiny ImageNet is a subset of the ImageNet dataset featuring 200 classes with 64x64x3 color images. This dataset is significantly more challenging and computationally due to the more complex task with larger and more images, as well as a larger number of classes. All datasets are split into training (50,000 or 60,000 samples) and test (10,000 samples) sets. We further apply standard data pre-processing and augmentation techniques: For the three MNIST variants, we use pixel rescaling to $[0, 1]$. The CIFAR and Tiny ImageNet images are normalized. For larger networks, we additionally employ data augmentation, including horizontal flips, width and height shifts (up to 12.5%), and rotations (up to $15°$). Table 4 contains the combinations of architectures and datasets we conducted experiments on.

Training hyperparameters   In our experiments, we use training hyperparameter configurations following broadly established standard settings (Simonyan & Zisserman, 2014; He et al., 2015; Zagoruyko & Komodakis, 2016), as displayed in Table 4. For both LeNet-300-100 and LeNet-5 we set the initial LR to 0.15 and found it to perform well across datasets, with the exception of LeNet-300-100 on K-MNIST. Because established LRs were found to be suboptimal for DWF, we additionally select the best-performing LR (using small $\lambda = 10^{-6}$) from a discrete grid between 0.05 and 1 for each factorization depth, architecture, and dataset. For DWF, the sparsity level is controlled using a logarithmically spaced sequence of λ parameters between 10^{-6} and 10^{-1} on which we train each model to obtain the sparsity-accuracy tradeoff curves.

For the comparison methods in Section 5.3, we follow the implementation details provided in Frankle et al. (2020); Lee et al. (2019) if available. To make for a fair comparison, we also train the two LeNet architectures using the same LR of 0.15 and cosine decay. For the larger networks, we only adjust the LR schedule from step to cosine decay but use the prescribed initial LR. To obtain tradeoff curves for the respective pruning methods, we train each method on a sequence of 15 compression ratios between 10^1 and 10^5.

Further details for DWF   Although our method requires no post-hoc pruning, it is sensible to apply a sufficiently small threshold to the final collapsed weights to account for numerical inaccuracies which have no impact on performance. We set this threshold to `float32.mach.eps` $\approx$

Table 4: Training hyperparameters for different architectures and datasets. The LRs for the larger models correspond to factorization depths $D = 2, 3, 4$. The comparison methods use standard Kaiming initialization. LRs for the supplementary results on WRN-16-8 and ResNet-34 were not tuned.

Architecture	Dataset	Epochs	Batch size	Optim.	Mom.	Init.	LR	Schedule
LeNet-300-100	MNIST	75	256	SGD	0.9	DWF-Init	0.15	Cosine
	F-MNIST	75	256	SGD	0.9	DWF-Init	0.15	Cosine
	K-MNIST	75	256	SGD	0.9	DWF-Init	0.4	Cosine
LeNet-5	MNIST	75	256	SGD	0.9	DWF-Init	0.15	Cosine
	F-MNIST	75	256	SGD	0.9	DWF-Init	0.15	Cosine
	K-MNIST	75	256	SGD	0.9	DWF-Init	0.15	Cosine
VGG-16	CIFAR-10	250	128	SGD	0.9	DWF-Init	{0.5,0.6,0.6}	Cosine
VGG-19	CIFAR-100	250	128	SGD	0.9	DWF-Init	{0.3,0.6,0.6}	Cosine
ResNet-18	CIFAR-10	250	128	SGD	0.9	DWF-Init	{0.2,0.5,0.7}	Cosine
	CIFAR-100	250	128	SGD	0.9	DWF-Init	{0.2,0.5,0.7}	Cosine
	Tiny ImageNet	250	128	SGD	0.9	DWF-Init	{0.5,0.8,1.1}	Cosine
WRN-16-8	CIFAR-10	250	128	SGD	0.9	DWF-Init	{0.2,0.5,0.7}	Cosine
	CIFAR-100	250	128	SGD	0.9	DWF-Init	{0.2,0.5,0.7}	Cosine
	Tiny ImageNet	250	128	SGD	0.9	DWF-Init	{0.2,0.5,0.7}	Cosine
ResNet-34	CIFAR-100	250	128	SGD	0.9	DWF-Init	{0.2,0.5,0.7}	Cosine
	Tiny ImageNet	150	128	SGD	0.9	DWF-Init	{0.2,0.5,0.7}	Cosine

1.19×10^{-7}. Additionally, the DWF initialization (Algorithm 1) requires specification of the lower truncation threshold for the factor initializations, which we set to $\varpi_{\min} = 3 \times 10^{-3}$ for all our experiments (cf. left plot of Fig. 4).

H OTHER APPROACHES TO FACTOR INITIALIZATION

H.1 ROOT INITIALIZATION AND RESULTS

An alternative option to obtain an initialization of factors ω that recovers the distribution of the original weight w is given in the following.

Definition 5 (Root initialization). A root initialization of a depth-D factorized weight $w = \omega_1 \odot \ldots \odot \omega_D$ is given by first drawing a single standard weight initialization (Definition 3) for w and assigning $\omega_1 \leftarrow \text{sign(w)} \cdot |\text{w}|^{1/D}$ and $\omega_2, \ldots, \omega_D \leftarrow |\text{w}|^{1/D}$.

Fig. 24 compares the root initialization against the vanilla initialization and the proposed `DWF` initialization with and without truncation. While the root initialization yields satisfactory results improving upon vanilla initialization for $D = 2$, we observe that it behaves similarly to the VarMatch initialization for $D = 3$, both outperformed compared to our `DWF` initialization and yields the worst results for $D = 4$.

Figure 24: Comparison of different sparsity-accuracy tradeoffs for different depths (columns) and different initialization strategies (colors).

In Fig. 25, we further analyze the learning dynamics of a DWF model with root initialization. The results demonstrate qualitatively similar learning dynamics to our proposed DWF initialization, suggesting them to be a general feature of DWF and SGD optimization.

Figure 25: Learning dynamics for the root initialization for different learning rate schedules (columns).

H.2 DERIVATION OF EXACT GAUSSIAN FACTOR DISTRIBUTION IN DWF

We now present a theoretical approach to derive a distribution of the factors ω_d in Deep Weight Factorization, such that the product of D i.i.d. random variables from this distribution follows a normal distribution $\mathcal{N}(0, \sigma_w^2)$ with pre-specified variance σ_w^2. This analysis provides insight into the statistical properties of factorized weights and the challenges arising from of such a construction. Consider a neural network $f_{\mathbf{w}}(\mathbf{w}, \boldsymbol{x})$ parameterized by weights $\mathbf{w} \in \mathbb{R}^p$. In DWF, these weights are factorized into D factors $\mathbf{w} = \boldsymbol{\varpi} = \boldsymbol{\omega}_1 \odot \boldsymbol{\omega}_2 \odot \ldots \odot \boldsymbol{\omega}_D$, where $\boldsymbol{\omega}_d \in \mathbb{R}^p$ for $d \in [D]$. Our goal is to find a distribution $\mathcal{P}$ for the elements $\omega_{j,d}$ of the factor weights $\boldsymbol{\omega}_d$, such that the product of D i.i.d. random variables from $\mathcal{P}$ follows a distribution $\mathcal{N}(0, \sigma_w^2)$. Specifically, for each $j \in [p]$, we require (with layer-wise varying σ_w^2):

$$\text{w}_j = \prod_{d=1}^{D} \omega_{j,d} \sim \mathcal{N}(0, \sigma_w^2). \tag{18}$$

To find such a distribution $\mathcal{P}$, we utilize the Mellin transform, which is used in statistics for analyzing products of independent non-negative random variables, with extensions to cases with both positive

and negative values (Springer & Thompson, 1966). An important property of the Mellin transform is that it converts the convolution of the densities of products into multiplication in the Mellin domain, but only for non-negative random variables. Since the random variables $\omega_{j,d}$ can take both positive and negative values, we partition their density into positive and negative parts $\rho_\omega(\omega) = \rho_\omega^+(\omega) + \rho_\omega^-(\omega)$ (Springer, 1979), where:

$$\rho_\omega^+(\omega) = \begin{cases} \rho_\omega(\omega), & \omega \geq 0, \\ 0, & \text{elsewhere,} \end{cases} \qquad \rho_\omega^-(\omega) = \begin{cases} \rho_\omega(\omega), & \omega \leq 0, \\ 0, & \text{elsewhere.} \end{cases} \tag{19}$$

Similarly, we partition the density of the product w_j into $\rho_w(w) = \rho_w^+(w) + \rho_w^-(w)$. The Mellin transform $M_\rho(s)$ of a function $\rho(\omega)$ defined on $\mathbb{R}_0^+$ is defined as:

$$M_\rho(s) = \int_0^\infty \omega^{s-1} \rho(\omega)\, d\omega. \tag{20}$$

The Mellin transform of the positive part of the product of D i.i.d. and even (symmetric around 0) random variables is given by (Springer & Thompson, 1966):

$$M_w^+(s) = 2^{D-1} \left[M_\omega^+(s) \right]^D. \tag{21}$$

Since we want the product distribution to be $\mathcal{N}(0, \sigma_w^2)$, we require the Mellin transform of the positive part of a zero-mean Gaussian density (Springer, 1979):

$$M_\mathcal{N}^+(s) = \int_0^\infty w^{s-1} \rho_w^+(w)\, dw = \frac{2^{(s-3)/2}}{\sqrt{\pi}} (\sigma_w)^{s-1} \Gamma\left(\frac{s}{2}\right), \quad \text{Re}(s) > 0, \tag{22}$$

where $\Gamma(\cdot)$ denotes the Gamma function. Setting $M_w^+(s) = M_\mathcal{N}^+(s)$, we have:

$$2^{D-1} \left[M_\omega^+(s) \right]^D = \frac{2^{(s-3)/2}}{\sqrt{\pi}} (\sigma_w)^{s-1} \Gamma\left(\frac{s}{2}\right). \tag{23}$$

Dividing both sides by 2^{D-1}, taking the D-th root, and simplifying, we obtain the Mellin transform of the positive part of the factor distribution $\mathcal{P}$:

$$M_\omega^+(s) = \left(\frac{2^{s-2D-1}}{\pi} \right)^{1/(2D)} (\sigma_w)^{(s-1)/D} \left[\Gamma\left(\frac{s}{2}\right) \right]^{1/D}. \tag{24}$$

To obtain $\rho_\omega^+(\omega)$, computation of the inverse Mellin transform is required, with c a real constant such that the integration path is in the region of convergence:

$$\rho_\omega^+(\omega) = \mathbb{1}_{\{\omega > 0\}} \frac{1}{2\pi i} \int_{c-i\infty}^{c+i\infty} \omega^{-s} M_\omega^+(s)\, ds. \tag{25}$$

Finally, the full factor density is obtained by reflecting the positive part about the y-axis to get $\rho_\omega^-(\omega) = \rho_\omega^+(-\omega)$ and combined $\rho_\omega(\omega) = \rho_\omega^+(\omega) + \rho_\omega^-(\omega)$, defined on the whole real line.

Practical challenges While the theoretical approach provides a valid method to derive the factor distribution, significant practical challenges arise because the factor density is obtained as the inverse Mellin transform that involves integrating over an infinite contour in the complex plane. Numerical methods for inverse Mellin transforms can further be unstable and sensitive to several parameter choices, although high computational precision is required, especially for large D or varying σ_w^2. Lastly, the Mellin transform $M_\omega^+(s)$ depends on both the D and σ_w^2, altering the factor distribution non-parametrically and complicating the practical applicability. Due to these challenges, deriving the factor distribution via inverse Mellin transforms remains challenging and with unclear utility in deep learning applications, given that preliminary experiments suggest it is unlikely that precise approximations have a notable effect on trainability and performance in non-pathological cases. Alternative methods, such as our proposed initialization using simple Gaussian distributions with variance scaling and interval truncation, are sufficient to reach baseline performances and thus are more suitable from a practical point of view.

I COMPUTATIONAL ENVIRONMENT AND RUNTIME ANALYSIS

I.1 COMPUTATIONAL ENVIRONMENT

Large experiments on ResNet-18 and VGG-19 on datasets CIFAR10, CIFAR100, and Tiny Ima-geNet were run on an A-100 GPU server with 32GB RAM and 16 CPU cores. Smaller experiments were conducted on a single A-4000 GPU with 48GB RAM or CPU workstations.

I.2 RUNTIME ANALYSIS

Here, we investigate the computational overhead induced by DWF compared to vanilla training. We conducted experiments with WRN-16-8 on CIFAR10 and VGG-19 on CIFAR100 across various batch sizes. Each model was trained for 1000 iterations using SGD with a batch size of 128. We measured the average wall-clock time per sample and peak GPU memory utilization during training. All experiments were performed on a single A-4000 GPU with 48GB RAM, repeated five times to report means and standard deviations. Our results, displayed in Fig. 26 and Fig. 27, show that the factorization depth D in the DWF model only has a minor impact on computational costs during training. For batch sizes of 256 or higher, both networks exhibit an indistinguishable time per sample comparable to vanilla training across all levels of D. At smaller batch sizes, we observe a slight monotonic increase in runtime with greater D. For example, WRN-16-8 with a batch size of 128 runs approximately 10% longer than vanilla training, while VGG-19 with a batch size of 64 and $D = 4$ shows the largest increase of about 80%. These findings demonstrate that DWF training under typical settings incurs only small additional cost compared to standard training. This contrasts with many sparsification techniques like Iterative Magnitude Pruning (Frankle & Carbin, 2019), which can lead to several-fold increases in training time due to multiple cycles of pruning and re-training.

Figure 26: Comparison of wall-clock time per sample for WRN-16-8 (**left**) and VGG-19 (**right**) on CI-FAR10/100 across factorization depths D. Results indicate insignificant runtime overhead for DWF compared to vanilla training, particularly for larger batch sizes where runtime is identical.

GPU memory utilization is primarily dependent on batch size, with D having rather small effects in total. In conclusion, besides factorizing the weights into D factors, DWF incurs only a minor additional runtime and memory cost on commonly used convolutional architectures. The minimal increase, especially for typical batch sizes, suggests DWF can be readily integrated into existing training protocols without major changes in computational overhead.

Figure 27: Peak GPU memory utilization for WRN-16-8 (**left**) and VGG-19 (**right**) across factorization depths D. The results show that batch training is the dominant factor for memory usage, with only a small minimal impact of D.