VF-PS: How to Select Important Participants in Vertical Federated Learning, Efficiently and Securely?

Abstract

Vertical Federated Learning (VFL), that trains federated models over vertically partitioned data, has emerged as an important learning paradigm. However, existing VFL methods are facing two challenges: (1) *scalability* when # participants grows to even modest scale and (2) *diminishing return* w.r.t. # participants: not all participants are equally important and many will not introduce quality improvement in a large consortium. Inspired by these two challenges, in this paper, we ask: *How can we select l out of m participants, where $l \ll m$, that are most important?*

We call this problem *Vertically Federated Participant Selection*, and model it with a principled mutual information-based view. Our first technical contribution is VF-MINE—a *Vertically Federated Mutual INformation Estimator*—that uses one of the most celebrated algorithms in database theory—Fagin's algorithm as a building block. Our second contribution is to further optimize VF-MINE to enable VF-PS, a group testing-based participant selection framework. We empirically show that vertically federated participation selection can be orders of magnitude faster than training a full-fledged VFL model, while being able to identify the most important subset of participants that often lead to a VFL model of similar quality.

1   Introduction

The quality of machine learning models heavily relies on the quality and volume of available data. As our understanding of machine learning shifts towards such a data-centric view, mechanisms of making data available to machine learning have attracted intensive interests [1, 2]. Towards this goal, Federated Learning [3–5] is an emerging research area that focuses on training a single ML model using all data available in a federated "*data consortium*" in a secure and privacy-preserving way.

Vertical Federated Learning. In this paper, we focus on a specific federated learning scenario: *Vertical Federated Learning* (VFL) [5]. As illustrated in Figure 1(a), the VFL setting involves a data consortium that consists of m participants $\mathcal{P} = \{P_1, ..., P_m\}$. Each participant holds *a disjoint subset of features* associated with the same entity (e.g., different hospitals holding medical records of the same patient but for different types of diseases). The goal of vertical federated learning is to train a single ML model over the joint feature space, in a secure and privacy-preserving way, without communicating their data to each other [6–10].

Technical Challenges of VFL. Despite many recent efforts that significantly improved the scalability and efficiency of model training in the VFL setting, two great challenges linger, as illustrated in Figure 1(b). The first challenge is *scalability* w.r.t # participants. Because of the requirement on security and privacy, many VFL approaches have to resort to expensive methods such as Homomorphic Encryption [11, 12] and Secure Multi-party Computation [13, 14]. This greatly limits the scalability of today's VFL systems. Another challenge is *diminishing return*, also when # participants grows. Since not all participants contribute equally informative knowledge, it is not unusual to observe that adding more participants does not provide significant quality gain on the final ML model. These two challenges, when put together, form a quite "ironic" picture, as illustrated in Figure 1(b)(iii) — *supporting a large data consortium makes training time significantly longer, however, a dominating amount of these computations might not be translated into any significant quality gain.*

Preprint. Under review.

(a) In the Vertical Federated Learning (VFL) setting, each participant holds a disjoint set of features for the same set of entities; the coordinator also holds the ground truth labels. These participants communicate in a secure and privacy preserving way in order to train a single machine learning model over the joint feature space.

(b) VFL faces two challenges: (i) *Scalability* and (ii) *Diminishing Return* w.r.t # participants, since many participants in a large consortium might not provide significant quality gain. As a result, (iii) a dominating amount of the computation cost for a large consortium might not lead to any quality gain. (LR, Bank dataset)

Figure 1: Vertical federated learning and challenges

Vertically Federated Participant Selection (VF-PS). Whereas designing more efficient model training methods in the VFL setting continues to be crucially important, in this paper, we focus on an orthogonal direction to accommodate these challenges. Given a data consortium with m participants, instead of trying to speed-up the training of a single ML model over all m participants, we ask: "*Can we identify $l \ll m$ participants that are most important, and only train expensive VFL models on them instead?*" We call this problem *Vertically Federated Participant Selection (VF-PS)*.

From Feature Selection (FS) to VF-PS: Connections and New Challenges. At first glance, the VF-PS problem is closely connected to traditional feature selection problems [15, 16]. This is definitely true and is what, in our opinion, makes VF-PS promising — the last half-century of study on feature selection provides not only principled theoretical framework but also strong evidence that we should be able to significantly decrease # participants (# features) involved but still obtain similar quality. However, VF-PS imposes unique challenges compared to feature selection. VF-PS should (1) provide *no weaker* security and privacy guarantees compared with other VFL training systems [9] and (2) should be much *more efficient* than training a single VFL model over all participants.

Summary of Technical Contributions. In this paper, we focus on a specific, while one of the most natural, way of modeling VF-PS: *we should select the subset of participants that jointly preserve the greatest amount of mutual information (MI) between features and labels.* Under this view, designing a VF-PS algorithm involves two technical issues: (1) *how to estimate MI for a subset of participants?* and (2) *how to search the subset of participants that preserve the greatest amount of MI?*

- **(C1)** Our first contribution is VF-MINE—a Vertically Federated Mutual INformation Estimator. Given a subset of participants, VF-MINE estimates MI between the features of these participants and the labels. VF-MINE protects data privacy via homomorphic encryption. The most surprisingly technical observation is that one of the most popular MI estimators [17], used by `sklearn`, can be made orders of magnitude faster. This is by optimizing data movement between different participants, with Fagin's algorithm [18] as a building block.
- **(C2)** Our second contribution is VF-PS, that uses VF-MINE to search for the subset of participants that preserves the greatest amount of MI in a group testing-based framework. We provide a set of optimization techniques to further optimize data movement between different participants.
- **(C3)** We provide rigorous security analysis for the proposed methods. We then empirically show that, our VF-PS framework can be up to two orders of magnitude faster than training full-fledged VFL models. Moreover, VF-PS can often select a much smaller subset of participants but maintain a similar model quality.

2 Preliminaries

Federated Learning. Federated learning is a category of distributed learning technique that enables different organizations or users to collaboratively learn machine learning (ML) models, without exposing their personal data to other parties [19–21]. Assume $\mathcal{X}$ denotes instance features, $\mathcal{Y}$ denotes instance labels and $\mathcal{I}$ denotes instance IDs, federated learning can be classified into two categories, i.e., horizontal federated learning and vertical federated learning, according to how $(\mathcal{X}, \mathcal{Y}, \mathcal{I})$ are distributed across different participants.

Privacy Protection Techniques. As a critical property of federated learning, data privacy has been extensively studied. Briefly speaking, there are three major categories of privacy protection techniques. 1) *Differential Privacy* randomly perturbs the transferred data (e.g., gradient) with noises, such as Gaussian noise [22], Laplacian noise [23], and Binomial noise [24]. 2) *Homomorphic Encryption* encrypts all data before they are transferred [12, 25, 26] and supports arithmetic computation on encrypted data. 3) *Secure Multiparty Computation* (SMC) enables multiple parties to collaboratively compute an agreed-upon function without leaking local input to any other party except for what can be inferred from the output [13, 14, 27, 28].

3 Vertically Federated Participant Selection via Mutual Information

In this section, we describe our algorithm for Vertically Federated Participant Selection (VF-PS).

3.1 Vertically Federated Participant Selection

We assume a standard data model, following previous efforts in VFL [7, 8] — let there be m participants and N data instances, and $X \in \mathbb{R}^{N \times F}$ be the joint feature space where F is the dimension of the joint feature space. In the VFL setting, this joint feature space X is vertically partitioned over different participants — each participant $P_i \in \mathcal{P}$ holds a subset of features (columns) of X, denoted by X_i. Without loss of generality, we have: $X = [X_1 ... X_i ... X_m]$. Among all m, there is a *leader participant*, which holds the instance labels Y. We assume that all participants agree on the same identifier (ID) of each data instance.

Security Requirements. Following previous systems, e.g., Pivot [9], VF^{2}Boost [29], we have the following standard security requirements. 1) *Feature Security*: Features X_i on each participant cannot be shared with any other party. 2) *Aggregation Security*: Only the leader participant can obtain an *aggregated* result over all *participants*' local data. 3) *Identity Security*: No other party, except the participants, can obtain the identifiers (IDs) of instances.

Mutual Information-based VF-PS. Similar to the classic feature selection problem, we focus on one of the most natural ways to model VF-PS — we aim at selecting the *subset* of participants that jointly preserve the greatest amount of mutual information with the label. Formally, the computation that we hope to conduct, under the previous security requirements and vertically partitioned data model, is

$$\max_{\alpha_1....\alpha_l} MI([X_{\alpha_1} ... X_{\alpha_l}]; Y); \ s.t, \forall i \in [l] : \alpha_i \in [m] \text{ and } \forall i, j \in [l] : \alpha_i \neq \alpha_j. \qquad (1)$$

where $MI(\cdot)$ estimates the mutual information from finite samples, and $l < m$ is a pre-defined constant specifying the number of participants to select.

3.2 VF-MINE: A Vertically Federated Mutual Information Estimator

As we see in Equation 1, solving this problem involves two different questions: (1) *how to estimate MI given a fixed subset of participants, i.e.,* $MI([X_{\alpha_1} ... X_{\alpha_l}]; Y)$*? and* (2) *how to efficiently search for the best subset, i.e.,* $\max_{\alpha_1....\alpha_l}$*, without enumerating exponential many possibilities?* We focus on the first problem in this section, and leave the second question to Section 3.3.

3.2.1 Baseline Method

KNN-based MI Estimator. We focus on a standard family of MI estimators that is widely used in practice (e.g., in sklearn's feature selection module), which is based on k-nearest neighbors (KNN)[17, 30]. Let there be N data pairs $\mathcal{D} = \{(x_j, y_j)\}$ where y_j is a label and x_j is a feature vector. A KNN-based MI estimator enumerates multiple *query* data pairs. For each query $q = (x_q, y_q)$:

1. We first compute N_q, the number of examples in $\mathcal{D}$ that share the same labels as y_q, i.e.,

$$N_q = |\{(x,y) \in D : y = y_q\}|$$

2. We then construct NN_{k,y_q}, containing all k-nearest neighbors among data examples that share the same label. Let $\bar{d}_q$ be the maximal distance between examples in NN_{K,y_q} and x_q.
3. We then compute m_q, the number of examples in $\mathcal{D}$ that has a distance to x_q smaller than $\bar{d}_q$.

Given Q as a subset of query data pairs, we estimate the mutual information as follows:

$$\frac{1}{|Q|} \sum_q \left(\psi(N) - \psi(N_q) + \psi(K) - \psi(m_q) \right)$$

where ψ is the digamma function $\psi(x) = \frac{d}{dx} ln(\Gamma(x)) \sim lnx - \frac{1}{2x}$.

Baseline Implementation of VF-MINE. We now provide a baseline implementation of this estimator in the vertically federated setting. We assume that we use *Euclidean distance* as our distance metric, but our technique can be naturally applied to other distance metrics. We choose *homomorphic encryption* (HE) to protect data privacy since it is widely adopted in the literature [8, 11, 25]; however, our proposed algorithm can also be instantiated with other privacy protection techniques such as SMC (see discussion in Appendix C). [1] We use $HE.Enc(\text{-})/HE.Dec(\text{-})$ to denote the encryption/decryption function, and $[\text{-}]$ an encrypted data item. Below, we present a single VF-MINE routine. There are three roles in the system — *key server*, *aggregation server*, and *participant*:

- *Key server.* The key server generates public and private HE (homomorphic encryption) keys (pk, sk), allocates sk to the leader participant, and pk to all participants and the aggregation server.
- *Aggregation server.* An aggregation server provides an `addition` operator that securely aggregates multiple encrypted data items: $[\mathbf{d}] = HE.Sum(\{[\mathbf{d}_i]\}; pk)$.
- *Participant.* Each participant P_i holds a feature subset of all N data instances. For a query data pair $q = (x_q, y_q)$, each participant P_i calculates $\mathbf{d}_i = [(x_{q,i} - x_{j,i})^2 \text{ for } (x_j, y_j) \in \mathcal{D}]$, the distances between its local features of x_q and data pairs in $\mathcal{D}$. We call $\mathbf{d}_i$ the partial distances. Then, P_i encrypts partial distances and sends $[\mathbf{d}_i] = HE.Enc(\mathbf{d}_i; pk)$ to the aggregation server via the `addition` operator. There is a *leader participant* that holds the labels. It receives the complete distances $[\mathbf{d}]$ from the aggregation server, decrypts it to $\mathbf{d} = HE.Dec([\mathbf{d}]; sk)$, and calculates MI, responding to the procedure of KNN-based estimator.

3.2.2 Fagin-Inspired Method

The baseline method has a potential performance issue, that is, it has to aggregate all the data instances. Since the operation through homomorphic encryption is often time-consuming, this baseline method can be inefficient in practice, especially for many large-scale datasets. To decrease the cost, a potential way is to decrease the number of aggregated instances. Motivated as such, our first question is — *can we aggregate fewer data instances and meanwhile obtain the correct results?* We observe that the vertical KNN task can be seen as aggregating multiple "sub-ranking"s into a "global ranking". Based on this interpretation, we propose to leverage a textbook aggregation algorithm, called *Fagin*, to efficiently find k-nearest neighbors.

Fagin Algorithm. The problem of top-k query aims at finding k instances with the highest (or lowest) scores from multiple lists of instances. Assume there are m parties and N instances, each party i has a score for each instance j, denoted by s_j^i. On each party, the instances are sorted by their scores. Globally, each instance is assigned an overall score by combining the scores on all parties using an aggregate function. This problem has been extensively studied by a series of algorithms [31]. In this work, we choose Fagin as it is widely used [18]. Fagin requires that the aggregation function `aggr` is monotone: $\texttt{aggr}(s_1, s_2, ..., s_m) \leq \texttt{aggr}(s_1', s_2', ..., s_m')$ if $s_i < s_i'$ for every i.

Figure 2(a) shows an example of Fagin algorithm that selects top-2 instances from three parties with the `addition` aggregation function. The processing of Fagin algorithm contains three major steps: 1) sequentially scan the sorted lists from all parties until there are k instances that have been seen in all lists, 2) obtain the scores of all the instances seen so far (including those have not yet occurred in all lists), and 3) use the aggregation function to compute global scores for candidate instances found

---

[1] Differential privacy is unfit because a central server can obtain the aggregated results, such as aggregated distances in KNN-based algorithm.

s_1	2
s_2	1.9
s_3	1.9
s_4	0.7

(a) Fagin Algorithm   (b) Implementation with HE

Figure 2: Fagin-inspired method for estimating MI

in the previous step and select top-k instances therein. In the example of Figure 2(a), Fagin scans three rows and finds that s_1 and s_3 are in three lists. Afterwards, the scores of all instances in three rows (i.e., s_1, s_2, s_3, s_4) are aggregated. We denote $math.Fagin(\cdot)$ the standard Fagin algorithm in this paper, that takes multiple lists of instance IDs as input and outputs candidate IDs.

Fagin-inspired Optimization for VF-MINE. We now implement the Fagin-inspired method. The key allocation (step ①) is the same as the baseline method. The key is to aggregate "sub-ranking"s with Fagin algorithm while preserving their privacy. The implementation of the secure `Fagin` operator is shown in Figure 2(b) (step ②-⑤). We propose a shuffle strategy — each participant uses the same seed to randomly shuffle local data instances (step ②). Then, we generate a "pseudo ID" for each instance that is equal to the index after shuffling. Each participant P_i sends the sub-ranking of pseudo IDs, denoted by I'_i, to the aggregation server, instead of sending the real IDs (step ③-④). The aggregation server runs the standard Fagin algorithm to find k-nearest candidates from all sub-rankings. Since the estimation of MI depends on the label, the leader participant is responsible for stopping Fagin. The aggregation server sends the pseudo IDs of Fagin candidates, denoted by I'_k, to each participant (step ⑤). After the `Fagin` operator, the participants re-index these pseudo IDs to their original IDs (step ⑥). The following steps are similar to the baseline method (step ⑦-⑩).

3.3 VF-PS: Group Testing-based Participant Selection

The second component in our framework is to search for the *subset* of participants that maximizes MI. We adopt a standard group testing-based search procedure.

Group-testing Framework. The VF-PS problem under the group testing framework runs as follows:

1. We select a collection of T *tests*, each of which corresponds to a subset of participants $S_t \subseteq \mathcal{P}$;
2. For each S_t, we estimate its mutual information and use it as the *score*;
3. For each participant, we compute its *importance* as the average score in all *tests* it participated in.
4. We pick the top-k most important participants.

Formally, let $U(S)$ be the score of group $S \subseteq \mathcal{P}$ defined as the mutual information over N_v validation data pairs: $V = \{(x^v_j, y^v_j)\}$, and let $\mathbf{A}$ of dimension $T \times m$ be the participating matrix, where $\mathbf{A}_{t,i} = 1$ if participant i belongs to the t-th test group. Corresponding to each row of $\mathbf{A}$ is a "score" $U(\mathbf{A}[t]) = U(\{i|\mathbf{A}_{t,i} = 1\})$. Consider $\mathbf{A}$ as the test design, the total score of participant P_i is $u_i = \mathbf{A}[:][i] \cdot [U(\mathbf{A}[0]), ..., U(\mathbf{A}[T-1])]$. The participant selection is conducted using these scores.

Implementation of Group Testing. The implementation of group testing for Fagin-inspired method is quite natural. Specifically, we run Fagin-inspired MI estimation over each test group (subset of participants). The counterpart using the baseline method can be obtained by skipping the Fagin stage.

1. *Generate testing groups.* The leader participant randomly generates T groups (e.g., the first group $S_1 = \{P_1\}$ and the second group $S_2 = \{P_1, P_2\}$), which are sent to other participants.
2. *Run Fagin-inspired method.* The proposed framework handles each test group t independently. Specifically, for each validation instance, the participants in test group $\mathbf{A}[t]$ jointly run Fagin-

---

Algorithm 1 Fagin-inspired Participant Selection with Communication Batching

---

Key Server:

$(pk, sk) = HE.KeyGen()$ //generate homomorphic public and private keys
Send pk to aggregation server, send (pk, sk) to participants

Participants:

(Leader) Generate groups $\mathcal{G} = \{S_1, ..., S_T\}$ and send them to aggregation server
. . . . . .   //find Fagin candidate instances, whose IDs are I_k
1: $[d_i^F] = HE.Enc(d_i(I_k); pk)$ //encrypt partial distances of Fagin candidates
2: $Server.addition([d_i^F])$ //send encrypted partial distances to aggregation server
3: $\{[d_S]\} = Server.scheduler()$ //receive aggregated distances from aggregation server
4: $\{I_S'\} = \{math.argsort(HE.Dec([d_S]; sk)\}$ //decrypt and sort aggregated distances
5: $\{I_S\} = Server.scheduler\_callback(\{I_S'\})$ //send local sorted indices to aggregation server
6: (Leader) $scores = group\_testing(\{I_S\}, \mathcal{G}, Y)$ //leader calculates MI scores

Aggregation Server:

function $Server.addition(\{[d_i^F]\})$:
     $\{[d_{S \in \mathcal{G}}]\} = \{HE.Sum(\{[d_i^F]; p_i \in S\}; pk); S \in \mathcal{G}\}$
function $Server.scheduler()$:
     randomly assign $\{[d_{S \in \mathcal{G}}]\}$ to participants
function $Server.scheduler\_callback(\{I_S'\})$:
     return $\{I_S\} = reindex(\{I_S'\}; S \in \mathcal{G})$ to leader participant

---

inspired KNN and calculate the mutual information. The score of the group, $U(\mathbf{A}[t])$, is averaged over all the validation instances.

3. *Participant selection.* Once running all the groups, the leader participant calculates the MI-based score of each participant, with which most valuable participants are selected.

3.3.1   Group Testing with Communication Batching

The naive implementation of the group testing routine has a critical drawback. The Fagin candidates generated by different groups may contain overlapping instances, causing significant amount of redundant overheads. As we will show, by leveraging what we call the *Inclusion Property* of the Fagin algorithm, we can batch the communication and computation of all test groups.

Inclusion Property of Fagin. The principle of the Fagin algorithm is to scan the sub-rankings from multiple participants until k distinct instances are found in all the sub-rankings. Given two subsets of participants, $\mathcal{S}_1$ and $\mathcal{S}_2$, what we can say about their data access pattern?

Theorem 1. *(Fagin's Inclusion Property) Given two groups of participants $\mathcal{S}_1 \subseteq \mathcal{P}$ and $\mathcal{S}_2 \subseteq \mathcal{P}$, their k-nearest candidates generated by Fagin algorithm satisfy $\mathcal{F}_1 \subseteq \mathcal{F}_2$ if $\mathcal{S}_1 \subseteq \mathcal{S}_2$.*

Please refer to Appendix A for the proof of Theorem 1. This indicates that the Fagin candidates of all groups can be found in those of the *"complete group"* that consists of all the participants. Based on this observation, we propose to batch the Fagin tasks of different groups in a single execution.

Implementation of Batch Optimization. The batching optimization is illustrated in Algorithm 1. The leader participant generates groups $\mathcal{G} = \{S_1, ...S_T\}$ and sends $\mathcal{G}$ to the aggregation server. The following shows the steps after getting the Fagin candidates, I_k, for the complete group $\mathcal{P}$.

1. Each participant P_i encrypts partial distances with homomorphic encryption. (line 1)
2. Each participant sends encrypted partial distances of Fagin candidates, i.e., $[\mathbf{d}_i^F]$, to the aggregation server through $Server.addition$ (line 2). For each group $S \in \mathcal{G}$, the aggregation server calculates the sum of all partial distances in S.
3. A random scheduler, $Server.scheduler$, on the aggregation server sends the aggregated distances of each group (denoted by $[\mathbf{d}_S]$) to a participant randomly (line 3).
4. For each received $[\mathbf{d}_S]$, the participant performs decryption and gets the sorted index I_S' (line 4).
5. The sorted indices are sent to the aggregation server through $Server.scheduler\_callback$ (line 5). The aggregation server lets the random scheduler associate them with the corresponding groups. Then, the aggregation server sends the sorted IDs of all the groups, $\{I_S\}$, to the leader participant.
6. The leader participant calculates the MI-based scores using the method of group testing and performs participant selection (line 6).

Datasets	Synthesis	G2-4	G2-128	Bank	Unbalance	Letter	Birch1	Birch2
# instances	1000	2048	2048	3200	6500	20K	100K	100K
# features	50	4	128	8	2	16	2	2
# classes	2	2	2	2	8	26	100	100
# partitions	5	4	4	4	2	4	2	2

Table 1: Evaluated datasets.

Figure 3: Selection performance (Pivot, 50% participants). "All-Train" refers to training on all participants. The other datasets are not reported because each training task costs more than one day.

Figure 4: Selection performance (LR, 50% participants).

Figure 5: Selection performance (KNN, 50% participants).

3.4 Security Analysis

Threat Model. Without loss of generality, we assume that the key server is honest and does not collude with any involved party. The aggregation server and all the participants are honest-but-curious, a common knowledge threat model used in the federated learning literature [28, 32].

The security properties of our proposed methods are summarized as follows (recall security requirements in Section 3.1). *Feature security* is protected against any curious party since the participants do not share their local features. *Aggregation security* is assured against curious aggregation server by homomorphic encryption. Regarding curious or colluding participants, aggregation security is also assured if the leader participant is benign. *Identity security* is achieved against a curious server if there is no server-participant collusion, because the proposed methods do not share instance identifiers I with the server. For detailed analysis, please refer to Appendix B.

4 Evaluation

We conducted experiments to validate the efficiency and effectiveness of the proposed methods.

4.1 Experimental Setting

Implementation. Numpy and PyTorch libraries are used to perform data loading and tensor manipulations. We implement RPC communication with proto2 and gRPC. TenSEAL [33] is a homomorphic library built on top of Microsoft SEAL [34]. We run all experiments in a cluster, in which each machine is equipped with 24 GB memory, 8 cores and 10 Gbps bandwidth.

Datasets. Table 1 illustrates all datasets that we used. Synthesis is a synthesis dataset by randomly generating a separation hyperplane, based on which data instances are sampled. The other datasets are collected from online repository [35, 36] and prior work [37–39]. Each dataset is split into a training set (80%), a validation set (10%), and a test set (10%). We randomly partition the training set into several vertical partitions and put each partition on one machine.

	Synthesis	G2-4	G2-128	Bank	Unbalance	Letter	Birch1	Birch2
VF-Ps/50%	0.60	0.68	1.0	0.89	0.93	0.89	0.1	0.99
VF-Ps/25%	0.59	0.61	1.0	0.8	-	0.83	-	-
Brute-force/50%	0.60	0.68	1.0	0.93	0.93	0.94	0.1	0.99
Brute-force/25%	0.59	0.63	1.0	0.93	-	0.86	-	-

Table 2: Comparison to the brute-force strategy on KNN. The metric is the test accuracy.

Figure 6: Ablation study of our proposed method.

ML Models. In this evaluation, we choose Pivot [9], a recent vertically federated tree training engine, as the downstream ML model. Additionally, we also implement *logistic regression* (LR), and *k-nearest neighbor* (KNN).

Participant Selection Baselines. We compare the following baselines on participant selection. 1) RANDOM: We randomly choose l participants and run ML model. The result is averaged over ten runs to assure the robustness. 2) LASSO. Lasso regression is a standard feature selection method in *scikit-learn*. We train a Lasso model and choose high-importance participants according to the absolute sum of coefficients on each participant. 3) VF-Ps is our proposed method that uses group testing and VF-MINE for participant selection.

Protocols. We implement Adam [40] and vanilla SGD as the optimization algorithm for LR and Lasso. We grid search the optimal learning rate in $\{0.001, 0.01, 0.1\}$ and the regularization term in $\{10^{-4}, 10^{-3}, 10^{-2}\}$, and choose a batch size of 256. We terminate the task after 50 epochs or the validation loss does not decrease within 5 epochs. For Pivot, we choose GBDT tree, and tune tree depth in $\{2, 3, 4\}$ and tree number in $\{1, 2, 3\}$. The other hyper-parameters are set as default.

4.2 Evaluation of Participant Selection

Selection Performance. We first study the following question: *can our proposed method outperform baselines regarding the selection of high-importance participants?* We compare RANDOM, LASSO and VF-Ps in terms of their performance of participant selection. When the downstream classification model is Pivot, Figure 3 shows the performance of all methods for selecting 50% participants. RANDOM is the fastest by instantly choosing participants; however, its selection accuracy can be much worse on many datasets. LASSO is the slowest since it needs to run multiple epochs until convergence and tunes the hyper-parameters. VF-Ps is only slightly slower than RANDOM and significantly faster than LASSO. Meanwhile, VF-Ps selects comparable, and often better, subsets of participants, indicated by the accuracy of training Pivot only on selected subsets. When the classification model becomes LR and KNN, we observe similar phenomena, as shown in Figure 4-5. We also study cases when the selection becomes more aggressive (25%), and find that VF-Ps also achieves the best trade-offs between selection speed and selection quality (refer to Appendix D.1).

Comparison to Full-fledged Training. We then turn to another question: *does participant selection provide benefits compared to training with all the participants?* To answer this question, we also show the result of training using all participants ("All-Train") in Figure 3-5. As we can see, the selection time of VF-Ps is orders of magnitude faster than the training time using all the participants; meanwhile, if we were to train a model only on the selected subset, we can achieve similar test accuracy on most datasets. On some datasets, e.g., Synthesis, G2-128, and Letter, we even observe higher accuracy after participant selection compared to the full-fledged training. This shows that some participants may have negative impacts on the model quality, and it is beneficial to choose high-importance participants. These experimental results verify the effectiveness and efficiency of participant selection.

Comparison to Brute-force Strategy. Intuitively, the brute-force solution for participant selection is to enumerate all the possible groups and choose the best one. Although this method is too time-consuming (up to two orders of magnitude slower according to our results), it provides the best possible selection strategy that can be used to understand — *how big is the gap between our selection strategy and the optimal (brute-force strategy)?* Table 2 shows the results of VF-PS and brute-force on KNN (other models are too slow to run the brute-force strategy). When the selection ratio is 50%, VF-PS gets the same selection quality on six datasets out of eight. Overall, the gap of selection quality is moderate on most datasets. It is an interesting future direction to come up with better participant selection criteria, going beyond mutual information.

Ablation Study. We now validate that both system optimizations (Fagin and Batching) significantly improve the system performance. We compare VF-PS with three variants—w/o Fagin, w/o batching, and w/o both—as illustrated in Figure 6. We see that both optimizations are crucial to the performance — disabling either of them significantly slows down the runtime on all dataasets.

5   Related Work

Federated Learning. Federated Learning (FL) is a category of distributed machine learning approach that lets multiple clients jointly train machine learning models over their personal data without data leakage [3–5]. Since the feature space and sample space of participating parties may not be identical, federated learning can be classified into horizontally federated learning and vertically federated learning. Horizontally federated learning is a scenario in which different parties share the same feature space but different sample space. In contrast, in vertically federated learning, different parties have the same sample space but different feature space. Other popular topics in federated learning include, but not limited to, federated transfer learning, heterogeneity-aware federated learning, fairness, and interpretability [41, 42].

Vertically Federated Learning. Hardy et al. [8] proposed a three-party vertically federated logistic regression solution by entity resolution and additively homomorphic encryption. Yang et al. [43] from WeBank and Yang et al. [44] from Baidu further extended vertically federated logistic regression to Quasi-Newton optimization and non-coordinator scenario. Feng and Yu [6] designed a multi-participant and multi-class federated learning framework for vertical training data. VAFL [7] was a vertically federated learning framework that allows each client to asynchronously run stochastic gradient algorithms without coordination with other clients. Pyvertical [45] was proposed to train multi-headed SplitNNs in the context of vertically federated learning using private set intersection. Liu et al. [46] proposed an asymmetrical vertically federated learning framework that protects sample IDs with the private set intersection protocol. Pivot [9] was proposed to train privacy-preserving vertical decision tree using SMC protocol. However, a single training job often takes several hours and the proposed framework is not suitable for cross-silo scenarios.

Federated Participant Selection. In the horizontally federated scenario, FedCS [47] tried to solve the resource heterogeneity in federated setting and conducted client selection to accelerate system performance. FedMCCS [48] further introduced a multicriteria approach for client selection, considering clients resources including CPU, memory, energy, and time. To address limited bandwidth in the presence of many clients, Huang et al. [49] proposed a selection policy to improve training efficiency while assuring client fairness. Different from these works that studied participant selection for system heterogeneity [50], our work focuses on selection regarding the contribution of each individual participant for the trained model. A few early, seminal works studied contribution-based participant selection in horizontally federated learning [51]; however, as far as we know, it has not been well studied how to perform participant selection in vertically federated scenario.

6   Conclusion

In this work, we study participant selection in the context of vertically federated learning. We model this problem as a mutual information-based view. We first propose a novel mutual information estimator, called VF-MINE, that uses Fagin's algorithm. To perform participant selection, we propose a group testing-base framework VF-PS on top of VF-MINE. We implement our proposed method using homomorphic encryption and design a batching optimization. We analyze the security properties of the proposed methods and show that our methods achieve orders of magnitude improvements.

References

[1] Arun Kumar, Matthias Boehm, and Jun Yang. Data management in machine learning: Challenges, techniques, and systems. In *Proceedings of the 2017 ACM SIGMOD International Conference on Management of Data*, pages 1717–1722, 2017.

[2] Neoklis Polyzotis, Sudip Roy, Steven Euijong Whang, and Martin Zinkevich. Data management challenges in production machine learning. In *Proceedings of the 2017 ACM SIGMOD International Conference on Management of Data*, pages 1723–1726, 2017.

[3] Tian Li, Anit Kumar Sahu, Ameet Talwalkar, and Virginia Smith. Federated learning: Challenges, methods, and future directions. *IEEE Signal Processing Magazine*, 37(3):50–60, 2020.

[4] Keith Bonawitz, Hubert Eichner, Wolfgang Grieskamp, Dzmitry Huba, Alex Ingerman, Vladimir Ivanov, Chloe Kiddon, Jakub Konečný, Stefano Mazzocchi, H Brendan McMahan, et al. Towards federated learning at scale: System design. *arXiv preprint arXiv:1902.01046*, 2019.

[5] Qiang Yang, Yang Liu, Tianjian Chen, and Yongxin Tong. Federated machine learning: Concept and applications. *ACM Transactions on Intelligent Systems and Technology (TIST)*, 10(2):1–19, 2019.

[6] Siwei Feng and Han Yu. Multi-participant multi-class vertical federated learning. *arXiv preprint arXiv:2001.11154*, 2020.

[7] Tianyi Chen, Xiao Jin, Yuejiao Sun, and Wotao Yin. Vafl: a method of vertical asynchronous federated learning. *arXiv preprint arXiv:2007.06081*, 2020.

[8] Stephen Hardy, Wilko Henecka, Hamish Ivey-Law, Richard Nock, Giorgio Patrini, Guillaume Smith, and Brian Thorne. Private federated learning on vertically partitioned data via entity resolution and additively homomorphic encryption. *arXiv preprint arXiv:1711.10677*, 2017.

[9] Yuncheng Wu, Shaofeng Cai, Xiaokui Xiao, Gang Chen, and Beng Chin Ooi. Privacy preserving vertical federated learning for tree-based models. *Proceedings of the VLDB Endowment*, 13 (11):2090–2103, 2020.

[10] Arash Fard, Anh Le, George Larionov, Waqas Dhillon, and Chuck Bear. Vertica-ml: Distributed machine learning in vertica database. In *Proceedings of the 2020 ACM SIGMOD International Conference on Management of Data*, pages 755–768, 2020.

[11] Michael Naehrig, Kristin Lauter, and Vinod Vaikuntanathan. Can homomorphic encryption be practical? In *Proceedings of the 3rd ACM workshop on Cloud Computing Security Workshop*, pages 113–124, 2011.

[12] Abbas Acar, Hidayet Aksu, A Selcuk Uluagac, and Mauro Conti. A survey on homomorphic encryption schemes: Theory and implementation. *ACM Computing Surveys (CSUR)*, 51(4): 1–35, 2018.

[13] Payman Mohassel and Yupeng Zhang. Secureml: A system for scalable privacy-preserving machine learning. In *2017 IEEE Symposium on Security and Privacy*, pages 19–38, 2017.

[14] Wenting Zheng, Ryan Deng, Weikeng Chen, Raluca Ada Popa, Aurojit Panda, and Ion Stoica. Cerebro: A platform for multi-party cryptographic collaborative learning. In *30th USENIX Security Symposium (USENIX Security 21)*, 2021.

[15] Kenji Kira and Larry A Rendell. A practical approach to feature selection. In *Machine Learning Proceedings*, pages 249–256. 1992.

[16] Shay Cohen, Eytan Ruppin, and Gideon Dror. Feature selection based on the shapley value. In *Proceedings of the 19th International Joint Conference on Artificial Intelligence*, pages 665–670, 2005.

[17] Brian C Ross. Mutual information between discrete and continuous data sets. *PloS one*, 9(2): e87357, 2014.

[18] Ronald Fagin, Amnon Lotem, and Moni Naor. Optimal aggregation algorithms for middleware. *Journal of Computer and System Sciences*, 66(4):614–656, 2003.

[19] Essam Mansour, Kavitha Srinivas, and Katja Hose. Federated data science to break down silos [vision]. *ACM SIGMOD Record*, 50(4):16–22, 2022.

[20] Evangelia Kalyvianaki, Marco Fiscato, Theodoros Salonidis, and Peter Pietzuch. Themis: Fairness in federated stream processing under overload. In *Proceedings of the 2016 ACM SIGMOD International Conference on Management of Data*, pages 541–553, 2016.

[21] Sebastian Baunsgaard, Matthias Boehm, Ankit Chaudhary, Behrouz Derakhshan, Stefan Geißelsöder, Philipp M Grulich, Michael Hildebrand, Kevin Innerebner, Volker Markl, Claus Neubauer, et al. Exdra: Exploratory data science on federated raw data. In *Proceedings of the 2021 ACM SIGMOD International Conference on Management of Data*, pages 2450–2463, 2021.

[22] Martin Abadi, Andy Chu, Ian Goodfellow, H Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. Deep learning with differential privacy. In *Proceedings of the 2016 ACM SIGSAC Conference on Computer and Communications Security*, pages 308–318, 2016.

[23] Luca Melis, George Danezis, and Emiliano De Cristofaro. Efficient private statistics with succinct sketches. *arXiv preprint arXiv:1508.06110*, 2015.

[24] Naman Agarwal, Ananda Theertha Suresh, Felix Yu, Sanjiv Kumar, and H Brendan Mcmahan. cpsgd: Communication-efficient and differentially-private distributed sgd. *arXiv preprint arXiv:1805.10559*, 2018.

[25] Valeria Nikolaenko, Udi Weinsberg, Stratis Ioannidis, Marc Joye, Dan Boneh, and Nina Taft. Privacy-preserving ridge regression on hundreds of millions of records. In *2013 IEEE Symposium on Security and Privacy*, pages 334–348, 2013.

[26] Ronald L Rivest, Len Adleman, Michael L Dertouzos, et al. On data banks and privacy homomorphisms. *Foundations of Secure Computation*, 4(11):169–180, 1978.

[27] Wenliang Du, Yunghsiang S Han, and Shigang Chen. Privacy-preserving multivariate statistical analysis: Linear regression and classification. In *Proceedings of the 2004 SIAM International Conference on Data Mining*, pages 222–233, 2004.

[28] Keith Bonawitz, Vladimir Ivanov, Ben Kreuter, Antonio Marcedone, H Brendan McMahan, Sarvar Patel, Daniel Ramage, Aaron Segal, and Karn Seth. Practical secure aggregation for privacy-preserving machine learning. In *Proceedings of the 2017 ACM SIGSAC Conference on Computer and Communications Security*, pages 1175–1191, 2017.

[29] Fangcheng Fu, Yingxia Shao, Lele Yu, Jiawei Jiang, Huanran Xue, Yangyu Tao, and Bin Cui. Vf2boost: Very fast vertical federated gradient boosting for cross-enterprise learning. In *Proceedings of the 2021 ACM SIGMOD International Conference on Management of Data*, pages 563–576, 2021.

[30] Alexander Kraskov, Harald Stögbauer, and Peter Grassberger. Estimating mutual information. *Physical Review E*, 69(6):066138, 2004.

[31] Yingbo Zhou, Utkarsh Porwal, Ce Zhang, Hung Q Ngo, XuanLong Nguyen, Christopher Ré, and Venu Govindaraju. Parallel feature selection inspired by group testing. *Advances in Neural Information Processing Systems*, 27, 2014.

[32] Reza Shokri and Vitaly Shmatikov. Privacy-preserving deep learning. In *Proceedings of the 22nd ACM SIGSAC Conference on Computer and Communications Security*, pages 1310–1321, 2015.

[33] Ayoub Benaissa, Bilal Retiat, Bogdan Cebere, and Alaa Eddine Belfedhal. Tenseal: A library for encrypted tensor operations using homomorphic encryption, 2021. URL https://github.com/OpenMined/TenSEAL.

[34] SEAL. Microsoft SEAL (release 4.0). `https://github.com/Microsoft/SEAL`, March 2022. Microsoft Research, Redmond, WA.

[35] Rong-En Fan. Libsvm data: Classification, regression, and multi-label. URL `https://www.csie.ntu.edu.tw/~cjlin/libsvmtools/datasets/`.

[36] Pasi Fränti and Sami Sieranoja. K-means properties on six clustering benchmark datasets, 2018. URL `http://cs.uef.fi/sipu/datasets/`.

[37] Pang Wei Koh and Percy Liang. Understanding black-box predictions via influence functions. In *International Conference on Machine Learning*, pages 1885–1894, 2017.

[38] Ruoxi Jia, David Dao, Boxin Wang, Frances Ann Hubis, Nick Hynes, Nezihe Merve Gürel, Bo Li, Ce Zhang, Dawn Song, and Costas J Spanos. Towards efficient data valuation based on the shapley value. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 1167–1176, 2019.

[39] Bojan Karlaš, Peng Li, Renzhi Wu, Nezihe Merve Gürel, Xu Chu, Wentao Wu, and Ce Zhang. Nearest neighbor classifiers over incomplete information: from certain answers to certain predictions. *Proceedings of the VLDB Endowment*, 14(3):255–267, 2020.

[40] Diederik Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[41] Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial Intelligence and Statistics*, pages 1273–1282, 2017.

[42] Tian Li, Maziar Sanjabi, Ahmad Beirami, and Virginia Smith. Fair resource allocation in federated learning. *arXiv preprint arXiv:1905.10497*, 2019.

[43] Kai Yang, Tao Fan, Tianjian Chen, Yuanming Shi, and Qiang Yang. A quasi-newton method based vertical federated learning framework for logistic regression. *arXiv preprint arXiv:1912.00513*, 2019.

[44] Shengwen Yang, Bing Ren, Xuhui Zhou, and Liping Liu. Parallel distributed logistic regression for vertical federated learning without third-party coordinator. *arXiv preprint arXiv:1911.09824*, 2019.

[45] Daniele Romanini, Adam James Hall, Pavlos Papadopoulos, Tom Titcombe, Abbas Ismail, Tudor Cebere, Robert Sandmann, Robin Roehm, and Michael A Hoeh. Pyvertical: A vertical federated learning framework for multi-headed splitnn. *arXiv preprint arXiv:2104.00489*, 2021.

[46] Yang Liu, Xiong Zhang, and Libin Wang. Asymmetrical vertical federated learning. *arXiv preprint arXiv:2004.07427*, 2020.

[47] Takayuki Nishio and Ryo Yonetani. Client selection for federated learning with heterogeneous resources in mobile edge. In *ICC 2019-2019 IEEE International Conference on Communications (ICC)*, pages 1–7, 2019.

[48] Sawsan AbdulRahman, Hanine Tout, Azzam Mourad, and Chamseddine Talhi. Fedmccs: Multicriteria client selection model for optimal iot federated learning. *IEEE Internet of Things Journal*, 8(6):4723–4735, 2020.

[49] Tiansheng Huang, Weiwei Lin, Wentai Wu, Ligang He, Keqin Li, and Albert Y Zomaya. An efficiency-boosting client selection scheme for federated learning with fairness guarantee. *IEEE Transactions on Parallel and Distributed Systems*, 32(7):1552–1564, 2020.

[50] Yae Jee Cho, Jianyu Wang, and Gauri Joshi. Client selection in federated learning: Convergence analysis and power-of-choice selection strategies. *arXiv preprint arXiv:2010.01243*, 2020.

[51] Tianhao Wang, Johannes Rausch, Ce Zhang, Ruoxi Jia, and Dawn Song. A principled approach to data valuation for federated learning. In *Federated Learning*, pages 153–167. 2020.

[52] Seny Kamara, Payman Mohassel, Mariana Raykova, and Saeed Sadeghian. Scaling private set intersection to billion-element sets. In *International Conference on Financial Cryptography and Data Security*, pages 195–215, 2014.

A Proof of Theorem 1

Proof. For the group $\mathcal{S}_2$, assume the Fagin algorithm scans F rows of sub-rankings $\{R_i, \forall p_i \in \mathcal{S}_2\}$ before finding instances $D = \{x_1, x_2, ..., x_k\}$ occurring in $\forall p \in \mathcal{S}_2$. The ranking of each instance in D should satisfy:

$$I(x_i, p_j) \leq F, \quad for \ \ \forall x_i \in D \ \ and \ \ p_j \in \mathcal{S}_2$$

Since $\mathcal{S}_1$ is a subset of $\mathcal{S}_2$, we can directly infer:

$$I(x_i, p_k) \leq F, \quad for \ \ \forall x_i \in D \ \ and \ \ p_k \in \mathcal{S}_1$$

The above implies that we can find D in each participant $p \in \mathcal{S}_1$ before scanning F rows The Fagin candidate set of $\mathcal{S}_2$ contains all the unique instances within F rows:

$$\mathcal{F}_2 = Set(\cup_{p_i \in \mathcal{S}_2} R_i[: F])$$

Similarly, the Fagin candidate set of $\mathcal{S}_1$ is a subset of all unique samples within F rows:

$$\mathcal{F}_1 \subseteq Set(\cup_{p_i \in \mathcal{S}_1} R_i[: F])$$

Since $\mathcal{S}_1$ is a subset of $\mathcal{S}_2$, all the samples appear within F rows of $\mathcal{S}_1$ also appear in $\mathcal{S}_2$:

$$Set(\cup_{p_i \in \mathcal{S}_1} R_i[: F]) \subseteq Set(\cup_{p_i \in \mathcal{S}_2} R_i[: F])$$

Therefore, we can conclude:

$$\mathcal{F}_1 \subseteq \mathcal{F}_2$$

$\square$

Based on Theorem 1, we can deduce the following Lemma:

Lemma 1. *If the Fagin candidates $\mathcal{F}$ of the complete group $\mathcal{P}$ are known, we can find top-k instances in $\mathcal{F}$ for any $\mathcal{S} \subseteq \mathcal{P}$.*

B Security Analysis

We conduct a comprehensive analysis to discuss the security properties of our methods.

B.1 Threat Model

Below, we define the threat model for three roles in the framework.

- *Key server.* Without loss of generalization, we assume the key server is honest and does not collude with any involved party.
- *Aggregation server.* The aggregation server is *honest-but-curious*, a common threat model used in the federated learning literature [28, 32]. The aggregation server may try to recover the received data. Besides, there is no collusion between the aggregation server and any participant; otherwise, the aggregation server can decrypt anything it receives from the participants.
- *Participant.* All the participants are also *honest-but-curious*. Each of them provides the correct data and follows the protocol, but may try to learn other participants' data. In terms of collusion, some participants may collude with each other and try to recover data from benign participants.

B.2 Baseline Method for MI Estimation

Here we analyze the baseline method for MI estimation.

Feature Security. Our proposed method does not allow the participants to share their local features. As a result, the feature security is protected against any curious party.

Aggregation Security. The aggregation security is assured after encryption if all the participants are benign. We separately discuss the cases of curious parties and collusion.

- *Curious aggregation server.* Since the aggregation server does not have the private key of HE nor collude with any participant, the partial distances are fully protected against a curious aggregation server.
- *Curious participant.* A curious participant does not directly receive $[\mathbf{d}_i]$ from other participants, and hence cannot speculate benign participants. A special case is that there are only two participants, and a curious leader participant can infer the other participant's partial distance. Therefore, the baseline method is secure if the leader participant is benign or there are more than two participants.
- *Colluding participant.* If the leader participant does not collude, the colluding participants cannot speculate other participants' partial distances, since they do not have the complete distances. On the contrary, if the leader participant does collude, it can directly get the partial distances of the colluding participants. However, as long as there are more than two benign participants, the leader participant still cannot speculate their partial distances. In summary, the aggregation security is assured if the leader participant is benign or there are at least two benign participants.

Identity Security. Since the baseline method does not share instance identities I with the server and there is no server-participant collusion, the data identities are protected against the server.

B.3 Fagin-inspired Method for MI Estimation

Feature Security & Aggregation Security. Same as the baseline method, the Fagin-inspired method does not share local features and original partial distances to the aggregation server. Therefore, the feature security and aggregation security remain the same.

Identity Security. The Fagin-inspired method needs to find k-nearest candidates through the aggregation server. Although the instance IDs are randomly shuffled and replaced by "puesduo" IDs, it is still unknown whether this method can protect the local ranking of each participant. Conceptually, the Fagin algorithm can be seen as an extension of private set intersection, which has been studied in [52]. According to their rigorous analysis, the random shuffling operation can assure the security of local rankings if (1) all participants are benign, (2) the aggregation server is curious but the participants are benign, or (2) the aggregation server is benign with any collusion of participants.

B.4 Fagin-inspired Participant Selection

We next conduct a security analysis for the proposed participant selection method.

Feature Security & Identity Security. Refer to the analysis for Fagin-inspired MI estimation.

Aggregation Security. If the aggregation server and the participants are benign, the partial distances are protected by homomorphic encryption. We analyze the following threat models.

- *Curious aggregation server.* If there is no server-participant collusion, the aggregation security is not harmed as the aggregation server only has the public key.
- *Curious participant.* The proposed method allocates aggregated distances across the participants. This raises a potential risk — *can a curious participant recover other participants' partial distances?* This is possible if the assignment strategy is fixed and the curious participant can somehow guess it. However, since our proposed approach adopts a random scheduler, it is impossible for any curious participant to speculate the allocation pattern.
- *Colluding participant.* It is possible for colluding participants to speculate benign participants if the allocation strategy is easy to speculate, due to the same reason explained above. Likewise, the random scheduler can protect aggregation security in the presence of colluding participant.

C   Other Privacy Preserving Techniques

In principle, our framework can be instantiated with other security protocol, such as Secure Multi-party Computation (SMC). Providing a full implementation in SMC is beyond the scope of this paper, and we expect, just like the HE implementation is non-trivial, an SMC-based implementation will have its own challenges but also open up new opportunities for optimization. In the following, we provide some thoughts about a potential SMC-based implementation and our perceived challenges. Since two oracle operators in our protocols are secure `addition` and secure `Fagin`, we will focus on these two operators.

Secure Addition Operator with SMC. Addition is a basic operation in SMC. Since our protocol for participant selection needs to handle groups of different sizes, we need to tailor the secure addition operator under two-party and multi-party scenarios.

Secure Fagin Operator with SMC. As Fagin is not a standard mathematical or logical operator, the existing SMC works have not studied how to implement Fagin. This is indeed an obstacle for the instantiation of our proposed protocol. The most similar standard SMC operator is set intersection [52] that finds overlapping items from multiple lists. But, this cannot fully replicate Fagin because Fagin outputs all the items have seen after finding k overlapping items. Nonetheless, if SMC-based Fagin has an efficient solution in the future, it can be integrated into our proposed protocol. Note that, since SMC operators are generally more costly than plaintext operators, it is important to assess the overall cost when SMC-based Fagin is introduced.

D   More Experimental Results

Due to space constraints, we present additional experimental results here.

Figure 7: Selection performance (Pivot, 25% participants). Unbalance is not reported because there are only two participants.

Figure 8: Selection performance (LR, 25% participants). The other three datasets are not reported because there are only two participants.

Figure 9: Selection performance (KNN, 25% participants). The other three datasets are not reported because there are only two participants.

Figure 10: Scalability on Participant Selection (KNN, Letter, 50% participants).

D.1 Selection Performance

Figure 7 to 9 show the results when selecting 25% participants. We observe similar phenomena as what we have summarized for selecting 50% participants.

D.2 Scalability

We evaluate the scalability of different participant selection methods. We partition the Letter dataset into different numbers of partitions (m=2/4/8/16), and then run participant valuation for a KNN model. As shown in Figure 10, the brute-force approach encounters timeout failure (longer than one day) when m become larger than 4, because there are too many groups to evaluate. Unsurprisingly, the RANDOM approach costs nearly zero time on the selection. VF-PS w/o batching and w/o Fagin both outperform the brute-force method since the Fagin strategy reduces a large portion of instances

to be processed and the batching optimization reduces redundancy. When the number of participants increases, VF-PS also encounters performance degradation because the Fagin strategy becomes less effective for a large group. Nevertheless, VF-PS still significantly outperforms other methods with the batching optimization.