To be Robust or to be Fair: Towards Fairness in Adversarial Training

Abstract

Adversarial training algorithms have been proven to be reliable to improve machine learning models' robustness against adversarial examples. However, we find that adversarial training algorithms tend to introduce severe disparity of accuracy and robustness between different groups of data. For instance, PGD adversarially trained ResNet18 model on CIFAR-10 has 93% clean accuracy and 67% PGD l_∞-8 adversarial accuracy[1] on the class "automobile" but only 59% and 17% on class "cat". This phenomenon happens in balanced datasets and does not exist in naturally trained models when only using clean samples. In this work, we theoretically show that this phenomenon can generally happen under adversarial training algorithms which minimize DNN models' robust errors. Motivated by these findings, we propose a Fair-Robust-Learning (FRL) framework to mitigate this unfairness problem when doing adversarial defenses and experimental results validate the effectiveness of FRL.

1 Introduction

The existence of adversarial examples (Goodfellow et al., 2014; Szegedy et al., 2013) causes huge concerns when applying deep neural networks on safety-critical tasks, such as autonomous driving vehicles and face identification. These adversarial examples are artificially crafted samples. They have imperceptible difference from natural samples, but can misguide the model to give wrong predictions. As countermeasures against the attack from adversarial examples, adversarial training algorithms aim to train classifier that can classify the input samples correctly even when they are adversarially perturbed. Namely, they optimize the model to have minimum risk that a sample can be perturbed to be wrongly classified. These adversarial training methods (Goodfellow et al., 2014; Madry et al., 2017; Zhang et al., 2019) have been shown to be one type of the most effective and reliable ways to improve the model robustness against adversarial attacks. Although promising to improve model's robustness, recent studies also show one side-effect of adversarial training – it usually degrades model's clean accuracy (Tsipras et al., 2018).

In our work, we find a new intriguing property about adversarial training algorithms: they usually result in a large disparity of accuracy and robustness between different classes. As a preliminary study in Section 2, we apply natural training and PGD adversarial training (Madry et al., 2017) on the CIFAR10 dataset (Krizhevsky et al., 2009) using a ResNet (He et al., 2016) architecture. For a naturally trained model, the model performance in each class is similar. However, in the adversarially trained model, there is a severe performance discrepancy (both accuracy and robustness) of the model for data in different classes. For example, the model has high clean accuracy and robust accuracy (93% and 67% successful rate, separately) on the samples from the class "car", but much poorer performance on those "cat" images (59% and 17% successful rate). More preliminary results in Section 2 further show the similar "unfair" phenomenon from other datasets and models. Meanwhile, we find that this fairness issue does not appear in natural models which are trained on clean data. This fact demonstrates that adversarial training algorithms can indeed unequally help to improve model robustness for different data groups and unequally degrade their clean accuracy.

In this work we define this problem as the *unfairness problem of adversarial training algorithms*. If this phenomenon happens in real-world applications, it can raise huge concerns about safety or even social ethics. Imagine that an adversarially trained traffic sign recognizer has overall high robustness, but it is very inaccurate and vulnerable to perturbations for some specific signs such as stop signs. The safety of this autonomous driving car is still not guaranteed. In such case, the safety of this

---

[1] The model's accuracy on the input samples that have been adversarially perturbed.

recognizer depends on the worst class performance. Therefore, in addition to achieving overall performance, it is also essential to achieve fair accuracy and robustness among different classes, which can guarantee the worst performance. Meanwhile, this problem may also lead to the issues from social ethics perspectives, which are similar to traditional ML fairness problems (Buolamwini & Gebru, 2018). For example, a robustly trained face identification system might provide different qualitative levels of service safety for different ethnic communities.

In this paper, we first explore the potential reason which may cause this unfair accuracy / unfair robustness problem. In particular, we aim to answer the question - "*Will adversarial training algorithms naturally cause unfairness problems, such as the disparity of clean accuracy and adversarial robustness between different classes?*" To answer this question, we first propose a conceptual example under a mixture of two spherical Gaussian distributions which resembles to the previous work (Tsipras et al., 2018) but with different variances. In this setting, we hypothesize that adversarial training tends to only use robust features for model prediction, whose dimension is much lower than the non-robust feature space. In the lower dimensional space, an optimal linear model is more sensitive to the inherent data distributional difference and be biased when making predictions.

Motivated by these empirical and theoretical findings, we then propose a Fair Robust Learning (FRL) framework to mitigate this unfairness issue, which is inspired from the tradition debiasing strategy to solve a series of cost-sensitive classification problems but we make specific effort to achieve the fairness goal in adversarial setting. Our main contributions can be summarized as following: (a) We discover the phenomenon of "unfairness" problem of adversarial training algorithms and implement empirical studies to present this problem can be general; (b) We build a conceptual example to theoretically investigate the main reasons that cause this unfairness problem; and (c) We propose a Fair Robust Learning (FRL) framework to mitigate the unfairness issue in adversarial setting.

2 PRELIMINARY STUDIES

In this section, we present our preliminary studies to show that adversarial training algorithms usually present the unfairness issues, which are related to the strong disparity of clean accuracy and robustness among different classes. We implement algorithms including PGD adversarial training (Madry et al., 2017) and TRADES (Zhang et al., 2019) on the CIFAR10 dataset (Krizhevsky et al., 2009). In CIFAR10, we both naturally and adversarially train ResNet18 (He & Garcia, 2009) models. In Figure 1, we present list the the model's accuracy and robustness performance (under PGD attack by intensity $4/255$ and $8/255$) for each individual class.

Figure 1: Clean and adversarial accuracy in each class of CIFAR10 dataset, from a naturally trained ResNet model (left), PGD-adversarially trained model (middle) and TRADES (right). Adversarial examples are generated using PGD untargeted attack under l_∞-norm constrained by $8/255$ and $4/255$.

From the Figure 1, we can observe that – for the naturally trained models, every class has similar clean accuracy (around $90 \pm 5\%$) and adversarial accuracy (close to 0%) under the PGD attack. It suggests that naturally trained models do not have strong disparity of both clean and robustness performance among classes. However, for adversarially trained models (under PGD Adv. Training or TRADES), the disparity phenomenon becomes severe. For example, a PGD-adversarially trained model has 59.1% clean accuracy and 17.4% adversarial accuracy for the samples in the class "cat", which are much lower than the model's overall performance. This phenomenon demonstrates that adversarial training algorithms cannot provide the same help for the robustness for the samples in class "cat" as other classes, and unfairly degrades too much clean accuracy for "cat". We list the overall performance for more models in Appendix A.1 and results on GTRSB (Stallkamp et al., 2011) in Appendix A.2. We can make the similar observation that adversarial training introduces serious unfairness issues.

3 THEORETICAL ANALYSIS BASED ON A CONCEPTUAL EXAMPLE

From our preliminary studies, we always observe that adversarially trained models have huge performance disparity (clean and adversarial accuracy) between different groups. In this section, we try to understand the unfairness problem via theoretical analysis based on a binary classification problem on a mixture-Gaussian distribution, which is similar to (Tsipras et al., 2018). We show that this unfairness problem can be related to the lower dimension of the robust feature space (used by robust model) compared to the non-robust feature space (used by natural model).

Notations. In the following, we use f to denote the classification model which is a mapping $f : \mathcal{X} \to \mathcal{Y}$ from input data space $\mathcal{X}$ and output labels $\mathcal{Y}$. Generally, naturally training will find the optimal f to minimize the overall clean error $\mathcal{R}_{\text{nat}}(f) = \Pr.(f(x) \neq y)$; and adversarially training will minimize the overall robust error $\mathcal{R}_{\text{rob}}(f) = \Pr.(\exists \delta, ||\delta|| \leq \epsilon, \text{s.t.} f(x + \delta) \neq y)$. Specifically in the following binary classification problem, $\mathcal{Y} = \{-1, +1\}$ and each class's clean error and robust error are denoted as the conditional probabilities: $\mathcal{R}_{\text{nat}}(f, -1) = \Pr.(f(x) = +1|y = -1)$, and $\mathcal{R}_{\text{rob}}(f, -1) = \Pr.(\exists \delta, ||\delta|| \leq \epsilon, \text{s.t.} f(x + \delta) = +1|y = -1)$, respectively.

3.1 A BINARY CLASSIFICATION TASK

Our study is motivated by (Tsipras et al., 2018) which uncovers one key behavior of adversarial training: it excludes high-dimensional non-robust features (which are vulnerable to attack) and only preserves lower-dimensional robust features for prediction. Thus, in our case, we assume our conceptual dataset has the data-label pairs (x, y) sampled from a distribution $\mathcal{D}$ follows:

$$y \overset{u.a.r}{\sim} \{-1, +1\}, \quad \theta = (\overbrace{\gamma, ..., \gamma}^{\text{dim} = m}, \overbrace{\eta, ..., \eta}^{\text{dim} = d}), \quad x \sim \begin{cases} \mathcal{N}(\theta, \sigma_{+1}^2 I) & \text{if } y = +1 \\ \mathcal{N}(-\theta, \sigma_{-1}^2 I) & \text{if } y = -1 \end{cases} \tag{1}$$

where $\mathcal{N}(\theta, \sigma_{+1}^2 I)$ is a normal distribution with mean vector θ and covariance matrix $\sigma_{+1}^2 I$ and same for class "-1". Following the work (Tsipras et al., 2018), we suppose that the feature space consists of two kinds of features: (a) **robust features** with center γ and dimension m; and (b) **non-robust features** with center η and dimension d. We assume $\eta < \epsilon < \gamma$, so an adversarial perturbation δ with intensity $||\delta||_\infty \leq \epsilon$ can manipulate a non-robust feature to have a different sign in expectation, but δ cannot attack a robust feature. Usually, the non-robust features' dimension d is far higher than the robust features' dimension d, i.e., $(m << d)$. The significantly different properties of the two feature sets will facilitate us to explicitly demonstrate the "unfairness" impact from adversarial training on this dataset. In our case, we assume that the 2 classes have a key difference between their variances: $\sigma_{+1} : \sigma_{-1} = K : 1$, where $K > 1$. In the theoretical example, our main hypothesis is that the variance difference between 2 classes will not lead to strong disparity of model performance for naturally trained models, but can cause large performance gap (both accuracy and robustness) after adversarial training.

3.2 OPTIMAL LINEAR MODEL TO MINIMIZE CLEAN ERROR

We first calculate one linear model for this data to minimize the total clean errors. Specifically, we consider a linear classifier f with its optimal parameters w^* and b^*:

$$f^*(x) = \text{sign}(\langle w^*, x \rangle + b^*)$$
$$\text{where } w^*, b^* = \arg\min_{w,b} \Pr.(f(x) \neq y) \tag{2}$$

where w is features' weight vector and b is the model intersection. In later parts, we use f to represent f^* for convenience. We call the optimized model *naturally trained model* because it minimizes model's clean error to get overall high clean accuracy. Typically, a naturally trained model will use both robust features and non-robust features for inference but its prediction outcome majorly depends on non-robust features. Next, we show the exact form of the errors for each class in Theorem 1 and the proof is provided in Appendix B.1.

Theorem 1 *Optimal linear classifier which minimizes overall clean error in $\mathcal{D}$ will have class-conditional clean errors:*

$$\mathcal{R}_{nat}(f, -1) = Pr.\{\mathcal{N}(0, 1) \leq \overbrace{A - \sqrt{K \cdot A^2 + q(K)}}^{Z_{nat}(f, -1))}\}, \tag{3}$$

$$\mathcal{R}_{nat}(f, +1) = Pr.\{\mathcal{N}(0, 1) \leq \underbrace{-K \cdot A + \sqrt{A^2 + q(K)}}_{Z_{nat}(f, +1))}\}, \tag{4}$$

where $A = \frac{2}{\sigma(K^2-1)}\sqrt{m\gamma^2 + d\eta^2}$ and $q(K) = \frac{2\log(K)}{K^2-1}$. *It has the robust error under attack* $||\delta|| \leq \epsilon_0$:

$$\mathcal{R}_{rob}(f,-1) = Pr.\{\mathcal{N}(0,1) \leq \overbrace{Z_{nat}(f,-1) + \frac{m\gamma + d\eta}{\sqrt{m\gamma^2 + d\eta^2}}\frac{\epsilon_0}{\sigma}}^{Z_{rob}(f,-1))}\} \tag{5}$$

$$\mathcal{R}_{rob}(f,+1) = Pr.\{\mathcal{N}(0,1) \leq \underbrace{Z_{nat}(f,+1) + \frac{m\gamma + d\eta}{\sqrt{m\gamma^2 + d\eta^2}}\frac{\epsilon_0}{K\sigma}}_{Z_{rob}(f,+1))}\}. \tag{6}$$

Note that the term A (consisting of feature dimension d, m and center γ, η) represents how expressive the information from $\mathcal{D}$ that model f can use for prediction. Thus, when the term A is large, the model has close clean errors between the 2 classes, namely $\mathcal{R}_{nat}(f,-1) \approx \mathcal{R}_{nat}(f,+1)$. It is because the $q(K)$ term in their z-scores[2] can be ignored when A is large. On the other hand for their robust errors, typically we assume the adversarial attack by $||\delta|| \leq \epsilon_0$ can bring in major threat to mislead natural model f, which will result both $Z_{rob}(f,-1)$ and $Z_{rob}(f,+1)$ to be large positive numbers, so that the robust errors of both classes $\mathcal{R}_{rob}(f,-1)$ and $\mathcal{R}_{rob}(f,+1)$ are also large.

3.3 OPTIMAL LINEAR MODEL TO MINIMIZE ROBUST ERROR

During adversarial training, the desired linear classifier should minimize the total robust error, which minimizes the probability that there exists a perturbation δ constrained by budge $||\delta||_\infty \leq \epsilon$ that can let the model make mistake. Formally, we describe a linear classifier after adversarial training as:

$$f_{adv}^*(x) = \text{sign}(\langle w_{adv}^*, x\rangle + b_{adv}^*)$$
$$\text{where } w_{adv}^*, b_{adv}^* = \underset{w,b}{\arg\min} \; Pr.(\exists\delta, ||\delta|| \leq \epsilon, \text{ s.t. } f_{adv}(x+\delta) \neq y). \tag{7}$$

Similarly we use f_{adv} to denote f_{adv}^* for convenience. During adversarial training, the linear model will only preserve the weights on robust features and exclude all non-robust features as proved in Lemma 2 in the Appendix. We will also call the adversarially trained model in $\mathcal{D}$ a robust model, because its features cannot be easily manipulated by perturbations under $||\delta|| \leq \epsilon$. We show the robust model's clean and robust errors in Theorem 2 and the proof is provided in Appendix B.2.

Theorem 2 *Optimal linear classifier which minimizes overall robust error in $\mathcal{D}$ will have class-conditional clean errors:*

$$\mathcal{R}_{nat}(f_{adv},-1) = Pr.\{\mathcal{N}(0,1) \leq B - \sqrt{K \cdot B^2 + q(K)} \tag{8}$$

$$\mathcal{R}_{nat}(f_{adv},+1) = Pr.\{\mathcal{N}(0,1) \leq -K \cdot B + \sqrt{B^2 + q(K)}\} \tag{9}$$

where $B = \frac{2}{\sigma(K^2-1)}\sqrt{m \cdot (\gamma - \epsilon)^2}$, $q(K) = \frac{2\log(K)}{K^2-1}$, *and robust errors under attack* $||\delta|| \leq \epsilon_0$:

$$\mathcal{R}_{rob}(f_{adv},-1) = Pr.\{\mathcal{N}(0,1) \leq Z_{nat}(f_{adv},-1) + \sqrt{m}\frac{\epsilon_0}{\sigma}\} \tag{10}$$

$$\mathcal{R}_{rob}(f_{adv},+1) = Pr.\{\mathcal{N}(0,1) \leq Z_{nat}(f_{adv},+1) + \sqrt{m}\frac{\epsilon_0}{K\sigma}\}. \tag{11}$$

Recall that we assume the dimension of non-robust features is much higher than that of robust features ($d >> m$) and γ, η and ϵ have similar scale: $\epsilon = \Theta(\gamma)$ and $\eta = \Theta(\gamma)$. Therefore, in Eq. (8) and Eq. (9), for model f_{adv}'s clean errors, the decisive term B is at scale $\Theta((d/m)^{-\frac{1}{2}} \cdot A)$, where A is the term in Eq.(3). In Corollary 1 (proved in Appendix B.3), we show that it is this relationship between A and B that will finally bring in the "unfair" issue to both model accuracy and robustness performance.

Corollary 1 *Adversarially Trained Model on $\mathcal{D}$ will have larger clean error disparity between the 2 classes, compared to a Naturally Trained model.*

---

[2]At here we use $Z_{nat}(f,-1)$ and $Z_{nat}(f,+1)$ to denote the z-score for the standard normal distribution corresponding to $\mathcal{R}_{nat}(f,-1)$ and $\mathcal{R}_{nat}(f,+1)$. Similarly, we use $Z_{rob}(f,-1)$ and $Z_{rob}(f,+1)$ to denote the z-score of the standard normal distribution of $\mathcal{R}_{rob}(f,-1)$ and $\mathcal{R}_{rob}(f,+1)$.

We calculate 2 classes' clean error difference: $(\mathcal{R}_{nat}(f, +1) - \mathcal{R}_{nat}(f, -1))$ for natural model f; and $(\mathcal{R}_{nat}(f_{adv}, +1) - \mathcal{R}_{nat}(f_{adv}, -1))$ for adversarially trained model f_{adv}. Since both terms are positive, we show their ratio (detailed proof in Appendix):

$$\Omega = \frac{\mathcal{R}_{nat}(f_{adv}, +1) - \mathcal{R}_{nat}(f_{adv}, -1)}{\mathcal{R}_{nat}(f, +1) - \mathcal{R}_{nat}(f, -1)} \geq \frac{(K^2 - 1)\log(K)\sigma^2}{2\Theta(\gamma^2)} \cdot \Theta(\frac{d}{m})^{\frac{1}{2}}. \qquad (12)$$

In Eq. (12), we can tell once d/m is large, the ratio Ω is also large (e.g. > 1) and the adversarial training is showed to enlarge the 2 classes' clean error disparity. The ratio Ω in Eq. (12) uncovers the main factor which may cause the "unfair" phenomenon in adversarially trained models: because the robust models make prediction in a feature space with dimension m which is much lower than d (dimension for natural models), their clean accuracy disparity between classes can be more sensitive to the classes' distributional difference K. In this way the robust model presents strong disparity of clean accuracy.

Furthermore, for the robust errors (i.e., Eqs. (10) and (42)) in adversariallly trained model, an adversarial attack under intensity ϵ_0 will make the test error increase only by a small margin compared to the model's clean error in Eqs. (8) and (9). It is because the their z-scores difference is decided by $\sqrt{m}$ which is small and much lower than d. Because of the marginal difference between $R_{nat}(f_{adv}, -1)$ and $R_{rob}(f_{adv}, -1)$ (also for class "+1"), the model's fairness condition on robust errors will align to the clean errors (in Eq. (12)). Empirical results on real datasets also support this assumption (Table 2 in Appendix A.1). As a conclusion, adversarial training can bring in unfairness issues on both clean and robust performance.

4 FAIR ROBUST LEARNING (FRL)

Faced with the unfairness problem of adversarial training shown in Section 2 and 3, we desire to devise a Fair Robust Learning (FRL) strategy, in order to train robust models that have balanced accuracy and robustness performance for each class. Formally, we aim to train a classifier f to have minimal overall robust error ($\mathcal{R}_{rob}(f)$); while stressing f to satisfy a series of fairness constraints:

$$\begin{aligned} \underset{f}{\text{minimize}} \quad & \mathcal{R}_{rob}(f) \\ \text{s.t.} \quad & \mathcal{R}_{nat}(f, i) - \mathcal{R}_{nat}(f) \leq \tau_1 \text{ and } \mathcal{R}_{rob}(f, i) - \mathcal{R}_{rob}(f) \leq \tau_2 \text{ for each } i \in Y \end{aligned} \qquad (13)$$

where τ_1 and τ_2 are small and positive values. The constraints in Eq. (13) restrict the model's error for each class i (both clean error $\mathcal{R}_{nat}(f, i)$ and robust error $\mathcal{R}_{rob}(f, i)$) should not be too larger than the average level ($\mathcal{R}_{nat}(f)$ and $\mathcal{R}_{rob}(f)$). Therefore, the model will not have specific weak points under the risk of wrong prediction or adversarial attacking. Next, we will discuss the detailed components of our proposed Fair Robust Learning (FRL) algorithm to solve the problem in Eq. (13).

4.1 TRADITIONAL MODEL DEBIASING METHOD: A REDUCTIONS APPROACH

In order to solve the fair robust training problem in Eq. (13), we follow the main pipeline from traditional machine learning debiasing works such as (Agarwal et al., 2018), which reduces the problem in Eq. (13) into a series of *Cost-sensitive* classification problems and continuously penalizes the terms which violate the fairness constraints. We begin by introducing Lagrange multipliers $\phi = (\phi_{nat}^i, \phi_{rob}^i)$ (non-negative) for each constraint in Eq. (13) and form the Lagrangian:

$$L(f, \phi) = \mathcal{R}_{rob}(f) + \sum_{i=1}^{Y} \phi_{nat}^i(\mathcal{R}_{nat}(f, i) - \mathcal{R}_{nat}(f) - \tau_1) + \sum_{i=1}^{Y} \phi_{rob}^i(\mathcal{R}_{nat}(f, i) - \mathcal{R}_{rob}(f) - \tau_2) \qquad (14)$$

It equals to solving the max-min game between f and ϕ as:

$$\max_{\phi_{nat}, \phi_{rob} \geq 0} \min_{f} L(f, \phi). \qquad (15)$$

Typically, given a fixed ϕ, if the current model f violates some constraints in Eq. (13) (for example $\mathcal{R}_{nat}(f, i) - \mathcal{R}_{nat}(f) - \tau_1 > 0$), we first solve the outer-maximization problem in Eq. (15) by increasing its corresponding multiplier ϕ_{nat}^i. As a result, we upweight the training weight (or cost) for the clean loss $\mathcal{R}_{nat}(f, i)$ of all samples in the class i. Then, the algorithm will solve the inner-minimization given new ϕ to optimize the model f, the error of $\mathcal{R}_{nat}(f, i)$ is therefore heavily penalized and the model will give more priority to the correct prediction for the class i. In this way the model gives more priority to mitigate violated terms in Eq. (14). During this process, the

model f and Lagrangian multiplier ϕ will be alternatively updated to achieve the equilibrium until we finally reach an optimal model that satisfies the fairness constraints. Based on this traditional debiasing strategy, next we will discuss the main difference of our task in the adversarial setting from this traditional approach.

4.2 DEBIAS CLEAN ERROR AND BOUNDARY ERROR SEPARATELY

One thing to note is that in the Eq (13), the robust error is always strongly related to clean errors (Zhang et al., 2019; Tsipras et al., 2018) (see Eq. 16). Thus, during the debiasing process above, we could have twisted the influence on some class i's clean and robust errors $\mathcal{R}_{\text{nat}}(f, i)$ and $\mathcal{R}_{\text{rob}}(f, i)$. It means that when we upweight the cost for $\mathcal{R}_{\text{rob}}(f, i)$ as introduced in Eq. (15), we also implicitly upweight the cost for $\mathcal{R}_{\text{nat}}(f, i)$. Thus, we will not get a precise update for ϕ. To solve this issue, we can separate the robust error into the sum of *clean error* and *boundary error* inspired by (Zhang et al., 2019) as:

$$
\begin{aligned}
\mathcal{R}_{\text{rob}}(f, i) &= \Pr.\{\exists \delta, \text{ s.t. } f(x + \delta) \neq y | y = i\} \\
&= \Pr.\{f(x) \neq y | y = i\} + \Pr.\{\exists \delta, f(x + \delta) \cdot f(x) \leq 0 | y = i\} \\
&= \mathcal{R}_{\text{nat}}(f, i) + \mathcal{R}_{\text{bdy}}(f, i)
\end{aligned}
\tag{16}
$$

where $\mathcal{R}_{\text{bdy}}(f, i) = \Pr.\{\exists \delta, f(x + \delta) \cdot f(x) \leq 0 | y = i\}$ represents the probability that a sample from class i lies close to the decision boundary and can be attacked. By separating the clean error and boundary error during adversarial training, we are able to independently debias the unfairness from both clean error and boundary error. Formally, we have the training objective as:

$$
\begin{aligned}
\underset{f}{\text{minimize}} \quad & \mathcal{R}_{\text{nat}}(f) + \mathcal{R}_{\text{bdy}}(f) \\
\text{s.t.} \quad & \mathcal{R}_{\text{nat}}(f, i) - \mathcal{R}_{\text{nat}}(f) \leq \tau_1 \text{ and } \mathcal{R}_{\text{bdy}}(f, i) - \mathcal{R}_{\text{bdy}}(f) \leq \tau_2 \text{ for each } i \in Y
\end{aligned}
\tag{17}
$$

We introduce Lagrangian multipliers $\phi = (\phi_{\text{nat}}^i, \phi_{\text{bdy}}^i)$ and solve the max-min game for Eq. (17) similar to Eq. (15). Note that if the constraints in Eq. (17) are satisfied, the fairness quality for robust error ($\mathcal{R}_{\text{rob}}(f, i) = \mathcal{R}_{\text{nat}}(f, i) + \mathcal{R}_{\text{bdy}}(f, i)$) of each class can also be guaranteed by $\tau_1 + \tau_2$. In practice, we will use surrogate loss functions (such as cross entropy) $\mathcal{L}(f(x), y)$ and $\max_{||\delta|| \leq \epsilon} \mathcal{L}(f(x), f(x'))$ to optimize the clean and boundary errors as suggested by (Zhang et al., 2019).

4.3 COST-SENSITIVE CLASSIFICATION FOR CLEAN ERRORS VS BOUNDARY ERRORS

During the debiasing training process in Eq. (17), if one class i's clean error violates the fairness inequality: $\mathcal{R}_{\text{nat}}(f, i) - \mathcal{R}_{\text{nat}}(f) - \tau_1 > 0$, upweighting the cost for $\mathcal{R}_{\text{nat}}(f, i)$ can help penalize large $\mathcal{R}_{\text{nat}}(f, i)$ and mitigate the unfairness issue as suggested by (Agarwal et al., 2018). Note that we refer to this strategy as "Reweight". However, if the boundary error for class i: $\mathcal{R}_{\text{bdy}}(f, i) - \mathcal{R}_{\text{bdy}}(f) - \tau_2 > 0$, we claim that only upweighting its cost (or Reweight) could not succeed to fulfill the cost-sensitive classification goal in adversarial setting. Our empirical studies in Section **??** show that upweighting the boundary error for some class i cannot effectively reduce model's boundary error specifically for class i but can bring in side-effects to degrade class i's clean accuracy. It is evident from (Ding et al., 2018) that increasing the margin ϵ during adversarial training can effectively improve model's robustness against attacks under current intensity ϵ. Therefore, we hypothesize that enlarging the adversarial margin ϵ when generating adversarial examples during training specifically for the class i can improve this class's robustness and reduce the large boundary error $\mathcal{R}_{\text{bdy}}(f, i)$. In this work, we refer to this strategy as "Re-margin". Empirical study in **??** validates its effectiveness.

We present the main components and process of Fair Robust Learning (FRL) in Algorithm 1. Note that $\text{BEST}(f, \phi, \epsilon)$ denotes the adversarial training process under adjusted hyper-parameter ϕ, ϵ mentioned in Eq. (14) and we test the performance under the validation set which is denoted as $\text{EVAL}(f, \cdot)$. In Algorithm 1, in each iteration we first test our initialized or pretrained model f on the validation set to check whether it violates the unfairness constraints (step 5). Then we update Lagrangian multiplier ϕ_{nat} to reweight the clean loss for each class. We propose three strategies to update hyper-parameter to balance the boundary loss including Reweight (option 1), Remargin (option 2) and Reweight+Regmargin (option 3). We follow one of the options (step 7) for boundary loss. Finally we adversarially train the model under the updated setting by ϕ, ϵ.

5 EXPERIMENT

In this section, we will present the experimental results to validate the effectiveness of the proposed framework (FRL) for building fairly robust DNN models. We implement and compare our proposed

---

Algorithm 1 The Fair Robust Learning (FRL) Algorithm

1: **Input:** Fairness constraints specified by $\tau_1 > 0$ and $\tau_2 > 0$, test time attacking radius ϵ_0 and hyper-param update rate α_1, α_2

2: **Output:** Fairly robust neural network f

3: Randomly initialize network f or initialize network with pre-trained configuration
   Set $\phi_{\text{nat}}^i = 0$, $\phi_{\text{bdy}}^i = 0$ and $\phi = (\phi_{\text{nat}}, \phi_{\text{bdy}})$, adv. training radius $\epsilon_i = \epsilon_0$ for each $i \in \mathcal{Y}$

4: **repeat**

5: $\quad \mathcal{R}_{\text{nat}}(i, f), \mathcal{R}_{\text{bdy}}(i, f) = \text{EVAL}(f, \epsilon_0)$ $\qquad\qquad\qquad$ ▷ Test f for each class

6: $\quad \phi_{\text{nat}}^i = \phi_{\text{nat}}^i + \alpha_1 \cdot (\mathcal{R}_{\text{nat}}(i, f) - \tau_1)$ $\qquad\qquad$ ▷ Update multiplier ϕ_{nat}

7: $\quad \phi_{\text{bdy}}^i = \phi_{\text{bdy}}^i + \alpha_2 \cdot (\mathcal{R}_{\text{bdy}}(i, f) - \tau_2)$ $\qquad$ ▷ Option 1. Update multiplier ϕ_{bdy}

7: $\quad$ **or** $\phi_{\text{bdy}}^i = \phi_{\text{bdy}}^i$; $\epsilon_i = \epsilon_i \cdot \exp(\alpha_2 \cdot (\mathcal{R}_{\text{bdy}}(i, f) - \tau_2))$ $\qquad$ ▷ Option 2. Remargin

7: $\quad$ **or** $\phi_{\text{bdy}}^i = \phi_{\text{bdy}}^i + \alpha_2 \cdot (\mathcal{R}_{\text{bdy}}(i, f) - \tau_2)$;
   $\quad \epsilon_i = \epsilon_i \cdot \exp(\alpha_2 (\mathcal{R}_{\text{bdy}}(i, f) - \tau_2))$ $\qquad\qquad$ ▷ Option 3. Reweight + Remargin

8: $\quad f \leftarrow \text{BEST}(f, \phi, \epsilon)$ $\qquad\qquad$ ▷ Adv. training under hyper-param ϕ, ϵ from current f

9: **until** Model f satisfies all constraints

---

three strategies (i.e., Reweight, Remargin and Reweight+Remargin) on real-world data and discuss their possible different consequences. We also discuss the main difference of the manner of our proposed three potential debiasing strategies.

Experimental Setup & Baselines We conduct our experiments on CIFAR10 (Krizhevsky et al., 2009). For CIFAR10, we present our main results under the model architecture PreAct Residual Network (He et al., 2016). As comparison sets to show our method can improve fairness, we also present the original performance from two popular adversarial training algorithms (Madry et al., 2017; Zhang et al., 2019). Meanwhile we add a baseline debiasing method which are inherited from (Agarwal et al., 2018) (we directly apply it to reweight the cost of adversarial examples during adversarial training) as a representative to show traditional debiasing methods might not be easily applied to solve unfairness issues in adversarial setting. For each of the debiasing algorithm, we set the fairness constraints τ_1 and τ_2 be 5% and 7% respectively, for clean and boundary errors. Please refer to this link[3] for our empirical implementations.

Debiasing Performance We first check whether our proposed FRL framework can help resolve the unfairness issue in adversarial training. Refer to our goal in Eq. (13) to achieve the fairness constraints to get both balanced clean and robustness performance. We report the trained model's average *clean error* rate, *boundary error* rate and *robust error* rate (defined in Eq.(16)), as well as the worst intra-class clean, boundary and robust error rates (Table 1). Thus, for an optimal fairly robust model, we hope each of these worst intra-class errors is not too large compared to the average errors. Meanwhile, it is also necessary that one debiasing strategy should not have too much sacrifice on the model's overall clean and robustness performance. In Table 1 for CIFAR10 dataset,

Table 1: Average & worst-class clean error, boundary error and robust error for various algorithms.

	Avg. Clean	Worst Clean	Avg. Bdy.	Worst Bdy.	Avg. Rob.	Worst Rob.
PGD	17.3	40.9	39.4	54.4	56.9	82.6
TRADES($\beta = 1$)	**14.4**	27.9	43.6	62.6	58.0	83.6
TRADES($\beta = 2$)	16.9	34.9	**39.1**	56.6	**55.5**	82.2
Baseline Reweight	19.2	28.3	39.2	53.7	58.2	80.1
FRL(Reweight)	17.0	**22.5**	41.6	51.2	58.6	73.3
FRL(Remargin)	16.9	24.9	41.6	50.6	58.5	76.3
FRL(Reweight+Remargin)	18.4	24.7	40.3	**47.4**	58.7	**70.2**

we present the performance of all three versions of our proposed FRL framework. Compared to the baselines, all the FRL algorithms reduce the worst intra-class clean, boundary and robust error under different degrees. FRL (Reweight) can get the best debiasing performance to achieve minimal "worst-class" clean error, but it cannot debias boundary loss well. The method (Reweight + Remar-

---

[3] https://drive.google.com/open?id=1IjE11VpV5CGXx633Nef3McgVOoRGMK9x

gin) can be the most effective way to debias boundary error disparity and robust error disparity.Our added baseline method (Baseline Reweight) (Agarwal et al., 2018) only have minor help for clean performance fairness but cannot debias boundary error or robust error. For each debiasing method of FRL, compared to vanilla PGD and TRADES, the total average performance is only degraded by a slight margin ($1 \sim 2\%$ for clean error and $1 \sim 3\%$ for robust error), thus the debiasing method will not sacrifice too much total performance.

Compare Different Debiasing Strategies In Figure 2, we take a closer look at the behavior of different proposed debiasing strategies mentioned in Section 4.3 and test whether they can succeed in solving the constrained training problem in Eq.(17). We present the model's maximum

Figure 2: Debiasing Manner for Various FRL Options.

violation (e.g. $v(i) = \mathcal{R}_{\text{nat}}(f, i) - \mathcal{R}_{\text{nat}}(f, i) - \tau_1$) among all classes for each training epoch that hot-started from a pre-trained (adversarially) ResNet model. If $v(i) \leq 0$ for each class in $\mathcal{Y}$, each fairness constraint is satisfied. From the figure we can tell that FRL (Reweight) method cannot adequately balance the boundary error, and it always presents a trade-off relation with the clean error constraints. Introducing the *Remargin* method will facilitate to achieve fairness for boundary errors. More details (e.g. average and worst clean / robustness in training) are in Fig. 4 in Appendix A.2.

6 RELATED WORKS

6.1 ADVERSARIAL ATTACKS AND ADVERSARIAL TRAINING

The existence of adversarial attacks (Goodfellow et al., 2014) causes huge concerns when people adopt machine learning models in various application domains (Xu et al., 2019; Jin et al., 2020). As countermeasures against adversarial examples, adversarial training (robust optimization) algorithms (Madry et al., 2017; Zhang et al., 2019) directly minimize the model's risk on the input samples even it can be perturbed, so that the machine learning model is safe under adversarial attacks. They are shown to be one of the most reliable strategies to improve model safety. In our work, we study the potential risk of adversarial training from a new scope about the fairness concerns.

6.2 FAIRNESS IN MACHINE LEARNING & IMBALANCED DATASET

Fairness issues recently draw much attention from the community of machine learning. These issues can generally divided into two categorizations: (1) prediction outcome disparity: the models tend to have some unreasonable preference of prediction for some specific demographic groups (Zafar et al., 2017); and (2) prediction quality disparity: the models tend to have much lower performance on some specific groups than others (Buolamwini & Gebru, 2018). The reasons that cause these discrimination problems might come from data distribution or the learning algorithms. In our work, we are the first to propose the unfairness issue in the adversarial setting. We argue that robustly trained models are likely to have different accuracy and robustness quality among different classes, and it may be introduced by both data distribution and the adversarial training algorithm.

We also mention imbalanced data learning problem (He & Garcia, 2009; Lin et al., 2017) as one related topic of our work. Since in our work, (e.g. Figure 1), we show that the prediction performance differences are indeed existing between different classes. This phenomenon is also well-studied in imbalanced data problems or long-tail distribution learning problems (Wang et al., 2017) where some classes have much fewer training samples than others. However, in our case, we show that this unfairness problem can also happen in the balanced data, so it desires new scopes and methods for a further study.

7 CONCLUSION

In this work we first uncover one side-effect of adversarial training algorithms: it can cause serious disparity for both clean accuracy and adversarial robustness between different classes of the data. We established both theoretical understanding and empirical analysis to verify that this phenomenon can be general in reality. As a first attempt to resolve unfairness issues from adversarial training, we propose the Fair Robust Learning (FRL) framework to mitigate this issue.

REFERENCES

Alekh Agarwal, Alina Beygelzimer, Miroslav Dudík, John Langford, and Hanna Wallach. A reductions approach to fair classification. *arXiv preprint arXiv:1803.02453*, 2018.

Joy Buolamwini and Timnit Gebru. Gender shades: Intersectional accuracy disparities in commercial gender classification. In *Conference on fairness, accountability and transparency*, pp. 77–91, 2018.

Gavin Weiguang Ding, Yash Sharma, Kry Yik Chau Lui, and Ruitong Huang. Max-margin adversarial (mma) training: Direct input space margin maximization through adversarial training. *arXiv preprint arXiv:1812.02637*, 2018.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

Haibo He and Edwardo A Garcia. Learning from imbalanced data. *IEEE Transactions on knowledge and data engineering*, 21(9):1263–1284, 2009.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Wei Jin, Yaxin Li, Han Xu, Yiqi Wang, and Jiliang Tang. Adversarial attacks and defenses on graphs: A review and empirical study. *arXiv preprint arXiv:2003.00653*, 2020.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection. In *Proceedings of the IEEE international conference on computer vision*, pp. 2980–2988, 2017.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Johannes Stallkamp, Marc Schlipsing, Jan Salmen, and Christian Igel. The German Traffic Sign Recognition Benchmark: A multi-class classification competition. In *IEEE International Joint Conference on Neural Networks*, pp. 1453–1460, 2011.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Dimitris Tsipras, Shibani Santurkar, Logan Engstrom, Alexander Turner, and Aleksander Madry. Robustness may be at odds with accuracy. *arXiv preprint arXiv:1805.12152*, 2018.

Yu-Xiong Wang, Deva Ramanan, and Martial Hebert. Learning to model the tail. In *Advances in Neural Information Processing Systems*, pp. 7029–7039, 2017.

Han Xu, Yao Ma, Haochen Liu, Debayan Deb, Hui Liu, Jiliang Tang, and Anil Jain. Adversarial attacks and defenses in images, graphs and text: A review. *arXiv preprint arXiv:1909.08072*, 2019.

Muhammad Bilal Zafar, Isabel Valera, Manuel Gomez Rodriguez, and Krishna P Gummadi. Fairness beyond disparate treatment & disparate impact: Learning classification without disparate mistreatment. In *Proceedings of the 26th international conference on world wide web*, pp. 1171–1180, 2017.

Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric P Xing, Laurent El Ghaoui, and Michael I Jordan. Theoretically principled trade-off between robustness and accuracy. *arXiv preprint arXiv:1901.08573*, 2019.

A APPENDIX.

A.1 OVERALL PERFORMANCE ON MORE MODELS

Table 2: Adversarial training algorithms on CIFAR10 dataset (ResNet18 (above) and ReNet34(below)). We report the average clean accuracy and adversarial accuracy (under PGD attack by $8/255$), as well as the worst / best clean accuracy and adv. accuracy among all classes.

	Avg. Clean.	Avg. Adv.	Worst Clean	Best Clean	Worst Adv.	Best Adv.
Natural Training	93.1	0.0	87.5	97.7	0.0	0.0
PGD Adv. Training	82.7	43.1	59.1	93.6	17.4	64.9
TRADES	83.1	44.0	65.1	93.4	17.8	67.0
Natural Training	95.1	0.0	88.1	98.2	0.0	0.0
PGD Adv. Training	86.6	46.3	72.3	96.4	19.8	72.2
TRADES	85.5	56.3	67.0	95.2	27.5	79.5

A.2 THE PHENOMENON OF UNFAIR ROBUSTNESS ON GTSRB

GTSRB We also show the similar unfairness phenomenon in German Traffic Sign Recognition Benchmark (GTRSB) (Stallkamp et al., 2011), which consist of 43 classes of images from different traffic signs, with image sizes $32 \times 32 \times 3$. In this dataset we also both naturally and adversarially train a 3-Layer CNN classifier. We list the model's performance and sort the classes in the order of decreasing clean accuracy and adv. accuracy. From the Figure 3, we also see the natural training has similar clean accuracy between different classes, but adversarial training will enlarge their gap and

Figure 3: Unfairness in GTSRB

result the clean performance has a heavier tail property. In this dataset, both natural model and robust model have clear distinguished adversairal accuracy (robustness). However, adversarial training even hardly provide any robustness improvement for some classes.

	Avg. Clean.	Avg. Adv.	Worst Clean	Best Clean	Worst Adv.	Best Adv.
Natural Training	99.5	18.9	91.7	100.0	0.0	72.5
PGD Adv. Training	94.5	44.4	50.0	100.0	1.3	90.0
TRADES	91.2	47.2	35.3	100.0	3.3	92.0

Table 3: Adversarial training algorithms on GTSRB dataset (on a 3-layer CNN model). We report the average clean accuracy and adversarial accuracy (under PGD attack by $12/255$), as well as the worst / best clean accuracy and adv. accuracy among all classes.

B PROOF OF THEOREMS

B.1 PROOF OF THEOREM 1

Before proving Theorem 1, we first establish the optimal linear classifier in natural training through Lemma 1, which facilitates us to prove the clean error and robust error after natural training.

Lemma 1 (Optimal linear classifier in natural training) *For the data following the distribution in Eq. (1), the naturally trained linear classifier $f(x) = sign(w^T x + b)$ has the optimal weight that satisfy: $w_1 = w_2 = \cdots = w_m$ and $w_{m+1} = w_{m+2} = \cdots = w_{m+b}$. Moreover, their ratio satisfy $w_1 : w_{m+1} = \gamma : \eta$ and $b : w_1 = w_0 : 1$ where*

$$w_0 = A^2 \frac{K^2+1}{K^2-1} - A^2 K \sqrt{\frac{4}{(K^2-1)^2} + \frac{2\sigma^2 \log K}{A^2(K^2-1)}}.$$

Figure 4: Debiasing training process

Proof 1 (Proof of Lemma 1) *We first prove* $w_1 = w_2 = \cdots = w_m$ *and* $w_{m+1} = w_{m+2} = \cdots = w_{m+b}$ *by contradiction. We define* $G_1 = \{1, 2, \ldots, m\}$ *and* $G_2 = \{m+1, m+2, \ldots, m+d\}$. *We make the following assumption: for the optimal* w *and* b, *we assume there exist* $w_i < w_j$ *for* $i \neq j$ *and* $i, j \in G_1$. *Then we obtain the following clean error for two classes with this classifier* w

$$R(f, -1) = Pr\{ \sum_{k \neq i, k \neq j} w_k \mathcal{N}_k + b + w_i \mathcal{N}(-\gamma, \sigma_{-1}^2) + w_j \mathcal{N}(-\gamma, \sigma_{-1}^2) > 0 \} \tag{18}$$

$$R(f, +1) = Pr\{ \sum_{k \neq i, k \neq j} w_k \mathcal{N}_k + b + w_i \mathcal{N}(+\gamma, \sigma_{+1}^2) + w_j \mathcal{N}(+\gamma, \sigma_{+1}^2) < 0 \} \tag{19}$$

If we use w_j *to replace* w_i, *we obtain new errors*

$$\overline{R(f, -1)} = Pr\{ \sum_{k \neq i, k \neq j} w_k \mathcal{N}_k + b + w_j \mathcal{N}(-\gamma, \sigma_{-1}^2) + w_j \mathcal{N}(-\gamma, \sigma_{-1}^2) > 0 \} \tag{20}$$

$$\overline{R(f, +1)} = Pr\{ \sum_{k \neq i, k \neq j} w_k \mathcal{N}_k + b + w_j \mathcal{N}(+\gamma, \sigma_{+1}^2) + w_j \mathcal{N}(+\gamma, \sigma_{+1}^2) < 0 \}. \tag{21}$$

It implies $\overline{R(f, -1)} + \overline{R(f, +1)} < R(f, -1) + R(f, +1)$.

Therefore, it contradicts with the assumption we make and we conclude for an optimal linear classifier in natural training, it must satisfies $w_1 = w_2 = \cdots = w_m$. *The same argument applies to* $i, j \in G_2$ *and we conclude* $w_{m+1} = w_{m+2} = \cdots = w_{m+d}$ *similarly.*

Next, we calculate the ratio between w_1, w_{m+1}.

$$R(f) = Pr\{f(x) \neq y\} \tag{22}$$

$$= Pr\{f(x) = 1|y = -1\} \cdot Pr\{y = -1\} + Pr\{f(x) = -1|y = 1\} \cdot Pr\{y = +1\}$$

$$\propto Pr\{w^T x + b > 0|y = -1\} + Pr\{w^T x + b < 0|y = -1\}$$

$$= Pr\{\sum_{i \in G_1} w_i \mathcal{N}(-\gamma, \sigma_{-1}^2) + \sum_{j \in G_2} w_j \mathcal{N}(-\eta, \sigma_{-1}^2) + b > 0|y = -1\}$$

$$+ Pr\{\sum_{i \in G_1} w_i \mathcal{N}(+\gamma, \sigma_{+1}^2) + \sum_{j \in G_2} w_j \mathcal{N}(+\eta, \sigma_{+1}^2) + b < 0|y = +1\}$$

$$= Pr\{\mathcal{N}(0,1) < \underbrace{\frac{b - mw_1\gamma - dw_{m+1}\eta}{\sqrt{mw_1^2 + dw_{m+1}^2}\sigma}}_{Z(-1)}\} + Pr\{\mathcal{N}(0,1) < \underbrace{\frac{-b - mw_1\gamma - dw_{m+1}\eta}{\sqrt{mw_1^2 + dw_{m+1}^2}\sigma K}}_{Z(+1)} .\}$$

$$\tag{23}$$

We derive the optimal w_1 and w_{m+1} by taking $\frac{\partial R(f)}{\partial w_1} = 0$ and $\frac{\partial R(f)}{\partial w_{m+1}} = 0$:

$$\frac{\partial R(f)}{\partial w_1} = \frac{1}{\sqrt{2\pi}} \exp\left(-\frac{1}{2}(Z(-1))^2\right) \cdot \frac{\partial Z(-1)}{\partial w_1} + \frac{1}{\sqrt{2\pi}} \exp\left(-\frac{1}{2}(Z(+1))^2\right) \cdot \frac{\partial Z(+1)}{\partial w_1} = 0$$

$$\frac{\partial R(f)}{\partial w_{m+1}} = \frac{1}{\sqrt{2\pi}} \exp\left(-\frac{1}{2}(Z(-1))^2\right) \cdot \frac{\partial Z(-1)}{\partial w_{m+1}} + \frac{1}{\sqrt{2\pi}} \exp\left(-\frac{1}{2}(Z(+1))^2\right) \cdot \frac{\partial Z(+1)}{\partial w_{m+1}} = 0$$

These imply

$$\frac{\partial Z(-1)}{\partial w_1} \Big/ \frac{\partial Z(+1)}{\partial w_1} = \frac{\partial Z(-1)}{\partial w_{m+1}} \Big/ \frac{\partial Z(+1)}{\partial w_{m+1}}$$

and therefore

$$\frac{-\gamma dw_{m+1}^2 - bw_1 + d\eta w_1 w_{m+1}}{-\gamma dw_{m+1}^2 + bw_1 + d\eta w_1 w_{m+1}} = \frac{-\eta mw_1^2 - bw_2 + m\gamma w_1 w_{m+1}}{-\eta mw_1^2 + bw_{m+1} + m\gamma w_1 w_{m+1}}. \tag{24}$$

Simplifying it gives $w_1 : w_{m+1} = \eta : \gamma$.

Then, we calculate the ratio between w_1 and b. Based on the relation between w_1 and w_{m+1}, we let $w_1 = \gamma w$ and $w_{m+1} = \eta w$ for some constant w. Substitute w_1 and w_{m+1} into Eq. (23), we have

$$R(f, -1) = Pr\{\mathcal{N}(0,1) < \frac{b}{\sigma w\sqrt{w\gamma^2 + d\eta^2}} - \frac{m\gamma^2 w + d\eta^2 w}{\sigma w\sqrt{m\gamma^2 + d\eta^2}}\} \tag{25}$$

$$= Pr\{\mathcal{N}(0,1) < \frac{b}{\sigma w\sqrt{w\gamma^2 + d\eta^2}} - \frac{\sqrt{m\gamma^2 + d\eta^2}}{\sigma}\}, \tag{26}$$

$$R(f, +1) = Pr\{\mathcal{N}(0,1) < \frac{-b}{\sigma wK\sqrt{w\gamma^2 + d\eta^2}} + \frac{\sqrt{m\gamma^2 + d\eta^2}}{K\sigma}\}. \tag{27}$$

For simplicity, we denote $A = \sqrt{m\gamma^2 + d\eta^2}$ and assume $w_o = \frac{b}{w}$. We will find optimal b by letting $\frac{\partial[R(f,-1)+R(f,+1)]}{\partial w_0} = 0$. In detail, it is

$$\frac{1}{A\sigma\sqrt{2\pi}} \exp(-\frac{1}{2}(\frac{w_0}{A\sigma} - \frac{A}{\sigma})^2) - \frac{1}{KA\sigma\sqrt{2\pi}} \exp(-\frac{1}{2}(\frac{w_0}{KA\sigma} - \frac{A}{K\sigma})^2) = 0 \tag{28}$$

which gives $\frac{1}{2}(\frac{w_0}{KA\sigma} + \frac{A}{K\sigma})^2 + \frac{1}{2}(\frac{w_o}{A\sigma} - \frac{A}{\sigma})^2 = 2\log K$ and therefore we obtain

$$w_0 = A^2 \frac{K^2 + 1}{K^2 - 1} - A^2 K \sqrt{\frac{4}{(K^2 - 1)^2} + \frac{2\sigma^2 \log K}{A^2(K^2 - 1)}}.$$

Proof 2 (Proof of Theorem 1) *Substitute the optimal linear model $\{w, b\}$ in Eq. (23), we have clean errors*

$$\mathcal{R}_{nat}(f, -1) = Pr.\{\mathcal{N}(0, 1) \le Z_{nat}(f, -1)\}, \tag{29}$$

$$\mathcal{R}_{nat}(f, +1) = Pr.\{\mathcal{N}(0, 1) \le Z_{nat}(f, +1)\}, \tag{30}$$

where

$$Z_{nat}(f, -1)\} = \frac{2A}{(K^2 - 1)\sigma} - K\sqrt{\frac{4A^2}{(K^2 - 1)^2} + \frac{2\log K}{(K^2 - 1)}}, \tag{31}$$

$$Z_{nat}(f, +1)\} = \frac{-2KA}{(K^2 - 1)\sigma} + \sqrt{\frac{4A^2}{(K^2 - 1)^2\sigma^2} + \frac{2\log K}{(K^2 - 1)}}. \tag{32}$$

Substitute the optimal linear model $\{w, b\}$ into robust error in Eq. (35) and (36), we have robust errors:

$$\mathcal{R}_{rob}(f, -1) = Pr.\{\mathcal{N}(0, 1) \le Z_{nat}(f, -1) + \frac{m\gamma + d\eta}{\sqrt{m\gamma^2 + d\eta^2}} \frac{\epsilon_0}{\sigma}\}, \tag{33}$$

$$\mathcal{R}_{rob}(f, +1) = Pr.\{\mathcal{N}(0, 1) \le Z_{nat}(f, +1) + \frac{m\gamma + d\eta}{\sqrt{m\gamma^2 + d\eta^2}} \frac{\epsilon_0}{K\sigma}\}. \tag{34}$$

B.2 PROOF OF THEOREM 2

Before proving Theorem 2, we first establish the optimal linear classifier in adversarial training through Lemma 2, which facilitates us to prove the clean error and robust error after adversarial training.

Lemma 2 (Optimal linear model in adversarial training) *For the data distribution assumed in Eq. (1), the adversarially trained linear classifier $f(x) = sign(w^T x + b)$ has the optimal weight that satisfy: $w_1 = w_2 = \cdots = w_m$, $w_{m+1} = w_{m+2} = \cdots = w_{m+b} = 0$ and $b : w_1 = w_0 : 1$ where*

$$w_0 = m(\gamma - \epsilon)^2 \frac{K^2 + 1}{K^2 - 1} - m(\gamma - \epsilon)^2 K\sqrt{\frac{4}{(K^2 - 1)^2} + \frac{2\sigma^2 \log K}{m(\gamma - \epsilon)^2(K^2 - 1)}}.$$

Proof 3 (Proof of Lemma 2)

$$\begin{aligned}
R_{rob}(f, -1) &= Pr.\{\exists \|\delta\| \le \epsilon, f(x + \delta) > 0 \mid y = -1\} \\
&= Pr.\{\max_{\|\delta\| \le \epsilon} f(x + \delta) > 0 \mid y = -1\} \\
&= Pr.\{\max_{\|\delta\| \le \epsilon} \sum_{i=1}^{m} w_i(\mathcal{N}(-\gamma, \sigma_{-1}^2) + \delta_i) + \sum_{i=m+1}^{m+d} w_i(\mathcal{N}(-\eta, \sigma_{-1}^2) + \delta_i) + b > 0\}.
\end{aligned} \tag{35}$$

Similarly, we have

$$\begin{aligned}
R_{rob}(f, +1) &= Pr.\{\exists \|\delta\| \le \epsilon, f(x + \delta) < 0 | y = +1\} \\
&= Pr.\{\max_{\|\delta\| \le \epsilon} f(x + \delta) > |y = +1\} \\
&= Pr.\{\max_{\|\delta\| \le \epsilon} \left\{ \sum_{i=1}^{m} w_i(\mathcal{N}(\gamma, \sigma_{+1}^2) + \delta_i) + \sum_{i=m+1}^{m+d} w_i(\mathcal{N}(+\eta, \sigma_{+1}^2) + \delta_i) \right\} + b < 0\}.
\end{aligned} \tag{36}$$

To prove the theorem by contradiction, we first assume that for the optimal w, there exist some $w_i > 0$ where $i \in G_2 = \{m + 1, m + 2, \ldots, m + d\}$. Then

$$R_{rob}(f, -1) = Pr.\{\underbrace{\sum_{j \neq i} \max_{|\delta_j| \leq \epsilon} w_j(\mathcal{N}(\theta_j, \sigma_{-1}^2) + \delta_j) + b}_{\mathbb{A}} + \underbrace{\max_{|\delta_i| \leq \epsilon} w_i(\mathcal{N}(-\eta, \sigma_{-1}^2) + \delta_i)}_{\mathbb{B}} > 0\}. \quad (37)$$

Because $w_i > 0$, $\mathbb{B}$ is maximized when $\delta = \epsilon$. We obtain

$$R_{rob}(f, -1) = Pr.\{\mathbb{A} + w_i N(-\eta + \epsilon, \sigma_{-1}^2) > 0\} \geq Pr.\{\mathbb{A} > 0\} \quad (38)$$

So $w_i = 0$ gives a better robust error. We can also assume $w_i < 0$ and use similar contradiction to prove $w_i = 0$. Similar argument holds for $R_{rob}(f, +1)$. Therefore, we arrive at the conclusion $w_i = 0$ for all $m + 1 \leq i \leq m + d$. The calculation of w_0 is similar to the proof of Lemma 1 and we omit the proof here.

Proof 4 (Proof of Theorem 2) *Substitute the optimal linear model in Lemma 2 into Eq. (23), we obtain the clean error on the adversarially trained model:*

$$R_{nat}(f, -1) = Pr.\{N(0, 1) < \underbrace{\frac{2\sqrt{m}(\gamma - \epsilon)}{(K^2 - 1)\sigma} - K\sqrt{\frac{4m(\gamma - \epsilon)^2}{(K^2 - 1)^2\sigma^2} + \frac{2\log K}{K^2 - 1}}}_{Z_{nat}(f_{adv}, -1)}\}, \quad (39)$$

$$R_{nat}(f, +1) = Pr.\{N(0, 1) < \underbrace{-\frac{2\sqrt{m}(\gamma - \epsilon)}{(K^2 - 1)\sigma} + K\sqrt{\frac{4m(\gamma - \epsilon)^2}{(K^2 - 1)^2\sigma^2} + \frac{2\log K}{K^2 - 1}}}_{Z_{nat}(f_{adv}, +1)}\}. \quad (40)$$

Substitute the optimal linear model in Lemma 2 into Eq. (35) and (36), we obtain the robust error on the adversarially trained model:

$$\mathcal{R}_{rob}(f_{adv}, -1) = Pr.\{\mathcal{N}(0, 1) \leq Z_{nat}(f_{adv}, -1) + \sqrt{m}\frac{\epsilon_0}{\sigma}\}, \quad (41)$$

$$\mathcal{R}_{rob}(f_{adv}, +1) = Pr.\{\mathcal{N}(0, 1) \leq Z_{nat}(f_{adv}, +1) + \sqrt{m}\frac{\epsilon_0}{K\sigma}\}. \quad (42)$$

B.3 PROOF OF COROLLARY 1

Proof 5 (Proof of Corollary 1) *We try to show $R'(f, +1) - R'(f, -1) > R(f, +1) - R(f, -1)$.*

$$R'(f, +1) - R'(f, -1) = \int_{Z'(-1)}^{Z'(+1)} g(x)dx = \underbrace{g(\epsilon')}_{\mathcal{C}} \underbrace{(Z'(+1) - Z'(-1))}_{\mathcal{A}} \quad (43)$$

$$R(f, +1) - R(f, -1) = \int_{Z(-1)}^{Z(+1)} g(x)dx = \underbrace{g(\epsilon)}_{\mathcal{D}} \underbrace{(Z(+1) - Z(-1))}_{\mathcal{B}} \quad (44)$$

where $Z'(-1) \leq \epsilon' \leq Z'(+1)$ and $Z(-1) \leq \epsilon \leq Z(+1)$ according to Mean Value Theorem. Here $g(\cdot)$ is the density function of standard normal distribution.

Next, we try to show: $\frac{R'(f, +1) - R'(f, -1)}{R(f, +1) - R(f, -1)} = \frac{\mathcal{AC}}{\mathcal{BD}} > 1$. Remind that

$$Z(-1) = \frac{2\sqrt{m + d}\Theta(\gamma)}{\sigma(K^2 - 1)} - K\sqrt{\frac{4m\Theta(\gamma^2)}{(K^2 - 1)^2\sigma^2} + \frac{2\log K}{K^2 - 1}} \quad (45)$$

$$= \frac{2\Theta(\gamma)}{(K^2 - 1)\sigma}(\sqrt{m + d} - K\sqrt{m + d + q(K)}) \quad (46)$$

$$\propto (\sqrt{m + d} - K\sqrt{m + d + q(K)}), \quad (47)$$

where $q(K) = \frac{\sigma^2(K^2-1)\log K}{2\Theta(\gamma^2)}$, and similarly we have

$$Z(+1) \propto (-K\sqrt{m+d} + \sqrt{m+d+q(K)}), \tag{48}$$

$$Z'(-1) \propto (\sqrt{m} - K\sqrt{m+q(K)}), \tag{49}$$

$$Z'(+1) \propto (-K\sqrt{m} + \sqrt{m+q(K)}). \tag{50}$$

Therefore, we derive

$$\frac{\mathcal{A}}{\mathcal{B}} = \frac{Z'(+1) - Z'(-1)}{Z(+1) - Z(-1)} \tag{51}$$

$$\propto \frac{(-K\sqrt{m} + \sqrt{m+q(K)}) - (\sqrt{m} - K\sqrt{m+q(K)})}{(-K\sqrt{m} + \sqrt{m+d+q(K)}) - (\sqrt{m} - K\sqrt{m+d+q(K)})} \tag{52}$$

$$= \frac{\sqrt{m+q(K)} - \sqrt{m}}{\sqrt{m+d+q(K)} - \sqrt{m+d}} \tag{53}$$

$$= \frac{\sqrt{m+d+q(K)} + \sqrt{m+d}}{\sqrt{m+q(K)} + \sqrt{m}} \tag{54}$$

$$= \Theta((\frac{d}{m})^{\frac{1}{2}}) \tag{55}$$

and

$$\frac{\mathcal{C}}{\mathcal{D}} = \frac{g(\epsilon')}{g(\epsilon)} \tag{56}$$

where $Z'(-1) \leq \epsilon' \leq Z'(+1)$ and $Z(-1) \leq \epsilon \leq Z(+1)$

Finally,

$$\frac{\mathcal{A}\mathcal{B}}{\mathcal{C}\mathcal{D}} \geq q(K) \cdot \Theta((\frac{d}{m})^{\frac{1}{2}}) \tag{57}$$