FEW-SHOT LEARNING WITH REPRESENTATIVE GLOBAL PROTOTYPE

ABSTRACT

Few-shot learning is often challenged by low generalization performance due to the assumption that the data distribution of novel classes and base classes is similar while the model is trained only on the base classes. To mitigate the above issues, we propose a few-shot learning with representative global prototype method. Specifically, to enhance the generalization to novel classes, we propose a method to jointly train the base classes and the novel classes, using selected representative and non-representative samples to optimize representative global prototypes, respectively. Additionally, a method that organically combines the sample of base classes conditional on semantic embedding to generate new samples of novel classes with the original data is proposed to enhance the data of novel classes. Results show that this training method improves the model's ability to describe novel classes, improving the classification performance for a few shots. Intensive experiments have been conducted on two popular benchmark datasets, and the experimental results show that this method significantly improves the classification ability of few-shot learning tasks and achieves state-of-the-art performance.

1 INTRODUCTION

The advantages of deep learning depend on big data, and machines can learn effectively under the drive of big data. However, an insufficient amount of data leads to problems, such as model overfitting, which makes the model not fit well on the dataset outside the training data, showing weak generalization ability Kang et al. (2019). Thus, few-shot learning for small datasets has become a key technology to solve this type of problem. Few-shot learning (FSL) refers to the use of a small amount of labeled data per class training to make the model show higher performance, in line with the law of human learning.

Meta-learning is the basis of most of the existing FSL methods. In meta-learning, training is modeled after a test, i.e., both base and novel classes learn a task consisting of a few samples from N-way K-shot, after which knowledge is transferred from the base classes in the form of appropriate initial conditions Finn et al. (2017); Fei et al. (2020); Zhang et al. (2020), embeddings Vinyals et al. (2016); Chopra et al. (2005); Hadsell et al. (2006); Sung et al. (2018) or optimization strategies Ravi & Larochelle (2017). There is, however, a fundamental limitation to all of these approaches: the models assumed that the distribution of base class data and novel class data was similar, so they mostly learned using only base class data, which does not guarantee that they are generalizable to novel class data.

A few-shot learning method uses the transferability of knowledge to learn the ability to characterize samples from novel classes with only a few markers, while traditional machine learning and deep learning feed all classes of samples to the model at the beginning of training. Once the data distribution has low consistency, transferred knowledge is not applicable to generalize the novel class of data. Thus, learning the global representation of all class data together can alleviate the problem of model overfitting on the base classes like machine learning and deep learning. The novel class data is learned at the beginning, and the metric novel class data and the global representation strengthen the discriminative nature of the novel class samples Wang et al. (2018); Li et al. (2019). At the same time, the sample synthesis strategy of Wang et al. (2018) is used to enhance the samples of the novel classes to alleviate the sample imbalance. However, since the global prototype is optimized directly using all samples, it is not representative. Moreover, the sample generation method actually requires

Figure 1: An illustration of representative global prototype. Combining representative samples from the base class, semantic embeddings, and novel class samples allows us to generate new samples, which are then used to train a representative global prototype.

that the base classes data and the novel classes data are similarly distributed, and do not break the fundamental restrictions Wang et al. (2018). Finally, the generation process is not directly involved in sample training and cannot optimize the quality of the generated samples.

Therefore, we propose a new FSL method to solve the problem of poor generalization ability for few-shot data and sample imbalance to better describe the data of the novel class. The novel class and the selected representative and non-representative data from the base class are fed together into the network to jointly learn the representational ability of the data, and thus it is called a representative global prototype. In our view, the FSL model does not have to meet the barrier of similar distribution of the novel and base class data, and is better suited to identify novel classes when it is trained with novel class data.

In addition, to enhance the representativeness of the global prototype, we counteract the optimization loss in two steps. (1) We select "easy-to-identify" samples as representative samples in the support set, which faithfully reflect the key features of the class. Metric representative sample and representative global prototype to generate a global loss. (2) The selected non-representative samples that are partially orthogonal to the support set from the original training set as the query set, metric the representative global prototype optimized in the previous step and query set samples, and calculate the classification loss. Both of them jointly optimize the representative global prototype.

However, trying to learn the global prototype of the base and novel class requires overcoming the problem of data imbalance with sparse data in the novel class. To overcome the strong correlation between the base and novel class data distribution, we propose a new sample generation strategy. Specifically, as in Xu & Le (2022), more representative samples are selected to generate more representative features for the novel class using the CVAE Sohn et al. (2015) generative model conditional on semantic embedding. In the above operation, we obtain enhanced data strongly correlated with the novel class, with the base class as auxiliary information.

Our main contributions are summarized as follows: (1) We propose a novel jointly training strategy for few-shot learning via representative and non-representative samples to break the assumption of meta-learning. (2) We propose a sample synthesis method to enhance novel classes of data. (3) Experiments show that our method exhibits state-of-the-art performance on both miniImageNet and tieredImageNet datasets.

2 RELATED WORK

2.1 FEW-SHOT LEARNING

Few-shot learning comes into play when we only have very limited training samples. Most of the recent deep learning approaches rely on meta-learning or learning-to-learn Hochreiter et al. (2001) strategy, which improves the performance of the novel task by the provided data set and the meta knowledge extracted across tasks by a meta-learner. Specifically, the meta-learner transfers knowledge learned from many base class tasks to help few-shot learning to complete training tasks in novel classes.

Presently, representative FSL via meta-learning can be divided into three categories: fine-tune based, metric based, and optimization based. (1) The methods of the first category aim to learn suitable initialization parameters for training novel class samples in order to train a novel classifier faster and better Finn et al. (2017); Rusu et al. (2019); Nichol & Schulman (2018); Fei et al. (2020); Zhang et al. (2020). The models of the second category are learning a good metric, the core of which is to learn effective discriminative features through a kernel function. Specifically, metric learning calculates the similarity between two samples by learning an embedding module and a metric module. The samples of all classes are embedded into the vector space through the embedding module, and then a similarity score is given based on the metric module Vinyals et al. (2016); Chopra et al. (2005); Hadsell et al. (2006); Sung et al. (2018); Snell et al. (2017). The methods of the third category adapt optimizers for meta-learning scenarios by replacing general optimization methods Munkhdalai & Yu (2017); Ravi & Larochelle (2017). However, the above meta-learning based methods are all limited by one barrier: the sample distribution of the novel class and the base class are similar. Therefore, the samples of the novel class do not appear in the training phase, so the model is prone to overfitting on the base class.

2.2 GLOBAL REPRESENTATION LEARNING

A model overfitting problem can be alleviated by learning the global representation of all classes data together Li et al. (2019); Xi et al. (2022). It aims to learn a global representation for the classification of novel classes samples. Nevertheless, not all labeled samples are equally important, and non-representative samples can influence the accuracy of global representations. Model training can involve different sampled instances depending on the sampling strategy. Most mainstream work focuses on samples that affect decision boundaries, which is more common in active learning, in which training samples affecting classification are selected using different uncertainty metric Bappy et al. (2017); Li & Guo (2013); Zhao et al. (2021). In contrast, the representativeness of the data distribution is of less concern when sampling. In FSL, an approach that uses only representative samples to fit global representations is proposed by Xu & Le (2022), but it ignores the overall distribution of the data. A representative global representation is therefore proposed. To optimize the representativeness of the global representation, two loss functions are generated using representative samples and non-representative samples.

2.3 CVAE

In the past, conditional VAE has been used to model feature distributions for a variety of computer vision tasks, including image classification Kim et al. (2019); Schönfeld et al. (2019); Xing et al. (2019); Zhang et al. (2019), image generation Esser & Sutter (2018); Liu et al. (2017), image recovery Du et al. (2020), or video processing Pan et al. (2019). Essentially, VAE models are trained to learn the data distribution of the training set. As reported in Xi et al. (2022); Wang et al. (2018); Li et al. (2019) that VAE can be used to generate data for novel classes based on training fixed parameters from base classes. However, the problem is that the parameters learned using only the base class data, which are suitable for the base class to generate better data, but not necessarily for the novel class data. Therefore, the method of using CVAE Sohn et al. (2015) was proposed to combine the features of the extracted base class data conditioned on semantic embedding to generate features or images of the novel class data Xu & Le (2022). In this way, the novel class data can be generated more accurately by using common semantic embeddings as a bridge between the novel class and the base class. However, these methods are essentially still under the assumption of meta-learning. Therefore, we propose a new sample generation strategy that makes full use of the novel and base class data to synthesize new data. This does not depend on the parameters of the base class data training but also facilitates the classification of the novel class.

3 FEW-SHOT LEARNING WITH REPRESENTATIVE GLOBAL PROTOTYPE

The key idea of our model is to learn representative global prototype using the base and novel class training the representative and non-representative samples jointly. Furthermore, we employ a new sample generation strategy for novel classes to overcome the sample imbalance problem. In this section, we will first discuss these two key components before reviewing the entire process.

Figure 2: **Overview.** First, we propose a sample generation method to generate new samples of novel classes in the representative support set. Second, the representative global prototype are updated according to the similarity score of features of each class and representative global prototype, and the new representative global prototype and non-representative samples are then used to classify query images. The classification loss of query images, global loss, and generation loss are used to jointly optimize the global representations and the generation module.

3.1 PROBLEM DEFINITION

In this section, we assign data. There are a total of N classes of samples, denoted as $C_{all} = \{c_1, c_2, \cdots, c_N\}$. The class set C_{all} consists of two disjoint sets: a set of base classes C_{base} and a set of novel classes C_{novel}. Please note, the classes of training set D_{train} are from C_{all} but not C_{base}. And a test set D_{test} with samples from classes in C_{novel}. In D_{train}, the samples from the base class have enough labels but are very limited from the novel class, with only $n_{few}(n_{few} \leq 5)$ labeled samples. A total of n_s representative samples are sampled from D_{train} to form a support set to form a support set $S = \{(\mathbf{x}_i, y_i), i = 1, \cdots, n_s \times N\}$, and the non-representative samples are formed a query set $Q = \{(\mathbf{x}_k, y_k), k = 1, \cdots, n_q \times N\}$.

3.2 REPRESENTATIVE GLOBAL PROTOTYPE LEARNING

As a result of the lack of generalization ability for models trained only on base classes, a joint training strategy is proposed to learn a global prototype. Furthermore, to enhance its representativeness, only the representative support set is used to compute the global loss, while the classification loss is computed using the query set consisting of non-representative samples to compensate for the global prototype's incompleteness.

The process of training the model is divided into two steps: (1) metric the global prototype initialized by the representative data and the visual features $\mathbf{x}_j$ of the representative support set samples, and calculate the global loss. (2) Metric the new global prototype and the selected non-representative query sets orthogonal to the support set, and compute the classification loss.

Specifically, we use representativeness as a criterion for selecting samples. $S = \{\mathbf{x}_j \mid p(\mathbf{x}_j) \mid \mu_i, \Sigma_i > \epsilon\}$ is a representative set of training samples of the base class selected by the method of Xu & Le (2022), where $p(\cdot)$ is the probability density of Gaussian distribution $\mathbf{x}_j$, μ_i is the average of all vectors in class i, the covariance matrix Σ_i is the distribution of class i. A artificial threshold of ϵ is used to filter out samples with low probability. Identifies the sample easier if the sample is close to the mean vector u_i, which is its covariance Σ_i is small and its probability $p(\cdot)$ is large. For training the global loss, we selected the support set that is closest to the center vector.

A global loss is calculated by metricating the visual features of samples and all global representations of each class $\mathbf{G} = \{\mathbf{g}(i), i \subseteq C_{all}\}$, where $\mathbf{g}(i)$ is the global prototypical representation of the class i. The initialization of $\mathbf{g}(i)$ is the mean of embedding features of all the selected representative samples in S. For each visual feature x_j, the similarity vector $\mathbf{V}_j = [v_j^1, v_j^2, \cdots v_j^N]^T$ is obtained

by a metric kernel function, where the i-th element is the similarity score of class i in the embedding space:

$$v_j^i = - \|\mathbf{x}_j - \mathbf{g}(i)\|_2 \tag{1}$$

In this paper, in order to bring the global prototype closer to a representative sample, i.e.: smaller covariance, larger posterior probability and more identifiable sample, we define a loss for class i in the representative support set (called global loss).

$$\mathcal{L}_g = CE(y_j, \mathbf{V}_j) \tag{2}$$

where $CE(\cdot)$ is a cross entropy loss.

Immediately afterward, we utilize the representative global prototype as a class representative and identify non-representative samples of the query set. For classification, since the global prototype in the above step is optimized using representative samples, it may be misleading for non-representative samples. For the fitting of the distribution, using only representative samples from a multivariate Gaussian distribution in the middle of the 'bell' may not fit the correct distribution of the original global data, and non-representative samples in the tails cannot be judged. As a result, we optimize the representative global prototype in this subsection again with some of the non-representative samples.

Due to the large number of non-representative samples and the fact that we consider the most uncertain samples to be more beneficial for the classification task Settles (2009). This reduces the training cost and speeds up the training process by filtering out some samples. Inspired by the largest margin uncertainty Joshi et al. (2009), we measure the maximum and minimum probability values if a sample belongs to a certain class. Obviously, if the difference between the two is significantly larger, then the classifier has a higher degree of confidence that the sample belongs to the class. Alternatively, if the difference is small, the sample is in the tail of a Gaussian distribution and its class is harder to identify. Therefore, we implement the criterion of largest margin uncertainty to choose the samples that are most difficult to identify class affiliation as our query set.

$$Q = \{\mathbf{x}_j \mid max \{p(y_i \mid \mathbf{x}_j)\} - min \{p(y_i \mid \mathbf{x}_j)\} < \beta\} \tag{3}$$

Once the query set data has been determined, we measure representative global prototypes and non-representative samples. In order to make the representative global prototype differentiable in backward propagation, softmax is used as the normalization function. At this point, the similarity vector $\mathbf{V}_j$ is normalized to a probability distribution $\mathbf{P}_j = \left[p_j^1, p_j^2, \cdots, p_j^N\right]^T$.

The global prototypical representation of each class is then updated according to:

$$\mathbf{g}_{new}(i) = \mathbf{G}\mathbf{P}_j \tag{4}$$

where $\mathbf{G}$ is consisting of the representative global prototype before being updated.

The similarity score $\mathbf{W}_k = \left[w_k^1, w_k^2, \cdots, w_k^N\right]^T$ between the new representative global prototype and the non-representative sample $\mathbf{x}_k$ in the query set Q is defined as:

$$w_k^i = - \|\mathbf{x}_k - \mathbf{g}_{new}(i)\|_2 \tag{5}$$

A loss for the non-representative sample $\mathbf{x}_k$ in the query dataset $\mathbf{Q}$ (called classification loss) is defined as:
$$\mathcal{L}_{cla} = CE(y_k, \mathbf{W}_k) \tag{6}$$

The representative global prototype is jointly optimized by joint training of samples from the base class and the novel class by $\mathcal{L}_g$ and $\mathcal{L}_{cla}$, taking into account both the sample distribution and the classification performance. In contrast to methods using only representative samples, our approach considers the completeness of the data distribution. With a simple sample selection strategy, we reduce the amount of training data in comparison to an all-sample approach. The next step is to optimize a representative global prototype by jointly generating loss.

3.3 FEATURE GENERATION WITH CVAE

We propose a sample generation strategy to generate samples of the novel class without the assumption of meta-learning to solve the sample imbalance problem caused by limited data (few shots). Two steps are involved in the generation of features in this paper: (1) The features of the novel class are generated from original samples of the base class and semantic attributes. (2) All the features obtained in the first step and the original features of the novel class are used to synthesize new features.

Specifically, we combine the base class data and semantic embedding to generate new features by CVAE model. The selected representative samples are fed into the CVAE model to generate more representative features conditioned on the semantic embedding, the generate loss function is defined as:

$$\mathcal{L}_{CVAE} = \sum_{i=1}^{C_{base}} \sum_{\mathbf{x} \subseteq S} KL(q(\mathbf{z} \mid \mathbf{x}, \mathbf{a}^i) \parallel p(\mathbf{z} \mid \mathbf{a}^i))$$
$$- E_{q(\mathbf{z} \mid \mathbf{x}, \mathbf{a}^i)}(log p(\mathbf{x} \mid \mathbf{z}, \mathbf{a}^i)) \quad (7)$$

where $\mathbf{a}^i$ is the semantic embedding of class i. The first term is the regularization term, which aligns the variation term $q(\mathbf{z} \mid \mathbf{x}, \mathbf{a})$ to the prior distribution $p(\mathbf{z} \mid \mathbf{a})$ through the Kullback-Leibler divergence. The second term is the reconstruction loss, which aims to make the features $\mathbf{z}$ from the encoder generated by the decoder $p(\mathbf{x} \mid \mathbf{z}, \mathbf{a})$ approximate the original input features. And it is stipulated that $N(0, I)$ is the prior distribution.

Using the method on the original base class samples, we will obtain a total of k_t samples for every novel class. After that, we further synthesize new features from k_t samples of each class. To enhance the distinguish ability of the generated features $\mathbf{x}'_j$, the similarity between the features $\mathbf{x}'_j$ and the global representation $\mathbf{g}(i)$ is computed, denoted as: $\mathbf{U}_j = \left[u_j^1, u_j^2, \cdots, u_j^t\right]^T$.

$$u_j^i = - \left\| \mathbf{x}'_j - \mathbf{g}(i) \right\|_2 \quad (8)$$

Please note that only the score with the highest similarity to the novel classes are selected here.

To obtain the final enhanced feature $\hat{\mathbf{x}}_j$, normalize the similarity score $\mathbf{U}_j$ using softmax to $\mathbf{P}_{novel} = \left[p_j^1, p_j^2, \cdots, p_j^t\right]^T$, and add it as the weight of generating features $\mathbf{x}'_j$ with the original global prototype representation.

$$\hat{\mathbf{x}}_j = \mathbf{g}(i) + \mathbf{x}'_j \mathbf{P}_{novel}, i \subseteq C_{novel} \quad (9)$$

By the above operation, we obtain the enhanced data strongly related to the novel classes with the base classes as auxiliary information. Finally, the $\hat{\mathbf{x}}_j$ and $\mathbf{x}_j$ in the novel class and the base class are fed to the model to optimize the representative global prototype.

3.4 MODEL REVIEW

We divide the whole model into two parts as Figure 2: representative global prototype learning and sample generation. The base class, the novel class and the semantic embedding are utilized to jointly generate the data of the novel class. After that, the novel and base class data are jointly trained to optimize the global representation. Unlike methods of generating novel class samples Wang et al. (2018); Xu & Le (2022), our model trains representative as well as non-representative data from all classes from the beginning to accurately describe novel class data. In contrast to the joint training approach Li et al. (2019); Xi et al. (2022), we jointly generate the loss of the model and use the novel class data to further generate data that better matches the novel class distribution. As an additional step, the representative samples are trained in order to optimize the representative global prototype. The loss of the entire model is as follows:

$$\mathcal{L}_{total} = \mathcal{L}_g + \mathcal{L}_{cla} + \mathcal{L}_{CVAE} \quad (10)$$

During the test phase, the same procedure is used to predict labels for unlabeled data in C_{novel}. To increase the number of samples in the novel class, a sample generation strategy is used. Our next step is to compute the Euclidean distance between the feature vectors of the test samples and the representative global prototype in the novel class in order to conduct the nearest neighbor search.

Table 1: Few-shot classification accuracies (%) with 5-way on miniImageNet and tieredImageNet.

model	backbone	miniImageNet		tieredImageNet	
		1-shot	5-shot	1-shot	5-shot
Matching NetVinyals et al. (2016)	ResNet-12	65.64±0.20	78.72±0.15	68.50±0.92	80.60±0.71
MAMLFinn et al. (2017)	ResNet-18	64.06±0.18	80.58±0.12	-	-
SimpleShotWang et al. (2019)	ResNet-18	62.85±0.20	80.02±0.14	69.09±0.22	84.58±0.16
CANHou et al. (2019)	ResNet-12	63.85±0.48	79.44±0.34	69.89±0.51	84.23±0.37
S2M2Mangla et al. (2020)	ResNet-12	64.06±0.18	80.58±0.12	-	-
TADAMOreshkin et al. (2018)	ResNet-12	58.50±0.30	76.70±0.30	62.13±0.31	81.92±0.30
AM3Xing et al. (2019)	ResNet-12	65.30±0.49	78.10±0.36	66.22±0.75	82.79±0.48
Variational FSLZhang et al. (2019)	ResNet-12	61.23±0.26	77.69±0.17	-	-
MetaOptNetLee et al. (2019)	ResNet-12	62.64±0.61	78.63±0.46	65.99±0.72	81.56±0.53
Robust20-distillDvornik et al. (2019)	ResNet-18	63.06±0.61	80.63±0.42	65.43±0.21	70.44±0.32
MELR Fei et al. (2020)	ResNet-12	67.40±0.43	83.40±0.28	72.14±0.51	87.01±0.35
RFS Tian et al. (2020)	ResNet-12	62.02±0.63	79.64±0.44	69.74±0.72	84.41±0.55
Neg-Cosine Liu et al. (2020a)	ResNet-12	63.85±0.81	81.57±0.56	-	-
IEPTZhang et al. (2020)	ResNet-12	67.05±0.44	82.90±0.30	72.24±0.50	86.73±0.34
Meta-BaselineChen et al. (2021)	ResNet-12	63.17±0.23	79.26±0.17	68.62±0.27	83.29±0.18
ProtoNetYe et al. (2020)	ResNet-12	62.39	80.53	68.23	84.03
E3BMLiu et al. (2020b)	ResNet-12	64.09±0.37	80.29±0.25	71.34±0.41	85.82±0.29
R-SVAEXu & Le (2022)	ResNet-12	74.84±0.23	83.28±0.40	76.98±0.65	85.77±0.50
GP(Ours)	ResNet-12	75.92±0.08	84.03±0.53	79.85±0.27	87.03±0.10
RGP(Ours)	ResNet-12	**76.42±0.35**	**84.54±0.19**	**80.35±0.47**	**87.21±0.32**

4 EXPERIMENTS

In this section, we evaluate and compare our method with state-of-the-art approaches on two datasets, i.e., miniImageNet and tieredImageNet. As a first step, we explain the detail settings. Then, we compare the proposed method with several state-of-the-art few-shot approaches to prove how effective it is. The experimental results are analyzed at the end of this section.

4.1 DATASETS

miniImageNet Dataset Vinyals et al. (2016) is a lightweight subset of the large-scale dataset ImageNet. It contains a total of 60,000 color images with an image size of 84×84. The set of these images is labeled with a size of 100, so there are 600 classes in each class. The data is divided into three parts by labels. The training set contains 64 classes, the validation set contains 16 classes, and the remaining 20 classes are used as the test set.

tieredImageNet Dataset Ren et al. (2018) is also a subset of ImageNet like miniImageNet. ImageNet categories are sampled and grouped according to a hierarchical structure to separate the data into broader classes, and the image size is also 84×84. A total of 608 classes are contained in tieredImageNet, which has 34 categories containing between 10 and 30 classes. Among these, 20 categories / 351 classes make up the training set, 6 categories / 97 classes make up the validation set, and the remaining 8 categories / 160 classes make up the test set.

4.2 DETAIL SETTINGS

A feature extractor based on ResNet12 with feature representations output from the final layer was trained using data from the base class before global training was conducted. A feature extractor is then used to average the visual features of all class samples to initialize the representative global prototype. Adam acts as an optimizer to train the entire network at 10^{-4}. The dimensions of the latent space and semantic vector are both set to 512. Our semantic embeddings are extracted from CLIP Radford et al. (2021). We use the same feature extractor on images in the support and query sets. During our experiments, ϵ was set to 0.9 and β was set to 0.1.

Figure 3: **Feature Visualization.** We visualize the features of the original and generated data. The transparent points are the generated features and the non-transparent points are the original features. (a): the support set features. (b): the query set features. (c): the generated features by CVAE. (d): the generated features by ours.

Figure 4: Some examples for representative samples (left) and non-representative samples (right) from miniImageNet.

4.3 RESULTS

We compare with state-of-the-art few-shot learning methods, among them, our method is most related to Xu & Le (2022). To be fair, all methods use feature extractors with a similar number of layers, namely: ResNet12 and ResNet18. In the remainder of the paper, we denote the method of training a global prototype using all data as **GP** and the training model with the selected representative and non-representative data as **RGP**.

We show in Table 1 the classification results for the 5-way k-shot (k = 1 or 5) on the dataset. The results show that our method outperforms state-of-the-art methods. Furthermore, not only did the use of selected representative samples and non-representative partial samples not degrade the classification performance of the model, but the RGP showed a slight improvement in performance compared to the GP using full training. For example, the representative approach, outperformed the GP by 0.5% in 1-shot classification on miniImageNet. Another interesting finding is that 5-shot is not as good as 1-shot for classification. RGP outperforms previous state-of-the-art methods by $1.18 \sim 3.34\%$ for 1-shot and $0.2 \sim 1.14\%$ for 5-shot.

4.4 VISUALIZATION

During training, Figure 3 illustrates the process of generating data with different methods using tieredImageNet datasets. Each of the four images in Figure 3 depicts the features of three novel classes, which are mapped to 2-d space using t-SNE Van der Maaten & Hinton (2008). Figure 3 (d) illustrates the rationality and effectiveness of our synthesis strategy since the features generated by our method are closer to the real features than CVAE alone as shown in Figure 3 (c).

Depending on different selection criteria, we visualized representative and non-representative samples as shown in Figure 4. The representative samples are closer to the center of the distribution and are therefore assigned a higher probability and contain the main clean features so that they are more easily identified. The non-representative samples are selected at the tail of the distribution

Table 2: 1-shot classification accuracies (%) with different generation methods on miniImageNet and tieredImageNet.

model	miniImageNet	tieredImageNet
VAE	73.62±0.41	75.64±0.37
CVAE	75.18±0.64	78.38±0.25
RGP	**76.42±0.35**	**80.35±0.47**

and therefore have a lower probability of being assigned and may contain features related to other categories and therefore be misclassified or not easily identified.

4.5 ABLATION STUDY

Our main experiments involve synthesizing samples in three parts. We compare synthesis strategies that use only one step separately to our approach in the ablation experiments: CVAE generation with semantic embedding as a condition Xu & Le (2022) and VAE generation with Wang et al. (2018).

As shown in Table 2, the 1-shot performance in different sample generation strategies on miniImageNet and tieredImageNet datasets. We can see that the VAE-based approach fixes the parameters obtained by training the base class, which is less effective than using CVAE that span different distributions in terms of semantic embeddings. Finally, the classification performance of both is inferior to our proposed approach which does not rely on the assumption of similar distributions.

5 CONCLUSION

A new few-shot learning with representative global prototype framework is proposed to alleviate the problem of poor generalization ability. In order to obtain a representative global prototype with strong generalization ability on the performance of the novel class, a joint training strategy is proposed, which trains both the base class and the novel class on representative and non-representative data. Second, to alleviate the problem of sample imbalance in joint training, a sample synthesis strategy that combines base classes and novel classes conditioned on semantic embeddings is proposed, which is not restricted to the strong assumption of meta-learning. As a final step, three loss functions are combined to train the entire model. Experimental results show that our method outperforms existing few-shot methods. In the future, we will explore the impact of different sample selection methods on model classification performance.

REFERENCES

Jawadul H. Bappy, Sujoy Paul, Ertem Tuncel, and Amit K. Roy-Chowdhury. The impact of typicality for informative representative selection. In *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 771–780, 2017.

Yinbo Chen, Zhuang Liu, Huijuan Xu, Trevor Darrell, and Xiaolong Wang. Meta-baseline: Exploring simple meta-learning for few-shot learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 9062–9071, 2021.

S. Chopra, R. Hadsell, and Y. LeCun. Learning a similarity metric discriminatively, with application to face verification. In *2005 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'05)*, pp. 539–546, 2005.

Yingjun Du, Jun Xu, Xiantong Zhen, Ming-Ming Cheng, and Ling Shao. Conditional variational image deraining. *IEEE Transactions on Image Processing*, pp. 6288–6301, 2020.

Nikita Dvornik, Cordelia Schmid, and Julien Mairal. Diversity with cooperation: Ensemble methods for few-shot classification. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 3723–3731, 2019.

Patrick Esser and Ekaterina Sutter. A variational u-net for conditional appearance and shape generation. In *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8857–8866, 2018.

Nanyi Fei, Zhiwu Lu, Tao Xiang, and Songfang Huang. Melr: Meta-learning via modeling episode-level relationships for few-shot learning. In *International Conference on Learning Representations*, 2020.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International conference on machine learning*, pp. 1126–1135, 2017.

R. Hadsell, S. Chopra, and Y. LeCun. Dimensionality reduction by learning an invariant mapping. In *2006 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'06)*, pp. 1735–1742, 2006.

Sepp Hochreiter, A. Steven Younger, and Peter R. Conwell. Learning to learn using gradient descent. In *Artificial Neural Networks — ICANN 2001*, pp. 87–94, 2001.

Ruibing Hou, Hong Chang, Bingpeng Ma, Shiguang Shan, and Xilin Chen. Cross attention network for few-shot classification. *Advances in Neural Information Processing Systems*, 32, 2019.

Ajay J. Joshi, Fatih Porikli, and Nikolaos Papanikolopoulos. Multi-class active learning for image classification. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2372–2379, 2009.

Bingyi Kang, Zhuang Liu, Xin Wang, Fisher Yu, Jiashi Feng, and Trevor Darrell. Few-shot object detection via feature reweighting. In *2019 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 8419–8428, 2019.

Junsik Kim, Tae-Hyun Oh, Seokju Lee, Fei Pan, and In So Kweon. Variational prototyping-encoder: One-shot learning with prototypical images. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 9454–9462, 2019.

Kwonjoon Lee, Subhransu Maji, Avinash Ravichandran, and Stefano Soatto. Meta-learning with differentiable convex optimization. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 10649–10657, 2019.

Aoxue Li, Tiange Luo, Tao Xiang, Weiran Huang, and Liwei Wang. Few-shot learning with global class representations. In *2019 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 9714–9723, 2019.

Xin Li and Yuhong Guo. Adaptive active learning for image classification. In *2013 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 859–866, 2013.

Bin Liu, Yue Cao, Yutong Lin, Qi Li, Zheng Zhang, Mingsheng Long, and Han Hu. Negative margin matters: Understanding margin in few-shot classification. In *European conference on computer vision*, pp. 438–455, 2020a.

Ming-Yu Liu, Thomas Breuel, and Jan Kautz. Unsupervised image-to-image translation networks. *Advances in neural information processing systems*, 2017.

Yaoyao Liu, Bernt Schiele, and Qianru Sun. An ensemble of epoch-wise empirical bayes for few-shot learning. In *European Conference on Computer Vision*, pp. 404–421, 2020b.

Puneet Mangla, Nupur Kumari, Abhishek Sinha, Mayank Singh, Balaji Krishnamurthy, and Vineeth N Balasubramanian. Charting the right manifold: Manifold mixup for few-shot learning. In *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, pp. 2218–2227, 2020.

Tsendsuren Munkhdalai and Hong Yu. Meta networks. In *International Conference on Machine Learning*, pp. 2554–2563, 2017.

Alex Nichol and John Schulman. Reptile: a scalable metalearning algorithm. *arXiv preprint arXiv:1803.02999*, pp. 4, 2018.

Boris Oreshkin, Pau Rodríguez López, and Alexandre Lacoste. Tadam: Task dependent adaptive metric for improved few-shot learning. *Advances in neural information processing systems*, pp. 721–731, 2018.

Junting Pan, Chengyu Wang, Xu Jia, Jing Shao, Lu Sheng, Junjie Yan, and Xiaogang Wang. Video generation from single semantic label map. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 3728–3737, 2019.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pp. 8748–8763, 2021.

Sachin Ravi and Hugo Larochelle. Optimization as a model for few-shot learning. In *International Conference on Learning Representations*, 2017.

Mengye Ren, Eleni Triantafillou, Sachin Ravi, Jake Snell, Kevin Swersky, Joshua B Tenenbaum, Hugo Larochelle, and Richard S Zemel. Meta-learning for semi-supervised few-shot classification. *International Conference on Learning Representations*, 2018.

Andrei A. Rusu, Dushyant Rao, Jakub Sygnowski, Oriol Vinyals, Razvan Pascanu, Simon Osindero, and Raia Hadsell. Meta-learning with latent embedding optimization. In *International Conference on Learning Representations*, 2019.

Edgar Schönfeld, Sayna Ebrahimi, Samarth Sinha, Trevor Darrell, and Zeynep Akata. Generalized zero- and few-shot learning via aligned variational autoencoders. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 8239–8247, 2019.

Burr Settles. Active learning literature survey. 2009.

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. *Advances in neural information processing systems*, pp. 4077–4087, 2017.

Kihyuk Sohn, Honglak Lee, and Xinchen Yan. Learning structured output representation using deep conditional generative models. *Advances in neural information processing systems*, 2015.

Flood Sung, Yongxin Yang, Li Zhang, Tao Xiang, Philip H.S. Torr, and Timothy M. Hospedales. Learning to compare: Relation network for few-shot learning. In *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 1199–1208, 2018.

Yonglong Tian, Yue Wang, Dilip Krishnan, Joshua B Tenenbaum, and Phillip Isola. Rethinking few-shot image classification: a good embedding is all you need? In *European Conference on Computer Vision*, pp. 266–282, 2020.

Laurens Van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 2008.

Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Daan Wierstra, et al. Matching networks for one shot learning. *Advances in neural information processing systems*, pp. 3630–3638, 2016.

Yan Wang, Wei-Lun Chao, Kilian Q Weinberger, and Laurens van der Maaten. Simpleshot: Revisiting nearest-neighbor classification for few-shot learning. *arXiv preprint arXiv:1911.04623*, 2019.

Yu-Xiong Wang, Ross Girshick, Martial Hebert, and Bharath Hariharan. Low-shot learning from imaginary data. In *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 7278–7286, 2018.

Bobo Xi, Jiaojiao Li, Yunsong Li, Rui Song, Danfeng Hong, and Jocelyn Chanussot. Few-shot learning with class-covariance metric for hyperspectral image classification. *IEEE Transactions on Image Processing*, pp. 5079–5092, 2022.

Chen Xing, Negar Rostamzadeh, Boris Oreshkin, and Pedro O O Pinheiro. Adaptive cross-modal few-shot learning. *Advances in Neural Information Processing Systems*, 2019.

Jingyi Xu and Hieu Le. Generating representative samples for few-shot classification. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9003–9013, 2022.

Han-Jia Ye, Hexiang Hu, De-Chuan Zhan, and Fei Sha. Few-shot learning via embedding adaptation with set-to-set functions. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8808–8817, 2020.

Jian Zhang, Chenglong Zhao, Bingbing Ni, Minghao Xu, and Xiaokang Yang. Variational few-shot learning. In *2019 IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 1685–1694, 2019.

Manli Zhang, Jianhong Zhang, Zhiwu Lu, Tao Xiang, Mingyu Ding, and Songfang Huang. Iept: Instance-level and episode-level pretext tasks for few-shot learning. In *International Conference on Learning Representations*, 2020.

Guang Zhao, Edward Dougherty, Byung-Jun Yoon, Francis Alexander, and Xiaoning Qian. Uncertainty-aware active learning for optimal bayesian classifier. In *International Conference on Learning Representations (ICLR 2021)*, 2021.