DECOUPLING CONCEPT BOTTLENECK MODEL

ABSTRACT

Concept Bottleneck Model (CBM) is a kind of powerful interpretable neural network, which utilizes high-level concepts to explain model decisions and interact with humans. However, CBM cannot always work as expected due to the troublesome collection and commonplace insufficiency of high-level concepts in real-world scenarios. In this paper, we theoretically reveal that insufficient concept information will induce the mixture of explicit and implicit information, which further leads to the inherent dilemma of concept and label distortions in CBM. Motivated by the proposed theorem, we present Decoupling Concept Bottleneck Model (DCBM), a novel concept-based model decoupling heterogeneous information into explicit and implicit concepts, while still retaining high prediction performance and interpretability. Extensive experiments expose the success in the alleviation of concept/label distortions, where DCBM achieves state-of-the-art performances in both concept and label learning tasks. Especially for situations where concepts are insufficient, DCBM significantly outperforms other models based on concept bottleneck and respectively achieves error rates 24.95% and 20.09% lower than other CBMs on concept/label prediction. Moreover, to express effective human-machine interactions for DCBM, we devise two algorithms based on mutual information (MI) estimation, including forward intervention and backward rectification, which can automatically correct labels and trace back to wrong concepts. The construction of the interaction regime can be formulated as a light min-max optimization problem achieved within minutes. Multiple experiments show that such interactions can effectively promote concept/label accuracy.

1 INTRODUCTION

Concept Bottleneck Model (CBM) (Koh et al., 2020; Losch et al., 2021) is an interactive and interpretable AI system, which encodes the prior expert knowledge into the neural network and makes decisions according to corresponding concepts. In detail, CBM firstly maps input images into corresponding high-level concepts, and then utilizes these concepts for downstream tasks. Moreover, CBM gives the ante-hoc explanations for the model's predictions due to its end-to-end training regimes and has been widely applied to healthcare (Chen et al., 2021; Rong et al., 2022), shift detection (Wijaya et al., 2021), algorithmic reasoning (Xuanyuan et al., 2022), and so on.

However, high-level concepts in real-world scenarios often suffer a troublesome collection and commonplace insufficiency due to the consumption of large amounts of resources. Thus, the concept information is usually not sufficient

Figure 1: Concept/label distortions in CBM. (a) is the main pipeline in CBM. (b) CBM expects an ideal case with all explicit concepts. (c) Heterogeneous concepts in real-world scenarios. (d) Thus, CBM has to mix explicit/implicit concepts to achieve both concept/label learning.

to recover label information. In this circumstance, CBM cannot fit the ground-truth labels only according to the clean but insufficient concepts. On the contrary, to learn a better classifier, CBM

Figure 2: Two human-machine interactive tasks in DCBM. *Forward Intervention:* correcting labels according to the more accurate concepts given by human; *Backward Rectification:* tracking back to wrong concepts according to the labels updated by human.

has to inject extra information into the concept layer, i.e., sacrifice the concept accuracy (Fig. 1). Inspired by such observations, we theoretically reveal that CBM cannot avoid the inherent trade-off between concept and label distortions due to the mixture of explicit/implicit information.

Motivated by the theoretical results, we propose Decoupling Concept Bottleneck Model (DCBM), a novel concept-based model, to decouple the heterogeneous information into explicit and implicit concepts. In detail, DCBM automatically allocates the implicit concepts to auxiliary neurons, as such the pollution of explicit concepts can be avoided. Furthermore, DCBM maximizes the interpretability of the models via the Jensen-Shannon (JS) divergence constraint during training.

Equipped with the proposed model, we aim to conduct corresponding human-machine interactive tasks via DCBM, regarded as one of the most important components for such concept-based models. However, the design of interaction algorithms for DCBM is not straightforward due to the correlation between explicit and implicit concepts. To this end, we propose a phase-two decoupling algorithm for DCBM to peel out the explicit information via mutual information (MI) estimation (Belghazi et al., 2018). The phase-two decoupling algorithm can be reduced to a light min-max optimization problem solved in minutes. After the phase-two decoupling stage, we consider two interaction tasks, including forward intervention and backward rectification, which can correct labels and trace back to wrong concepts automatically via human-machine interaction (Fig. 2).

In summary, we make the following contributions:

• To our best knowledge, we are the first to theoretically reveal and prove the existence of inherent concept/label distortions in CBM for the situation where high-level concepts are insufficient.

• Motivated by the theoretical results, we propose Decoupling Concept Bottleneck Model (DCBM), a novel concept-based framework, to alleviate the distortions by automatically decoupling the concepts into explicit and implicit ones during the training process.

• Extensive experiments show that DCBM achieves state-of-the-art results in both concept and label learning tasks. In particular, compared with other concept-based models, the concept/label distortions can be alleviated conspicuously for DCBM with inadequate concepts.

• We devise a novel comprehensive human-machine system, which can automatically correct labels and ascertain wrong concepts via feedback from human experts. The system is designed to decouple heterogeneous information by solving a light MI-based min-max optimization problem within minutes. Multiple experiments show the system's effectiveness in promoting concept/label accuracy.

2 RELATED WORKS

Concepts bottleneck models (Koh et al., 2020; Kazhdan et al., 2020; Losch et al., 2021) extract the high-level expert knowledge from data and utilize them for downstream tasks, which aim to make the AI system more interpretable and interactive. On the one hand, post-hoc CBMs (Kazhdan et al., 2020; Yuksekgonul et al., 2022; Bai et al., 2022) generate the concept explanations from the pre-trained model, which has no access to concepts during training process. However, such methods cannot guarantee that the information of concepts can be recovered from the hidden layers of the pre-trained networks (Kazhdan et al., 2021). On the other hand, ante-hoc CBMs (Koh et al., 2020)

learn the given concepts during training process to obtain informative embedding. However, several works (Kazhdan et al., 2021; Yuksekgonul et al., 2022) point out that ante-hoc CBMs suffer the catastrophic label distortion with insufficient high-level concepts. In this paper, we focus on ante-hoc CBMs and look more closely at the situations with insufficient concepts. Instead of pointing out the label distortions empirically (Kawahara et al., 2018; Yuksekgonul et al., 2022), we reveal the inherent concept/label trade-off for CBM with insufficient concepts theoretically. Furthermore, we propose DCBM to alleviate this trade-off via decoupling the heterogeneous information.

Several methods also aim to generate high-level synthetic concepts automatically during the training process (Bau et al., 2017; Kim et al., 2018; Zhou et al., 2018; Yeh et al., 2020; Parekh et al., 2021; Sarkar et al., 2022). These methods do not require explicit domain knowledge, and can give explainable patterns which are responsible for the model's predictions. However, such methods are not interactive due to the synthetic concepts. In this paper, we utilize the expert knowledge as the concepts directly and aim to design interactive AI system.

3 THEORETICAL RESULTS

We firstly introduce Concept Bottleneck Model (CBM) (Koh et al., 2020), and then present the dilemma of concept/label distortions in CBM theoretically when the concepts are insufficient.

3.1 CONCEPT BOTTLENECK MODEL (CBM)

Given N training triples $\{\boldsymbol{x}_n, \boldsymbol{c}_n, \boldsymbol{y}_n\}_{n=1}^N$, where $\boldsymbol{x}_n \in \mathbb{R}^D$, $\boldsymbol{c}_n \in \mathbb{R}^d$, $\boldsymbol{y}_n \in \mathbb{R}^k$ respectively indicate input, concept, and label vector. With $g : \mathbb{R}^D \to \mathbb{R}^d$ mapping from input space into concept space and $f : \mathbb{R}^d \to \mathbb{R}^k$ mapping from concept space into label space, CBM defines two loss functions, i.e., $\mathcal{L}_Y$ and $\mathcal{L}_C$, which measure the difference between the ground-truth labels (concepts) and the predicted ones, respectively. Note that CBM utilizes the supervision of concepts during training while having no access to them at test time. Specifically, CBM devises three constructions to learn the functions g and f, i.e., *Independent*, *Sequential*, and *Joint* models as follows:

1. *Independent* CBM learns f and g independently: $\hat{g} = \arg\min_g \sum_{n=1}^N \mathcal{L}_C[g(\boldsymbol{x}_n), \boldsymbol{c}_n]$, $\hat{f} = \arg\min_f \sum_{n=1}^N \mathcal{L}_Y[f(\boldsymbol{c}_n), \boldsymbol{y}_n]$. Note that f is trained with the ground-truth concept $\boldsymbol{c}$, while using $\hat{g}(\boldsymbol{x}_n)$ as input at test time.

2. *Sequential* CBM learns g in the same way as *Independent* CMB, but uses $\hat{g}(\boldsymbol{x}_n)$ to learn $\hat{f}$, i.e., $\hat{f} = \arg\min_f \sum_{n=1}^N \mathcal{L}_Y[f \circ \hat{g}(\boldsymbol{x}_n), \boldsymbol{y}_n]$.

3. *Joint* CBM learns g and f jointly via a hyperparameter α to control the weight of two parts, namely $\hat{g}, \hat{f} = \arg\min_{g,f} \sum_{n=1}^N \{\mathcal{L}_Y[f \circ g(\boldsymbol{x}_n), \boldsymbol{y}_n] + \alpha \mathcal{L}_C[g(\boldsymbol{x}_n), \boldsymbol{c}_n]\}$.

3.2 MAIN THEOREM

We state a simplified version of our main theorem in this section. The full version and its corresponding proof can be seen in Appendix B.

Theorem 1 (Informal). *Consider a dataset $\{\boldsymbol{x}_n, \boldsymbol{c}'_n, \boldsymbol{y}_n\}_{n=1}^N$ generated from the regime $\mathcal{X} \to \mathcal{C} \to \mathcal{Y}$ with insufficient concept information. Let d_1 (d_2) denote the number of known (missing) concepts, and $\mathcal{E}_Y$ ($\mathcal{E}_C$) denote the label (concept) error. Then, the following inequation holds for Joint CBM with high probability:*

$$\mathcal{E}_Y \geq \Phi(d_1, d_2) - 2\gamma \mathcal{E}_C, \tag{1}$$

where $\gamma \in \mathbb{R}^+$, and $\Phi(d_1, d_2) \in \mathbb{R}^+$ increases (decreases) with d_2 (d_1), respectively.

The analysis of the main theorem consists of two steps: (1) analyzing the relationship between the number of missing concepts and the label error for *Sequential* CBM; (2) revealing the trade-off between concept and label error for *Joint* CBM via the perturbation theory of least square problem (Higham, 2002). Theorem 1 reveals the following two important properties of CBM. On the one hand, $\Phi(d_1, d_2)$ increases with the number of missing concepts d_2, thus the concept and label error of CBM will increase with d_2 in general. On the other hand, the lower bound in Theorem 1 reveals the inherent trade-off between concept error ($\mathcal{E}_C$) and the label error ($\mathcal{E}_Y$).

Figure 3: Pipeline of the proposed DCBM. 'Exp-Outputs' and 'Imp-Outputs' represent the outputs of explicit and implicit concepts, respectively. We jointly consider three objectives, including a) Label prediction, to optimize the label accuracy; b) Concept prediction, to optimize the concept accuracy; c) JS Divergence, to force the model to make predictions according to explicit concepts. As such, the issue of forcible concept/label distortions in CBM can be automatically alleviated.

4 METHODOLOGY

Based on the above theorem, we argue that CBM suffers from concept/label distortions. Thus, we embark on devising a Decoupled Concept Bottleneck Model (DCBM) to relieve such distortions.

4.1 DECOUPLING CONCEPT BOTTLENECK MODEL

According to the Theorem 1 and its proof, the main reason for concept/label distortions under insufficient concepts in CBM is the mixture of explicit/implicit information. To decouple the aforementioned heterogeneous information, we devise an extra mapping $\tilde{f} \circ \tilde{g}$ to store the implicit information in the concept layer of previous CBM (Fig. 3). We consider two loss functions:

$$\mathcal{L}_1 = \sum_{n=1}^{N} \mathcal{L}_Y\big[(f \circ g + \tilde{f} \circ \tilde{g})(\boldsymbol{x}_n), \boldsymbol{y}_n\big], \quad \mathcal{L}_2 = \sum_{n=1}^{N} \mathcal{L}_C\big[g(\boldsymbol{x}_n), \boldsymbol{c}_n\big], \quad (2)$$

where $\tilde{g} : \mathbb{R}^D \to \mathbb{R}^{\tilde{d}}$ maps $\boldsymbol{x}_n$ into implicit concept space and $\tilde{f} : \mathbb{R}^{\tilde{d}} \to \mathbb{R}^k$ maps implicit concept values into the label space.

However, such designed loss functions cannot always protect the model's interpretability, since the predicted label might mainly depend on $\tilde{f} \circ \tilde{g}$ regardless of $f \circ g$. To ensure the model interpretability, we add an auxiliary JS Divergence constraint as follows to force the model to make decisions according to the explicit concepts as far as possible:

$$\mathcal{L}_3 = \sum_{n=1}^{N} \text{JS}\big[(f \circ g + \tilde{f} \circ \tilde{g})(\boldsymbol{x}_n) \,\|\, f \circ g(\boldsymbol{x}_n)\big], \quad (3)$$

where $\text{JS}(\text{p} \,\|\, \text{q}) = \text{KL}\big[\text{p} \,\|\, \frac{1}{2}(\text{p} + \text{q})\big] + \text{KL}\big[\text{q} \,\|\, \frac{1}{2}(\text{p} + \text{q})\big]$ is a symmetrization of Kullback–Leibler (KL) Divergence, for some random variables p, q. The overall loss function is indicated as $\mathcal{L}_{\text{DCBM}} = \mathcal{L}_1 + \alpha \cdot \mathcal{L}_2 + \beta \cdot \mathcal{L}_3$, where α and β are hyperparameters to control the weight of different objectives. Note that the classification accuracy of explicit parts, i.e., $f \circ g$, can be guaranteed by appropriate β, while the DCBM converges to CBM when β tends to ∞. However, β is not that the higher the better, and we further analyze the choice of β in Sec. 5.4.

4.2 THE PROPOSED PHASE-TWO DECOUPLING ALGORITHM

In this section, we consider two human-machine interaction tasks for DCBM, including forward intervention and backward rectification (Fig. 2). In detail, after DCBM makes decision $\hat{\boldsymbol{y}}$ according to the corresponding concepts $\hat{\boldsymbol{c}}$, the above two tasks can be formulated as follows.

Figure 4: Forward intervention and backward rectification as devised in DCBM. Based on MI estimation, implicit concept values are decoupled into two parts, i.e., simulated explicit concepts and residual, to extract the information of explicit concepts from implicit ones. In forward intervention, we both intervene explicit concepts and simulated explicit concepts through ground-truth explicit concepts, to promote the label prediction accuracy. In the process of backward rectification, DCBM can automatically trace back to the cause through a light optimization task.

Forward Intervention. Human experts check the learned concepts $\hat{c}$ for DCBM, and correct them to the right concepts c^*. Then, how would the model update its decision according to the more accurate concepts c^*?

Backward Rectification. Human experts check the learned labels $\hat{y}$ for DCBM, and tell the model that the right labels should be y^*. Then, how would the model trace back to wrong concepts according to the more accurate labels y^* given by human experts?

The first task is proposed in (Koh et al., 2020) for the first time, and the backward rectification task is mentioned first in this paper. Despite being equipped with clear definitions, the algorithm designed for these tasks is not straightforward due to the correlation between explicit and implicit concept values. To this end, we propose a phase-two decoupling algorithm which separates the explicit/implicit concepts in the implicit layer via MI-based min-max optimization.

To begin with, we decouple the information of explicit concept values $\hat{c} \in \mathbb{R}^{d_1}$ from the implicit ones $\tilde{c} \in \mathbb{R}^{\tilde{d}}$. Specifically, we assume the implicit concept values $\tilde{c}$ can be divided into the sum of the following two parts: (1) simulated explicit concepts, i.e., the information of explicit concepts, which can be represented as the output of a decouple function $f_{\text{DEC}} : \mathbb{R}^{d_1} \to \mathbb{R}^{\tilde{d}}$, i.e., $f_{\text{DEC}}(\hat{c}) \in \mathbb{R}^{\tilde{d}}$; (2) the residual, i.e., $\tilde{c} - f_{\text{DEC}}(\hat{c})$. Then, we utilize a neural network to approximate f_{DEC} which aims to minimize the MI between the decouple term $f_{\text{DEC}}(\hat{c})$ and the residual term $\tilde{c} - f_{\text{DEC}}(\hat{c})$, i.e., consider the following optimization problem:

$$\min_{f_{\text{DEC}}} \text{MI}(\hat{c}; \tilde{c} - f_{\text{DEC}}(\hat{c})) + \eta \|f_{\text{DEC}}(\hat{c})\|_2^2, \tag{4}$$

where η is a hyperparameter to control the energy of the decoupling parts. However, the above optimization problem cannot be solved directly due to the challenge of MI estimation in high dimension. To combat this, we borrow the tool from MI neural estimation(Belghazi et al., 2018), and consider the following min-max optimization:

$$\min_{f_{\text{DEC}}} \max_{f_{\text{MI}}} \mathbb{E}\left[f_{\text{MI}}\left(\hat{c}; \tilde{c} - f_{\text{DEC}}(\hat{c})\right)\right] - \log \mathbb{E}[\exp\left\{f_{\text{MI}}(\hat{c}; \tilde{c} - f_{\text{DEC}}(\hat{c}))\right\}] + \eta \|f_{\text{DEC}}(\hat{c})\|_2^2, \tag{5}$$

where $f_{\text{MI}} : \mathbb{R}^{d_1 + \tilde{d}} \to \mathbb{R}$ is an auxiliary network for the MI estimation. Equipped with the pre-trained decoupling neural network f_{DEC}, it is convenient to conduct the above two interaction tasks.

For forward intervention, we only need to replace the predicted concepts $\hat{c}$ by expert concepts c^* in the explicit concepts layer and the input of decoupling network f_{DEC}, respectively. For backward rectification, we solve the following light optimization problem and update the concept c_{new}:

$$\min_{c_{\text{new}}} \mathcal{L}_Y \left[f(c_{\text{new}}) + \tilde{f}(\tilde{c} + f_{\text{DEC}}(c_{\text{new}}) - f_{\text{DEC}}(\hat{c})), y^* \right]. \tag{6}$$

The detailed description of the algorithm can be found in Appendix A.

5 Experiments: Concept/Label Learning

Referring to (Koh et al., 2020; Yuksekgonul et al., 2022), we perform experiments on two real-world benchmark datasets, including CUB (Wah et al., 2011) and Derm7pt (Kawahara et al., 2018), to show whether the concept/label distortions can be effectively relieved. Meanwhile, experiments on three variants of CUB are performed to show the existed concept/label distortions that CBM is suffering. We summarize the datasets in Table 1 and the detailed introduction in Appendix C.1. Furthermore, we must claim that DCBM can do more than just promoting the prediction results. As an interpretable model, DCBM performs visible process of forward intervention and backward rectification, which we will further explore in Sec. 6. Each experiment is repeated three times with mean and standard deviation reported in line with (Koh et al., 2020), and is preformed on a machine with AMD EPYC 7742 64-Core Processor CPU, NVIDIA A100-SXM4-80GB GPU, and 1T RAM. All experiments in this paper are implemented by Pytorch (Paszke et al., 2019). **The source code will be made publicly available for reproduction requirements.**

Table 1: Brief summary of the datasets. Here, # means 'the number of'. Note that the splitting of train-test-validation is in line with (Koh et al., 2020; Kawahara et al., 2018).

DATASET	#CONCEPT	#CLASS	#TRAIN	#VAL	#TEST
CUB (Wah et al., 2011)	112				
CUB%50	56				
CUB%20	22	200	4796	1198	5794
CUB%10	11				
Derm7pt (Kawahara et al., 2018)	8	2	688	322	636

5.1 Concept/Label Distortions in CBM

We show that there indeed exists a forcible concept/label distortions in CBM obviously, no matter it is an *Independent*, *Sequential*, or *Joint* model. Take CUB dataset for example, we execute concept and label learning tasks under several cases with different ratios of concepts, namely CUB%10, CUB%20, CUB%50, as well as the original CUB with no concept discarded, as depicted in Fig. 5. We explore the compared performances of *Independent*, *Sequential*, *Joint* models. While $\alpha = 0.01$ is the best concept weight introduced by (Koh et al., 2020), we still present another one, i.e., $\alpha = 0.005$, performing better on label learning task. Note that there is no difference in $x \to c$ process between *Independent* and *Sequential* models, thus they perform the same in concept learning task. As expected, all these models undoubtedly suffer a severe distortion in either or both tasks, especially label distortion for *Independent* and *Sequential* models, and concept distortion for *Joint* model with $\alpha = 0.005$. It is this phenomenon that inspires us to think about the underlying cause and envision an ideal model structure that can alleviate concept/label distortions.

5.2 Model Setting

For each experiment, DCBM fine-tunes a pretrained Inception-v3 network (Szegedy et al., 2016), which maps to explicit and implicit concept values, respectively, and then connects to linear layers to obtain outputs of explicit/implicit concepts. In particular, explicit concept values are exploited to predict $x \to c$, while the sum of two outputs is used to predict the label. Despite some general hyperparameters, e.g., learning rate, we mainly search concept weight α and JS Divergence weight β, to achieve high performance and maintain the interpretability. Detailed setting is shown in Appendix C.4. In short, we choose $\alpha = 0.01$ and $\alpha = 0.1$, which respectively perform better on concept and label learning tasks. Analysis about the choice of β is further discussed in Appendix D.

Figure 5: Label (left) / Concept (right) prediction accuracy on CUB when concepts are randomly dropped. Here, we respectively abbreviated *Independent* and *Sequential* model as IND and SEQ. Besides, two kinds of concept weights are considered in *Joint* model, with $\alpha = 0.01$ and $\alpha = 0.005$, which show better performance in concept and label learning tasks, respectively. We compare different cases with 10%/20%/50%/100% concepts. As expected, *Independent*, *Sequential*, and *Joint* models suffer an obvious distortion in either or both tasks, especially label distortion for *Independent*, *Sequential* models, and concept distortion for *Joint* model with $\alpha = 0.005$.

5.3 Benchmarking Model Accuracy

Table 2 displays the prediction accuracy for label and concept learning tasks on five datasets: Derm7pt, CUB, and three variants of CUB, i.e., CUB%50, CUB%20, and CUB%10, with 50%/20%/10% ratios of concepts left. DCBM is compared with concept-based models, including *Independent*, *Sequential*, *Joint*, Concept-based Model Extraction (Kazhdan et al., 2020) (*CME*), and some models without interpretability, including *Standard* models with/without bottleneck, and *Multitask* model. Though *Joint* model had little trade-off between label and concept when concepts are sufficient, we still find the amplified concept/label distortions with more concepts invisible. To verify this, we give two groups of concept weights to ensure the best performances in either label or concept learning task, which are $\alpha = 0.01/0.005$ in *Joint* model and $\alpha = 0.1/0.01$ in our DCBM. The results in Table 2 indicate that DCBM outperforms all other approaches, and even surpasses the models with no interpretability, except in the case that *Standard* model without bottleneck performs the best in label learning task on CUB%10 dataset. This is reasonable since *Standard* model without bottleneck ignores concepts and thus is totally not sensitive to the number of concepts. Note that compared with other concept-based models, with more ratios of concepts discarded on CUB, the performance decline in both tasks is alleviated obviously for DCBM. Especially for DCBM with $\alpha = 0.1$, the decline of label and concept learning tasks is **1.45%** and **0.86%**, respectively, while it is 4.11%/2.73% in *Joint*-0.01, 5.00%/11.57% in *Joint*-0.005, 42.93%/2.13% in *Independent* model, 30.65%/2.13% in *Sequential* model, and 40.41%/1.21% in *CME*. Moreover, DCBM-0.1 significantly outperforms other concept-based models in both concept and label learning tasks on datasets with insufficient concepts, i.e., CUB20%, CUB10%, Derm7pt.

5.4 Weight of JS Divergence

Since the prediction is based on both explicit and implicit outputs, it is an interesting question how the explicit and implicit outputs themselves influence the final prediction. We show the model performances in terms of weight β in Appendix D and conclude that the choice of β is not arbitrary and not always implies a trade-off between interpretability and accuracy.

6 Experiments: Human-machine Interaction

As introduced in Sec. 4.2, two algorithms based on MI estimation, including forward intervention and backward rectification, are devised to automatically correct label predictions and trace back to wrong concepts, while they can be achieved only by few additional training costs. In Table 3 and Table 4, we experiment the corresponding tasks for DCBM with $\alpha = 0.1$ and $\beta = 0.01/0.1$ on

Table 2: Accuracy (%) of concept and label learning on CUB, Derm7pt, and three variants of CUB. We compare DCBM with interpretable (abbreviated as INTE.) baselines, including *Independent* (IND), *Sequential* (SEQ), *Joint*, and *CME* models. Meanwhile, a series of black-box models are compared due to their high performances, including *Standard* models with bottleneck (STAN-BNK) / without bottleneck (STAN), and *Multitask* (MULTI) model. To display better performances on either task, we employ two groups of concept weights in *Joint* model ($\alpha = 0.01/0.005$) and DCBM ($\alpha = 0.1/0.01$). The best results in each task are in **bold**. Our methods are marked brown.

TASK	INTE.	APPROACH	DATASET				
			CUB	**CUB%50**	**CUB%20**	**CUB%10**	**DERM7PT**
LABEL	✓	IND	76.65 ± 0.22	74.76 ± 1.61	61.34 ± 0.61	33.72 ± 2.12	71.28 ± 1.32
		SEQ	75.95 ± 0.26	73.43 ± 0.76	65.22 ± 0.39	45.30 ± 5.44	75.68 ± 0.39
		JOINT-0.01	79.64 ± 0.18	79.71 ± 0.67	78.15 ± 0.30	75.53 ± 0.29	83.02 ± 0.29
		JOINT-0.005	83.10 ± 0.28	82.84 ± 0.03	80.66 ± 0.07	78.10 ± 0.36	82.29 ± 0.36
		CME	78.33 ± 0.21	74.53 ± 0.04	61.78 ± 0.97	37.92 ± 0.39	79.45 ± 1.48
		(ours) DCBM-0.1	81.01 ± 0.40	81.34 ± 0.20	81.58 ± 0.51	80.77 ± 0.40	$\mathbf{85.32 \pm 0.39}$
		(ours) DCBM-0.01	$\mathbf{83.95 \pm 0.12}$	$\mathbf{83.53 \pm 0.17}$	$\mathbf{82.87 \pm 0.33}$	82.50 ± 0.46	85.12 ± 1.04
	✗	STAN-BNK	81.93 ± 0.20	81.56 ± 0.44	80.39 ± 0.50	77.92 ± 0.24	83.23 ± 2.43
		STAN[#]	82.54 ± 0.17	82.54 ± 0.17	82.54 ± 0.17	$\mathbf{82.54 \pm 0.17}$	82.18 ± 1.67
		MULTI	83.43 ± 0.22	82.80 ± 0.14	81.35 ± 0.08	78.01 ± 0.54	84.80 ± 0.65
CONCEPT	✓	IND[+]	96.75 ± 0.03	96.34 ± 0.16	95.93 ± 0.11	94.62 ± 0.54	78.69 ± 0.49
		SEQ[+]					
		JOINT-0.01	96.89 ± 0.03	96.60 ± 0.01	95.87 ± 0.03	94.16 ± 0.07	73.83 ± 2.72
		JOINT-0.005	94.30 ± 0.26	93.53 ± 0.73	91.12 ± 0.78	82.73 ± 0.99	72.54 ± 3.45
		CME	95.96 ± 0.06	95.78 ± 0.06	95.54 ± 0.07	94.75 ± 0.09	79.45 ± 1.48
		(ours) DCBM-0.1	$\mathbf{96.92 \pm 0.04}$	$\mathbf{96.90 \pm 0.07}$	$\mathbf{96.66 \pm 0.03}$	$\mathbf{96.06 \pm 0.09}$	$\mathbf{80.70 \pm 0.22}$
		(ours) DCBM-0.01	96.30 ± 0.12	96.14 ± 0.15	94.89 ± 0.35	93.26 ± 0.10	76.85 ± 1.91
	✗	STAN-BNK[*]	91.34 ± 0.15	90.37 ± 0.05	87.73 ± 0.16	82.20 ± 0.35	77.06 ± 0.47
		MULTI	96.10 ± 0.46	95.52 ± 0.19	94.34 ± 0.57	89.13 ± 0.90	77.07 ± 1.42

[#] *Standard* models without bottleneck share the same structure regardless of the number of concepts.
[+] *Independent* and *Sequential* model have no difference in $x \rightarrow c$ process.
[*] *Standard* model is trained with concepts unsupervised, thus we inject a linear probe to the bottleneck so it can predict the concept values.

Table 3: Forward intervention on Derm7pt, CUB and its three variants. We present the label accuracy (%) for the original *Joint* model with $\alpha = 0.01$, *CME*, and DCBM with $\alpha = 0.1$, and then respectively intervene 10% concepts to show the promotion, see JOINT-INT, CME-INT, and DCBM-INT. Moreover, we intervene simulated explicit concept values decoupled from implicit concept values (abbreviated as DCBM-INT-DEC), where label accuracy can be further improved.

APPROACH	DATASET				
	CUB	**CUB%50**	**CUB%20**	**CUB%10**	**DERM7PT**
JOINT (Koh et al., 2020)	79.65 ± 0.18	79.70 ± 0.67	78.15 ± 0.30	75.53 ± 0.27	83.02 ± 0.26
JOINT-INT (Koh et al., 2020)	82.04 ± 0.39	83.06 ± 0.10	80.99 ± 0.26	67.85 ± 0.42	74.15 ± 2.93
CME (Kazhdan et al., 2020)	78.33 ± 0.21	74.53 ± 0.04	61.78 ± 0.97	37.92 ± 0.39	79.45 ± 1.48
CME-INT (Kazhdan et al., 2020)	82.43 ± 0.21	80.59 ± 0.17	71.57 ± 0.36	54.31 ± 0.31	79.56 ± 1.60
(ours) DCBM[+]	80.82 ± 0.13	81.49 ± 0.32	81.38 ± 0.44	82.43 ± 0.14	84.28 ± 1.78
(ours) DCBM-INT[+]	81.96 ± 0.09	83.39 ± 0.77	84.76 ± 0.24	86.23 ± 0.01	86.06 ± 0.59
(ours) DCBM-INT-DEC[+]	82.52 ± 0.38	84.32 ± 0.71	$\mathbf{86.21 \pm 0.11}$	87.34 ± 0.38	$\mathbf{86.16 \pm 0.68}$
(ours) DCBM[*]	81.01 ± 0.39	81.36 ± 0.20	81.57 ± 0.51	82.10 ± 0.05	85.12 ± 0.15
(ours) DCBM-INT[*]	82.59 ± 0.25	84.07 ± 0.11	85.55 ± 0.40	$\mathbf{87.91 \pm 0.25}$	85.54 ± 1.71
(ours) DCBM-INT-DEC[*]	$\mathbf{82.80 \pm 0.32}$	$\mathbf{84.46 \pm 0.18}$	85.82 ± 0.53	87.75 ± 0.23	$\mathbf{86.16 \pm 0.77}$

[+] DCBM with $\beta = 0.01$, typically displaying the best model performance.
[*] DCBM with $\beta = 1.0$, owning high performance while retaining the best model interpretability.

CUB, CUB%50, CUB%20, CUB%10, and Derm7pt. The choices of $\beta = 0.01/0.1$ respectively represent the best model performance and the best interpretability.

Forward Intervention. In Table 3, we display the noninterventive model performance for *Joint* model with $\alpha = 0.01$ and DCBM. Then, for CUB and its variants, we respectively intervene 10% concept values of the total for wrong predictions, while we intervene all the concepts related to pigment network for Derm7pt, to show the intervention promotion, see JOINT-INT and DCBM-INT. Concept values are respectively intervened to the 95th or 5th percentile of the ones over the training distribution for positive/negative samples, which is in line with (Koh et al., 2020). Besides, we perform a novel forward intervention algorithm called DCBM-INT-DEC, as introduced in Sec. 4,

Table 4: Backward rectification on Derm7pt, CUB and its three variants. We present the original concept accuracy of DCBM with $\alpha = 0.1$ only on samples with wrong label predictions. Then, we respectively show the rectification promotion under an optimization regime without (DCBM-REC) / with (DCBM-REC-DEC) decoupling neural network. The best results for each β are in **bold.**

APPROACH	DATASET				
	CUB	**CUB%50**	**CUB%20**	**CUB%10**	**DERM7PT**
DCBM[+]	89.36 ± 0.05	88.38 ± 0.11	87.62 ± 0.12	85.24 ± 0.14	73.37 ± 2.16
DCBM-REC[+]	90.02 ± 0.05	89.73 ± 0.12	89.63 ± 0.34	85.49 ± 0.47	$\mathbf{75.39 \pm 3.01}$
DCBM-REC-DEC[+]	$\mathbf{90.25 \pm 0.08}$	$\mathbf{90.18 \pm 0.04}$	$\mathbf{91.31 \pm 0.14}$	$\mathbf{89.12 \pm 1.97}$	75.30 ± 2.97
DCBM[*]	89.23 ± 0.06	88.48 ± 0.22	87.48 ± 0.13	85.12 ± 0.25	71.59 ± 3.14
DCBM-REC[*]	90.22 ± 0.11	90.32 ± 0.08	91.22 ± 0.42	90.03 ± 0.45	72.13 ± 3.89
DCBM-REC-DEC[*]	$\mathbf{90.33 \pm 0.15}$	$\mathbf{90.48 \pm 0.05}$	$\mathbf{91.35 \pm 0.27}$	$\mathbf{91.03 \pm 0.80}$	$\mathbf{72.83 \pm 4.09}$

[+] DCBM with $\beta = 0.01$, typically displaying the best model performance.
[*] DCBM with $\beta = 1.0$, owning high model performance while retaining the best model interpretability.

Table 5: Time overheads (seconds) on the training process of concept/label prediction (DCBM), decoupling neural network (DEC), forward intervention (DCBM-INT-DEC), and backward rectification (DCBM-REC-DEC).

APPROACH	DATASET				
	CUB	**CUB%50**	**CUB%20**	**CUB%10**	**DERM7PT**
DCBM[+]	33260 ± 5212	21920 ± 9138	26264 ± 6824	14654 ± 4991	3436 ± 788
DEC	362 ± 78	312 ± 83	210 ± 35	147 ± 34	491 ± 61
DCBM-INT-DEC[*]	< 0.01	< 0.01	< 0.01	< 0.01	< 0.01
DCBM-REC-DEC[*]	0.27 ± 0.01	0.34 ± 0.02	0.47 ± 0.02	0.67 ± 0.10	0.39 ± 0.13

[+] High standard deviations are mainly due to the early stopping strategy during training.
[*] We show the time overhead of each intervened/rectified sample.

and as expected, the label accuracy can be further promoted in most cases. Especially for the situation where concepts are insufficient, our proposed algorithm can still provide effective intervention instead of even severely reducing the accuracy as *Joint* model does.

Backward Rectification. Table 4 presents the unrectified model performance (DCBM) as well as the rectification without (DCBM-REC) / with (DCBM-REC-DEC) MI estimation. To our best knowledge, we are the first to propose backward rectification. Results in Table 4 show the effectiveness of backward rectification, where DCBM-REC and DCBM-REC-DEC succeed in promoting concept accuracy in all cases, especially for DCBM-REC-DEC.

Time Overhead. The interaction system is based on a light min-max optimization introduced in Appendix A, which can be achieved within minutes. Equipped with the pretrained decoupling networks, DCBM can respectively perform forward intervention and backward rectification within 0.01s and 1s for each sample. Detailed time overheads are shown in Table 5, where we choose $\alpha = 0.1$ and $\beta = 1.0$ as a typical example in all tasks.

7 CONCLUSION

In this paper, we theoretically reveal the inherent concept/label trade-off for CBM with insufficient concept information and develop DCBM to expand the application range for CBM. Furthermore, we propose a phase-two decoupling algorithm via MI-based min-max optimization to implement human-machine interaction tasks for DCBM, including forward intervention and backward rectification. Extensive experimental results on public benchmarks show that DCBM achieves state-of-the-art concept/label accuracy and significantly alleviates the concept/label distortions when concepts are insufficient. Moreover, DCBM effectively promotes the model performance under human-machine interactions. Some future works are mentioned as follows: (1) Extend the proposed DCBM to broad scenarios, such as graph-structured data, bioinformatics databases, and so on; (2) Utilize the concepts information with causal or other hierarchical relationships to learn the DCBM; (3) Constrain the MI between explicit/implicit concepts during the training process.

REPRODUCIBILITY STATEMENT

The source code to reproduce every experiment will be available to the public. See Appendix B for the proof of the main theory and Appendix C for experimental details.

REFERENCES

Abubakar Abid, Mert Yuksekgonul, and James Zou. Meaningfully explaining model mistakes using conceptual counterfactuals. *arXiv preprint arXiv:2106.12723*, 2021.

Andrew Bai, Chih-Kuan Yeh, Pradeep Ravikumar, Neil YC Lin, and Cho-Jui Hsieh. Concept gradient: Concept-based interpretation without linear assumption. *arXiv preprint arXiv:2208.14966*, 2022.

David Bau, Bolei Zhou, Aditya Khosla, Aude Oliva, and Antonio Torralba. Network dissection: Quantifying interpretability of deep visual representations. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 6541–6549, 2017.

Mohamed Ishmael Belghazi, Aristide Baratin, Sai Rajeshwar, Sherjil Ozair, Yoshua Bengio, Aaron Courville, and Devon Hjelm. Mutual information neural estimation. In *Proceedings of the 35th International Conference on Machine Learning*, 2018.

Irene Y. Chen, Emma Pierson, Sherri Rose, Shalmali Joshi, Kadija Ferryman, and Marzyeh Ghassemi. Ethical machine learning in healthcare. *Annual Review of Biomedical Data Science*, 4(1): 123–144, 2021.

Tianping Chen and Hong Chen. Universal approximation to nonlinear operators by neural networks with arbitrary activation functions and its application to dynamical systems. *IEEE Transactions on Neural Networks*, 6(4):911–917, 1995.

Yin Cui, Yang Song, Chen Sun, Andrew Howard, and Serge Belongie. Large scale fine-grained categorization and domain-specific transfer learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4109–4118, 2018.

Kenneth R Davidson and Stanislaw J Szarek. Local operator theory, random matrices and banach spaces. *Handbook of the geometry of Banach spaces*, 1(317-366):131, 2001.

Yonina C Eldar and Gitta Kutyniok. *Compressed sensing: theory and applications*. Cambridge University Press, 2012.

Ruth Fong and Andrea Vedaldi. Net2vec: Quantifying and explaining how concepts are encoded by filters in deep neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 8730–8738, 2018.

Nicholas J Higham. *Accuracy and stability of numerical algorithms*. SIAM, 2002.

Jeremy Kawahara, Sara Daneshvar, Giuseppe Argenziano, and Ghassan Hamarneh. Seven-point checklist and skin lesion classification using multitask multimodal neural nets. *IEEE Journal of Biomedical and Health Informatics*, 23(2):538–546, 2018.

Dmitry Kazhdan, Botty Dimanov, Mateja Jamnik, Pietro Liò, and Adrian Weller. Now you see me (cme): Concept-based model extraction. In *CIKM (Workshops)*, 2020.

Dmitry Kazhdan, Botty Dimanov, Helena Andres Terre, Mateja Jamnik, Pietro Liò, and Adrian Weller. Is disentanglement all you need? comparing concept-based & disentanglement approaches. *arXiv preprint arXiv:2104.06917*, 2021.

Been Kim, Martin Wattenberg, Justin Gilmer, Carrie Cai, James Wexler, Fernanda Viegas, et al. Interpretability beyond feature attribution: Quantitative testing with concept activation vectors (tcav). In *International Conference on Machine Learning*, pp. 2668–2677. PMLR, 2018.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *ICLR (Poster)*, 2015.

Harald Kittler, Ashfaq A Marghoob, Giuseppe Argenziano, Cristina Carrera, Clara Curiel-Lewandrowski, Rainer Hofmann-Wellenhof, Josep Malvehy, Scott Menzies, Susana Puig, Harold Rabinovitz, et al. Standardization of terminology in dermoscopy/dermatoscopy: Results of the third consensus conference of the international society of dermoscopy. *Journal of the American Academy of Dermatology*, 74(6):1093–1106, 2016.

Pang Wei Koh, Thao Nguyen, Yew Siang Tang, Stephen Mussmann, Emma Pierson, Been Kim, and Percy Liang. Concept bottleneck models. In *International Conference on Machine Learning*, pp. 5338–5348. PMLR, 2020.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Max Losch, Mario Fritz, and Bernt Schiele. Semantic bottlenecks: Quantifying and improving inspectability of deep representations. *International Journal of Computer Vision*, 129(11):3136–3153, 2021.

Yulong Lu and Jianfeng Lu. A universal approximation theorem of deep neural networks for expressing probability distributions. *Advances in Neural Information Processing Systems*, 33:3094–3105, 2020.

Adriano Lucieri, Muhammad Naseer Bajwa, Stephan Alexander Braun, Muhammad Imran Malik, Andreas Dengel, and Sheraz Ahmed. On interpretability of deep learning based skin lesion classifiers using concept activation vectors. In *2020 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–10. IEEE, 2020.

M Nevitt, D Felson, and Gayle Lester. The osteoarthritis initiative. *Protocol for the cohort study*, 1, 2006.

Jayneel Parekh, Pavlo Mozharovskyi, and Florence d'Alché Buc. A framework to learn with interpretation. In *Advances in Neural Information Processing Systems*, 2021.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in Neural Information Processing Systems*, 32, 2019.

Yao Rong, Nora Castner, Efe Bozkir, and Enkelejda Kasneci. User trust on an explainable ai-based medical diagnosis support system. *arXiv preprint arXiv:2204.12230*, 2022.

Veronica Rotemberg, Nicholas Kurtansky, Brigid Betz-Stablein, Liam Caffery, Emmanouil Chousakos, Noel Codella, Marc Combalia, Stephen Dusza, Pascale Guitera, David Gutman, et al. A patient-centric dataset of images and metadata for identifying melanomas using clinical context. *Scientific Data*, 8(1):1–8, 2021.

Anirban Sarkar, Deepak Vijaykeerthy, Anindya Sarkar, and Vineeth N Balasubramanian. A framework for learning ante-hoc explainable models via concepts. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10286–10295, 2022.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2818–2826, 2016.

Philipp Tschandl, Cliff Rosendahl, and Harald Kittler. The ham10000 dataset, a large collection of multi-source dermatoscopic images of common pigmented skin lesions. *Scientific data*, 5(1):1–9, 2018.

Catherine Wah, Steve Branson, Peter Welinder, Pietro Perona, and Serge Belongie. The caltech-ucsd birds-200-2011 dataset. 2011.

Peter Welinder, Steve Branson, Takeshi Mita, Catherine Wah, Florian Schroff, Serge Belongie, and Pietro Perona. Caltech-ucsd birds 200. 2010.

Maleakhi A Wijaya, Dmitry Kazhdan, Botty Dimanov, and Mateja Jamnik. Failing conceptually: Concept-based explanations of dataset shift. *arXiv preprint arXiv:2104.08952*, 2021.

Han Xuanyuan, Pietro Barbiero, Dobrik Georgiev, Lucie Charlotte Magister, and Pietro Lió. Global concept-based interpretability for graph neural networks via neuron analysis. *arXiv preprint arXiv:2208.10609*, 2022.

Chih-Kuan Yeh, Been Kim, Sercan Arik, Chun-Liang Li, Tomas Pfister, and Pradeep Ravikumar. On completeness-aware concept-based explanations in deep neural networks. *Advances in Neural Information Processing Systems*, 33:20554–20565, 2020.

Mert Yuksekgonul, Maggie Wang, and James Zou. Post-hoc concept bottleneck models. In *ICLR 2022 Workshop on PAIR^2Struct: Privacy, Accountability, Interpretability, Robustness, Reasoning on Structured Data*, 2022.

Bolei Zhou, Yiyou Sun, David Bau, and Antonio Torralba. Interpretable basis decomposition for visual explanation. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 119–134, 2018.

A DETAILS OF PHASE-TWO DECOUPLING ALGORITHM FOR DCBM

Algorithm 1: Phase-two Decoupling Algorithm

 # MI-based min-max optimization for training f_{DEC};

Input: Explicit (implicit) concepts $\{\hat{c}_n\}_{n=1}^{N}$ ($\{\tilde{c}_n\}_{n=1}^{N}$) learned by DCBM, decoupling network f_{DEC} and auxiliary network f_{MI} with initialized parameters θ_{DEC} and θ_{MI}.

for E_1 *epochs* **do**

    Sample N pairs from the joint distribution $\{\hat{c}_n; \tilde{c}_n - f_{\text{DEC}}(\hat{c}_n)\}_{n=1}^{N}$;

    for E_2 *epochs* **do**

        Shuffle N residuals: $\{\tilde{c}_{j_n} - f_{\text{DEC}}(\hat{c}_{j_n})\}_{n=1}^{N}$;

        Calculate the lower bound: $\mathcal{L}(\theta_{\text{MI}}) = $
        $\frac{1}{N}\sum_{n=1}^{N}[f_{\text{MI}}(\hat{c}_n; \tilde{c}_n - f_{\text{DEC}}(\hat{c}_n))] - \log[\frac{1}{N}\sum_{n=1}^{N}\exp\{f_{\text{MI}}(\hat{c}_n; \tilde{c}_{j_n} - f_{\text{DEC}}(\hat{c}_{j_n}))\}]$;

        Update θ_{MI}: $\theta_{\text{MI}} = \text{optim.Adam}(\theta_{\text{MI}}, -\nabla\mathcal{L}(\theta_{\text{MI}}))$;

    Shuffle N residuals: $\{\tilde{c}_{k_n} - f_{\text{DEC}}(\hat{c}_{k_n})\}_{n=1}^{N}$;

    Calculate the loss for decoupling network: $\mathcal{L}(\theta_{\text{DEC}}) = \frac{1}{N}\sum_{n=1}^{N}[f_{\text{MI}}(\hat{c}_n; \tilde{c}_n - $
    $f_{\text{DEC}}(\hat{c}_n))] - \log[\frac{1}{N}\sum_{n=1}^{N}\exp\{f_{\text{MI}}(\hat{c}_n; \tilde{c}_{k_n} - f_{\text{DEC}}(\hat{c}_{k_n}))\}] + \eta\|f_{\text{DEC}}(\hat{c})\|_2^2$;

    Update θ_{DEC}: $\theta_{\text{DEC}} = \text{optim.SGD}(\theta_{\text{MI}}, \nabla\mathcal{L}(\theta_{\text{DEC}}))$;

 # Forward Intervention;

Input: Explicit (implicit) concepts $\hat{c}$ ($\tilde{c}$) learned by DCBM, the ground-truth concepts c^* given by expert, and the pre-trained decoupling network f_{DEC}.

Calculate the residual: $r = \tilde{c} - f_{\text{DEC}}(\hat{c})$;

Update the new predicted label: $y_{\text{new}} = f(c^*) + \tilde{f}(f_{\text{DEC}}(c^*) + r))$;

 # Backward Rectification;

Input: Explicit (implicit) concepts $\hat{c}$ ($\tilde{c}$) learned by DCBM, the ground-truth label y^* given by experts, and the pre-trained decoupling network f_{DEC}.

Initialize c_{new} via $\hat{c}$: $c_{\text{new}} = \hat{c}$;

for M *epochs* **do**

    Calculate the classification loss:
    $\mathcal{L}_Y(c_{\text{new}}) = \mathcal{L}_Y\Big[f(c_{\text{new}}) + \tilde{f}(\tilde{c} + f_{\text{DEC}}(c_{\text{new}}) - f_{\text{DEC}}(\hat{c})), y^*\Big]$;

    Update the concept c_{new}: $c_{\text{new}} = \text{optim.Adam}(c_{\text{new}}, \nabla\mathcal{L}_Y(c_{\text{new}}))$;

B THEORETICAL RESULTS

This section presents the inherent dilemma of concept/label distortions in CBM theoretically. The analysis of the main theorem consists of two steps: (1) analyzing the relationship between the

number of missing concepts and the label error for *Sequential* CBM; (2) revealing the trade-off between concept and label accuracy for *Joint* CBM via the perturbation theory of least square problem (Higham, 2002).

B.1 ASSUMPTIONS

To model the above phenomenon mathematically, we firstly introduce the functional families $\mathcal{F}_{d,k}$ and the non-redundant assumption in Definition 1 and 2, respectively.

Definition 1. *Define $\mathcal{F}_{d,k}$ as the families of linear transform from $\mathbb{R}^d$ to $\mathbb{R}^k$:*

$$\mathcal{F}_{d,k} \triangleq \{f : \boldsymbol{c} \in \mathbb{R}^d \rightarrow \boldsymbol{W}\boldsymbol{c} \in \mathbb{R}^k | \boldsymbol{W} \in \mathbb{R}^{k \times d}, \boldsymbol{W}_{i,j} \sim \mathcal{N}(0, \frac{1}{d})\}. \tag{7}$$

Definition 2. *Let $\mathcal{C}$ be a probability distribution over $\mathbb{R}^d$. We say $\mathcal{C}$ is non-redundant if and only if:*

$$\mathrm{MI}(\mathcal{C}_{\mathbb{A}}; \mathcal{C}_{\mathbb{B}}) < \mathrm{H}(\mathcal{C}_{\mathbb{A}}), \quad \text{for all } \mathbb{A}, \mathbb{B} \subset \{1, 2, \cdots, d\}, \mathbb{A} \cap \mathbb{B} = \varnothing, \tag{8}$$

where $\mathrm{MI}(\cdot; \cdot)$ and $\mathrm{H}(\cdot)$ denote the mutual information and entropy, respectively.

We state our main assumption for the data generating process in Assumption 1.

Assumption 1. *[Two-phase Generation] The data are generated from a two-phase processes $\mathcal{G}$:*

$$\mathcal{G} : \mathcal{X} \xrightarrow{g^*} \mathcal{C} \xrightarrow{f^*} \mathcal{Y}, \tag{9}$$

where $\mathcal{X} \subset \mathbb{R}^D$ is the distribution of the input images, $\mathcal{C} \subset \mathbb{R}^d$ and $\mathcal{Y} \subset \mathbb{R}^k$ represent the corresponding distribution of concepts and labels, respectively. $g^* : \mathcal{X} \rightarrow \mathcal{C}$ is a Lipschitz continuous concept mapping, which maps the data point to its corresponding concept, and f^* is a linear classifier sampled from the families of linear transform $\mathcal{F}_{d,k}$ randomly. Furthermore, we assume that the concept distribution $\mathcal{C}$ satisfies the non-redundant assumption in Definition 2.

To generate the dataset, we firstly sample a data generator G from the corresponding family $\mathcal{G}$. Then, we sample N triples $\{\boldsymbol{x}_n, \boldsymbol{c}_n, \boldsymbol{y}_n\}_{n=1}^N$ from the data generator G, and only select $d_1 < d$ concepts randomly from $\mathcal{C}$, denoted as $\{\boldsymbol{x}_n, \boldsymbol{c}'_n, \boldsymbol{y}_n\}_{n=1}^N$ to simulate the case of insufficient concepts.

The non-redundant assumption reveals that arbitrary concept cannot be represented by the rest ones, which guarantees the uniqueness of the linear probe in the proof of the main theorem. Furthermore, we assume the concept bottleneck model comprises two modules as follows.

Assumption 2. *Let g and f be two modules in CBM, where $g : \mathcal{X} \rightarrow \mathcal{C}$ be a powerful neural network function which can represent arbitrary Lipschitz continuous mapping and $f \in \mathcal{F}_{d,k}$ is a linear probe.*

The universal approximation assumption of neural network function can be guaranteed by the theorems in (Chen & Chen, 1995; Lu & Lu, 2020).

B.2 MAIN RESULTS

Now we are ready to state our main theorem in this section as follows.

Theorem 2. *Consider a dataset $\{\boldsymbol{x}_n, \boldsymbol{c}'_n, \boldsymbol{y}_n\}_{n=1}^N$ generated from $\mathcal{G}$ described in Assumption 1, and the CBM model which satisfies the Assumption 2. Let d_1 (d_2) denote the number of known (unknown) concepts, and assume $k < \min\{d_1, d_2\}$. Let $\mathcal{E}_C$ and $\mathcal{E}_Y$ denote the ℓ_2 error of concepts and labels for CBM, respectively. Then, for all $\epsilon \geq 0$, the following inequation holds for Joint CBM with probability at least $1 - 2\exp(-\epsilon^2/2)$:*

$$\mathcal{E}_Y \geq \frac{1}{\sqrt{d}}(\sqrt{d_2} - \sqrt{k} - \epsilon)\|\mathbb{P}_{\boldsymbol{U}_2}(\boldsymbol{C}_2)\|_F - 2\|\boldsymbol{C}_1^\dagger\|_2\|\boldsymbol{Y}\|_F \mathcal{E}_C, \tag{10}$$

where $\mathbb{P}_{\boldsymbol{A}}(\boldsymbol{B})$ denotes the projection of $\boldsymbol{B}$ onto the subspace $\mathrm{span}(\boldsymbol{A})$, $\boldsymbol{C}_1 \in \mathbb{R}^{N \times d_1} (\boldsymbol{C}_2 \in \mathbb{R}^{N \times d_2})$ denotes the matrices of known (unknown) concepts, and $\boldsymbol{U}_2$ denotes the orthogonal complement space of $\boldsymbol{C}_1$ such that $\mathrm{span}(\boldsymbol{C}_1 + \boldsymbol{C}_2) = \mathrm{span}(\boldsymbol{C}_1) \oplus \mathrm{span}(\boldsymbol{U}_2)$.

Proof Let $\boldsymbol{X} \triangleq [\boldsymbol{x}_1, \boldsymbol{x}_2, \cdots, \boldsymbol{x}_N]^\top \in \mathbb{R}^{N \times D}$, $\boldsymbol{C} \triangleq [\boldsymbol{c}_1, \boldsymbol{c}_2, \cdots, \boldsymbol{c}_N]^\top \in \mathbb{R}^{N \times d}$, $\boldsymbol{Y} \triangleq [\boldsymbol{y}_1, \boldsymbol{y}_2, \cdots, \boldsymbol{y}_N]^\top \in \mathbb{R}^{N \times k}$ be the concatenation of N input images, concepts, and labels, respectively. Without loss of generality, we assume that the first d_1 concepts are known, and divide $\boldsymbol{C}$ into two parts, the given concepts $\boldsymbol{C}_1 \in \mathbb{R}^{N \times d_1}$ and the unknown parts $\boldsymbol{C}_2 \in \mathbb{R}^{N \times d_2}$, respectively. Applying block QR factorization on $\boldsymbol{C}$, we have:

$$\boldsymbol{C} = [\boldsymbol{C}_1 \| \boldsymbol{C}_2] = [\boldsymbol{U}_1 \| \boldsymbol{U}_2] \left[\begin{array}{cc} \boldsymbol{B}_{11} & \boldsymbol{B}_{12} \\ \boldsymbol{0} & \boldsymbol{B}_{22} \end{array} \right], \tag{11}$$

where $\boldsymbol{U}_1 \in \mathbb{R}^{N \times d_1}$ and $\boldsymbol{U}_2 \in \mathbb{R}^{N \times d_2}$ denote two orthogonal basis matrices, and the block $\boldsymbol{B}_{11} \in \mathbb{R}^{d_1 \times d_1}$, $\boldsymbol{B}_{12} \in \mathbb{R}^{d_1 \times d_2}$ and $\boldsymbol{B}_{22} \in \mathbb{R}^{d_2 \times d_2}$ denote the coefficient matrices. Similarly, we divide the linear transform matrix $\boldsymbol{W} \in \mathbb{R}^{k \times d}$ in Assumption 1 as $\boldsymbol{W} = [\boldsymbol{W}_1 \| \boldsymbol{W}_2]$, where $\boldsymbol{W}_1 \in \mathbb{R}^{k \times d_1}$ and $\boldsymbol{W}_2 \in \mathbb{R}^{k \times d_2}$ represent the linear transform matrices corresponding to $\boldsymbol{C}_1$ and $\boldsymbol{C}_2$, respectively. It is worth mentioning that $\boldsymbol{W}$ is almost surely unique due to the non-redundant and the Gaussian distribution assumptions in Assumption 1.

Firstly, we analyze the relationship between the number of missing concepts and the label error for *Sequential* CBM. Due to the universal approximation ability of the neural network function g, we only need to consider the following optimization problem:

$$\min_{f \in \mathcal{F}_{d_1, k}} \quad \sum_{n=1}^N \|f(\boldsymbol{c}_n') - \boldsymbol{y}_n\|_2^2. \tag{12}$$

According to the law of data generator $\mathcal{G}$, we have:

$$\boldsymbol{Y} = \boldsymbol{C} \boldsymbol{W}^\top = [\boldsymbol{U}_1 \| \boldsymbol{U}_2] \left[\begin{array}{cc} \boldsymbol{B}_{11} & \boldsymbol{B}_{12} \\ \boldsymbol{0} & \boldsymbol{B}_{22} \end{array} \right] \left[\begin{array}{c} \boldsymbol{W}_1^\top \\ \boldsymbol{W}_2^\top \end{array} \right]. \tag{13}$$

Then, $\boldsymbol{Y}' \triangleq \boldsymbol{U}_1 \boldsymbol{B}_{11} \boldsymbol{W}_1^\top + \boldsymbol{U}_1 \boldsymbol{B}_{12} \boldsymbol{W}_2^\top$ and $\boldsymbol{Y}^\perp \triangleq \boldsymbol{U}_2 \boldsymbol{B}_{22} \boldsymbol{W}_2^\top$ denote the optimal projection and the residual of $\boldsymbol{Y}$ onto the subspace of $\mathrm{span}(\boldsymbol{C}_1)$, respectively. Thus, we can give the lower bound for the ℓ_2 label error of *Sequential* CBM $\mathcal{L}_Y^s$ as follows:

$$\begin{aligned} \mathcal{L}_Y^s &= \|\boldsymbol{Y}^\perp\|_F^2 \\ &= \|\boldsymbol{U}_2 \boldsymbol{B}_{22} \boldsymbol{W}_2^\top\|_F^2 \\ &\geq \lambda_{\min}^2(\boldsymbol{W}_2) \|\mathbb{P}_{\boldsymbol{U}_2}(\boldsymbol{C}_2)\|_F^2, \end{aligned} \tag{14}$$

where $\lambda_{\min}(\boldsymbol{W}_2)$ denotes the least eigenvalue of $\boldsymbol{W}_2$. Due to $\boldsymbol{W}_2 \in \mathbb{R}^{d_2 \times k}$ is the sub-matrix of $\boldsymbol{W}$, which sampled from a random matrix family satisfying the Gaussian distribution. According to the random matrix theory (Davidson & Szarek, 2001; Eldar & Kutyniok, 2012), for all $\epsilon \geq 0$, with probability at least $1 - 2\exp\left(-\epsilon^2/2\right)$ we have:

$$\lambda_{\min}(\boldsymbol{W}_2) \geq \frac{1}{\sqrt{d}}(\sqrt{d_2} - \sqrt{k} - \epsilon). \tag{15}$$

Thus, with high probability, we have:

$$\mathcal{L}_Y^s \geq \frac{1}{d}(\sqrt{d_2} - \sqrt{k} - \epsilon)^2 \|\mathbb{P}_{\boldsymbol{U}_2}(\boldsymbol{C}_2)\|_F^2. \tag{16}$$

Next, we consider the equivalent form of the *Joint* CBM, which can be formulated as the following optimization problem:

$$\min_{\{\hat{\boldsymbol{c}}_n\}_{n=1}^N, f \in \mathcal{F}_{d_1, k}} \mathcal{L}_Y + \alpha \mathcal{L}_C,$$

$$\mathcal{L}_C = \sum_{n=1}^N \|\hat{\boldsymbol{c}}_n - \boldsymbol{c}_n'\|_2^2; \ \mathcal{L}_Y = \sum_{n=1}^N \|f(\hat{\boldsymbol{c}}_n) - \boldsymbol{y}_n\|_2^2. \tag{17}$$

The equivalence can be guaranteed due to the universal approximation property of the neural network function. Let $\{\hat{\boldsymbol{c}}_n^*\}_{n=1}^N$ and $\hat{f}^*$ be the optimizer of the optimization problem 17, and concatenate all $\{\hat{\boldsymbol{c}}_n^*\}_{n=1}^N$ as $\hat{\boldsymbol{C}}^*$. Furthermore, let $\hat{\boldsymbol{Y}}^\perp$ denote the projection residual of $\boldsymbol{Y}$ onto the subspace

$\mathrm{span}(\hat{\boldsymbol{C}}^*)$. Then, according to the perturbation theory of the least square problem (Higham, 2002), we have:

$$
\begin{aligned}
& \|\boldsymbol{Y}^\perp - \hat{\boldsymbol{Y}}^\perp\|_F \\
\leq & \|\hat{\boldsymbol{C}}^* - \boldsymbol{C}_1\|_F \|\boldsymbol{C}_1^\dagger \boldsymbol{Y}\|_F + \|\hat{\boldsymbol{C}}^* - \boldsymbol{C}_1\|_F \|\boldsymbol{C}_1^\dagger\|_2 \|\boldsymbol{Y}^\perp - \boldsymbol{Y}\|_F \\
\leq & 2\|\hat{\boldsymbol{C}}^* - \boldsymbol{C}_1\|_F \|\boldsymbol{Y}\|_F \|\boldsymbol{C}_1^\dagger\|_2.
\end{aligned}
\tag{18}
$$

Then, we can obtain the lower bound of label error $\mathcal{E}_Y$ for *Joint* CBM as follows:

$$
\begin{aligned}
\mathcal{E}_Y = & \|\hat{\boldsymbol{Y}}^\perp\|_F \\
\geq & \|\boldsymbol{Y}^\perp\|_F - \|\boldsymbol{Y}^\perp - \hat{\boldsymbol{Y}}^\perp\|_F \\
\geq & [\mathcal{L}_Y^{\mathrm{s}}]^{\frac{1}{2}} - 2\|\hat{\boldsymbol{C}}^* - \boldsymbol{C}\|_F \|\boldsymbol{C}_1^\dagger\|_2 \|\boldsymbol{Y}\|_F \\
\geq & \frac{1}{\sqrt{d}}(\sqrt{d_2} - \sqrt{k} - \epsilon)\|\mathbb{P}_{\boldsymbol{U}_2}(\boldsymbol{C}_2)\|_F - 2\|\hat{\boldsymbol{C}}^* - \boldsymbol{C}_1\|_F \|\boldsymbol{C}_1^\dagger\|_2 \|\boldsymbol{Y}\|_F \\
= & \frac{1}{\sqrt{d}}(\sqrt{d_2} - \sqrt{k} - \epsilon)\|\mathbb{P}_{\boldsymbol{U}_2}(\boldsymbol{C}_2)\|_F - 2\|\boldsymbol{C}_1^\dagger\|_2 \|\boldsymbol{Y}\|_F \mathcal{E}_C.
\end{aligned}
\tag{19}
$$

$\square$

C   EXPERIMENTAL PROTOCOLS

C.1   DATASET

We consider two commonly-used datasets, including bird species and dermoscopic images, as shown in Fig. 6. Both of them express high-level concepts as such one can provide interpretability analysis.

CUB (Wah et al., 2011) Caltech-UCSD Birds-200-2011, which we call CUB in the following text, is an extension of CUB-200 (Welinder et al., 2010), collecting a total of 200 bird species with 11,788 bird photographs. CUB comprises 312 bird attributes including wing shape, back pattern, eye color, etc. Since the concepts are noisy and sparse, we leave only 112 binary concepts instead, following the work (Koh et al., 2020), detailed in Table 6. This task aims to classify each bird photograph out of 200 different species. Thanks to the splitting standard of train/test/validation dataset (Koh et al., 2020), we only need to follow this given setting.

Derm7pt (Kawahara et al., 2018) Seven-Point Checklist Dermatology dataset, abbreviated as Derm7pt, is a dataset comprising 1,011 groups of images. Each group contains a clinic photograph and a dermoscopic image, respectively. Due to the lack of Seborrheic Keratosis (SK) samples, we follow the setting of the work (Lucieri et al., 2020), only considering Melanoma (MEL) and Naevi (NV) ones with a total of 823 groups. Derm7pt contains several authoritative concepts (Kittler et al., 2016) including Pigmented Networks, Streaks, etc. On account of the concept absence and inter-pretability on Melanoma detection, we leave 8 malignancy-associated binary concepts, including Blue Whitish Veil, Pigmented Networks, and Regression Structures, as (Yuksekgonul et al., 2022) did. We also show the concepts in Table 6. This task is a binary classification problem, judging whether an image is a melanoma or naevus. Similarly, the train/test/validation indexes are already given as well.

Note that CUB succeeds to have a large group of concepts, while Derm7pt fails. However, most datasets we have investigated typically have a small number of concepts (Nevitt et al., 2006), or have to be extracted (Tschandl et al., 2018; Rotemberg et al., 2021; Krizhevsky et al., 2009; Fong & Vedaldi, 2018) by other trained models (Lucieri et al., 2020; Abid et al., 2021). This phenomenon is understandable, since high-quality and abundant labeled concepts are labour-intensive and infre-quent. This brings about a new question — What if CUB also has an insufficient group of concepts? And then, how will CBM perform under this condition? To achieve the answer, we randomly drop 50%, 80%, and 90% concepts in CUB, respectively, and form three new datasets named **CUB%50**, **CUB%20**, and **CUB%10**. We display a brief summary of the referred datasets in Table 1, while the left concepts are randomly chosen by programs and fixed as:

Table 6: Concepts used in CUB and Derm7pt.

			Concepts in CUB				
No.	**Concept Name**	**No.**	**Concept Name**	**No.**	**Concept Name**	**No.**	**Concept Name**
1	bill shape: dagger	29	back color: black	57	forehead color: yellow	85	back pattern: striped
2	bill shape: hooked seabird	30	back color: white	58	forehead color: black	86	back pattern: multi-colored
3	bill shape: all-purpose	31	back color: buff	59	forehead color: white	87	tail pattern: solid
4	bill shape: cone	32	tail shape: notched tail	60	under tail color: brown	88	tail pattern: striped
5	wing color: brown	33	upper tail color: brown	61	under tail color: grey	89	tail pattern: multi-colored
6	wing color: grey	34	upper tail color: grey	62	under tail color: black	90	belly pattern: solid
7	wing color: yellow	35	upper tail color: black	63	under tail color: white	91	primary color: brown
8	wing color: black	36	upper tail color: white	64	under tail color: buff	92	primary color: grey
9	wing color: white	37	upper tail color: buff	65	nape color: brown	93	primary color: yellow
10	wing color: buff	38	head pattern: eyebrow	66	nape color: grey	94	primary color: black
11	upperparts color: brown	39	head pattern: plain	67	nape color: yellow	95	primary color: white
12	upperparts color: grey	40	breast color: brown	68	nape color: black	96	primary color: buff
13	upperparts color: yellow	41	breast color: grey	69	nape color: white	97	leg color: grey
14	upperparts color: black	42	breast color: yellow	70	nape color: buff	98	leg color: black
15	upperparts color: white	43	breast color: black	71	belly color: brown	99	leg color: buff
16	upperparts color: buff	44	breast color: white	72	belly color: grey	100	bill color: grey
17	underparts color: brown	45	breast color: buff	73	belly color: yellow	101	bill color: black
18	underparts color: grey	46	throat color: grey	74	belly color: black	102	bill color: buff
19	underparts color: yellow	47	throat color: yellow	75	belly color: white	103	crown color: blue
20	underparts color: black	48	throat color: black	76	belly color: buff	104	crown color: brown
21	underparts color: white	49	throat color: white	77	wing shape: rounded-wings	105	crown color: grey
22	underparts color: buff	50	throat color: buff	78	wing shape: pointed-wings	106	crown color: yellow
23	breast pattern: solid	51	eye color: black	79	size: small (5 - 9 in)	107	crown color: black
24	breast pattern: striped	52	bill length: about the same as head	80	size: medium (9 - 16 in)	108	crown color: white
25	breast pattern: multi-colored	53	bill length: shorter than head	81	size: very small (3 - 5 in)	109	wing pattern: solid
26	back color: brown	54	forehead color: blue	82	shape: duck-like	110	wing pattern: spotted
27	back color: grey	55	forehead color: brown	83	shape: perching-like	111	wing pattern: striped
28	back color: yellow	56	forehead color: grey	84	back pattern: solid	112	wing pattern: multi-colored
			Concepts in Derm7pt				
No.	**Concept Name**	**No.**	**Concept Name**	**No.**	**Concept Name**	**No.**	**Concept Name**
1	blue whitish veil: present	3	pigment network: atypical	5	regression structures: absent	7	regression structures: combinations
2	pigment network: absent	4	pigment network: typical	6	regression structures: blue areas	8	regression structures: white areas

Figure 6: Examples of CUB (left) and Derm7pt (right) datasets. In CUB, each line indicates a bird species, while in Derm7pt, each line corresponds to the clinic or dermoscopic images of melanoma or nevus. The clinic and dermoscopic images are aligned up and down.

- **CUB50%**: 1, 2, 5, 6, 8, 10, 12, 13, 18, 19, 21, 27, 28, 32, 33, 34, 37, 39, 40, 41, 43, 46, 47, 50, 52, 54, 56, 57, 61, 62, 63, 64, 65, 66, 67, 69, 71, 72, 75, 78, 79, 80, 81, 84, 86, 92, 93, 95, 96, 98, 100, 101, 103, 104, 107, 109.
- **CUB20%**: 6, 13, 18, 28, 33, 34, 37, 39, 46, 50, 52, 54, 62, 63, 65, 66, 75, 80, 96, 98, 101, 109.
- **CUB10%**: 6, 34, 50, 52, 54, 63, 66, 98, 101, 107, 109.

C.2 BASELINES

We adopt seven models as our baselines in this paper, including:

- *Independent / Sequential / Joint* models in CBM, as recommended in Sec. 3.1.
- *Standard model with / without bottleneck*, introduced in (Koh et al., 2020). The former learns f, g with no concept supervised: $\hat{f}, \hat{g} = \arg\min_{f,g} \sum_{n=1}^{N} \mathcal{L}_Y[f \circ g(\boldsymbol{x}_n), \boldsymbol{y}_n]$, while the latter is devised to directly predict $x \to y$: $\hat{h} = \arg\min_h \sum_{n=1}^{N} \mathcal{L}_Y[h(\boldsymbol{x}_n), \boldsymbol{y}_n]$, with mapping $h : \mathbb{R}^D \to \mathbb{R}^k$.
- *Multitask*, also introduced in (Koh et al., 2020), is devised with an additional auxiliary loss to enable the last layer to be predictive of the concepts, which learns g, h simultaneously: $\hat{g}, \hat{h} = \arg\min_{g,h} \sum_{n=1}^{N} \{\mathcal{L}_Y[h(\boldsymbol{x}_n), \boldsymbol{y}_n] + \alpha\mathcal{L}_C[g(\boldsymbol{x}_n), \boldsymbol{c}_n]\}$.
- *CME* (Kazhdan et al., 2020), also named as Concept-based Model Extraction, is based on a pre-trained deep neural network and searches a mapping from a deep layer to each concept that performs

the best on concept accuracy, and then predicts the final label via traditional machine learning approaches.

Note that it is impossible for the *Standard* and *Multitask* model to be interpreted with the concepts ignored or uncovered by the final prediction, however, since there is no trade-off between concept and label, their performances on label prediction are competitive and worth enough attention.

C.3 METRICS

Top-1 accuracy is exploited in both label and concept tasks. The former is a multi-class learning task, while the latter describes a multi-label classification task. In particular, in label prediction task, we use cross entropy loss to describe the difference between the predicted label and the ground-truth one. In concept prediction task, each concept corresponds to a binary classification mission and thus we compute the mean accuracy for all labels, where we also use a cross entropy loss to compute the difference of each predicted concept and the ground truth one during training process. This setting is in line with (Koh et al., 2020).

C.4 MODEL SETTING

For the pre-processing of the training images, we adjust the size of each image in CUB and Derm7pt to $299 \times 299 \times 3$ via random jittering, horizontal flip, and cropping, which is the same setting in (Koh et al., 2020; Cui et al., 2018), while the images at test time are center-cropped and resized to 299. Similarly, but with a few differences, in DCBM training, we increase the parameter search field. We search hyperparameters on the validation dataset with α in [0.005, 0.01, 0.05, 0.1, 0.5, 1.0], learning rate in [0.001, 0.01], regularization strengths in [0.0004, 0.00004], reducing learning rates by 10 times after every [10, 15, 20, 30] epochs until the rates come to 0.0001. Once these parameters are fixed, we retrained models with training and validation datasets altogether until convergence with β in [0.0, 0.01, 0.1, 1.0, 10.0]. Besides, the dimension of implicit concept values is set to 256 in all cases. The best model is chosen by either the best label accuracy or the best concept accuracy on validation dataset. Each experiment is trained with a batch size of 64 and Stochastic Gradient Descent (SGD) with a momentum of 0.9.

f_{MI} in Sec. 4.2 is a multilayer perception (MLP), which has neuron sizes of [*input size*, 50, 50, *output size*], where the *input size* equals to the dimension sum of explicit and implicit concept values, and *the output size* is set as 1 to compute MI. In addition, f_{DEC} in Sec. 4.2 is also an MLP layer with neuron sizes of [*input size*, 100, 100, 100, *output size*], where the *input size* and *output size* respectively equal to the dimensions of explicit and implicit concept values. Among each layer in f_{MI} and f_{DEC}, we add activation functions $\text{ReLU}(x) = \max(0, x)$ to achieve nonlinearity.

For forward intervention, to obtain a rather high performance, MI estimation optimization is trained by Adam (Kingma & Ba, 2015) with a learning rate in [0.005, 0.01, 0.05, 0.1], and the decoupling neural network is trained by SGD with a learning rate in [0.005, 0.01, 0.05, 0.1] and momentum of 0, where MI estimation is optimized for [20, 30, 40, 50] times corresponding to each decoupling process. We use the cross entropy on training datasets to perform early stopping. Besides, the backward rectification is learned by Adam with a learning rate in [0.0025, 0.025] and normalization weight in [0, 0.01, 0.1] until convergence. The best models are chosen via the best performances on validation datasets.

D WEIGHT OF JS CONVERGENCE

Fig. 7 shows the Label (a-e) / Concept (f) accuracy for DCBM with $\alpha = 0.1$ on Derm7pt, CUB, and three variants of CUB, where EXP-DCBM and IMP-DCBM present the prediction results only harnessing explicit and implicit outputs, respectively. The results show that EXP-DCBM keeps a very low label accuracy when the weight of JS Divergence is close to 0 and gradually transcends with the rise of weight. By contrast, IMP-DCBM has a rather higher label accuracy than EXP-DCBM when the weight of JS Divergence is close to 0, and keeps stable with the rise of weight, but suddenly drops to a very low degree when the weight achieves a very high level, e.g., β=10.0 on CUB and its variants. We argue that a large weight of JS Divergence forces EXP-DCBM to be close to DCBM, and thus might damage the influence of IMP-DCBM. However, though the label

Figure 7: Label (a-e) / Concept (f) prediction accuracy for DCBM with $\alpha = 0.1$ on Derm7pt / CUB / CUB%50,%20,%10 when the weight of JS divergence differs. EXP-DCBM and IMP-DCBM represent the prediction results only harnessing explicit and implicit outputs, respectively. Note that EXP-DCBM is interpretable, while IMP-DCBM is a pure black-box model.

accuracy for DCBM's gradients fluctuates severely, the label accuracy for DCBM itself remains stable, with the exception that the accuracy drops a little due to the nosedive of the label accuracy for IMP-DCBM. Under this perspective, we believe that the choice of β is not arbitrary, and not always implies a trade-off between interpretability and accuracy. For instance, the label accuracy for DCBM keeps stable or rises slightly, while the one of EXP-DCBM significantly improves when β varies from 0.0 to 1.0. In addition to this, as shown in Fig. 7 (f), the influence of concept accuracy changes little with different weights of JS Divergence, which indicates the concept robustness in terms of β.