DOMAIN GENERALIZATION FOR ROBUST MODEL-BASED OFFLINE RL

ABSTRACT

Existing offline reinforcement learning (RL) algorithms typically assume that training data is either: 1) generated by a known policy, or 2) of entirely unknown origin. We consider multi-demonstrator offline RL, a middle ground where we know which demonstrators generated each dataset, but make no assumptions about the underlying policies of the demonstrators. This is the most natural setting when collecting data from multiple human operators, yet remains unexplored. Since different demonstrators induce different data distributions, we show that this can be naturally framed as a domain generalization problem, with each demonstrator corresponding to a different domain. Specifically, we propose Domain-Invariant Model-based Offline RL (DIMORL), where we apply Risk Extrapolation (REx) (Krueger et al., 2020) to the process of learning dynamics and rewards models. Our results show that models trained with REx exhibit improved domain generalization performance when compared with the natural baseline of pooling all demonstrators' data. We observe that the resulting models frequently enable the learning of superior policies in the offline model-based RL setting, can improve the stability of the policy learning process, and potentially increase exploration.

1 INTRODUCTION

In the standard online reinforcement learning (RL) paradigm, agents often require millions of interactions with the environment in order to learn an optimal policy for completing a task. In many settings, however, the process of exploration in the real-world is undesirable, impractical or unsafe (Levine et al., 2020; Prudencio et al., 2022). It would therefore be preferable to enable learning from *demonstrations*, rather than direct *interaction* with the environment. Datasets targeting activity recognition from ego-centric videos (Damen et al., 2022) highlight the prevalence and ease of collecting demonstrations in our setting. These are provided by one or more *demonstrators*, each executing their own behavioural policy, π_β–their method of achieving the task. Various approaches to performing offline RL have been proposed (Levine et al., 2020; Prudencio et al., 2022). However, to the best of our knowledge, none of these approaches exploit information regarding the collection of data from multiple demonstrators.

A fundamental challenge in off-policy RL is policy-induced *distributional shift*; this is especially problematic in offline RL (Levine et al., 2020; Yu et al., 2020). Standard off-policy RL methods often fail when trained using offline data (Fujimoto et al., 2018). Value-based offline RL algorithms have addressed this by encouraging the agent to stay close to the behaviour policy used when generating the data. Such a constraint can (provably) limit performance (Buckman et al., 2020). Buckman et al. (2020) and other model-based approaches which do not suffer from this weakness have been found to outperform value-based methods (Yu et al., 2020; Kidambi et al., 2020).

Rather than constraining the learning policy's exploration, the aim of our work is to increase the robustness of *environment models*[1] to distributional shifts by applying *Risk Extrapolation (REx)* (Krueger et al., 2020) during training. REx assumes that training data from multiple domains (in our case, demonstrators) is available. While the demonstrator that generated each training record is

---

[1]We use the term *environment model* to highlight that both dynamics and rewards models are learned. We do not learn an initial state distribution. During policy training, transitions are generated from starting locations sampled from the offline dataset. When evaluating policies, the real initial state distribution is used.

known, no knowledge about the demonstrator's policy is required. REx aims to achieve similar risk on out-of-distribution domains by encouraging the training losses/risks across the domains present in the training data to be equal, even if the distributional shift is more extreme than those observed at training/test time (Krueger et al., 2020).

The primary contribution of our work is a practical algorithm for performing **Domain-Invariant Model-base Offline RL (DIMORL)** using multi-demonstrator datasets. We empirically show that environment models trained with REx exhibit improved average and worst-case performance on out-of-distribution datasets. Furthermore, in a majority of cases, policies trained offline using these models attain higher average returns. We demonstrate that environment models trained with REx can enable more stable offline model-based policy learning, and potentially support increased exploration. We present hypotheses for the benefits observed, and share the supporting evidence gathered thus far. However, further experimentation and analysis are needed to draw firm conclusions.

2   BACKGROUND AND RELATED WORK

Offline Reinforcement Learning   In offline RL, an agent π is trained using *only* a fixed dataset $\mathcal{D}$ of transitions ($\{s, a, r, s'\}$) (Fujimoto et al., 2018), or trajectories ($\{s_1, a_1, r_1, ..., s_T, a_T, r_T\}$) (Agarwal et al., 2019), without any further interaction with the environment (Levine et al., 2020; Prudencio et al., 2022). The data may also include meta-data about the policy or policies used to collect the data. Our aim is to learn the optimal policy, $\pi^*(a|s)$, that maximises the expected sum of discounted rewards $\pi^* = \arg\max_\pi \mathbb{E}_\pi[\sum_{t=0}^\infty \gamma^t r(s_t, a_t)]$, using discount factor $\gamma \in (0, 1]$.

Distributional Shift   While the transition distribution of a Markov-Decision Process (MDP) is independent of the policy being followed, the state and state-action visitation distributions induced by behavioural policy π_β, $d^{\pi_\beta}(s)$ and $d^{\pi_\beta}(s, a)$ respectively, are not. The data collected for offline policy training is typically assumed to be composed of *iid* samples drawn from $d^{\pi_\beta}(s, a)$, and is likely to cover only a fraction of the total state-action space. In order to learn optimal policies, we would like our learning algorithm to *generalize* to other areas of this space; departing from the support of the training data in order to learn good behaviours that are not exhibited in the static dataset (Yu et al., 2020; Wu et al., 2021). The policy being learned, π_{off}, would therefore induce new state and state-action visitation distributions, $d^{\pi_{\text{off}}}(s)$ and $d^{\pi_{\text{off}}}(s, a)$. Errors made by the learned environment models, such as those arising from poor generalization performance under distributional shift, can result in *model exploitation*: the policy being trained learns to take advantage of model errors when optimizing the reward, leading to poor performance in the real environment (Cang et al., 2021; Rajeswaran et al., 2016; Janner et al., 2019; Clavera et al., 2018; Levine et al., 2020). However, in more extreme cases, model exploitation can cause significant instability in training, preventing a policy from being learned (Kurutach et al., 2018; Matsushima et al., 2020).

Offline Model-Based Reinforcement Learning   Kidambi et al. (2020) and Yu et al. (2020) proposed the model-based offline RL algorithms MoREL and MOPO respectively. Both of these methods are conservative in the face of model uncertainty. However, they do not explicitly penalize deviations from the demonstrator's distribution, thus avoiding performance limitations demonstrated by Buckman et al. (2020). Both MoREL and MOPO work by modifying a learned MDP to penalize uncertain transitions. MoREL's pessimistic MDP adjusts $P(s'|s, a)$ to transition to a low-reward terminal state when the dynamics of (s, a) are uncertain, as measured by disagreement within an ensemble of learned dynamics models (Kidambi et al., 2020). In MOPO, Yu et al. (2020) instead penalize uncertain transitions directly in the reward function, and measure uncertainty as the maximum standard deviation across members of an ensemble. MOPO extends MBPO (Janner et al., 2019), which combines the soft-actor critic (SAC) policy gradient algorithm (Haarnoja et al., 2018a;b) with using learned dynamics models to generate short roll-outs.

3   METHODS

Our method stems from the observation that different demonstrators in an offline RL setting correspond to different domains in a domain generalization setting. Therefore, **Domain-Invariant Model-based Offline RL (DIMORL)** leverages the MOPO codebase (Yu et al., 2020), and supplements it with domain generalization approaches for training the environment model.

(a) Risks for OOD Datasets

(b) Average and Worst Case OOD Risks

Figure 1: **Left:** We observe that REx increases the similarity of risks across OOD datasets by decreasing the risk (i.e., increasing the log-likelihood) for certain datasets, while increasing it for others. Data has been plotted according to increasing log-likelihood using the environment model trained with $\beta = 0$. **Right:** REx increases the average and worst-case risks across the OOD datasets. Environment models were trained against the HalfCheetah Mixed multi-demonstrator dataset using REx penalty coefficients $\beta \in \{0, 5, 10, 20\}$.

3.1 RISK EXTRAPOLATION (REX)

Risk Extrapolation (REx) is a particular domain generalization method that aims to enforce strict equality of risk (i.e., loss) across all training domains (Krueger et al., 2020). This helps guarantee that a model trained with REx will be invariant; i.e., it should also achieve (roughly) the same loss on test domains that are in the *affine span* of the training domains. We focus on REx as the domain generalization method in this paper. However, other domain generalization methods are equally applicable here (Arjovsky et al., 2019).

The resulting "flattening of the risk plane" is demonstrated in Fig. 1a, which shows the evaluation results on a range of OOD datasets using an environment model trained with REx. A simple risk extrapolation approach (**V-REx**) penalizes the variance of the training risks:

$$\mathcal{R}_{\text{V-REx}}(\theta) \doteq \beta \, \text{Var}(\{\mathcal{R}_1(\theta), ..., \mathcal{R}_n(\theta)\}) + \sum_{e=1}^{n} \mathcal{R}_e(\theta) \tag{1}$$

where $\mathcal{R}_e$ is the risk on the e-th domain, and β controls the strength of the variance regularizer.

3.2 DOMAIN-INVARIANT MODEL-BASED OFFLINE RL (DIMORL)

Since DIMORL combines both MOPO and REx, we test it in isolation as well as in conjunction with MOPO's uncertainty penalty term. We use β and λ to denote the REx and MOPO penalty terms, respectively. Environment models $p_{\theta,\phi}(s_{t+1}, r_t | s_t, a_t)$ were trained against multi-demonstrator datasets $\mathcal{D}_{\mathcal{E}} = \bigcup_{e=1}^{M} \mathcal{D}_e$, where the outputs of the models parameterize a Gaussian distribution with diagonal covariance matrix: $\mathcal{N}(s_{t+1}, r_t; \mu_\theta^i(s, a), \Sigma_\phi^i(s, a))$. Individual risks, $\mathcal{R}_e$ were calculated for each demonstrator's data, and REx used to reduce the variance across the demonstrators in the multi-demonstrator dataset. Further details are provided in Appendix A.

4 EXPERIMENTS

As a proxy for real-world demonstrators, we trained a selection of policies online against the OpenAI Gym MuJoCo Hopper, HalfCheetah and Walker2d environments (Brockman et al., 2016; Todorov et al., 2012) using the soft actor-critic (SAC) algorithm (Haarnoja et al., 2018a;b). Subsets comprising five of these pseudo-demonstrators were used to generate three multi-demonstrator datasets for each environment i.e. Novice, Mixed, and Expert. See Appendix B for details of the SAC pseudo-demonstrators and multi-demonstrator datasets produced.

| | Mult-Demonstrator Dataset | | | | | | | | |
| | Novice | | | Mixed | | | Experienced | | |
Environment	Max Dem. Return	DIMORL Return	(β,λ,h)	Max Dem. Return	DIMORL Return	(β,λ,h)	Max Dem. Return	DIMORL Return	(β,λ,h)
HalfCheetah	7663	**9056** ± 122	(0,1,5)	11032	6687 ± 4888	(0,1,5)	14511	4547 ± 288	(10,5,10)
Hopper	3239	**3482** ± 23	(20,5,5)	3553	**3569** ± 40	(20,5,50)	3553	3493 ± 33	(0,5,50)
Walker2D	1587	**1594** ± 1598	(20,0,10)	5430	2265 ± 141 (2)	(20,0,5)	5430	4796 ± 113	(20,0,10)

Table 1: Environment models trained with REx ($\beta > 0$) yielded policies with the highest average returns in two-thirds of datasets across three MuJoCo environments. For the Novice multi-demonstrator datasets and Hopper Mixed dataset, the policies learned using DIMORL had higher average returns (bolded values) than any of the individual demonstrators used to generate the dataset. The average policy evaluation returns ± one standard deviation over three random seeds are shown, along with the REx penalty coefficient β, MOPO penalty coefficient λ, and roll-out length h used.

4.1 Domain Generalization Performance of Environment Models

We found that environment models trained with REx achieved higher average and worst-case out-of-distribution (OOD) log-likelihoods for each environment and multi-demonstrator dataset. Across all environments, OOD performance was worst for the "Experienced" dataset, and was most greatly improved by the incorporation of REx to model training. As demonstrated by Figure 1b, the average and worst case performance generally continued to improve as the REx penalty coefficient was increased from 5 to 20. While this might encourage the use of larger coefficients, we did not find the domain generalization performance of the models to be well correlated with the average returns of policies trained using them. This is discussed further in Appendix C.

4.2 Offline Agent Training

Policies learned using environment models trained with REx obtained the highest average return for two-thirds of multi-demonstrator datasets across the MuJoCo environments investigated. Of these, the largest REx penalty coefficient investigated ($\beta = 20$) yielded the highest return in all but one setting. Across all environments, a policy trained offline obtained a higher average return for the "Novice" multi-demonstrator dataset than any of the individual demonstrators that were used to generate the dataset. However, this was not the case for two of the three "Mixed" datasets, or any of the "Experienced" datasets. Table 1 provides an overview of the results, and the hyperparameter settings used to achieve them. The complete results including further discussion are provided in Appendix D.

We additionally found that environment models trained with REx were more robust to noisy initial state distributions; highlighting the benefits that improved domain generalization performance can bring to policy training (see Appendix F.1). We further attempted to learn policies using roll-out starting locations sampled from datasets that were not used to train the environment models, with the expectation that environment models trained with REx would be much more robust to such distributional shifts. However, no good policies were learned under any settings investigated thus far (see Appending D.2), likely due to the distributional shift being simply too extreme.

4.3 Increased Policy Training Stability

In an attempt to pinpoint the sources of the benefits brought by environment models trained with REx, we analyzed the agent training performance and found that, for the HalfCheetah environment, the Q-functions of soft actor-critic policies were often less prone to becoming degenerate when using REx penalty coefficients $\beta \in \{5, 10\}$. This is demonstrated in Fig. 2. We present two hypotheses regarding the source of the Q-function instability, and why environment models trained with REx may be yielding improvements.

Degenerate Predictions: From the evaluation returns shown in Figure 2b, we know that the reward models can make degenerate predictions, which could lead to instability in Q-function training. However, the returns shown were obtained over 1000 step episodes, whereas in policy training roll-outs of 5-10 steps were typically used. The learned reward models would therefore need to

| (a) Average Q-Values | (b) Evaluation Returns |

Figure 2: Environment models trained using larger REx penalty coefficients were observed to be more robust to the Q-function being learned as part of SAC policy training becoming degenerate. This is demonstrated by the relative stability of the average Q-values. When evaluating policies against the learned environment model being used to train them, we observe extreme episode returns for those models trained with no or low REx penalty coefficients. Results reported for Mixed HalfCheetah multi-demonstrator dataset, with MOPO penalty coefficient $\lambda = 0$ and roll-out length of $h = 5$.

make degenerate predictions within 5-10 steps to negatively impact Q-function learning. We have observed cases of this occurring (see Appendix E), however it does not appear to be a necessary condition for Q-function instability to occur. Note, rather than the issue lying solely with the reward model, it is likely that errors in the dynamics models will also be contributing by leading the agent into unnatural states. Further analysis of the trajectories produced in the learned environment is necessary.

Environment Model Complexity: The environment model may be less well-behaved and more complex than the real environment. For instance, a small change in the current state could have a large and unpredictable impact on the predicted next state. If we assume the neural network used has sufficient capacity and is provided with sufficient data to capture the real environment, the function approximation component of the classic deadly triad (Sutton & Barto, 2018) would theoretically not be an issue. However, the environment model state representation may fail to capture all quirks in the environment model, resulting in function approximation continuing to be problematic. That is: function approximation is not an issue if we can perfectly approximate the function, and perhaps the actor and critic can manage to do that on the real environment but struggle to do the same for the learned environment model.

4.4 INCREASED EXPLORATION DURING POLICY TRAINING

In addition to improving the stability of policy training, we hypothesise that the improved domain generalization performance of environment models trained with REx may enable increased exploration of the state-action space, leading to the identification of more optimal policies. To evaluate the extent of exploration during policy training, we used PCA to project transition records into two-dimensions, such that they could be visualised. Initial experiments indicate this technique may hold promise (see Appendix F.2), however further work is necessary to ensure observed differences cannot simply be explained by the fraction of the original data's variance captured by the projection.

5 CONCLUSIONS

In this paper, we have highlighted and exploited the opportunity to take advantage of knowledge that static datasets have been collected from multiple demonstrators, which we believe to be the most natural setting. We presented a practical algorithm for Domain-Invariant Model-based Offline RL (DIMORL), and have illustrated that this method may increase the stability of policy learning, enable greater exploration, and yield more optimal policies in many settings. Further experimentation and analysis is needed to validate our findings, and to fully take advantage of the algorithm's potential.

REFERENCES

Rishabh Agarwal, Dale Schuurmans, and Mohammad Norouzi. An Optimistic Perspective on Offline Reinforcement Learning. *37th International Conference on Machine Learning, ICML 2020*, PartF168147-1:92–102, jul 2019. doi: 10.48550/arxiv.1907.04543. URL https://arxiv.org/abs/1907.04543v4.

Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant Risk Minimization. jul 2019. doi: 10.48550/arxiv.1907.02893. URL https://arxiv.org/abs/1907.02893v3.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba Openai. OpenAI Gym. jun 2016. doi: 10.48550/arxiv.1606.01540. URL https://arxiv.org/abs/1606.01540v1.

Jacob Buckman, Carles Gelada, and Marc G. Bellemare. The Importance of Pessimism in Fixed-Dataset Policy Optimization. sep 2020. doi: 10.48550/arxiv.2009.06799. URL https://arxiv.org/abs/2009.06799v3.

Catherine Cang, Aravind Rajeswaran, Pieter Abbeel, and Michael Laskin. Behavioral Priors and Dynamics Models: Improving Performance and Domain Transfer in Offline RL. jun 2021. doi: 10.48550/arxiv.2106.09119. URL https://arxiv.org/abs/2106.09119v2.

Kurtland Chua, Roberto Calandra, Rowan McAllister, and Sergey Levine. Deep Reinforcement Learning in a Handful of Trials using Probabilistic Dynamics Models. *Advances in Neural Information Processing Systems*, 2018-Decem:4754–4765, may 2018. ISSN 10495258. doi: 10.48550/arxiv.1805.12114. URL https://arxiv.org/abs/1805.12114v2.

Ignasi Clavera, Jonas Rothfuss, John Schulman, Yasuhiro Fujita, Tamim Asfour, and Pieter Abbeel. Model-Based Reinforcement Learning via Meta-Policy Optimization. sep 2018. doi: 10.48550/arxiv.1809.05214. URL https://arxiv.org/abs/1809.05214v1.

Dima Damen, Hazel Doughty, Giovanni Maria Farinella, , Antonino Furnari, Jian Ma, Evangelos Kazakos, Davide Moltisanti, Jonathan Munro, Toby Perrett, Will Price, and Michael Wray. Rescaling egocentric vision: Collection, pipeline and challenges for epic-kitchens-100. *International Journal of Computer Vision (IJCV)*, 130:33–55, 2022. URL https://doi.org/10.1007/s11263-021-01531-2.

Justin Fu, Aviral Kumar, Ofir Nachum, Google Brain, George Tucker Google Brain, and Sergey Levine. D4RL: Datasets for Deep Data-Driven Reinforcement Learning. apr 2020. doi: 10.48550/arxiv.2004.07219. URL https://arxiv.org/abs/2004.07219v4.

Scott Fujimoto, David Meger, and Doina Precup. Off-Policy Deep Reinforcement Learning without Exploration. *36th International Conference on Machine Learning, ICML 2019*, 2019-June:3599–3609, dec 2018. doi: 10.48550/arxiv.1812.02900. URL https://arxiv.org/abs/1812.02900v3.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft Actor-Critic: Off-Policy Maximum Entropy Deep Reinforcement Learning with a Stochastic Actor. *35th International Conference on Machine Learning, ICML 2018*, 5:2976–2989, jan 2018a. doi: 10.48550/arxiv.1801.01290. URL https://arxiv.org/abs/1801.01290v2.

Tuomas Haarnoja, Aurick Zhou, Kristian Hartikainen, George Tucker, Sehoon Ha, Jie Tan, Vikash Kumar, Henry Zhu, Abhishek Gupta, Pieter Abbeel, and Sergey Levine. Soft Actor-Critic Algorithms and Applications. dec 2018b. doi: 10.48550/arxiv.1812.05905. URL https://arxiv.org/abs/1812.05905v2.

Michael Janner, Justin Fu, Marvin Zhang, and Sergey Levine. When to Trust Your Model: Model-Based Policy Optimization. *Advances in Neural Information Processing Systems*, 32, 06 2019. ISSN 10495258. doi: 10.48550/arxiv.1906.08253. URL https://arxiv.org/abs/1906.08253v3.

Rahul Kidambi, Aravind Rajeswaran, Praneeth Netrapalli, and Thorsten Joachims. MOReL : Model-Based Offline Reinforcement Learning. *Advances in Neural Information Processing Systems*, 2020-Decem, may 2020. ISSN 10495258. doi: 10.48550/arxiv.2005.05951. URL https://arxiv.org/abs/2005.05951v3.

David Krueger, Ethan Caballero, Joern-Henrik Jacobsen, Amy Zhang, Jonathan Binas, Dinghuai Zhang, Remi Le Priol, and Aaron Courville. Out-of-Distribution Generalization via Risk Extrapolation (REx). mar 2020. doi: 10.48550/arxiv.2003.00688. URL https://arxiv.org/abs/2003.00688v5.

Thanard Kurutach, Ignasi Clavera, Yan Duan, Aviv Tamar, and Pieter Abbeel. Model-Ensemble Trust-Region Policy Optimization. *6th International Conference on Learning Representations, ICLR 2018 - Conference Track Proceedings*, feb 2018. doi: 10.48550/arxiv.1802.10592. URL https://arxiv.org/abs/1802.10592v2.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline Reinforcement Learning: Tutorial, Review, and Perspectives on Open Problems. 05 2020. doi: 10.48550/arxiv.2005.01643. URL https://arxiv.org/abs/2005.01643v3.

Tatsuya Matsushima, Hiroki Furuta, Yutaka Matsuo, Ofir Nachum Google Research, and Shixiang Shane Gu Google Research. Deployment-Efficient Reinforcement Learning via Model-Based Offline Optimization. jun 2020. doi: 10.48550/arxiv.2006.03647. URL https://arxiv.org/abs/2006.03647v2.

Rafael Figueiredo Prudencio, Marcos R. O. A. Maximo, and Esther Luna Colombini. A Survey on Offline Reinforcement Learning: Taxonomy, Review, and Open Problems. mar 2022. doi: 10.48550/arxiv.2203.01387. URL https://arxiv.org/abs/2203.01387v2.

Aravind Rajeswaran, Sarvjeet Ghotra, Balaraman Ravindran, and Sergey Levine. EPOpt: Learning Robust Neural Network Policies Using Model Ensembles. *5th International Conference on Learning Representations, ICLR 2017 - Conference Track Proceedings*, oct 2016. doi: 10.48550/arxiv.1610.01283. URL https://arxiv.org/abs/1610.01283v4.

Takuma Seno and Michita Imai. d3rlpy: An Offline Deep Reinforcement Learning Library. nov 2021. doi: 10.48550/arxiv.2111.03788. URL https://arxiv.org/abs/2111.03788v1.

Richard S Sutton and Andrew G Barto. *Reinforcement Learning: An Introduction.* Adaptive computation and machine learning series. The MIT Press, Cambridge, MA, second edition edition, 2018. ISBN 9780262039246.

Emanuel Todorov, Tom Erez, and Yuval Tassa. MuJoCo: A physics engine for model-based control. *IEEE International Conference on Intelligent Robots and Systems*, pp. 5026–5033, 2012. ISSN 21530858. doi: 10.1109/IROS.2012.6386109.

Yue Wu, Shuangfei Zhai, Nitish Srivastava, Joshua Susskind, Jian Zhang, Ruslan Salakhutdinov, and Hanlin Goh. Uncertainty Weighted Actor-Critic for Offline Reinforcement Learning. may 2021. doi: 10.48550/arxiv.2105.08140. URL https://arxiv.org/abs/2105.08140v1.

Tianhe Yu, Garrett Thomas, Lantao Yu, Stefano Ermon, James Zou, Sergey Levine, Chelsea Finn, and Tengyu Ma. MOPO: Model-based Offline Policy Optimization. *Advances in Neural Information Processing Systems*, 2020-Decem, may 2020. ISSN 10495258. doi: 10.48550/arxiv.2005.13239. URL https://arxiv.org/abs/2005.13239v6.

Tianhe Yu, Aviral Kumar, Rafael Rafailov, Aravind Rajeswaran, Sergey Levine, and Chelsea Finn. COMBO: Conservative Offline Model-Based Policy Optimization. feb 2021. doi: 10.48550/arxiv.2102.08363. URL https://arxiv.org/abs/2102.08363v2.

A DIMORL Implementation Details

The MOPO algorithm (Yu et al., 2020) and codebase[2] was used as the basis for DIMORL. Our modified version is outlined in Algorithm 1. We trained environment models $p_{\theta,\phi}(s_{t+1}, r_t | s_t, a_t)$ against multi-demonstrator datasets $\mathcal{D}_\mathcal{E} = \bigcup_{e=1}^{M} \mathcal{D}_e$, where the outputs of the models parameterise a Gaussian distribution with diagonal covariance matrix: $\mathcal{N}(s_{t+1}, r_t; \mu_\theta^i(s,a), \Sigma_\phi^i(s,a))$.

Individual negative log-likelihood values, $\mathcal{R}_{nll}^e$, are calculated for each demonstrator's data, $\mathcal{D}_e$. These are then used to calculate the MOPO V-REx loss given by Equation 2, where β is the REx penalty coefficient. $\mathcal{R}_{wr}$ is an ℓ_2 weight regularisation penalty, and $\mathcal{R}_{vb}$ is a loss term relating to the learning of variance bounds. Chua et al. (2018) highlight that outside of the training distribution the predicted variance can assume arbitrary values, and can both collapse to zero or explode to infinity (in contrast to models like GPs where variance values are better behaved). Chua et al. (2018) found that bounding the output variance such that it cannot exceed the range seen in the training data was beneficial, and so include the $\mathcal{R}_{vb}$ penalty.

$$\mathcal{R}_{MOPO\ V\text{-}REx} = \sum_{e=1}^{M} [\mathcal{R}_{nll}^e] + \beta \cdot \text{Var}\left(\mathcal{R}_{nll}^1, \mathcal{R}_{nll}^2, \ldots, \mathcal{R}_{nll}^M\right) + \mathcal{R}_{wr} + \mathcal{R}_{vb} \tag{2}$$

Algorithm 1 DIMORL - an extension of MOPO(Yu et al., 2020) to include REx in environment model training

---

Require: : MOPO reward penalty coefficient λ, roll-out length h, roll-out batch size b, REx penalty coefficient β
1: Train on batch data $\mathcal{D}_{\text{env}}$ an ensemble of N probabilistic dynamics models $\{p_{\theta,\phi}(s_{t+1}, r_t | s_t, a_t) = \mathcal{N}(\mu_\theta^i(s,a), \Sigma_\phi^i(s,a))\}_{i=1}^{N}$ with REx penalty coefficient β
2: Initialise policy π^{off} and empty replay buffer $\mathcal{D}_{\text{model}} \leftarrow \varnothing$
3: **for** epoch $1, 2, \ldots$ **do**
4:     **for** $1, 2, \ldots, b$ (in parallel) **do**
5:         Sample state s_1 from $\mathcal{D}_{\text{env}}$ for the initialisation of the roll-out
6:         **for** $j = 1, 2, \ldots, h$ **do**
7:             Sample an action $a_j \sim \pi(s_j)$
8:             Randomly pick dynamics $\hat{T}$ from $\{\hat{T}^i\}_{i=1}^{N}$ and sample $s_{j+1}, r_j \sim \hat{T}(s_j, a_j)$
9:             Compute $\tilde{r}_j = r_j - \lambda \max_{i=1}^{N} ||\Sigma_\phi^i(s_j, a_j)||_F$
10:            Add sample $(s_j, a_j, \tilde{r}_j, s_{j+1})$ to $\mathcal{D}_{\text{model}}$
11:     Drawing samples from $\mathcal{D}_{\text{env}} \bigcup \mathcal{D}_{\text{model}}$, use SAC to update π^{off}

Environment model training was split into two phases:

1. **ERM:** No REx penalty is used (i.e., $\beta = 0$) until the original MOPO termination condition is reached: the loss on a held-out evaluation dataset does not decrease by more than 1 % for any model in the ensemble for five consecutive epochs Yu et al. (2020).

2. **REx:** Training was then allowed to continue for the same number of epochs completed in the ERM phase, with the REx penalty coefficient now set to a user defined value. We investigated REx penalty coefficients $\beta \in \{0, 5, 10, 20\}$ in our work.

B SAC Demonstrators and Multi-Demonstrator Datasets

To proxy for real-world demonstrators (whether humans, or pre-existing control policies), we trained a selection of demonstrator policies, π^e, using online RL algorithms and the OpenAI Gym MuJoCo Hopper, HalfCheetah and Walker2d environments. The sole purpose of these policies was to generate individual demonstrator datasets, $\mathcal{D}_e$, for use in training environment models. To increase data diversity, additional demonstrator datasets are created using a random policy, $\pi^\mathcal{N}$. Each

---

[2]https://github.com/tianheyu927/mopo

Environment	Online Training Steps (millions)	Policy Return Softlearning	Policy Return D3RLPY
HalfCheetah	0.1	5126	3744
HalfCheetah	0.2	-	5050
HalfCheetah	0.25	7663	-
HalfCheetah	0.5	9324	7225
HalfCheetah	1	11032	8300
HalfCheetah	2	14511	9022
HalfCheetah	3	14215	-
Hopper	0.1	667	2567
Hopper	0.2	3239	1974
Hopper	0.4	3414	2395
Hopper	0.6	3051	2158
Hopper	0.8	3524	2625
Hopper	1.0	3553	3179
Walker2d	0.1	319	369
Walker2d	0.2	-	1587
Walker2d	0.25	1225	-
Walker2d	0.5	3004	3900
Walker2d	1	4139	4312
Walker2d	2	4134	5430
Walker2d	3	4795	-

Table 2: Two implementations (Softlearning (Haarnoja et al., 2018a;b) and D3RLPY Seno & Imai (2021)) of the online soft actor-critic (SAC) algorithm (Haarnoja et al., 2018a;b) were used to create pseudo-demonstrators by taking snapshots of the policy being learned. As would be expected, the return of the policy generally increases with the amount of training.

dataset comprises N_e transition tuples of the form: (s^e, a^e, s'^e, r^e, e). The unique demonstrator identifier e is used during the training of dynamics models with Risk Extrapolation (REx) to identify individual domains. The identifier is simply a number, and provides no information about the demonstrator. Independently sampled evaluation datasets are also created for each demonstrator. Collections of M individual datasets are combined to produce multi-demonstrator datasets: $\mathcal{D}_{\mathcal{E}} = \{(s_i^e, a_i^e, s_i'^e, r_i^e, e)_{i=1}^{N_e}\}_{e=1}^{M}$.

As a proxy for real-world demonstrators, a selection of soft actor-critic (SAC) (Haarnoja et al., 2018a;b) policies were trained online. To increase the diversity of the demonstrators, we used two different implementations of the SAC algorithm: **Softlearning**, the official SAC implementation (Haarnoja et al., 2018a;b); and **D3RLPY**, which implements a version of SAC with delayed policy updates (Seno & Imai, 2021). Policies were trained using the default hyperparameters provided in their respective repositories. As shown in Table 2, snapshots of each policy were taken at regular intervals during training to emulate demonstrators with varying degrees of skill.

We selected subsets of five pseudo-demonstrators for each MuJoCo environment to produce three multi-demonstrator datasets: Novice, Mixed, and Experienced. As their names indicate, the Novice and Mixed datasets comprised transition records generated using pseudo-demonstrators trained online for minimal and extended number of training steps respectively, while Mixed uses a combination of each. Table 3 shows the individual pseudo-demonstrator policies used to create the datasets. Each policy contributed 20,000 transition records, and so each multi-demonstrator dataset consists of a total of 100,000 records.

C ENVIRONMENT MODEL OOD PERFORMANCE

Figure 3 shows the average and worst-case OOD log-likelihoods and mean-squared errors (MSEs) obtained for all MuJoCo environments and multi-demonstrator datasets. Across all environments and multi-demonstrator datasets, environment models trained using REx achieved improved average and worst-case log-likelihoods. The results were more mixed for the MSE values–small increases in MSE were sometimes observed, as can be seen for the Walker2d experienced dataset in Figure 3f.

Environment	Policy Identifier	Multi-Demonstrator Dataset								
		Novice			Mixed			Experienced		
		Type	Steps	Return	Type	Steps	Return	Type	Steps	Return
HalfCheetah	1	Rand	-	-	Rand	-	-	SL	1	11032
HalfCheetah	2	SL	0.1	5126	SL	0.25	7663	SL	2	**14511**
HalfCheetah	3	SL	0.25	**7663**	SL	1	**11032**	SL	3	14215
HalfCheetah	4	D3	0.1	3744	D3	0.2	5050	D3	1	8300
HalfCheetah	5	D3	0.2	5050	D3	2	9022	D3	2	9022
Hopper	1	Rand	-	-	Rand	-	-	SL	0.6	3051
Hopper	2	SL	0.1	667	SL	0.2	3239	SL	0.8	3524
Hopper	3	SL	0.2	**3239**	SL	1	**3553**	SL	1	**3553**
Hopper	4	D3	0.1	2567	D3	0.2	1974	D3	0.8	2625
Hopper	5	D3	0.2	1974	D3	1	3179	D3	1	3179
Walker2D	1	Rand	-	-	Rand	-	-	SL	1	4139
Walker2D	2	SL	0.1	319	SL	0.25	1225	SL	2	4134
Walker2D	3	SL	0.25	1225	SL	1	4139	SL	3	4795
Walker2D	4	D3	0.1	369	D3	0.2	1587	D3	1	4312
Walker2D	5	D3	0.2	**1587**	D3	2	**5430**	D3	2	**5430**

Table 3: Individual demonstrator policies the comprise the Novice, Mixed and Experienced multi-demonstrator datasets, including the return of the policy. Each individual demonstrator contributed 20,000 transition records. *Rand* denotes a random policy, *SL* a policy trained using the Softlearning library, and *D3* a policy trained using the D3RLPY library.

The discrepancy likely arises given it was the variance of log-likelihoods across training domains that was minimised during model training. Future experiments could evaluate the impact of updating the training procedure to minimise the variance of the training MSEs, or both the log-likelihoods and MSEs simultaneously.

Increasing the REx penalty coefficient leads to higher log-likelihood values in the majority of cases. One exception is the peak in worst-case performance that all Hopper multi-demonstrator datasets exhibit when $\beta = 10$. This indicates that the REx penalty coefficient is still a hyperparameter that needs to be appropriately tuned.

C.1 CORRELATION BETWEEN ENVIRONMENT MODEL OOD PERFORMANCE AND POLICY RETURNS

As demonstrated by Figure 4, no correlation is observed between the average OOD log-likelihood of environment models and the average evaluation return of policies trained using them. It should, however, be noted that the distribution of roll-out starting locations differs across the experiments, which will have had an influence on the observed results.

D OFFLINE TRAINING RESULTS

D.1 ID ROLL-OUT STARTING LOCATIONS

The results of experiments run against multi-demonstrator datasets generated using the HalfCheetah, Hopper and Walker2d environments are shown in Table 4, Table 5 and Table 6 respectively. In all of these experiments, during policy training, roll-out starting locations were drawn from the same dataset used to train the environment model.

As noted in the main text, across all environments, a policy trained offline with DIMORL obtained a higher average return for the Novice multi-demonstrator dataset than any of the individual demonstrators that were used to generate the dataset. The same consistency was not observed for the Mixed or Experienced datasets. This reaffirms the importance of action diversity in offline model-based methods, whereas model-free techniques are potentially better suited to datasets collected from less-diverse, more experienced demonstrators Yu et al. (2020).

We also note the lack of consistency regarding the optimal MOPO penalty coefficient. Yu et al. (2021) highlight the poor calibration between MOPO penalty and actual model error, which is likely responsible for the inconsistency observed.

Dataset	Roll-out Length	MOPO Pen. Coeff, λ	REx Penalty Coefficient, β			
			0	5	10	20
Novice	5	0	8591 ± 417	5917 ± 2700	6723 ± 1616	8157 ± 908
Novice	5	1	**9056 ± 122**	7188 ± 1800	7591 ± 647	6352 ± 3320
Novice	5	5	7134 ± 263	3066 ± 2962	2242 ± 3340	4349 ± 3135
Novice	10	0	5511 ± 4172	6553 ± 1776	2822 ± 2288	4235 ± 3419
Novice	10	1	8977 ± 190	6774 ± 2508	6705 ± 1704	5719 ± 4102
Novice	10	5	7004 ± 312	2259 ± 3344	-197 ± 157	2188 ± 3283
Novice	20	0	4062 ± 4340 (2)	6344 ± 2459	2772 ± 2399	5410 ± 2667 (2)
Novice	20	1	4207 ± 4554	7392 ± 1953	5662 ± 1463 (2)	4070 ± 4113 (2)
Novice	20	5	3285 ± 3705 (2)	2329 ± 3531	-111 ± 39 (2)	3078 ± 3147 (2)
Novice	50	0	-205 ± 0 (1)	3700 ± 133 (2)	4210 ± 902 (2)	3839 ± 4340 (2)
Novice	50	1	4219 ± 4410 (2)	4847 ± 0 (1)	5602 ± 221 (2)	4249 ± 4182 (2)
Novice	50	5	3537 ± 3802 (2)	-82 ± 0 (1)	-152 ± 17	2842 ± 3143 (2)
Mixed	5	0	4961 ± 3372	2627 ± 1646	3160 ± 597	3273 ± 2486
Mixed	5	1	**6687 ± 4888**	4230 ± 1853	3195 ± 1720	4579 ± 77
Mixed	5	5	2374 ± 3472	6633 ± 499	4973 ± 3564	5161 ± 3728
Mixed	5	10	-197 ± 73	2362 ± 2944	2054 ± 3012	477 ± 445
Mixed	5	20	-131 ± 269	1588 ± 2415	84 ± 281	397 ± 136
Mixed	10	0	-369 ± 93	1329 ± 1448 (2)	1983 ± 1172	3087 ± 527
Mixed	10	1	-211 ± 147	3906 ± 34 (2)	3592 ± 805	3843 ± 966
Mixed	10	5	-379 ± 360	4464 ± 3360	4616 ± 3467	4722 ± 3401
Mixed	10	10	-67 ± 280	1637 ± 2564	2381 ± 3463	3904 ± 2862
Mixed	10	20	-359 ± 219	-196 ± 65	135 ± 250	-557 ± 238
Experienced	5	0	40 ± 714	-279 ± 344	-369 ± 112	-252 ± 161
Experienced	5	1	1607 ± 2549	-348 ± 83	-145 ± 125	-331 ± 21
Experienced	5	5	1424 ± 1799	1453 ± 2458	3612 ± 979	3629 ± 747
Experienced	10	0	-461 ± 17 (2)	-404 ± 97	-455 ± 114	-344 ± 96
Experienced	10	1	-178 ± 48	-665 ± 248	-128 ± 125	-301 ± 107
Experienced	10	5	-239 ± 42 (2)	1227 ± 2208	**4547 ± 288**	3492 ± 614
Experienced	20	5	-56 ± 0 (1)	634 ± 1594	3291 ± 2146	2958 ± 1644

Table 4: Average and standard deviation, over three random seeds, of the evaluation returns for policies learned using dynamics models trained against multi-demonstrator datasets generated from the HalfCheetah environment. The overall highest return for each multi-demonstrator dataset has been bolded. If a value has a number in brackets next to it then only this number of agents completed 0.5 million steps of training. If there is no value then none of the agents completed 0.5 million steps of training.

Dataset	Roll-out Length	MOPO Pen. Coeff, λ	REx Penalty Coefficient, β			
			0	5	10	20
Novice	5	0	1184 ± 772	200 ± 11	483 ± 242	210 ± 44
Novice	5	1	1386 ± 1444	1240 ± 550	567 ± 154	1104 ± 416
Novice	5	5	502 ± 214	788 ± 90	1473 ± 1423	1305 ± 1560
Novice	10	0	978 ± 69	1558 ± 832	1323 ± 395	1686 ± 815
Novice	10	1	1796 ± 320	1506 ± 274	2313 ± 938	1829 ± 694
Novice	10	5	3117 ± 488	3073 ± 335	3056 ± 516	3471 ± 25
Novice	20	0	2591 ± 1100	2412 ± 840	2052 ± 992	2596 ± 600
Novice	20	1	2350 ± 1270	1804 ± 1165	2356 ± 223	3254 ± 303
Novice	20	5	3001 ± 622	2621 ± 1165	2788 ± 932	3449 ± 15
Novice	50	0	2437 ± 1081	2570 ± 1331	2761 ± 981	2145 ± 909
Novice	50	1	2467 ± 1165	2809 ± 724	2708 ± 1097	3461 ± 26
Novice	50	5	2527 ± 1236	2632 ± 845	2762 ± 1017	**3482 ± 23**
Novice	100	5	3411 ± 0 (1)	3489 ± 12 (2)	3220 ± 396	3444 ± 0 (1)
Mixed	5	0	586 ± 128	602 ± 93	667 ± 128	459 ± 189
Mixed	5	1	664 ± 142	781 ± 257	574 ± 137	781 ± 24
Mixed	5	5	645 ± 119	749 ± 28	738 ± 34	1016 ± 150
Mixed	10	0	800 ± 33	876 ± 170	993 ± 325	1782 ± 1160
Mixed	10	1	1318 ± 622	911 ± 163	950 ± 468	919 ± 116
Mixed	10	5	1398 ± 639	1923 ± 1101	1491 ± 1481	2953 ± 518
Mixed	20	0	2521 ± 356	2706 ± 1232	2936 ± 823	1928 ± 731
Mixed	20	1	2208 ± 771	1988 ± 1149	1916 ± 780	2369 ± 857
Mixed	20	5	3483 ± 85	3558 ± 24	2864 ± 973	3320 ± 289
Mixed	50	0	2607 ± 863	2323 ± 1100	2010 ± 1146	2983 ± 724
Mixed	50	1	1443 ± 141	2940 ± 918	2598 ± 677	2767 ± 1121
Mixed	50	5	2839 ± 1049	3560 ± 48	3542 ± 50	**3569 ± 40**
Mixed	100	5	3226 ± 0 (1)	3529 ± 33	3142 ± 609	3445 ± 156
Experienced	5	0	638 ± 231	355 ± 49	689 ± 48	380 ± 232
Experienced	5	1	607 ± 205	505 ± 254	316 ± 184	225 ± 107
Experienced	5	5	517 ± 200	304 ± 194	538 ± 104	601 ± 73
Experienced	10	0	864 ± 74	542 ± 204	757 ± 114	904 ± 113
Experienced	10	1	971 ± 393	429 ± 593	827 ± 45	842 ± 122
Experienced	10	5	1813 ± 1214	1191 ± 972	781 ± 85	683 ± 162
Experienced	20	0	2199 ± 811	1735 ± 1287	517 ± 354	1297 ± 239
Experienced	20	1	2472 ± 1024	868 ± 447	880 ± 130	984 ± 168
Experienced	20	5	1030 ± 640	1632 ± 1343	1006 ± 44	1774 ± 1171
Experienced	50	0	2811 ± 904	1424 ± 1528	960 ± 745	1756 ± 1035
Experienced	50	1	2479 ± 1002	2098 ± 1068	931 ± 663	1242 ± 134
Experienced	50	5	**3493 ± 33**	1343 ± 1142	3441 ± 52	2443 ± 782
Experienced	100	5	3318 ± 0 (1)	334 ± 0 (1)	-	-

Table 5: Average and standard deviation, over three random seeds, of the evaluation returns for policies learned using dynamics models trained against multi-demonstrator datasets generated from the Hopper environment. The overall highest return for each multi-demonstrator dataset has been bolded. If a value has a number in brackets next to it then only this number of agents completed 1 million steps of training. If there is no value then none of the agents completed 1 million steps of training.

Figure 3: Environment models trained with REx typically achieve improved average and worst-case out-of-distribution performance, both in terms of log-likelihood (LL) and mean-squared error (MSE).

Figure 4: No correlation is observed between the average OOD log-likelihood of environment models and the average evaluation return of policies trained using them. The results shown are for a roll-out length of 5. A line of best fit (LBF) is shown, along with the corresponding R^2 value.

D.2 OOD Roll-out Starting Locations

We refer to roll-out starting locations as being OOD if they are sampled from any dataset other than the one used to train the environment model that is used in policy training. The results of experiments run against multi-demonstrator datasets generated using the HalfCheetah and Hopper environments are shown in Table 7 and Table 8 respectively. roll-out starting locations for these experiments were drawn from the following datasets:

Dataset	Roll-out Length	MOPO Pen. Coeff, λ	REx Penalty Coefficient, β			
			0	5	10	20
Novice	5	0	263 ± 203	412 ± 263	501 ± 89	1068 ± 849
Novice	5	1	214 ± 222	98 ± 141	-2 ± 1	-2 ± 0
Novice	5	5	-2 ± 0	-3 ± 0	-2 ± 0	-3 ± 0
Novice	10	0	327 ± 62	521 ± 182	817 ± 242	**1594 ± 1598**
Novice	10	1	83 ± 121	325 ± 364	82 ± 118	86 ± 125
Novice	10	5	-3 ± 0	-2 ± 1	-2 ± 0	-3 ± 0
Mixed	5	0	-1 ± 3 (2)	500 ± 508	1721 ± 1700	**2265 ± 141 (2)**
Mixed	5	1	1 ± 6	1544 ± 2187	245 ± 349	-2 ± 0
Mixed	5	5	-3 ± 0	-3 ± 0	-3 ± 0	-3 ± 0
Mixed	10	0	2050 ± 1922	1614 ± 2099	1095 ± 704	1653 ± 1563
Mixed	10	1	-2 ± 0	1501 ± 2125	273 ± 390	-2 ± 0
Mixed	10	5	-3 ± 0	-3 ± 0	-2 ± 1	-2 ± 1
Experienced	5	0	1685 ± 1850	144 ± 10	316 ± 232	947 ± 263
Experienced	5	1	-3 ± 0 (2)	2318 ± 2326 (2)	1297 ± 1839	3080 ± 2202
Experienced	5	5	-3 ± 0	-4 ± 0	-3 ± 0	-4 ± 0
Experienced	10	0	3245 ± 1375	3121 ± 1667	3524 ± 1791	**4796 ± 113**
Experienced	10	1	1602 ± 2270	4785 ± 126	979 ± 1389	1501 ± 2127
Experienced	10	5	-3 ± 1	-3 ± 0	-3 ± 0	-3 ± 0

Table 6: Average and standard deviation, over three random seeds, of the evaluation returns for policies learned using dynamics models trained against multi-demonstrator datasets generated from the Walker2d environment. The overall highest return for each multi-demonstrator dataset has been bolded. If a value has a number in brackets next to it then only this number of agents completed 3 million steps of training. If there is no value then none of the agents completed 3 million steps of training.

Env. Model Train. Dataset	Roll-out Start. Loc. Dataset	Roll-out Length	REx Penalty Coefficient, β			
			0	5	10	20
Novice	RAND-1	5	374 ± 24 (2)	-54 ± 496	-710 ± 613	-164 ± 216
Novice	RAND-1	10	-156 ± 180 (2)	153 ± 0 (1)	-311 ± 6 (2)	-345 ± 9 (2)
Novice	D4RL-HC-MR	5	155 ± 392	-438 ± 77	-354 ± 152	-518 ± 192
Novice	D4RL-HC-MR	10	442 ± 625 (2)	-411 ± 124	-485 ± 223	-786 ± 370
Mixed	RAND-1	5	-339 ± 41	-453 ± 64 (2)	-395 ± 42 (2)	-392 ± 40
Mixed	RAND-1	10	-485 ± 0 (1)	-360 ± 0 (1)	-361 ± 9 (2)	-369 ± 10
Mixed	D4RL-HC-MR	5	-459 ± 209	-598 ± 211	-641 ± 58	-638 ± 94
Mixed	D4RL-HC-MR	10	-767 ± 378 (2)	-494 ± 200 (2)	-483 ± 114	-665 ± 160

Table 7: Average and standard deviation, over three random seeds, of the evaluation returns for policies learned using dynamics models trained against multi-demonstrator datasets generated from the HalfCheetah environment. During offline policy training with the SAC algorithm, roll-out starting locations were sampled from the indicated dataset. If a value has a number in brackets next to it then only this number of agents completed 0.5 million steps of training. If there is no value then none of the agents completed 0.5 million steps of training.

1. **RAND:** Transitions were generated by taking random actions in the environment.

2. **D4RL-MR:** The D4RL medium-replay datasets for each of the environments (Fu et al., 2020).

Experiments were not run for environment models trained on the HalfCheetah Experienced multi-demonstrator dataset given that (when using MOPO penalty coefficient $\lambda = 0$) no policies were learned when drawing starting locations from the same dataset used to train the models. If policies cannot be learned using in-distribution starting locations, then we do not expect to be able to learn them using OOD starting locations. We are yet to run similar experiments for the Walker2D multi-demonstrator datasets, but we anticipate similar results to those seen for the HalfCheetah and Walker2D datasets (i.e., an inability to learn a policy). Additionally, experiments are still to be run for MOPO penalty coefficients $\lambda > 0$.

Env. Model Train. Dataset	Roll-out Start. Loc. Dataset	Roll-out Length	REx Penalty Coefficient, β			
			0	5	10	20
Novice	RAND-1	5	6 ± 1	8 ± 2	9 ± 2	8 ± 2
Novice	RAND-1	10	5 ± 1	9 ± 1	8 ± 2	9 ± 3
Novice	D4RL-H-MR	5	179 ± 126	253 ± 175	281 ± 200	236 ± 165
Novice	D4RL-H-MR	10	245 ± 172	385 ± 27	398 ± 35	297 ± 170
Mixed	RAND-1	5	5 ± 1	7 ± 2	7 ± 2	6 ± 2
Mixed	RAND-1	10	7 ± 1	9 ± 2	8 ± 2	31 ± 36
Mixed	D4RL-H-MR	5	270 ± 70	102 ± 130	99 ± 133	82 ± 104
Mixed	D4RL-H-MR	10	311 ± 66	310 ± 15	310 ± 36	307 ± 1
Experienced	RAND-1	5	10 ± 4	8 ± 2	9 ± 2	9 ± 2
Experienced	RAND-1	10	16 ± 12	9 ± 3	12 ± 4	13 ± 3
Experienced	D4RL-H-MR	5	177 ± 132	355 ± 467	186 ± 121	313 ± 29
Experienced	D4RL-H-MR	10	261 ± 172	181 ± 54	332 ± 81	281 ± 64

Table 8: Average and standard deviation, over three random seeds, of the evaluation returns for policies learned using dynamics models trained against multi-demonstrator datasets generated from the Hopper environment. During offline policy training with the SAC algorithm, roll-out starting locations were sampled from the indicated dataset. If a value has a number in brackets next to it then only this number of agents completed 1 million steps of training. If there is no value then none of the agents completed 1 million steps of training.

E   DEGENERATE REWARD PREDICTIONS

Figure 5 demonstrates that abnormally large reward predictions can occur within the first 10 steps of episodes generated using environment models trained without REx. Out of the 60 episodes shown in Figure 5, six contained reward predictions with an absolute value exceeding one million. If these episodes are excluded then the largest absolute reward prediction was 12.29. No episodes generated absolute reward predictions greater than 12.29 in the first 5 steps, while 2 episodes did within the first 10 steps. Note that our aim in this experiment was merely to show the possibility of abnormally large reward predictions in the early stages of episodes, not prove that the problem is common/widespread.

F   ADDITIONAL EXPERIMENTS

F.1   NOISY ROLL-OUT STARTING LOCATIONS

To further assess the potential benefits of environment models trained with REx, we analysed the impact of adding noise to the roll-out starting locations used during offline policy training. Note that the environment models were trained on the original multi-demonstrator datasets (which have no noise), and starting locations were still sampled from the same dataset used to train the environment models. The only change was that noise with standard deviation $\sigma \in \{0.00, 0.01, 0.05, 0.10\}$ was added to the dataset before starting locations were sampled from it. Figure 6 shows that environment models trained with REx yielded policies with higher average returns across all noise levels for both the HalfCheetah and Hopper environments. For the Walker2D environment, environment models trained with REx penalty coefficients $\beta \in \{10, 20\}$ yielded policies with higher returns. For both HalfCheetah and Hopper environments, the highest policy evaluation return was obtained when $\sigma = 0.01$–suggesting that a small amount of noise was beneficial. We hypothesise that the distribution of noisy starting locations is more diverse, enabling greater exploration. In the case of the Hopper environment, it was the environment model trained without REx that obtained the highest average return for $\sigma = 0.01$, whereas the returns for the equivalent HalfCheetah and Walker2D environment models decreased significantly. This may be thanks to the greater simplicity of the Hopper environment.

Figure 5: Abnormally large reward predictions can be made within the first 10 steps of an episode. Six different starting locations were randomly sampled from the HalfCheetah Mixed multi-demonstrator dataset. Ten episodes of 1000 steps were then generated from each starting location, using an environment model trained on the HalfCheetah Mixed multi-demonstrator dataset and a policy trained using the same environment model ($\beta = 0, \lambda = 0, h = 10$). For each episode, the rewards at each step over the first 100 steps are shown. The dashed vertical red lines denote the 5 and 10 step marks.

(a) HalfCheetah, $h = 5$ (b) Hopper, $h = 5$ (c) Walker2D, $h = 10$

Figure 6: No correlation is observed between the average OOD log-likelihood of environment models and the average evaluation return of policies trained using them. The results shown are for a roll-out length of 5. A line of best fit (LBF) is shown, along with the corresponding R^2 value.

F.2 Analysis of Training Exploration using PCA

In an attempt to determine whether environment models trained with REx supported increased exploration of the state-action space during policy training, we investigated the use of PCA to project transition records into two-dimensions, such that they could be visualised. For experiments using the Gym MuJoCo HalfCheetah environment, we sampled 100,000 transition records from the model pool every 100,000 training steps, excluding the zeroth and final training steps. Figure 7 shows the projections for a set of six policy training experiments, using the Mixed dataset and $\beta \in \{0, 10\}$. The projection matrix was trained on the complete collection of sampled transition records for the six experiments. Note that, unlike all other experiments in this paper, the environment models used in these experiments received one additional epoch of training prior to being used to learn a policy. This is the default behaviour of the MOPO codebase when utilising pre-trained environment models (Yu et al., 2020). The average return for the experiments that did not use an environment model trained with REx was -420 ± 50, while for the REx experiments it was 8128 ± 1053. The projected records appear to indicate that increased exploration of the state-action space took place when using an environment model trained with REx. It is important to recognise, however, that the projections for REx experiments have higher explained variance, which may partially or fully explain the observed difference. The results will of course be sensitive to the datasets used to learn the projection matrix. We believe that further investigation of this method is warranted.

Figure 7: A 2D projection of state-action pairs sampled from the model pool during policy training appears to indicate that increased exploration of the space took place when using an environment model trained with REx ($\beta = 10$). It is important to recognise, however, that the projections for REx experiments have higher explained variance, which may partially or fully explain the observed difference. The projection matrix was trained on the complete collection of sampled transition records for the six experiments shown. MOPO penalty coefficient $\lambda = 5$ and roll-out length $h = 10$ were used.