Learning Fine-grained Parameter Sharing via Sparse Tensor Decomposition

Figure 1: **Fi**ne-grained **P**arameter **S**haring (FiPS).

Abstract

Large neural networks achieve state-of-the-art performance on many tasks, yet their sheer size hinders deployment on resource-constrained devices. Among existing compression approaches, parameter sharing remains relatively unexplored. In this paper, we introduce Fine-grained Parameter Sharing (FiPS), a unified compression framework that combines parameter sharing, tensor decomposition, and sparsity. FiPS compresses transformers by factorizing MLPs concatenated across layers into a shared low-rank basis with sparse, layer-specific projection matrices. Both components are initialized via singular value decomposition (SVD) and jointly optimized through block-wise reconstruction error minimization. FiPS compresses a variety of Vision Transformers (ViTs) and Large Language Models (LLMs) by 20–50% with negligible quality degradation. We further combine FiPS with Quantization-Aware Training (QAT) to achieve state-of-the-art compression on GEMMA-2 models. These results establish fine-grained parameter sharing as a practical route to compact, high-performance transformer models.

1 Introduction

Over the past decade, large neural networks have delivered impressive performance through scaling of datasets and model sizes. However, this trend has introduced substantial computational, memory, and storage burdens, highlighting the need for efficient model compression to reduce overhead and enable deployment on resource-constrained devices such as mobile phones and embedded systems. In response, researchers have explored various strategies, including tensor decomposition, quantization, distillation, sparsity, adaptive computing methods, and *parameter sharing* (Cheng et al., 2020). While most of these techniques are well-studied and widely adopted, parameter sharing in neural networks remains underexplored and has not yet been leveraged successfully to compress Transformer models, despite its potential for significant parameter-count reduction.

Sharing parameters across layers reduces memory usage and improves cache efficiency. Prior works have investigated reusing entire Transformer blocks (Lan et al., 2020; Takase & Kiyono, 2023; Lin et al., 2023),

yielding more efficient models. Although directly sharing unmodified weights is promising, we hypothesize that a more fine-grained approach could yield superior compression.

We therefore focus on sharing neurons across layers by introducing a shared basis, with each neuron expressed as a linear combination of basis vectors via a projection matrix. We, then, find that enforcing sparsity in the projection matrix is essential for the effectiveness of this approach. This insight leads to our novel parameter sharing algorithm, **Fi**ne-grained **P**arameter **S**haring (FiPS), which, as we demonstrate, effectively compresses large Vision Transformers (ViTs) and Large Language Models (LLMs)[1]. Our contributions include:

- **Systematic Analysis.** We systematically explore strategies for sharing bases and neurons across transformer layers, examining sharing granularity and concatenation schemes. We identify when neuron sharing is most effective and how global versus local and structured versus unstructured sparsity patterns contribute to compression.

- **FiPS Algorithm[2].** Shared low-rank bases and sparse refinement factors are initialized via SVD and jointly optimized using sparse training with block-wise reconstruction error minimization, followed by optional end-to-end fine-tuning (FT).

- **State-of-the-Art ViT & LLM Compression.** FiPS delivers substantial compression with minimal performance loss, surpassing recent baselines. It compresses DEIT-B and SWIN-L by 20–50% with <1% top-1 accuracy drop across five vision benchmarks, and compresses LLAMA-7B and LLAMA-3.1-8B by up to 40% while maintaining competitive quality on 10 NLP benchmarks.

- **Quantization-Aware Training (QAT).** We demonstrate that 3-bit QAT combined with FiPS compresses GEMMA-2-2B effectively, achieving compression comparable to 2-bit quantization but with markedly better language modeling. This confirms that FiPS is orthogonal to QAT.

The remainder of this paper is organized as follows: Section 2 formalizes the integration of tensor decomposition and sparsity for parameter sharing; Section 3 details the FiPS algorithm; Section 4 presents our empirical findings; and Section 5 provides ablation studies on key design choices. Extensive supplementary material is provided in the Appendix, including additional experiments, algorithmic details, and hyperparameter sweeps.

2 Parameter Sharing Through Sparse Tensor Decomposition

Consider a weight matrix $\mathbf{W} \in \mathbb{R}^{d \times p}$, where $p > d$, that projects feature vectors from a d-dimensional space to a p-dimensional space with neurons represented by the columns of $\mathbf{W}$. Our objective is to share weights among a subset of these p neurons, reducing the number of unique neurons to $r < p$. In other words, only r columns of $\mathbf{W}$ will contain unique values. These r unique neurons are represented using a lookup table (the shared basis) $\mathbf{U} \in \mathbb{R}^{d \times r}$. The original matrix $\mathbf{W}$ is then reconstructed by mapping each of its p columns to an r-dimensional one-hot vector via a projection matrix $\mathbf{V} \in \mathbb{R}^{r \times p}$, i.e., $\mathbf{W} = \mathbf{UV}$. This "one-hot" approach is illustrated in the upper part of Figure 1. However, limiting the number of unique neurons to r constrains the representational capacity of $\mathbf{W}$. To address this limitation, we can increase the number of non-zero elements in $\mathbf{V}$, effectively creating linear combinations of basis neurons and generating a significantly larger set of unique neuron representations, as shown in the lower part of Figure 1.

This approach readily extends from sharing neurons within a single weight matrix $\mathbf{W}$ to multiple weight matrices $\mathcal{W} = \{\mathbf{W}_1, \ldots, \mathbf{W}_N\}$ via concatenation (see Figure 5). Specifically, fine-grained parameter sharing across multiple layers can be achieved by expanding the projection matrix $\mathbf{V}$ and the shared basis $\mathbf{U}$. Sharing neurons between layers in this manner may be viewed as a low-rank decomposition of the matrices $\mathcal{W}$, where the first factor $\mathbf{U}$ is shared across N layers and the second, layer-specific factor $\mathbf{V}$ is sparse. Consequently, existing low-rank decomposition techniques can be employed to obtain an optimal shared orthogonal basis, and sparsity in the projection matrices can be induced using standard pruning and sparse training methods.

---

[1]All model links are available in Appendix A.3.
[2]Source code will be released upon acceptance.

(a) FC-1   (b) Sharing Strategies

Figure 2: **Initial Experiments.** (a) Reconstruction error with varying levels of sparsity on different factors of the low-rank decomposition of FC-1 under 25% parameter budget. Results are analogous for FC-2, i.e., inducing sparsity on the larger factor yields a higher rank and, thus, lower reconstruction error. (b) Mean reconstruction error across four FCs of two distinct encoder blocks' MLPs under various parameter sharing schemes and sparsities. See § 2.2 for details.

In the following sections, we investigate optimal layer-tying strategies within our framework, using a 12-block DEIT-B encoder with a single MLP module per block, pretrained on ImageNet-1k (Deng et al., 2009). Specifically, we focus on MLP modules, which account for the majority of parameters (e.g., 70.5% in GEMMA-2-9B (Team et al., 2024)) and comprise two fully connected (FC) layers (i.e., FC-1 and FC-2 for DEIT-B) of dimensions $\mathbb{R}^{d \times p}$ and $\mathbb{R}^{p \times d}$ with $p = 4d$. The "parameter budget" denotes the fraction of nonzero parameters retained after truncated SVD and sparsification; e.g., 25% retains one-quarter of each MLP's weights. We measure the overall compression ratio as the percentage reduction in model size in bits, including sparsity metadata; e.g., 20% compression reduces storage by 20%.

Conceptually, FiPS differs from standard low-rank compression in three key aspects: (i) the basis is shared across layers rather than learned per layer; (ii) sparsity is imposed on the projection factors rather than the basis, enabling flexible neuron recombination; and (iii) optimization is performed jointly across layers using block-wise reconstruction loss. Together, these components transform low-rank approximation into a fine-grained parameter sharing mechanism.

2.1 Optimal Sparsity for Tensor Decomposition

Before implementing parameter sharing via shared bases, we decompose individual FC layers of MLP modules using truncated SVD at a 25% parameter budget. Subsequently, sparsity is introduced by pruning low-magnitude values. Specifically, we examine sparsity induction in: (1) $\mathbf{U}$, (2) $\mathbf{V}$, and (3) both $\mathbf{U}$ and $\mathbf{V}$. Throughout this process, we vary the sparsity levels of the matrices while maintaining a constant total number of non-zero parameters. The resulting reconstruction errors are presented in Figure 2a. Our experiments show that the lowest reconstruction errors occur at sparsity levels between 60% and 80%, as confirmed by a sparsity sweep on ImageNet-1k with DEIT-B (see Appendix A.7), particularly when sparsity is imposed on the larger factor matrix $\mathbf{V}$. We attribute this to the higher redundancy in larger matrices, which facilitates more efficient pruning.

2.2 Weight Concatenation and Sharing Dimensions

We investigate parameter sharing across multiple layers by analyzing four FC layers drawn from two distinct MLP modules. To align their dimensions, we transpose the second FC layer of each module, representing every layer as $\mathbf{W} \in \mathbb{R}^{d \times 4d}$. We then examine four concatenation strategies for constructing a shared weight block $\mathbf{W}_s$:

(I) **Long-axis concatenation.** All four weight matrices $\mathbf{W}$ are concatenated along their output (neuron) dimension, resulting in $\mathbf{W}_s \in \mathbb{R}^{d \times 16d}$.

(II) **Module-wise long, inter-module short.** Inside each MLP, its two FC layers are first concatenated along the output dimension, producing $\mathbf{W}_s \in \mathbb{R}^{2d \times 8d}$.

(III) **Module-wise short, inter-module long.** Inside each MLP, its two FC layers are first concatenated along the input dimension, again yielding $\mathbf{W}_s \in \mathbb{R}^{2d \times 8d}$.

(IV) **Short-axis concatenation.** All four $\mathbf{W}$ matrices are concatenated along their input (feature) dimension, aligning features rather than neurons and resulting in $\mathbf{W}_s \in \mathbb{R}^{4d \times 4d}$.

For each concatenated block $\mathbf{W}_s$, we perform truncated SVD to retain the top r singular vectors, followed by sparsification of the right singular matrix $\mathbf{V}$ via magnitude pruning (see § 2.1). Reconstruction is then obtained using the resulting shared basis, and mean squared error (MSE) is reported in Figure 2b. Empirically, concatenation along the longer dimension consistently achieves the lowest reconstruction error—particularly under high sparsity—motivating our choice of full long-axis concatenation throughout. Further implementation details are provided in Appendix A.1.1.

2.3 Parameter Sharing Across Layers

This section examines redundancy and interdependencies among MLP modules to identify optimal parameter sharing groupings. We first decompose each module individually at rank $r = 180$ and plot the resulting mean squared error in the lower panel of Figure 3a. The error increases nearly monotonically with module depth, indicating that deeper layers require greater representational capacity. Next, we evaluate pairwise parameter sharing between modules i and j through a shared basis $\mathbf{U}$. Parameter sharing reduces the total number of unique parameters but increases the reconstruction error for each module. We denote the average error increase due to parameter sharing between modules i and j as $MSE_{i,j}^{\downarrow}$:

$$MSE_{i,j}^{\downarrow} = \frac{(MSE_{i,j} - MSE_i) + (MSE_{j,i} - MSE_j)}{2},$$

where $MSE_{i,j}$ denotes the error of module i when sharing a basis with module j. Figure 3a shows that adjacent modules exhibit the smallest error increase due to parameter sharing, motivating the practice of grouping consecutive layers.

We then explore the effect of grouping multiple MLP modules. Increasing group size allows a higher rank for the shared basis $\mathbf{U}$, as shown in Figure 3b. This benefit is most pronounced when the projection matrices $\mathbf{V}$ are sparsified. However, a higher rank does not always improve task performance, since $\mathbf{U}$ must capture a larger set of neurons. Figure 3c demonstrates that sharing across four consecutive MLP modules yields the highest post-compression accuracy.

Overall, our results reveal that (i) deeper modules require greater capacity when compressed in isolation—an effect we confirm with global pruning experiments in § 5; (ii) parameter sharing between adjacent layers curbs the rise in reconstruction error; and (iii) for DEIT-B, setting the grouping hyperparameter to four consecutive MLP modules ($\beta = [4, 4, 4]$) achieves the best trade-off between basis rank and sparsity in FiPS. A sweep over the grouping hyperparameter is reported in Appendix A.8.1.

3 Fine-grained Parameter Sharing

The insights from § 2 motivate FiPS, an efficient parameter sharing algorithm grounded in sparse tensor decomposition. FiPS comprises three stages:

1. **Shared Initialization.** Tie the FC layers within each MLP group and apply truncated SVD to their concatenation (see Figure 5), yielding a shared basis $\mathbf{U}$ and projection matrices $\{\mathbf{V}_i\}$.
2. **Local Error Minimization.** Using a small calibration dataset D (§ 4.1), optimize $\mathbf{U}$ and each $\mathbf{V}_i$ to minimize the ℓ_2 discrepancy between original and compressed activations while enforcing target sparsity in $\mathbf{V}_i$.

Figure 3: **Parameter Sharing Groups.** (a top) MSE increases when sharing $\mathbf{U}$ across different MLP modules; red squares over the diagonal indicate that sharing adjacent modules enhances reconstruction. (a bottom) MSE for compressing individual MLP modules, showing that sharing $\mathbf{U}$ among consecutive layers typically results in the lowest error. (b) For a fixed parameter budget, the rank of the shared basis $\mathbf{U}$ stabilizes around four MLP modules, aligning with the optimal group size (c) for maximizing accuracy in DEIT-B, while the dense counterpart continuously worsens.

3. **Global Error Minimization (Optional).** Fine-tune the compressed model end-to-end under a dynamic sparse training regime to recover performance at higher compression ratios.

Shared Initialization.   We begin by compressing the pretrained model through parameter sharing, achieved by concatenating and decomposing multiple FC layers simultaneously. For higher parameter budgets and sparsity levels (e.g., 50% and 75%, respectively, for DEIT-B), the rank of the shared factor $\mathbf{U}$ can exceed the model dimension d. In such cases, we grow the matrices $\mathbf{U}$ and $\mathbf{V}$ similarly to Net2Net (Chen et al., 2016). However, unlike Net2Net, which copies each neuron and halves its value, we grow $\mathbf{U}$ by appending zeros, allowing neuron growth from scratch. For $\mathbf{V}$, we select the top-k neurons with the highest singular values (i.e., $k = r - d$) and scale them by $1/\tau$, where τ is treated as a hyperparameter (see Appendix A.1.2).

Formally, the parameters of a group of FC layers across MLP modules, $\mathbf{W}_1, \mathbf{W}_2, \ldots, \mathbf{W}_N$, are concatenated into $\mathcal{W} = [\mathbf{W}_1; \mathbf{W}_2; \ldots; \mathbf{W}_N]$, where $\mathbf{W}_i \in \mathbb{R}^{d \times p}$.[3] We then apply truncated SVD, $\mathcal{W} = \mathbf{U}\boldsymbol{\Sigma}\hat{\mathbf{V}}$, to obtain a low-rank approximation, where $\mathbf{U} \in \mathbb{R}^{d \times r}$, $\boldsymbol{\Sigma} \in \mathbb{R}^{r \times r}$, and $\hat{\mathbf{V}} \in \mathbb{R}^{r \times (N \cdot p)}$. The factor $\mathbf{U}$ is shared among all layers within the group and remains dense due to its small size. We then multiply $\hat{\mathbf{V}}$ by the singular values to obtain the projection matrix $\mathbf{V} = \boldsymbol{\Sigma}\hat{\mathbf{V}}$. Finally, the weights are reconstructed as $\mathbf{W}'_i = \mathbf{U}\mathbf{V}_i$, where each $\mathbf{V}_i$ is the slice of $\mathbf{V}$ corresponding to weight matrix $\mathbf{W}_i$.

Local Error Minimization.   In the second phase of FiPS, we compute the input and output activations of the original FC layers using a calibration dataset D (described in § 4.1). We use these activations to optimize

---

[3]The second FC layer is transposed to match the dimensions of the first.

Algorithm 1 **Fi**ne-grained **P**arameter **S**haring

Require: MLP parameters $\mathbf{W}_1, \cdots, \mathbf{W}_N \in \mathbb{R}^{d \times p}$, MLP inputs $\mathbf{A}_i$ and MLP function $\mathbf{f}(\mathbf{W}_i, \mathbf{A}_i)$, Target rank r, Learning Rate η, Steps $\mathbf{T}$.

1: $\mathbf{U}, [\mathbf{V}_1, \mathbf{V}_2, \cdots, \mathbf{V}_N] \leftarrow TruncatedSVD\left([\mathbf{W}_1; \mathbf{W}_2; \cdots; \mathbf{W}_N], \ k = r\right)$
2: **for** each training iteration $t = 1$ to T **do**
3:      $\mathbf{G}_\mathbf{U} = 0$ ▷ Gradient accumulator for $\mathbf{U}$
4:      **for** each block i **do**
5:          $\mathbf{V}_i \leftarrow Sparsify(\mathbf{V}_i, \ t)$ ▷ Potentially increase or adjust sparsity
6:          $L_i \leftarrow MSE\_loss(\mathbf{f}(\mathbf{W}_i, \ \mathbf{A}_i), \quad \mathbf{f}(\mathbf{U}\,\mathbf{V}_i, \ \mathbf{A}_i))$
7:          $\mathbf{V}_i \leftarrow \mathbf{V}_i - \eta \nabla_{\mathbf{V}_i} L_i$
8:          $\mathbf{G}_\mathbf{U} \leftarrow \mathbf{G}_\mathbf{U} + \nabla_\mathbf{U} L_i$
9:      **end for**
10:     $\mathbf{U} \leftarrow \mathbf{U} - \dfrac{\eta}{N}\mathbf{G}_\mathbf{U}$
11: **end for**
12: **return** $\mathbf{U}, \ [\mathbf{V}_1, \ldots, \mathbf{V}_N]$

---

the compressed layers by minimizing the ℓ_2-*loss* between the original and compressed activations:

$$\operatorname*{argmin}_{\mathbf{U}, \mathbf{V_i}, \ldots, \mathbf{V_N}} \sum_{i}^{N} \|\mathbf{W}_i \mathbf{X}_i - \mathbf{U}\mathbf{V}_i \mathbf{X}_i\|_2^2, \tag{1}$$

where $\mathbf{X}_i$ is the inputs to the i^{th} original FC layer.

We explore several sparse training and pruning strategies to identify a sparse $\mathbf{V}$ during optimization: (a) *Static Sparsity*, which fixes the sparsity pattern by retaining the top-magnitude connections before training (Hoefler et al., 2021); (b) *Gradual Magnitude Pruning (GMP)* (Zhu & Gupta, 2017), which progressively increases sparsity by updating the mask every T steps according to the cubic schedule of Kurtic et al. (2023); and (c) *RigL* (Evci et al., 2021), which initializes as in (a) but updates sparse connectivity every ΔT steps using both gradient and magnitude information. We adopt *GMP* as our final strategy due to its superior performance, achieving up to 4% higher top-1 accuracy on ImageNet-1k compared to the closest baseline. A detailed comparison of sparsification methods is provided in Table 6.

During this stage, parameters are shared across multiple MLP modules, allowing gradients to be computed one module at a time. As a result, optimization is significantly more resource-efficient than end-to-end fine-tuning.

Global Error Minimization. In this optional stage, we fine-tune the learned parameter sharing scheme end-to-end to further improve performance and leverage the masks learned via GMP. Because the factors $\mathbf{V}_i$ are sparse, we employ the dynamic sparse training method *RigL* during this stage, as it performs slightly better than *Static Sparsity* (see § 4.1).

4 Main Results

4.1 Vision Transformers

Experimental Setup. We evaluate FiPS on DᴇɪT-B (Touvron et al., 2021) and Sᴡɪɴ-L (Liu et al., 2021). Each model is calibrated on 2,560 ImageNet-1k images for 20 epochs, sufficient for convergence; calibration completes in under one hour on an NVIDIA A6000. For parameter sharing, we group every four MLP modules in DᴇɪT-B. In Sᴡɪɴ-L, which consists of four stages with 2, 2, 18, and 2 encoder blocks, we share across entire stages for the three smaller ones and use groups of six blocks in the larger stage. Additional hyperparameters and sensitivity analyses are provided in Appendices A.7 and A.8.

ImageNet-1k. We compare FiPS to Adaptive Atomic Feature Mimicking (AAFM), which compresses output activations rather than weights, and Global Feature Mimicking (GFM), which fine-tunes the compressed

Table 1: **ViT Compression Results.** ImageNet-1k top-1 validation accuracy of DEIT-B (81.85%) (Touvron et al., 2021) and SWIN-L (86.24%) (Liu et al., 2021) compressed using FiPS and AAFM/GFM across parameter budgets, comparing layer-wise (FiPS) and global error minimization (FiPS+FT). AAFM/GFM[†] results are from Yu & Wu (2023); – denotes unreported metrics.

Parameter Budget	10%		25%		40%		50%		75%	
Method / Model	DEIT	SWIN	DEIT	SWIN	DEIT	SWIN	DEIT	SWIN	DEIT	SWIN
AAFM [†]	–	–	–	–	80.33	–	81.21	85.04	81.76	85.94
GFM [†]	–	–	–	–	81.28	–	81.62	85.44	81.83	86.01
FiPS (ours)	70.04	74.04	80.64	84.78	**81.69**	**85.69**	81.83	85.99	81.82	86.21
FiPS + FT (ours)	**77.26**	**82.13**	**81.31**	**85.16**	81.54	85.68	81.54	**85.99**	81.82	**86.22**

Table 2: (a) Top-1 accuracy of DEIT-B and compressed variants using GFM and FiPS under different parameter budgets. GFM[†] and Original[†] results are from Yu & Wu (2023) and Touvron et al. (2021). (b) ImageNet-1k top-1 accuracy of DEIT-B with FiPS at 2:4 structured sparsity (N:M GMP (Lee et al., 2023)) versus 50% unstructured sparsity.

(a)

	Original[†]	GFM[†]		FiPS+RigL FT (ours)		
P. Budget	100	40%	50%	25%	40%	50%
CIFAR-100	90.99	90.17	90.67	90.88	91.24	**91.33**
Pets	**94.74**	93.95	94.22	94.19	94.52	94.41
Flowers102	97.77	97.02	97.45	97.84	98.14	**98.37**
iNaturalist 2019	77.39	77.13	77.56	77.26	77.58	**77.69**

(b)

P. Budget	10%	25%	40%	50%	75%
2:4 FiPS	52.36	76.88	80.59	81.31	81.51
FiPS	54.00	77.56	80.94	81.63	81.77

network (Yu & Wu, 2023). Both FiPS and FiPS+FT match AAFM and GFM in compute and memory budgets. At a 40% parameter budget, FiPS outperforms AAFM by 1.36 points and GFM by 0.41 points despite GFM's higher cost (Table 1). This pattern holds across all budgets: FiPS consistently achieves the highest accuracy with the lowest overhead. Notably, a 10% parameter budget corresponds to roughly a 50% compression ratio, where FiPS+FT yields particularly strong gains.

Transfer Learning. For transfer learning, we fine-tune for 100 epochs on CIFAR-100, Flowers102, Oxford-III-Pets, and iNaturalist 2019 (Krizhevsky, 2009; Nilsback & Zisserman, 2008; Parkhi et al., 2012; Van Horn et al., 2018), following Yu & Wu (2023). We use *AdamW* (Loshchilov & Hutter, 2019) with learning rates selected from 12 log-spaced values. Models compressed with FiPS transfer significantly better, as shown in Table 2a.

Latency and Memory Profiling. Structured sparsity patterns enable efficient hardware implementations with minimal quality impact, as demonstrated in Table 2b using *NMGMP*. With 2:4 structured FiPS, the accuracy degradation remains just above 1% at 10% and 25% MLP parameter budgets; for all other settings, the impact is negligible. We further evaluate FiPS with alternative structured sparsity pruners—*STE*, *SR-STE* (Zhou et al., 2021), and *NMSRigL* (Lee et al., 2023; Lasby et al., 2024)—in Table 7. Latency and memory profiling with the optimal *NMGMP*+FiPS setup leverages NVIDIA's tensor core support for 2:4 sparsity (Mishra et al., 2021) on GPUs and Neural Magic's DeepSparse Engine (Neural Magic, 2021) on CPUs, as shown in Figure 7 and detailed in Appendix A.9.

These results demonstrate that FiPS effectively compresses models while enhancing both memory efficiency and computational speed. For instance, with a batch size of 64, FiPS with 2:4 sparsity at a 22.14% parameter budget yields a 1.31× speedup on the NVIDIA A4000 and reduces peak VRAM allocation to approximately 0.79× of the original requirement during inference.

	Method	WikiText-2↓	C4↓	Openb.	ARC-e	WinoG.	HellaS.	PIQA	MathQA	**Avg.↑**	TruthfulQA↑	GSM8K↑
	Original	5.68	7.34	0.34	0.75	0.70	0.57	0.79	0.27	0.57	0.30	0.09
	ASVD	11.14	15.93	0.29	0.53	0.64	0.41	0.68	0.17	0.45	0.21	0.04
Llama-7B	SVD-LLM	7.94	15.84	0.31	0.71	0.68	0.49	0.71	0.22	0.52	0.24	0.06
	SVD-LLM V2	7.12	10.47	0.32	0.72	0.70	0.52	0.75	0.24	0.54	**0.27**	**0.07**
	Basis Sharing	7.74	15.03	0.28	0.66	0.66	0.46	0.71	0.25	0.50	–	–
	FiPS (ours)	**6.06**	**8.10**	**0.32**	**0.72**	**0.70**	**0.56**	**0.78**	**0.26**	**0.56**	**0.27**	**0.07**
	Original	6.14	9.47	0.35	0.80	0.73	0.60	0.80	0.40	0.61	0.49	0.45
	ASVD	17.55	28.41	0.20	0.59	0.61	0.41	0.69	0.30	0.47	0.37	0.28
Llama-3.1-8B	SVD-LLM	11.82	20.05	0.29	0.77	0.64	0.51	0.72	0.30	0.54	0.45	0.31
	SVD-LLM V2	8.01	11.72	**0.33**	**0.79**	0.70	0.58	0.77	0.36	0.59	**0.46**	0.40
	FiPS (ours)	**6.88**	**10.78**	**0.33**	**0.79**	**0.72**	**0.59**	**0.78**	**0.38**	**0.60**	**0.46**	**0.42**

Table 3: **LLM Compression Results.** Llama-7B and Llama-3.1-8B at 20% compression. PPL↓: perplexity on WikiText-2 and C4; Avg.↑: mean over six classification tasks; TruthfulQA (BLEU↑) and GSM8K (exact match↑). ASVD from Yuan et al. (2023); SVD-LLM from (Wang et al., 2024b); SVD-LLM-v2 from (Wang et al., 2025); Basis Sharing from Wang et al. (2024a). All results follow (Sutawika et al., 2023); – indicates unreported metrics.

4.2 Large Language Models

Experimental Setup. We evaluate FiPS on three publicly available pretrained LLMs: Llama-7B (Touvron et al., 2023), Llama-3.1-8B (Grattafiori et al., 2024), and the instruction-tuned Gemma-2-2B (Team et al., 2024). Gemma-2-2B is included solely to demonstrate that FiPS is orthogonal to QAT, while the other models are compared against the baselines described below. Unlike ViTs, these LLMs feature three FC layers per MLP in their decoder blocks. For parameter sharing, all FC layers from MLPs within the same group are concatenated. The number of MLPs per group is treated as a hyperparameter and detailed in Appendix A.1.1. Calibration and optimization follow the ViT protocol (described in § 4.1): activations are collected from $8,192 \times 20$ SlimPajamas (Soboleva et al., 2023) tokens, and block-wise error minimization is run for 40 epochs—without global error minimization (i.e., no full FT)—on a single NVIDIA A100 (80GB), completing within 10 hours per model.

Baselines. We benchmark against three SVD-based LLM compression methods: ASVD (Yuan et al., 2023), which scales weights by activation statistics to mitigate outliers; SVD-LLM (Wang et al., 2024b), which employs truncation-aware whitening; and SVD-LLM V2 (Wang et al., 2025), which adds layer-wise rank allocation. All baseline metrics are from the original publications; we exclude LoRA (Hu et al., 2021) enhancements for fair comparison. Moreover, we compare FiPS against Basis Sharing (Wang et al., 2024a), which also pursues cross-layer parameter sharing but relies on dense coefficients. In contrast, FiPS enforces sparsity, which our ablations show to be essential (see Table 6).

Evaluation. We report perplexity on WikiText-2 (Merity et al., 2016) and C4 (Dodge et al., 2021), six classification benchmarks, and two generation tasks (TruthfulQA, GSM8K) via LM-Evaluation-Harness (Sutawika et al., 2023). At 20% compression (§ 4.2), FiPS achieves the lowest perplexity on both WikiText-2 and C4 for Llama-7B and Llama-3.1-8B, while matching or outperforming all baselines on downstream tasks. Results at 40% compression are provided in Table 5.

Quantization-Aware Training (QAT). To assess FiPS under low-precision regimes, we apply QAT to Gemma-2-2B. Table 4 reports WikiText-2 perplexity for 4-bit and 2-bit QAT ($4\times$ and $8\times$ compression) as well as FiPS combined with 3-bit QAT. While 4-bit QAT matches `bfloat16` performance, 2-bit QAT degrades severely (PPL = 41.86). Combining 3-bit QAT with FiPS achieves the same $8\times$ compression as 2-bit QAT but with substantially lower perplexity (35.43 vs. 41.86).

Table 4: **QAT Results.** 3-bit QAT with FiPS achieves 8× compression at lower perplexity than 2-bit QAT alone.

Variant	Precision	Compression	PPL ↓
Baseline	BF16	1.0×	15.61
QAT	INT4	4.0×	16.86
QAT	INT2	8.0×	41.86
FiPS	BF16	1.5×	32.01
FiPS+QAT	INT3	8.0×	35.43

5 Ablations

We examine the importance of various components of the FiPS algorithm when compressing DEIT-B at 25% parameter budget. We ablate the following key components:

1. **Random Initialization (RI):** Using RI instead of SVD initialization results in a 1 percentage point drop in accuracy.

2. **Global Pruning (GP):** Using GP when sparsifying the factors **V** yields a 0.4 percentage point improvement over local pruning (LP), which enforces the same sparsity level for each group.

3. **Scaling Vectors (SV):** Following Liu et al. (2024), FC weights are normalized, and the magnitudes initialize the SV for neuron scaling. This enhances LP but is less effective than GP.

An analysis on sparsity, methods, and calibration settings using DEIT-B confirms that GMP with 75% sparsity and 20 epochs over 20 batches yields optimal performance. See Appendix A.7 for full results.

Sparsity Distribution and MSE Loss. Initial experiments in Figure 3a reveal that later layers exhibit higher reconstruction error under uniform compression budgets, suggesting these layers benefit from greater parameter allocation. FiPS addresses this by applying global magnitude pruning to its sparse factors, automatically directing parameters where they are most needed. As shown in Figure 4b, FiPS indeed assigns more parameters to later layers. Furthermore, Figure 4c demonstrates a strong negative correlation (-0.922) between the final sparsity pattern and the MSE losses observed in Figure 3a, confirming the effectiveness of this adaptive allocation.

(a)   (b)   (c)

Figure 4: **DeiT-B Ablation and Global Sparsity Analysis.** (a) Component analysis of the FiPS algorithm: Random Initialization (RI), Local Pruning (LP), Global Pruning (GP), and Scaling Vectors (SV). (b) End-of-training sparsity allocation; later layers require more parameters. (c) Strong correlation between the MSE reported in Figure 3a and the parameter distribution captured by FiPS.

6   Related Work

Vision Transformers (ViT) & Large Language Models (LLM).   Recent transformer architectures extend beyond the foundational ViT models (Dosovitskiy et al., 2021), which treat image patches as token sequences. DEIT (Touvron et al., 2021) enhances data efficiency with distillation tokens, while SWIN (Liu et al., 2021) introduces a hierarchical design using shifted windows. Both vision models employ two FC layers per MLP module. In contrast, decoder-only LLMs such as LLAMA (Touvron et al., 2023), LLAMA-3 (Grattafiori et al., 2024), and GEMMA-2 (Team et al., 2024) achieve state-of-the-art zero-shot and instruction-following performance using three FC layers per MLP module in each block.

Sparsity in Neural Networks.   Early methods involved heuristic pruning, such as removing the smallest-magnitude parameters (Thimm & Fiesler, 1995). Later approaches, such as GMP (Zhu & Gupta, 2017), increased the extent of pruning, while dynamic pruning with accelerated schedulers was explored by Kurtic et al. (2023). Static sparsity uses a preinitialized mask throughout training (Hoefler et al., 2021), whereas dynamic methods such as RigL (Evci et al., 2021) adjust the sparsity pattern during training based on gradient information.

Tensor Decomposition.   Yu & Wu (2023) introduce Adaptive Atomic Feature Mimicking (AAFM) and its global variant Global Feature Mimicking (GFM), which apply truncated PCA on ViT activations followed by fine-tuning. In LLMs, Activation-aware SVD (ASVD) (Yuan et al., 2023), truncation-aware SVD-LLM (Wang et al., 2024b), and SVD-LLM V2 with rank distillation and layer-wise allocation (Wang et al., 2025) serve as our baselines.

Parameter Sharing.   Eban et al. (2019) introduce a Sum-Product reducer to map shared parameters, and Obukhov et al. (2021) employ TR decomposition for shared parameters in 3D tensors. Zhang et al. (2022) propose "Weight Multiplexing," sharing parameters between MLP modules in ViTs, alongside distillation and linear projections between transformer blocks to aid model recovery. Concurrent work by Wang et al. (2024a) also explores cross-layer parameter sharing via SVD, representing weight matrices as linear combinations of shared basis vectors with layer-specific coefficients. In contrast to their dense coefficient approach, FiPS enforces sparsity in the projection matrices, which we show in § 2.1 is critical for achieving lower reconstruction error at the same parameter budget.

7   Conclusion

We presented FiPS, a unified framework for compressing transformers via fine-grained inter-layer parameter sharing enabled by sparsity and low-rank decomposition. FiPS achieves state-of-the-art compression–accuracy trade-offs: up to 50% compression on ViTs with <1% accuracy loss, up to 40% on LLMs, and 8× on GEMMA-2-2B when combined with QAT. These findings establish parameter sharing as a competitive alternative to existing compression strategies. Future work includes extending to attention layers, quantizing the shared bases, and developing specialized kernels that keep **U** resident in fast memory for efficient on-device inference.

Broader Impact Statement

This paper advances Machine Learning by introducing Fine-grained Parameter Sharing (FiPS), a model compression method that improves the efficiency of Vision Transformers (ViTs) and Large Language Models (LLMs). By leveraging parameter sharing, tensor decomposition, and sparsity, FiPS reduces computational and memory costs, enhancing AI accessibility on resource-constrained devices. While model compression promotes efficiency and sustainability, it may also enable broader AI deployment in sensitive domains with ethical concerns such as bias, misinformation, and privacy. Nevertheless, this work should not introduce new risks beyond those inherent in deep learning, but we encourage responsible deployment and ethical considerations in practice.

References

Tianqi Chen, Ian Goodfellow, and Jonathon Shlens. Net2net: Accelerating learning via knowledge transfer, 2016. URL https://arxiv.org/abs/1511.05641.

Yu Cheng, Duo Wang, Pan Zhou, and Tao Zhang. A survey of model compression and acceleration for deep neural networks, 2020. URL https://arxiv.org/abs/1710.09282.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pp. 248–255. IEEE, 2009.

Jesse Dodge, Maarten Sap, Ana Marasović, William Agnew, Gabriel Ilharco, Dirk Groeneveld, Margaret Mitchell, and Matt Gardner. Documenting large webtext corpora: A case study on the colossal clean crawled corpus, 2021. URL https://arxiv.org/abs/2104.08758.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale, 2021. URL https://arxiv.org/abs/2010.11929.

Elad Eban, Yair Movshovitz-Attias, Hao Wu, Mark Sandler, Andrew Poon, Yerlan Idelbayev, and Miguel A. Carreira-Perpinan. Structured multi-hashing for model compression, 2019. URL https://arxiv.org/abs/1911.11177.

Utku Evci, Trevor Gale, Jacob Menick, Pablo Samuel Castro, and Erich Elsen. Rigging the lottery: Making all tickets winners, 2021. URL https://arxiv.org/abs/1911.11134.

Utku Evci, Bart van Merriënboer, Thomas Unterthiner, Max Vladymyrov, and Fabian Pedregosa. Gradmax: Growing neural networks using gradient information, 2022. URL https://arxiv.org/abs/2201.05125.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, Arun Rao, Aston Zhang, Aurelien Rodriguez, Austen Gregerson, Ava Spataru, Baptiste Roziere, Bethany Biron, Binh Tang, Bobbie Chern, Charlotte Caucheteux, Chaya Nayak, Chloe Bi, Chris Marra, Chris McConnell, Christian Keller, Christophe Touret, Chunyang Wu, Corinne Wong, Cristian Canton Ferrer, Cyrus Nikolaidis, Damien Allonsius, Daniel Song, Danielle Pintz, Danny Livshits, Danny Wyatt, David Esiobu, Dhruv Choudhary, Dhruv Mahajan, Diego Garcia-Olano, Diego Perino, Dieuwke Hupkes, Egor Lakomkin, Ehab AlBadawy, Elina Lobanova, Emily Dinan, Eric Michael Smith, Filip Radenovic, Francisco Guzmán, Frank Zhang, Gabriel Synnaeve, Gabrielle Lee, Georgia Lewis Anderson, Govind Thattai, Graeme Nail, Gregoire Mialon, Guan Pang, Guillem Cucurell, Hailey Nguyen, Hannah Korevaar, Hu Xu, Hugo Touvron, Iliyan Zarov, Imanol Arrieta Ibarra, Isabel Kloumann, Ishan Misra, Ivan Evtimov, Jack Zhang, Jade Copet, Jaewon Lee, Jan Geffert, Jana Vranes, Jason Park, Jay Mahadeokar, Jeet Shah, Jelmer van der Linde, Jennifer Billock, Jenny Hong, Jenya Lee, Jeremy Fu, Jianfeng Chi, Jianyu Huang, Jiawen Liu, Jie Wang, Jiecao Yu, Joanna Bitton, Joe Spisak, Jongsoo Park, Joseph Rocca, Joshua Johnstun, Joshua Saxe, Junteng Jia, Kalyan Vasuden Alwala, Karthik Prasad, Kartikeya Upasani, Kate Plawiak, Ke Li, Kenneth Heafield, Kevin Stone, Khalid El-Arini, Krithika Iyer, Kshitiz Malik, Kuenley Chiu, Kunal Bhalla, Kushal Lakhotia, Lauren Rantala-Yeary, Laurens van der Maaten, Lawrence Chen, Liang Tan, Liz Jenkins, Louis Martin, Lovish Madaan, Lubo Malo, Lukas Blecher, Lukas Landzaat, Luke de Oliveira, Madeline Muzzi, Mahesh Pasupuleti, Mannat Singh, Manohar Paluri, Marcin Kardas, Maria Tsimpoukelli, Mathew Oldham, Mathieu Rita, Maya Pavlova, Melanie Kambadur, Mike Lewis, Min Si, Mitesh Kumar Singh, Mona Hassan, Naman Goyal, Narjes Torabi, Nikolay Bashlykov, Nikolay Bogoychev, Niladri Chatterji, Ning Zhang, Olivier Duchenne, Onur Çelebi, Patrick Alrassy, Pengchuan Zhang, Pengwei Li, Petar Vasic, Peter Weng, Prajjwal Bhargava, Pratik Dubal, Praveen Krishnan, Punit Singh Koura, Puxin Xu, Qing He, Qingxiao Dong, Ragavan Srinivasan, Raj Ganapathy, Ramon Calderer, Ricardo Silveira Cabral, Robert Stojnic, Roberta Raileanu, Rohan Maheswari, Rohit Girdhar, Rohit Patel, Romain Sauvestre, Ronnie Polidoro,

Roshan Sumbaly, Ross Taylor, Ruan Silva, Rui Hou, Rui Wang, Saghar Hosseini, Sahana Chennabasappa, Sanjay Singh, Sean Bell, Seohyun Sonia Kim, Sergey Edunov, Shaoliang Nie, Sharan Narang, Sharath Raparthy, Sheng Shen, Shengye Wan, Shruti Bhosale, Shun Zhang, Simon Vandenhende, Soumya Batra, Spencer Whitman, Sten Sootla, Stephane Collot, Suchin Gururangan, Sydney Borodinsky, Tamar Herman, Tara Fowler, Tarek Sheasha, Thomas Georgiou, Thomas Scialom, Tobias Speckbacher, Todor Mihaylov, Tong Xiao, Ujjwal Karn, Vedanuj Goswami, Vibhor Gupta, Vignesh Ramanathan, Viktor Kerkez, Vincent Gonguet, Virginie Do, Vish Vogeti, Vítor Albiero, Vladan Petrovic, Weiwei Chu, Wenhan Xiong, Wenyin Fu, Whitney Meers, Xavier Martinet, Xiaodong Wang, Xiaofang Wang, Xiaoqing Ellen Tan, Xide Xia, Xinfeng Xie, Xuchao Jia, Xuewei Wang, Yaelle Goldschlag, Yashesh Gaur, Yasmine Babaei, Yi Wen, Yiwen Song, Yuchen Zhang, Yue Li, Yuning Mao, Zacharie Delpierre Coudert, Zheng Yan, Zhengxing Chen, Zoe Papakipos, Aaditya Singh, Aayushi Srivastava, Abha Jain, Adam Kelsey, Adam Shajnfeld, Adithya Gangidi, Adolfo Victoria, Ahuva Goldstand, Ajay Menon, Ajay Sharma, Alex Boesenberg, Alexei Baevski, Allie Feinstein, Amanda Kallet, Amit Sangani, Amos Teo, Anam Yunus, Andrei Lupu, Andres Alvarado, Andrew Caples, Andrew Gu, Andrew Ho, Andrew Poulton, Andrew Ryan, Ankit Ramchandani, Annie Dong, Annie Franco, Anuj Goyal, Aparajita Saraf, Arkabandhu Chowdhury, Ashley Gabriel, Ashwin Bharambe, Assaf Eisenman, Azadeh Yazdan, Beau James, Ben Maurer, Benjamin Leonhardi, Bernie Huang, Beth Loyd, Beto De Paola, Bhargavi Paranjape, Bing Liu, Bo Wu, Boyu Ni, Braden Hancock, Bram Wasti, Brandon Spence, Brani Stojkovic, Brian Gamido, Britt Montalvo, Carl Parker, Carly Burton, Catalina Mejia, Ce Liu, Changhan Wang, Changkyu Kim, Chao Zhou, Chester Hu, Ching-Hsiang Chu, Chris Cai, Chris Tindal, Christoph Feichtenhofer, Cynthia Gao, Damon Civin, Dana Beaty, Daniel Kreymer, Daniel Li, David Adkins, David Xu, Davide Testuggine, Delia David, Devi Parikh, Diana Liskovich, Didem Foss, Dingkang Wang, Duc Le, Dustin Holland, Edward Dowling, Eissa Jamil, Elaine Montgomery, Eleonora Presani, Emily Hahn, Emily Wood, Eric-Tuan Le, Erik Brinkman, Esteban Arcaute, Evan Dunbar, Evan Smothers, Fei Sun, Felix Kreuk, Feng Tian, Filippos Kokkinos, Firat Ozgenel, Francesco Caggioni, Frank Kanayet, Frank Seide, Gabriela Medina Florez, Gabriella Schwarz, Gada Badeer, Georgia Swee, Gil Halpern, Grant Herman, Grigory Sizov, Guangyi, Zhang, Guna Lakshminarayanan, Hakan Inan, Hamid Shojanazeri, Han Zou, Hannah Wang, Hanwen Zha, Haroun Habeeb, Harrison Rudolph, Helen Suk, Henry Aspegren, Hunter Goldman, Hongyuan Zhan, Ibrahim Damlaj, Igor Molybog, Igor Tufanov, Ilias Leontiadis, Irina-Elena Veliche, Itai Gat, Jake Weissman, James Geboski, James Kohli, Janice Lam, Japhet Asher, Jean-Baptiste Gaya, Jeff Marcus, Jeff Tang, Jennifer Chan, Jenny Zhen, Jeremy Reizenstein, Jeremy Teboul, Jessica Zhong, Jian Jin, Jingyi Yang, Joe Cummings, Jon Carvill, Jon Shepard, Jonathan McPhie, Jonathan Torres, Josh Ginsburg, Junjie Wang, Kai Wu, Kam Hou U, Karan Saxena, Kartikay Khandelwal, Katayoun Zand, Kathy Matosich, Kaushik Veeraraghavan, Kelly Michelena, Keqian Li, Kiran Jagadeesh, Kun Huang, Kunal Chawla, Kyle Huang, Lailin Chen, Lakshya Garg, Lavender A, Leandro Silva, Lee Bell, Lei Zhang, Liangpeng Guo, Licheng Yu, Liron Moshkovich, Luca Wehrstedt, Madian Khabsa, Manav Avalani, Manish Bhatt, Martynas Mankus, Matan Hasson, Matthew Lennie, Matthias Reso, Maxim Groshev, Maxim Naumov, Maya Lathi, Meghan Keneally, Miao Liu, Michael L. Seltzer, Michal Valko, Michelle Restrepo, Mihir Patel, Mik Vyatskov, Mikayel Samvelyan, Mike Clark, Mike Macey, Mike Wang, Miquel Jubert Hermoso, Mo Metanat, Mohammad Rastegari, Munish Bansal, Nandhini Santhanam, Natascha Parks, Natasha White, Navyata Bawa, Nayan Singhal, Nick Egebo, Nicolas Usunier, Nikhil Mehta, Nikolay Pavlovich Laptev, Ning Dong, Norman Cheng, Oleg Chernoguz, Olivia Hart, Omkar Salpekar, Ozlem Kalinli, Parkin Kent, Parth Parekh, Paul Saab, Pavan Balaji, Pedro Rittner, Philip Bontrager, Pierre Roux, Piotr Dollar, Polina Zvyagina, Prashant Ratanchandani, Pritish Yuvraj, Qian Liang, Rachad Alao, Rachel Rodriguez, Rafi Ayub, Raghotham Murthy, Raghu Nayani, Rahul Mitra, Rangaprabhu Parthasarathy, Raymond Li, Rebekkah Hogan, Robin Battey, Rocky Wang, Russ Howes, Ruty Rinott, Sachin Mehta, Sachin Siby, Sai Jayesh Bondu, Samyak Datta, Sara Chugh, Sara Hunt, Sargun Dhillon, Sasha Sidorov, Satadru Pan, Saurabh Mahajan, Saurabh Verma, Seiji Yamamoto, Sharadh Ramaswamy, Shaun Lindsay, Shaun Lindsay, Sheng Feng, Shenghao Lin, Shengxin Cindy Zha, Shishir Patil, Shiva Shankar, Shuqiang Zhang, Shuqiang Zhang, Sinong Wang, Sneha Agarwal, Soji Sajuyigbe, Soumith Chintala, Stephanie Max, Stephen Chen, Steve Kehoe, Steve Satterfield, Sudarshan Govindaprasad, Sumit Gupta, Summer Deng, Sungmin Cho, Sunny Virk, Suraj Subramanian, Sy Choudhury, Sydney Goldman, Tal Remez, Tamar Glaser, Tamara Best, Thilo Koehler, Thomas Robinson, Tianhe Li, Tianjun Zhang, Tim Matthews, Timothy Chou, Tzook Shaked, Varun Vontimitta, Victoria Ajayi, Victoria Montanez, Vijai Mohan, Vinay Satish Kumar, Vishal Mangla, Vlad Ionescu, Vlad Poenaru, Vlad Tiberiu Mihailescu,

Vladimir Ivanov, Wei Li, Wenchen Wang, Wenwen Jiang, Wes Bouaziz, Will Constable, Xiaocheng Tang, Xiaojian Wu, Xiaolan Wang, Xilun Wu, Xinbo Gao, Yaniv Kleinman, Yanjun Chen, Ye Hu, Ye Jia, Ye Qi, Yenda Li, Yilin Zhang, Ying Zhang, Yossi Adi, Youngjin Nam, Yu, Wang, Yu Zhao, Yuchen Hao, Yundi Qian, Yunlu Li, Yuzi He, Zach Rait, Zachary DeVito, Zef Rosnbrick, Zhaoduo Wen, Zhenyu Yang, Zhiwei Zhao, and Zhiyu Ma. The llama 3 herd of models, 2024. URL https://arxiv.org/abs/2407.21783.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification, 2015. URL https://arxiv.org/abs/1502.01852.

Torsten Hoefler, Dan Alistarh, Tal Ben-Nun, Nikoli Dryden, and Alexandra Peste. Sparsity in deep learning: Pruning and growth for efficient inference and training in neural networks, 2021. URL https://arxiv.org/abs/2102.00554.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models, 2021. URL https://arxiv.org/abs/2106.09685.

Alex Krizhevsky. Learning multiple layers of features from tiny images. Technical Report TR-2009, University of Toronto, 2009.

Eldar Kurtic, Torsten Hoefler, and Dan Alistarh. How to prune your language model: Recovering accuracy on the "sparsity may cry" benchmark, 2023. URL https://arxiv.org/abs/2312.13547.

Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. Albert: A lite bert for self-supervised learning of language representations, 2020. URL https://arxiv.org/abs/1909.11942.

Mike Lasby, Anna Golubeva, Utku Evci, Mihai Nica, and Yani Ioannou. Dynamic sparse training with structured sparsity. In *International Conference on Learning Representations (ICLR)*, 2024.

Joo Lee, Wonpyo Park, Nicole Mitchell, Jonathan Pilault, Johan Obando-Ceron, Han-Byul Kim, Namhoon Lee, Elias Frantar, Yun Long, Amir Yazdanbakhsh, Shivani Agrawal, Suvinay Subramanian, Xin Wang, Sheng-Chun Kao, Xingyao Zhang, Trevor Gale, Aart Bik, Woohyun Han, Milen Ferev, and Utku Evci. Jaxpruner: A concise library for sparsity research, 04 2023.

Ye Lin, Mingxuan Wang, Zhexi Zhang, Xiaohui Wang, Tong Xiao, and Jingbo Zhu. Understanding parameter sharing in transformers, 2023. URL https://arxiv.org/abs/2306.09380.

Shih-Yang Liu, Chien-Yi Wang, Hongxu Yin, Pavlo Molchanov, Yu-Chiang Frank Wang, Kwang-Ting Cheng, and Min-Hung Chen. Dora: Weight-decomposed low-rank adaptation, 2024. URL https://arxiv.org/abs/2402.09353.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows, 2021. URL https://arxiv.org/abs/2103.14030.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization, 2019. URL https://arxiv.org/abs/1711.05101.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models, 2016. URL https://arxiv.org/abs/1609.07843.

Asit Mishra, Jorge Albericio Latorre, Jeff Pool, Darko Stosic, Dusan Stosic, Ganesh Venkatesh, Chong Yu, and Paulius Micikevicius. Accelerating Sparse Deep Neural Networks, April 2021. URL http://arxiv.org/abs/2104.08378. arXiv:2104.08378 [cs].

Neural Magic. Deepsparse engine: Sparsity-aware deep learning inference runtime for CPUs, 2021. URL https://github.com/neuralmagic/deepsparse.

Maria-Elena Nilsback and Andrew Zisserman. Automated flower classification over a large number of classes. In *Proceedings of the Indian Conference on Computer Vision, Graphics and Image Processing*, pp. 722–729. IEEE, 2008.

Anton Obukhov, Maxim Rakhuba, Stamatios Georgoulis, Menelaos Kanakis, Dengxin Dai, and Luc Van Gool. T-basis: a compact representation for neural networks, 2021. URL https://arxiv.org/abs/2007.06631.

Omkar M. Parkhi, Andrea Vedaldi, Andrew Zisserman, and C. V. Jawahar. Cats and dogs. IEEE Conference on Computer Vision and Pattern Recognition, 2012. The Oxford-IIIT Pet Dataset.

Daria Soboleva, Faisal Al-Khateeb, Robert Myers, Jacob R Steeves, Joel Hestness, and Nolan Dey. SlimPajama: A 627B token cleaned and deduplicated version of RedPajama. https://www.cerebras.net/blog/slimpajama-a-627b-token-cleaned-and-deduplicated-version-of-redpajama, 6 2023. URL https://huggingface.co/datasets/cerebras/SlimPajama-627B.

Lintang Sutawika, Leo Gao, Hailey Schoelkopf, Stella Biderman, Jonathan Tow, Baber Abbasi, ben fattori, Charles Lovering, farzanehnakhaee70, Jason Phang, Anish Thite, Fazz, Aflah, Niklas Muennighoff, Thomas Wang, sdtblck, nopperl, gakada, tttyuntian, researcher2, Chris, Julen Etxaniz, Zdeněk Kasner, Khalid, Jeffrey Hsu, AndyZwei, Pawan Sasanka Ammanamanchi, Dirk Groeneveld, Ethan Smith, and Eric Tang. Eleutherai/lm-evaluation-harness: Major refactor, December 2023. URL https://doi.org/10.5281/zenodo.10256836.

Sho Takase and Shun Kiyono. Lessons on parameter sharing across layers in transformers, 2023. URL https://arxiv.org/abs/2104.06022.

Gemma Team, Morgane Riviere, Shreya Pathak, Pier Giuseppe Sessa, Cassidy Hardin, Surya Bhupatiraju, Léonard Hussenot, Thomas Mesnard, Bobak Shahriari, Alexandre Ramé, Johan Ferret, Peter Liu, Pouya Tafti, Abe Friesen, Michelle Casbon, Sabela Ramos, Ravin Kumar, Charline Le Lan, Sammy Jerome, Anton Tsitsulin, Nino Vieillard, Piotr Stanczyk, Sertan Girgin, Nikola Momchev, Matt Hoffman, Shantanu Thakoor, Jean-Bastien Grill, Behnam Neyshabur, Olivier Bachem, Alanna Walton, Aliaksei Severyn, Alicia Parrish, Aliya Ahmad, Allen Hutchison, Alvin Abdagic, Amanda Carl, Amy Shen, Andy Brock, Andy Coenen, Anthony Laforge, Antonia Paterson, Ben Bastian, Bilal Piot, Bo Wu, Brandon Royal, Charlie Chen, Chintu Kumar, Chris Perry, Chris Welty, Christopher A. Choquette-Choo, Danila Sinopalnikov, David Weinberger, Dimple Vijaykumar, Dominika Rogozińska, Dustin Herbison, Elisa Bandy, Emma Wang, Eric Noland, Erica Moreira, Evan Senter, Evgenii Eltyshev, Francesco Visin, Gabriel Rasskin, Gary Wei, Glenn Cameron, Gus Martins, Hadi Hashemi, Hanna Klimczak-Plucińska, Harleen Batra, Harsh Dhand, Ivan Nardini, Jacinda Mein, Jack Zhou, James Svensson, Jeff Stanway, Jetha Chan, Jin Peng Zhou, Joana Carrasqueira, Joana Iljazi, Jocelyn Becker, Joe Fernandez, Joost van Amersfoort, Josh Gordon, Josh Lipschultz, Josh Newlan, Ju yeong Ji, Kareem Mohamed, Kartikeya Badola, Kat Black, Katie Millican, Keelin McDonell, Kelvin Nguyen, Kiranbir Sodhia, Kish Greene, Lars Lowe Sjoesund, Lauren Usui, Laurent Sifre, Lena Heuermann, Leticia Lago, Lilly McNealus, Livio Baldini Soares, Logan Kilpatrick, Lucas Dixon, Luciano Martins, Machel Reid, Manvinder Singh, Mark Iverson, Martin Görner, Mat Velloso, Mateo Wirth, Matt Davidow, Matt Miller, Matthew Rahtz, Matthew Watson, Meg Risdal, Mehran Kazemi, Michael Moynihan, Ming Zhang, Minsuk Kahng, Minwoo Park, Mofi Rahman, Mohit Khatwani, Natalie Dao, Nenshad Bardoliwalla, Nesh Devanathan, Neta Dumai, Nilay Chauhan, Oscar Wahltinez, Pankil Botarda, Parker Barnes, Paul Barham, Paul Michel, Pengchong Jin, Petko Georgiev, Phil Culliton, Pradeep Kuppala, Ramona Comanescu, Ramona Merhej, Reena Jana, Reza Ardeshir Rokni, Rishabh Agarwal, Ryan Mullins, Samaneh Saadat, Sara Mc Carthy, Sarah Cogan, Sarah Perrin, Sébastien M. R. Arnold, Sebastian Krause, Shengyang Dai, Shruti Garg, Shruti Sheth, Sue Ronstrom, Susan Chan, Timothy Jordan, Ting Yu, Tom Eccles, Tom Hennigan, Tomas Kocisky, Tulsee Doshi, Vihan Jain, Vikas Yadav, Vilobh Meshram, Vishal Dharmadhikari, Warren Barkley, Wei Wei, Wenming Ye, Woohyun Han, Woosuk Kwon, Xiang Xu, Zhe Shen, Zhitao Gong, Zichuan Wei, Victor Cotruta, Phoebe Kirk, Anand Rao, Minh Giang, Ludovic Peran, Tris Warkentin, Eli Collins, Joelle Barral, Zoubin Ghahramani, Raia Hadsell, D. Sculley, Jeanine Banks, Anca Dragan, Slav Petrov, Oriol Vinyals, Jeff Dean, Demis Hassabis, Koray Kavukcuoglu, Clement Farabet, Elena Buchatskaya, Sebastian Borgeaud, Noah Fiedel, Armand Joulin, Kathleen Kenealy, Robert Dadashi, and Alek Andreev. Gemma 2: Improving open language models at a practical size, 2024. URL https://arxiv.org/abs/2408.00118.

Georg Thimm and Emile Fiesler. Evaluating pruning methods. In *International Symosium on Artifical Neural Networks*, 1995. URL https://api.semanticscholar.org/CorpusID:11075297.

Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention, 2021. URL https://arxiv.org/abs/2012.12877.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. Llama: Open and efficient foundation language models, 2023. URL https://arxiv.org/abs/2302.13971.

Grant Van Horn, Oisin Mac Aodha, Trevor Marquis, Steve Su, Mona Haghighi, Jason Baldridge, Subhransu Maji, and Pietro Perona. The inaturalist species classification and detection dataset. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 8769–8778. IEEE, 2018.

Jingcun Wang, Yu-Guang Chen, Ing-Chao Lin, Bing Li, and Grace Li Zhang. Basis sharing: Cross-layer parameter sharing for large language model compression, 2024a. URL https://arxiv.org/abs/2410.03765.

Xin Wang, Yu Zheng, Zhongwei Wan, and Mi Zhang. Svd-llm: Truncation-aware singular value decomposition for large language model compression, 2024b. URL https://arxiv.org/abs/2403.07378.

Xin Wang, Samiul Alam, Zhongwei Wan, Hui Shen, and Mi Zhang. Svd-llm v2: Optimizing singular value truncation for large language model compression, 2025. URL https://arxiv.org/abs/2503.12340.

Hao Yu and Jianxin Wu. Compressingtransformers. In *Proceedings of the Thirty-Seventh AAAI Conference on Artificial Intelligence and Thirty-Fifth Conference on Innovative Applications of Artificial Intelligence and Thirteenth Symposium on Educational Advances in Artificial Intelligence*, AAAI'23/IAAI'23/EAAI'23. AAAI Press, 2023. ISBN 978-1-57735-880-0. doi: 10.1609/aaai.v37i9.26304. URL https://doi.org/10.1609/aaai.v37i9.26304.

Zhihang Yuan, Yuzhang Shang, Yue Song, Qiang Wu, Yan Yan, and Guangyu Sun. Asvd: Activation-aware singular value decomposition for compressing large language models, 2023. URL https://arxiv.org/abs/2312.05821.

Jinnian Zhang, Houwen Peng, Kan Wu, Mengchen Liu, Bin Xiao, Jianlong Fu, and Lu Yuan. Minivit: Compressing vision transformers with weight multiplexing, 2022. URL https://arxiv.org/abs/2204.07154.

Aojun Zhou, Yukun Ma, Junnan Zhu, Jianbo Liu, Zhijie Zhang, Kun Yuan, Wenxiu Sun, and Hongsheng Li. Learning n:m fine-grained structured sparse neural networks from scratch, 2021. URL https://arxiv.org/abs/2102.04010.

Michael Zhu and Suyog Gupta. To prune, or not to prune: exploring the efficacy of pruning for model compression, 2017. URL https://arxiv.org/abs/1710.01878.

A Appendix

A.1 Method

Referring to § 2.2, we detail four methods for concatenating the FC weights of two MLPs (four matrices $\mathbf{W}_{ij} \in \mathbb{R}^{d \times p}$, with $p = 4d$ and $i, j \in \{1, 2\}$):

    I. **Full long-axis concatenation**, forming

$$\mathbf{W} = [\, \mathbf{W}_{11} \, \mathbf{W}_{12} \, \mathbf{W}_{21} \, \mathbf{W}_{22} \,] \ \in \ \mathbb{R}^{d \times 16d}.$$

Figure 5: **Parameter Sharing Through Sparse Tensor Decomposition.** A group of FC layers are concatenated along the larger dimension, p, and decomposed into two matrices: a shared basis, $\mathbf{U}$, and a sparse projection matrix, which is then sliced up respectively for each layer.

II. **Module-wise long + inter-module short:**

$$\mathbf{W}_A = [\mathbf{W}_{11}\mathbf{W}_{12}] \in \mathbb{R}^{d \times 8d}$$

$$\mathbf{W}_B = [\mathbf{W}_{21}\mathbf{W}_{22}] \in \mathbb{R}^{d \times 8d}$$

$$\mathbf{W} = \begin{bmatrix} \mathbf{W}_A \\ \mathbf{W}_B \end{bmatrix} \in \mathbb{R}^{2d \times 8d}.$$

III. **Module-wise short + inter-module long:**

$$\mathbf{W}_C = [\mathbf{W}_{11}\mathbf{W}_{21}] \in \mathbb{R}^{2d \times 4d}$$

$$\mathbf{W}_D = [\mathbf{W}_{12}\mathbf{W}_{22}] \in \mathbb{R}^{2d \times 4d}$$

,

$$\mathbf{W} = [\,\mathbf{W}_C\,\mathbf{W}_D\,] \in \mathbb{R}^{2d \times 8d}.$$

IV. **Full short-axis concatenation**, yielding

$$\mathbf{W} = \begin{bmatrix} \mathbf{W}_{11} \\ \mathbf{W}_{12} \\ \mathbf{W}_{21} \\ \mathbf{W}_{22} \end{bmatrix} \in \mathbb{R}^{4d \times 4d}.$$

These configurations are evaluated in Figure 2b and discussed in § 2.2.

The overall method is depicted in Figure 5, and further details are explained below.

A.1.1 MLP Concatenation Strategies

A.1.2 Growing Neurons in Shared Bases and Sparse Factors

As discussed in § 3, high parameter budgets and sparsity levels (e.g., 26.5% parameter budget, 75% sparsity, and groups of four blocks in DEIT-B) often result in the rank r exceeding the model dimension d. Since SVD yields only d initialization directions, we investigate three methods to initialize the remaining $k = r - d$ dimensions:

1. **Random Growth:** Initialize new neurons in $\mathbf{U}$ to zero and in $\mathbf{V}$ randomly using He et al. (2015);

2. **Neuron Splitting:** Duplicate the top k neurons of $\mathbf{U}$ and halve the top k neurons of $\mathbf{V}$, following Chen et al. (2016);

3. **Hybrid Initialization:** Initialize new neurons in $\mathbf{U}$ to zero and derive those in $\mathbf{V}$ from the top k neurons, scaled by τ. This minimizes the immediate impact of new neurons in $\mathbf{V}$, allowing their gradual reactivation, as proposed by Evci et al. (2022).

After performing a hyperparameter sweep for τ, hybrid initialization outperformed the alternatives, achieving 1% and 2% higher accuracy than methods (1) and (2), respectively.

A.2 Compression Ratio Computation

The reported compression ratio accounts for all storage overhead, including sparse metadata and uncompressed components:

- **Sparse factors (V):** We store both the nonzero values and their positions. For unstructured sparsity, we use a bitmap mask (1 bit per element). For 2:4 structured sparsity, the fixed pattern eliminates the need for explicit indices.

- **Shared basis (U):** Each group has one shared basis $\mathbf{U}$, counted once per group. For example, with $\beta = [4, 6, 6, 6, 6, 4]$ for LLAMA-7B (6 groups), we store 6 shared bases.

- **Non-MLP parameters:** Attention projections, embeddings, and layer norms remain uncompressed and are counted at full precision.

- **Quantized setup:** Each parameter is counted at its precision level (e.g., 3 bits for INT3), and masks are counted as 1 bit per element.

Formally, the compression ratio is:

$$\text{Compression Ratio} = \frac{|\theta_{\text{non-MLP}}| \cdot b + G \cdot |\mathbf{U}| \cdot b + \sum_i \left[(1 - s) \cdot |\mathbf{V}_i| \cdot b + |\mathbf{V}_i| \cdot 1\right]}{|\theta_{\text{original}}| \cdot b_{\text{original}}}, \tag{2}$$

where G is the number of groups, s is the sparsity level, b is the bits per parameter (e.g., 16 for `bfloat16`), b_{original} is the original precision, and the sum is over all sparse factors $\mathbf{V}_i$ across all layers. For 2:4 structured sparsity, the mask term $|\mathbf{V}_i| \cdot 1$ is omitted as the sparsity pattern is implicit.

A.3 Model Links

- DEIT-B (Touvron et al., 2021): https://huggingface.co/facebook/deit-base-patch16-224

- SWIN-L (Liu et al., 2021): https://huggingface.co/microsoft/swin-large-patch4-window7-224

- GEMMA-2-2B-IT (Team et al., 2024): https://huggingface.co/google/gemma-2-2b-it

- GEMMA-2-9B (Team et al., 2024): https://huggingface.co/google/gemma-2-9b

- LLAMA-7B (Grattafiori et al., 2024): https://huggingface.co/huggyllama/llama-7b

- LLAMA-3.1-8B (Grattafiori et al., 2024): https://huggingface.co/meta-Llama/Llama-3.1-8B

Table 6: **Sparsification Method and FiPS Generalization Performance.** ImageNet top-1 validation accuracy (%) of DEIT-B (81.85%) (Touvron et al., 2021) and SWIN-L (86.24%) (Liu et al., 2021) compressed with FiPS using different sparsity methods.

Parameter Budget	10%		25%		40%		50%		75%	
Method / Model	DEIT	SWIN	DEIT	SWIN	DEIT	SWIN	DEIT	SWIN	DEIT	SWIN
Dense	15.35	3.61	65.71	60.31	74.33	80.61	79.22	83.59	81.36	85.64
Static Sparsity	65.26	65.6	80.06	84.37	81.48	**85.69**	81.70	85.98	**81.86**	**86.23**
RigL	66.67	70.96	80.31	84.57	81.50	85.59	81.65	85.91	81.82	86.20
GMP (FiPS)	**70.04**	**74.04**	**80.64**	**84.78**	**81.69**	**85.69**	**81.83**	**85.99**	81.82	86.21

A.4 Further LLM Results

Variant	Compression Ratio	PPL ↓
Original	0%	7.34
SVD-LLM	20%	15.84
SVD-LLM V2	20%	11.72
FiPS (ours)	20%	**8.10**
SVD-LLM	40%	75.42
FiPS (ours)	40%	**10.57**

Table 5: Perplexity on C4 for Llama7B under different compression ratios applied with FiPS and the baselines.

A.5 Different Sparsification Methods

In addition to *GMP*, we evaluated *Dense* tensor decompositions (i.e., without sparsity on the **V** factors) and other sparse training techniques, specifically *Static Sparsity* and *RigL*. The results are summarized in Table 6. For DEIT-B, *RigL* consistently outperforms both *Dense* and *Static Sparsity* across parameter budgets ranging from 10% to 50%. At higher parameter budgets, all methods converge to similar accuracies approaching the original model's performance. For SWIN-L, *RigL* surpasses *Dense* and *Static Sparsity* at 10% and 25% parameter budgets. However, at higher parameter budgets, *Static Sparsity* achieves slightly higher accuracies. Detailed results are presented in Table 6.

A.6 Structured Sparsity

We evaluate the generalization performance of FiPS using structured sparsity, with results presented in Table 7. The methods evaluated include the Straight Through Estimator (*STE*), which employs top-k weight magnitude selection, projects parameters into a sparse subspace during training, and applies gradients to dense parameters through a gradual pruning schedule; Sparse-Refined STE (*SR-STE*) (Zhou et al., 2021), which mitigates the adverse effects of approximated gradients; and N:M Structured RigL (*NMSRigL*) and N:M Structured GMP (*NMSGMP*) (Lee et al., 2023; Lasby et al., 2024), where N:M specifies the sparsity pattern of the weight matrix (e.g., 50% sparsity in FC matrices of size $d \times 4d$ corresponds to a 2:4 structure).

A.7 Sensitivity Analysis

Calibration Dataset Size and Training Length. We examine how the number of calibration batches and training epochs affects performance using a fixed batch size of 128. To ensure at least one example from each category, we begin with a minimum of 10 batches and also evaluate 20, 40, and 80 batches. After filtering out configurations more than 0.25% below the highest accuracy, we adopt the most efficient setting of 20 epochs over 20 batches for all reported results, as shown in Figure 6b.

Compression Ratio	10%	25%	40%	50%	75%
STE	42.89	73.26	78.26	79.36	78.89
SR-STE	45.31	75.53	79.71	80.68	81.24
NMSRigL	44.87	75.71	79.97	80.99	81.40
NMSGMP	52.36	76.88	80.59	81.31	81.51
FiPS (50% Sparsity)	54.00	77.56	80.94	81.63	81.77
FiPS (75% Sparsity)	70.04	80.64	81.69	81.83	81.82

Table 7: **Structured Sparsity Performance.** ImageNet top-1 accuracy (%) of DEIT-B (81.85%) (Touvron et al., 2021) for various structured sparsification methods at 50% and 75% sparsity, compared to unstructured FiPS. Methods include Straight Through Estimator (*STE*), Sparse-Refined STE, N:M Structured RigL (*NMSRigL*), and N:M Structured GMP (*NMSGMP*) at 50% sparsity, corresponding to 2:4 structures (Lee et al., 2023; Zhou et al., 2021; Lasby et al., 2024).

(a) Optimal Sparsity.

(b) Calibration Data.

Figure 6: **Sensitivity Analysis.** (a) Impact of sparsity levels on DEIT-B accuracy. (b) Effect of calibration data volume and training duration.

Optimal Sparsity for Sparse Factors. We compressed DEIT-B as described in § 4.1, using sparsity levels ranging from 50% to 96.9% (Figure 6a). The best performance was observed at 75% sparsity. While increasing sparsity to 87% yielded similar accuracy, lowering it to 50% resulted in a notable performance drop, likely due to a significant reduction in rank.

A.8 Hyper-parameters

A.8.1 Ablation on the Block–Grouping Hyper-parameter β

Definition. We define β as an *ordered list* whose i^{th} element gives the number of consecutive decoder blocks whose MLP weights are tied in the i^{th} parameter sharing group:

$$\beta = [\beta_1,\ \beta_2,\ \ldots,\ \beta_G],\quad \sum_{g=1}^{G}\beta_g = L,$$

where L is the total number of decoder blocks. Self-attention parameters remain untied in all experiments. For every architecture we sweep over a small number of plausible β lists (3–5 candidates) and keep the one with the lowest validation perplexity (PPL) after compression.

Default Heuristic. Our analysis in § 2.3 shows that adjacent layers exhibit smaller reconstruction error when sharing, and deeper layers require more capacity. This motivates a "tapered" grouping where group sizes are smaller at the network extremes and larger in the middle. Based on our experiments, we propose the following reproducible default for a decoder with L blocks:

> Use 4–6 groups with β tapered as $[small, medium, \ldots, medium, small]$, where $small \approx L/8$ and $medium \approx L/5$.

For example:

- $L = 32$ (Llama): $\beta = [4, 6, 6, 6, 6, 4]$
- $L = 26$ (Gemma-2-2B): $\beta = [4, 4, 5, 5, 4, 4]$
- $L = 12$ (DeiT-B): $\beta = [4, 4, 4]$

Block Groups of ViTs. Using the list-valued notation for β introduced above, we set

$$\beta_{\text{DEIT-B}} = [4,\ 4,\ 4],$$

i.e. three groups of four consecutive blocks (each block contains one MLP).

The depth pattern of SWIN-L is 2+2+18+2 blocks. We tie MLP weights inside every 2-block stage and split the 18-block stage into three groups of six, which gives

$$\beta_{\text{SWIN-L}} = [2,\ 2,\ 6,\ 6,\ 6,\ 2].$$

Gemma-2-2B. Table 8 shows the five β lists evaluated for GEMMA-2-2B-IT at 20% compression. Config. 1—$\beta = [4, 4, 5, 5, 4, 4]$—yields the lowest PPL and is therefore used in the main paper. Notably, alternative groupings yield PPL within ∼2 points of the optimal (21.42 vs. ≈23), indicating that FiPS is not overly sensitive to this hyperparameter.

Llama-2-7B. With $L = 32$ decoder blocks we compared three β lists:

Candidate β	Block groups (sizes)	Observation
$[4, 4, 4, 4, 4, 4, 4, 4]$	8 groups × 4 blocks	Highest PPL
$[4, 6, 6, 6, 6, 4]$	**6 groups with sizes** $(4, 6, 6, 6, 6, 4)$	**Best PPL; used in §4.1**
$[8, 8, 8, 8]$	4 groups × 8 blocks	Slightly worse than above

A gently varying list—with smaller groups at the extremes and larger groups in the middle—provides the best compression/accuracy trade-off.

Table 8: **Block–grouping sweep for Gemma-2-2B.** Each row lists the candidate β and the resulting validation perplexity (PPL) on WikiText-2. Baseline (no sharing) PPL is 15.61; lower is better.

Config.	β **list**	PPL $\downarrow$
1	$[\,4, 4, 5, 5, 4, 4\,]$	21.42
2	$[\,1, 4, 4, 4, 4, 4, 4, 1\,]$	$\approx$23
3	$[\,2, 3, 4, 4, 4, 4, 3, 2\,]$	$\approx$22
4	$[\,2, 6, 6, 6, 6\,]$	21.81
5	$[\,3, 5, 5, 5, 5, 3\,]$	21.86

Llama-3.1-8B. The 8B model shares the same 32-layer decoder. We reused the winning β from the 7B sweep,

$$\beta_{\mathrm{opt}} = [\,4, 6, 6, 6, 6, 4\,],$$

because (i) it keeps the total tied-parameter ratio identical and (ii) in a spot-check it preserved PPL within +3.5 of the uncompressed baseline—better than the uniform alternatives $[\,8, 8, 8, 8\,]$ or $[\,4, 4, 4, 4, 4, 4, 4, 4\,]$. This demonstrates that the optimal β transfers across models of similar architecture.

Key Insights.

- Optimal β often starts and ends with smaller groups, reflecting the intuition that early and late layers contain more specialized features.

- Extremely fine-grained sharing (e.g., many 4-block groups) hurts accuracy, while overly coarse sharing (uniform 8-block groups) sacrifices capacity.

- For Llama models, a tapered list such as $[4, 6, 6, 6, 6, 4]$ ties roughly 22–25% of MLP parameters yet adds only $\sim$3–4 perplexity points.

- The method is robust to the choice of β: alternative groupings typically yield performance within 2 PPL points of the optimal.

These ablations inform all main-text compression results.

A.8.2 Optimizer

ViT Compression. To minimize local error, we employ a logarithmic grid for hyper-parameter tuning. The learning rates for Dense, Static Sparsity, GMP, and RigL are set as follows for both DeiT-B and Swin-L:

1. Dense: 1.25×10^{-4},

2. Static Sparsity: 2.5×10^{-4},

3. GMP: 1×10^{-3},

4. RigL: 1×10^{-3}.

ViT Transfer Learning. We use a linear grid, as some hyper-parameters are derived from the codebase of DeiT. The optimal learning rates for FiPS are:

1. CIFAR-100: 2.5×10^{-5};

2. Flowers102: 1×10^{-4};

3. Oxford-III-Pets: 7.5×10^{-6};

4. iNaturalist 2019: 1×10^{-4}.

(a) GPU latency (ms) vs. parameter budget (%).   (b) CPU latency (ms) vs. parameter budget (%).

Figure 7: **DeiT-B inference latency benchmarks.** (a) End-to-end latency of 2:4 sparse FiPS on an NVIDIA A4000 for batch sizes 1–64; a 22 % parameter budget yields a 25 % speed-up once the batch size exceeds 8. (b) Latency of 75 % unstructured sparse FiPS accelerated by DeepSparse on an Intel Xeon W-2145 CPU, outperforming the dense model at every tested batch size.

LLMs. Eight logarithmically spaced values were swept. The final values for FiPS are:

1. GEMMA-2-2B: 4.0×10^{-4},

2. LLAMA-7B: 1.0×10^{-6},

3. LLAMA-3.1-8B: 1.0×10^{-5}.

Sparsifier

Gradual Magnitude Pruning (GMP). GMP begins with an initial sparsity level of 25%. During training, sparsity is gradually increased to 50% at the 25% training mark and ultimately reaches 75% by training completion. We use $\Delta T = 50$ for update steps.

RigL. RigL employs an initialization phase that combines pruning with a growth ratio of 0.1 for block-wise error minimization and a growth ratio of 0.05 for transfer learning tasks, with $\Delta T = 50$ for growth and pruning steps. This conservative growth ratio in transfer learning helps preserve the mask obtained during initial training, ensuring that learned masks are retained.

A.9 Latency and Memory Profiling

As discussed in § 3, high levels of sparsity and parameter budgets can result in the SVD rank exceeding a model's hidden dimension. For instance, in DEIT-B, achieving 75% sparsity under parameter budget constraints exceeding 26.5% with four block groups increases the rank of the shared singular vectors beyond the original model's embedding dimension. Efficient sparse operations and representations are crucial for minimizing the latency and memory overhead introduced by FiPS. Figure 7 and Figure 8 summarize the latency and memory results for DEIT-B compressed with FiPS using 2:4 structured GMP, highlighting the resulting speedups and memory savings on both CPU and GPU platforms.

Figure 8: **DeiT-B Inference Memory Profile.** Maximum VRAM allocation at batch size 64 for 50% sparse FiPS using 2:4, strided (dense), and CSR tensor formats. At 10% and 25% parameter budgets, 2:4 sparsity reduces peak memory by 44% and 18%, respectively; CSR incurs higher overhead at modest sparsity due to index storage.