SUPERCLASS-CONDITIONAL GAUSSIAN MIXTURE MODEL FOR LEARNING FINE-GRAINED EMBEDDINGS

ABSTRACT

Learning fine-grained embeddings is essential for extending the generalizability of models pretrained on "coarsely" annotated labels (*e.g.*, animals). It is crucial to fields where fine-grained labeling (*e.g.*, breeds) requires strong domain expertise thus is prohibitive, such as medicine, but predicting them is desirable. The dilemma necessitates the adaptation of a "coarsely" pretrained model to new tasks with a few unseen "finer-grained" training labels. However, pretraining with only coarse supervision tends to suppress intra-class variation, which is indispensable for cross-granularity adaptation. In this paper, we develop a training framework underlain by a novel superclass conditional Gaussian mixture model (SCGM). SCGM imitates the generative process of samples from hierarchies of classes by means of latent variable modeling of the superclass-subclass relationships. The framework is agnostic to the encoders and only adds a few distribution related parameters, thus is efficient, and flexible to different domains. The model parameters are learned end-to-end by maximum-likelihood estimation via an Expectation-Maximization algorithm in a principled manner. Extensive experimental results on benchmark datasets and a real-life medical dataset demonstrate the effectiveness of our method.

1 INTRODUCTION

Training deep models with sufficient generalizability is of fundamental importance in real-life tasks, which often demands immense training data with fine-grained annotations (Krizhevsky et al., 2012; Brown et al., 2020). This need, however, is hard to fulfill in many fields as exhaustive data labeling requires domain-specific knowledge, such as medicine (Sohoni et al., 2020), which is prohibitive, and infeasible at a large-scale. Therefore, it is a common practice that during model training, only data with "coarse" labels are available, while later the model may be tested on a finer-grained classification task (Bukchin et al., 2021). For example, consider an event prediction task for dialysis patients (Inaguma et al., 2019). Hemodialysis is a major renal replacement therapy for patients with end-stage renal failure. These patients have to undertake hemodialysis thrice a week, each lasts for 4-5 hours. During the treatment, unexpected events, such as muscle cramp, perspiration, and dizziness, may happen as a result of lowering blood pressure, which need intensive medical care, thus should always be avoided. It is therefore an important medical issue to predict such events before an initiation of hemodialysis. In this task, binary labels, which mark whether an event has occurred in a dialysis or not, can be collected. In contrast, finer-grained labels that annotate different subtypes of events are seldom recorded. Whereas, distinguishing different subtypes could facilitate precise diagnoses, given that different patients have different chances of having certain types of events. Hence, it is desirable that a model trained with only coarse (binary) labels can perform well on a finer-grained multi-class (subtypes) task.

To fill the gap of granularity between the training and testing scenarios, a practical way is to collect a few new records for a patient, with their fine-grained annotations. These data constitute a *support set* for adapting a pre-trained model to the specific data distribution of the target patient, for whom the adapted (personalized) model is used for future predictions. Although massive fine-grained annotation is impractical, annotating a few-shot set is feasible. In this work, we are interested in such a Cross-Granularity Few-Shot (CGFS) learning problem, where a model pre-trained on a set of coarse classes (denoted as *superclasses*), needs to adapt to an unseen set of fine-grained target classes (denoted as *subclasses*). The target subclasses could be descendants of the superclasses (as in the

aforementioned example), or a separate set that descends from unseen siblings of the superclasses. To be practical, the adaptation should only use a few samples from the subclasses.

The CGFS problem is not limited to the above application. It typically occurs in the lifespan of a model when an application requires separating some subclasses from the superclasses yet when the training dataset was created these subclasses were unknown or unannotated. For example, it occurs in detecting rare pathology or variants using medical images that were coarsely described (Oakden-Rayner et al., 2020; Sohoni et al., 2020), and in personalizing a generic model that was trained on all historical users to a specific customer (Luo et al., 2020).

Despite its practical significance, CGFS is challenging. It cannot be trivially solved by regularly training models with coarse supervision, because typical losses for supervised learning aim to maximize inter-class boundaries but neglect intra-class variation. As a result, subclasses may arbitrarily spread within every superclass. Until very recently, Bukchin et al. (2021) proposed to integrate coarse supervision and contrastive learning (within superclasses) for solving CGFS. However, their approach is confined to images, and cannot be readily used for medical records which typically contain static profiles and time series (Che et al., 2016). This is due to the absence of a standard data augmentation method for generating positive/negative pairs on data other than images. Also, since contrastive learning does not model subclasses explicitly, their solution is suboptimal. Moreover, as their model was built upon MoCo (He et al., 2020), and maintains as many dictionaries as the number of superclasses, its computational costs are high (evaluated in Sec. 4).

In this work, we propose a novel Superclass-Conditional Gaussian Mixture model (SCGM) to learn fine-grained embeddings for CGFS problem. SCGM is agnostic to the encoder, thus is flexible to different applications. SCGM models the generation of samples from hierarchies of classes. It explicitly represents the unobserved subclasses by latent variables, and dynamically computes a Gaussian mixture for every sample conditioned on its superclass. Instantiating the conditional probabilities by Mahalanobis distance, the entire system forms a hierarchy of Gaussian mixtures. SCGM only adds a small overhead to an encoder, for parameterizing its distributions. The model parameters are learned by maximum likelihood estimation (MLE) via an Expectation-Maximization (EM) algorithm, of which both E-step and M-step optimize the same loss in a principled manner. We also theoretically linked our loss to InfoNCE (Oord et al., 2018), explaining its effectiveness from a contrastive perspective. In the experiments, we evaluated SCGM on both benchmark image datasets and a real-life medical dataset. Since SCGM is compatible with contrastive learning, we also tested it with a momentum encoder (He et al., 2020). The results demonstrate SCGM on generic encoders has already outperformed SOTA baselines, with less computational costs, and it achieves boosted performance in some cases with momentum contrast integrated.

2 RELATED WORK

To our best knowledge, this is the first work to develop a superclass-conditional Gaussian mixture model for underlying a framework that enables tackling CGFS across domains. The most relevant work (Bukchin et al., 2021) combines superclass-wise contrastive learning with coarse classification for preserving intra-class variation. Another work (Yang et al., 2021) used a three-step approach that pseudo-labels the pretrained embeddings (learned by coarse classification and batch-wise contrastive learning) by clustering every superclass. The pseudo-fine-labels were used to retrain the encoder. A similar three-step method was used in (Sohoni et al., 2020), but with a different loss for maximizing the worst-case expected accuracy over the pseudo-labeled subclasses. As discussed before, by contrastive learning, the former two methods cannot be trivially extended to non-image data due to the absence of a general method for data augmentation. By splitting training steps, the latter two methods cannot leverage coarse training to guide their pseudo-labeling, thus may induce misleading labels that could confuse the downstream step. In contrast, our model is end-to-end. It explicitly infers the posterior of the subclass during coarse training. Moreover, it can achieve better performance without using as many computational resources as the model of (Bukchin et al., 2021) (Sec. 4).

Learning with coarse supervision. Several works deal with coarse/fine labels from the perspective of weakly supervised learning (Zhou, 2018) than to tackle the CGFS problem, including training methods that take advantage of a mixture of either balanced (Ristin et al., 2015; Guo et al., 2018; Taherkhani et al., 2019) or unbalanced (Hsieh et al., 2019; Liu et al., 2019; Robinson et al., 2020) coarse and fine labels. Among them, Liu et al. (2019) addressed a few-shot learning problem, but

the model training assumes access to some fine labels and a graph of class hierarchy, which are unavailable in our problem. Thus it cannot be adapted to solve our problem.

Few-shot learning. Meta-learning has become a popular idea to handle the few-shot learning problem, which derives metric-based (Vinyals et al., 2016; Snell et al., 2017) and optimization-based methods (Finn et al., 2017; Nichol et al., 2018). The idea has been extended to semi-supervised (Ren et al., 2018), unsupervised (Hsu et al., 2018) and semantics-augmented (Xing et al., 2019) scenarios, when labels are scarce. However, none of them explores coarse labels for cross-granularity learning. Recently, many works observed that learning embeddings on all classes (without episodic training), followed by simple fine-tuning, is superior to SOTA meta-learning methods (Wang et al., 2019; Dhillon et al., 2020; Tian et al., 2020). In this work, similar to (Bukchin et al., 2021), we focus on this paradigm to learn useful embeddings, and do not use meta-learning for pre-training.

Embedding methods. The emerging self-supervised methods, such as contrastive methods (Oord et al., 2018; Chen et al., 2020a; He et al., 2020), are appealing in their ability to attain comparable embeddings to the supervised counterparts, and even surpass them when transferring to other tasks (He et al., 2020; Tian et al., 2020). Beyond instance-wise contrast, recent methods have explored instance-cluster contrast to boost performance (Caron et al., 2020; Li et al., 2020). In unsupervised methods, joint embedding and clustering has been found beneficial (Caron et al., 2018; Asano et al., 2020). Whereas, these methods never exploited coarse supervision. Thus, their embeddings/clusters do not necessarily reflect intra-class variation, which is important to the CGFS task.

Vanilla Gaussian mixture (GM) model is unfit for the CGFS scenario. A recent work (Manduchi et al., 2021) extended GM to constrained clustering by conditioning every sample with a prior clustering preference. It is neither supervised by coarse classes nor hierarchically structured. Conventional hierarchical GM is used for hierarchical clustering (Goldberger & Roweis, 2005; Olech & Paradowski, 2016; Athey et al., 2019) by applying GM agglomeratively or divisively. These methods are unsupervised, and cannot be used to solve our investigated problem.

3 SUPERCLASS-CONDITIONAL GAUSSIAN MIXTURE MODEL

Firstly, a word about some notations. Let $\mathcal{D}_{\text{train}} = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$ be n sample-label training pairs, where $y_i \in \mathcal{Y}_{\text{super}} = \{1, ..., c\}$ is a *superclass* label. Each $\mathbf{x}_i$ is associated with a latent (unobserved) *subclass* label $\hat{y}_i \in \mathcal{Y}_{\text{sub}} = \{1, ..., s\}$. $\mathcal{Y}_{\text{sub}}$ relates to $\mathcal{Y}_{\text{super}}$ by a hierarchical structure, *i.e.*, $\mathcal{Y}_{\text{sub}}$ can be partitioned into c disjoint sets $\mathcal{Y}_{\text{sub-1}}, ..., \mathcal{Y}_{\text{sub-}c}$, such that if $\hat{y}_i \in \mathcal{Y}_{\text{sub-}j}$, then $y_i = j$ ($1 \leq j \leq c$). Let $f_{\boldsymbol{\theta}}$ be an encoder (*i.e.*, backbone network) that is trained on $\mathcal{D}_{\text{train}}$ (without knowing $\mathcal{Y}_{\text{sub}}$). It maps $\mathbf{x}_i$ to a d-dimensional feature $f_{\boldsymbol{\theta}}(\mathbf{x}_i)$. At test time, given a k-shot support set for a subset $\mathcal{Y}_{\text{sub}}^m \subseteq \mathcal{Y}_{\text{sub}}$ of m subclasses, *i.e.*, $\mathcal{D}_{\text{support}} = \{(\mathbf{x}_i, \hat{y}_i)|\hat{y}_i \in \mathcal{Y}_{\text{sub}}^m\}_{i=1}^{mk}$, the task is to train a classifier $C: \mathbb{R}^d \rightarrow \mathcal{Y}_{\text{sub}}^m$ with optimal accuracy on a test set of $\mathcal{Y}_{\text{sub}}^m$ subclasses. In our experiments, we also explored the case when the subclasses belong to unseen superclasses. As discussed in Sec. 2, our focus is to train $f_{\boldsymbol{\theta}}$ for good embeddings without modifying $f_{\boldsymbol{\theta}}$ during the adaptation–a paradigm with SOTA few-shot performance (Wang et al., 2019; Dhillon et al., 2020; Tian et al., 2020).

Formally, let $f_{\boldsymbol{\theta}}(\mathbf{x}_i) = \mathbf{v}_i$, our goal is to find the model parameter $\boldsymbol{\theta}$ that maximizes the likelihood of the posterior distribution $p_{\boldsymbol{\theta}}(y_i|\mathbf{v}_i)$ on the observed data in $\mathcal{D}_{\text{train}}$ for classification tasks (Grathwohl et al., 2019). To model the unobserved subclasses, we associate every $\mathbf{v}_i$ with a latent variable z_i to indicate to which subclass $\mathbf{v}_i$ belongs. Suppose there are r possible subclasses, the log-likelihood to maximize can be rewritten by marginalizing out the latent variables.

$$\ell(\mathcal{D}_{\text{train}}; \boldsymbol{\theta}) = \frac{1}{n} \sum_{i=1}^n \log \left[p_{\boldsymbol{\theta}}(y_i|\mathbf{v}_i) \right] = \frac{1}{n} \sum_{i=1}^n \log \left[\sum_{z_i=1}^r p(y_i|z_i) p_{\boldsymbol{\theta}}(z_i|\mathbf{v}_i) \right] \tag{1}$$

where the distribution $p_{\boldsymbol{\theta}}(z_i|\mathbf{v}_i)$ specifies the subclass membership of $\mathbf{v}_i$, and $p(y_i|z_i)$ associates z_i with a subclass partition $\mathcal{Y}_{\text{sub-}y_i}$. Unlike some previous works (Sohoni et al., 2020), which allocated a pre-determined number of subclasses to every superclass, we only assume a total number of r subclasses, and seek to infer their relationship to superclasses, *i.e.*, $p(y_i|z_i)$, without any prior on subclass partitions, so that the model is more generalizable.

3.1 PARAMETERIZATION OF PROBABILITIES

In Eq. (1), both $p(y_i|z_i)$ and $p_{\boldsymbol{\theta}}(z_i|\mathbf{v}_i)$ are not specified, and involve non-parametric variables. To make it solvable, we introduce our SCGM that models the generative process of the embeddings.

Figure 1: An illustration of (a) embedding distribution tuned by SCGM via dynamic mixture probabilities $\boldsymbol{\pi}^i$, when $y_i = 1$, and (b) when $y_i = 2$, where (c) summarizes SCGM's graphical model.

Let $\boldsymbol{\mu}_j$ and $\boldsymbol{\Sigma}_j$ ($1 \leq j \leq r$) be the mean and variance of the j-th mixture component, and π_j be its corresponding mixture probability. In a generic GM model, the generation of $\mathbf{v}_i$ involves two steps: (1) draw a latent variable z_i from a categorical distribution on all mixture components, and (2) draw $\mathbf{v}_i$ from the Gaussian distribution $\mathcal{N}(\boldsymbol{\mu}_{z_i}, \boldsymbol{\Sigma}_{z_i})$ (Bishop, 2006), as illustrated by Fig. 1(c).

In step (1), the categorical distribution is usually defined on $\boldsymbol{\pi} = [\pi_1, ..., \pi_r] \in \mathbb{R}^r$, *i.e.*, the static mixture probabilities, which cannot reflect different samples' superclasses. In light of this, for each $\mathbf{v}_i$, we propose to define $\boldsymbol{\pi}^i = [\pi_1^i, ..., \pi_r^i]$ to be conditional on y_i, which dynamically changes w.r.t. different samples. To this end, we introduce $\bar{\boldsymbol{\mu}}_{y_i}$ and $\bar{\boldsymbol{\Sigma}}_{y_i}$ as the mean and variance of superclass y_i, and compute $\pi_j^i = \text{softmax}(-D_{y_i}(\boldsymbol{\mu}_j)^2/2)$, where $D_{y_i}(\cdot)$ measures the Mahalanobis distance between a data point and the superclass distribution $\mathcal{N}(\bar{\boldsymbol{\mu}}_{y_i}, \bar{\boldsymbol{\Sigma}}_{y_i})$. Basically, π_j^i evaluates the density ratio of the mixture component mean $\boldsymbol{\mu}_j$, by regarding it as a sample from y_i's distribution.

$$\pi_j^i = \frac{\exp\left(-\frac{1}{2}(\boldsymbol{\mu}_j - \bar{\boldsymbol{\mu}}_{y_i})^\top \bar{\boldsymbol{\Sigma}}_{y_i}^{-1}(\boldsymbol{\mu}_j - \bar{\boldsymbol{\mu}}_{y_i})\right)}{\sum_{j'=1}^{r} \exp\left(-\frac{1}{2}(\boldsymbol{\mu}_{j'} - \bar{\boldsymbol{\mu}}_{y_i})^\top \bar{\boldsymbol{\Sigma}}_{y_i}^{-1}(\boldsymbol{\mu}_{j'} - \bar{\boldsymbol{\mu}}_{y_i})\right)} = \frac{p_N(\boldsymbol{\mu}_j | \bar{\boldsymbol{\mu}}_{y_i}, \bar{\boldsymbol{\Sigma}}_{y_i})}{\sum_{j'=1}^{r} p_N(\boldsymbol{\mu}_{j'} | \bar{\boldsymbol{\mu}}_{y_i}, \bar{\boldsymbol{\Sigma}}_{y_i})} \qquad (2)$$

where $p_N(\cdot|\cdot)$ represents the density function of a multivariate Gaussian distribution.

Our generative process can be summarized as

1. for each sample index i:
   (a) draw a superclass label $y_i \sim \text{Categorical}(p(y_i))$
   (b) for $j = 1, ..., r$:
       i. compute $\pi_j^i = \text{softmax}(-D_{y_i}(\boldsymbol{\mu}_j)^2/2)$ using Mahalanobis distance $D_{y_i}(\cdot)$
   (c) draw a latent subclass variable for the i-th sample $z_i \sim \text{Categorical}([\pi_1^i, ..., \pi_r^i])$
   (d) draw a feature vector $\mathbf{v}_i \sim \mathcal{N}(\boldsymbol{\mu}_{z_i}, \boldsymbol{\Sigma}_{z_i})$

where $p(y_i)$ is a prior on superclasses, which can be drawn from a Dirichlet distribution $\text{Dir}(\boldsymbol{\alpha})$ (the conjugate of categorical distribution), and $\boldsymbol{\alpha}$ can be estimated by the ratios of different labels in $\mathcal{D}_{\text{train}}$. $p(y_i)$ can also be set as a uniform prior, for unknown datasets and better generalization.

As can be seen, steps (a)(b) specifies a (static) mixture of superclasses, and steps (c)(d) specifies a (dynamic) mixture of subclasses. The whole process establishes a hierarchical GM distribution. Fig. 1(a)(b) illustrate the process using 2 superclasses and 3 subclasses, where the embedding distribution $p(\mathbf{v}_i|y_i)$ dynamically changes w.r.t. $\mathbf{v}_i$'s superclass as a result of updated $\boldsymbol{\pi}^i$. For example, when $y_i = 1$ (Fig. 1(a)), $\mathbf{v}_i$ is more likely to be generated from the first two subclasses. This y_i-adjusted Gaussian mixture distribution highlights the first two subclasses, and will be used to fit data with $y_i = 1$ during model training. Fig. 1(c) bottom illustrates the graphical model of SCGM, which distinguishes itself from the generic GM in Fig. 1(c) by (1) the condition y_i, and (2) the variable $\boldsymbol{\pi}^i$.

Now, if we consider $\bar{\boldsymbol{\mu}}_{y_i}$ and $\boldsymbol{\mu}_{z_i}$ as the *surrogate representations* of y_i and z_i in the embedding space, we can specify two probabilities $p(z_i|y_i)$ and $p(\mathbf{v}_i|z_i)$ using their corresponding densities:

$$p(z_i|y_i) = p_N(\boldsymbol{\mu}_{z_i} | \bar{\boldsymbol{\mu}}_{y_i}, \bar{\boldsymbol{\Sigma}}_{y_i}), \qquad p(\mathbf{v}_i|z_i) = p_N(\mathbf{v}_i | \boldsymbol{\mu}_{z_i}, \boldsymbol{\Sigma}_{z_i}) \qquad (3)$$

from which, the probabilities $p(y_i|z_i)$ and $p(z_i|\mathbf{v}_i)$ in Eq. (1) can be derived by using Bayesian rules as (the detailed derivation is deferred to Appendix A.1)

$$p_\phi(y_i|z_i) = \frac{p_N(\boldsymbol{\mu}_{z_i} | \bar{\boldsymbol{\mu}}_{y_i}, \bar{\boldsymbol{\Sigma}}_{y_i}) p(y_i)}{\sum_{y_i'=1}^{c} p_N(\boldsymbol{\mu}_{z_i} | \bar{\boldsymbol{\mu}}_{y_i'}, \bar{\boldsymbol{\Sigma}}_{y_i'}) p(y_i')}, \qquad p_{\boldsymbol{\theta}, \phi}(z_i|\mathbf{v}_i) = \frac{p_N(\mathbf{v}_i | \boldsymbol{\mu}_{z_i}, \boldsymbol{\Sigma}_{z_i}) \pi_{z_i}^i}{\sum_{z_i'=1}^{r} p_N(\mathbf{v}_i | \boldsymbol{\mu}_{z_i'}, \boldsymbol{\Sigma}_{z_i'}) \pi_{z_i'}^i} \qquad (4)$$

where $\boldsymbol{\theta}$ are the parameters of encoder $f_{\boldsymbol{\theta}}$, $\boldsymbol{\phi}$ includes our added distribution parameters. To reduce complexity, in this work, we investigate the feasibility of using isotropic Gaussian with tied variance, *i.e.*, $\boldsymbol{\Sigma}_{z_i} = \mathbf{I}\sigma^2$ and $\bar{\boldsymbol{\Sigma}}_{y_i} = \mathbf{I}\bar{\sigma}^2$, which turned out to be efficient in our experiments. Here, $\mathbf{I}$ is the identity matrix, σ and $\bar{\sigma}$ are hyperparameters. Empirically, it is sufficient to set $\bar{\sigma} = 1$ and tune σ to adjust the relativity between super- and subclasses. Also, tied variance is a commonly used trick in Gaussian discriminate analysis (GDA) for generative classifiers (Lee et al., 2018).

Finally, substituting the factors in Eq. (1) with Eq. (4), whose probabilities are specified and parameterized, we get our SCGM induced loss $\ell_{\text{SCGM}}(\mathcal{D}_{\text{train}}; \boldsymbol{\theta}, \boldsymbol{\phi})$, where $\boldsymbol{\phi} = \{\{\boldsymbol{\mu}_j\}_{j=1}^r, \{\bar{\boldsymbol{\mu}}_j\}_{j=1}^c\}$.

3.2 Model Optimization via Expectation-Maximization

It is hard to directly optimize $\ell_{\text{SCGM}}(\mathcal{D}_{\text{train}}; \boldsymbol{\theta}, \boldsymbol{\phi})$, because exact posterior inference is intractable (due to an exponential searching space). To solve it, we resort to variational methods, and introduce an approximated posterior $q(z_i|\mathbf{v}_i, y_i)$, where y_i is included so that the inference is also conditioned on superclass. Then, a lower-bound of Eq. (1) is derived as (the details are in Appendix A.2)

$$\ell_{\text{SCGM}}(\mathcal{D}_{\text{train}}; \boldsymbol{\theta}, \boldsymbol{\phi}) \geq \frac{1}{n}\sum_{i=1}^n \mathbb{E}_{q(z_i|\mathbf{v}_i, y_i)}\big[\log p_{\boldsymbol{\phi}}(y_i|z_i) + \log p_{\boldsymbol{\theta},\boldsymbol{\phi}}(z_i|\mathbf{v}_i) - \log q(z_i|\mathbf{v}_i, y_i)\big] \quad (5)$$

which can be maximized by alternately inferring the posterior $q(z_i|\mathbf{v}_i, y_i)$ and solving the model parameters $\{\boldsymbol{\theta}, \boldsymbol{\phi}\}$ through an Expectation-Maximization (EM) algorithm.

E-step. This step is to infer $q(z_i|\mathbf{v}_i, y_i)$ when fixing model parameters. A straightforward way is to apply k-means on the embeddings $\mathbf{v}_i$, similar to (Caron et al., 2018). However, as discussed in (Asano et al., 2020), alternately applying k-means and learning embeddings without any constraints will lead to a degenerate solution, *i.e.*, all samples are assigned to a single (arbitrary) subclass. Also, k-means is unaware of the superclass y_i as it doesn't optimize Eq. (5) theoretically. To address this problem, inspired by (Asano et al., 2020), let $\mathbf{Q}_{z_i, i} = q(z_i|\mathbf{v}_i, y_i)$ and $\mathbf{P}_{z_i, i} = p_{\boldsymbol{\phi}}(y_i|z_i)p_{\boldsymbol{\theta},\boldsymbol{\phi}}(z_i|\mathbf{v}_i)$ be two $r \times n$ matrices, we enforce an equal partition of subclasses by constraining $\mathbf{Q}$ to belong to the *transportation polytope*, and rewrite Eq. (5) as (the derivation is in Appendix A.3)

$$\min_{\mathbf{Q} \in \mathcal{Q}} -\frac{1}{n}\Big(\text{Tr}(\mathbf{Q}^\top \log \mathbf{P}) + \frac{1}{\lambda}H(\mathbf{Q})\Big), \quad \text{where } \mathcal{Q} = \Big\{\mathbf{Q} \in \mathbb{R}_+^{r \times n} | \mathbf{Q}\mathbf{1}_n = \frac{1}{r}\mathbf{1}_r, \mathbf{Q}^\top\mathbf{1}_r = \frac{1}{n}\mathbf{1}_n\Big\} \quad (6)$$

where $H(\mathbf{Q}) = -\sum_{ij}\mathbf{Q}_{ij}\log\mathbf{Q}_{ij}$ is the entropy function, $\mathbf{1}_n$ is the vector of ones in dimension n, and $\lambda \geq 1$ controls the regularization (it also further relaxes the lower-bound in Eq. (5)).

The problem in Eq. (6) is a regularized instance of the optimal transport problem, whose minimizer can be written as $\mathbf{Q}^* = \text{Diag}(\mathbf{u})\mathbf{P}^\lambda\text{Diag}(\mathbf{v})$, where $\mathbf{u} \in \mathbb{R}^r$ and $\mathbf{v} \in \mathbb{R}^n$ are renormalization vectors. These vectors can be efficiently solved by the iterative Sinkhorn-Knopp algorithm (Cuturi, 2013). Once $\mathbf{Q}^*$ is found, rounding its values and using discrete codes adds more algorithmic stability.

M-step. Fixing $q(z_i|\mathbf{v}_i, y_i)$, the model parameters $\{\boldsymbol{\theta}, \boldsymbol{\phi}\}$ can be efficiently solved by stochastic gradient descent (SGD). Combining Eq. (4) and Eq. (5), the loss to minimize is (Appendix A.4)

$$\ell_{\boldsymbol{\phi},\boldsymbol{\theta}} = -\frac{1}{n}\sum_{i=1}^n q(z_i|\mathbf{v}_i, y_i)\Bigg[\log \frac{\exp(\boldsymbol{\mu}_{z_i}^\top \cdot \bar{\boldsymbol{\mu}}_{y_i}/\bar{\sigma}^2)p(y_i)}{\sum_{y_i'=1}^c \exp(\boldsymbol{\mu}_{z_i}^\top \cdot \bar{\boldsymbol{\mu}}_{y_i'}/\bar{\sigma}^2)p(y_i)} + \log \frac{\exp(\mathbf{v}_i^\top \cdot \boldsymbol{\mu}_{z_i}/\sigma^2)\pi_{z_i}^i}{\sum_{z_i'=1}^c \exp(\mathbf{v}_i^\top \cdot \boldsymbol{\mu}_{z_i'}/\sigma^2)\pi_{z_i'}^i}\Bigg] \quad (7)$$

It is noteworthy that the two terms in the bracket have similar form to InfoNCE (Oord et al., 2018). Therefore, Eq. (7) can be interpreted from a contrastive perspective, where the positive pairs in both terms are specified by $q(z_i|\mathbf{v}_i, y_i)$ from E-step, *i.e.*, (z_i, y_i) and $(z_i, \mathbf{v}_i)$ that induce the maximal $q(z_i|\mathbf{v}_i, y_i)$, and the variances σ^2 and $\bar{\sigma}^2$ resemble temperature scaling. Thus, the M-step seeks to push the embedding $\mathbf{v}_i$ to its closest subclass $\boldsymbol{\mu}_{z_i}$, which should meanwhile be close to its superclass $\bar{\boldsymbol{\mu}}_{y_i}$, in contrast to the distances of the negative pairs. In the second term, $\pi_{z_i}^i$ (Eq. (2)) serves as a weight to select $\boldsymbol{\mu}_{z_i}$ that is close to $\bar{\boldsymbol{\mu}}_{y_i}$. As such, our problem can be seen as a generalized InfoNCE for subclass- and superclass-level contrasitive learning.

In practice, we found it is beneficial to integrate Eq. (7) with cross-entropy loss ℓ_{CE} (on superclass)

$$\ell(\mathcal{D}_{\text{train}}; \boldsymbol{\theta}, \boldsymbol{\phi}) = \ell_{CE}(\mathcal{D}_{\text{train}}; \boldsymbol{\theta}, \{\bar{\boldsymbol{\mu}}_j\}_{j=1}^c) + \gamma\ell_{\boldsymbol{\phi},\boldsymbol{\theta}}(\mathcal{D}_{\text{train}}; \boldsymbol{\theta}, \boldsymbol{\phi}) \quad (8)$$

where ℓ_{CE} uses superclass means $\{\bar{\boldsymbol{\mu}}_j\}_{j=1}^c$ as the classification weights, γ is a trade-off parameter. The detailed algorithm for training SCGM can be found in Algorithm 1 in Appendix A.5.

4 EXPERIMENTS

In this section, we first evaluate SCGM on benchmark datasets and compare it with SOTA methods. Then we evaluate SCGM for a model personalization task on a real-life medical dataset.

The table below summarizes the benchmark datasets: (1) {Living17, Nonliving26, Entity13, Entity30} are four datasets from BREEDS (Santurkar et al., 2020), which was derived from ImageNet with class hierarchy calibrated so that classes on the same level are of similar visual granularity; (2) CIFAR-100 (Krizhevsky, 2009); and (3) *tiered*ImageNet (Ren et al., 2018), which is widely used for few-shot learning study. It has 34 superclasses as per the ImageNet hierarchy, and was divided into 20/6/8 splits for train/val/test sets. For BREEDS and CIFAR-100, the val set is 10% of the train set. These datasets have been used in (Bukchin et al., 2021).

Dataset	Living17	Nonliving26	Entity13	Entity30	CIFAR-100	Tiered
# Coarase classes	17	26	13	30	20	20/6/8
# Fine classes	68	104	260	240	100	351/97/160
# Train images	88K	132K	334K	307K	50K	448K
# Test images	3.4K	5.2K	13K	12K	10K	206K
Image resolution	224×224	224×224	224×224	224×224	32×32	84×84

4.1 EXPERIMENTAL SETUP

Baselines. We compare SCGM with the most relevant SOTA models on embedding learning, including self-supervised models: (1) MoCo-v2 (Chen et al., 2020b) trained on each of the above dataset; (2) MoCo-v2-ImageNet pretrained on ImageNet by Chen et al. (2020b); (3) SwAV-ImageNet is a pretrained model by (Caron et al., 2020), which takes advantage of cluster-level contrastive learning. Note that pretrained models on full ImageNet saw more data during training than did SCGM. (4) ANCOR (Bukchin et al., 2021), as introduced in Sec.1 and 2; (5) GEORGE (Sohoni et al., 2020), a three-step framework that uses a separate clustering step to pseudo-fine-label the dataset; and (6) SeLa (Asano et al., 2020), an unsupervised algorithm for joint clustering and embedding. The detailed setup of these models was deferred to Appendix B.1.

Similar to (Bukchin et al., 2021), we include natural baselines trained on superclasses: (7) "Coarse", uses encoder $\mathcal{B}$ followed by classifier C; (8) "Coarse+", uses $\mathcal{B} \to \mathcal{E} \to C$, which adds an embedder $\mathcal{E}$. Also, baselines trained on subclass labels represent performance upper-bounds: (9) "Fine", uses $\mathcal{B} \to C$; and (10) "Fine+", uses $\mathcal{B} \to \mathcal{E} \to C$. For our method, since it is a flexible framework, we tested it with a generic encoder, and a momentum-based encoder with superclass-wise dictionaries similar to ANCOR (Bukchin et al., 2021). We denote these two variants by SCGM-G and SCGM-A, where the training loss (*i.e.*, Eq. (8)) of the latter adds an InfoNCE term with angular normalization. The detailed implementation of SCGM-A can be found in Appendix B.2.

Implementation. The encoder is ResNet-50 (He et al., 2016) for the 224×224 images in BREEDS, and ResNet-12 for the small resolution images in CIFAR-100 and *tiered*ImageNet, as is common in few-shot learning works. The output dim of these networks is 2048 and 640, respectively. Similar to (Chen et al., 2020b), two types of embedder $\mathcal{E}$ were tested: (1) *fc* layer: $d \to e$, and (2) MLP: $d \to d \to e$, with $e = 128$. At test time, some models performed better with $\mathcal{E}$ dropped while some were better otherwise. For each model, the better case was reported. For training, we used cosine annealing with warm restarts schedule (Loshchilov & Hutter, 2017) with 20 epochs per cycle. The batch size was 256 for BREEDS, 1024 for CIFAR-100, and 512 for *tiered*ImageNet. The learning rate was 0.03 for BREEDs, and 0.12 for CIFAR-100 and *tiered*ImageNet. The weight decay was $1e^{-4}$. All models were trained with 200 epochs. The best training practices of (Tian et al., 2020) were also applied. For SCGM, we set $\gamma = 0.5$, $\sigma = 0.1$, and $\lambda = 25$ (λ follows (Asano et al., 2020)). The number of latent variables r varies w.r.t. different datasets, and was grid-searched from 100 to 500 with step size 50. All hyperparameters were set according to validation sets.

4.2 EXPERIMENTAL RESULTS

Following (Tian et al., 2020), we report results for 1000 random episodes with 5-way k-shot and all-way k-shot, 15-query tests. Unless otherwise stated, $k = 1$. Effects of more shots is evaluated in Appendix C.1. For each episode, 5 augmented copies were created per support sample. A logistic regression classifier was trained on the support set embedded by each model followed by L2 norm.

Method	Living17		Nonliving26		Entity13		Entity30	
	5-way	All-way	5-way	All-way	5-way	All-way	5-way	All-way
Fine (upper-bounds)	91.10±0.47	58.95±0.16	85.25±0.49	47.68±0.13	91.01±0.39	50.19±0.08	91.65±0.41	56.54±0.09
Fine+ (upper-bounds)	90.75±0.48	62.65±0.18	90.33±0.47	60.68±0.14	94.72±0.33	65.18±0.09	94.02±0.36	63.72±0.10
MoCo-v2	56.66±0.70	18.57±0.11	63.51±0.75	21.07±0.11	82.00±0.67	33.06±0.07	80.37±0.62	28.62±0.06
MoCo-v2-ImageNet	83.85±0.65	40.59±0.15	77.02±0.72	35.13±0.11	85.07±0.61	35.78±0.07	83.44±0.64	32.00±0.08
SwAV-ImageNet	81.15±0.63	39.57±0.15	75.67±0.70	35.28±0.12	81.76±0.61	34.53±0.07	80.76±0.63	31.92±0.08
GEORGE	85.50±0.63	32.10±0.11	80.75±0.62	31.07±0.10	77.68±0.68	15.58±0.05	83.41±0.59	21.12±0.06
SeLa	52.46±0.68	14.87±0.10	54.08±0.72	14.23±0.07	63.29±0.73	13.83±0.05	60.68±0.71	12.20±0.05
Coarse	85.12±0.74	33.83±0.10	83.53±0.64	33.52±0.11	82.33±0.61	17.49±0.04	87.03±0.54	24.01±0.06
Coarse+	79.29±0.65	37.44±0.12	75.91±0.66	36.80±0.11	83.23±0.66	31.15±0.07	84.81±0.61	33.22±0.08
ANCOR	89.23±0.55	45.14±0.12	86.23±0.54	43.10±0.11	**90.58±0.54**	**42.29±0.08**	88.12±0.54	41.79±0.08
ANCOR-*fc*	90.41±0.57	46.19±0.16	88.77±0.54	45.34±0.13	89.05±0.58	38.52±0.08	91.84±0.49	42.33±0.10
SCGM-G	89.72±0.54	48.74±0.15	**89.87±0.51**	**49.25±0.13**	90.15±0.51	40.00±0.08	**92.90±0.46**	42.17±0.08
SCGM-A	**90.97±0.55**	**49.31±0.16**	88.78±0.55	46.93±0.13	88.48±0.59	41.07±0.09	91.22±0.51	**44.14±0.09**

Table 1: Comparison on BREEDS datasets. Bold and underlined numbers are the best and second best results.

Method	5-way	All-way
Fine	74.36±0.68	28.82±0.11
Fine+	75.53±0.68	31.35±0.11
MoCo-v2	48.07±0.68	10.61±0.06
GEORGE	70.64±0.70	24.54±0.10
SeLa	38.52±0.60	5.87±0.05
Coarse	74.40±0.70	27.37±0.11
Coarse+	70.69±0.69	26.16±0.10
ANCOR	74.56±0.70	29.84±0.11
ANCOR-*fc*	74.73±0.73	27.32±0.10
SCGM-G	76.19±0.73	**29.92±0.11**
SCGM-A	**77.37±0.77**	25.91±0.10

Table 2: Comparison on CIFAR-100 datasets. Bold and underlined numbers are the best and second best results.

Method	Living17	Nonliving26	Entity13	Entity30
Fine (upper-bounds)	66.60±0.89	66.33±0.92	64.20±0.63	65.74±0.68
Fine+ (upper-bounds)	70.72±0.92	74.02±0.91	72.24±0.60	73.86±0.67
MoCo-v2	41.38±0.62	45.21±0.78	37.78±0.49	41.67±0.59
MoCo-v2-ImageNet	51.73±0.79	53.69±0.94	42.78±0.54	45.13±0.60
SwAV-ImageNet	52.26±0.73	54.77±0.90	42.95±0.54	45.78±0.60
GEORGE	38.17±0.52	43.55±0.69	21.42±0.30	30.79±0.47
SeLa	40.58±0.61	42.56±0.70	23.90±0.32	31.02±0.46
Coarse	38.14±0.53	40.38±0.62	16.01±0.22	28.20±0.44
Coarse+	40.70±0.59	50.21±0.83	37.13±0.48	43.10±0.65
ANCOR	48.77±0.71	49.64±0.88	42.00±0.47	45.17±0.59
ANCOR-*fc*	51.07±0.82	53.51±1.00	41.83±0.48	47.82±0.65
SCGM-G	53.48±0.81	**57.32±1.04**	43.89±0.58	46.80±0.78
SCGM-A	**53.88±0.90**	55.12±1.00	**45.09±0.58**	**50.02±0.71**

Table 3: Intra-class few-shot learning results of the compared methods on BREEDS datasets.

The model with the resulting regression classifier was used to classify the query samples. The test classes of each episode were a random subset of all subclasses (or all of them for all-way tests). Two cases were evaluated: (1) unseen subclasses of *seen* superclasses (on BREEDS, CIFAR-100); and (2) unseen subclasses of *unseen* superclasses (on *tiered*ImageNet). On CIFAR-100 and *tiered*ImageNet, ImageNet-pratrained models were excluded since pretrained ResNet-12 models are unavailable.

Evaluation case (1). We first evaluate when test classes are unseen subclasses of the training super-classes. Table 1 and 2 summarize the results. For ANCOR, its variants when the embedder $\mathcal{E}$ is *fc* (with '-*fc*') or MLP (without '-*fc*') were included as either variant does not consistently outperform another. The embedder setup of all models are in Appendix B.1. From the tables, we have several observations. First, models that cannot leverage supervision from superclasses, such as MoCo-v2 and SeLa, are inferior to Coarse(+). Although full ImageNet-pretrained models used larger training datasets, they are unable to fill the gap of superclass supervision, compared with Coarse(+). Second, the limitation of GEORGE indicates a separate clustering step induces misleading pseudo labels that could degenerate embedding quality. Compared to them, ANCOR and SCGM consistently outperform Coarse(+), and SCGM significantly outperforms ANCOR(-*fc*) in most cases. With a generic encoder, SCGM-G is superior or competitive to ANCOR(-*fc*) across different datasets. Using momentum contrast, SCGM-A further gains on some datasets. Note that 5-way has less room to improve than the all-way cases, because the randomly selected subclasses are more likely to be from different superclasses in the 5-way case, which may degrade to evaluate coarse classification. To investigate it, we evaluated an "intra-class" case when all subclasses of a random superclass were sampled in each episode. Table 3 indicates SCGM got more improvements in this challenging task, implying its embeddings distinguish subclasses better than other models.

Moreover, Table 4 compares the computational costs of ANCOR and SCGM-G, from which we can see training ANCOR requires much more resources and time than SCGM-G as it inherits MoCo-v2 (Chen et al., 2020b).

Dataset	ANCOR			SCGM-G		
	memory	time (h)	size	memory	time (h)	size
Living17	51.98G	16.43	0.74G	29.63G	8.09	0.09G
Nonliving26	55.27G	25.42	1.02G	29.63G	12.94	0.09G
Entity13	50.35G	65.45	0.62G	29.63G	43.94	0.09G
Entity30	56.91G	58.98	1.15G	29.63G	34.56	0.09G

Table 4: Computational costs on 4 Quadro RTX6000 24G GPUs.

Method	5-way-1-shot	5-way-5-shot	All-way-1-shot
Fine	70.15±0.70	84.96±0.47	15.42±0.06
Fine+	67.33±0.69	84.43±0.47	15.22±0.06
MoCo-v2	53.19±0.68	70.90±0.58	8.33±0.04
GEORGE	60.97±0.70	77.72±0.55	10.24±0.05
SeLa	47.96±0.63	66.39±0.57	7.17±0.04
C2F-VSME	60.54±0.79	75.22±0.63	N/A
Coarse	61.61±0.74	75.72±0.56	8.42±0.04
Coarse+	64.07±0.75	78.41±0.58	10.70±0.05
ANCOR	62.86±0.70	79.93±0.52	11.97±0.06
ANCOR-*fc*	60.43±0.69	78.18±0.53	11.04±0.05
SCGM-G	**64.64±0.71**	**80.83±0.52**	**12.32±0.05**
SCGM-A	64.47±0.71	80.68±0.51	11.75±0.05

Table 5: Comparison on *tiered*ImageNet.

Figure 2: The tSNE visualization of the embeddings learned by ANCOR and SCGM-G. Star represents superclass means. "+" marker represents subclass means of SCGM-G.

Also, its memory costs vary a lot by datasets since its dictionaries are superclass-wise whose size changes w.r.t. the number of superclasses. In contrast, SCGM-G had lower and stable costs, with better performance, thus is more favorable in practical deployments.

Evaluation case (2). Since *tiered*ImageNet has distinct train/val/test sets, it was used to evaluate the case when the testing subclasses is out of any training superclass. All models were trained with the superclasses of the train set, and tested on the subclass labels of the test set. Table 5 presents the results. Another three-step method C2F-VSME (Yang et al., 2021) was included as the same evaluation has been performed (but their code is unavailable). First, from the smaller gaps between Fine(+) and Coarse(+), this task is more difficult than the previous case. Similar to Table 1, MoCo-v2 and SeLa are inferior to Coarse(+), underlining the benefit of superclass supervision, even when test subclasses are not their descendants. Compared to GEORGE and C2F-VSME, ANCOR and SCGM can better leverage superclasses, by using coherent learning frameworks. Both SCGM-G and SCGM-A outperform ANCOR(-*fc*) in most cases, demonstrating the effectiveness of explicit modeling of latent subclasses, in both evaluation case (1) and (2).

Visualization of embedding. To understand how SCGM uncovers the subclass structures, we visualize a random batch of embeddings using tSNE (Maaten & Hinton, 2008). Fig. 2 presents the visualization results of ANCOR and SCGM-G on Living17 dataset, where colors mark different superclasses, "+" markers are the learned subclass means by SCGM-G, and stars represent superclass means. ANCOR's embeddings resemble those of Coarse+ (Appendix C.4) as it distinguishes subclasses from an angular perspective, which induces intra-class variation that is suboptimal. SCGM-G explicitly detects the boundaries of both super- and subclasses, properly positions Gaussian means, and associates subclasses with their corresponding superclasses, whereby establishing a hierarchical structure. We evaluated SCGM-G's detected subclasses using the subclass labels in the val set. It got an NMI of 71.58% and purity accuracy of 74.79%, much higher than its unsupervised counterpart SeLa (NMI 36.50%, purity 38.14%). This validates SCGM's effectiveness in leveraging superclass guidance for subclass inference. Several other model's visualization can be found in Appendix C.4.

Performance analysis. We have evaluated SCGM in terms of the effects of more shots, the impacts of the number of latent variables r, and the convergence, which are in Appendix C.1, C.2, C.3.

4.3 CASE STUDY: PERSONALIZED PREDICTION ON MEDICAL RECORDS

Next, we evaluate SCGM on a real Dialysis-Event dataset collected by several hospitals in Japan. This dataset consists of one-year medical records of 673 hemodialysis patients. It contains 40 temporal features (*e.g.*, blood flow, venous pressure, *etc.*) that were monitored during each hemodialysis session (thrice/week). Each session was annotated to indicate whether certain subtypes of events have occurred. A subtype corresponds to certain unstable behaviors of blood pressure during the dialysis, as categorized by experts. As introduced in Sec. 1, these events are risky and may develop complications, thus should be avoided. Formally, our task is as follows. Given $\mathbf{x}^i_{t:t+w-1} \in \mathbb{R}^{d \times w}$, a length-$w$ segment including the i-th patient's records starting at time step t, where $d = 40$ is the dimensionality, the task outcome is a label $y \in \{0, 1\}$ indicating event occurs ($y = 1$) or not ($y = 0$), at time step $t + w$. When $y = 1$, a fine-grained label $\hat{y} \in \{1, ..., s\}$ is to be predicted to mark the subtype of the event.

Figure 3: (a) An illustration of the model personalization framework for fine-grained event prediction for hemodialysis patients. (b) The distributions of patient-wise prediction accuracy on the query set by different methods. Each dot represents the accuracy of one patient's personalized model.

Since annotating fine-grained labels is costly, training a model on them at a large scale is infeasible in practice. To predict event subtypes, we use a *model personalization* framework as illustrated in Fig. 3(a). At the pre-training stage, only binary labels are used. For every new patient, a short period of (few) medical records are collected as the support set for the fine-grained labels w.r.t. that specific patient. It is used to train a personalized classifier based on the pre-trained model.

To evaluate how SCGM fits this paradigm, we randomly split the 673 patients into 50%/50% train/test set, and reserved 10% of the train set for validation. For each testing patient, the first 50% records (*i.e.*, half year) form the support set, and the remaining form the query set. It is likely some event types didn't appear in the support set will appear in the query set, which are out-of-distribution (OOD) cases, thus is out of our scope. Hence, we only selected patients without such cases, which constitute a major part ($>65\%$) of the test set. The dataset has two event subtypes, *i.e.* $s = 2$. The segments $\mathbf{x}_{t:t+w}^{(i)}$ were sampled with $w = 5$ and stride 1. The encoder is a Dual-Channel Combiner Network (DCCN), similar to (Che et al., 2016). DCCN has two channels (*e.g.*, RNNs and MLP) for encoding temporal and static features, respectively. The outputs of them are integrated by a classification head. Its architecture can be found in Appendix B.3. In this application, each patient has 28 static features such as demographic information and infrequent blood test results.

As discussed in Sec. 1, baselines on contrastive learning cannot be applied. Table 6 presents the average accuracy of all testing patients over 10 random train/test splits for applicable methods. As is consistent with Sec. 4.2, unsupervised method SeLa and three-step framework GEORGE cannot improve DCCN's performance due to (1) ignorance of superclass supervision, and (2) a separate pseudo-labeling step, respectively. In contrast, SCGM outperforms the original DCCN significantly. Fig. 3(b) compares different models by their distributions of personalized prediction accuracy of different testing patients in a random train/test split. Each dot repre-

Method	Accuracy
DCCN	45.59±0.99
GEORGE	43.63±0.63
SeLa	42.32±0.80
SCGM	**49.89±0.90**

Table 6: The comparison results on Dialysis-Event dataset.

sents the mean accuracy of one patient's personalized predictions in the query set (220 dots in total). From the figure, SCGM has more dots close to the top (*e.g.*, above 0.8) than other models, meaning more patients received fairly accurate predictions on the fine-grained labels. Although current performance could be limited by the data size, the results demonstrate the flexibility of SCGM, and its potential in tackling the CGFS problem in real practice.

5 CONCLUSION

In this paper, we proposed a new method, superclass-conditional Gaussian mixture model (SCGM), that underlies a general framework for tackling CGFS across domains. SCGM imitates the generative process of samples from hierarchies of classes, and explicitly models unobserved subclasses by latent variables. It dynamically computes a Gaussian mixture for every sample given its superclass, with a small overhead to an encoder. We learned model parameters by MLE in an EM-based framework, and also theoretically linked SCGM with contrastive learning. The extensive experiments on various datasets demonstrated the effectiveness, efficiency, and flexibility of our proposed method.

6   ETHICS STATEMENT

In the case study in Sec. 4.3, we evaluated our SCGM on datasets related to human subjects that are hemodialysis patients. We clarify that we got the permission to perform the experiments on the dataset as described in Sec. 4.3. There is no ethics issue nor harmful insights in our current experiments. The dataset was properly used under the guidance of the data providers and domain experts. Sensitive information about the patients was well protected. The final description about the experiments was checked and approved by the data providers and relevant authorities.

7   REPRODUCIBILITY STATEMENT

In our supplementary material, we provided the code for reproducibility study. The benchmark datasets are large and cannot be upooladed. The supplementary material includes an instruction on how to obtain the datasets and process them. Relevant instructions were provided on how to use the code to train SCGM-G and SCGM-A, and evaluate their performance for CGFS task in 5-way and all-way cases (Table 1, 2, 5), and in the intra-class case (Table 3).

REFERENCES

Yuki Markus Asano, Christian Rupprecht, and Andrea Vedaldi. Self-labelling via simultaneous clustering and representation learning. In *ICLR*, 2020.

Thomas L Athey, Benjamin D Pedigo, Tingshan Liu, and Joshua T Vogelstein. Autogmm: Automatic and hierarchical gaussian mixture modeling in python. *arXiv preprint arXiv:1909.02688*, 2019.

M. Christopher Bishop. *Pattern recognition and machine learning*. Springer, 2006.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Guy Bukchin, Eli Schwartz, Kate Saenko, Ori Shahar, Rogerio Feris, Raja Giryes, and Leonid Karlinsky. Fine-grained angular contrastive learning with coarse labels. In *CVPR*, pp. 8730–8740, 2021.

Mathilde Caron, Piotr Bojanowski, Armand Joulin, and Matthijs Douze. Deep clustering for unsupervised learning of visual features. In *ECCV*, pp. 132–149, 2018.

Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. Unsupervised learning of visual features by contrasting cluster assignments. In *NeurIPS*, 2020.

Zhengping Che, Sanjay Purushotham, Robinder Khemani, and Yan Liu. Interpretable deep models for icu outcome prediction. In *AMIA annual symposium proceedings*, volume 2016, pp. 371. American Medical Informatics Association, 2016.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020a.

Xinlei Chen, Haoqi Fan, Ross Girshick, and Kaiming He. Improved baselines with momentum contrastive learning. *arXiv preprint arXiv:2003.04297*, 2020b.

Marco Cuturi. Sinkhorn distances: Lightspeed computation of optimal transport. In *NeurIPS*, pp. 2292–2300, 2013.

Guneet Singh Dhillon, Pratik Chaudhari, Avinash Ravichandran, and Stefano Soatto. A baseline for few-shot image classification. In *ICLR*, 2020.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *ICML*, pp. 1126–1135. PMLR, 2017.

Jacob Goldberger and Sam T Roweis. Hierarchical clustering of a mixture model. In *NeurIPS*, pp. 505–512, 2005.

Will Grathwohl, Kuan-Chieh Wang, Jörn-Henrik Jacobsen, David Duvenaud, Mohammad Norouzi, and Kevin Swersky. Your classifier is secretly an energy based model and you should treat it like one. *arXiv preprint arXiv:1912.03263*, 2019.

Yanming Guo, Yu Liu, Erwin M Bakker, Yuanhao Guo, and Michael S Lew. Cnn-rnn: a large-scale hierarchical image classification framework. *Multimedia tools and applications*, 77(8):10251–10271, 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, pp. 770–778, 2016.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *CVPR*, pp. 9729–9738, 2020.

Cheng-Yu Hsieh, Miao Xu, Gang Niu, Hsuan-Tien Lin, and Masashi Sugiyama. A pseudo-label method for coarse-to-fine multi-label learning with limited supervision. In *ICLR*, 2019.

Kyle Hsu, Sergey Levine, and Chelsea Finn. Unsupervised learning via meta-learning. In *International Conference on Learning Representations*, 2018.

Daijo Inaguma, Daichi Morii, Daijiro Kabata, Hiroyuki Yoshida, Akihito Tanaka, Eri Koshi-Ito, Kazuo Takahashi, Hiroki Hayashi, Shigehisa Koide, Naotake Tsuboi, et al. Prediction model for cardiovascular events or all-cause mortality in incident dialysis patients. *PloS one*, 14(8): e0221352, 2019.

Alex Krizhevsky. Learning multiple layers of features from tiny images. *Technical report*, 2009.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *NeurIPS*, 25:1097–1105, 2012.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In *NeurIPS*, 2018.

Junnan Li, Pan Zhou, Caiming Xiong, and Steven Hoi. Prototypical contrastive learning of unsupervised representations. In *International Conference on Learning Representations*, 2020.

Lu Liu, Tianyi Zhou, Guodong Long, Jing Jiang, Lina Yao, and Chengqi Zhang. Prototype propagation networks (ppn) for weakly-supervised few-shot learning on category graph. In *IJCAI*, pp. 3015–3022, 2019.

Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. In *ICLR*, 2017.

Mi Luo, Fei Chen, Pengxiang Cheng, Zhenhua Dong, Xiuqiang He, Jiashi Feng, and Zhenguo Li. Metaselector: Meta-learning for recommendation with user-level adaptive model selection. In *The Web Conference*, pp. 2507–2513, 2020.

Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(11), 2008.

Laura Manduchi, Kieran Chin-Cheong, Holger Michel, Sven Wellmann, and Julia E Vogt. Deep conditional gaussian mixture model for constrained clustering. *arXiv preprint arXiv:2106.06385*, 2021.

Alex Nichol, Joshua Achiam, and John Schulman. On first-order meta-learning algorithms. *arXiv preprint arXiv:1803.02999*, 2018.

Luke Oakden-Rayner, Jared Dunnmon, Gustavo Carneiro, and Christopher Ré. Hidden stratification causes clinically meaningful failures in machine learning for medical imaging. In *CHIL*, pp. 151–159, 2020.

Łukasz P Olech and Mariusz Paradowski. Hierarchical gaussian mixture model with objects attached to terminal and non-terminal dendrogram nodes. In *Proceedings of the 9th International Conference on Computer Recognition Systems CORES 2015*, pp. 191–201. Springer, 2016.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Mengye Ren, Eleni Triantafillou, Sachin Ravi, Jake Snell, Kevin Swersky, Joshua B Tenenbaum, Hugo Larochelle, and Richard S Zemel. Meta-learning for semi-supervised few-shot classification. In *ICLR*, 2018.

Marko Ristin, Juergen Gall, Matthieu Guillaumin, and Luc Van Gool. From categories to subcategories: large-scale image classification with partial class label refinement. In *CVPR*, pp. 231–239, 2015.

Joshua Robinson, Stefanie Jegelka, and Suvrit Sra. Strength from weakness: Fast learning using weak supervision. In *ICML*, pp. 8127–8136. PMLR, 2020.

Shibani Santurkar, Dimitris Tsipras, and Aleksander Madry. Breeds: Benchmarks for subpopulation shift. *arXiv preprint arXiv:2008.04859*, 2020.

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In *NeurIPS*, pp. 4077–4087, 2017.

Nimit Sohoni, Jared Dunnmon, Geoffrey Angus, Albert Gu, and Christopher Ré. No subclass left behind: Fine-grained robustness in coarse-grained classification problems. In *NeurIPS*, 2020.

Fariborz Taherkhani, Hadi Kazemi, Ali Dabouei, Jeremy Dawson, and Nasser M Nasrabadi. A weakly supervised fine label classifier enhanced by coarse supervision. In *ICCV*, pp. 6459–6468, 2019.

Yonglong Tian, Yue Wang, Dilip Krishnan, Joshua B Tenenbaum, and Phillip Isola. Rethinking few-shot image classification: a good embedding is all you need? In *ECCV*, pp. 266–282. Springer, 2020.

Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Daan Wierstra, et al. Matching networks for one shot learning. In *NeurIPS*, pp. 3630–3638, 2016.

Yan Wang, Wei-Lun Chao, Kilian Q Weinberger, and Laurens van der Maaten. Simpleshot: Revisiting nearest-neighbor classification for few-shot learning. *arXiv preprint arXiv:1911.04623*, 2019.

Chen Xing, Negar Rostamzadeh, Boris Oreshkin, and Pedro O O Pinheiro. Adaptive cross-modal few-shot learning. In *NeurIPS*, pp. 4847–4857, 2019.

Jinhai Yang, Hua Yang, and Lin Chen. Towards cross-granularity few-shot learning: coarse-to-fine pseudo-labeling with visual-semantic meta-embedding. In *MM*, 2021.

Zhi-Hua Zhou. A brief introduction to weakly supervised learning. *National science review*, 5(1): 44–53, 2018.

A   APPENDIX FOR DETAILS OF DERIVING SCGM

A.1   DERIVATION OF PARAMETERIZED PROBABILITIES

In this section, we provide the details of the probabilities in Eq. (4). First, using Bayesian rules and marginal property, we can derive

$$p(y_i|z_i) = \frac{p(z_i|y_i)p(y_i)}{p(z_i)} = \frac{p(z_i|y_i)p(y_i)}{\sum_{y_i'=1}^{c} p(z_i|y_i')p(y_i')}, \quad p(z_i|\mathbf{v}_i) = \frac{p(\mathbf{v}_i|z_i)\pi_{z_i}^i}{p(\mathbf{v}_i)} = \frac{p(\mathbf{v}_i|z_i)\pi_{z_i}^i}{\sum_{z_i'=1}^{r} p(\mathbf{v}_i|z_i')\pi_{z_i'}^i} \quad (9)$$

Since $\boldsymbol{\mu}_{z_i}$ and $\bar{\boldsymbol{\mu}}_{y_i}$ are surrogate representations of z_i and y_i in the embedding space, substituting $p(z_i|y_i)$ and $p(\mathbf{v}_i|z_i)$ with the equality in Eq. (3), Eq. (4) can be achieved.

A.2   THE LOWER-BOUND OF THE LIKELIHOOD FUNCTION

In this section, we provide the details of the lower-bound in Eq. (5). By introducing the approximated posterior $q(z_i|\mathbf{v_i}, y_i)$, the likelihood in Eq. (1) becomes

$$\ell(\mathcal{D}_{\text{train}}; \boldsymbol{\theta}) = \frac{1}{n} \sum_{i=1}^{n} \log \left[\sum_{z_i=1}^{r} p(y_i|z_i)p_{\boldsymbol{\theta}}(z_i|\mathbf{v}_i)\frac{q(z_i|\mathbf{v_i}, y_i)}{q(z_i|\mathbf{v_i}, y_i)} \right]$$

$$\geq \frac{1}{n} \sum_{i=1}^{n} \sum_{z_i=1}^{r} q(z_i|\mathbf{v_i}, y_i)\Big[\log p(y_i|z_i) + \log p_{\boldsymbol{\theta}}(z_i|\mathbf{v}_i) - \log q(z_i|\mathbf{v_i}, y_i) \Big] \quad (10)$$

$$= \frac{1}{n} \sum_{i=1}^{n} \mathbb{E}_{q(z_i|\mathbf{v}_i, y_i)}\big[\log p_{\boldsymbol{\phi}}(y_i|z_i) + \log p_{\boldsymbol{\theta},\boldsymbol{\phi}}(z_i|\mathbf{v}_i) - \log q(z_i|\mathbf{v}_i, y_i) \big]$$

where the second step uses Jensen's inequality. This completes the derivation of Eq. (5).

A.3   THE OPTIMIZATION PROBLEM IN E-STEP

In this section, we elaborate the optimization problem for inferring the posterior $q(z_i|\mathbf{v_i}, y_i)$ in Eq. (6). Substituting $q(z_i|\mathbf{v_i}, y_i)$ with $\mathbf{Q}_{z_i,i}$, and substituting $p_{\boldsymbol{\phi}}(y_i|z_i)p_{\boldsymbol{\theta},\boldsymbol{\phi}}(z_i|\mathbf{v}_i)$ with $\mathbf{P}_{z_i,i}$, the second step in Eq. (11) can rewritten by

$$\frac{1}{n} \sum_{i=1}^{n} \sum_{z_i=1}^{r} \Big[\mathbf{Q}_{z_i,i} \log \mathbf{P}_{z_i,i} - \mathbf{Q}_{z_i,i} \log \mathbf{Q}_{z_i,i} \Big] \geq \frac{1}{n}\Big(\text{Tr}(\mathbf{Q}^\top \log \mathbf{P}) + \frac{1}{\lambda}H(\mathbf{Q}) \Big) \quad (11)$$

where $\text{Tr}(\cdot)$ is the trace function, $H(\cdot)$ is the entropy function, and the inequality stems from $\lambda \geq 1$, which is introduced to control the strength of the regularization (Cuturi, 2013). This is the objective function in Eq. (6). In addition, the transport polytope $\mathcal{Q}$ in Eq. (6) is introduced as an equal partition constraint on subclasses (Asano et al., 2020), so that the optimization problem is feasible. It is noteworthy that although subclasses have the equal partition constraint, superclasses can have different sizes since they can have different numbers of subclasses.

A.4   THE OPTIMIZATION PROBLEM IN M-STEP

In this section, we derive the optimization problem for learning model parameters in Eq. (7). Introducing the probabilities specification in Eq. (4) to the negative of the lower-bounded likelihood in Eq. (5), and removing terms that are irrelevant to model parameters $\{\boldsymbol{\theta}, \boldsymbol{\phi}\}$, we have

$$\ell_{\boldsymbol{\theta},\boldsymbol{\phi}} = \frac{1}{n} \sum_{i=1}^{n} \sum_{z_i=1}^{r} q(z_i|\mathbf{v_i}, y_i)\Big[\log \frac{p_N(\boldsymbol{\mu}_{z_i}|\bar{\boldsymbol{\mu}}_{y_i}, \bar{\boldsymbol{\Sigma}}_{y_i})p(y_i)}{\sum_{y_i'=1}^{c} p_N(\boldsymbol{\mu}_{z_i}|\bar{\boldsymbol{\mu}}_{y_i'}, \bar{\boldsymbol{\Sigma}}_{y_i'})p(y_i')} + \log \frac{p_N(\mathbf{v}_i|\boldsymbol{\mu}_{z_i}, \boldsymbol{\Sigma}_{z_i})\pi_{z_i}^i}{\sum_{z_i'=1}^{r} p_N(\mathbf{v}_i|\boldsymbol{\mu}_{z_i'}, \boldsymbol{\Sigma}_{z_i'})\pi_{z_i'}^i} \Big]$$
$$(12)$$

where considering isotropic Gaussian with $\bar{\boldsymbol{\Sigma}}_{y_i} = \mathbf{I}\bar{\sigma}^2$, we have

$$p_N(\boldsymbol{\mu}_{z_i}|\bar{\boldsymbol{\mu}}_{y_i}, \bar{\boldsymbol{\Sigma}}_{y_i}) = \exp\Big(\frac{-(\boldsymbol{\mu}_{z_i} - \bar{\boldsymbol{\mu}}_{y_i})^2}{2\sigma^2} \Big) = \exp\Big(\frac{(\boldsymbol{\mu}_{z_i}^\top \cdot \bar{\boldsymbol{\mu}}_{y_i} - 1)}{\sigma^2} \Big) \triangleq \exp\Big(\boldsymbol{\mu}_{z_i}^\top \cdot \bar{\boldsymbol{\mu}}_{y_i}/\sigma^2 \Big) \quad (13)$$

where in the last equation, constants were removed. Similarly, considering $\boldsymbol{\Sigma}_{z_i} = \mathbf{I}\sigma^2$, we have

$$p_N(\mathbf{v}_i|\boldsymbol{\mu}_{z_i}, \boldsymbol{\Sigma}_{z_i}) = \exp\Big(\frac{-(\mathbf{v}_i - \boldsymbol{\mu}_{z_i})^2}{2\sigma^2} \Big) = \exp\Big(\frac{(\mathbf{v}_i^\top \cdot \boldsymbol{\mu}_{z_i} - 1)}{\sigma^2} \Big) \triangleq \exp\Big(\mathbf{v}_i^\top \cdot \boldsymbol{\mu}_{z_i}/\sigma^2 \Big) \quad (14)$$

Substituting the corresponding terms in Eq. (12) with Eq. (13) and Eq. (14), we obtain the loss function in Eq. (7). In Eq. (7), the prior $p(y_i)$ can be set as uniform, *i.e.*, $p(y_i) = \frac{1}{c}$. If using a prior from Dirichlet distribution, $p(y_i)$ can be instantiated by estimating the parameters $\boldsymbol{\alpha}$ (of the Dirichlet distribution) by the ratio of different superclass labels in $\mathcal{D}_{\text{train}}$, the training dataset. Also, $\pi_{z_i}^i$ in the second term of Eq. (7) can be calculated using Eq. (2).

A.5 THE TRAINING ALGORITHM OF SCGM

Algorithm 1: Superclass-conditional Gaussian mixture model (SCGM)

Input: encoder $f_{\boldsymbol{\theta}}$, training dataset $\mathcal{D}_{\text{train}}$ (number of classes is c), hyperparameters r, λ, γ, σ
Output: model parameters $\{\boldsymbol{\theta}, \boldsymbol{\phi}\}$

1 $\boldsymbol{\phi} = \text{Initialization}(c, r)$ // initialize Gaussian means $\boldsymbol{\phi} = \{\{\boldsymbol{\mu}_j\}_{j=1}^r, \{\bar{\boldsymbol{\mu}}_j\}_{j=1}^c\}$
2 **for** $i \leftarrow 1$ *to MaxEpoch* **do**
    /* E-step */
3   **for** $(\mathbf{x}, y)$ *in Dataloader($\mathcal{D}_{train}$)* **do**
      /* load a minibatch $(\mathbf{x}, y)$ */
4     $\mathbf{v} = f_{\boldsymbol{\theta}}(\mathbf{x})$ // get embeddings
5   Compute $\mathbf{p}$ for Eq. (6) based on Eq. (4) using $\mathbf{v}$ and $\boldsymbol{\phi}$
6   **end**
7   Concatenate all batch-wise probabilities $\mathbf{p}$ to get $\mathbf{P}$ for $\mathcal{D}_{\text{train}}$
8   $\mathbf{Q} = \text{SinkhornKnopp}(\mathbf{P}, \lambda)$ // Inferring posterior using Sinkhorn-Knopp
     algorithm for optimizing Eq.(6)
    /* M-step */
9   **for** $(\mathbf{x}, y, \mathbf{q})$ *in Dataloader($\mathcal{D}_{train}$)* **do**
      /* load a minibatch $(\mathbf{x}, y, \mathbf{q})$ where $\mathbf{q}$ is obtained from E-step */
10    $\mathbf{v} = f_{\boldsymbol{\theta}}(\mathbf{x})$ // forward pass through the encoder
11   Calculate $\ell(\mathbf{v}, y, \boldsymbol{\phi}, \gamma, \sigma)$ // calculate loss using ℓ_{CE} and ℓ_{SCGM} in Eq.(7)
12    $\boldsymbol{\theta}, \boldsymbol{\phi} = \text{SGD}(\ell, \boldsymbol{\theta}, \boldsymbol{\phi})$ // update model parameters
13 **end**
14 **end**

B APPENDIX FOR IMPLEMENTATION DETAILS

B.1 THE SETUP OF THE COMPARED MODELS

For MoCo-v2 and MoCo-v2-ImageNet, following (Chen et al., 2020b), we set its queue size 65536, momentum 0.999 (0.99 for CIFAR-100), temperature 0.2, embedder $\mathcal{E}$ as MLP. For SwAV-ImageNet, following (Caron et al., 2020), its number of prototypes was 3000, embedder $\mathcal{E}$ as MLP. For ANCOR, following (Bukchin et al., 2021), we set its queue size 65536, momentum 0.999 (0.99 for CIFAR-100), temperature 0.2, embedder $\mathcal{E}$ as fc and MLP, with the multi-class queue, and angular norm on. For GEORGE (Sohoni et al., 2020), we set its robust learning rate $1e^{-4}$, $\mathcal{E}$ as fc, (dim 16, 10 neighbors, 0 distance) for its dimension reduction step, the number of clusters per superclasses was grid-searched within $\{5, 10, 15, 20\}$. For SeLa, following (Asano et al., 2020), we set its $\lambda = 25$, $\mathcal{E}$ as fc, and number of clusters was grid-searched from 100 to 500 with step size 50. For Coarse+ and Fine+, we set $\mathcal{E}$ as MLP. For our SCGM, we set $\gamma = 0.5$, $\sigma = 0.1$, and $\lambda = 25$ (λ follows (Asano et al., 2020)), $\mathcal{E}$ as fc, the number of latent variables r was grid-searched from 100 to 500 with step size 50.

B.2 THE ARCHITECTURE OF SCGM-A

Fig. 4 illustrates the architecture of SCGM-A, which was implemented on a generic encoder (*e.g.*, ResNet-50) with momentum encoders. The query $\mathbf{v}$ and positive key $\mathbf{k}_+$ are computed from two random augmentations of the input images through the encoder and embedder, and their momentum updates. There is a superclass-wise dictionary maintains c queues for c different superclasses so that superclass-wise negative keys $\mathbf{k}_-$ can be generated for within-superclass contrastive learning, which facilitates preserving intra-class variation. At the SCGM classification head, $\mathbf{v}$, $\mathbf{k}_+$ and $\mathbf{k}_-$ are applied with an angular normalization, followed by the InfoNCE loss, where the angular normalization

Figure 4: An illustration the architecture of SCGM-A

is defined by (Bukchin et al., 2021)

$$|\mathbf{v}_i|_{\mathrm{A}} = \left(\frac{\mathbf{v}_i}{\|\mathbf{v}_i\|} - \frac{\bar{\boldsymbol{\mu}}_{y_i}}{\|\bar{\boldsymbol{\mu}}_{y_i}\|} \right) / \| \frac{\mathbf{v}_i}{\|\mathbf{v}_i\|} - \frac{\bar{\boldsymbol{\mu}}_{y_i}}{\|\bar{\boldsymbol{\mu}}_{y_i}\|} \| \tag{15}$$

which enables contrasts from an angular perspective, and induces better synergy with cross-entropy loss.

The top part of the SCGM classification head are similar to its counterpart using a generic encoder, where $\mathbf{v}$ interacts with superclass means $\{\bar{\boldsymbol{\mu}}_j\}_{j=1}^c$ and subclass means $\{\boldsymbol{\mu}_j\}_{j=1}^r$ for computing our SCGM loss $\ell_{\boldsymbol{\theta}, \boldsymbol{\phi}}$ and a cross-entropy loss ℓ_{CE} as in Eq. (8). Thus the loss for training SCGM-A is as below.

$$\ell(\mathcal{D}_{\text{train}}; \boldsymbol{\theta}, \boldsymbol{\phi}) = \ell_{CE}(\mathcal{D}_{\text{train}}; \boldsymbol{\theta}, \{\bar{\boldsymbol{\mu}}_j\}_{j=1}^c) + \ell_{\text{InfoNCE}}(|\mathcal{D}_{\text{train}}|_{\mathrm{A}}; \boldsymbol{\theta}) + \gamma \ell_{\boldsymbol{\phi}, \boldsymbol{\theta}}(\mathcal{D}_{\text{train}}; \boldsymbol{\theta}, \boldsymbol{\phi}) \tag{16}$$

where the model parameters are learned by our proposed EM-based algorithm that alternates between the SGD backpropagation (M-step) for computing model parameters $\{\boldsymbol{\theta}, \boldsymbol{\phi}\}$ and the posterior inference (E-step) for computing subclass distributions.

B.3 THE ARCHITECTURE OF DCCN

Figure 5: An illustration the architecture of DCCN

Fig. 5 illustrates the architecture of the Dual-Channel Combiner Network (DCCN). DCCN is effective to process heterogeneous medical records data that usually consists of static profiles and time series (*i.e.*, records) (Che et al., 2016). It has a static channel realized by MLPs to encode static features (*e.g.*, demographic information, infrequent blood test results, *etc.*) and a temporal channel realized by RNNs (*e.g.*, LSTM) to encode temporal feature (*e.g.*, blood flow, venous pressure, *etc.*). The hidden representations output by the two channels are concatenated (or using certain pooling method) and further projected to a compact embedding that is used for prediction by the classification head, *i.e.*, the combination layer in Fig. 5, which is realized by MLPs. Attention layer may

be added before the combination layer for weighted combination of the hidden representations from different channels and different time steps.

C   APPENDIX FOR MORE EXPERIMENTAL RESULTS

C.1   EFFECTS OF MORE SHOTS

Method	1-shot	5-shot	10-shot	20-shot
Coarse+	37.44±0.12	50.51±0.31	57.35±0.33	63.23±0.25
ANCOR	45.14±0.12	59.60±0.35	65.14±0.28	68.87±0.26
ANCOR-*fc*	46.19±0.16	60.64±0.30	64.31±0.27	66.85±0.26
SCGM-G	48.74±0.15	60.39±0.29	63.42±0.31	65.67±0.25
SCGM-A	**49.31±0.16**	**63.82±0.32**	**67.43±0.30**	**69.99±0.25**

Table 7: Effects of more shots (all-way)

Method	1-shot	5-shot	10-shot	20-shot
Coarse+	79.29±0.65	92.99±0.41	94.33±0.36	95.27±0.31
ANCOR	89.23±0.55	94.44±0.36	95.33±0.31	95.90±0.27
ANCOR-*fc*	90.41±0.57	93.84±0.36	94.52±0.32	95.09±0.29
SCGM-G	89.72±0.54	94.38±0.37	95.09±0.35	95.52±0.31
SCGM-A	90.97±0.55	94.41±0.34	95.11±0.30	95.43±0.28

Table 8: Effects of more shots (5-way)

Table 7 and 8 summarize the performance of SCGM-G and SCGM-A, with the strongest baseline ANCOR and ANCOR-*fc*, together with the coarse baseline Coarse+, on Living17 dataset. From Table 7, we observe SCGM-A continuously improves performance as more shots are added, consistently outperforms other models, which validate the effectiveness of SCGM framework with varying number of shots. SCGM-G's performance becomes comparable to ANCOR(-*fc*) as more shots are added, due to its more simplified architecture, which however is more computationally efficient. Thus it provides a good balance between performance and efficiency. From Table 8, we observe both ANCOR and SCGM perform similarly. This may because the task is close to the regular superclass classification, and its performance limit can be easily reached by adding a few more shots. This can be seen from Coarse+'s results, which become close to other models when there are 20 shots in the support set.

C.2   IMPACTS OF THE NUMBER OF SUBCLASSES

Setting	r=50	r=100	r=150	r=200	r=250	r=300	r=400	r=500
5-way	89.45±0.60	89.72±0.54	88.29±0.57	88.26±0.55	88.05±0.56	87.88±0.56	86.82±0.56	86.35±0.58
All-way	42.98±0.14	48.74±0.15	46.21±0.15	47.81±0.15	47.55±0.16	46.91±0.16	45.23±0.15	44.63±0.15

Table 9: Impacts of the number of latent variables r on the performance of SCGM-G

Table 9 presents the results of SCGM-G on Living17 by varying the number of latent variables r from 50 to 500. As can be seen, the performance of SCGM-G is generally stable and it consistently outperforms Coarse(+) (Table 1) w.r.t. different r. By looking into the details, we observe too small (*e.g.*, 50) or too big (*e.g.*, 500) r may degenerate the performance in the all-way case, which may be caused by slight underfitting and overfitting, respectively. In the 5-way case, small r does not impact performance obviously, this is because the 5-way case is close to evaluate coarse classification, which does not need exact inference of subclasses. Thus a small number of r is fine (which may not distinguish all possible subclasses).

C.3   CONVERGENCE ANALYSIS

Fig. 6 presents the training loss $\ell(\mathcal{D}_{\text{train}}; \boldsymbol{\theta}, \boldsymbol{\phi})$ in Eq. (8) of SCGM-G, and $\ell(\mathcal{D}_{\text{train}}; \boldsymbol{\theta}, \boldsymbol{\phi})$ in Eq. (16) of SCGM-A, during the training process on the four BREEDS datasets. The training alternates between E-step and M-step, where E-step runs every 5 epochs. As can be seen, although there are some periodic fluctuations, the loss function values generally decrease and converge to a small value across different datasets. The periodic fluctuations are not synchronized with the alternate E-step

Figure 6: The training loss w.r.t. the number of epochs of SCGM on BREEDS datasets

and M-step since its period is not 5 epoch as can be observed. In practice, we observed both E-step and M-step can decrease the loss function values since both steps are theoretically optimizing the same loss function. The instability may come from the rounding step (as discussed in Sec. 3.2) for generating discrete code from the posterior, which follows the E-step. This rounding step may occasionally lead to some jump of loss values since it may make the optimization more aggressive than gradient updates. However, we still found this rounding step is beneficial, since without it, too small values may be generated in the posterior inference, which is unstable in computation. Generally, the current setup provides a stable training framework and we don't need to interfere in the program during the training process on all of our experimental datasets.

C.4 VISUALIZATION OF EMBEDDING

Figure 7: The tSNE visualization of the embeddings learned by different methods. Star represents superclass means. "+" marker represents subclass means.

In addition to the visualization results of ANCOR and SCGM-G provided in Fig. 2, Fig. 7 presents the tSNE visualization of the embeddings of several most relevant methods in comparison using Living17 dataset, including Coarse+, MoCo-v2, ANCOR-*fc* and SCGM-A. In the figure, colors mark different superclasses, "+" markers are the learned subclass means by SCGM-G, and stars represent superclass means. From Fig. 7(a)(c), we can observe the embeddings of both ANCOR and ANCOR-*fc* resemble Coarse+. Although ANCOR-*fc* slightly distinguish several small groups of embeddings in some superclasses, their intra-class variation is suboptimal. From Fig. 7(b), MoCo-v2 has the ability to detect superclasses to some extent, but cannot fill the gap of superclass supervision, by comparing with Coarse+, in this dataset. The reason may be the Living17 dataset is not sufficiently large and comprehensive for MoCo-v2 to learn embeddings that are comparable to supervised methods. In contrast to them, SCGM-A (and SCGM-G in Fig. 2) explicitly detects subclasses, with proper position of subclass means and superclass means. It also associates every subclass to its corresponding superclass, which establishes a hierarchical class structure. This explains the effectiveness of SCGM in cross-granularity learning tasks.