# KITE: Keypoint-Conditioned Policies for Semantic Manipulation

**Abstract:** While natural language offers a convenient shared interface for humans and robots, enabling robots to interpret and follow language commands remains a longstanding challenge in manipulation. A crucial step to realizing a performant instruction-following robot is achieving *semantic manipulation* — where a robot interprets language at different specificities, from high-level instructions like 'Pick up the stuffed animal' to more detailed inputs like 'Grab the left ear of the elephant.' To tackle this, we propose KITE: Keypoints + Instructions to Execution, a two-step framework for semantic manipulation which attends to both *scene* semantics (distinguishing between different objects in a visual scene) and *object* semantics (precisely localizing different parts within an object instance). KITE first grounds an input instruction in a visual scene through 2D image keypoints, providing a highly accurate object-centric bias for downstream action inference. Provided an RGB-D scene observation, KITE then executes a learned keypoint-conditioned skill to carry out the instruction. The combined precision of keypoints and parameterized skills enables fine-grained manipulation with generalization to scene and object variations. Empirically, we demonstrate KITE in 3 real-world environments: long-horizon 6-DoF tabletop manipulation, semantic grasping, and a high-precision coffee-making task. In these settings, KITE achieves a 75%, 70%, and 71% overall success rate for instruction-following, respectively. KITE outperforms frameworks that opt for pre-trained visual language models over keypoint-based grounding, or omit skills in favor of end-to-end visuomotor control, all while being trained from fewer or comparable amounts of demonstrations. Supplementary material, datasets, code, and videos can be found on our website.[1]

**Keywords:** Semantic Manipulation, Language Grounding, Keypoint Perception

## 1 Introduction

Language has the potential to serve as a powerful communication channel between humans and robots in homes, workplaces, and industrial settings. However, two primary challenges prevent today's robots from handling free-form language inputs. The first is enabling a robot to reason over *what* to manipulate. Instruction-following requires not only recognizing task-relevant objects from a visual scene, but possibly refining visual search to specific features on a particular object. For instance, telling a robot to "Open the top shelf" vs. "Yank open the bottom shelf" of a cabinet requires not only parsing and resolving any liberties taken with phrasing and localizing the cabinet in the scene (*scene* semantics), but also identifying the exact object feature that matters for the task — in this case the top or bottom handle (*object* semantics). In this work, we refer to instruction-following with scene and object awareness as *semantic manipulation*. Similarly, pick-and-place is a standard manipulation benchmark [1, 2, 3, 4], knowing how to pick up a stuffed animal by the ear versus leg, or a soap bottle by the dispenser versus side requires careful discernment. After identifying what to manipulate, the second challenge is determining *how* the robot can accomplish the desired behavior, i.e., low-level sensorimotor control. In many cases, low-level action execution requires planning in SE(3) with 6 degrees-of-freedom (DoF), such as reorienting the gripper sideways to grasp and pull open a drawer.

---

[1]https://tinyurl.com/kite-manip

Submitted to the 7th Conference on Robot Learning (CoRL 2023). Do not distribute.

Figure 1: **Real-World Semantic Manipulation Environments:** We visualize our semantic manipulation framework KITE on three real-world environments: long-horizon instruction following, semantic grasping, and coffee-making. Using keypoint-based grounding, KITE contextualizes scene-level semantics ('Pick up the green/red/blue/brown coffee pod') as well as object-level semantics ('Pick up the unicorn by the leg/ear/tail', 'Open the cabinet by the top/middle/bottom shelf') and precisely executes keypoint-conditioned skills.

Going beyond grasping, we want robots to assist us in many daily real-world tasks which may require even finer-grained precision. Making coffee, for example, is a simple daily task for humans, but for a robot it involves complex steps like reorienting a mug from sideways to upright or carefully inserting a coffee pod into an espresso machine. Thus to achieve semantic manipulation, robots must extract scene and object semantics from input instructions and plan precise low-level actions accordingly.

Leveraging advances in open-vocabulary object detection [5, 6, 7, 8], prior works in language-based manipulation determinine *what* to manipulate via bounding boxes or keypoints obtained from pre-trained [9] or fine-tuned vision language models (VLMs) [10]. So far, these works operate at the level of scene semantics (distinguishing amongst objects) rather than object semantics (identifying within-object features). In addition, these works do not apply VLMs to any complex manipulation beyond simple pick-and-place. To address these shortcomings, follow-up works couple the *what* and *how* subproblems together and learn end-to-end 6-DoF language-conditioned policies from demonstrations [11, 12, 13]. However, learning high dimensional action spaces from raw sensor inputs such as images or voxelized scene representations can require excessive amounts of data [12, 13] and can be difficult in high-precision tasks especially when using discretized actions [11].

Between approaches that leverage pre-trained visual representations from off-the-shelf VLMs, and those that plan directly from pixels or voxels, we lack an intermediate object-centric representation that can link natural language to scene and object semantics. Prior work has demonstrated that open-vocabulary VLMs can address scene semantics to some extent by locating different objects with coarse bounding boxes [9], but these representations are still too granular to precisely locate parts on objects. A suitable visual representation would be one that can represent both across-object or within-object features, and is interpretable enough to inform downstream 6-DoF action planning. We argue that keypoints provide this happy medium by offering a way to precisely pinpoint objects at the scene-level or even features within an object (*what*) and a way to condition downstream 6-DoF manipulation (*how*) on a region of interest.

In this work, we present **KITE:** Keypoints + Instructions To Execution, a flexible framework for semantic manipulation. KITE is decoupled into a grounding policy which maps input images and language commands to task-relevant keypoints, and an acting module which employs keypoint-conditioned skills to carry out low-level 6-DoF actions. We show that KITE can be trained from just a few hundred annotated examples for the grounding model, and less than 50 demos per skill for the acting module, while outperforming and generalizing better than methods that do not make use of either keypoints or skills. We experimentally evaluate KITE on semantic manipulation across three challenging real-world scenarios with varying tiers of difficulty: 6-DoF tabletop manipulation, semantic grasping, and coffee-making (Figure 1). Results indicate that KITE demonstrates fine-grained instruction following, while exhibiting a capacity for long-horizon reasoning and generalization.

## 2   Related Work

**Language-Based Manipulation**: Many recent works ground language to manipulation skills as a means for long-horizon instruction following. Several methods learn language conditioned policies end-to-end using imitation learning; however, end-to-end learning can require many demonstrations and can be brittle to novel scenes or objects [12, 11, 14, 15, 16, 17, 18, 19, 10, 20]. To improve sample efficiency, Shridhar et al. [11] predicts robot waypoints rather than low-level actions, conditioned on language and point cloud inputs. Waypoints alone do not specify *how* to go from one waypoint to another, and thus fail to capture dynamic tasks such as peg insertion or pouring motions. Other works take a hierarchical approach that first learn or define a library of language-conditioned skills, and then plan over skills with large language models (LLM) [21, 22, 23, 24, 25, 26]. However, each skill often requires hundreds of demonstrations. In addition, the LLM planner can only reason about the scene at a high level, lacking *visual grounding*. Alternatively, Liang et al. [27] query the LLM to generate code using an API for low-level skills, but predicting continuous parameters of these skills is challenging for an ungrounded LLM limiting this approach to tasks that do not require precision or dexterity. Vision-Language Models (VLM) are often proposed to ground LLM planners. For instance, Stone et al. [28] leverage a pretrained VLM to identify task-relevant objects from language. However, this approach has also been limited to pick and place tasks suggesting that today's pretrained VLMs struggle with more precise language instructions. In contrast, KITE maps language and vision directly to desired keypoints, enabling precise and semantic manipulation over long horizons.

**Skill-Based Manipulation**: Many prior works study multi-task manipulation by defining *skills* to represent sub-tasks, and then composing these skills over long horizons. These skills can either be learned to output each action or parameterized by expert-defined features. In reinforcement learning (RL), hierarchy can be imposed on the policy to learn both skills and composition end-to-end, but these methods can be sample inefficient and rarely integrate well with natural language [29, 30, 31]. Other RL works parameterize skills to reduce the action space size for sample efficiency, but these skills are usually rigid and cannot generalize to new settings [32, 33, 34]. Imitation learning (IL) aims to learn skills from demonstrations in a more sample efficient manner than RL, but these skills still fail to generalize to scene perturbations [35, 36]. Furthermore, in both IL and RL, connecting learned skills to precise language in a generalizable fashion is an open challenge. KITE avoids learning skills from scratch and instead defines a library of keypoint-conditioned skills, where the exact parameters of each skill are learned from demonstration. We show that keypoint-conditioned skills are sample efficient to learn and generalizable to new objects, while also easily integrated with precise language.

**Keypoints for Manipulation**: Keypoints have emerged in the literature as a more robust skill representation for manipulation [37, 10]. Keypoints are 2D points on images that serve as a natural intermediary between images and low-level behaviors. Several methods use keypoints to force the model to attend to the most important features in the input images [37]. Others predict keypoints and then translate keypoints into 3D points, or directly predict 3D points, to parameterize low level behaviors in a general and visually-grounded fashion [38, 10, 39, 40]. For example, Shridhar et al. [10] parameterize pick and place tasks using keypoints learned with image supervision, showing that this keypoint abstraction generalizes better to new objects. Keypoint action spaces have also helped in deformable object manipulation, for example in the domains of cloth folding, rope untangling, and food manipulation [41, 42, 43, 44, 45]. For many of these prior works, keypoints have yet to be integrated with language, and the methods that are linked to language are limited to a small library of primitives, usually focusing only on pick and place scenarios. Our approach defines a much broader library of keypoint-conditioned skills, and integrates keypoints with complex language instructions.

## 3   KITE: Keypoints + Instructions To Execution

In this work, our goal is to train an instruction-following agent capable of performing semantic manipulation at both scene and object-level granularity. We accomplish this with KITE, a sample-efficient and generalizable framework operating in two stages: *grounding* language into keypoints and *acting* on those keypoints. In this section, we first formalize the semantic manipulation problem (Section 3.1), discuss data collection (Section 3.2), and then discuss the training procedures for the grounding (Section 3.3) and acting modules (Section 3.4).

Figure 2: **KITE System Overview:** KITE receives an image observation $I_t$ along with user instruction $i_t$ and grounds these inputs to a 2D semantic keypoint in the image. After inferring which skill type $l_t$ is appropriate from a set of skill labels, KITE takes an RGB-D point cloud observation $\mathcal{P}_t$, annotated with the deprojected keypoint $\mathcal{M}_t$, and infers the appropriate waypoint policy $\pi$ for execution. After executing this action, KITE replans based on a new observation $(I_{t+1}, i_{t+1})$ and repeats the whole process.

### 3.1 Semantic Manipulation Problem Formulation

We aim to tackle instruction-following with scene and object-level semantic awareness using a library of *skills*. We assume each *skill* can be parameterized by 6-DoF waypoints, and we decouple each skill into a waypoint *policy* $\pi$ and *controller* $\rho$ to move between waypoints in a task-specific manner. Additionally, we assume each skill can be represented by a skill label $l$, e.g., pick, open, etc. We construct a library $\mathcal{L}$ of $M$ specialized skills where $\mathcal{L} = \{l^1 : (\pi^1, \rho^1), \ldots, l^M : (\pi^M, \rho^M)\}$ maps from a skill label to an underlying policy $\pi$ and controller $\rho$.

We assume access to multiple calibrated cameras that provide RGB and depth. We assume that at least one "grounding" camera can partially see all relevant objects. An observation $o_t = (I_t, \mathcal{P}_t)$ where $I_t \in \mathbb{R}^{W \times H \times 3}$ is the image from the grounding camera, and $\mathcal{P}_t \in \mathbb{R}^{D \times 6}$ is a multi-view point cloud. We denote low-level robot actions $a_t = (x, y, z, \psi, \theta, \phi)$ at time $t$ which consist of the end-effector position, yaw, pitch, and roll. We denote waypoints as $\kappa$ which is also a 6-DoF pose, but represents a high-level pose (e.g., grasp pose for pick) rather than a low-level action.

At time $t$, given an instruction $i_t$, we want to know *which* skill to execute by associating $i_t$ to a corresponding skill label $l_t \in \{l^1, \ldots, l^M\}$. Next, we aim to infer a 2D keypoint $[u, v]$ in the current visual observation $o_t$ which grounds $i_t$ to an associated object or object part. Finally, the chosen skill $(\pi, \rho) = \mathcal{L}[l_t]$ is executed (Figure 2). For each skill, we want to find a waypoint policy $\pi$ that takes as input the visual observation $o_t$ and 2D keypoint $[u_t, v_t]$ and outputs $K$ waypoints: $\pi : (o_t, [u_t, v_t]) \to \{\kappa^1, \ldots, \kappa^K\}$. Then, the associated controller $\rho$ can output a low-level trajectory between waypoints $\rho : \{\kappa^1, \ldots, \kappa^K\} \to \tau = \{(o_t, a_t), \ldots, (o_{t+T-1}, a_{t+T-1})\}$ (i.e. via linear interpolation, motion planning, etc.) for the robot to execute. For multi-step manipulation tasks, we restart the above process at each step with the new observation $o_{t+T}$ and paired language input $i_{t+T}$.

We consider instructions which refer to *scene* semantics, such as specifying desired spatial rearrangements of objects (e.g. "Pick up the lemon"), and *object* semantics, which reference desired object parts to be manipulated (e.g. "Grab the kangaroo stuffed animal by the tail"). As we do not assume access to the interaction history, our space of feasible language inputs excludes post-hoc feedback ("Pick up the *other* marker") or online-corrections ("No, to the *left*!"), which we leave to future work. Next we outline how KITE learns to predict keypoints (grounding) and learns each skill $\pi$ (acting).

### 3.2 Demonstration Collection

To learn both the grounding and acting modules, we collect a dataset $\mathcal{D}_\pi$ consisting of $N$ expert demonstrations per skill. Each demonstration has an initial observation, a list of $K$ waypoints, and a language instruction: $\mathcal{D}_\pi = \{(o_n, \{\kappa_n^1 \ldots \kappa_n^K\}, i_n) : n \in \{1, \ldots, N\}\}$. For instance, for a pick skill, we record the initial image and point cloud, provide an instruction (e.g., 'Pick up the lemon'), and then kinesthetically move the robot and record each end-effector waypoint. We use the calibrated robot-to-camera transformation to automatically project each robot end-effector pose $\kappa_n^j$ to 2D coordinates $[u_n, v_n]$ in the image plane of the camera used for grounding. For each skill, we train the acting module from $\mathcal{D}_\pi$. Aggregating across all skills yields a dataset of paired images, keypoint annotations, and language instructions with which to train the grounding module.

### 3.3 Grounding Module

The grounding module learns to identify 2D keypoints from RGB images that correspond to object features mentioned in an input instruction. We draw inspiration from recent works which use explicitly supervised [10, 38] or self-supervised keypoint attention networks [37, 46] to implement a grounding model $Q_{\text{ground}}$. Specifically, we learn a grounding function $Q_{\text{ground}}(u, v, I_t, i_t)$ representing the likelihood of keypoint $[u, v]$ given image $I_t$ and paired language instruction $i_t$. In this work, we attempt to learn a single-step look-ahead grounding function that takes a language input (e.g. "Put the lemon into the cabinet") and outputs the most immediately relevant keypoint (e.g. the pixel for the lemon if not already grasped, otherwise the pixel for the cabinet drawer to be placed) (see Fig. 2).

Given this grounding function $Q_{\text{ground}}$, we infer the 2D pixel in the image with highest likelihood:

$$[u_t, v_t] = \arg\max_{u,v} Q_{\text{ground}}(u, v, I_t, i_t) \tag{1}$$

In practice, we implement $Q_{\text{ground}}$ using the two-stream architecture from [10] which fuses pre-trained CLIP [47] embeddings of visual and textual features in a fully-convolutional network to output a heatmap of $Q_{\text{ground}}$. The grounding function is trained with a binary cross-entropy loss between the predicted heatmaps and 2D Gaussian heatmaps centered at the ground-truth pixel.

### 3.4 Acting Module

Although keypoints can pinpoint both scene and object semantics, they critically lack the 3D geometric context necessary to recover precise 6-DoF actions for a given task. For instance, the command "Pick up the bowl" may result in a predicted keypoint located at the bottom of a bowl, where there is no feasible grasp The exact 6-DoF actions are also dependent not just on the keypoint, but also language: "pick the lemon" and "cut the lemon" have similar keypoints but require completely different actions. We need a way to *refine* a predicted keypoint into candidate 6-DoF actions based on a desired language command, which we discuss next.

**Skill Selection:** Given a free-form language instruction, KITE first leverages the knowledge of LLMs to determine the appropriate skill label (e.g. $i_t =$ "Put the lemon in the cabinet" should result in the LLM outputting $\hat{l}_t = $ 'pick_place'), following prior work [48, 21]. The procedure entails prompting the LLM, in our case OpenAI's text-davinci-003 [49], with in-context examples of instructions and the appropriate skill type (see Appendix B.3 for examples of our prompting strategy). At test-time, we concatenate the example prompt with instruction $i_t$ and generate skill label $\hat{l}_t \in \{l^1, \ldots, l^M\}$ using the LLM. Then, we obtain the skill, consisting of the waypoint policy $\pi$ and controller $\rho$ via lookup in the library: $(\pi, \rho) = \mathcal{L}[\hat{l}_t]$.

**Learning Waypoint Policies:** Given the keypoint $[\hat{u}_t, \hat{v}_t]$ predicted by the grounding module and skill label $\hat{l}_t$, we need to learn a waypoint policy $\pi$ to perform the skill. KITE learns $\pi$ for each skill from demonstrations of keypoints $\{\kappa^1, \ldots, \kappa^K\}$. The waypoint policy $\pi$ takes a point cloud $\mathcal{P}_t$ and keypoint $[\hat{u}_t, \hat{v}_t]$ as input, and aims to output $K$ waypoints $\{\kappa^1, \ldots, \kappa^K\}$ to execute the chosen skill.

In KITE we align both 3D point cloud and a 2D keypoint representations by "annotating" $\mathcal{P}_t$ with the keypoint. We do this by first taking the depth image $D_t$ from the same view as $I_t$, and deprojecting all nearby pixels within a radius $R$: $\mathcal{K}_R = \{[u, v] \in I_t, \|[u, v] - [\hat{u}_t, \hat{v}_t]\| < R\}$ to their associated 3D points $\mathcal{P}_R = \{(x, y, z) = \texttt{deproject}(u, v), \forall (u, v) \in \mathcal{K}_R\}$. This yields a set of "candidate" points to consider for interaction. In the bowl grasping example, $\mathcal{P}_R$ would be points on the bottom of the bowl. Next, we augment the point cloud $\mathcal{P}_t$ with a 1-channel mask $\mathcal{M}_t \in \mathbb{R}^{N \times 1}$ (Fig. 2). For any point $(x, y, z) \in \mathcal{P}_t$, the mask channel label is 1 if $(x, y, z) \in \mathcal{P}_R$ (i.e., the point is in close proximity to the deprojected keypoint) and 0 otherwise.

Given the pointcloud and keypoint mask, KITE predicts all $K$ waypoints *relative* to individual points in the point cloud. For each point, we classify which of the $K$ waypoints it is nearest to, along with the offset to the desired 7-DoF end-effector pose (position and quaternion) for each of the $K$ waypoints. To do so, we adapt the PointNet++ [50] architecture, and define $Q_\pi : (\mathcal{P}_t, \mathcal{M}_t) \to \mathcal{P}_\pi$ where $\mathcal{P}_\pi \in \mathbb{R}^{N \times d}$ and $d = K \times (1 + 3 + 4)$. Continuing the example of grasping a bowl, the predicted pose offsets for each point on the bottom of the bowl (ungraspable) should lead to the bowl rim (graspable). See Appendix A for more details about the actor. We supervise $Q_\pi$ using the

following per-point loss:

$$L_{\text{skill}} = \lambda_{\text{cls}} CE(\hat{k}, k) + \lambda_{\text{ori}}(1 - \langle \hat{q}_{\hat{k}}, q_k \rangle) + \lambda_{\text{pos}} L1([\hat{x}_{\hat{k}}, \hat{y}_{\hat{k}}, \hat{z}_{\hat{k}}], [x_k, y_k, z_k]) \tag{2}$$

The first term corresponds to the 1-hot cross-entropy classification loss between the predicted waypoint index $\hat{k}$ and the true nearest waypoint index $k$. The remaining terms supervise the predicted gripper orientation and position using waypoint $\kappa^k$ for only the points that have classification label $k$, so as to only penalize points that matter (are in close proximity) to the $\kappa^k$.

**Action Module Inference:** At test time, given a point cloud $\mathcal{P}_t$ with associated keypoint mask $\mathcal{M}_t$, we use $Q_\pi$ to obtain $\hat{\mathcal{P}}_\pi$. By taking the highest likelihood point for each of the $K$ indices (representing the points nearest each of the $K$ waypoints). Then, we index the predicted end-effector poses in $\hat{\mathcal{P}}_\pi$ by these $K$ indices, resulting in $K$ waypoints $\{\hat{\kappa}^1, \ldots, \hat{\kappa}^K\}$. Finally, we obtain the final trajectory to carry out the skill with using the skill-specific controller: $\tau = \rho(\{\hat{\kappa}^1, \ldots, \hat{\kappa}^K\})$.

In summary, KITE's full pipeline first grounds a language command $i_t$ in an observation $o_t$ via $Q_{\text{ground}}$ to infer keypoints (Section 3.3), infers the skill label $l_t$ (Section 3.4), maps the label to a skill and controller $(\pi, \rho) = \mathcal{L}[l_t]$, then and executes $\pi$ and $\rho$, and finally replans.

## 4  Experiments

In this section, we aim to answer the following questions: (Q1) How well does KITE handle scene semantic instructions? (Q2) How well does KITE handle precise object-semantic instructions? (Q3) Does KITE's scene and object semantic awareness generalize to unseen object instances? and (Q4) Can KITE's primitives capture precise and dexterous motions beyond pick and place? We first outline KITE's key implementation details and the baseline methods we benchmark against. Finally, we analyze KITE's comparative and overall performance across three real-world environments which stress test scene and object-aware semantic manipulation (Section 4.1).

**Implementation Details:** Across all evaluation environments, we specify a library of skills and collect 50 kinesthetic demonstrations per-skill. In order to improve precision of the grounding module, and because keypoint supervision is easy to obtain compared to kinesthetic teaching, we supplement the grounding dataset obtained from kinesthetic data collection by manually labeling a small amount of images with paired language instructions (0.75:1 supplemental to original samples ratio). We implement the grounding module according to the architecture from [10] and each waypoint policy in the acting module as a PointNet++ backbone [50] with a point cloud resolution of 20K points. See Appendix A for more details.

**Baselines:** We benchmark KITE's performance against two state-of-the-art instruction-following frameworks. The first is PerAct [11], which trains a PerceiverIO [51] transformer backbone to predict waypoint poses end-to-end conditioned on a voxelized scene representation and language. In comparing against PerAct, we hope to understand whether KITE's use of keypoint-parameterized skills can offer better precision over end-to-end actions. To understand the value of keypoint-based grounding over frozen representations obtained from VLMs, we compare to RobotMoo [9], which extends a library of language-conditioned skills to additionally condition on segmentation masks from an open-vocabulary object detector. Since exact models and data were not released, we use a state-of-the-art VLM and our set of learn skills for RobotMoo. See Appendix A.3 for more details.

### 4.1  Real-World Evaluation

We explore three real-world manipulation environments that provide a rich testbed to explore KITE's sensitivity to scene and object semantics. Task variations are detailed in Appendix B.1. Across all experimental trials, we use a Franka Emika 7DoF robot and 3 Realsense D435 RGB-D cameras.

**Tabletop Instruction-Following:** We train a library of four skills: {pick, place, open, close} to reorganize a tabletop environment with 15 different household objects and an articulated storage organizer with three pull-out drawers (see Figure 1, Appendix B.1). While we do not test on completely unseen objects, we randomly vary the positions of objects on the table and the degree of clutter by adding distractor objects to the scene.

Table 1 compares KITE against PerAct and RobotMoo in this setting. We evaluate all approaches with 12 trials of instruction-following across three tiers of difficulty, ranging from a few objects on

the table and fairly straightforward language instructions (Tier 1), a visually cluttered table (Tier 2), and a cluttered table with more ambiguous instructions (Tier 3). See Appendix B.1 for examples of the objects considered and variations across tiers.

We first evaluate individual actions (`open`, `close`, `pick`), finding KITE to be the most robust and repeatable. KITE's use of precise keypoint grounding enables scene semantic awareness (Q1) over different objects (`pick, place`) and object semantic understanding (Q2) by distinguishing amongst different drawer handles with the `open` and `close` skills. PerAct's disadvantage is its discrete visual space, where any slight 1-off voxel predictions can make it difficult to grasp objects or cabinet handles. Due to the weak classification objectives it is trained on, its most common failure mode is misclassified gripper opening/closing actions. These failures are alleviated by the parameterized skills used in KITE and RobotMoo. Unsurprisingly, RobotMoo does well at grasping different objects referenced in language, as VLMs trained on internet-scale data have strong object priors.

Figure 3: **Semantic Grasping Experimental Setup:** We evaluate KITE on semantic grasping across rigid tools, deformable objects, and articulated items. We show 17 of the 20 objects tested along with ground-truth semantic labels for different features. The top row includes objects seen during grounding module training, and the bottom consists of unseen object instances.

Still, RobotMoo struggles with object semantics like the distinction amongst top, middle, or bottom drawers when opening or closing. We find that KITE is also the most competitive framework for long-horizon sequential reasoning (last two columns in Table 1), and the most common failures still include grasping the wrong object or with slightly misaligned gripper poses. RobotMoo's inability to reason over multiple cabinet handles for opening and closing impedes its long-horizon performance, whereas PerAct's compounding precision errors render long horizon tasks especially difficult.

|        |          | `open` | `close` | `pick` | `pick`→`place` | `open`→`pick`→ `place`→`close` |
|--------|----------|--------|---------|--------|----------------|--------------------------------|
|        | KITE     | **1**  | **0.92**| **0.83**| **0.75**       | **0.75**                       |
| Tier 1 | RobotMoo | 0.33   | 0.41    | 0.75   | 0.41           | 0.08                           |
|        | PerAct   | 0.08   | 0.5     | 0.33   | 0.08           | N/A                            |
| Tier 2 | KITE     | **1**  | **0.83**| **0.76**| **0.66**       | **0.42**                       |
|        | RobotMoo | 0.36   | 0.36    | 0.55   | 0.36           | 0.09                           |
| Tier 3 | KITE     | **0.75**| **0.83**| **0.58**| **0.66**      | **0.58**                       |
|        | RobotMoo | 0.33   | 0.42    | 0.5    | 0.42           | 0.0                            |

Table 1: **Tabletop Instruction Following Results:** Across 12 trials per method per tier, KITE outperforms both RobotMoo and PerAct for individual actions (`open`, `close`, `pick`) and chaining together up to four actions in sequence. We test all approaches on Tier 1 (fewer objects, straightforward language), Tier 2 (more objects, straightforward language), and Tier 3 (more objects, more free-form language). KITE's use of parameterized skills gives it an edge with precision over PerAct, which is highly susceptible to one-off voxel predictions. This makes skills like opening and picking especially hard, and renders the approach virtually ineffective for higher complexity tiers (2 and 3). RobotMoo is the most competitive approach to KITE, but its main pitfall is a lack of object semantic awareness such as distinguishing amongst different-level cabinet handles.

**Semantic Grasping:** Aside from recognizing and manipulating different objects, we explore in greater detail whether KITE can perform *object*-semantic manipulation (Q2). We evaluate KITE on the task of *semantic grasping*, with instructions of the form "Pick up the X by the Y" (i.e. 'stuffed bear' and 'ear'; 'marker' and 'cap'; 'shoe' and 'laces') (examples in Fig. 1). For these trials, we train $Q_{\mathrm{ground}}$ on a subset of rigid tools, deformable items, and articulated items (Fig. 3) and retain the keypoint-conditioned `pick` skill from Section 4.1. We summarize the findings in Table 2 with 26 trials per category of items, noting that KITE can achieve precise semantic grasping with generalization to unseen object instances (Q2, Q3). We omit a comparison to PerAct as its difficulties

with pick-and-place in the tabletop environment are only exacerbated in the semantic grasping setting where specific intra-object features matter. In the trials summarized in Table 2, KITE outperforms RobotMoo, suggesting the utility of keypoints to pinpoint specific object parts compared to coarse segmentation masks or bounding boxes output by VLMs. We also observe that the majority of KITE's failures in this setting are due to misinterpretations with symmetry (i.e. grasping the left instead of right handle of the pliers), rather than a completely erroneous keypoint as is common in RobotMoo. We posit that this could be alleviated with more diverse data of object semantic variations.

| | | Rigid Tools | Deformable Objects | Articulated Items | Failures | | |
| | | | | | A | B | C |
|---|---|---|---|---|---|---|---|
| Seen Instances | KITE | **0.77** | **0.77** | **0.70** | 5 | 3 | 3 |
| Unseen Instances | KITE | **0.70** | **0.54** | **0.70** | 4 | 5 | 4 |
| All | RobotMoo | 0.23 | 0.35 | 0.19 | 2 | 36 | 7 |

Table 2: **Semantic Grasping Results**: Across 20 total objects, 3 diverse object categories, and 26 trials per method per category, KITE achieves the highest rate of pick success for various object semantic features (Fig. 3), and with the least severity of failures. We categorize failure modes as follows, with (A) denoting a symmetry error (picking the left instead of right handle), (B) representing a grounding error with an erroneous keypoint prediction, and (C) indicating a manipulation failure (wrong inferred orientation or slip during grasping).

**Coffee-Making:** Finally, we seek to answer whether KITE can execute fine-grained behaviors from instructions (Q4) by studying a coffee-making

| | reorient_mug | pour_cup | refill_keurig | load_pod |
|---|---|---|---|---|
| KITE | 8/12 | 9/12 | 8/12 | 9/12 |

Table 3: **Coffee-Making Results:** KITE handles fine-grained manipulation across 4 skills requiring highly precise manipulation.

scenario with four skills: {reorient_mug, pour_cup, refill_keurig, load_pod} (examples in Fig. 1). We evaluate on the same object instances seen in training, but subject to spatial variations and language variations (i.e. 'Place the blue/red/green/brown pod in the machine', 'Pour the red/grey pitcher into the mug/Keurig refill area,'Place the cup/mug that's sideways right-side-up.'). Even for these very fine-grained motions, KITE is able to follow instructions with 67-75% success (Table 3). The main failures reside with low-level control errors rather than grounding, such as partial coffee pod insertion, misaligned mugs and pitchers during pouring, or slippage during mug reorientation. This suggests that the individual skills could benefit from scaling up demonstration collection, while retaining the existing grounding modules.

## 5 Discussion

**Summary** In this work, we present KITE a framework for semantic manipulation that identifies 2D task-relevant keypoints and extrapolates 6-DoF actions accordingly. By leveraging 2D keypoints to precisely localize semantic concepts, KITE is adept at recognizing semantic labels both across different object instances and on different regions within the same object. KITE does action-planning by drawing from a library of parameterized skills. Empirically, we find that KITE surpasses existing language-based manipulation frameworks along the axes of scene semantic awareness and object semantic awareness. We also find that KITE can be trained from orders of magnitude less data and with large precision gains over end-to-end approaches, while exhibiting an ability to generalize and operate over extended horizons. Finally, we show that KITE offers a flexible interface for instruction-following, including tabletop rearrangement, fine-grained grasping, and dexterous manipulation.

**Limitations and Future Work** One limiting factor of KITE is its reliance on building a library of skills. However, we show that a relatively small library of keypoint-parameterized skills is expressive enough to accomplish many standard manipulation tasks with object variations over an extended horizon. Additionally, KITE requires less than 50 demonstrations per new skill, meaning that adding new skills is fairly straightforward. We also note that KITE's grounding module is trained from scratch. As VLMs continually improve and in the future may be able to pinpoint keypoints in images, it would be interesting to replace or enhance KITE's grounding module with these models. Additionally, we acknowledge that KITE currently executes skills in an open-loop manner as parameterized by waypoints. In, the future, we are excited to extend KITE's skills with closed-loop feedback and extend the complexity of these skills to even more dexterous settings.

# References

[1] Y.-W. Chao, W. Yang, Y. Xiang, P. Molchanov, A. Handa, J. Tremblay, Y. S. Narang, K. Van Wyk, U. Iqbal, S. Birchfield, et al. Dexycb: A benchmark for capturing hand grasping of objects. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9044–9053, 2021.

[2] M. Sundermeyer, A. Mousavian, R. Triebel, and D. Fox. Contact-graspnet: Efficient 6-dof grasp generation in cluttered scenes. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pages 13438–13444. IEEE, 2021.

[3] J. Mahler, J. Liang, S. Niyaz, M. Laskey, R. Doan, X. Liu, J. A. Ojea, and K. Goldberg. Dex-net 2.0: Deep learning to plan robust grasps with synthetic point clouds and analytic grasp metrics. *arXiv preprint arXiv:1703.09312*, 2017.

[4] N. Correll, K. E. Bekris, D. Berenson, O. Brock, A. Causo, K. Hauser, K. Okada, A. Rodriguez, J. M. Romano, and P. R. Wurman. Analysis and observations from the first amazon picking challenge. *IEEE Transactions on Automation Science and Engineering*, 15(1):172–188, 2016.

[5] X. Gu, T.-Y. Lin, W. Kuo, and Y. Cui. Open-vocabulary object detection via vision and language knowledge distillation. *arXiv preprint arXiv:2104.13921*, 2021.

[6] M. Minderer, A. Gritsenko, A. Stone, M. Neumann, D. Weissenborn, A. Dosovitskiy, A. Mahendran, A. Arnab, M. Dehghani, Z. Shen, et al. Simple open-vocabulary object detection. In *Computer Vision–ECCV 2022: 17th European Conference, Tel Aviv, Israel, October 23–27, 2022, Proceedings, Part X*, pages 728–755. Springer, 2022.

[7] X. Zhou, R. Girdhar, A. Joulin, P. Krähenbühl, and I. Misra. Detecting twenty-thousand classes using image-level supervision. In *Computer Vision–ECCV 2022: 17th European Conference, Tel Aviv, Israel, October 23–27, 2022, Proceedings, Part IX*, pages 350–368. Springer, 2022.

[8] S. Liu, Z. Zeng, T. Ren, F. Li, H. Zhang, J. Yang, C. Li, J. Yang, H. Su, J. Zhu, et al. Grounding dino: Marrying dino with grounded pre-training for open-set object detection. *arXiv preprint arXiv:2303.05499*, 2023.

[9] A. Stone, T. Xiao, Y. Lu, K. Gopalakrishnan, K.-H. Lee, Q. Vuong, P. Wohlhart, B. Zitkovich, F. Xia, C. Finn, et al. Open-world object manipulation using pre-trained vision-language models. *arXiv preprint arXiv:2303.00905*, 2023.

[10] M. Shridhar, L. Manuelli, and D. Fox. Cliport: What and where pathways for robotic manipulation. In *Conference on Robot Learning*, pages 894–906. PMLR, 2022.

[11] M. Shridhar, L. Manuelli, and D. Fox. Perceiver-actor: A multi-task transformer for robotic manipulation. In *Conference on Robot Learning*, pages 785–799. PMLR, 2023.

[12] E. Jang, A. Irpan, M. Khansari, D. Kappler, F. Ebert, C. Lynch, S. Levine, and C. Finn. Bc-z: Zero-shot task generalization with robotic imitation learning. In *Conference on Robot Learning*, pages 991–1002. PMLR, 2022.

[13] A. Brohan, N. Brown, J. Carbajal, Y. Chebotar, J. Dabis, C. Finn, K. Gopalakrishnan, K. Hausman, A. Herzog, J. Hsu, et al. Rt-1: Robotics transformer for real-world control at scale. *arXiv preprint arXiv:2212.06817*, 2022.

[14] S. Stepputtis, J. Campbell, M. Phielipp, S. Lee, C. Baral, and H. Ben Amor. Language-conditioned imitation learning for robot manipulation tasks. *Advances in Neural Information Processing Systems*, 33: 13139–13150, 2020.

[15] O. Mees, L. Hermann, and W. Burgard. What matters in language conditioned robotic imitation learning. *arXiv preprint arXiv:2204.06252*, 2022.

[16] F. Codevilla, M. Müller, A. López, V. Koltun, and A. Dosovitskiy. End-to-end driving via conditional imitation learning. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 4693–4700, 2018. doi:10.1109/ICRA.2018.8460487.

[17] L. Shao, T. Migimatsu, Q. Zhang, K. Yang, and J. Bohg. Concept2robot: Learning manipulation concepts from instructions and human demonstrations. *The International Journal of Robotics Research*, 40(12-14): 1419–1434, 2021.

[18] A. Akakzia, C. Colas, P.-Y. Oudeyer, M. Chetouani, and O. Sigaud. Grounding language to autonomously-acquired skills via goal generation. In *ICLR 2021-Ninth International Conference on Learning Representation*, 2021.

[19] P. Goyal, R. J. Mooney, and S. Niekum. Zero-shot task adaptation using natural language. *CoRR*, abs/2106.02972, 2021. URL https://arxiv.org/abs/2106.02972.

[20] H. Hu, D. Yarats, Q. Gong, Y. Tian, and M. Lewis. Hierarchical decision making by generating and following natural language instructions. *Advances in neural information processing systems*, 32, 2019.

[21] A. Brohan, Y. Chebotar, C. Finn, K. Hausman, A. Herzog, D. Ho, J. Ibarz, A. Irpan, E. Jang, R. Julian, et al. Do as i can, not as i say: Grounding language in robotic affordances. In *Conference on Robot Learning*, pages 287–318. PMLR, 2023.

[22] W. Huang, F. Xia, T. Xiao, H. Chan, J. Liang, P. Florence, A. Zeng, J. Tompson, I. Mordatch, Y. Chebotar, P. Sermanet, T. Jackson, N. Brown, L. Luu, S. Levine, K. Hausman, and brian ichter. Inner monologue: Embodied reasoning through planning with language models. In *6th Annual Conference on Robot Learning*, 2022. URL https://openreview.net/forum?id=3R3Pz5i0tye.

[23] I. Singh, V. Blukis, A. Mousavian, A. Goyal, D. Xu, J. Tremblay, D. Fox, J. Thomason, and A. Garg. Progprompt: Generating situated robot task plans using large language models. *arXiv preprint arXiv:2209.11302*, 2022.

[24] W. Huang, P. Abbeel, D. Pathak, and I. Mordatch. Language models as zero-shot planners: Extracting actionable knowledge for embodied agents. In *International Conference on Machine Learning*, pages 9118–9147. PMLR, 2022.

[25] K. Lin, C. Agia, T. Migimatsu, M. Pavone, and J. Bohg. Text2motion: From natural language instructions to feasible plans. *arXiv preprint arXiv:2303.12153*, 2023.

[26] Y. Jiang, A. Gupta, Z. Zhang, G. Wang, Y. Dou, Y. Chen, L. Fei-Fei, A. Anandkumar, Y. Zhu, and L. Fan. Vima: General robot manipulation with multimodal prompts. *arXiv preprint arXiv:2210.03094*, 2022.

[27] J. Liang, W. Huang, F. Xia, P. Xu, K. Hausman, B. Ichter, P. Florence, and A. Zeng. Code as policies: Language model programs for embodied control. In *arXiv preprint arXiv:2209.07753*, 2022.

[28] A. Stone, T. Xiao, Y. Lu, K. Gopalakrishnan, K.-H. Lee, Q. Vuong, P. Wohlhart, B. Zitkovich, F. Xia, C. Finn, and K. Hausman. Open-world object manipulation using pre-trained vision-language model. In *arXiv preprint*, 2023.

[29] P. Dayan and G. E. Hinton. Feudal reinforcement learning. *Advances in neural information processing systems*, 5, 1992.

[30] L. X. Shi, J. J. Lim, and Y. Lee. Skill-based model-based reinforcement learning. In *6th Annual Conference on Robot Learning*, 2022. URL https://openreview.net/forum?id=iVxy2eO601U.

[31] S. Mirchandani, S. Karamcheti, and D. Sadigh. Ella: Exploration through learned language abstraction. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P. Liang, and J. W. Vaughan, editors, *Advances in Neural Information Processing Systems*, volume 34, pages 29529–29540. Curran Associates, Inc., 2021. URL https://proceedings.neurips.cc/paper_files/paper/2021/file/f6f154417c4665861583f9b9c4afafa2-Paper.pdf.

[32] C. Agia, T. Migimatsu, J. Wu, and J. Bohg. Stap: Sequencing task-agnostic policies. *arXiv preprint arXiv:2210.12250*, 2022.

[33] S. Nasiriany, H. Liu, and Y. Zhu. Augmenting reinforcement learning with behavior primitives for diverse manipulation tasks. In *IEEE International Conference on Robotics and Automation (ICRA)*, 2022.

[34] M. Dalal, D. Pathak, and R. Salakhutdinov. Accelerating robotic reinforcement learning via parameterized action primitives. In *NeurIPS*, 2021.

[35] C. Lynch, M. Khansari, T. Xiao, V. Kumar, J. Tompson, S. Levine, and P. Sermanet. Learning latent plans from play. *CoRR*, abs/1903.01973, 2019. URL http://arxiv.org/abs/1903.01973.

[36] S. Belkhale and D. Sadigh. Plato: Predicting latent affordances through object-centric play. In *Conference on Robot Learning*, pages 1424–1434. PMLR, 2023.

[37] S. James and A. J. Davison. Q-attention: Enabling efficient learning for vision-based robotic manipulation. *IEEE Robotics and Automation Letters*, 7(2):1612–1619, 2022.

[38] L. Manuelli, W. Gao, P. Florence, and R. Tedrake. kpam: Keypoint affordances for category-level robotic manipulation. In *Robotics Research: The 19th International Symposium ISRR*, pages 132–157. Springer, 2022.

[39] C. Wang, M. Chai, M. He, D. Chen, and J. Liao. Clip-nerf: Text-and-image driven manipulation of neural radiance fields. *CoRR*, abs/2112.05139, 2021. URL https://arxiv.org/abs/2112.05139.

[40] J. Kerr, C. M. Kim, K. Goldberg, A. Kanazawa, and M. Tancik. Lerf: Language embedded radiance fields, 2023.

[41] X. Ma, D. Hsu, and W. S. Lee. Learning latent graph dynamics for deformable object manipulation. *CoRR*, abs/2104.12149, 2021. URL https://arxiv.org/abs/2104.12149.

[42] H. Ha and S. Song. Flingbot: The unreasonable effectiveness of dynamic manipulation for cloth unfolding. In *Conference on Robotic Learning (CoRL)*, 2021.

[43] V. Viswanath, J. Grannen, P. Sundaresan, B. Thananjeyan, A. Balakrishna, E. Novoseller, J. Ichnowski, M. Laskey, J. E. Gonzalez, and K. Goldberg. Disentangling dense multi-cable knots. In *2021 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 3731–3738, 2021. doi:10.1109/IROS51168.2021.9636397.

[44] P. Sundaresan, J. Grannen, B. Thananjeyan, A. Balakrishna, J. Ichnowski, E. R. Novoseller, M. Hwang, M. Laskey, J. E. Gonzalez, and K. Goldberg. Untangling dense non-planar knots by learning manipulation features and recovery policies. *CoRR*, abs/2107.08942, 2021. URL https://arxiv.org/abs/2107.08942.

[45] P. Sundaresan, S. Belkhale, and D. Sadigh. Learning visuo-haptic skewering strategies for robot-assisted feeding. In *6th Annual Conference on Robot Learning*, 2022. URL https://openreview.net/forum?id=lLq09gVoaTE.

[46] C. Wang, R. Wang, A. Mandlekar, L. Fei-Fei, S. Savarese, and D. Xu. Generalization through hand-eye coordination: An action space for learning spatially-invariant visuomotor control. In *2021 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 8913–8920. IEEE, 2021.

[47] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pages 8748–8763. PMLR, 2021.

[48] J. Wu, R. Antonova, A. Kan, M. Lepert, A. Zeng, S. Song, J. Bohg, S. Rusinkiewicz, and T. Funkhouser. Tidybot: Personalized robot assistance with large language models. *arXiv preprint arXiv:2305.05658*, 2023.

[49] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

[50] C. R. Qi, L. Yi, H. Su, and L. J. Guibas. Pointnet++: Deep hierarchical feature learning on point sets in a metric space. *Advances in neural information processing systems*, 30, 2017.

[51] A. Jaegle, S. Borgeaud, J.-B. Alayrac, C. Doersch, C. Ionescu, D. Ding, S. Koppula, D. Zoran, A. Brock, E. Shelhamer, et al. Perceiver io: A general architecture for structured inputs & outputs. *arXiv preprint arXiv:2107.14795*, 2021.

[52] A. Kirillov, E. Mintun, N. Ravi, H. Mao, C. Rolland, L. Gustafson, T. Xiao, S. Whitehead, A. C. Berg, W.-Y. Lo, et al. Segment anything. *arXiv preprint arXiv:2304.02643*, 2023.