Excessive Reasoning Attack on Reasoning LLMs

Abstract

Recent reasoning large language models (LLMs), such as OpenAI o1 and DeepSeek-R1, exhibit strong performance on complex tasks through test-time inference scaling. However, prior studies have shown that these models often incur significant computational costs due to excessive reasoning, such as frequent switching between reasoning trajectories (e.g., underthinking) or redundant reasoning on simple questions (e.g., overthinking). In this work, we expose a novel threat: crafting adversarial inputs to exploit excessive reasoning behaviors. However, directly optimizing for excessive reasoning is non-trivial because reasoning length is non-differentiable. To overcome this, we introduce a proxy framework that approximates the long reasoning objective and shapes token-level behavior. We optimize and evaluate our attack for the GSM8K and ORCA datasets on DeepSeek-R1-Distill-LLaMA and Qwen. Empirical results demonstrate a 3x to 6.5x increase in reasoning length with comparable utility performance. Furthermore, our crafted adversarial inputs exhibit transferability, inducing computational overhead in OpenAI, Google, and DeepSeek's models. Our findings highlight an emerging efficiency-oriented vulnerability in modern reasoning LLMs, posing new challenges for their reliable deployment.

1 Introduction

Inference-time scaling has emerged as a critical technique for enhancing the reasoning capabilities of LLMs (Wei et al., 2022; Wang et al., 2023; Besta et al., 2024; Yang et al., 2024). Methods such as Chain-of-Thought (CoT) (Wei et al., 2022) guide models through intermediate reasoning steps by outside prompts, while recent models like DeepSeek (DeepSeek-AI et al., 2025) and QWQ (Team, 2025) embed reasoning capabilities inside models during training. However, recent studies have shown that these models often suffer from excessive reasoning behaviors, such as frequent shifts in reasoning strategies or redundant processing, which can lead to substantial computational overhead (Wang et al., 2025; Chen et al., 2024). In addition, recent studies (Turpin et al., 2023; Wu et al., 2025) have shown that longer reasoning chains can sometimes result in unfaithful or incorrect outputs. In particular, Wu et al. (2025) demonstrates that task accuracy initially improves but declines once the reasoning becomes too lengthy. These inefficiencies introduce a novel security risk: the attacker can craft adversarial inputs to exploit them, intentionally inflating inference-time resource usage or inducing unfaithful behaviors.

Prior works have explored related threats in LMs. For example, Sponge examples (Shumailov et al., 2021) increase computational costs by maximizing activation norms, while the NICGSlowDown attack (Chen et al., 2022) manipulates token logits to delay output generation. More recently, Kumar et al. (2025) propose the Overthink attack, which adopts an indirect prompt injection strategy and inserts a decoy to external resources. This compels the model to allocate additional reasoning resources toward solving intermediary tasks before addressing the primary query. These attacks highlight the vulnerability to resource-exhaustion threats. However, these approaches either rely on modifying model internals, controlling output logits, or injecting external distractions, which can limit their generality and practicality.

In this work, we directly perturb the input to elicit excessive reasoning behavior, increasing computational overhead without requiring external content or architectural manipulation. However, directly optimizing for excessive reasoning is non-trivial because reasoning length is non-differentiable explicitly. Therefore, we propose differentiable proxy losses to approximate the length objective and enhance the attack performance via

shaping token-level behavior. Concretely, we craft the adversarial suffixes with three complementary losses:

- **Priority Cross-Entropy Loss** prioritizes key tokens while masking less informative ones to enhance optimization efficiency. This loss leverages the autoregressive nature of LM to enable more targeted and effective gradient updates.

- **Excessive Reasoning Loss** increases the likelihood of branched or recursive reasoning, leading to greater computational overhead.

- **Delayed Termination Loss** encourages the model to defer the termination of reasoning and answer generation.

We optimize and evaluate our attacks for the GSM8K (Cobbe et al., 2021) and ORCA (Mitra et al., 2024) datasets on DeepSeek-R1-Distill-Llama and DeepSeek-R1-Distill-Qwen. Our attacks consistently increase the reasoning length by over 3x to 6.5x using only 10 crafted adversarial tokens. Moreover, our attack demonstrates strong transferability across models on commercial platforms, including OpenAI o3-mini, gpt5-mini, Google Gemini-Flash, DeepSeek-R1, and QWQ, suggesting a broader vulnerability among reasoning LLMs. These findings expose an underexplored issue. While such models are proficient in reasoning, they remain susceptible to targeted manipulations that exploit their reasoning mechanisms to induce significant computational overhead. Our results underscore the urgent need for defenses that can detect and mitigate excessive reasoning triggered by adversarial prompts.

2 Related Work

Adversarial Attacks on LLMs. Adversarial attacks on LLMs are challenging because text is discrete, limiting direct gradient-based optimization. Early methods such as HotFlip (Ebrahimi et al., 2018) and UAT (Wallace et al., 2019) use token-level perturbations or universal triggers to manipulate model behavior. More recent suffix-based attacks, including GCG (Zou et al., 2023) and BEAST (Sadasivan et al., 2024), further improve attack effectiveness and prompt coherence.

Denial-of-Service Attacks on LLMs. Denial-of-service (DoS) attacks increase inference cost, latency, or energy through malicious inputs. Sponge attacks (Shumailov et al., 2021) exhaust resources by maximizing activation norms, while NICGSlow-Down (Chen et al., 2022) prolongs generation by suppressing EOS probabilities. Recent attacks induce reasoning overhead via decoy tasks, either through indirect prompt injection in Overthink (Kumar et al., 2025) or within-query distractions in Crabs (Zhang et al., 2025). Moreover, Engorgio Prompt (Dong et al., 2025) also shows white-box resource amplification through re-parameterized prompts.

3 Methodology

This section presents our adversarial attack framework that increases the computational overhead of reasoning LLMs by inducing excessive reasoning. We begin by stating the threat model and the use cases. We then conduct two studies. First, we design proxy objectives to approximate the non-differentiable length objective. Second, we introduce two token-level losses that further shape token behaviors. Finally, we describe the optimization procedure used to generate adversarial attacks.

3.1 Threat Model

The primary objective of our attack is to craft inputs (e.g., suffixes) that compel the model to extend the reasoning processes as long as possible, thus significantly increasing the computational cost at inference time. Similar to prior work (Carlini et al., 2023; Zou et al., 2023; Gao et al., 2024; Boucher et al., 2022), we assume a white-box scenario in which the attacker has complete access to the model's architecture, parameters, and gradients.

Following (Carlini et al., 2023), we consider two primary use cases for our attack. In the first use case, a malicious user intentionally induces excessive computational load, degrading overall system performance and diminishing service quality for other users, akin to a DoS attack. In the second use case, a benign user queries the model within an autonomous system (e.g., LLM Agent) that processes untrusted third-party data (e.g., crafted adversarial data), resulting in significantly higher costs (e.g., money) than expected. As we later demonstrate, these crafted adversarial inputs exhibit strong transferability across different models. Moreover, our attack aligns with the Model Denial of Service (MDoS) threat as defined by OWASP, wherein adversarial inputs lead to resource exhaustion, degrading system responsiveness and service availability

for other users.[1]

3.2 Approximate Objective for Long Reasoning Trajectories

In this attack, we aim to craft inputs that elicit the model to produce excessive reasoning. Formally, this corresponds to optimizing the objective $\mathcal{L}_{long}$ that rewards generations exhibiting excessive reasoning. Since $\mathcal{L}_{long}$ depends on non-differentiable properties of sampled text (e.g., the length and density of intermediate steps), it cannot be optimized directly.

Following the adversarial prompt optimization paradigm, we instead optimize against a differentiable proxy. Prior work, such as ATA (Gan et al., 2024) and GCG (Zou et al., 2023), employs cross-entropy (CE) against short fixed targets (e.g., "Sorry, I'm unable to answer the question" or "Sure, I can. . . ") as surrogates for latent objectives like refusal or compliance. A natural extension is to use CE with long, reasoning-dense targets as a proxy for $\mathcal{L}_{long}$. However, this direct approach is ineffective since when supervision is spread uniformly across thousands of tokens, gradients become diffuse. Moreover, because the adversarial suffix typically contains only a few tokens, forcing it to match the distribution of thousands of target tokens is unrealistic.

To address this, we propose Priority Cross-Entropy (PCE) loss, which reweights supervision to focus on informative, prompt-dependent tokens rather than treating all positions equally. We further enhance the attack performance by constructing reasoning-rich target sequences with DSPy (Khattab et al., 2024), yielding more effective surrogates for the $\mathcal{L}_{long}$ objective.

Optimizing toward long targets. We begin by examining the standard CE objective and its limitations when applied to a long target. Traditional adversarial attacks on LMs minimize CE to increase the likelihood of a target sequence (e.g., "Sure, I can ..."). Formally, for base input x, adversarial suffix x', and target sequence y, the objective is

$$\mathcal{L}_{\text{CE}} = -\log p(y \mid \{x, x'\}). \quad (1)$$

In prior work, the target y is typically short (often < 10 tokens). However, to elicit excessive reasoning, y is much longer (e.g., $> 1{,}000$ tokens). Uniformly supervising all positions in such sequences

is optimization-inefficient since the gradient signal is spread across thousands of tokens. Also, many tokens (e.g., "the" and "I") can be accurately generated even without the prompt, due to statistical priors learned during pretraining. This suggests that optimizing every token is unnecessary; instead, supervision should focus on the prompt-dependent tokens that may influence the emergence of excessive reasoning.

To investigate this, we analyze the per-token perplexity distribution of a target sequence with and without the input prompt. As shown in Fig. 1, only a small subset of tokens exhibits a substantial change in perplexity when the prompt is removed. This supports our hypothesis that informativeness is not uniformly distributed across tokens, and that only a subset is highly dependent on the prompt.

Building on this insight, we design a token-level importance mask that emphasizes tokens the model considers informative, thereby improving optimization efficiency. For each target token y_t, we compute an importance score as the change in log-probability with and without the prompt:

$$S_t = \log p(y_t \mid x, y_{<t}) - \log p(y_t \mid y_{<t}). \quad (2)$$

This score quantifies the extent to which each token's prediction relies on the presence of the prompt. We then construct a binary mask $\mathcal{M}$ by selecting the top $K\%$ of tokens with the highest importance scores (set $M_t = 1$) and assigning zero weight to the rest (set $M_t = 0$).

Priority Cross-Entropy Loss. Putting these pieces together, we modify standard CE to focus supervision on prompt-sensitive tokens. The resulting PCE objective is

$$\mathcal{L}_{\text{PCE}} = -\frac{1}{|y|} \sum_{t=1}^{|y|} \mathcal{M}_t \cdot \log p(y_t \mid \{x, x'\}, y_{<t}). \quad (3)$$

This targeted supervision improves optimization efficiency and increases the likelihood that the model produces excessive reasoning at inference. Empirically, PCE substantially raises the frequency of reasoning (Fig. 3).

Constructing long targets. Because our attack seeks to elicit excessive reasoning, the proxy objective itself must involve long outputs. Short fixed targets (as in ATA and GCG) are less effective here since they do not encourage extended reasoning and provide little supervision on reasoning structure. We therefore construct long proxy targets.

---

[1] https://genai.owasp.org/llmrisk2023-24/llm04-model-denial-of-service/

Figure 1: The perplexity of a reasoning sample in the output with and without the prompt. Bold tokens are assigned 1 in the mask.

As simple baselines, we (i) sample multiple model outputs per input and select the longest sequence, and (ii) append the reasoning-oriented prompt (e.g., CoT) that naturally elicits step-by-step derivations to each input.

To obtain stronger proxies, we first leverage DSPy to iteratively refine the CoT prompt on a small dataset with the explicit objective of maximizing output length. Then, we query the model with each input and append the DSPy-optimized prompt to obtain the long, reasoning-dense target trajectories. Together with PCE, these long trajectories serve as effective proxies for the $\mathcal{L}_{long}$ objective. App. B.7 provides the DSPy-optimized prompt, a sample output, and statistics across different prompting baselines. We also examine the impact of various constructions in App. B.2.

3.3 Shaping Token-Level Behavior for Excessive Reasoning

Building on PCE and long targets, we next shape token-level behavior to further promote excessive reasoning. We introduce two complementary losses: Excessive Reasoning (ER) Loss, which increases the likelihood of reasoning-associated tokens, and Delayed Termination (DT) Loss, which discourages premature end-of-thinking/sequence decisions.

Excessive Reasoning Loss. In the previous section, we have described how DSPy-optimized prompts yield long target trajectories. Within these outputs, we observe that certain tokens (e.g., *"Wait"*, *"Alternatively"*; see App. 14) frequently occur in outputs and often signal branching or recursive reasoning steps, consistent with prior findings (Wang et al., 2025; Chen et al., 2024). To exploit this behavior, we aim to increase the likelihood of generating such tokens during the reasoning. While it is possible to construct a manual list of indicative tokens, this approach does not scale and may miss less obvious but influential cases. Instead, we adopt

a data-driven approach to automatically identify reasoning-associated tokens. As demonstrated in our analysis (Sec. 4.2), this approach uncovers influential tokens that would likely be overlooked through manual inspection, underscoring the efficacy of our method.

Concretely, we extract the top n most frequent tokens that appear in the first two positions of each sentence generated during constructing long-from targets. These tokens are hypothesized to play a critical role in initiating new reasoning trajectories. Let $\mathcal{T}$ denote the collected set of high-impact tokens. To promote their occurrence during generation, we define the ER Loss as:

$$\mathcal{L}_{\text{ER}} = -\frac{1}{|y|} \sum_{t=1}^{|y|} \sum_{v \in \mathcal{T}} \log p(y_t = v \mid \{x, x'\}, y_{<t}). \tag{4}$$

This objective increases the likelihood of generating collected high-impact tokens, thereby inducing longer reasoning sequences.

Delayed Termination Loss. In many reasoning LLMs, the generation process typically begins with intermediate reasoning steps, which conclude with a designated end-of-thinking (EOT) token (e.g., `</think>`). Then, the model would generate an answer conclusion terminated by an end-of-sequence (EOS) token (e.g., `<eos>`). To prolong both the reasoning and answer conclusion phases, we aim to reduce the model's tendency to emit these termination tokens during decoding. However, due to the stochastic nature of autoregressive generation, the precise timestep at which these tokens appear is not fixed. To address this, we adopt a strategy from prior work (Chen et al., 2022; Gao et al., 2024), which minimizes the likelihood of generating termination tokens across all positions in the output

sequence:

$$\mathcal{L}_{\text{DT}} = \frac{1}{|y|} \sum_{t=1}^{|y|} \Big[p(y_t = \text{EOS} \mid \{x, x'\}, y_{<t})$$

$$+ \ p(y_t = \text{EOT} \mid \{x, x'\}, y_{<t}) \Big]. \quad (5)$$

This objective discourages premature termination, encouraging the model to continue generating extended reasoning and answer conclusions before finalizing its output.

3.4 Optimization

Optimizing suffixes in the text domain presents a unique challenge due to the discrete nature of language. Unlike continuous domains (e.g., images), where gradients can be directly applied to pixel values, LMs operate on sequences of discrete tokens drawn from a fixed vocabulary. As a result, standard gradient-based optimization cannot be directly applied to manipulate individual tokens.

To address this, we adopt the Greedy Coordinate Gradient-based Search (GCG) framework (Zou et al., 2023), which has demonstrated strong performance in adversarial text generation. GCG linearizes the loss landscape by computing gradients with respect to input embeddings and identifying substitutions that are most likely to improve the loss. Specifically, for a given token position i in the suffix, we compute the gradient of the loss with respect to its embedding and search for the token x_i' that maximally improves the objective. Formally:

$$x_i' = \arg\max_{w \in V} \big\langle \nabla_{e(x_i)} \mathcal{L}, \ e(w) - e(x_i) \big\rangle, \quad (6)$$

where $\nabla_{e(x_i)} \mathcal{L}$ denotes the gradient of the loss with respect to the embedding of token x_i, and $e(w)$ is the embedding of candidate token w. This inner product quantifies the expected gain from substituting x_i with w, and the best candidate is selected greedily. Our overall objective combines the three loss components introduced previously:

$$\mathcal{L}_{long} = \alpha \cdot \mathcal{L}_{\text{PCE}} + \beta \cdot \mathcal{L}_{\text{ER}} + \gamma \cdot \mathcal{L}_{\text{DT}}. \quad (7)$$

In this work, we employ a fixed-length suffix-based optimization, where a set of tokens is appended to the end of the original prompt. Each token in the suffix is iteratively updated using GCG to minimize the combined loss. Although this paper focuses on crafting adversarial suffixes, it is important to note that our approach is *method-agnostic* and can be adapted to any paradigms. For instance,

alternative strategies such as character-level perturbations (e.g., typos) can be incorporated, as shown in prior work (Gan et al., 2024). This flexible framework facilitates the efficient generation of adversarial inputs tailored to different attack constraints.

4 Experiments

4.1 Experimental Setups

Models and Datasets. We optimize adversarial suffixes and evaluate them on two reasoning LLMs: DeepSeek-R1-distill-LLaMA-8B and DeepSeek-R1-distill-Qwen-7B.[2] Both models are distilled variants of DeepSeek-R1. We report results under two decoding strategies: greedy decoding and sampling decoding. For sampling, we set the temperature to 0.6, apply nucleus sampling with top-$p = 0.95$, and repeat 10 times. To assess cross-model transferability, we additionally evaluate the attack on larger-scale models, including QWQ-32B, DeepSeek-R1, o3-mini, gpt5-mini, and Gemini-Flash, using their default decoding settings. Our evaluation is conducted on two widely used mathematical reasoning benchmarks: GSM8K (Cobbe et al., 2021) and ORCA (Mitra et al., 2024). For each dataset, we randomly sample 50 examples for both optimization and evaluation. More details are provided in App. B.1.

Attack Setup. For DSPy, we use the COPRO optimizer with "gpt-4o-mini" to refine the CoT prompt. Specifically, we use 10 training examples from the GSM8K dataset for DSPy optimization and evaluate on a separate set of 10 randomly selected test samples. Due to computational constraints, we restrict target outputs to a maximum length of 3,000 tokens. For the PCE Loss, we set the token selection threshold $K = 1$, and for the ER Loss, we use $n = 5$. The overall loss function combines the three components using the following weighting coefficients: $\alpha = 1$, $\beta = 50$, and $\gamma = 1$. We fix the length of the adversarial suffix to 10 tokens. During optimization, we apply the GCG algorithm for 1,000 steps per input. The candidate pool size is set to 64, and at each step, the top 64 candidate tokens are retained.

Evaluation Metrics. To evaluate the effectiveness of our adversarial attack, we consider three primary metrics: (1) output sequence length (tokens), (2) inference latency (seconds), and (3) energy con-

---

[2] For simplicity, we omit the prefix DeepSeek-R1-distill throughout the remainder of the paper.

| | | GSM8K | | | | | | ORCA | | | | | |
Models	Methods	Rea	Ans	Full	Lat	Ent	Acc	Rea	Ans	Full	Lat	Ent	Acc
LLaMA	Original	668	239	907	24.3	4628	72%	499	213	712	19.3	4366	**82%**
	Random	447	264	711	19.0	3571	74%	440	228	668	17.6	3570	76%
	CoT	574	**266**	839	22.2	4712	70%	344	**259**	603	14.7	2789	**82%**
	Engorgio	168	274	443	10.4	1804	68%	189	219	408	9.19	1644	82%
	CatAttack	496	232	729	19.7	3959	76%	338	233	571	15.3	3013	78%
	Ours	**1914**	160	**2074**	**54.9**	**12827**	**92%**	**1575**	167	**1743**	**47.2**	**9929**	80%
Qwen	Original	237	282	519	12.8	2498	84%	531	220	750	18.4	4034	84%
	Random	159	294	453	11.2	2097	82%	527	225	752	18.7	3505	86%
	CoT	169	**310**	479	11.9	2535	82%	379	248	626	15.6	2910	86%
	Engorgio	832	274	1106	24.4	4661	82%	273	203	476	9.99	1811	86%
	CatAttack	167	295	461	11.3	2171	78%	532	234	766	18.5	4040	82%
	Ours	**1531**	193	**1724**	**42.4**	**8188**	**88%**	**1459**	166	**1624**	**39.6**	**9155**	**88%**

Table 1: The token length for reasoning (Rea), answer (Ans), and full output (Full); inference latency (Lat, in seconds); energy consumption (Ene, in joules); and task accuracy (Acc). Experimental results across methods under greedy decoding. **Bold** indicates the best result.

sumption (Joules). Energy usage is measured using the NVIDIA Management Library, following the methodology introduced by (Shumailov et al., 2021). To ensure consistency and fair comparison, all inference is performed using the HuggingFace pipeline (Wolf et al., 2019) on a single hardware (NVIDIA A100 80GB). Each inference is repeated three times to reduce the impact of runtime variability. To assess model utility, we extract final answers from the generated outputs using "Meta-Llama-3.1-8B-Instruct", and compute accuracy by comparing the extracted answers against ground-truth labels. The exact prompt used for extraction is provided in App. 6.

Baselines. We compare our attack against various baselines:

- **Random**: 10 randomly sampled tokens.

- **Standard CoT** (Wei et al., 2022): A widely used CoT prompt that appends the phrase "Let's think step by step."

- **Engorgio** (Dong et al., 2025): A method for crafting "inference-cost" attacks via adversarial prompts that force auto-regressive LLMs to produce excessively long outputs.

- **CatAttack** (Rajeev et al., 2025): A prompt-based adversarial strategy that appends the distractor statement "Interesting fact: cats sleep most of their lives," which has been shown to induce incorrect reasoning outputs.

4.2 Main Results

Performance. As shown in Table 1 and Table 14, our adversarial suffix substantially increases computational overhead while preserving task accuracy

(a) LLaMA

(b) Qwen

Figure 2: Token counts between the generated outputs from the original and adversarial prompts.

across all settings. For example, our attack causes LLaMA to generate significantly longer outputs on the GSM8K dataset with greedy decoding, increasing the average reasoning length by 3x from 668 to 1,914 tokens. This is accompanied by a corresponding increase in energy consumption (from 4,628J to 12,827J) and latency (from 24.3s to 54.9s). A similar trend is observed for Qwen, where the average reasoning length increases by 6.5x, demonstrating the effectiveness of our attack across different model architectures. Under sampling-based decoding, the attack remains robust. The reason-

ing length increases by 3x for LLaMA and 4x for Qwen on GSM8K, with similar results observed on the ORCA dataset.

In comparison, baseline methods generally induce relatively short reasoning. For example, CoT prompts produce shorter outputs than our adversarial prompt on LLaMA for GSM8K under greedy decoding (839 vs. 2,074 tokens), indicating the limitations of standard methods in eliciting excessive reasoning behavior. We also observe an inverse correlation between reasoning and answer lengths, suggesting that longer reasoning often compresses the final answer segment without degrading task accuracy. In most cases, our triggered excessive reasoning produces meaningless reasoning, as shown in App. B.6 (sample 1). However, we also find that in a few cases, the regular reasoning is too simple and fails to solve the problem, while our triggered excessive reasoning occasionally fixes it, as shown in App. B.6 (sample 2). For example, the original response contains a single solution (reasoning path) and it actually leads to an incorrect calculation. In contrast, our attack triggers excessive reasoning that explicitly extends the thinking with multiple solutions; however, we can see that the last solution (reasoning path) is redundant since the answer has already been inferred correctly. Together, these results demonstrate that our attack amplifies the computational burden of models without compromising their effectiveness. We also provide additional results on ELI5, optimized suffix, and sample outputs in App. B.6.

Analysis. We further analyze whether adversarial suffixes elicit excessive reasoning rather than merely increasing output length. First, we observe that the average number of reasoning sentences rises substantially, from 32 to 88 for LLaMA and from 11 to 74 for Qwen, compared with original prompts, indicating that our attack expands the reasoning process itself.

Next, we examine the distribution of the first two tokens in reasoning sentences (Fig. 2), which reveal distinct model-specific patterns. LLaMA frequently starts with deliberative tokens such as *"Alternatively"* and *"Wait,"* which are associated with recursive reasoning, while Qwen is less sensitive to *"Alternatively"*; nevertheless, Qwen becomes vulnerable once adversarial suffixes are applied. Tokens such as *"Let"*, *"Maybe"*, and *"Hmm"*, which are difficult to identify manually, further show that ER Loss with automated token selection can surface subtle excessive reasoning triggers.

Finally, we measure reasoning efficiency using Tokens per Accuracy in Table 8, where higher values indicate less concise reasoning. Adversarial suffixes inflate this metric across all model-dataset pairs. For example, on GSM8K, LLaMA increases from 12.6 to 22.5 tokens per accuracy point. This consistent pattern shows that our method induces inefficient, overextended reasoning rather than merely longer responses.

Transferability. We evaluate transferability to larger commercial LMs, including o3-mini, DeepSeek-R1, and QWQ, using GSM8K suffixes optimized on LLaMA and Qwen (Table 2). Overall, these suffixes generalize effectively, increasing output length without degrading task accuracy. For the OpenAI model family, both LLaMA- and Qwen-optimized suffixes increase output length; on o3-mini, they yield 245- and 596-token increases, respectively.

However, the transfer performance on DeepSeek-R1 depends on the source model: Qwen-optimized suffixes increase length by 260 tokens, whereas LLaMA-optimized suffixes fail to induce longer outputs. We hypothesize that this discrepancy arises from token mismatch between source and target models. To quantify this effect, we report Match, the token-alignment rate between source and target tokenizers. A suffix is counted as matched if its token length remains the same under both encodings, indicating no token splitting or merging. Higher Match scores correspond to longer outputs, suggesting that token alignment alongside architectural differences plays a critical role in adversarial prompt transferability.

4.3 Ablation Studies

We conduct a series of ablation studies to assess the impact of different experimental configurations, including the introduction of the PCE Loss and the individual contribution of each loss component.

PCE Loss. We begin by evaluating the effectiveness of the proposed PCE Loss by varying the proportion of top-K tokens from 100% (Original CE) to 1%, as shown in Fig. 3. The results show that focusing optimization on the top 5%, and particularly the top 1% of tokens, consistently outperforms applying loss uniformly across all tokens. Peak performance is observed when focusing solely on the top 1%, with the number of reasoning tokens increasing from 660 to 1,100. This pattern sug-

| Model | LLaMA | | | | | Qwen | | | | |
	Reason	Answer	Full	Accuracy	Match	Reason	Answer	Full	Accuracy	Match
QWQ	1761 (-151)	231 (-6)	1992 (-157)	93% (-3%)	62%	2489 (+577)	317 (+80)	2806 (+657)	98% (+2%)	100%
R1	997 (-74)	185 (-13)	1182 (-87)	95% (-2%)	4%	1295 (+224)	233 (+36)	1528 (+260)	93% (-4%)	60%
o3-mini	446 (+199)	184 (+46)	630 (+245)	90% (+1%)	20%	645 (+398)	336 (+199)	982 (+596)	89% (0%)	70%
gpt5-mini	343 (+175)	106 (+34)	449 (+209)	77% (-7%)	60%	578 (+410)	210 (+138)	787 (+547)	83% (-2%)	70%
Gemini-Flash	665 (+146)	350 (+76)	1015 (+222)	86% (-3%)	–	874 (+355)	513 (+239)	1388 (+594)	90% (+1%)	–

Table 2: Transferability analysis of adversarial suffixes originally optimized for LLaMA and Qwen.

Figure 3: Impact of varying the top-K most informative tokens on LLaMA under greedy decoding.

Setup	Reason	Answer	Full	Latency	Energy	Accuracy
$\mathcal{L}_{PCE}$	1100	**202**	1303	35.0	7016	84%
$\mathcal{L}_{PCE} + \mathcal{L}_{ER}$	1169	188	1357	36.1	8089	88%
$\mathcal{L}_{PCE} + \mathcal{L}_{DT}$	1447	201	1648	43.9	9558	88%
$\mathcal{L}_{PCE} + \mathcal{L}_{ER} + \mathcal{L}_{DT}$	**1914**	160	**2074**	54.9	12827	**92%**

Table 3: Different loss combinations on LLaMA under greedy.

gests that selectively emphasizing a small subset of salient, prompt-dependent tokens can more effectively induce extended reasoning behavior. Additionally, we observe an inverse relationship between the number of reasoning and answer tokens, implying a redistribution of the model's generative capacity toward reasoning content. These findings underscore the value of targeted token optimization and demonstrate that prioritizing high-impact tokens is more effective than uniformly distributing the loss across the entire sequence.

Loss Objectives. Second, we evaluate the individual contributions of each loss function and assess their collective impact as presented in Table 3. The results show that optimizing each loss independently leads to an increase in output sequence length, and the combination of all three losses yields the most substantial gains in both sequence length and computational burden. For instance, the full composite loss achieves the longest average output (up to 2,074 tokens), the highest inference latency (54.9 seconds), and the largest energy consumption (12,827J). These results underscore the synergistic effect of combining all objectives.

We further analyze ER Loss using a word cloud

of frequently prioritized tokens in Fig. 5. Besides common deliberative tokens from prior work, such as *"Alternatively"* and *"Wait"*, our method surfaces underexplored triggers such as *"Maybe"* and *"Hmm"*. These results show that the joint loss amplifies reasoning while preserving task accuracy, and that ER Loss uncovers subtle lexical cues for recursive reasoning.

5 Potential Defenses

Currently, no defenses are proposed explicitly against reasoning-based attacks. To evaluate potential countermeasures, we test four strategies: two at the input level and two at the output level, with details summarized in App.A. Naïve methods, such as perplexity-based filtering, yield high false positives and significantly degrade user experience. Safety classifiers are another possible input-level defense, but our attack bypasses them with high success rates. At the output level, we examine two decoding techniques aimed at curbing excessive reasoning. Thought Switching Penalty (TIP) (Wang et al., 2025) penalizes reasoning-disruptive tokens but fails to shorten overall outputs, while Dynamic Early Exit for Reasoning (DEER) (Yang et al., 2025) halts decoding once a confident answer is reached but may even reduce model utility. Overall, these findings show that our attack remains robust against different defenses.

6 Conclusion

In this work, we present a novel adversarial attack on reasoning LLMs that induces computational overhead during inference. Our approach appends adversarial suffixes that trigger extended reasoning trajectories, optimized through a composite loss function that maximizes output length and complexity. Empirical results demonstrate that the method reliably increases sequence length, inference latency, and energy consumption. Moreover, the strong cross-model transferability highlights the practical relevance of this threat.

Limitations

Based on the analysis, we can see that the choice of optimized tokens is also critical and constrained by the tokenizer used. Right now, many commercial APIs—such as OpenAI—release their tokenizers, and tokenizer inference attacks also exist and can be used to recover unknown tokenizers. In future work, the selection of optimized tokens can be incorporated as an additional optimization constraint, not only for this attack but for other adversarial methods as well.

Ethics Statement

This study utilizes publicly available datasets and models, with appropriate citations provided. No private or sensitive information is used, and the work does not include any harmful content. Because the research relies exclusively on publicly available data and does not involve human participants, it does not qualify as human subjects research under Institutional Review Board (IRB) definitions. Accordingly, we conclude that this paper raises no ethical concerns.

Broader Impacts

This study uncovers a new class of inference-time vulnerabilities in reasoning LLMs, with significant implications for both computational security and resource efficiency. We demonstrate that minimal adversarial perturbations, crafted as short suffixes, can dramatically increase inference costs. In large-scale deployments, such inefficiencies may translate into substantial computational burdens.

Moreover, the transferability of these adversarial behaviors across model families highlights a pressing concern for the robustness and reliability of LLMs in real-world applications. These results call for the development of evaluation frameworks that go beyond accuracy to include efficiency, resilience, and scalability under adversarial conditions.

We advocate for the integration of resource-awareness and adversarial robustness into the design and deployment of future LLMs to ensure their sustainability and operational safety. To support continued research in this direction, we will release our codebase publicly, contributing to the development of more secure and efficient language model systems.

References

Maciej Besta, Nils Blach, Ales Kubicek, Robert Gerstenberger, Michal Podstawski, Lukas Gianinazzi, Joanna Gajda, Tomasz Lehmann, Hubert Niewiadomski, Piotr Nyczyk, and Torsten Hoefler. 2024. Graph of Thoughts: Solving Elaborate Problems with Large Language Models. In *AAAI Conference on Artificial Intelligence (AAAI)*, pages 17682–17690. AAAI.

Nicholas Boucher, Ilia Shumailov, Ross Anderson, and Nicolas Papernot. 2022. Bad Characters: Imperceptible NLP Attacks. In *IEEE Symposium on Security and Privacy (S&P)*, pages 1987–2004. IEEE.

Nicholas Carlini, Milad Nasr, Christopher A. Choquette-Choo, Matthew Jagielski, Irena Gao, Pang Wei Koh, Daphne Ippolito, Florian Tramèr, and Ludwig Schmidt. 2023. Are aligned neural networks adversarially aligned? In *Annual Conference on Neural Information Processing Systems (NeurIPS)*. NeurIPS.

Simin Chen, Zihe Song, Mirazul Haque, Cong Liu, and Wei Yang. 2022. NICGSlowDown: Evaluating the Efficiency Robustness of Neural Image Caption Generation Models. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 15344–15353. IEEE.

Xingyu Chen, Jiahao Xu, Tian Liang, Zhiwei He, Jianhui Pang, Dian Yu, Linfeng Song, Qiuzhi Liu, Mengfei Zhou, Zhuosheng Zhang, Rui Wang, Zhaopeng Tu, Haitao Mi, and Dong Yu. 2024. Do NOT Think That Much for 2+3=? On the Overthinking of o1-Like LLMs. *CoRR abs/2412.21187*.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. Training Verifiers to Solve Math Word Problems. *CoRR abs/2110.14168*.

DeepSeek-AI, Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, Xiaokang Zhang, Xingkai Yu, Yu Wu, Z. F. Wu, Zhibin Gou, Zhihong Shao, Zhuoshu Li, Ziyi Gao, and 81 others. 2025. DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning. *CoRR abs/2501.12948*.

Jianshuo Dong, Ziyuan Zhang, Qingjie Zhang, Tianwei Zhang, Hao Wang, Hewu Li, Qi Li, Chao Zhang, Ke Xu, and Han Qiu. 2025. An engorgio prompt makes large language model babble on. In *The Thirteenth International Conference on Learning Representations, ICLR 2025, Singapore, April 24-28, 2025*. OpenReview.net.

Javid Ebrahimi, Anyi Rao, Daniel Lowd, and Dejing Dou. 2018. HotFlip: White-Box Adversarial Examples for Text Classification. In *Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 31–36. ACL.

Esther Gan, Yiran Zhao, Liying Cheng, Yancan Mao, Anirudh Goyal, Kenji Kawaguchi, Min-Yen Kan, and Michael Shieh. 2024. Reasoning Robustness of LLMs to Adversarial Typographical Errors. In *Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 10449–10459. ACL.

Kuofeng Gao, Yang Bai, Jindong Gu, Shu-Tao Xia, Philip Torr, Zhifeng Li, and Wei Liu. 2024. Inducing High Energy-Latency of Large Vision-Language Models with Verbose Images. In *International Conference on Learning Representations (ICLR)*.

Omar Khattab, Arnav Singhvi, Paridhi Maheshwari, Zhiyuan Zhang, Keshav Santhanam, Sri Vardhamanan, Saiful Haq, Ashutosh Sharma, Thomas T. Joshi, Hanna Moazam, Heather Miller, Matei Zaharia, and Christopher Potts. 2024. DSPy: Compiling Declarative Language Model Calls into State-of-the-Art Pipelines. In *International Conference on Learning Representations (ICLR)*.

Abhinav Kumar, Jaechul Roh, Ali Naseh, Marzena Karpinska, Mohit Iyyer, Amir Houmansadr, and Eugene Bagdasarian. 2025. OverThink: Slowdown Attacks on Reasoning LLMs. *CoRR abs/2502.02542*.

Arindam Mitra, Hamed Khanpour, Corby Rosset, and Ahmed Awadallah. 2024. Orca-Math: Unlocking the potential of SLMs in Grade School Math. *CoRR abs/2402.14830*.

Meghana Arakkal Rajeev, Rajkumar Ramamurthy, Prapti Trivedi, Vikas Yadav, Oluwanifemi Bamgbose, Sathwik Tejaswi Madhusudhan, James Zou, and Nazneen Rajani. 2025. Cats Confuse Reasoning LLM: Query Agnostic Adversarial Triggers for Reasoning Models. *CoRR abs/2503.01781*.

Vinu Sankar Sadasivan, Shoumik Saha, Gaurang Sriramanan, Priyatham Kattakinda, Atoosa Malemir Chegini, and Soheil Feizi. 2024. Fast adversarial attacks on language models in one GPU minute. In *Forty-first International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024*. OpenReview.net.

Ilia Shumailov, Yiren Zhao, Daniel Bates, Nicolas Papernot, Robert D. Mullins, and Ross Anderson. 2021. Sponge Examples: Energy-Latency Attacks on Neural Networks. In *IEEE European Symposium on Security and Privacy (Euro S&P)*, pages 212–231. IEEE.

Qwen Team. 2025. QwQ-32B: Embracing the Power of Reinforcement Learning. https://qwenlm.github.io/blog/qwq-32b/.

Miles Turpin, Julian Michael, Ethan Perez, and Samuel R. Bowman. 2023. Language Models Don't Always Say What They Think: Unfaithful Explanations in Chain-of-Thought Prompting. *CoRR abs/2305.04388*.

Eric Wallace, Shi Feng, Nikhil Kandpal, Matt Gardner, and Sameer Singh. 2019. Universal Adversarial Triggers for Attacking and Analyzing NLP. In *Conference on Empirical Methods in Natural Language Processing and International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 2153–2162. ACL.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc V. Le, Ed H. Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. 2023. Self-Consistency Improves Chain of Thought Reasoning in Language Models. In *International Conference on Learning Representations (ICLR)*.

Yue Wang, Qiuzhi Liu, Jiahao Xu, Tian Liang, Xingyu Chen, Zhiwei He, Linfeng Song, Dian Yu, Juntao Li, Zhuosheng Zhang, Rui Wang, Zhaopeng Tu, Haitao Mi, and Dong Yu. 2025. Thoughts Are All Over the Place: On the Underthinking of o1-Like LLMs. *CoRR abs/2501.18585*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed H. Chi, Quoc V. Le, and Denny Zhou. 2022. Chain-of-Thought Prompting Elicits Reasoning in Large Language Models. In *Annual Conference on Neural Information Processing Systems (NeurIPS)*. NeurIPS.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, and Jamie Brew. 2019. HuggingFace's Transformers: State-of-the-art Natural Language Processing. *CoRR abs/1910.03771*.

Yuyang Wu, Yifei Wang, Tianqi Du, Stefanie Jegelka, and Yisen Wang. 2025. When more is less: Understanding chain-of-thought length in llms. *CoRR*, abs/2502.07266.

Chenxu Yang, Qingyi Si, Yongjie Duan, Zheliang Zhu, Chenyu Zhu, Zheng Lin, Li Cao, and Weiping Wang. 2025. Dynamic early exit in reasoning models. *CoRR*, abs/2504.15895.

Ling Yang, Zhaochen Yu, Tianjun Zhang, Shiyi Cao, Minkai Xu, Wentao Zhang, Joseph E. Gonzalez, and Bin Cui. 2024. Buffer of Thoughts: Thought-Augmented Reasoning with Large Language Models. *CoRR abs/2406.04271*.

Yuanhe Zhang, Zhenhong Zhou, Wei Zhang, Xinyue Wang, Xiaojun Jia, Yang Liu, and Sen Su. 2025. Crabs: Consuming resource via auto-generation for llm-dos attack under black-box settings. In *Findings of the Association for Computational Linguistics, ACL 2025, Vienna, Austria, July 27 - August 1, 2025*, pages 11128–11150. Association for Computational Linguistics.

Andy Zou, Zifan Wang, J. Zico Kolter, and Matt Fredrikson. 2023. Universal and Transferable Adversarial Attacks on Aligned Language Models. *CoRR abs/2307.15043*.

	LLaMA				Qwen			
	Reason	Answer	Full	Accuracy	Reason	Answer	Full	Accuracy
Base	668	239	907	72%	237	282	519	84%
Base + TIP	422	250	673	74%	264	283	547	84%
Ours	1914	160	2074	92%	1531	193	1724	88%
Ours + TIP	1863	173	2037	94%	1464	198	1661	84%
Base	668	239	907	72%	237	282	519	84%
Base + DEER	247	237	484	70%	217	268	485	86%
Ours	1914	160	2074	92%	1531	193	1724	88%
Ours + DEER	1074	216	1290	72%	426	518	945	88%

Table 4: Output-level defense results for GSM8k on LLaMA and Qwen.

Quantile	LLaMA		Qwen	
	FP (%)	TP (%)	FP (%)	TP (%)
25	100	100	100	100
50	78	100	84	100
75	16	100	28	100

Table 5: False positive rate (FP) for filtering clean prompts and true positive rate (TP) for filtering attack prompts using perplexity-based filtering across different quantiles.

A Defense Studies

Input-level. At the input level, we begin by evaluating a perplexity-based filtering strategy, following the similar setup described in (Dong et al., 2025). We compute universal perplexity thresholds using the Open-Platypus dataset, assuming the model owner has no prior knowledge of the adversarial suffix. Specifically, we select the 25th, 50th, and 75th percentile quantiles as thresholds to filter prompts exhibiting unusually high perplexity.

We test the filter on both clean prompts and prompts appended with adversarial suffixes as shown in Table 5. While this method achieves a 100% true positive rate in detecting adversarial prompts, it also results in high false positive rates for clean prompts—100%, 78%, and 16% on LLaMA, and 100%, 84%, and 28% on Qwen at the respective thresholds. These results suggest that our optimized suffixes are difficult to identify when the model owner lacks prior knowledge of their structure. Also, applying high-percentile quantile thresholds may severely degrade the utility of the model on benign inputs. For the second defense, we apply an open-source safety classifier, "meta-llama/Llama-Prompt-Guard-2-86M," to flag unsafe inputs. The classifier detects only 8% of adversarial prompts on LLaMA and 6% on Qwen. These findings indicate that our adversarial suffixes are able to bypass the classifier in most cases.

Output-level. At the output level, we evaluate two complementary mitigation techniques. The first, Thought Switching Penalty (TIP) (Wang et al., 2025), penalizes the generation of reasoning-disruptive tokens such as "Wait" or "Alternatively." The second, Dynamic Early Exit for Reasoning (DEER) (Yang et al., 2025), reduces unnecessary token generation by terminating decoding early once a confident answer is detected.

As shown in Table 4, on LLaMA, our attack generated 1,914 reasoning tokens and 160 answer tokens, totaling 2,074 tokens, with an accuracy of 92%. Applying TIP led to a modest reduction in total tokens (2,037) and a slight increase in accuracy to 94%. In contrast, DEER reduced the length of reasoning (to 1,290 tokens) but caused a more substantial performance drop, lowering accuracy to 72%. A similar trend was observed on Qwen: TIP preserved accuracy while modestly reducing output length, whereas DEER can only reduce the total token count (945 tokens). In addition, DEER requires extra processing time, which also incurs additional latency and energy costs. Overall, these results suggest that TIP provides only limited mitigation against our attack, while DEER is more effective at curbing excessive reasoning, but at the cost of degraded task performance and additional computational resources. Nevertheless, our attack still incurs substantial resource overhead due to excessive and redundant token generation compared to Original.

B Additional Experimental Details

In this section, we present additional details of our experimental setup, including the prompting

templates, sample outputs and suffixes, outputs and prompts from DSPy, analysis of the attack behavior, descriptions of the models and datasets employed, as well as the computational resources utilized.

B.1 Experimental Setups

All models in our experiments are downloaded from HuggingFace. DeepSeek-R1-Distill-Llama-8B and DeepSeek-R1-Distill-Qwen-7B are originally licensed under the Apache 2.0 License. The GSM8K and ORCA datasets are under the MIT License. All experiments in the paper were conducted on an A100 (80GB) compute node. Also, we interact with o3-mini via the OpenAI API, and with DeepSeek-R1 and QWQ-32B via the Baidu Cloud API, to simulate real-world deployment conditions.

B.2 Target Output Construction

Setup	Reason	Answer	Full	Latency	Energy	Accuracy
Raw	1695	190	1885	50.9	12120	80%
CoT	1060	**224**	1283	34.0	7719	80%
CoT + DSPy	**1914**	160	**2074**	54.9	**12827**	**92%**

Table 6: Different target constructions on LLaMA under greedy decoding.

Setup	Reason	Answer	Full	Latency	Energy	Accuracy
Raw	1396	223	1619	206.8	**20252**	82%
CoT	1034	**250**	1283	150.2	15685	79%
CoT + DSPy	**1501**	216	**1718**	209.9	19491	**87%**

Table 7: Different target construction strategies on LLaMA under sampling decoding.

We evaluate several strategies for constructing target outputs to guide adversarial optimization, as summarized in Table 6 and 7. The comparison includes a raw baseline (no additional prompt), a standard CoT prompt, and a DSPy-optimized CoT prompt. Interestingly, we find that the standard CoT prompt does not consistently produce longer reasoning sequences; in some cases, it even results in shorter outputs than raw prompting, highlighting its limitations in eliciting extended reasoning. In contrast, DSPy-optimized CoT prompts increase the average output length from 1,283 to 2,074 tokens under greedy decoding compared to CoT prompts, with corresponding increases in both energy consumption and task accuracy. These results highlight the critical role of target output quality in guiding adversarial optimization. Longer reasoning sequences, especially those produced via DSPy, serve as more effective targets for inducing excessive computation. This reinforces the

Models	Methods	GSM8K			ORCA		
		Toks	Acc	Toks/Acc	Toks	Acc	Toks/Acc
LLaMA	Original	907	72%	12.6	712	**82%**	8.7
	Ours	**2074**	**92%**	**22.5 (1.8×)**	**1743**	80%	**21.8 (2.5×)**
Qwen	Original	519	84%	6.2	750	84%	8.9
	Ours	**1724**	**88%**	**19.6 (3.2×)**	**1624**	**88%**	**18.5 (2.1×)**

Table 8: Tokens per accuracy (Toks/Acc) under Original vs. our attack with greedy decoding. Ratios show relative increases.

importance of target construction in maximizing the efficacy of our attack.

B.3 Additional Results

Figure 4: Impact of varying the top-K most informative tokens on LLaMA under sampling decoding.

Setup	Reason	Answer	Full	Latency	Energy	Accuracy
$\mathcal{L}_{PCE}$	1104	218	1322	143.9	19810	86%
$\mathcal{L}_{PCE} + \mathcal{L}_{ER}$	1095	205	1301	124.9	14879	87%
$\mathcal{L}_{PCE} + \mathcal{L}_{DT}$	1184	**223**	1407	145.3	17731	88%
$\mathcal{L}_{PCE} + \mathcal{L}_{ER} + \mathcal{L}_{DT}$	**1437**	204	**1641**	**197.0**	**21228**	**90%**

Table 9: Ablation study of loss objectives combinations on LLaMA under sampling decoding.

	Reason	Answer	Full
Original	1070	287	1356
Ours	1495	310	1805

Table 10: Experimental results for ELI5 on Qwen under greedy decoding.

B.4 Additional Transferability

Furthermore, to better understand whether we can reuse our optimized suffixes on other instances, we extend our experiments without re-optimizing suffixes by selecting the top-3 strongest suffixes from Table 1 and evaluating their cross-model transferability. We observe that:

- The effect consistently persists at scale, confirming robustness beyond the initial 50-sample evaluation.

(a) LLaMA

(b) Qwen

Figure 5: Tokens used for ER Loss. Word clouds generated from the CoT outputs of LLaMA and Qwen on GSM8K.

Source	Model	LLaMA			Qwen		
		Reason	Answer	Full	Reason	Answer	Full
LLaMA	Base	559	243	802	559	243	802
	Ours	2383	164	2547	375	269	644
Qwen	Base	353	269	618	353	265	618
	Ours	205	285	490	4184	163	4346

Table 11: The performance of top-3 strongest suffixes on the full GSM8K dataset.

Source	Model	LLaMA			Qwen		
		Reason	Answer	Full	Reason	Answer	Full
QWQ	Base	1912	237	2149	1912	237	2149
	Ours	2348	229	2577	3367	333	3700
o3-mini	Base	247	137	386	247	137	386
	Ours	373	157	530	604	344	948
gpt5-mini	Base	168	72	210	168	72	210
	Ours	281	87	368	575	226	801

Table 12: The performance of top-3 strongest suffixes on the larger commericial models.

- Cross-model transfer remains effective, especially for Qwen-optimized suffixes, which show strong generalization.

These results indicate that our conclusions are not sensitive to sample size and remain valid under larger-scale evaluation.

B.5 Prompt Template

B.6 Samples

B.7 DSPy

	Mean
Raw	805
CoT	717
CoT+DSPy	1247

Table 13: The statistics of sample outputs with different promptings.

Figure 6

Prompt + Optimized Suffix

Janet's ducks lay 16 eggs per day. She eats three for breakfast every morning and bakes muffins for her friends every day with four.
She sells the remainder at the farmers' market daily for $2 per fresh duck egg.
How much in dollars does she make every day at the farmers' market?
?! Contains more tricks........ Elijahnumeric paradox nearer[/

Figure 7

Sample response 1 from our attack

Okay, so I need to figure out how much money Janet makes every day from selling her duck eggs. Let me start by breaking down the information given.
First, Janet's ducks lay 16 eggs per day. That's the total number of eggs she gets each day. Now, she has some daily responsibilities that involve using these eggs. She eats three for breakfast every morning, so that's 3 eggs used daily. Then, she bakes muffins for her friends every day with four eggs. Wait, does that mean she uses 4 eggs per day ...
So far, she's using 3 eggs for breakfast and 4 for baking, which totals 7 eggs per day. She lays 16 eggs ...
So, 9 eggs sold at $2 each would be 9 times 2, which equals $18. Therefore, Janet makes $18 every day from selling her eggs ...
Wait, let me double-check to make sure I didn't miss anything. She lays 16, uses 3 for breakfast, 4 for baking, so 16 - 3 - 4 = 9. Yes, that's correct. And each egg is sold for $2, so 9 times 2 is indeed $18. I think that's all there is to it. ...
. . .

Figure 8

Sample response 1 from original

First, determine the total number of eggs Janet's ducks lay each day, which is 16.

Next, calculate the number of eggs Janet uses for breakfast and baking muffins. She eats 3 eggs for breakfast and uses 4 eggs for baking, totaling 7 eggs.

Subtract the used eggs from the total to find out how many eggs she has left to sell: 16 - 7 = 9 eggs.

Finally, multiply the number of eggs she sells by the price per egg to find out how much money she makes daily: 9 eggs * $2 per egg = $18 . . .

Figure 9

Sample question 2

Raymond and Samantha are cousins.
Raymond was born 6 years before Samantha.
Raymond had a son at the age of 23.
If Samantha is now 31, how many years ago was Raymond's son born?

Figure 10

Sample response 2 from our attack

Okay, so I'm trying to figure out this problem about Raymond and Samantha . . .
Raymond and Samantha are cousins. Raymond was born 6 years before Samantha. Raymond had a son at the age of 23 . . .
Alright, so Raymond was born 6 years before Samantha . . .
Wait, no, that's not right. If Raymond was born 6 years before Samantha . . .
Yeah, that makes sense because if you subtract 6 years from Samantha's age . . .
So, 31 - 6 = 25?
Wait, no, that's the opposite . . .
Raymond had a son at the age of 23.
So, Raymond was 23 when his son was born.
Now, Raymond is 37, so the time between Raymond having his son and now is 37 - 23 = 14 years.
So, the son was born 14 years ago.
Wait, but let me double-check that. If Raymond was 23 when his son was born, and he is now 37, then 37 - 23 = 14 years have passed since the son was born.
So, the son is now 14 years old, which means he was born 14 years ago. That seems right.
. . .
</think>

. . . **Answer:** Raymond's son was born 14 years ago.

Figure 11

Figure 12

Models	Methods	GSM8K						ORCA					
		Rea	Ans	Full	Lat	Ent	Acc	Rea	Ans	Full	Lat	Ent	Acc
LLaMA	Original	556	257	812	71.5	9778	76%	550	248	798	86.7	10490	81%
	Random	401	270	671	54.0	7928	72%	493	244	737	80.6	9689	81%
	CoT	476	**280**	757	68.5	7713	75%	402	**266**	668	75.9	9148	80%
	Engorgio	161	282	443	15.3	3055	68%	249	234	484	39.1	9663	80%
	CatAttack	528	257	785	64.8	9818	77%	475	224	700	81.4	10680	82%
	Ours	**1437**	204	**1641**	**197.0**	**21228**	**90%**	**1425**	206	**1631**	**178.2**	**19243**	**87%**
Qwen	Original	345	277	622	37.0	5996	82%	452	250	701	51.2	7538	84%
	Random	221	296	518	23.4	4245	84%	501	254	755	54.5	7353	86%
	CoT	176	**308**	484	16.0	3799	85%	293	**274**	567	33.1	5722	**87%**
	Engorgio	191	300	490	20.5	4352	81%	268	205	473	21.9	4718	78%
	CatAttack	187	295	482	17.4	3398	81%	432	253	686	50.0	6458	83%
	Ours	**1479**	217	**1696**	**149.1**	**16031**	**91%**	**1238**	183	**1421**	**111.2**	**14747**	**87%**

Table 14: Experimental results across methods under sampling decoding.

Figure 13

> **Sample output from DSPy-optimized prompt**
>
> Okay, so I need to figure out how much money Janet makes every day from selling her duck eggs at the farmers' market. Let me start by breaking down the problem step by step.
>
> First, Janet's ducks lay 16 eggs per day. That's the total number of eggs she gets each day. Now, she has some daily expenses and uses related to these eggs. She eats three eggs for breakfast every morning. So that's 3 eggs used for breakfast. Then, she bakes muffins for her friends every day, using four eggs each time. **Wait**, does she bake muffins once a day using four eggs, or does she bake them multiple times? The problem says "bakes muffins for her friends every day with four," which is a bit ambiguous. I think it probably means she uses four eggs per day for baking muffins. So that's another four eggs.
>
> So, adding up her daily egg usage: 3 eggs for breakfast plus 4 eggs for muffins equals 7 eggs used each day. Now, she lays 16 eggs, so how many does she have left after using 7? Let me subtract: 16 minus 7 equals 9 eggs remaining. These 9 eggs are sold at the farmers' market, and she sells each for $2. So, 9 eggs times $2 per egg would give her $18 per day.
>
> **Wait**, let me double-check that. 16 eggs laid minus 7 used equals 9 sold. 9 times 2 is indeed 18. . . .

Figure 14