SubTab: Subsetting Features of Tabular Data for Self-Supervised Representation Learning

Abstract

Self-supervised learning has been shown to be very effective in learning useful representations, and yet much of the success is achieved in data types such as images, audio, and text. The success is mainly enabled by taking advantage of spatial, temporal, or semantic structure in the data through augmentation. However, such structure may not exist in tabular datasets commonly used in fields such as healthcare, making it difficult to design an effective augmentation method, and hindering a similar progress in tabular data setting. In this paper, we introduce a new framework, **Sub**setting features of **Tab**ular data (SubTab), that turns the task of learning from tabular data into a multi-view representation learning problem by dividing the input features to multiple subsets. We argue that reconstructing the data from the subset of its features rather than its corrupted version in an autoencoder setting can better capture its underlying latent representation. In this framework, the joint representation can be expressed as weighted average of latent variables of the subsets at test time, which we refer to as collaborative inference. Our experiments show that the SubTab achieves the state of the art (SOTA) performance of 97.86% on MNIST in tabular setting, on par with CNN-based SOTA models, and surpasses existing baselines on three other real-world datasets by a significant margin.

1 Introduction

In recent years, the self-supervised learning has successfully been used to learn meaningful representations of the data in natural language processing [23, 28, 8, 20, 7, 14, 6]. A similar success has been achieved in image and audio domains [4, 10, 25, 3, 11, 9, 5]. This progress is mainly enabled by taking advantage of spatial, semantic, or temporal structure in the data through data augmentation [4], pretext task generation [8] and using inductive biases through architectural choices (e.g. CNN for images). However, these methods can be less effective in the lack of such structures and biases in the tabular data commonly used in many fields such as healthcare, advertisement, finance, and law. And some augmentation methods such as cropping, rotation, color transformation etc. are domain specific, and not suitable for tabular setting. The difficulty in designing similarly effective methods tailored for tabular data is one of the reasons why self-supervised learning is under-studied in this domain [33].

The most common approach in tabular data is to corrupt data through adding noise [30]. An autoencoder maps corrupted examples of data to a latent space, from which it maps back to uncorrupted data. Through this process, it learns a representation robust to the noise in the input. This approach may not be as effective since it treats all features equally as if features are equally informative of the data, however perturbing uninformative features may not result in the intended goal of the corruption. A recent work takes advantage of self-supervised learning in tabular data setting by introducing a pretext task [33], in which a de-noising autoencoder with a classifier attached to representation layer is trained on corrupted data. The classifier's task is to predict the location of corrupted features.

Figure 1: SubTab framework: i) Dividing the features into subsets, ii) Reconstruction of either subsets of features ($\tilde{x}_i, \tilde{x}_j, \tilde{x}_k$), or complete feature space ($\tilde{X}_i, \tilde{X}_j, \tilde{X}_k$), which are used to compute reconstruction loss. iii) Generating projections used to compute contrastive and distance loss. $E \equiv Encoder, D \equiv Decoder, G \equiv Projection$.

However, this framework still relies on noisy data in the input. Additionally, training a classifier on an imbalanced binary mask for a high-dimensional data may not be ideal to learn meaningful representations.

In this work, we turn the problem of learning representation from a single-view of the data into the one learnt from its multiple views by dividing the features into subsets, akin to cropping in image domain to generate different views of the data. Each subset can be considered a different view. We show that reconstructing data from the subset of its features forces the encoder to learn better representation than the ones learned through the existing methods such as adding noise. We train our model in a self-supervised setting and evaluate it on downstream tasks such as classification, and clustering. We use five different datasets; MNIST in tabular format, the cancer genome atlas (TCGA) [29], human gut metagen-omic samples of obesity cohorts (Obesity) [24, 18], UCI adult income (Income) [16], and UCI BlogFeedback (Blog) [2].

SubTab can: i) construct a better representation by using weighted average of the representation of the subsets, a process that we refer as collaborative inference ii) discover the regions of informative features by measuring predictive power of each subset, which is useful especially in high-dimensional data iii) do training and inference in the presence of missing features by ignoring corresponding subsets and iv) use smaller models by reducing input dimension, making it less prone to overfitting.

2 Method

The augmentation methods such as adding noise, rotation, cropping etc. are commonly used in image domain. Among them, the cropping is shown to be the most effective technique [4]. Inspired from this insight, we propose subsetting features of tabular data.

Figure 1 presents SubTab framework, in which we have an encoder (E), a decoder (D), and an optional projection (G). For the purpose of this paper, we will refer h as latent, or representation, z as projection, $\tilde{x}$, and $\tilde{X}$ as the reconstruction of subset, and whole data respectively. Small letters are associated with subsets while capital latters are associated the whole set of features. Moreover, throughout this work, when we say that a representation is "good", we refer to its performance in a classification task using a linear model.

In SubTab framework, we divide tabular data to multiple subsets. Neighbouring subsets can have overlapping regions, defined as a percentage of a dimension of the subset. All subsets are fed to the same encoder to get their corresponding latent representation. A shared decoder is used to reconstruct either the subset fed to the encoder, or full tabular data (i.e. reconstructing all features from the subset of features). We chose the latter in our experiments since it is more effective in learning good representations. We should also note that, in the latter case, the autoencoder cannot learn the identity,

| (a) Push-Pull forces | (b) Feature selection | (c) Representation at test time |

Figure 2: a) Push-Pull forces applied by each loss. PS / NS : Positive/Negative sample; CL/RL/DL: Contrastive, Reconstruction, Distance losses b) Column or feature selection strategies for adding noise to each subset. **Top:** Selecting a block of neighbouring columns; **Middle:** Selecting columns randomly; **Bottom:** Selecting random features per row c) Latent variables from each subset is averaged over at test time.

eliminating the constraint on the dimension of the bottleneck (i.e. representation). We compute one reconstruction loss term per subset.

Moreover, we can optionally add contrastive loss to our objective by using all combination of pairs of projections from all subsets. For example, given three subsets as in Figure 1, there are three combinations of two: $\binom{n}{k} = \binom{3}{2} = \frac{3!}{2!(1)!} = 3$. For four subsets, it would be 6 pairs of combination, and so on. We can add one more loss term, referred as distance loss, to reduce the distance between the pairs of projections of the subsets by using a loss function such as mean squared error (MSE). All three loss terms apply a pulling force on positive samples while contrastive loss also applies a push force between positive and negative samples as shown in Figure 2a.

Once the dataset is divided into subsets, we shuffle the order of subsets in every batch during training to avoid introducing any unintentional bias. However, *we don't change the relative order of features in a subset* since standard neural network architectures are not permutation invariant. This is to ensure that same features are fed to the same input units of neural network. However, our method can be extended to permutation invariant setting as a next step.

2.1 Strategies for adding noise

Our framework is complementary to other augmentation techniques used in tabular data setting. Thus, we experimented with adding noise to randomly selected entries in subsets by using three types of noise: i) adding Gaussian noise, $\mathcal{N}(0, \sigma^2)$, ii) overwriting the value of a selected entry with another value randomly sampled from the same column, referred as swap-noise, iii) zeroing-out randomly selected entries, referred as zero-out noise.

Moreover, we use three different strategies when selecting the features to add noise to, as shown in Figure 2b: i) a random block of neighboring columns (NC), ii) random columns (RC) iii) random features per each sample (RF). To add noise, we create a binomial mask, m, and a noise matrix, ϵ, with same shape as the subset, in which the entries of the mask is assigned to 1 with probability p, and to 0 otherwise. The corrupted version, x_{1c}, of subset x_1 is generated as following:

$$x_{1c} = (1 - m) \odot x_1 + m \odot \epsilon \tag{1}$$

2.2 Training

Our objective function is:

$$\mathcal{L}_t = \alpha * \mathcal{L}_r + \beta * \mathcal{L}_c + \gamma * \mathcal{L}_d, \tag{2}$$

where $\mathcal{L}_t$, $\mathcal{L}_r$, $\mathcal{L}_c$ and $\mathcal{L}_d$ are total, reconstruction, contrastive, and distance losses, respectively.

i) Reconstruction loss: Given a subset, denoted by x_k, we can reconstruct either the same subset, $\tilde{x}_k$ or the entire feature space $\tilde{X}_k$. Then, we can compute the reconstruction loss for k^{th} subset by computing mean squared error using either $(x_k, \tilde{x}_k)$, or $(X, \tilde{X}_k)$ pair as shown in Figure 1. We

chose the latter since it was more effective. Overall reconstruction loss:

$$\mathcal{L}_r = \frac{1}{Z_r} \sum_{k=1}^{K} \alpha_k * s_k, \text{ where } s_k = \frac{1}{N} \sum_{i=1}^{N} \left(\boldsymbol{X}^{(i)} - \tilde{\boldsymbol{X}}_{\boldsymbol{k}}^{(i)} \right)^2, Z_r = \sum_{k=1}^{K} \alpha_k \qquad (3)$$

where K is the total number of subsets, N is the size of the batch, Z_r is the normalizing constant, α_k and s_k are the coefficient and reconstruction loss for k^{th} subset respectively, and $\mathcal{L}_r$ is the weighted average of reconstruction loss over all subsets.

ii) Contrastive loss: If the dataset is rich in the number of classes such that chances of sampling negative samples are high, we can use a projection network (G) to get projections, $\boldsymbol{z}'s$, of representations, $\boldsymbol{h}'s$. Samples at the same rows of two subsets, $\boldsymbol{z_1}$ and $\boldsymbol{z_2}$, can be considered as positive pairs while remaining rows in the subsets can be considered as negative to those samples.This allows us to compute the contrastive loss for each pair of projections using a loss function such as the normalized temperature-scaled cross entropy loss (NT-Xent) [4]. For three subsets, $(\boldsymbol{x_1}, \boldsymbol{x_2}, \boldsymbol{x_3})$, we can compute such a loss for every pair of total three pairs $(\boldsymbol{z_1}, \boldsymbol{z_2}), (\boldsymbol{z_1}, \boldsymbol{z_3}), (\boldsymbol{z_2}, \boldsymbol{z_3})$. Overall contrastive loss is:

$$\mathcal{L}_c = \frac{1}{Z_c} \sum_{j=1}^{J} \beta_j * p_{a,b}, \text{ where } p_{a,b} = \frac{1}{2N} \sum_{i=1}^{N} \left[l_{a,b}(2i-1, 2i) + l_{a,b}(2i, 2i-1) \right], Z_c = \sum_{j=1}^{J} \beta_j \quad (4)$$

$$l_{a,b}(u, v) = -\log \frac{\exp(sim(\boldsymbol{z_a}^{(u)}, \boldsymbol{z_b}^{(v)})/\tau)}{\sum_{k=1}^{2N} \mathbb{1}_{k \neq u} \exp(sim(\boldsymbol{z_a}^{(u)}, \boldsymbol{z_b}^{(k)})/\tau)} \qquad (5)$$

where J is number of pairs, Z_c is the normalization factor, β_j is the coefficient for j_{th} pair, $p_{a,b}$ is total contrastive loss for a pair of projection $(\boldsymbol{z_a}, \boldsymbol{z_b})$, and $l_{a,b}(u, v)$ is the loss function for a corresponding positive pairs of examples (u, v) in subsets $(\boldsymbol{z_a}, \boldsymbol{z_b})$.

iii) Distance loss: We can also add mean-squared error (MSE) loss for pairs of projections of subsets since the corresponding samples in subsets should be close to each other. Hence, we can compute an overall MSE loss as:

$$\mathcal{L}_d = \frac{1}{Z_d} \sum_{j=1}^{J} \gamma_j * p_{a,b}, \text{ where } p_{a,b} = \frac{1}{N} \sum_{i=1}^{N} \left(\boldsymbol{z_a}^{(i)} - \tilde{\boldsymbol{z_b}}^{(i)} \right)^2, \text{ and } Z_d = \sum_{j=1}^{J} \gamma_j. \qquad (6)$$

The pseudocode of algorithm can be found in Algorithm 1 in the Appendix. We should note that we used $\alpha_k = \beta_j = \gamma_j = 1$ in equations (3), (4), and (7) respectively throughout our experiments.

2.3 Test time

At test time, we feed the subsets of test set to the encoder, and get the weighted average of the representations of all available subsets as shown in Figure 2c. Our experiments show that we can use the representations of only one, or few subsets and still achieve a good performance. For example, we could use only $\boldsymbol{h_1}$, or average of $\boldsymbol{h_1}$ and $\boldsymbol{h_2}$ rather than averaging over all subsets $(\boldsymbol{h_1}, \boldsymbol{h_2}, \boldsymbol{h_3})$ in Figure 2c. This allows the model to infer from the data even in the presence of missing features, in which case we can ignore the subset with missing features. We can also do weighted inference by weighting the representations of subsets since some subsets might be more informative than others:

$$\boldsymbol{h} = \frac{1}{Z} \sum_{k=1}^{K} \eta_k * \boldsymbol{h_k}, \text{ and } Z = \sum_{k=1}^{K} \eta_k, \qquad (7)$$

where K is number of subsets, and η_k is the weight for k_{th} subset. η can be a learnable parameter. We used $\eta_k = 1$ for all subsets throughout our experiments, unless explicitly stated.

3 Experiments

We conduct various experiments on diverse set of tabular datasets including MNIST [19] in tabular format, the cancer genome atlas (TCGA) [29], human gut metagen-omic samples of obesity cohorts (Obesity) [24, 18], UCI adult income (Income) [16], and UCI BlogFeedback (Blog) [2] to demonstrate the effectiveness of the SubTab framework. We compare our method to other self-supervised methods

such as VIME-self [33], Denoising Autoencoder (DAE) [30], Context Encoder (CAE) [27] as well as fully-supervised models such as Logistic regression, XGBoost, two-layer MLP as it is done in [33]. For each dataset, once we decided on a particular autoencoder architecture, we used it for all models compared (i.e. VIME-self, DAE, CAE, and our model). We tried both relu and leakyReLU as activation functions for all, but leakyReLU usually performed better. Please note that VIME-self's choice for MNIST is relu, based on the published code [32]. The code for SubTab is provided[1]. The summary of model architectures and hyper-parameters are in Table 3 in the Appendix.

3.1 Data

MNIST: We flattened 28x28 images, and scaled them by dividing all with 255 as it is done in [33]. We split training set into training and validation sets (90-10% split) when searching for hyper-parameters, and then used all of training set to train the final model. The test set is used only for final evaluation.

The Cancer Genome Atlas (TCGA): TCGA is a public cancer genomics dataset characterized over 20,000 primary cancer and matched normal samples that holds information over 38 cohorts. The task is to classify the cancer cohorts from the reverse phase protein array (RPPA) dataset. It includes 6671 samples with 122 features, which we divided to 80-10-10% train-validation-test sets. Once hyper-parameters is found, we trained the models on combined training and validation set.

Obesity: The dataset consists of publicly available human gut metagen-omic samples of obesity cohorts [24]. It is derived from whole-genome shotgun metagenomic studies. The dataset consists of 164 obese patients and 89 non-obese controls and has 425 features [18]. We scaled the dataset by using min-max scaling. Since it is a small dataset, we evaluated the model by using 10 randomly drawn training-test (90-10%) splits, for each of which we used 10-fold cross-validation.

UCI Adult Income: It is a well-known public dataset extracted from the 1994 Census database [16]. It includes the details such as education level and demographics to predict whether the income of a person exceeds $50K/yr. The data consists of six continuous and eight categorical features. After one-hot encoding of categorical features, there are total of 101 features. The pre-processing steps can be found in Section B.1 of Appendix.

UCI BlogFeedback: The data originates from blog posts, and is originally used for regression task of predicting the number of comments in the upcoming 24 hours. Similar to Yoon et al. [33], we turned it into a binary classification task of predicting whether there is a comment for a post or not.There are 280 integer and real valued features, and separate training and test datasets are provided. Further information can be found in Section B.2 of Appendix.

3.2 Evaluation

For self-supervised models, once the models are trained, we evaluate them by training a logistic regression model on the latent representations of training set, and testing it on the latent representation of the test set. We use the performance on a classification task as a measure of quality of the representation as it is usually done in the self-supervised learning. MNIST has 10, TCGA has 38, and the rest (i.e. Obesity, Income, and Blog) has 2 classes each.

3.3 Results

MNIST: We used a simple three-layer encoder architecture with dimensions of [512, 256, 128], referred as the base model, in which the last layer is a linear layer. During training of the base model, we used both reconstruction loss and contrastive loss. Additionally, we trained our model under three conditions: i) without any noise in the input data, ii) with noise in the input data and iii) same as (ii), but we also added distance loss computed for pairs of projections ($z_i, z_j, ...$).

In the first experiment, we trained our base model multiple times without noise at the input and using different number of subsets with different levels of overlap between neighbouring subsets (Figure 7a). In the case of small number of subsets (e.g. 2 or 3), the performance monotonically decreases by increasing the overlap between subsets. On the other hand, for higher number of subsets, the performance generally improves as we increase the number of shared features between the neighbouring subsets. In general, our results show that $K = 4$ with 75% overlap, and $K = 7$ with

---

[1]https://github.com/subtab/subtab

(a)   (b)   (c)

Figure 3: a) Test accuracy on MNIST dataset over different number of subsets and varying levels of overlaps. b-c) t-SNE plots for training (b) and test (c) sets of MNIST for the case of using 4 subsets with 75% overlap between neighboring subsets.

(a)   (b)

Figure 4: a) After training the base model (latent dimension=128) on four subsets with 75% overlap, we test its performance using different number of subsets. The performance improves as we start increasing number of subsets involved in prediction. b) Comparing our model (latent dimension=512) to VIME and CNN-based SOTA models trained on 28x28 MNIST in image format.

50% overlap perform the best in MNIST dataset, where K refers to the number of subsets. Figure 7 also shows t-SNE plots of training and test sets, which proves the high quality of clustering.

For the optimum case of $K = 4$ with 75% overlap, we trained and tested accuracy of a linear model using representations obtained from the varying number of subsets. Starting with a single subset of the data, we plot the training and test accuracy of the model (Figure 4a). The linear model is able to achieve 87.5% test accuracy using the representation of a single subset. As we start adding latent representations of remaining subsets, the test accuracy keeps increasing, eventually achieving top accuracy when all subset are used. At test time, the performance of our model using two subsets corresponding the half of the features already matches the performance ($95.77 \pm 0.22\%$) of full VIME model [33], which is trained with all features, and with labels. The evolution of clusters corresponding to Figure 4a can be seen in Figure 6 in Appendix.

Table 1 summarizes the classification accuracy of all the models on the test set. For MNIST, Blog, and Income datasets, the results for all other methods are taken from the Yoon et al. [33]. Our base model without noise outperforms self and full version (semi-supervised with 10% of training set) of VIME with a significant margin, and achieves the state of the art (SOTA) performance in tabular data setting. We experimented with three noise types, and observed that adding swap-noise at the input pushes the performance higher. Adding distance loss helps to improve the performance even further. Finally, increasing the dimensions of the last layer from 128 to 512 places the model performance on par with CNN-based SOTA models [13, 12, 17, 15, 22] as shown in Figure 4b.

In the second experiment, we divided *the unshuffled* features of MNIST to seven subsets with no overlap (corresponding to the yellow line in Figure 7a). We trained the base model five times on different sets of subsets; the first one is trained only on subset 4, the second one only on subsets 4 and 5, and so on. We also initialized a sixth model, but kept it untrained. We first compare the five trained models based on the test accuracy using linear model on the average of the latent representations of

Figure 5: a) The test accuracy using the average of the latent representations of subsets, starting with the first subset, and keep adding new subsets sequentially. b) The test accuracy of individual subsets. c) Comparing the test accuracy by averaging the latent variables of different set of subsets at test time for two versions of the model; untrained and the one trained on all subsets.

subsets, starting with the first subset (subset 1), and keep adding new subsets sequentially to add more information to the representation as shown in Figure 5a. We observe that even when the model is trained on a single subset (subset 4, or the blue line in Figure 5a), averaging the representations of all seven subsets including the subsets not used in training does improve the results. This is because the encoder is able to map samples of different classes to different points in latent space even if it is not trained on them. Since we do a vector averaging over different views (i.e. subsets) of the same class, we can still make each class in the data distinguishable from the rest in the latent space. We also note that when the model is trained on more and more subsets, its performance keeps improving. As a baseline, we also conducted the same test using untrained model (red line in the plot), and observed similar behaviour in which the test accuracy generally improves as we use more subsets when constructing the joint latent representation. Moreover, we measured the test accuracy of individual subsets to see how informative each subset is (Figure 5b). The result is as expected since we kept the features unshuffled in this experiment, and know that the subsets corresponding to the mid-region of the images (i.e. subsets 3, 4, and 5) should be more informative than the ones corresponding to the top and bottom regions (i.e. subsets 1, and 7).

In the third experiment, we compared the untrained model to the one trained on all subsets by measuring the test accuracy of a linear model using the average representations of different set of subsets obtained from each model. The test accuracy is measured using i) only subset 4, ii) average of the most informative subsets (3,4,5), iii) average of (2,3,4,5,6) excluding the least informative subsets, and iv) all subsets at test time (Figure 5c).

Overall, we can make the following observations from our experiments: i) the less informative subsets can add value to the overall representation, or at least does not harm the performance (see the average over [3,4,5] versus [2,3,4,5,6] in Figure 5c), ii) untrained model can be used to analyze which subsets can be potentially more informative, iii) once a model is trained on a subset, the performance of the individual subset does not change whether it is trained together with other subsets or not (for example, compare the performance of subset 3, 4, and 5 across all models in Figure 5b), and iv) general idea behind our framework works even for untrained model.

The results indicate that SubTab can accommodate missing features at test time, and can still perform well. This might also indicate that working with subsets can gives us a way to deal with uncertainty better when there are missing features at test time. As the model collects more information in the form of more features, its prediction improves. We can also train the model with missing subsets, and still perform well. We may not need to impute data in our framework since we can simply ignore them as missing subsets. This is good since imputation generally distorts data, and the results.

TCGA: We used an encoder architecture with three layers [1024, 784, 784], where the third layer is linear. For VIME-self, DAE, CAE, and our model, we experimented with three noise types (Gaussian, swap, and zero-out noise) at the different % levels of masking ratio p. We observed that $p = [0.15, 0.2]$ worked well for all models, except that $p = 0.3$ was the best for VIME-self. For Gaussian noise, we used a distribution with zero mean, and different levels of standard deviation (stdev). Among all three noise types, Gaussian noise with $stdev = 0.1$ worked the best for all models.

Table 1: Accuracy scores for all the models for various datasets. The abbreviations in the table; NC: Neighbour columns used, RF:Random features used, G: Gaussian noise, S: Swap noise. *: For MNIST, Income and Blog, the scores for the models other than ours are obtained from [33].

Type	Models	MNIST*	Income*	Blog*	Obesity	TCGA
Supervised	Logistic Regression	89.89±0.23	84.25±0.13	69.15±0.29	66.02±3.25	36.47± 1.92
	2-Layer Perceptron	93.87±0.14	85.20±0.23	79.72±0.58	62.31±3.22	60.48±1.39
	XGBoost	94.13±0.26	86.23±0.21	79.75±0.30	62.74±4.38	70.96±1.51
Self-supervised	DAE (RF)	94.31±0.32	85.78±0.28	80.01±0.39	56.43±5.79 (G)	54.31±1.39 (G)
	CAE (NC)	94.55±0.48	86.11±0.27	80.33±0.51	62.26±5.01 (G)	54.20±1.17 (G)
	VIME-self	94.06±0.19 (S)	85.99±0.26	81.47±0.37	60.78±3.93 (G)	50.75±1.89 (G)
	SubTab with:					
	Base model (No noise)	97.26±0.2	85.31±0.08	84.29±0.26	68.01±3.07	57.02±1.50
	+Noise	97.47±0.18 (S)	85.34±0.07 (G)	84.47±0.15 (G)	**71.13±4.08 (G)**	**58.25±1.36 (G)**
	+Distance loss	97.52±0.14 (S)	85.35±0.06 (G)	**84.64±0.19** (G)	69.25±4.19 (G)	58.15±1.56 (G)
	+LatentDim=512	**97.86±0.07 (S)**	-	-	-	-

Please note that VIME-self uses swap-noise in its original implementation, but swap-noise does not work well on this dataset. For our model, similar to MNIST, we used four subsets with 75% overlap. Our model performs better than all three models with a significant margin and almost doubles the performance of logistic regression model trained on raw data as shown in Table 1.

Obesity: We used a two-layer encoder with [1024, 1024] dimensions. Second layer is a linear layer. Gaussian noise $\mathcal{N}(0, 0.3)$ and masking ratio $p = 0.2$ works well across all models. Six subsets ($K = 6$) with 0% overlap performed the best for the SubTab. We note that this dataset has 164 obese patients out of 253 total patients. So, the baseline accuracy is $164/253 = 64.82\%$. Based on this fact, we can say that all models, except ours, did not perform well on this dataset. Our model with added Gaussian noise results in accuracy of $71.13 \pm 4.08\%$, which is well above all models, including supervised ones. It means that our model was able to learn useful representation from the data. We should also note that the performance of our model is much better than what Oh and Zhang [24] reported ($66 \pm 3.2\%$) even though they trained a DAE on the same data, and reported their results using a random forest, a non-linear model, on the learned representations rather than a linear model.

UCI Adult Income & BlogFeedback: For these two datasets, we used the same architecture as in Obesity. For Income dataset, the best performance is obtained using 5 subsets with 25% overlap whereas we used 7 subsets with 75% overlap for Blog dataset. For the base model, we only used reconstruction loss. Adding Gaussian noise to the input and distance loss to the objective improves the performance for both datasets. SubTab outperforms all models by a considerable margin in Blog dataset. All models perform similar in Adult Income dataset, given that the scores are within the margin of error. The choice of hyper-parameters and other details can be found in Table 3 in Section C.1 of Appendix.

3.4 Ablation study

We conducted a comprehensive ablation study using MNIST. Table 2 summarizes our experiments. The first thing to note is that the performance of the our base model is already good with only reconstruction loss. Hence, we can argue that the reconstruction of original feature space from a subset of features is a very effective way of learning representation. By adding noise to the input data, we can improve the performance. In the case of MNIST, swap-noise is very effective. Also, by adding additional losses such as contrastive, and distance losses, we can further improve the results. Increasing the dimension of representation layer from 128 to 512 places our model performance on par with CNN-based SOTA models. Lastly, we also shuffled the features of MNIST to make sure that we don't have any gains from unintentional spatial correlations between neighboring features. We kept all parameters and random seeds same for the comparison. As shown in the table, our model's performance does not change much. Finally, we tried concatenating latent variables of subsets rather than averaging them when testing the performance of the best model. Comparing last two rows in the table, averaging is shown to work much better.

4 Related works

We refer the reader to the introduction section that lists some of the recent noticeable works in self-supervised learning. Since our work focuses on tabular data, we will review some of the recent

work done in tabular data in self-supervised framework. The most recent work is mostly based on solving a pretext task. For example, Yoon et al. [33] uses a de-noising autoencoder with a classifier attached to its representation layer. A random binary mask is generated to mask and overwrite a portion of entries in the tabular data, and the corrupted data is given as input to the encoder. The classifier is used to predict the mask while decoder is used to re-construct the uncorrupted original input similar to de-noising autoencoder [30]. Although the proposed method is shown to work well in the experiments, there are couple drawbacks to this approach. Firstly, this approach might not work well in very high-dimensional, small and noisy data sets since the model might easily become over-parameterized and be prone to overfitting to the data. Secondly, training a classifier in this setting can be challenging since it needs to predict very high dimensional, sparse, and imbalanced binary mask, similar to the problems observed when training a model on imbalanced, binary dataset. In a similar way, TabNet [1] and TaBERT [31] also tries to recover original data from corrupted one.

5   Conclusion

In this work, we show that a simple MLP-based autoencoder trained on MNIST in tabular format can perform on par with the CNN-based SOTA models trained on MNIST images in unsupervised/self-supervised framework. SubTab achieves SOTA in MNIST dataset in tabular setting. We also tested our approach on other commonly used tabular datasets, and proved its benefits.

Using subsets of features not only may obviate the need for data imputation during training, but also allows inference using subsets of features at test time. It might open the door to distributed training of high-dimensional data since the models can be trained on different subsets of features at the same time. We can also potentially take advantage of different datasets with common features by assigning those features to same subsets. We should note

Table 2: Ablation study using MNIST with 4 subsets with 75% overlap between subsets. Abbreviations are; **RL:** Reconstruction Loss, **CL:** Contrastive Loss, **DL:** Distance Loss, **SF:** Shuffled features, **LD:** Latent Dim, **AL:** Averaging Latent.

RL	CL	Noise	DL	SF	LD	AL	Test Accuracy
+	-	-	-	-	128	+	97.13
-	+	-	-	-	128	+	97.11
+	+	-	-	-	128	+	97.26
+	+	Zero-out	-	-	128	+	97.25
+	+	Gaussian	-	-	128	+	97.25
+	+	Swap	-	-	128	+	97.47
+	+	Swap	+	-	128	+	97.52
+	+	Swap	+	+	128	+	97.2
+	+	Swap	+	-	512	-	97.08
+	+	Swap	+	-	512	+	**97.86**

that the subsets shared the same autoencoder in our experiments although we could use separate autoencoders for different subsets if some of the features are drastically different than the rest.

SubTab using only reconstruction loss is computationally scalable. However, when we use contrastive, and/or distance losses during training, we need to use the combinations of projections, making the computational complexity quadratic during training, and hence limiting the number subsets we can use to divide the data. However, computational complexity is still linear at test time since we need to compute only the weighted average of the representations of the subsets. Also, when we divide the features into subsets, we keep the location of features in each subset same throughout training and test time since neural networks are not permutation invariant. In theory, each feature can be considered as a subset to get around this issue. We can also extend our work to permutation invariant architectures by treating collection of features as a set.

6   Broader Impact

Tabular data is a commonly used format in healthcare, finance, law and many other fields. Despite its broad usage, the most of the research in deep learning, especially with regards to unsupervised representation learning, has been on other data types such as images, text and audio. Our paper tries to close this gap by introducing a new framework to learn good representations from tabular data in unsupervised/self-supervised setting. The progress in this line of research will open doors to widespread applications of tabular data in other areas such as transfer learning, distributed learning, and multi-view learning, in which we can combine knowledge such as demographics and genomics from tabular data with those in images, text and audio. However, we should be aware of the shortcomings of such data integration in terms of biases and privacy issues that it might introduce.

References

[1] Sercan O Arik and Tomas Pfister. Tabnet: Attentive interpretable tabular learning. *arXiv preprint arXiv:1908.07442*, 2019.

[2] Krisztian Buza. Feedback prediction for blogs. In *Data analysis, machine learning and knowledge discovery*, pages 145–152. Springer, 2014.

[3] Mathilde Caron, Ishan Misra, Julien Mairal, Priya Goyal, Piotr Bojanowski, and Armand Joulin. Unsupervised learning of visual features by contrasting cluster assignments. *arXiv preprint arXiv:2006.09882*, 2020.

[4] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pages 1597–1607. PMLR, 2020.

[5] Xinlei Chen, Haoqi Fan, Ross Girshick, and Kaiming He. Improved baselines with momentum contrastive learning. *arXiv preprint arXiv:2003.04297*, 2020.

[6] Ronan Collobert and Jason Weston. A unified architecture for natural language processing: Deep neural networks with multitask learning. In *Proceedings of the 25th international conference on Machine learning*, pages 160–167, 2008.

[7] Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. Unsupervised cross-lingual representation learning at scale. *arXiv preprint arXiv:1911.02116*, 2019.

[8] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

[9] William Falcon and Kyunghyun Cho. A framework for contrastive self-supervised learning and designing a new approach. *arXiv preprint arXiv:2009.00104*, 2020.

[10] Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre H Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Daniel Guo, Mohammad Gheshlaghi Azar, et al. Bootstrap your own latent: A new approach to self-supervised learning. *arXiv preprint arXiv:2006.07733*, 2020.

[11] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9729–9738, 2020.

[12] Weihua Hu, Takeru Miyato, Seiya Tokui, Eiichi Matsumoto, and Masashi Sugiyama. Learning discrete representations via information maximizing self-augmented training. In *International Conference on Machine Learning*, pages 1558–1567. PMLR, 2017.

[13] Xu Ji, João F Henriques, and Andrea Vedaldi. Invariant information clustering for unsupervised image classification and segmentation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9865–9874, 2019.

[14] Armand Joulin, Edouard Grave, Piotr Bojanowski, and Tomas Mikolov. Bag of tricks for efficient text classification. *arXiv preprint arXiv:1607.01759*, 2016.

[15] Lyes Khacef, Laurent Rodriguez, and Benoit Miramond. Improving self-organizing maps with unsupervised feature extraction. In *International Conference on Neural Information Processing*, pages 474–486. Springer, 2020.

[16] Ron Kohavi. Scaling up the accuracy of naive-bayes classifiers: A decision-tree hybrid. In *Kdd*, volume 96, pages 202–207, 1996.

[17] Adam R Kosiorek, Sara Sabour, Yee Whye Teh, and Geoffrey E Hinton. Stacked capsule autoencoders. *arXiv preprint arXiv:1906.06818*, 2019.

[18] Emmanuelle Le Chatelier, Trine Nielsen, Junjie Qin, Edi Prifti, Falk Hildebrand, Gwen Falony, Mathieu Almeida, Manimozhiyan Arumugam, Jean-Michel Batto, Sean Kennedy, et al. Richness of human gut microbiome correlates with metabolic markers. *Nature*, 500(7464):541–546, 2013.

[19] Yann LeCun. The mnist database of handwritten digits. *http://yann. lecun. com/exdb/mnist/*, 1998.

[20] Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

[21] Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*, 2017.

[22] Alireza Makhzani, Jonathon Shlens, Navdeep Jaitly, Ian Goodfellow, and Brendan Frey. Adversarial autoencoders. *arXiv preprint arXiv:1511.05644*, 2015.

[23] Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*, 2013.

[24] Min Oh and Liqing Zhang. Deepmicro: deep representation learning for disease prediction based on microbiome data. *Scientific reports*, 10(1):1–9, 2020.

[25] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

[26] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc., 2019. URL http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf.

[27] Deepak Pathak, Philipp Krahenbuhl, Jeff Donahue, Trevor Darrell, and Alexei A Efros. Context encoders: Feature learning by inpainting. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2536–2544, 2016.

[28] Jeffrey Pennington, Richard Socher, and Christopher D Manning. Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pages 1532–1543, 2014.

[29] Katarzyna Tomczak, Patrycja Czerwińska, and Maciej Wiznerowicz. The cancer genome atlas (tcga): an immeasurable source of knowledge. *Contemporary oncology*, 19(1A):A68, 2015.

[30] Pascal Vincent, Hugo Larochelle, Yoshua Bengio, and Pierre-Antoine Manzagol. Extracting and composing robust features with denoising autoencoders. In *Proceedings of the 25th international conference on Machine learning*, pages 1096–1103, 2008.

[31] Pengcheng Yin, Graham Neubig, Wen-tau Yih, and Sebastian Riedel. Tabert: Pretraining for joint understanding of textual and tabular data. *arXiv preprint arXiv:2005.08314*, 2020.

[32] J Yoon. Vime: Extending the success of self- and semi-supervised learning to tabular domain. https://github.com/jsyoon0823/VIME, 2020.

[33] Jinsung Yoon, Yao Zhang, James Jordon, and Mihaela van der Schaar. Vime: Extending the success of self-and semi-supervised learning to tabular domain. *Advances in Neural Information Processing Systems*, 33, 2020.