INSNET: An Efficient, Flexible, and Performant Insertion-based Text Generation Model

Abstract

We propose INSNET, an expressive insertion-based text generator with efficient training and flexible decoding (parallel or sequential). Unlike most existing insertion-based text generation works that require re-encoding of the context after each insertion operation and thus are inefficient to train, INSNET only requires one pass of context encoding for the entire insertion sequence during training by introducing a novel insertion-oriented position encoding to enable computation sharing. Furthermore, INSNET provides a controllable switch between parallel and sequential decoding, making it flexible to handle more parallelizable tasks such as machine translation to support efficient decoding, or less parallelizable tasks such as lexically constrained open-domain text generation to guarantee high-quality outputs. Experiments on two unsupervised lexically constrained text generation datasets and three machine translation datasets demonstrate INSNET's advantages over previous insertion-based methods in terms of training speed, inference efficiency, and generation quality.[1]

1 Introduction

Insertion-based text generation that formulates the generation process as a sequence of token insertion operations has received increasing attention in the research community in recent years. There are two major advantages of insertion-based generation over the prevalent left-to-right auto-regressive paradigm: 1) It can reduce the decoding cost to sub-linear *w.r.t.* the sequence length with parallel decoding (Stern et al., 2019; Gu et al., 2019b), and 2) these non-monotonic text generators with flexible decoding orders may better recover/utilize the underlying linguistic structures of languages (Welleck et al., 2019; Gu et al., 2019a).

However, this new paradigm of text generation brings unique challenges, mostly in the training efficiency. Unlike left-to-right auto-regressive decoders which monotonically expand the context, the insertion operations complicate the position information of each token as the context expands. Concretely, as is shown in Figure 1, the absolute position of a token in a sequence constantly changes along with the insertion operations. As a result, a naive implementation of insertion-based models (e.g., Stern et al. (2019); Gu et al. (2019b)) needs to re-encode the context with updated positional information for each token as the insertions proceed, yielding inefficient training with $O(n)$ times of context re-encoding (with n indicating the sequence length).

To tackle this problem, previous insertion-based generation models such as Insertion Transformer (InsT) (Stern et al., 2019) and Levenshtein Transformer (LevT) (Gu et al., 2019b) propose parallel token insertion to reduce the insertion/re-encoding steps from $O(n)$ to $\Theta(\log n)$ for both training and inference. However, while it works well for machine translation, such parallel insertion falls

---

[1]The code will be publicly released soon on github.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Figure 1: The absolute position information of each token is volatile for insertion-based models. Thus, vanilla encoding without optimization usually have to re-encode the sequence after each expansion even during training.

Table 1: Comparisons between INSNET and existing insertion-based models regarding training-time re-encoding steps (*#Re-Enc.* columns) and how the models encode positional information (the *PosInfo* column).

Model	#Re-Enc. w/ ParaDec	#Re-Enc. w/ SeqDec	PosInfo
Ins. Trans.	$\Theta(\log n)$	$O(n)$	Absolute
Lev. Trans.	$\Theta(\log n)$	$\Omega(n)$	Absolute
NMSTG	$O(n)$	$O(n)$	Markovian/Absolute
InDIGO	N/A	$O(1)$	Direction-only
INSNET (Ours)	$O(1)$	$O(1)$	Relative

short on high-entropy generation tasks such as open-domain dialogue systems(Li et al., 2017a), creative generation like story (Yao et al., 2019), poetry (Manurung et al., 2000), and humor generation (Hempelmann, 2008), where many output tokens are highly dependent on each other and thus cannot be accurately predicted in parallel. Another thread of work seek to maintain sequential insertions but simplify the position encoding for the tokens so that they do not change as the insertion operations proceed (Gu et al., 2019a) to save computation. However, this sacrifices model capability and limits its applications to complex sequences.

In this paper, we propose INSNET, which addresses the training efficiency issue of insertion-based text generators by enabling computation sharing similar as that in vanilla decoder transformers. **Our first contribution** is an insertion-oriented, relative positional encoding named *offset* that allows INSNET to achieve computation sharing without compromising model capacity. At each insertion step, previously computed position encodings ,*i.e.* offsets, remain unchanged while accurately recording the updated pairwise token spatial relations in the pair-wise level. A corresponding offset can be efficiently computed for any given insertion order with a novel process named *offset compression*. In this way, we avoid expensive re-encoding of the context, and based on the encoded context, **our second contribution** is the design of an effective aggregation process that allows us to parallelly generate expressive slot representations for every slot in the partially generated sequence, flexibly support both sequential and parallel decoding. **Finally**, inspired by the layerization idea of Dinic's algorithm(Dinitz, 2006), we propose an algorithm for INSNET to better determine the parallelized insertion operations in order to mitigate the likelihood discrepancy before and after the parallelization. With all the components, INSNET is a novel framework that enables efficient training, flexible decoding, and expressive positional encoding. Table 1 shows a comparison between INSNET and all prior insertion-based models.

2 Related Works and Background

Auto-regressive Language Models minimize the negative-log-likelihood of a sequence of n tokens $s_{<n} = [x_0, x_1, ..., x_{n-1}]$ with a left-to-right factorization. With the transformer architecture (Vaswani et al., 2017), each step of likelihood estimation can be calculated in parallel while sharing the prefix context encoding calculations. This makes it possible to build powerful and efficient text generation models, like the GPT family (Radford et al., 2018, 2019; Brown et al., 2020). A lot of successful applications are based on this paradigm of models, such as automatic story generation (Yao et al., 2019; Tan et al., 2020), image captioning (Vinyals et al., 2015; Xu et al., 2015), machine translation (Bahdanau et al., 2015; Liu et al., 2020), and dialogue system (Li et al., 2017b,a).

Insertion-based Models with Parallel Decoding Insertion transformer (Stern et al., 2019) (InsT) proposes a design for insertion-based text generation. In each step, a bi-directional encoder transformer is performed on the expanded sequence to compute the representation for each candidate slot between every two consecutive positions. After such, an optimization process for the joint distribution of position-token is performed to actually insert one or more token(s).

Variants of InsT share the common atomic objective that models the *step log-likelihood*. On step t where a token $x_{i\downarrow i+1}$ is inserted in slot $l_{i\downarrow i+1}$ between position i and $i + 1$ of context s_t^o, the *step log-likelihood* can be written as:

$$\log p(x_{i \downarrow i+1}, \boldsymbol{l}_{i \downarrow i+1} | \boldsymbol{s}_t^o) = \log p_{position}(i+1 | \boldsymbol{s}_t^o) + \log p_{token}(x_{i \downarrow i+1} | e(\boldsymbol{s}_t^o)_i \oplus e(\boldsymbol{s}_t^o)_{i+1}),$$

where $e(\cdot)_i$ stands for the i-th position of bi-directional encoding of the sequence and $\oplus$ stands for vector concatenation. InsT adopts the original absolute positional encoding of transformers, the representation of the generated sequence has to be *completely re-encoded* after each step of context expansion to match the position changes of tokens. The expectation of the negative log step likelihood over all permitted context-insertion pairs at each step is computed as the *step loss*. The step losses from the first step to the last one are summed up as the *sequence loss*. Benefiting from the partially parallelized prediction of tokens, InsT can reduce the number of re-encoding steps to $\Theta(\log n)$.

Levenshtein Transformer (Gu et al., 2019b) (LevT) contains two phases during generation: 1) Insertion phase: it first uses a similar strategy as InsT, but only inserts placeholders; an MLM is applied to fulfill the placeholders. 2) Deletion phase: the model is trained as a token-wise discriminator to determine where to delete, under the evaluation of the Levenshtein distance by dynamic programming. In practice, this would result in a slower process compared to InsT, but better generation quality as it alleviates the incoherence caused by parallel insertions.

Sequential Insertion-based Model Previous exploration in insertion-based models mostly assumed the usage of parallel decoding in each decoding step, resulting in a partially auto-regressive procedure. For those are trained to only generate one token per decoding step, a vanilla implementation would result in an $O(n)$ factor in training time complexity. NMSTG (Non-monotonic Sequential Text Generation, Welleck et al. (2019)) is one of the first attempts at modeling a non-monotonic sequential insertion-based generation process. It constrains the dependencies of each inserted token to pseudo-Markovian on an expansion tree. InDIGO(Gu et al., 2019a) is proposed as a sequentially-decoded insertion-based model with the transformer architecture. It supports the efficient likelihood estimation by working around the aforementioned *volatility problem* (see Figure 1) at a cost of omitting the distance information in its position encoding, and is thus able to adopt the conventional computation sharing trick to boost the multiplicative factor in training time complexity for each sequence to as fast as $O(1)$. However, InDIGO uses a encoding of all previously inserted tokens to predict the next token regardless of their tentative position. It is only after the next token is predicted, the inserted position for it is predicted. Thus, there's no trivial solution to use InDIGO as a (partially) non-autoregressive insertion-based generator.

Absolute vs. Relative Position Embedding The original transformer (Vaswani et al., 2017) uses sinusoidal, absolute position embeddings. Relative position embedding in transformers (Shaw et al., 2018; Dai et al., 2019) was originally proposed to make the modeling of spatial relation invariant to position translation, and to improve the long-term dependency performance of the model. In replacement of absolute positions, which are tied to each token in the sequence, relative positions try to encode the spatial layout of the tokens with a matrix that records a directed distance from the column token to the row token. We further develop the idea of relative position embedding as the key component to overcome the issue of volatile position information of absolute positions in an insertion-based generation process. A noticeable fact is that InDIGO's implementation of position encoding can also be regarded as a direction-only relative position embedding system.

3   The INSNET Model

There are three major components of INSNET: 1) An insertion context encoder based on the transformer architecture (Vaswani et al., 2017) that uses a novel way to compute relative position to better suit the insertion-based nature of the generation process and enable computation sharing; 2) a module to compose expressive slot representation for predicting tokens to insert in different slots simultaneously; and 3) an algorithm that adaptively determines the parallelization of the insertion operations to minimize conflicts. We introduce each component as follows.

3.1   Context Encoder: A Transformer with Insertion-Oriented Relative Position

In the introduction, we discussed the challenges in (efficient) computation sharing caused by the volatile position information of the context tokens as shown in Figure 1. We address this problem by empowering the transformer-based context encoder with a distance-aware, insertion-oriented pairwise relative position encoding. The proposed insertion-oriented relative position encoding shares

(a) Absolute Positions   (b) Vanilla Relative Positions   (c) Our Relative Positions   (d) Ours, Order-Restored

Figure 2: Comparison of different position encodings for an insertion-based generation process. From left to right, we illustrate 2(a) the volatile absolute positions, 2(b) the traditional non-insertion-oriented relative positions, 2(c) the proposed offset matrix presented in the insertion order, and 2(d) the same offset matrix permuted to show how it looks like if we restore the actual (partial-)sequence.

important designs with previous relative position embeddings(Dai et al., 2019; Yang et al., 2019; Shih et al., 2019), but differs in how it accurately depicts the spatial layout (i.e., the actual sequential order) of the inserted tokens in an insertion-based generation process.

Offset: Insertion-Oriented Relative Position Encoding   To illustrate our relative position encoding, considering the partial context (to be completed by further insertions) of *"I have pen"* with an insertion order of *"have pen I"*. To insert an *"a"* in between *"have"* and *"pen"*, the directed distance vector for token *"a"* against the rest of the context inserted so far should be [("have", -1), ("pen", +1), ("I", -2)], simplified as [-1, +1, -2]. This relative position encoding clearly defines where the insertion happens by only describing the pairwise spatial relationship between the incoming token and the existing context tokens. We can pack the relative position vectors for each insertion step to get a matrix that reflects the relative spatial relation along the trajectory of insertions, with each row corresponding to an insertion step. We name it the *offset* matrix.

As a concrete example, to generate the sentence *"I have a pen."* with an insertion order "⟨BOS⟩ ⟨EOS⟩ have pen I a .", the complete offset matrix is shown in Figure 2(c). The effective elements of this matrix are all in the lower triangular region, making the application of the computation sharing trick for the decoder transformers trivial. This reduces the number of context (re-)encoding steps from n in naive insertion-based models (Stern et al., 2019) to 1 during training.

Discussion: Comparisons With Other Positional Encoding Strategies   To illustrate how the proposed insertion-oriented relative position encoding is different from existing position encoding strategies, Figure 2 shows 2(a) the volatile, un-reusable absolute positions; 2(b) the traditional non-insertion-oriented relative positions; 2(c) the proposed offset matrix in the insertion order; and 2(d) the same offset matrix permuted to show the restored actual (partial-)sequence.   We can see that the absolute and the traditional relative positional encoding strategies are not applicable for efficient insertion-based generators. The former requires constant updates of the positional encoding of the existing tokens as the insertion progresses, disabling computation sharing. The latter requires knowledge about the final sequence length at the beginning of the insertion process, which is unrealistic and destroys the flexibility of insertion-based models. Our relative position encoding, on the other hand, reflects the order of the original sequence. Tokens that are on the left of the current one in the original sequence have a negative relative position to the current one while preserving the insertion order. As is illustrated in Figure 2(d), all the "later inserted tokens" are masked out and excluded from the previously inserted token's distance computation.

Efficient Computation of Offset Matrix   During training, given an *insertion order* to generate a sequence, we can pre-compute the offset matrix. However, naively constructing the offset matrix with element-wise operations takes $O(n^2)$ complexity for each sequence, limiting the training efficiency. Therefore we design an efficient algorithm to construct the offset matrix. Assume the *insertion order* is described in the form of absolute position *permutation indices* (i.e., in the previous example, [0, 6, 2, 4, 1, 3, 5]), we design a matrix algorithm called *offset compression* for our purpose. Figure 3 illustrates the algorithm with our exemplar sentence. Specifically, we first convert the absolute position vector into a matrix by duplication. Then, the upper triangular elements are masked by "infinity" to remove their impact in relative position computation because the inserting token should

Figure 3: Illustration of the offset compression algorithm. It efficiently transforms the insertion order/permutation indices to an offset matrix.

not attend to future to-be-inserted tokens. In the third step, each element is replaced by its in-row ranking *i.e.* its absolute position skipping the masked positions. In the final step, each row is baselined by the diagonal element to reflect that the relative position is between the last inserted token (the diagonal element) and previously inserted ones. The algorithm can be efficiently executed as a series of fast matrix operations.

An INSNET Layer   We hereby describe how to incorporate the offset matrix into each transformer layer in INSNET for efficient context encoding. In general, we inherit most designs from previous ones with relative position encoding (Dai et al., 2019; Yang et al., 2019). For layer number $i = 1...N$, given the output embedding $\mathbf{E}^{i-1}$ from the last layer and the offset matrix $\mathbf{R}$, the formulation of a transformer layer in an N-layer INSNET can be written as:

$$\mathbf{Q}^i, \mathbf{K}^i, \mathbf{V}^i, \mathbf{P}^i = \mathbf{W}_q^i \mathbf{E}^{i-1}, \mathbf{W}_{k,E}^i \mathbf{E}^{i-1}, \mathbf{W}_v^i \mathbf{E}^{i-1}, \mathbf{W}_{k,R}^i \mathbf{R}$$
$$\mathbf{A}^i = \mathbf{Q}^{i\top} \mathbf{K}^i + \mathbf{Q}^{i\top} \mathbf{P}^i + \mathbf{u}^{i\top} \mathbf{K}^i + \mathbf{v}^{i\top} \mathbf{P}^i$$
$$\mathbf{V}_{\text{reduced}}^i = \text{Masked-Softmax}(\mathbf{A}^i) \mathbf{V}^i$$
$$\mathbf{V}_{\text{skipconn}}^i = \mathbf{V}_{\text{reduced}}^i + \mathbf{E}^{i-1}$$
$$\mathbf{E}^i = \text{Feed-Forward}(\mathbf{V}_{\text{skipconn}}^i; \theta^i),$$

where $\mathbf{Q}^i, \mathbf{K}^i, \mathbf{V}^i, \mathbf{P}^i$ are query, key, value, position matrices, respectively, for layer i. $\mathbf{u}^i, \mathbf{v}^i, \mathbf{W}_q^i, \mathbf{W}_{k,E}^i, \mathbf{W}_v^i, \mathbf{W}_{k,R}^i$ and θ^i are learnable model parameters of each INSNET layer. We denote the input word embeddings as $\mathbf{E}^0$ for notation consistency. The last layer of transformer in INSNET outputs the step-wise context-aware token embeddings. They will be used to compute slot representations for the insertion steps.

3.2   Slot Representation and Insertion Prediction

With the context efficiently encoded, the subsequent step of an insertion-based generator is to predict the next position and token to insert. Thus, a representation for each potential insertion slot should be computed. We hereby show how slot representations can be *aggregated* from INSNET outputs and the potential challenges during this aggregation process.

A naive design of the slot representation is to simply concatenate the representation vectors from the left-neighbor and right-neighbor (in the natural observation order) of the slot as is done in prior works (Stern et al., 2019). This slot representation can efficiently compute the slot representation for all possible slots in parallel for each time step. However, the context encoding we obtained is insertion-order sensitive and unaware of the tokens inserted later in INSNET. This naive slot representation thus falls short of capturing the global sequence information. As a remedy, we propose to also include the last insertion token's representation to compose the slot representation $e_{i\downarrow j}^{(t)}$. Specifically, given the representations of the left-side neighbor $\boldsymbol{e}_{i-}$, the right-side neighbor $\boldsymbol{e}_{+j}$ and the last inserted token $\boldsymbol{e}_t$, the slot representation can be computed as:

$$\boldsymbol{e}_{i\downarrow j}^{(t)} = \text{LayerNorm}((f_l(\boldsymbol{e}_{i-}) \oplus f_r(\boldsymbol{e}_{+j})) + \boldsymbol{e}_t)$$

Figure 4: Illustration of how we generate the slot representations from INSNET transformer outputs.

where f_l and f_r are linear projections for left-point and right-point representation vectors and $\oplus$ stands for vector concatenation. Figure 4 illustrates the process and how the resulting representation changes in response to a new step.

The slot representation can then be converted into a probabilistic distribution over the vocabulary to predict the log-likelihood of inserted tokens using a log-linear transformation *i.e.* $\log p(x_{i\downarrow j}^{(t)}|\boldsymbol{e}_{i\downarrow j}^{(t)}) = $ log-softmax$(\mathbf{W}_p\boldsymbol{e}_{i\downarrow j}^{(t)} + \boldsymbol{b})_{x_{i\downarrow j}^{(t)}}$. To decide which slot to insert next, a position logit $\alpha_k^{(t)} = w_o^\top \boldsymbol{e}_{i_k\downarrow j_k}^{(t)}$ is computed for each slot k with a linear layer. Then a (log-)soft-max operation is applied on top of the position logits to obtain the log-probability to insert to each candidate slot. *i.e.* $\log o(x_{i_k\downarrow j_k}^{(t)}|\{\boldsymbol{e}_\downarrow^{(t)}\}) = $ log-softmax$([\alpha_0^{(t)}, \alpha_1^{(t)}, ...])_k$.

A binary classification head $q(0/1|\cdot)$ is applied to the last inserted token's representation $\boldsymbol{e}_t$ to decide the termination of the generation in each step. During training, only the final step $q(0/1|\boldsymbol{e}_{n-1})$ is trained to predict 1; all intermediate steps would be trained to predict 0. In the following section, we will continue to discuss how to formulate the final objective of our method using these step-wise distributions.

3.3 Adaptive Parallelization of Insertions

In addition to our efforts in better training efficiency, we also propose an algorithm to adaptively parallelize the generation process of INSNET to speed up the inference while preserving the generation quality. Precisely, the idea mimics the graph layerization process in the Dinic's algorithm (Dinitz, 2006). Assume that we partition the tokens into different *layers*, such that the tokens within the same layer are assumed to be *safe* to insert in parallel without corrupting the coherence of context. The algorithm aims to determine the partition such that the log-likelihood estimation of the resulting parallel insertion-based model is as close to the sequential insertion-based models as possible. The intuition is that the sequential insertion process maximally captures the inter-dependencies between the output tokens, but it is inefficient. By staying close to the sequential insertion-based model regarding likelihood prediction ability, we speed up the inference without severely sacrificing the likelihood estimation quality.

We initialize the layerization with a sequential insertion order, which is equivalent to single-node layerization, as is illustrated in Figure 5(a). Starting from this initialization, we perform INSNET-Dinic to gradually evolve this fully-sequential layerization into a non-autoregressive, parallelized layerization, as shown in Figure 5(b). We *promote* a token $x_\leftarrow$ from its respective slot (i^l, j^l) in layer l to (i^{l-1}, j^{l-1}) in the previous layer $l-1$ if two conditions are satisfied: 1) In layer $l-1$, slot (i^{l-1}, j^{l-1}) does not yet have an assigned insertion; 2) $\log p(x_\leftarrow|\boldsymbol{e}_{i^l\downarrow j^l}^{(l)}) - \log p(x_\leftarrow|\boldsymbol{e}_{i^{l-1}\downarrow j^{l-1}}^{(l-1)}) \leq \tau$.

(a) Initial Layerization   (b) Merged Layerization

Figure 5: (a) Initialized layerization of tokens after the pre-training stage. It assumes a fully sequential decoding process for now. (b) As the parallelization fine-tuning proceeds, the algorithm gradually merges different layers. Tokens within the same layer are safely parallelizable in decoding without sacrificing log-likelihood over the tolerance threshold τ.

(a) Yelp Review   (b) News

Figure 6: Illustration of the spectral study results in terms of BLEU-4/Sequential Ratio in decoding on Yelp Review and News dataset. Sequential Ratio is computed by $\frac{Avg.\#\,\text{Dec.Steps}}{Avg.\text{Length}}$

Here τ is a hyper-parameter that controls how much to parallel. Intuitively, larger τ usually indicates more tolerance for token likelihood loss caused by parallel decoding, *i.e.* more parallelization of insertion operations with tradeoffs on likelihood estimation accuracy. In practice, we find setting $\tau = 2.00$ effective enough for most machine translation tasks.

Note that the *promotion* of tokens only affects the slot representation computation and the insertion likelihood calculation of the respective insertion. When encoding the context (as is discussed in Section 3.1), we always serialize the layers and encode the context as if these insertion operations are performed sequentially.

For a target sequence $\boldsymbol{s}_{<n} = [x_0, x_1, ..., x_{n-1}]$, after the layerization algorithm, if token $x_{i\downarrow j}$ is layerized in the l-th layer and to be inserted in the slot (i, j), we denote it as $x^l_{i\downarrow j}$. Suppose we have m effective layers in total. Denote the corresponding representation for slot (i, j) given available context in layer l as $\boldsymbol{e}^{(l)}_{i\downarrow j}$ and the transformer's encoding of the partial context until the end of layer l as $\boldsymbol{e}^{(l)}_{-1}$. We denote the token likelihood, position likelihood and termination likelihood of the token $x^l_{i\downarrow j}$ to be $p(x^l_{i\downarrow j}|\boldsymbol{e}^{(l)}_{i\downarrow j})$, $o(x^l_{i\downarrow j}|\{\boldsymbol{e}^{(l)}_{\downarrow}\})$ and $q(0/1|\boldsymbol{e}^{(l)}_{-1})$, respectively. The general objective of INSNET parameterized by ϕ can be formulated as:

$$\mathcal{L}(\boldsymbol{s}, \phi) = -\sum_{l=0}^{m-1}\sum_{x^l_{i\downarrow j}}[\log p_\phi(x^l_{i\downarrow j}|\boldsymbol{e}^{(l)}_{i\downarrow j}) + \log o_\phi(x^l_{i\downarrow j}|\{\boldsymbol{e}^{(l)}_{\downarrow}\})] - \sum_{l=0}^{m}\log q_\phi(\mathbf{1}(l=m)|\boldsymbol{e}^{(l)}_{-1})$$

As is discussed in previous sections, to compute the objective function for each sequence, our formulation only requires one pass of transformer encoding computation.

4 Experiments

We demonstrate the efficiency, flexibility, and model capability of INSNET with two sets of experiments. 1) To show INSNET's performance and the flexibility to switch between sequential and parallel

Table 2: Performance comparison on Yelp Review and News datasets. For Levenshtein Transformer, insertion and deletion stages are both counted in # of decoding-time iterations. It's non-trivial to do unsupervised lexically constrained text generation with auto-regressive models. To work around this, we implemented a Plan-And-Write(Yao et al., 2019) style auto-regressive transformer-based model for better reference. Models with a star mark * are re-implemented by us. Other baseline results are directly taken from the original papers.

| Model | Yelp Review | | | News | | |
	BLEU-2/4	NIST-2/4	# Dec. Steps	BLEU-2/4	NIST-2/4	# Dec. Steps
Auto-regressive Transformer (Plan-And-Write-static, Yao et al. (2019))	16.68/5.46	2.79/2.86	39.24	8.79/2.40	1.65/1.67	36.74
NMSTG (Welleck et al., 2019)	10.06/1.92	1.11/1.12	27.92	10.67/1.58	2.70/2.70	27.85
InDIGO* (Gu et al., 2019a) (w/ Searched Adaptive Order)	16.14/4.63	3.08/3.10	45.63	13.89/3.62	3.08/3.10	26.78
Levenshtein Transformer (Parallel Decoding, (Gu et al., 2019b))	14.84/3.96	2.84/2.89	14.28	11.76/1.89	2.64/2.71	16.13
InsT-POINTER-Base (BERT init)	11.48/2.16	2.15/2.15	6.00	12.13/1.63	2.90/2.80	6.00
InsT-POINTER-Base (BERT init+Wiki)	15.63/3.32	3.27/3.30	6.00	13.01/2.51	3.04/3.06	6.00
InsT-POINTER-Large (BERT init+Wiki)	16.78/3.79	3.49/3.53	6.00	14.04/3.04	**3.28/3.30**	6.00
INSNET (Ours, Fully-Sequential)	**19.36/5.78**	**3.51/3.54**	48.73	**16.31/4.96**	3.10/3.13	32.69
INSNET-uniform (Ours)	12.31/2.30	2.19/2.17	7.00	12.89/2.01	2.99/2.90	7.00
INSNET-Dinic (Ours, $\tau = 10.0$)	16.73/4.35	3.19/3.20	11.83	14.13/3.75	2.97/3.00	8.13

decoding on datasets with high inter-token dependency (i.e., less suitable for parallel decoding). We follow the setup in Zhang et al. (2020) and address the unsupervised lexically constrained text generation problem on two datasets Yelp Review and News. 2) To further verify the effectiveness of INSNET-Dinic, we evaluate INSNET as a (partially) non-autoregressive machine translation model with parallel decoding on three classical datasets: WMT Ro-En, WMT En-De and WAT En-Ja.

The general setup about how hyper-parameters are determined can be found in appendixA.

4.1 Sequential-Parallel Trade-off

Experimental Setup Yelp Review dataset consists of 160K training sequences, 10K sequences for validation and 1k test sequences. News dataset consists of 268586 sentences in total, of which 10k are randomly selected as validation set, 1k for testing. YAKE [2] is performed to the test split of each dataset to extract lexical constraints.

We vary the hyperparameter τ in the range of $\{10.0, 3.0, 1.0, 0.3, -\infty(\text{fully-sequential})\}$ and collect the results on both datasets. For position prediction, we are inserting into slots with positions lying in the top 70% of the position distribution mass. For token prediction, we are doing top-$\{1, 1, 3, 3, 5\}$ sampling over the vocabulary distribution. The results are shown in Table 2, Figure 6(a) and 6(b)

Discussion 1) INSNET is able to significantly outperform most previous works on the quality-latency trade-off spectrum. With more sequential flavor (*i.e.* smaller τ), it is generally to achieve the new state-of-the-art in generation quality. Compared to a Plan-And-Write style autoregressive baseline, INSNET guarantees the perfect incorporation of keywords due to its insertion-based nature. Also, its improved performance is consistent on both datasets. 2) When setting τ larger to encourage more parallelization of decoding, INSNET is mostly able to parallelize the insertions with good preservation of the generative quality. Compared to the vanilla uniformly-parallel setup (INSNET-uniform), INSNET-Dinic significantly improved the effectiveness of parallel decoding.

4.2 Non-autoregressive Machine Translation

We train INSNET-Dinic models with $\tau = 2.00$ for extended investigation of the performance on machine learning problems. The results in Table 3 show that, INSNET-Dinic is able to achieve comparable or even better performance compared to previous state-of-the-art non-autoregressive (insertion-based) machine translation models in terms of generation quality and latency.

---

[2]https://github.com/LIAAD/yake

Table 3: Machine translation evaluation. Each generation iteration of Levenshtein Transformer requires at least two full executions of the transformer model. Results with a star mark * are collected from our re-implementation. Other baseline results are directly taken from the original papers. The results for a vanilla transformer is taken from the LevT paper (Gu et al., 2019b).

Model	Ro-En	En-De	En-Ja	#Dec Step.	Latency
InDIGO-SAO Gu et al.	32.47	26.14*	40.87*	n	516ms
InDIGO-random Gu et al.	20.20	17.48*	23.91*	n	502ms
InsT-uniform Stern et al.	28.52	26.72	41.89*	$\Theta(\log n) \leq 10$	107ms
InsT-binary ($\tau = 0.5$) Stern et al.	30.66	27.41	42.17*	$\Theta(\log n) \leq 10$	92ms
LevT Gu et al.	33.26	27.27	42.36	$\Theta(\log n) \leq 2 \times 10$	116ms
Vanilla Transformer	32.30	27.17	43.68	n	389ms
INSNET-uniform	29.13	26.45	41.67	$\Theta(\log n) \leq 10$	92ms
INSNET-Dinic (Ours, $\tau = 2.00$)	33.41	27.36	43.71	$\Theta(\log n) \approx 15.8$	105ms
+ KD	**33.91**	**28.05**	**44.10**	$\Theta(\log n) \approx 16.1$	103ms

Table 4: Empirical & theoretical comparative study of different algorithms' training efficiency. # of Steps/Seq means during training how many time the transformer needs to be executed per sequence.

Model	T_{train}/Epoch	# of Steps/Seq
Auto-regressive	35min48s	1
InDIGO-SAO	58min36s + 2h12min(SAO)	$1 + O(n)$
Insertion Transformer-Sequential	26h31min	$O(n)$
Levenshtein Transformer-Sequential	37h24min	$O(n)$
Insertion Transformer	8h24min	$\Theta(\log n)$
Levenshtein Transformer	16h33min	$\Theta(\log n)$
InsT-POINTER	9h36min	$\Theta(\log n)$
INSNET/INSNET-Dinic	1h12min	1

4.3 Training Time Analysis

To show the training efficiency of the proposed model, we hereby do an empirical and theoretical analysis on the candidate models' training procedure. See Table 4. For empirical results, the statistics are collected on the Yelp Review unsupervised lexically constrained text generation problem. All results are collected on a single NVIDIA RTX3090 GPU. The transformer Seq2seq baseline is trained as a Plan-And-Write model. POINTER's training time per epoch is calculated with the official implementation with mixed precision supported by the NVIDIA APEX library [3].

Discussion The results in Table 4 confirm the significant improvement in training efficiency of INSNET over most previous baselines. In addition, this concretely shows that it is not practically affordable to obtain a sequential insertion-based generator directly with InsT/LevT. Note that SAO of InDIGO is an offline, inference-only algorithm that does not require any computation of gradients. Thus its constant factor is significantly smaller than other $O(n)$ gradient-propagating procedures. According to its original paper and our previous experiments, InDIGO practically needs this process to achieve reasonable performance.

5 Conclusion & Future Work

We propose INSNET, an efficient, flexible and performant insertion-based generator that supports sequential and parallel decoding. INSNET provides a controllable and smooth trade-off between the two paradigms, allowing it to best adapt to different application scenarios. Experiments on two unsupervised lexically constrained text generation datasets and three machine translation datasets show the advantages of INSNET over previous methods.

As for future work, it is interesting to explore obtaining a large-scale pre-trained version of INSNET for further fine-tuning under different downstream scenarios, expecting such insertion-based models can better generalize on compositionally or recursively varied samples.

---

[3]https://github.com/dreasysnail/POINTER

References

Dzmitry Bahdanau, Kyung Hyun Cho, and Yoshua Bengio. 2015. Neural machine translation by jointly learning to align and translate. 3rd International Conference on Learning Representations, ICLR 2015 ; Conference date: 07-05-2015 Through 09-05-2015.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*.

Zihang Dai, Zhilin Yang, Yiming Yang, Jaime Carbonell, Quoc Le, and Ruslan Salakhutdinov. 2019. Transformer-XL: Attentive language models beyond a fixed-length context. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 2978–2988, Florence, Italy. Association for Computational Linguistics.

Yefim Dinitz. 2006. Dinitz'algorithm: The original version and even's version. In *Theoretical computer science*, pages 218–240. Springer.

Jiatao Gu, Qi Liu, and Kyunghyun Cho. 2019a. Insertion-based decoding with automatically inferred generation order. *Transactions of the Association for Computational Linguistics*, 7:661–676.

Jiatao Gu, Changhan Wang, and Jake Zhao. 2019b. Levenshtein transformer. *arXiv preprint arXiv:1905.11006*.

Christian F Hempelmann. 2008. Computational humor: Beyond the pun? *The Primer of Humor Research. Humor Research*, 8:333–360.

Jiwei Li, Will Monroe, Tianlin Shi, Sébastien Jean, Alan Ritter, and Dan Jurafsky. 2017a. Adversarial learning for neural dialogue generation. *arXiv preprint arXiv:1701.06547*.

Xiujun Li, Yun-Nung Chen, Lihong Li, Jianfeng Gao, and Asli Celikyilmaz. 2017b. End-to-end task-completion neural dialogue systems. *arXiv preprint arXiv:1703.01008*.

Yinhan Liu, Jiatao Gu, Naman Goyal, Xian Li, Sergey Edunov, Marjan Ghazvininejad, Mike Lewis, and Luke Zettlemoyer. 2020. Multilingual denoising pre-training for neural machine translation. *Transactions of the Association for Computational Linguistics*, 8:726–742.

Hisar Manurung, Graeme Ritchie, and Henry Thompson. 2000. Towards a computational model of poetry generation. Technical report, The University of Edinburgh.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. 2019. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32:8026–8037.

Alec Radford, Karthik Narasimhan, Tim Salimans, and Ilya Sutskever. 2018. Improving language understanding by generative pre-training.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. 2019. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9.

Peter Shaw, Jakob Uszkoreit, and Ashish Vaswani. 2018. Self-attention with relative position representations. *arXiv preprint arXiv:1803.02155*.

Yong-Siang Shih, Wei-Cheng Chang, and Yiming Yang. 2019. Xl-editor: Post-editing sentences with xlnet. *arXiv preprint arXiv:1910.10479*.

Mitchell Stern, William Chan, Jamie Kiros, and Jakob Uszkoreit. 2019. Insertion transformer: Flexible sequence generation via insertion operations. In *International Conference on Machine Learning*, pages 5976–5985. PMLR.

Bowen Tan, Zichao Yang, Maruan AI-Shedivat, Eric P Xing, and Zhiting Hu. 2020. Progressive generation of long text. *arXiv preprint arXiv:2006.15720*.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Lukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. In *NIPS*.

Oriol Vinyals, Alexander Toshev, Samy Bengio, and Dumitru Erhan. 2015. Show and tell: A neural image caption generator. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3156–3164.

Sean Welleck, Kianté Brantley, Hal Daumé Iii, and Kyunghyun Cho. 2019. Non-monotonic sequential text generation. In *International Conference on Machine Learning*, pages 6716–6726. PMLR.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander M. Rush. 2020. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 38–45, Online. Association for Computational Linguistics.

Kelvin Xu, Jimmy Ba, Ryan Kiros, Kyunghyun Cho, Aaron Courville, Ruslan Salakhudinov, Rich Zemel, and Yoshua Bengio. 2015. Show, attend and tell: Neural image caption generation with visual attention. In *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pages 2048–2057, Lille, France. PMLR.

Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Ruslan Salakhutdinov, and Quoc V Le. 2019. Xlnet: Generalized autoregressive pretraining for language understanding. *arXiv preprint arXiv:1906.08237*.

Lili Yao, Nanyun Peng, Ralph Weischedel, Kevin Knight, Dongyan Zhao, and Rui Yan. 2019. Plan-and-write: Towards better automatic storytelling. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 7378–7385.

Yizhe Zhang, Guoyin Wang, Chunyuan Li, Zhe Gan, Chris Brockett, and Bill Dolan. 2020. Pointer: Constrained text generation via insertion-based generative pre-training. *arXiv preprint arXiv:2005.00558*.

A Appendix

A.1 General Setup of Experiments

For all language generation tasks, based on whether the data is pre-processed upon release or not, either a BPE-based or a classical tokenizer is applied. Each of the evaluated transformer models, if not otherwise stated, is implemented as a *base*-sized transformer model, which has 12-layers with 12 attention head and 768 hidden dimensions. The batch size is set to 256. In cases where the model size exceeds the device capacity, the cumulative gradient trick is applied to support an equivalent optimization effect. The learning rate is selected from {5e-5, 1e-4, 2e-4}. The dropout rate is selected from {0.1, 0.2}. The weight decay rate is set to 0.02. All the models are trained with 1000 warm-up iterations and a maximum of 200000 iterations of training. A linear-decay learning rate scheduler is applied for fine-grained training of the model. If presented with a development set, the training will be early-stopped when the model stops improving for 5 consecutive epochs. For INSNET-Dinic, unless otherwise stated, the parallelization fine-tuning lasts for 5 epochs typically.

Models are implemented based on libraries like PyTorch(Paszke et al., 2019) (for the general construction of deep learning models, License: BSD) and huggingface's Transformers(Wolf et al., 2020) (for specific implementation of transformer-based models, License: Apache-2.0). Some of our baselines also used NVIDIA APEX for efficient mix-precision training [4]. We thank them for their contributions to the community. With the best of our effort we use datasets that contain either user-identity agnostic contents or those that could contain publicly reported information about famous, well-known individuals (for the News dataset).

All results that could contain randomness, if not otherwise stated, is collected from averaging the results of 3 individual runs of sampling. The variances of the results won't affect/reverse the conclusion.

A.2 Ablation Study on the Effectiveness of Components

Although different modules of InsNet are closely entangled with each other and thus hard to be ablated into some inferior variants, we hereby conduct an ablation study to show that:

- The proposed offset matrix is indeed a more powerful insertion-oriented position encoding with significantly better capacity. We show that this in particular helps the model learn to terminate the sequence in correct/better timings. To study this, we truncate the offset matrix to range $[-1.0, 1.0]$ (InsNet-truncated) so that it is somehow similar to that of InDIGO.

- The introduction of the current-step, global representation when computing the slot representation is necessary. It also in general helps to improve the sequence termination performance, and leads to (however slower) convergence to better local optimals. We report the results from an ablated version of InsNet without it (InsNet-noglobal).

Due to the limited time in the rebuttal period, we are only able to collect some primitive results on the yelp review dataset. Most hyperparameters of the three models are kept the same. The results are as follows.

For quantitative results, we report the termination NLL (see Sec 3.3) of each model. We also show some randomly picked samples that shows the performance instability of ablated variants.

	InsNet	InsNet-truncated	InsNet-noglobal
Terminating NLL $\downarrow$	**2.17**	2.97	2.56
BLEU-2/4 $\uparrow$	**19.17/5.69**	16.13/3.89	17.83/4.81

---

[4]https://github.com/NVIDIA/apex

Table 5: Ablated versions of the model fails to terminate the sequence at reasonable timings, leading to wordy/unreadable outputs in some cases. This is even more severe for samples from earlier checkpoints during the training.

InsNet	intriguing meals and traditional . fun atmosphere . great prices . great service .
InsNet-truncated	... very intriguing . great service , great staff , and the whole meals are amazing . i love the place . love the food here here . ... (**non-terminating**)
InsNet-noglobal	very intriguing meals . great atmosphere . and service was great . food was amazing . service was delicious . traditional italian cuisine , very fun . atmosphere is great . prices are good and very reasonable . ! .
InsNet	i have been here several times . great atmosphere and the service is always great . love the food , and the best steak salad . it is fantastic !
InsNet-truncated	i ve been coming here multiple times in years now . great food , good food and delicious . also , the service . great atmosphere and atmosphere . service and food was great . great experience here . love food and salad , and the staff is very friendly ! . ! .
InsNet-noglobal	... everything is very delicious . the whole menu was awesome , especially . we could have ever eaten since we found this place . we have had everything on the food , kids menu , , and large portions and food , great service . great place is awesome . great service , clean , fresh , tasty , tasty , hot , , , good food , service , ... (**non-terminating**)
InsNet	this place has been a long time to take out of my favorite spot . service is friendly and fast , the food here are excellent . fantastic sandwiches . this is my favorite spot.
InsNet-truncated	... we love it here , and it s always so delicious . the service is amazing . the owner owner is always nice and has been super friendly service , and one of my favorite lunch spot . the food is always fantastic . oh and delicious . and there is the best value . the food is so fresh and the sandwiches are great . is my favorite . , it is fantastic . i .. ... (**non-terminating**)
InsNet-noglobal	delicious food and service . great customer service and food . good food , clean atmosphere . nice staff . good breakfast . great service , fresh food and atmosphere . will come here everyday ! .