SHAPLEY EXPLANATION NETWORKS

ABSTRACT

Shapley values have become one of the most popular feature attribution explanation methods. However, most prior work has focused on post-hoc Shapley explanations, which can be computationally demanding (exponential time complexity) and preclude model regularization based on Shapley explanations during training. Thus, we propose to incorporate Shapley values themselves as latent representations in deep models—thereby making Shapley explanations first-class citizens in the modeling paradigm. This intrinsic explanation approach enables layer-wise explanations, explanation regularization of the model during training, and fast explanation computation at test time. We define the *Shapley transform* that transforms the input into a *Shapley representation* given a specific function. We operationalize the Shapley transform as a neural network module and construct both shallow and deep networks, called SHAPNETs, by composing Shapley modules. We prove that our Shallow SHAPNETs compute the exact Shapley values and our Deep SHAPNETs maintain the missingness and accuracy properties of Shapley values. We demonstrate on synthetic and real-world datasets that our SHAPNETs enable layer-wise Shapley explanations, novel Shapley regularizations during training, and fast computation while maintaining reasonable classification accuracy.

1 INTRODUCTION

Explaining the predictions of machine learning models has become increasingly important for many crucial applications such as healthcare, recidivism prediction, or loan assessment. Explanations based on feature importance are one key approach to explaining a model prediction. More specifically, additive feature importance explanations have become popular, and in Lundberg & Lee (2017), the authors argue for theoretically-grounded additive explanation method called SHAP based on Shapley values—a way to assign credit to members of a group developed in cooperative game theory (Shapley, 1953). Lundberg & Lee (2017) defined three intuitive theoretical properties called local accuracy, missingness, and consistency, and proved that only SHAP explanations satisfy all three properties.

Despite these elegant theoretically-grounded properties, exact Shapley value computation has exponential time complexity in the general case. To alleviate the computational issue, several methods have been proposed to approximate Shapley values via sampling (Strumbelj & Kononenko, 2010) and weighted regression (Kernel SHAP), a modified backpropagation step (Deep SHAP) (Lundberg & Lee, 2017), utilization of the expectation of summations (Ancona et al., 2019), or making assumptions on underlying data structures (Chen et al., 2019). To avoid approximation, the model class could be restricted to allow for simpler computation. Along this line, Lundberg et al. (2020) propose a method for computing exact Shapley values for tree-based models such as random forests or gradient boosted trees. However, even if this drawback is overcome, prior Shapley work has focused on *post-hoc* explanations, and thus, the explanation approach cannot aid in model design or training.

On the other hand, Generalized Additive Models (GAM) as explored in Lou et al. (2012; 2013); Caruana et al. (2015) (via tree boosting) and Wang et al. (2018) (via neural networks) can be seen as interpretable model class that exposes the exact Shapley explanation directly. In particular, the output of a GAM model is simply the summation of interaction-free functions: $f_{\text{GAM}}(\boldsymbol{x}) = \sum_s f_s(x_s)$, where $f_s(\cdot)$ are univariate functions that can be arbitrarily complex. Interestingly, the Shapley explanation values, often denoted $\phi_s(\boldsymbol{x}, f)$, for a GAM are exactly the values of the independent function, i.e., $\forall s, \phi_s(\boldsymbol{x}, f_{\text{GAM}}) = f_s(x_s)$. Hence, the prediction and the corresponding exact SHAP explanation can be computed simultaneously for GAM models. However, GAM models are inherently limited in their representational power, particularly for perceptual data such as images in which deep

Figure 1: Shapley representation of two-dimensional functions. Such representation can span beyond one dimensional manifold and depends on both the inner function and the reference values. In both groups, the gray-scale background indicates the respective function value while the rainbow-scale color indicates correspondence between input (left) and Shapley representation (right) along with function values—red means highest and purple means lowest function values. The red cross in the input plots represents the reference values for both inputs. More details in subsection 2.1.

networks are state-of-the-art. Thus, prior work is either post-hoc (which precludes leveraging the method during training) or limited in its representational power (e.g., GAMs).

To overcome these drawbacks, we propose to incorporate Shapley values themselves as learned latent representations (as opposed to post-hoc) in deep models—thereby making Shapley explanations first-class citizens in the modeling paradigm. Intuitive illustrations of such representation are provided in Fig. 1 and detailed discussion in subsection 2.1. We summarize our core contributions as follows:

- We formally define the *Shapley transform* and prove a simple but useful linearity property for constructing networks. We also develop important extensions of the base case to enhance the representational power of the transform.

- We develop a novel network architecture SHAPNET, which include Shallow and Deep SHAPNET, that intrinsically provides layer-wise explanations (i.e., explanations at every layer of the network) in the same forward pass as the prediction.

- We prove that a Shallow SHAPNET explanations are the *exact* Shapley values—thus satisfying all three SHAP properties—and prove that Deep SHAPNET explanations maintain the missingness and local accuracy properties.

- We propose a novel *explanation regularization* on Shapley values of the model during training enabled by the fact that the explanation is a latent representation in our model.

- We demonstrate empirically that our SHAPNETs can provide new capabilities such as layer-wise explanations and novel explanation regularizations based on Shapley values while maintaining comparable performance to other deep models. We also show that our method compares favorably with Shapley-based post-hoc explanation methods.

Dedicated Related Works Section We present related works that motivated our work above and in the text where appropriate. Due to space limit, for dedicated literature review, we refer to Appendix C.

2 SHAPLEY EXPLANATION NETWORKS

Background We give a short introduction to SHAP explanations and their properties as originally introduced in Lundberg & Lee (2017). Given a model $v : \mathbb{R}^d \mapsto \mathbb{R}$ that is not inherently interpretable (e.g., neural nets), additive feature-attribution methods form a linear approximation of the function over simplified binary inputs, denoted $z \in \{0, 1\}^d$, indicating the "presence" and "absence" of each feature, respectively: i.e., a local linear approximation $u(z) = a_0 + \sum_{i=1}^{d} a_i z_i$. While there are different ways to model "absence" and "presence", in this work, we take a simplified viewpoint: "presence" means that we keep the original value whereas "absence" means we replace the original value with a reference value, which has been validated in Sundararajan & Najmi (2020) as Baseline Shapley. If we denote the reference vector for all features by r, then we can define a simple mapping function between z and x as $\Psi_{x,r}(z) = z \odot x + (1 - z) \odot r$, where $\odot$ denotes element-wise product (eg, $\Psi_{x,r}([0, 1, 0, 1, 1]) = [r_1, x_2, r_3, x_4, x_5]$). A simple generalization is to group certain features together and consider including or removing all features in the group. Lundberg & Lee (2017) propose three properties that additive feature attribution methods should intuitively satisfy.

The first property called *local accuracy* states that the approximate model u at $\boldsymbol{z} = \boldsymbol{1}$ should match the output of the model v at the corresponding $\boldsymbol{x}$, i.e., $v(\boldsymbol{x}) = u(\boldsymbol{1}) = \sum_{i=0}^{d} a_i$. The second property called *missingness* formalizes the idea that features that are "missing" from the input $\boldsymbol{x}$ (or correspondingly the zeros in $\boldsymbol{z}$) should have zero attributed effect on the output of the approximation, i.e., $z_i = 0 \Rightarrow a_i = 0$. Finally, the third property called *consistency* formalizes the idea that if one model always sees a larger effect when removing a feature, the attribution value should be larger (see (Lundberg & Lee, 2017) for full definition).

Definition 1 (SHAP Values (Lundberg & Lee, 2017)). *SHAP values are defined as:*

$$\phi_i(v, \boldsymbol{x}) \triangleq \sum_{\tilde{\boldsymbol{z}} \subseteq \boldsymbol{z} \setminus i} \frac{|\tilde{\boldsymbol{z}}|! \, (d - |\tilde{\boldsymbol{z}}| - 1)!}{d!} \left[v \circ \Psi_{\boldsymbol{x}, \boldsymbol{r}} \left(\tilde{\boldsymbol{z}} \cup \{i\} \right) - v \circ \Psi_{\boldsymbol{x}, \boldsymbol{r}} \left(\tilde{\boldsymbol{z}} \right) \right], \tag{1}$$

where $|\tilde{\boldsymbol{z}}|$ is the number of non-zero entries, $\boldsymbol{z} \setminus i$ means $\boldsymbol{z}_j = 1$ for all $j \neq i$ and $\boldsymbol{z}_i = 0$, $\tilde{\boldsymbol{z}} \subseteq \boldsymbol{z} \setminus i$ represents all $\tilde{\boldsymbol{z}}$ whose non-zeros are subsets of the non-zero entries of $\boldsymbol{z} \setminus i$.

2.1 SHAPLEY TRANSFORM AND SHAPLEY REPRESENTATION

For the sake of generality, we will define the Shapley transform in terms of tensors (or multi-dimensional arrays). However, we first make a distinction between tensor dimensions that need to be explained and other tensor dimensions. For example, in image classification, usually an explanation (or attribution) value is required for each pixel (i.e., the spatial dimensions) but all channels are grouped together (i.e., an attribution is provided for each pixel but not for each channel of each pixel). We generalize this idea in the following definition of explainable and channel dimensions.

Definition 2 (Explainable Dimensions and Channel Dimensions). *Given a tensor representation $\boldsymbol{x} \in \mathbb{R}^{D \times C} \equiv \mathbb{R}^{(d_1 \times d_2 \times \cdots) \times (c_1 \times c_2 \times \cdots)}$, the tensor dimensions $D \equiv d_1 \times d_2 \times \cdots$ that require attribution will be called* explainable dimensions *and the other tensor dimensions $C \equiv c_1 \times c_2 \times \cdots$ will be called the* channel dimensions.

As a simplest example, if the input is a vector $\boldsymbol{x} \in \mathbb{R}^{d \times 1}$, then $D = d$ and $C = 1$, i.e., we have one (since $C = 1$) importance value assigned to each features. For images in the space $\mathbb{R}^{h \times w \times c}$ where h, w denote the height and width, respectively, the explainable dimensions correspond to the spatial dimensions (i.e., $D = h \times w$) and the channel dimensions correspond to the single channel dimension (i.e., $C = c$). While the previous examples discuss tensor dimensions of the input, our Shapley transforms can also operate on latent representations. For example, our latent representations for image models could be in the space $\mathbb{R}^{w \times h \times c_1 \times c_2}$, where the explainable dimensions correspond to spatial dimensions (i.e., $D = h \times w$) but there are two channel dimensions (i.e., $C = c_1 \times c_2$). Given this distinction between explainable and channel dimensions, we can now define the Shapley transform and Shapley representation.

Definition 3 (Shapley Transform). *Given an arbitrary function $f \in \mathcal{F}: \mathbb{R}^{D \times C} \mapsto \mathbb{R}^{C'}$ where $C' \triangleq c_1' \times c_2' \times \cdots$, the* Shapley transform *$\Omega: \mathbb{R}^{D \times C} \times \mathcal{F} \mapsto \mathbb{R}^{D \times C'}$ is defined as:*

$$[\Omega(\boldsymbol{x}, f)]_{i,j} = \phi_i(\boldsymbol{x}, f_j), \quad \forall i \in \mathcal{I}_D, j \in \mathcal{I}_{C'}, \tag{2}$$

where $\mathcal{I}_D$ denotes the set of all possible indices for values captured by the explainable dimensions D (and similarly for $\mathcal{I}_{C'}$) and f_j denotes the scalar function corresponding to the j-th output of f.

Definition 4 (Shapley Representation). *Given a function $f \in \mathcal{F}$ as in Def. 3 and a tensor $\boldsymbol{x} \in \mathbb{R}^{D \times C}$, we simply define the* Shapley representation *to be: $Z \triangleq \Omega(\boldsymbol{x}, f) \in \mathbb{R}^{D \times C'}$.*

Notice that in the Shapley transform, we always keep the explainable dimensions D unchanged. However, the channel dimensions of the output representation space, i.e., C', is determined by the co-domain of the function f. For example, if f is a scalar function (i.e., $C' = 1$), then the attribution for the explainable dimensions is a scalar. However, if f is a vector-valued function (i.e., $C' = c_1$), then the attribution is a *vector* (corresponding to the vector output of f). A multi-class classifier is a simple example of an f that is a vector-valued function. In summary, the Shapley transform maintains the explainable tensor dimensions, but each explainable element of D may be associated to a tensor of attribution values corresponding to each output of f.

We now present a simple but useful property of Shapley transforms (proof in Appendix A). Without loss of generality, we can assume that the explainable dimensions and the channel dimensions have been factorized so that $D = d_1 d_2 d_3 \cdots$ and $C = c_1 c_2 c_3 \cdots$ in the following lemma.

Figure 2: An example construction of SHAPNETs: we construct SHAPNET from simple Shapley modules (left) which explicitly compute the SHAP explanation values for the arbitrary function f. Shallow SHAPNET are based on computing many Shapley modules in parallel—in particular, we show computing all pairs of features. Deep SHAPNET are composed of Shallow SHAPNET blocks where the output explanation of the previous layer is used as input for the next layer. We show an example using disjoint subsets for each Shallow SHAPNET layer and then using a butterfly permutation as in the Fast Fourier Transform (FFT) algorithm to enable complex dependencies. The edge weights shown here are direct result of Eqn. 1 with $d = 2$.

Lemma 5 (Linear transformations of Shapley transforms are Shapley transforms). *The linear transform, denoted by a matrix $A \in \mathbb{R}^{C' \times C}$, of a Shapley representation, $Z \triangleq \Omega(\boldsymbol{x}, f) \in \mathbb{R}^{D \times C}$, is itself a Shapley transform for modified functions $\tilde{f}$, i.e.,*

$$AZ^T \equiv A \left(\Omega(\boldsymbol{x}, f) \right)^T = \left(\Omega(\boldsymbol{x}, \tilde{f}) \right)^T \quad \text{where } \tilde{f}_k(\boldsymbol{x}) = \mathbf{a}_k^T f(\boldsymbol{x}), \tag{3}$$

where $\mathbf{a}_k \in \mathbb{R}^C$ is the k-th column of A, and $\tilde{f}_k(\boldsymbol{x})$ is the corresponding k-th value of the output (see j for f_j in Def. 3) of the modified function.

Remark 6 (Alignment of channel dimensions and number of classes). By the local accuracy property and our construction, the output of the model is simply the summation of the Shapley values. This is natural if the output of a model is a scalar (e.g., binary classification). To make it work with multi-class models, we can force the dimensionality of the co-domain, C', of a function f to be able to decompose as $C' = c'_1 \times c'_2 \times c'_3 \times \cdots$, where c'_1 is the number of classes, and for the sake of simplicity, we will use c as the number of output classes henceforth. We perform summation for the dimensions captured by $c_2 \times c_3 \times \cdots$ to obtain the logit for each class. In this formulation, we can have attribution values for each class assigned to each element in $\mathbb{R}^D$.

Note that the summation operation described above, denoted by $\text{sum}^{[-1]} \colon \mathbb{R}^{m \times C'} \mapsto \mathbb{R}^{n \times \mathbb{R}^c}$ where n can be any positive integer, is a simple linear transformation so we can use it to create various simplified Shapley transforms via Lemma 5.

2.2 SHALLOW SHAPNET

We now concretely instantiate our SHAPNETs by presenting our Shallow SHAPNET and its accompanying Theorem 8 which is an extension of Lemma 5 with complete proof in Appendix A.

Definition 7 (Shallow SHAPNET). *A Shallow SHAPNET $\mathcal{G} \colon \mathbb{R}^D \mapsto \mathbb{R}^c$ is defined as*

$$\mathcal{G}(\boldsymbol{x}) = \text{sum}^{[D]} \circ g = \text{sum}^{[D]} \circ \text{sum}^{[-1]} \circ \Omega(\boldsymbol{x}, f), \tag{4}$$

where $\text{sum}^{[D]}$ denotes the summation over explainable dimensions D, which satisfies local accuracy, and $g(\boldsymbol{x}, f) \triangleq \text{sum}^{[-1]} \circ \Omega(\boldsymbol{x}, f) \in \mathbb{R}^{c \times D}$ is the Shallow SHAPNET explanation.

Theorem 8. *Shallow SHAPNETs compute the exact Shapley values, i.e., $g_{i,j}(\boldsymbol{x}; f) = \phi_i(\mathcal{G}_j, \boldsymbol{x})$.*

Remark 9 (Sparsity in active sets curbs computation). The bottleneck of computing Shapley values is the exponential complexity in the number of input features that renders large-scale computing of Shapley values infeasible. To alleviate such issue, we would like to promote sparsity in the computation. Consider a function f depending on a subset of input features, (e.g. $f_j(x_1, x_2, x_3) = 5x_2 + x_3$ only depends on x_2 and x_3), we will refer to such a subset *active set*, $\mathcal{A}(f)$ ($\mathcal{A}(f_j) =$

$\{x_2, x_3\}$ and for the example above). In principle, we would like to keep the cardinality of the active set low: $|\mathcal{A}(f_j)| \ll d$ for $j \in \mathcal{I}_{C'}$, s.t. we can limit the computational overhead, as features in the complementary set of $\mathcal{A}(f_j)$ will be trivially assigned Shapley values of 0's.

To enforce the sparsity as discussed in Remark 9, we propose a simple but novel wrapper around an arbitrarily complex function f_j derived from f called a *Shapley module F* that explicitly computes the Shapley values locally but only for the active set of inputs. One of the examples is in Fig. 2.

Definition 10 (Shapley Module). *Given an arbitrarily complex function $f \colon \mathbb{R}^{D \times C} \mapsto \mathbb{R}^{C'}$ parameterized by a neural network, from which we can derive $f_j \colon \mathbb{R}^{D \times C} \mapsto \mathbb{R}$ where $j \in \mathcal{I}_{C'}$, and a reference vector $\boldsymbol{r} \in \mathbb{R}^{D \times C}$, a Shapley module $F \colon \mathbb{R}^{D \times C} \mapsto \mathbb{R}^{D \times 1}$ is defined as: $F(\boldsymbol{x} \mid f_j, \boldsymbol{r}) \triangleq [\phi_1(f_j, \boldsymbol{x}), \ldots, \phi_d(f_j, \boldsymbol{x})]^T$, where $\phi_i(f_j, \boldsymbol{x}) = 0$ if $x_i \notin \mathcal{A}(f_j)$.*

We apply Shapley Modules inside Shallow SHAPNETs, and as shown in subsection 2.3 Deep SHAPNETs to make our model scalable and efficient. Notice that this is similar in spirit with L-Shapley in Chen et al. (2019), though L-Shapley computes local Shapley values based on the Markov assumption on data while we build such locally computed Shapley values directly into the model.

2.3 DEEP SHAPNET

While Shallow SHAPNET is quite powerful, it does not enable inter-layer Shapley representations within a deep model. To enable this, we construct deep SHAPNETs by cascading the output of Shallow SHAPNETs from Def. 7 with different co-domain $\mathbb{R}^{C'}$ of different underlying functions in different stages except the last co-domain which has to align with the desired output space per Remark 6. Note that effectively the Shapley representation Z in Def. 4 from a Shallow SHAPNET can be seen as input $\boldsymbol{x}$ to the next Shallow SHAPNET, making it possible to cascade the representations.

Definition 11 (Deep SHAPNET). *A Deep SHAPNET $\mathcal{H}$ is a cascade of pre-summation Shallow SHAPNETs:*

$$\mathcal{H} = \text{sum}^{[D]} \circ h = \text{sum}^{[D]} \circ \text{sum}^{[-1]} \circ \Omega^{(L)} \circ \Omega^{(L-1)} \cdots \circ \Omega^{(2)} \circ \Omega^{(1)}, \qquad (5)$$

where $h(\boldsymbol{x}) \in \mathbb{R}^{D \times c}$ is the Deep SHAPNET explanation, $\Omega^{(l)}$ is the l-th Shapley transform with its own underlying function $f^{(l)}$, and all the reference values are set to 0 except for the first Shapley transform Ω (whose reference values will depend on the application).

To ground our Deep SHAPNETs, we present the following theoretical properties about the explanations of Deep SHAPNETs (proof in Appendix B).

Theorem 12. *The Deep SHAPNET explanation $h(\boldsymbol{x})$ defined in Def. 11 provides an explanation that satisfies both local accuracy and missingness with respect to $\mathcal{H}$.*

Deep SHAPNET with Disjoint Pairs and Butterfly Connections It is immediately obvious that the computational graph determined by the choice of active sets in Shapley Modules dictates how the features interact with each other in a in Shallow SHAPNETs and hence a Deep SHAPNET. For our experiments, we focus on one particular construction of a Deep SHAPNET based on disjoint pairs (active sets of Shapley modules do not overlap: $\cap_{j=1}^c \mathcal{A}(f_j) = \emptyset$) in each layer and a butterfly permutation between each layer to allow interactions between many different pairs of features— similar to the Fast Fourier Transform (FFT) butterfly construction. This also means that the cardinality of the active set of all the Shapley modules is set to 2, making the overhead for computing the Shapley values roughly $4 \times$ that of the underlying function. An example of this construction can be seen on the right of Fig. 2. We emphasize that this permutation is one of the choices that enable fast feature interactions for constructing deep SHAPNETs from Shallow SHAPNETs. We do not claim it is necessarily the best but believe it is a reasonable choice if no other assumptions are made. One could also construct SHAPNETs based on prior belief (an example for images below). It is possible to learn the pairs by means discussed in Appendix D but applied during training time and over all inputs.

Deep SHAPNET for Images Here we describe one of the many possibilities to work on image dataset with SHAPNETs. This is largely inspired by works including Desjardins et al. (2015); Dinh et al. (2017); Kingma & Dhariwal (2018). Still, the Deep SHAPNET here consists of different layers

of Shallow SHAPNETs. We begin by describing the operations in each of the consecutive Shallow SHAPNETs, and then cascade from one stage to the next.

Canonical convolution operation is composed with three consecutive operations: sliding-window (unfolding the image representation tensor to acquire small patches matching the the filter), matrix multiplication between filters and the small patches from the images, and folding the resulting representation into the usual image representation tensor. We merely 1) replace the matrix multiplication operation with Shapley modules (similar to that in Desjardins et al. (2015)) and 2), since we have the same number of pixels, we can put the corresponding output vector representation in space $\mathbb{R}^{c'}$ back in the location of the original pixel (and performed summation of the values overlapping at a pixel location just as canonical convolution operation would). To create a hierarchical representation of images, we use à-trous convolution with increasing dilation as the Shapley transform goes from one stage to the next, similar to Chen et al. (2017); Chen et al. (2018). To reduce computation, we can choose a subset of the channel dimensions of each pixels to take as inputs, similar to Dinh et al. (2017); Kingma & Dhariwal (2018). For the final prediction, we do a global summation pooling, given that the final Shapley representation comform to Remark 6. More details in subsection H.3.

2.4 EXPLANATION REGULARIZATION DURING TRAINING

One of the important benefits to SHAPNETs is that we can regularize the explanations *during training*. The main idea is to regularize the last layer explanation so that the model learns to attribute features in ways aligned with human priors–e.g. sparse or smooth. This is quite different from smoothing the explanation *post-hoc* as in saliency map smoothing methods (Ross et al., 2017; Smilkov et al., 2017; Sundararajan et al., 2017; Yeh et al., 2019), but falls more into the lines of usage of interpretations of models (Liu & Avci, 2019; Erion et al., 2019; Rieger et al., 2020). For ℓ_1 regularization, the main idea is similar to sparse autoencoders in which we assume the latent representation is sparse. This is related to the sparsity regularization in LIME (Ribeiro et al., 2016) but is fundamentally different because it actually changes the learned model rather than just the explanation. For ℓ_∞ regularization, the idea is to smooth the Shapley values so that none of the input features become too important individually, be useful for example in a security setting where the model should not be too sensitive to any one sensor because the sensors could be adversarial attacked. Finally, with ad-hoc knowledge on the attribution appropriate for the task at hand, the user could specify different regularizations.

2.5 CONDITIONAL DYNAMIC PRUNING

Lemma 13 allows for pruning during inference time and learning during training time (Appendix D).

Lemma 13 (Missingness in Deep SHAPNETs). *In any of the Shapley representations, $Z_i^{(l)} \in \mathbb{R}^C$, from each Shallow SHAPNET inside a Deep SHAPNET, $Z^{(l)}$, if the Shapley values corresponding to a certain input feature $i \in \mathcal{I}_D$ is equal to the reference vector $\boldsymbol{r}_i \in \mathbb{R}^C$ (zeros for Shallow SHAPNETs other than the first) for the same feature, we have $Z_i^{(m)} = \mathbf{0}$ for any $m > l$.*

Lemma 13 is a simple extension of Theorem 12, which allows us to skip the computation for any input features whose importance values become zeros during any stage, as their importance values in all the subsequent representations will be zeros. In particular, the computation of a Shapley Module could be avoided if its features in active sets are all set to zeros. In practice, we set a threshold close to zeros, and skip the computations involving the input features with importance values lower than the threshold. Note that the importance values for the features are conditioned on the input instances instead of a static pruned model (Ancona et al., 2020), allowing more flexibility. Moreover, with the help of ℓ_1 regularization discussed in subsection 2.4 (which can applied on each $Z^{(l)}$), we can avoid even more computation as shown in Fig. 5. An illustration can be found in Fig. 3. We draw similarity to prior works including Han et al. (2015); Bengio et al. (2015); Theodorakopoulos et al. (2017).

3 EXPERIMENTS & VISUALIZATIONS

We will (1) validate that our SHAPNET models can be quite expressive despite the intrinsic explanation design, (2) demonstrate that our intrinsic SHAPNET explanations perform comparably or better than posthoc explanations, and (3) highlight the novel capabilities of layer-wise explanations and explanation regularization enabled by the design of SHAPNET. More details in Appendix H.

Figure 3: An visualizaiton of Lemma 13 and pruning in action: Notice 1) that once a pixel get to close to reference values at an earlier stage, it will stay that way for the rest of the computation. and 2) ℓ_1 regularization promotes the sparsity and hence increase the amount of computation that can be avoided. The visualization is generated by taking the ℓ_1 norm of the Shapley value vectors for each features, and for the sake of visual clarity, we mask the importance value under 0.03 (treated as close to zeros) after normalization. The first row is retrieved from regularly trained model, the second row from model with ℓ_1 regularization discussed in subsection 2.4, and the last row is retrieved from the model with ℓ_1 regularization applied on all inter-layer representations.

Datasets First, we create a synthetic regression dataset by sampling the input $\boldsymbol{v} \in [-0.5, 0.5]^{16}$ from the uniform distribution where the true (synthetic) regression model is $f(\boldsymbol{v}) = \prod_i v_i + \sum_i v_i^2 + 0.05\epsilon$, where ϵ is sampled from a standard normal distribution. Second, we choose five real-world datasets from Dua & Graff (2017): Yeast ($d = 8$) and Breast Cancer Wisconsin (Diagnostic) ($d = 30$), MNIST (LeCun & Cortes, 2010), FashionMNIST (Xiao et al., 2017), and Cifar-10 (Krizhevsky, 2009) datasets to validate SHAPNET on higher-dimensional datasets.

SHAPNET **model performance** We would first like to validate that our Deep and Shallow SHAP-NET models can be comparable in performance to other models—i.e., that our Shapley module structure does not significantly limit the representational power of our model. Thus, we define DNN models that are roughly comparable in terms of computation or the number of parameters—since our networks require roughly four times as much computation as a vanilla DNN but share many parameters. For our comparison DNNs, we set up a general feedforward network with residual connections (He et al., 2016). Note that for the vision tasks, we use two other models for comparison with our Deep SHAPNETs: a comparable convolutional-layer based model which shares the same amount of channels, layers, and hence parameters with only LeakyReLU activation (Xu et al., 2015) with no other tricks other than normalizing the input and random cropping after padding (same as our Deep SHAPNETs), and the state-of-the-art on each dataset (Byerly et al., 2020; Tanveer et al., 2020; Anonymous, 2021). The performance of the models are shown in Table 1 and Table 2 in which the loss is shown for the synthetic dataset (lower is better) and classification accuracy for the other datasets (higher is better). While there is a very slight degradation in performance, our lower-dimensional models are comparable in performance even with the structural restriction. While there is some gap between state-of-the-art for image data, our image-based deep SHAPNET models can indeed do reasonably well even on these high-dimensional non-linear classification problems, but we emphasize that they also provide fundamentally new capabilities as explored later. See Appendix H.

Intrinsic SHAPNET **explanations compared to post-hoc explanations** We now compare the intrinsic SHAPNET explanations with other post-hoc explanation methods. First, because our intrinsic SHAPNET explanations are simultaneously produced with the prediction, the explanation time is merely the cost of a single forward pass (we provide a wall-clock time experiment in Appendix E). For the lower-dimensional datasets, we validate our intrinsic explanations compared to other SHAP-based post-hoc explanations by computing the difference to the true SHAP values (which can be computed exactly or approximated well in low dimensions). Our results show that Shallow SHAPNET indeed gives the true SHAP values up to numerical precision as proved by Theorem 8, and Deep SHAPNET explanations are comparable to other post-hoc explanations (result in Table 3 and more discussion in Appendix F). For image-based data, we will evaluate our high-dimensional explanations in the MNIST dataset based on 1) digit flipping experiments as introduced in Shrikumar et al. (2017),

Table 1: Model performance (loss for synthetic or accuracy for others, averaged over 50 runs)

| Models
Datasets	Deep SHAPNET	DNN (eq. comp.)	DNN (eq. param.)	Shallow SHAPNET	GAM
Synthetic (loss)	3.37e-3	3.93e-3	6.62e-3	3.11e-3	3.36e-3
Yeast	0.585	0.576	0.575	0.577	0.597
Breast Cancer	0.959	0.966	0.971	0.958	0.969

Table 2: Accuracies of Deep SHAPNETs for images, comparable CNNs and state-of-the-art models.

| Models
Datasets	Deep SHAPNET	Comparable CNN	SOTA
MNIST	0.9950	0.9917	0.9984
FashionMNIST	0.9195	0.9168	0.9691
Cifar-10	0.8206	0.7996	0.9970

Table 3: Average difference from exact Shapley values for different models

| Explanations
Models	Ours	Deep SHAP	Kernel SHAP (77)	Kernel SHAP (def.)	Kernel SHAP (ext.)
Untrained models (100 independent trials each entry)					
Deep SHAPNET	1.29e-06	2.89e-05	1.42e+03	2.13e+05	5.00e-11
Shallow SHAPNET	2.97e-07	0.802	0.0733	4.05e-03	1.05e-03
Regression models on synthetic dataset (20 independent trials each entry)					
Deep SHAPNET	4.99e-03	3.71	4.91e-03	3.05e-04	2.26e-05
Shallow SHAPNET	4.19e-08	3.88	4.05e-03	2.39e-04	2.75e-05
Classification models on Yeast dataset (50 independent trials each entry)					
Deep SHAPNET	0.0504	0.307	0.01467	0	0
Shallow SHAPNET	2.20e-07	0.516	0.0132	0	0
Classification models on Breast Cancer Wisconsin (Diagnostic) (50 independent trials each entry)					
Deep SHAPNET	0.0167	0.120	0.0369	4.09e-03	8.05e-04
Shallow SHAPNET	1.20e-04	0.0581	0.0224	1.91e-03	2.03e-04

Table 4: Explanation regularization experiments with Deep SHAPNETs (averaged over 50 runs)

| Models
Metrics	Yeast			Breast Cancer Wisconsin		
	ℓ_∞ Reg.	ℓ_1 Reg.	No Reg.	ℓ_∞ Reg.	ℓ_1 Reg.	No Reg.
Coefficient of variation for abs. SHAP	**0.768**	1.23	1.05	**1.28**	NaN	2.04
Sparsity of SHAP values	0.003	**0.00425**	0.00275	0.429	**0.841**	0.209
Accuracy	**0.592**	**0.592**	0.587	0.957	**0.960**	**0.960**

where higher relative log-odds score is better, 2) removing the least-k salient features, where lower fraction of change is better, 3) dropping the top-k features as identified by the explanation and measuring the remaining output activation of the original predicted class, where ideally, the top features would drastically reduce the output logits—showing that our explanations do highlight the important features. We compare Deep SHAPNET explanations with DeepLIFT (Shrikumar et al., 2017), DeepSHAP (Lundberg & Lee, 2017), Integrated Gradients (Sundararajan et al., 2017), Input×Gradients (Shrikumar et al., 2016) and vanilla gradients (saliency). As shown in Fig. 4, Deep SHAPNET offers high-quality explanations on different benchmarks (Samek et al., 2017; Shrikumar et al., 2017; Ancona et al., 2018; Srinivas & Fleuret, 2019).

Layer-wise explanations With the layer-wise explanation structure, we can probe into the Shapley representation at each stage of a Deep SHAPNET as in Fig. 3 and perform dynamic pruning. Hence we also provide a set of pruning experiment with retaining accuracy shown in Fig. 5, visualization shown in Fig. 3, and discussion in Appendix G, where we show how pruning the values in the Shapley representations of different layer changes model performance, and argue that a large portion of the computation can be avoided during inference time and the model can retain almost the same accuracy. This showcases this unique ability to perform pruning dynamically conditioned input instances. We note that though this has been done before, our models is, to the best of our knowledge, the only model capable of learning the importance of different computational components in tandem with the importance of each feature, performing conditional dynamic pruning during inference time, and explanation regularization.

Figure 4: Our intrinsic Deep SHAPNET explanations perform better than post-hoc explanations in identifying the features that can flip the model prediction or that contribute most to the prediction as seen in figures on the left showing the results of flipping digits as introduced in Shrikumar et al. (2017) and right showing the remaining activation after removing the top k features identified by each explanation method. While Deep SHAPNET explanations did not perform the best in the middle where we show the results after removing least k-salient features as introduced in Srinivas & Fleuret (2019), our model still scores the second. All results are measured on MNIST test set. More results for digit flipping can be found in Fig. 11, which show the same conclusion.

Figure 5: 1) Pruning values from earlier layers have at least equal or stronger effects on the performance than from later layers due to Lemma 13; 2) ℓ_1 regularized model performs better especially when the regularization is applied on all all the layers instead of just the output; 3) Most of the values can be removed and retain the accuracy. We prune the values in the order from the least salient (in magnitude of ℓ_1 norm) to the most pixel by pixel. This is measured on the MNIST test set.

Figure 6: MNIST SHAPNET explanations for different regularizations qualitatively demonstrate the effects of regularization. We notice that ℓ_1 only puts importance on a few key features of the digits while ℓ_∞ spreads out the contribution over more of the image. Red and blue correspond to positive and negative contribution respectively. More visualization of the explanations, including the other classes and more in-depth discussion, can be found in subsection H.4.

Explanation regularization during training We experiment with ℓ_1 and ℓ_∞ explanation regularizations during training to see if the regularizations significantly affect the underlying model behavior. For the lower-dimensional datasets, we compute the accuracy, the sparsity, and the coefficient of variation (CV, standard deviation divided by mean) for our Deep SHAPNET. We see in Table 4 that our ℓ_∞ regularization spreads the feature importance more evenly over features (i.e., low CV), ℓ_1 regularization increases the sparsity (i.e., higher sparsity), and both either improve or marginally degrade the accuracy. For MNIST data, we visualize the explanations from different regularization models in Fig. 6, and we perform the top-k feature removal experiment with different regularizers in Fig. 7, which shows that our regularizers produce some model robustness towards missing features. Fig. 5 shows ℓ_1 regularized model achieves the best result under pruning across different layers, especially when applied on all layers, further increasing the amount of computation to be pruned.

REFERENCES

David Alvarez Melis and Tommi Jaakkola. Towards robust interpretability with self-explaining neural networks. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 7775–7784. Curran Associates, Inc., 2018. URL `http://papers.nips.cc/paper/8003-towards-robust-interpretability-with-self-explaining-neural-networks.pdf`.

Marco Ancona, Enea Ceolini, Cengiz Öztireli, and Markus Gross. Towards better understanding of gradient-based attribution methods for deep neural networks. In *International Conference on Learning Representations*, 2018. URL `https://openreview.net/forum?id=Sy21R9JAW`.

Marco Ancona, Cengiz Oztireli, and Markus Gross. Explaining deep neural networks with a polynomial time algorithm for shapley value approximation. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 272–281, Long Beach, California, USA, 09–15 Jun 2019. PMLR. URL `http://proceedings.mlr.press/v97/ancona19a.html`.

Marco Ancona, Cengiz Öztireli, and Markus Gross. Shapley Value as Principled Metric for Structured Network Pruning. *arXiv:2006.01795 [cs]*, June 2020. URL `http://arxiv.org/abs/2006.01795`. arXiv: 2006.01795.

Anonymous. Sharpness-aware minimization for efficiently improving generalization. In *Submitted to International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=6Tm1mposlrM`. under review.

Emmanuel Bengio, Pierre-Luc Bacon, Joelle Pineau, and Doina Precup. Conditional computation in neural networks for faster models. *CoRR*, abs/1511.06297, 2015. URL `http://arxiv.org/abs/1511.06297`.

Adam Byerly, Tatiana Kalganova, and Ian Dear. A branching and merging convolutional network with homogeneous filter capsules, 2020.

Rich Caruana, Yin Lou, Johannes Gehrke, Paul Koch, Marc Sturm, and Noemie Elhadad. Intelligible models for healthcare: Predicting pneumonia risk and hospital 30-day readmission. In *Proceedings of the 21th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '15, pp. 1721–1730, New York, NY, USA, 2015. Association for Computing Machinery. ISBN 9781450336642. doi: 10.1145/2783258.2788613. URL `https://doi.org/10.1145/2783258.2788613`.

Jianbo Chen, Le Song, Martin J. Wainwright, and Michael I. Jordan. L-shapley and c-shapley: Efficient model interpretation for structured data. In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=S1E3Ko09F7`.

L. Chen, G. Papandreou, I. Kokkinos, K. Murphy, and A. L. Yuille. Deeplab: Semantic image segmentation with deep convolutional nets, atrous convolution, and fully connected crfs. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 40(4):834–848, 2018.

Liang-Chieh Chen, George Papandreou, Florian Schroff, and Hartwig Adam. Rethinking atrous convolution for semantic image segmentation. *CoRR*, abs/1706.05587, 2017. URL `http://arxiv.org/abs/1706.05587`.

Guillaume Desjardins, Karen Simonyan, Razvan Pascanu, and koray kavukcuoglu. Natural neural networks. In C. Cortes, N. D. Lawrence, D. D. Lee, M. Sugiyama, and R. Garnett (eds.), *Advances in neural information processing systems 28*, pp. 2071–2079. Curran Associates, Inc., 2015. URL `http://papers.nips.cc/paper/5953-natural-neural-networks.pdf`.

Laurent Dinh, Jascha Sohl-Dickstein, and Samy Bengio. Density estimation using Real NVP. *ICLR*, 2017. URL `https://openreview.net/forum?id=HkpbnH9lx`.

Dheeru Dua and Casey Graff. UCI machine learning repository, 2017. URL `http://archive.ics.uci.edu/ml`.

Gabriel G. Erion, Joseph D. Janizek, Pascal Sturmfels, Scott Lundberg, and Su-In Lee. Learning explainable models using attribution priors. *CoRR*, abs/1906.10670, 2019. URL `http://arxiv.org/abs/1906.10670`.

Riccardo Guidotti, Anna Monreale, Salvatore Ruggieri, Dino Pedreschi, Franco Turini, and Fosca Giannotti. Local rule-based explanations of black box decision systems. *CoRR*, abs/1805.10820, 2018a. URL `http://arxiv.org/abs/1805.10820`.

Riccardo Guidotti, Anna Monreale, Salvatore Ruggieri, Franco Turini, Fosca Giannotti, and Dino Pedreschi. A survey of methods for explaining black box models. *ACM Comput. Surv.*, 51(5), August 2018b. ISSN 0360-0300. doi: 10.1145/3236009. URL `https://doi.org/10.1145/3236009`.

Song Han, Jeff Pool, John Tran, and William J. Dally. Learning both weights and connections for efficient neural networks. In *Proceedings of the 28th International Conference on Neural Information Processing Systems - Volume 1*, NIPS'15, pp. 1135–1143, Cambridge, MA, USA, 2015. MIT Press.

K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, Las Vegas, NV, June 2016. doi: 10.1109/CVPR.2016.90.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. 2014. URL `http://arxiv.org/abs/1412.6980`. cite arxiv:1412.6980Comment: Published as a conference paper at the 3rd International Conference for Learning Representations, San Diego, 2015.

Durk P Kingma and Prafulla Dhariwal. Glow: Generative flow with invertible 1x1 convolutions. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 10215–10224. Curran Associates, Inc., 2018. URL `http://papers.nips.cc/paper/8224-glow-generative-flow-with-invertible-1x1-convolutions.pdf`.

A. Krizhevsky. Learning multiple layers of features from tiny images. 2009.

Yann LeCun and Corinna Cortes. MNIST handwritten digit database. 2010. URL `http://yann.lecun.com/exdb/mnist/`.

Frederick Liu and Besim Avci. Incorporating priors with feature attribution on text classification. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 6274–6283, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1631. URL `https://www.aclweb.org/anthology/P19-1631`.

Yin Lou, Rich Caruana, and Johannes Gehrke. Intelligible models for classification and regression. In *Proceedings of the 18th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '12, pp. 150–158, New York, NY, USA, 2012. Association for Computing Machinery. ISBN 9781450314626. doi: 10.1145/2339530.2339556. URL `https://doi.org/10.1145/2339530.2339556`.

Yin Lou, Rich Caruana, Johannes Gehrke, and Giles Hooker. Accurate intelligible models with pairwise interactions. In *Proceedings of the 19th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '13, pp. 623–631, New York, NY, USA, 2013. Association for Computing Machinery. ISBN 9781450321747. doi: 10.1145/2487575.2487579. URL `https://doi.org/10.1145/2487575.2487579`.

Scott M Lundberg and Su-In Lee. A Unified Approach to Interpreting Model Predictions. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 4765–4774. Curran Associates, Inc., 2017. URL `http://papers.nips.cc/paper/7062-a-unified-approach-to-interpreting-model-predictions.pdf`.

Scott M. Lundberg, Gabriel Erion, Hugh Chen, Alex DeGrave, Jordan M. Prutkin, Bala Nair, Ronit Katz, Jonathan Himmelfarb, Nisha Bansal, and Su-In Lee. From local explanations to global understanding with explainable AI for trees. *Nature Machine Intelligence*, 2(1):56–67, January

2020. ISSN 2522-5839. doi: 10.1038/s42256-019-0138-9. URL `https://doi.org/10.1038/s42256-019-0138-9`.

W. James Murdoch, Peter J. Liu, and Bin Yu. Beyond word importance: Contextual decomposition to extract interactions from LSTMs. In *International Conference on Learning Representations*, 2018. URL `https://openreview.net/forum?id=rkRwGg-0Z`.

Vinod Nair and Geoffrey E. Hinton. Rectified linear units improve restricted boltzmann machines. In *Proceedings of the 27th International Conference on International Conference on Machine Learning*, ICML'10, pp. 807–814, Madison, WI, USA, 2010. Omnipress. ISBN 9781605589077.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019. URL `http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf`.

Gregory Plumb, Maruan Al-Shedivat, Eric P. Xing, and Ameet Talwalkar. Regularizing black-box models for improved interpretability. *CoRR*, abs/1902.06787, 2019. URL `http://arxiv.org/abs/1902.06787`.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. "why should i trust you?": Explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '16, pp. 1135–1144, New York, NY, USA, 2016. Association for Computing Machinery. ISBN 9781450342322. doi: 10.1145/2939672.2939778. URL `https://doi.org/10.1145/2939672.2939778`.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. Anchors: High-precision model-agnostic explanations. In *AAAI Conference on Artificial Intelligence*, 2018. URL `https://www.aaai.org/ocs/index.php/AAAI/AAAI18/paper/view/16982`.

Laura Rieger, Chandan Singh, W. James Murdoch, and Bin Yu. Interpretations are useful: penalizing explanations to align neural networks with prior knowledge. Proceedings of Machine Learning Research, Vienna, Austria, 12–18 July 2020. URL `http://https://arxiv.org/abs/1909.13584`.

Andrew Slavin Ross, Michael C. Hughes, and Finale Doshi-Velez. Right for the Right Reasons: Training Differentiable Models by Constraining their Explanations. *arXiv:1703.03717 [cs, stat]*, May 2017. URL `http://arxiv.org/abs/1703.03717`. tex.ids: rossRightRightReasons2017a arXiv: 1703.03717.

W. Samek, A. Binder, G. Montavon, S. Lapuschkin, and K. Müller. Evaluating the visualization of what a deep neural network has learned. *IEEE Transactions on Neural Networks and Learning Systems*, 28(11):2660–2673, 2017. doi: 10.1109/TNNLS.2016.2599820.

Lloyd S Shapley. A value for n-person games. *Contributions to the Theory of Games*, 2(28):307–317, 1953.

Avanti Shrikumar, Peyton Greenside, Anna Shcherbina, and Anshul Kundaje. Not just a black box: Learning important features through propagating activation differences. *CoRR*, abs/1605.01713, 2016. URL `http://arxiv.org/abs/1605.01713`.

Avanti Shrikumar, Peyton Greenside, and Anshul Kundaje. Learning important features through propagating activation differences. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 3145–3153, International Convention Centre, Sydney, Australia, 06–11 Aug 2017. PMLR. URL `http://proceedings.mlr.press/v70/shrikumar17a.html`.

Karen Simonyan, Andrea Vedaldi, and Andrew Zisserman. Deep inside convolutional networks: Visualising image classification models and saliency maps. In *Workshop at International Conference on Learning Representations*, 2014.

Chandan Singh, W. James Murdoch, and Bin Yu. Hierarchical interpretations for neural network predictions. In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=SkEqro0ctQ`.

Daniel Smilkov, Nikhil Thorat, Been Kim, Fernanda B. Viégas, and Martin Wattenberg. Smoothgrad: removing noise by adding noise. *CoRR*, abs/1706.03825, 2017. URL `http://arxiv.org/abs/1706.03825`.

Suraj Srinivas and François Fleuret. Full-gradient representation for neural network visualization. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32, pp. 4124–4133. Curran Associates, Inc., 2019. URL `https://proceedings.neurips.cc/paper/2019/file/80537a945c7aaa788ccfcdf1b99b5d8f-Paper.pdf`.

Erik Strumbelj and Igor Kononenko. An efficient explanation of individual classifications using game theory. *J. Mach. Learn. Res.*, 11:1–18, March 2010. ISSN 1532-4435.

Mukund Sundararajan and Amir Najmi. The many shapley values for model explanation. Proceedings of Machine Learning Research, Vienna, Austria, 12–18 July 2020. URL `http://https://arxiv.org/abs/1908.08474`.

Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic attribution for deep networks. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pp. 3319–3328, International Convention Centre, Sydney, Australia, 06–11 Aug 2017. PMLR. URL `http://proceedings.mlr.press/v70/sundararajan17a.html`.

Muhammad Suhaib Tanveer, Muhammad Umar Karim Khan, and Chong-Min Kyung. Fine-tuning darts for image classification, 2020.

Ilias Theodorakopoulos, Vasileios Pothos, Dimitris Kastaniotis, and Nikos Fragoulis. Parsimonious inference on convolutional neural networks: Learning and applying on-line kernel activation rules. *CoRR*, abs/1701.05221, 2017. URL `http://arxiv.org/abs/1701.05221`.

Xiaoqian Wang, Hong Chen, Jingwen Yan, Kwangsik Nho, Shannon L Risacher, Andrew J Saykin, Li Shen, Heng Huang, and for the ADNI. Quantitative trait loci identification for brain endophenotypes via new additive model with random networks. *Bioinformatics*, 34(17):i866–i874, 2018. ISSN 1367-4803. doi: 10.1093/bioinformatics/bty557. URL `https://doi.org/10.1093/bioinformatics/bty557`. _eprint: https://academic.oup.com/bioinformatics/article-pdf/34/17/i866/25702591/bty557.pdf.

Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms, 2017.

Bing Xu, Naiyan Wang, Tianqi Chen, and Mu Li. Empirical Evaluation of Rectified Activations in Convolutional Network. *arXiv:1505.00853 [cs, stat]*, November 2015. URL `http://arxiv.org/abs/1505.00853`. arXiv: 1505.00853.

Chih-Kuan Yeh, Cheng-Yu Hsieh, Arun Suggala, David I Inouye, and Pradeep K Ravikumar. On the (in)fidelity and sensitivity of explanations. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 10967–10978. Curran Associates, Inc., 2019. URL `http://papers.nips.cc/paper/9278-on-the-infidelity-and-sensitivity-of-explanations.pdf`.

A   PROOF OF THEOREM 8 & LEMMA 5

Proof of Lemma 5. For each row of $W \triangleq AZ$, we can show that it is the Shapley value for $\tilde{f}^{(k)}$ using the linearity of Shapley values (the original motivating axiom of Shapley values, see Shapley (1953, Axiom 4 & Axiom 5)):

$$\boldsymbol{w}_k = \sum_j a_{k,j}\phi(f^{(j)}, \boldsymbol{x}) = \phi(\sum_j a_{k,j}f^{(j)}, \boldsymbol{x}) = \phi(\tilde{f}^{(k)}, \boldsymbol{x}). \tag{6}$$

Combining this result for all rows with Def. 3, we arrive at the result. $\qquad\square$

We define a feature selector function $\pi^{(w)}$ as follows:

Definition 14 (Feature selector function). $\pi^{(w)} : \mathbb{R}^d \mapsto \mathbb{R}^{|w|}$ *(for any $w \in \mathcal{W}$, where $\mathcal{W}$ again indexes the set of all component Shapley modules in a given Shallow* SHAPNET *as in Def. 7) is defined to select the input features by the index w, which contains the indices of the supposed input features of $F^{(w)}$:*

$$\pi^{(w)}(\boldsymbol{x}) = [x_i] \text{ where } i \in w. \tag{7}$$

Lemma 15. *The composite function $F'^{(w)}$ for a given Shapley module $F^{(w)}$, defined as*

$$F'^{(w)} = F^{(w)} \circ \pi^{(w)}, \tag{8}$$

has the following Shapley values for its input features

$$\phi_i\left(F'(x), \boldsymbol{x}\right) = \begin{cases} \phi\left(F^{(w)}, \boldsymbol{x}\right) = \alpha_i^{(w)} & \text{if } i \in w \\ 0 & \text{otherwise,} \end{cases} \tag{9}$$

Proof. This holds since the absence (set to reference values) of a feature does not make a difference to the final output of $F'^{(w)}$. $\qquad\square$

Now we are ready to present proof for Theorem 8:

Proof. We consider a simpler, and yet more general case: consider where each of the modules defined in Def. 10, we first transform any Shapley module $F^{(w)}$ in the given Shallow SHAPNET G to $F'^{(w)}$. Then, by Def. 7, the zeros in Lemma 15 do not make any difference whether to the output of G or its associated β_i's, and yet β_i's are nothing but summations of Shapley values of different $F^{(w)}$'s and by Lemma 5,

$$\beta_i = \phi_i\left(G, \boldsymbol{x}\right), \tag{10}$$

which completes the proof. $\qquad\square$

B   PROOF OF THEOREM 12

Proof. The proof of local accuracy is trivial by construction since $\mathcal{H}(\boldsymbol{x}) \triangleq \text{sum}^{[d]}(h(\boldsymbol{x}))$ from Def. 11. The proof of missingness is straightforward via induction on the number of layers, where the claim is that if $x_i = r_i$ (i.e., the input for one feature equals the reference value), then $\forall \ell, \; h_i^{(\ell)}(\boldsymbol{x}) = 0$ (i.e., the pre-summation outputs of the Shapley modules in all layers corresponding to feature i will all be zero). For the base case of the first layer, we know that if $x_i = r_i$, then we know that $Z_i^{(1)} = \mathbf{0}$ by the construction of Shapley modules. For the future layers, the inductive hypothesis is then that if previous layer representation $Z_i^{(\ell-1)}$ of a feature i is $\mathbf{0}$, then the representation from the current layer ℓ for this feature remains the same, i.e., $Z_i^{(\ell)} = \mathbf{0}$. Because the reference values for all layers except the first layer are zero, then we can again apply the property of our Shapley modules and thus the inductive hypothesis will hold for $\ell > 1$. Thus, the the claim holds for all layers ℓ, and $h_i(\boldsymbol{x}) = \text{sum}^{[c]}Z_i^{(\ell)}$ will also be zero—which proves missingness for Deep SHAPNETs. $\qquad\square$

C   DEDICATED LITERATURE REVIEW

Post-hoc feature-attribution explanation methods, gained traction with the introduction of LIME explanations (Ribeiro et al., 2016) and its variants (Ribeiro et al., 2018; Guidotti et al., 2018a;b), which formulate an explanation as a local approximation to the model near the target instance. LIME attempts to highlight which features were important for the prediction. Saliency map explanations for image predictions based on gradients also assign importance to each feature (or pixel) (Simonyan et al., 2014; Shrikumar et al., 2017). SHAP explanations attempt to unify many previous feature attribution methods under a common additive feature attribution framework (Lundberg & Lee, 2017; Lundberg et al., 2020), which is the main motivation for our work.

Intrinsically interpretable models are an alternative to post-hoc explanation methods. In particular, GAM (Lou et al., 2012) and its extension (Lou et al., 2013; Caruana et al., 2015) construct models that can be displayed as series of line graphs or heatmaps. Because the entire model can be displayed and showed to users, it is possible for a user to directly edit the model based on their domain knowledge. In addition, Alvarez Melis & Jaakkola (2018) proposed an architecture that are complex and explicit if trained with a regularizer tailored to that architecture. Our methodology sits *in between* post-hoc and intrinsic approaches by constructing an explainable model but using SHAP post-hoc explanation concepts and allowing more complex feature interactions.

Recent works also focus on Shapley value approximations in deep neural nets, where Deep Approximate Shapley Propagation (DASP) approximates in polynomial time (Ancona et al., 2019), L-Shapley and C-Shapley do in linear (Chen et al., 2019) with the Markov assumption, and our method performs approximation with a constant complexity, which additionally allows regularizing the explanations according to human priors and hence modifying the underlying model during training. This falls in line with previous works (Ross et al., 2017; Liu & Avci, 2019; Erion et al., 2019; Rieger et al., 2020) each of which adds an extra term in the loss function measuring the disagreement between the explanations and human priors. Ross et al. (2017) proposed to regularize the input gradients as explanations, which creates the need for second-order gradient. Liu & Avci (2019) uses Integrated Gradients (IG) (Sundararajan et al., 2017), which is an extension to Shapley values (Sundararajan & Najmi, 2020). Due to the use of IG, several samples (for one explanation) are additionally warranted. Erion et al. (2019) proposed Expected Gradient to rid of reference values in IG and suggested the usage of a single sample. Rieger et al. (2020) adds to this line of work with Contextual Decomposition (Murdoch et al., 2018; Singh et al., 2019) which avoids the need of computation of second-order gradients and extra samples. Our work differs with these four in that we do not need a second order gradient and that we are focusing on the more theoretically-grounded Shapley values. The explanation-related regularizations in Alvarez Melis & Jaakkola (2018); Plumb et al. (2019) differ with ours in that the regularizers are used to *promote* interpretability and ours uses regularization to modify the underlying model to conform to prior belief. We also draw close similarity to works that that attempt to smooth saliency map explanations (Smilkov et al., 2017; Sundararajan et al., 2017; Yeh et al., 2019) which acts on explanation methods to induce certain properties in explanations but not the actual models.

D   LEARNED FEATURE INTERACTIONS

With both ℓ_1 regularization and missingness in Deep SHAPNET as discussed in subsection 2.5, we can discuss how it is possible to learn the specific choices for Shapley Modules in each Shallow SHAPNET in a Deep SHAPNET (how features interact in a Deep SHAPNET). Note that we have already discussed how we can perform instance-based pruning during inference.

To learn the interactions, we first create redundancies in each Shallow SHAPNET inside a Deep SHAPNET. During training, we automatically gain the importance values for each features by construction, from which we will determine the modules that are worth computing by comparing input representation of the features in their active sets to **0**s. If the input representation is close enough to **0**s, we can simply ignore that module. Of course, the underlying function can always change during training, and we argue that we can slowly strip away modules from the latter layers to the first layers as the training progresses to allow for more expressiveness and more room to correct early mistakes by the training procedure.

Table 5: Time for computing explanations (averaged over 1000 runs)

| Models
Explanations	Deep SHAPNET	DNN (eq. comp.)	DNN (eq. param.)
Ours	20.47	N/A	N/A
Deep SHAP	46.10	83.38	8.56
Kernel SHAP (40)	60.78	130.04	11.52
Kernel SHAP (77)	72.61	201.88	13.53
Kernel SHAP (def.)	598.79	789.08	142.85

E WALL-CLOCK TIME FOR EXPLANATION EXPERIMENT

To validate the efficiency of computing an explanation, we compare the wall-clock time of our SHAPNET explanations to other approximation methods related to Shapley-values including Deep SHAP and Kernel SHAP with different numbers of samples—40, 77, and default ($2 \times d + 2^{11}$). The wall-clock computation time in seconds can be seen in Table 5. We note importantly that this comparison is a bit odd because other Shapley-value explanation methods are *post-hoc* explanations, whereas SHAPNET is both a model and an intrinsic explanation method. Thus, the most fair comparison in terms of time is to have the post-hoc explanation methods explain our SHAPNET model as seen in the first column of Table 5. Nevertheless, we also show the wall-clock times for the post-hoc methods on our comparable DNNs in columns two and three of Table 5—note that SHAPNET cannot explain other DNNs hence the N/A's. From the first column, we can see that our method is inherently faster than the others when applied to our model. However, smaller model (i.e., DNN w. equivalent parameters) may come with faster explanations.

F LOWER-DIMENSIONAL COMPARISON BETWEEN SHAPNET EXPLANATIONS AND POST-HOC EXPLANATIONS

For lower-dimensional datasets, we seek validation for the explanations $h(\boldsymbol{x})$ provided by Deep SHAPNETs by comparing to the true Shapley values of our models (which can be computed exactly or aproximated well in low dimensions). Our metric is the normalized ℓ_1 norm between the true Shapley values denoted ϕ and the explanation denoted γ defined as:

$$\ell(\phi, \gamma) = \frac{\|\phi - \gamma\|_1}{d \sum_i \phi_i}. \tag{11}$$

Note that we measure the average difference from vector-output classifiers by means discussed in subsection F.1. The experimental setup and results are presented in subsection F.2.

F.1 COMPARING SHAP APPROXIMATION ERRORS WITH VECTOR OUTPUT MODELS

To compare the approximation errors for every output of the model, we use a weighted summation of the explanations for different outputs, where the weights are the models' output after passing into the soft-max function. Thus, we up weight the explanations that have a higher probability rather than taking a simple average. Thus, in the extremes, if the predicted probability for a label is zero, then the difference in explanation is ignored, while if the predicted probability for a label is one, then we put all the weight on that single explanation.

Concretely, for a classification model $C : \mathbb{R}^d \mapsto \mathbb{R}^n$, where d is the number of input features and n is the number of classes, we have the output vector of such model with an input instance $\boldsymbol{x} \in \mathbb{R}^d$ as $C(\boldsymbol{x}) \in \mathbb{R}^n$. For each output scalar value $[C(\boldsymbol{x})]_j$, we compute the approximation of the SHAP values w.r.t. that particular scalar for feature indexed i, denoted by $\gamma_i^{(j)}$, and hence its corresponding errors as measured in normalized ℓ_1 distance as discussed in Eqn. 11: $\ell_1^{(j)}$. The final error measure that we compare between classifiers ℓ_1^* is simply a weighted sum version of the normalized ℓ_1:

$$\ell_1^* = \sum_{j=1}^n [\mathrm{softmax}\,(C(\boldsymbol{x}))]_j \cdot \ell_1^{(j)},$$

where the softmax is taken on the non-normalized output of the classifiers. Note that ℓ_1^j is also taken on the raw output.

Table 6: Standard deviation of Shapley approximation errors on different datasets

Models \ Explanations	Ours	DeepSHAP	Kernel SHAP (77)	Kernel SHAP (def.)	Kernel SHAP (ext.)
Untrained models					
Deep SHAPNET	0.734	5.23	7.67e+08	4.25e+09	9.20e-03
Shallow SHAPNET	7.55e-07	1.57	0.124	8.02e-03	2.98e-03
Regression models on synthetic dataset					
Deep SHAPNET	3.28e-03	5.15	3.13e-03	8.79e-05	2.23e-05
Shallow SHAPNET	3.09e-04	1.28	4.75e-03	1.62e-04	6.33e-06
Classification models on Yeast dataset					
Deep SHAPNET	0.105	0.358	0.0288	0	0
Shallow SHAPNET	5.35e-07	0.894	0.0304	0	0
Classification models on Breast Cancer Wisconsin (Diagnoistic)					
Deep SHAPNET	0.0104	0.0359	0.0987	3.61e-03	1.72e-03
Shallow SHAPNET	0.0109	0.246	0.0141	1.93e-03	2.91e-04

F.2 SETUP AND RESULTS

Because the explanation difference from SHAP is independent of the training procedure but solely depends on the methods, we compare the performance of the explanation methods on untrained models that have randomly initialized parameters (i.e., they have the model structure but the parameters are random)—this is a valid model it is just not a model trained on a dataset. Additionally, we consider the metric after training the models on the synthetic, yeast, and breast cancer datasets. Note that for even a modest number of dimensions, computing the exact Shapley values is infeasible so we use a huge number of samples (2^{16}) with the kernel SHAP method to approximate the true Shapley values as the ground truth for all but the Yeast dataset, which only requires 2^8 samples for exact computation. Note that the extended Shapley value (ext.) requires 2^{14} times of model evaluation for a single explanation which is already extremely expensive, and thus included merely for comparison. Results of the average difference can be seen in Table 3. From the results in Table 3, we can see that indeed our Shallow SHAPNET model produces explanations that are the exact Shapley values (error by floating point computation) as Theorem 8 states. Additionally, we can see that even though our Deep SHAPNET model does not compute exact Shapley values, our explanations are actually similar to the true Shapley values.

We also provide in Table 6 the standard deviation of the approximation errors as in Table 3. These are the same runs as those in Table 3.

G PRUNING EXPERIMENT

We also conduct a set of pruning (set to reference values) experiment. This is, again, enabled by the layer-wise explainable property of Deep SHAPNET. Recent work has investigated the usage of Shapley values for pruning (Ancona et al., 2020), but our work means to showcase the ability even further. Results are shown in Fig. 5.

We perform the pruning experiment with all four MNIST-traiend models as discussed in subsection 2.3 and subsection 2.5 with no, output ℓ_1, layer ℓ_1, and ℓ_∞ regularizer, respectively. The values are removed (set to reference) by the order of their magnitude (from smallest to largest). We can see that most of the values might be dropped and the model performance stays unhinged. Moreover, ℓ_1 seems to have the best robustness against pruning, which makes sense as it induces sparsity in explanation values. Future works are to be done on the computational cost reduction under such pruning technique.

H MORE EXPERIMENTAL DETAILS

For all the experiments described below, the optimizers are Adam (Kingma & Ba, 2014) with default parameters in PyTorch (Paszke et al., 2019).

H.1 TIMING EXPERIMENTS

For Table 5, the timing is for the untrained (randomly initialized) models with 16 features. The numbers after Kernel SHAP indicates the number of samples allowed for Kernel SHAP's sampling method. Time is measured in seconds on CPU with 1000 independent trials per cell as Kernel SHAP supports solely CPU from the implementation of the authors of Lundberg & Lee (2017). The model of the CPU used for testing is Intel(R) Xeon(R) Silver 4114 CPU @ 2.20GHz.

We perform explanation on randomly initialized 16-feature Deep SHAPNET model for 1000 rounds. The 16-feature setup means we will have $(16/2) \times \log_2 16 = 32$ Shapley modules inside the entire model spanned out in 4 stages according to the Butterfly mechanism. The inner function f for every module in this setting is set as a fully-connected neural network of 1 hidden layer with 100 hidden units. For the two reference models, the model equivalent in computation time has 8 layers of 1800 hidden units in each layer, while the model equivalent in parameters has 11 layers of 123 hidden units in each layer. The output of the models are all scalars.

H.2 YEAST AND BREAST CANCER DATASETS EXPERIMENT SETUPS

This setup applies for the experiments involving both datasets, including those experiments for model performance and those that showcase the ability for explanation regularization. The experiments on the two datasets were run for 10 rounds each with different random initialization and the end results were obtained by averaging. For each round, we perform 5-fold cross validation on the training set, and arrive at 5 different models, giving us 50 different models to explain for each datasets. For the two datasets, we do 9 training epochs with a batch size of 32.

For the preprocessing procedures, we first randomly split the data into training and testing sets, with 75% and 25% of the data respectively. Then we normalize the training set by setting the mean of each feature to 0 and the standard deviation to 1. We use the training sets' mean and standard deviation to normalize the testing set, as is standard practice.

The inner functions of the Shapley modules are fully connected multilayer neural networks. The first and second stages of two models on the two datasets are identical in structure (not in parameter values). The first stage modules have 2 inputs and 25 outputs, with a single hidden layer of size 50. The modules in the second stage have 100 input units and 50 output units with two hidden layer of size 100. The non-linearity is introduced by ReLU (Nair & Hinton, 2010) in the inner functions. The rest of the specifics about the inner function are discussed below. Note that the dimensionality of the output from the last stage differs with that of the input to the next stage, as is expected by Shapley module where the input has twice the dimensionality of that of the output.

Model for Yeast dataset The Yeast dataset has 8 input features and hence 4 Shapley modules at each of the $\log_2 8 = 3$ stages. Within each stage, the structure of the inner function is identical except for the parameters. For the Yeast dataset, the third (last) stage comprises four-layer fully-connected model with inputs from $50 \times 2 = 100$ units to the number of classes, which is 10, with two hidden layers of 150 units.

Model for Breast Cancer Wisconsin (Diagnostic) This dataset has 30 input features, which is not a exponent of 2, but we can still construct a Deep SHAPNET by setting two extra variables to zero. In fact, in doing so we can simplify the Shapley modules since we know which of the modules in the network always have one or both of its input being 0 at all times. To construct the model, we realize that the number of stages is 5 and the number of modules at each stage is 16. For the Breast Cancer Wisconsin (Diagnostic) dataset, in the the third stage of the model, we use a model with 100 inputs units and 75 output units with two hidden layers of 150 units. The fourth stage has input units of $75 \times 2 = 150$ and output of 100 units with two hidden layers of size 200. The fifth (last) stage has a input dimension of 200, two hidden layers of 250 units and output of size 10.

H.3 SPECIFICS FOR VISION TASKS

H.3.1 STRUCTURE USED FOR VISION EXPERIMENTS

For all of the vision tasks, we use the same structure with the exception of input channel counts. We use a simple Linear-LeakyReLU (Xu et al., 2015) inside each Shapley Module, and the following are the output dimension of the linear layer: 1, 128, 128, 128, 128, 128, 128, 10, with 1 being the input channel of images in the case of MNIST & FashionMNIST or 3 with Cifar-10.

À-trous convolution   À-trous convolution is used for learning hierarchical representations of images. In our model, the dilations are set as follows: 1, 3, 5, 7, 9, 11, 13.

H.3.2 TRAINING RECIPE

Learning process   As discussed before, all the models are trained with Adam in PyTorch with the default parameters. The batch size is set to 64 for all the vision tasks. No warm-up or any other scheduling techniques are applied. The FashionMNIST & MNIST models in Table 1 are trained for 10 epochs while the MNIST models with which we investigate the new capabilities (layer-wise explanations & Shapley explanation regularizations) in Section 3 are trained with just 5 epochs. The Cifar-10 models are trained for 60 epochs.

Preprocessing   For both MNIST dataset and FashionMNIST dataset, we normalize the training and testing data with mean of 0.1307 and standard deviation of 0.3081, this gives us non-zero background and we would therefore set the reference values to 0's, allowing negative or positive contribution from the background. Both FashionMNIST and MNIST share the same preprocessing pipeline: 1) for training dataset, we extend the resolution from 28×28 to 36×36 and then randomly crop to 32×32, and then normalize. 2) for testing data, we simply pad the image to 32×32 and normalize them.

For Cifar-10 dataset, during training, we first pad 4 pixels on four sides of the image and then randomly crop back to 32×32, perform a horizontal flip with probability 0.5, and normalize the data with means $0.4914, 0.4822, 0.4465$ and standard deviaiton of $0.2023, 0.1994, 0.2010$ for each channel, respectively. For testing, we simply normalize the data with the same mean and standard deviation.

H.4 ILLUSTRATIONS OF EXPLANATION REGULARIZATION EXPERIMENTS

We present visual representations of our models' explanation on MNIST (LeCun & Cortes, 2010) dataset in Fig. 8, Fig. 9, and Fig. 10. In all three figures, the gray images from left to right are explanations laid out for all 10 classes from 0 to 9, where the red pixels indicate positive contribution and blue pixels indicate negative contribution, with magnitudes presented in the color bar below.

From an intuitive visual interpretation, we argue that our explanation regularizations are indeed working in the sense that ℓ_∞ regularization is indeed smoothing the explanations (to put more weight on a large number of pixels) and that ℓ_1 regularization limits the number of pixels contributing to the final classification.

One can notice that, by comparing the color bars below the figures, the contribution magnitudes for ℓ_∞ and ℓ_1 regularized models are lower than those of the unregularized counterpart. We have expected this to happen as both regularization techniques require to make one or more of the attribution values to be smaller. However, we note that this change in scale of the attribution values should not impact the accuracy of the prediction as the softmax operation at the end will normalize across the outputs for all of the classes.

More interesting discussions are provided in the caption of Fig. 8, Fig. 9, and Fig. 10, and we strongly encourage readers to have a read.

H.5 MORE RESULTS ON DIGIT FLIPPING

More results on digit flipping are in Fig. 11.

Figure 7: Both ℓ_1 and ℓ_∞ regularizations often introduce some robustness to the model against feature removal (the dotted and dashed lines are often above the solid lines). Three different feature orders are used: 1) most positive to most negative (top-down), 2) most negative to most positive (reversed), and 3) randomly chosen as a baseline. ℓ_1 regularization puts most importance on the first 100 features with relatively low importance to other features (seen in both top-down and reversed). ℓ_∞ regularization improves robustness when removing the top 50 or so features (as seen in the right figure which is zoomed in on the top 200 features).

Figure 8: The explanations produced by our model trained without explanation regularization for all 10 classes. From left to right are class index (also corresponding digits) from 0 to 9.

Figure 9: ℓ_1 regularization promotes sparsity in feature importance, which, by comparison with Fig. 8 and Fig. 10, one can easily argue has been successfully achieved. This shows that ℓ_1 regularization, combined with cross entropy loss, does (almost) remove negative contribution and only focuses on each digit's distinguishing features.

Figure 10: With ℓ_∞ regularization, the contribution among pixels are more laid out and less concentrated than they would be other wise as shown in Fig. 8. The explanations produced by our model trained with ℓ_∞ explanation regularization for all 10 classes. However, it is still easy to notice which part of the images contribute positively or negatively for a particular class.

Figure 11: Digit flipping results: Deep SHAPNET explanations perform well against post-hoc methods.