Feedback-Driven Vision-Language Alignment via Sampling-based Visual Projection

Abstract

Vision-language models (VLMs) combine image understanding and language generation, yet they frequently produce descriptions inconsistent with the visual input, leading to hallucinated objects and reduced reliability. We propose *Sampling-based Visual Projection* (SVP), a training framework that improves vision-language alignment by using a pretrained grounding model as feedback during data generation rather than as supervision. For each unlabeled seed image, the base model generates draft descriptions, a grounding model evaluates those drafts to return spatial feedback, and the VLM generates refined descriptions conditioned on that feedback. SVP selects the most informative candidates and fine-tunes the base model using only these natural-language outputs, effectively distilling spatial reasoning capabilities without injecting explicit grounding tokens or coordinates. Across ten benchmarks, SVP yields broad performance gains, including a 14% average improvement in captioning and a 12% increase in object recall, significantly reducing hallucinations while preserving robust question-answering capabilities.

1 Introduction

Vision-Language Models (VLMs (Bordes et al., 2024; Zhang et al., 2024a)) are essential for deploying expert-level artificial intelligence, as human intelligence is predominantly multimodal.

Generative VLMs (Li et al., 2024; 2022a; Ye et al., 2024; Chen et al., 2024a) built on Large Language Models (LLMs) demonstrate strong zero-shot performance across diverse vision-linguistic tasks (Achiam et al., 2023), unlocking new multimodal capabilities and enabling powerful generalization. By mapping linguistic tokens to visual features, these models combine the generation strengths of LLMs (Brown et al., 2020; Touvron et al., 2023) with the visual understanding of computer vision models (Radford et al., 2021; Dosovitskiy et al., 2020).

However, VLMs derived from pretrained backbones suffer from hallucinations and biases inherited from LLMs (Sasse et al., 2024; Rahmanzadehgervi et al., 2024). They frequently produce text inconsistent with visual content (Fig. 1), describing non-existent entities, missing relevant ones, or generating ungrounded content (Collerton et al., 2023; Bai et al., 2024).

Figure 1: Improving Vision-Language Alignment. Vision-language models (VLMs) often produce descriptions lacking specificity and accuracy, frequently hallucinating objects or missing important elements (left). Our *Sampling-based Visual Projection* (SVP) addresses these issues by leveraging self-captioning and grounding feedback. SVP enhances visual-language alignment without requiring additional human annotations, curated image-text pairs, or expensive AI feedback (right). This leads to models with greater contextual relevance, fewer hallucinations, and enhanced object recall. Appendix 11 for details.

Addressing these shortcomings is critical for deploying VLMs in high-stakes applications spanning scientific discovery (He et al., 2024) and engineering (Picard et al., 2023; Song et al., 2024).

(a) Referring w/ Bounding Box (left) and Segmentation Mask (right).

(b) Captioning w/ 7b (left) and 13b (right) models.

(c) Object Recall and Hallucination Reduction.

Figure 2: Benchmark Results comparing base models to our `SVP`-adapted model on captioning (CIDEr), referring (CIDEr), hallucination control (F1), and object recall (R). Models were adapted using three sets of 1,000 images from the `COCO2014` training set, with self-captioning and grounding feedback. Higher scores indicate better performance. `SVP` demonstrates significant improvements in captioning, referring, object recall, and hallucination reduction.

Researchers have explored various approaches to solve the above problem in VLMs (bottom Fig. 1). Most of these works focus on fine-tuning VLMs with supervised (carefully curated) data to improve grounding (Peng et al., 2024; Beyer et al., 2024; Yuan et al., 2021; You et al., 2023; Zhang et al., 2025) and vision-language alignment (Liu et al., 2024a; Sun et al., 2023). Unfortunately, this data approach tends to be costly and sample-inefficient, requiring large amounts of image-text annotations even for small models to resolve the above stated problem (Yuan et al., 2021). Preference-based post-training methods (Ouyang et al., 2022; Christiano et al., 2017; Rafailov et al., 2024) as another popular approach align VLM outputs with visual inputs (Zhou et al., 2024a; Sun et al., 2023) but require curated preference pairs (Sun et al., 2023; Favero et al., 2024). And, test-time approaches (Wan et al., 2024; Leng et al., 2024; Favero et al., 2024; Yin et al., 2023) improve grounding without architectural changes, yet their computational demands and model-specific heuristics limit broad applicability. See Appx A for extensive related work.

To address the challenge of improving VLM alignment without costly annotations, we introduce a feedback-driven adaptation framework. We leverage a pre-trained grounding model as an expert guide to enhance alignment in a task-agnostic manner (right side Fig. 1). *Drawing inspiration from human learning, we emulate how humans align sensory experiences with language by* grounding *new information via feedback* (Hattie

& Timperley, 2007; Tenenbaum & Goldring, 1989; Tenenbaum et al., 2011). We hypothesize that spatial reasoning is key to connecting low-level visual elements with high-level linguistic representations (Peirce, 2015; Oquab et al., 2014; Vallar, 2007); thus, we employ an external grounding model (Liu et al., 2023) to provide agnostic feedback and extract latent information from the model.

Specifically, we introduce `SVP` (*Sampling-based Visual Projection*, Fig. 4), an algorithm driven by iterative sampling and grounding feedback. Central to our approach is the concept of *Visual Projection* (VP) - an intermediate textual description that explicitly *maps raw visual features into the linguistic domain*. Functioning as a bridge for multimodal reasoning, similar to Chain-of-Thought (CoT) prompting (Wei et al., 2022), this projection allows the model's own outputs to be verified and refined by grounding experts (Zelikman et al., 2022; Anthony et al., 2017; Gulcehre et al., 2023), providing a mechanism to select informative samples.

Rather than constructing a new specialist model, we *leverage grounding as feedback to elicit latent information*, using an *existing grounding model as an expert guide* to align representations without additional human annotations (Sun et al., 2023; Peng et al., 2024) or preference data (Ouyang et al., 2022; Rafailov et al., 2024). Serving as a cost-effective proxy for ground-truth supervision, this off-the-shelf expert enables us to distill spatial reasoning into a generalist VLM. Unlike traditional knowledge distillation of generative capacity, SVP focuses on distilling the geometric alignment between vision and language through guided iterative refinement, effectively functioning as *alignment distillation*.

`SVP` can be formalized as a three-step process: *(i) **Sampling**:* a base VLM generates initial descriptions which are processed by a pre-trained grounding model (Liu et al., 2023). The resulting spatial feedback conditions the VLM to produce text that better aligns with the visual input (Fig. 4.(i)). *(ii) **Scoring**:* a scoring mechanism ranks and selects the most informative and visually aligned samples (Fig. 4.(ii)). *(iii) **Adaptation**:* the base VLM is adapted (Hu et al., 2021) using the filtered dataset. Crucially, fine-tuning relies solely on the refined natural language descriptions, excluding any grounding tokens or coordinates (Fig. 4.(iii)).

Contributions Our key contributions are:

- We introduce *Sampling-based Visual Projection (`SVP`)*, a feedback-driven adaptation framework that improves vision-language alignment using self-generated captions and external grounding feedback.

- We formalize SVP as a guided sampling and selective adaptation procedure, where grounding feedback is used during candidate generation and scoring, while final fine-tuning remains text-only.

- We demonstrate the effectiveness of SVP across ten benchmarks covering captioning, referring expression generation, hallucination control, object recall, VQA, and multitask evaluation, showing especially strong gains on grounding-sensitive tasks.

2 Background

(a) Vision-Language Generation   **(b)** Vision-Language Grounding

Figure 3: Visual Projection for Generation (left) and Grounding (right).

Notation We use $p(\mathbf{x}|\mathbf{c})$ and $p(\mathbf{z}|\mathbf{c})$ to denote auto-regressive distributions, where $\mathbf{c}$ is the conditioning information (image and prompt), $\mathbf{z}$ is a visual projection using grounding feedback, and $\mathbf{x}$ is the task-specific output. These distributions follow $p(\mathbf{x}|\mathbf{c}) = p(\mathbf{x}_T|\mathbf{c}) \prod_{t=1}^{T} p(\mathbf{x}_{t-1}|\mathbf{x}_t, \mathbf{c})$, with similar form for

$p(\mathbf{z}|\mathbf{c})$. For latent variables, $\mathbf{z}$ represents trajectories $\mathbf{z}_{1:T_z}$. We assume a deterministic output distribution $p(\mathbf{x}|\mathbf{z}, \mathbf{c}) = \delta(\mathbf{x} - d(\mathbf{z}, \mathbf{c}))$, as is common in tokenization-based models. Given context $\mathbf{c} = (\mathbf{c_v}, \mathbf{c_t})$ with visual input $\mathbf{c_v}$ and text prompt $\mathbf{c_t}$, we define a Visual Projection as $p(\mathbf{z}|\mathbf{c})$ and its grounded version as $q(\mathbf{z}|\mathbf{c}, \mathbf{g})$ when conditioning on grounding $\mathbf{g}$. The conditional entropy is $\mathbb{H}[\mathbf{z}|\mathbf{c}] = -\int_{\mathbf{z}} p(\mathbf{z}|\mathbf{c}) \log p(\mathbf{z}|\mathbf{c})$.

Vision-Language Models Generative VLMs are multimodal systems processing both text and images. LLaVA-like architectures (Fig. 3a, left) integrate a visual encoder $v_\theta(\mathbf{c_v})$, text encoder $t_\theta(\mathbf{c_t})$, visual-text alignment adapter a_θ, and large language model. The model p_θ generates token trajectories $\mathbf{z}$ from conditioning $\mathbf{c}$ for various downstream tasks. These systems undergo three training phases: multimodal pre-training, visual-text alignment, and instruction tuning (Zhu et al., 2023; Liu et al., 2024b; Li et al., 2022a), enabling broad cross-modal capabilities.

Vision-Language Grounding Grounding links language descriptions to spatial regions in images. A grounding model $g(\mathbf{z}, \mathbf{c_v})$ processes visual $\mathbf{c_v}$ and textual $\mathbf{z}$ inputs to produce open-set detection labels and bounding boxes (Fig. 3b, right). While traditional object detection uses fixed-class classification, modern approaches like GLIP (Li et al., 2022b) and GroundingDINO (Liu et al., 2023) reframe detection as text-guided grounding. This flexibility enables broader applications in detection and spatial understanding tasks.

3 Method

Figure 4: SVP Overview. Our framework employs a nested loop for guided refinement, combining data generation with model adaptation. *(i) Sampling:* For each image $\mathbf{c}$, the base VLM generates draft captions. A grounding expert (GDINO) adds spatial feedback $\mathbf{g}$ (e.g., bounding boxes), which acts as context to prompt the VLM for refined, grounded samples. *(ii) Scoring:* We score these samples to quantify improvement, selecting the top-k scoring captions to build a curated training dataset. *(iii) Adaptation:* The base VLM is fine-tuned on this new dataset. Crucially, the optimization targets $\mathbf{z}$ are text-only; bounding box coordinates are excluded from the loss. *(iv) Evaluation:* We validate the adapted VLM on ten benchmarks across six tasks, measuring improved alignment and reduced hallucinations. See Appx Fig. 11 for outputs and Appx G for prompts.

We present *Sampling-based Visual Projection* (SVP), a framework designed to improve vision-language alignment through guided sampling and adaptation. SVP draws inspiration from expert iterations techniques for reasoning in language models (Zelikman et al., 2022; 2024; Gulcehre et al., 2023) and sampling in latent variable models (Jordan et al., 1999; Hoffman et al., 2024).

Intuition To understand SVP, consider a scenario where a base VLM attempts to describe a home office setup (Fig. 1). Initially, the model may hallucinate details, describing a floor lamp where none exists ($\mathbf{z}_p$ in Table 1). For standard generation, this would be an error. However, in the SVP framework, we treat this

Table 1: Overview of symbols and components in the SVP framework, detailing input modalities, grounding mechanisms, and model outputs.

Symbol	Meaning	Description
$\mathbf{c} : (\mathbf{c}_v, \mathbf{c}_t)$	Input (image + prompt)	COCO image + "*Describe this image in details...*"
$\mathbf{z}_p$	Base caption (without grounding)	"*A desk with a lamp and laptop....*"
$\mathbf{g}$	Grounding feedback	`lamp [0.33,0.47,0.16,0.23]`, `laptop [0.48,...]`
$\mathbf{z}$	Guided caption (with grounding)	"*A silver desk lamp on the left, a black laptop in the center...*"
$p_\theta(\mathbf{z}_p \mid \mathbf{c})$	Base Vision-Language Model	Input: image; Output: self-generated caption
$g(\mathbf{z}_p, \mathbf{c}_v)$	Grounding Model	Input: image + base caption; Output: grounding (noun phrases + bounding boxes)
$q(\mathbf{z} \mid \mathbf{c}, \mathbf{g})$	Guided Vision-Language Model	Input: image + grounding; Output: self-generated improved caption

initial caption as a draft. We pass this draft to a grounding model, which acts as an expert guide. The guide fails to ground the `floor lamp` but successfully identifies a `desk lamp` and its coordinates (**g** in Table 1). This spatial feedback is injected back into the VLM, conditioning it to generate a refined projection (**z** in Table 1) that correctly describes a `desk lamp with a curved neck`. By iteratively scoring these grounded samples against the base model's priors, we identify high-quality trajectories to fine-tune the model, effectively transferring the spatial reasoning of the expert guide into the generalist VLM.

The SVP process involves:

(i) **Sampling**, where a base VLM generates initial captions that are then refined using feedback from a pretrained grounding model;

(ii) **Scoring**, where we identify the most informative and well-aligned captions by measuring the difference between the guided and original model outputs; and

(iii) **Adaptation**, where we fine-tune the base VLM on this curated set of high-quality, self-generated data.

In our experiments, we evaluate two variants of this framework. The primary variant, SVP (C), uses only these self-generated captions for fine-tuning. A second variant, SVP (CVQ), augments this data with visual queries from the VLM's original training set to ensure that its question-answering capabilities are preserved during adaptation.

SVP Algorithm (single iteration)

Require: Base VLM p_θ
Require: Grounding Model g
Require: Seed Images $\mathcal{C}$
1:   $\mathcal{D} \leftarrow \emptyset$ ▷ Dataset
2:   **for** each image $\mathbf{c} \in \mathcal{C}$ **do**
3:     **for** $k = 1$ to K **do**
4:       $\mathbf{z}_p \sim p_\theta(\cdot|\mathbf{c})$ ▷ Base Sample
5:       $\mathbf{g} \leftarrow g(\mathbf{z}_p, \mathbf{c})$ ▷ Grounding
6:       $\mathbf{z} \sim q(\cdot|\mathbf{c}, \mathbf{g})$ ▷ Guided Sample
7:       $s \leftarrow S(\mathbf{z}, p_\theta, q)$ ▷ Scoring (Eq. 4-6)
8:     **end for**
9:     $\mathcal{D} \leftarrow \mathcal{D} \cup \texttt{TopK}(\mathbf{z}, s)$ ▷ Select
10:   **end for**
11: Fine-tune p_θ on $\mathcal{D}$ ▷ Adaptation (Eq. 7)
12: **return** $p_{\theta'}$

Visual Projection The core idea of SVP is to generate a comprehensive textual description **z** of the visual input **c**. We refer to this intermediate text as a Visual Projection (VP) because it projects the visual features into the linguistic domain, serving as a bridge for the model's reasoning. These VPs function as latent variables or generalized captions, and SVP aims to refine them through methods guided by external grounding feedback, strengthening the alignment between vision and language modalities to enhance the base VLM's performance across diverse tasks.

Problem Formulation For a VLM represented with a conditional model $p_\theta(\mathbf{x}|\mathbf{c})$, where $\mathbf{c} = (\mathbf{c}_v, \mathbf{c}_t)$ contains visual input and optional text prompt, direct sampling often yields poor alignment between visual and textual modalities. To address this, we introduce a visual projection as a latent variable (Fig 5, left):

$$p_\theta(\mathbf{x}, \mathbf{z}_p|\mathbf{c}) = p(\mathbf{x}|\mathbf{z}_p, \mathbf{c}) \, p_\theta(\mathbf{z}_p|\mathbf{c}), \tag{1}$$

where $\mathbf{z}_p$ acts as an intermediate visual projection bridging vision and language, similar to chain-of-thought (CoT) approaches in LLMs (Wei et al., 2022; Zelikman et al., 2022): just as CoT helps LLMs reason by generating intermediate text steps, VP helps VLMs reason by forcing them to explicitly output (project) what they see into text before answering a question or refining a caption.

To enhance flexibility and control through ancestral sampling, we extend to a hierarchical structure (Fig 5, center):

$$p_\theta(\mathbf{x}, \mathbf{z}, \mathbf{z}_p | \mathbf{c}) = p(\mathbf{x} | \mathbf{z}, \mathbf{c}) \; p(\mathbf{z} | \mathbf{z}_p, \mathbf{c}) \; p_\theta(\mathbf{z}_p | \mathbf{c}). \qquad (2)$$

While this hierarchical structure offers more flexibility, it provides minimal improvement without proper optimization. Simply iterating through the same visual input and refining projections without feedback can lead to model collapse. To address this limitation, we incorporate a grounding model $\mathbf{g} = g(\mathbf{z}_p, \mathbf{c})$ into the hierarchical projection (Fig 5, right):

$$p_\theta^g(\mathbf{x}, \mathbf{z}, \mathbf{z}_p | \mathbf{c}) = p(\mathbf{x} | \mathbf{z}, \mathbf{c}) \; q(\mathbf{z} | g(\mathbf{z}_p, \mathbf{c}), \mathbf{c}) \; p_\theta(\mathbf{z}_p | \mathbf{c}). \qquad (3)$$

Figure 5: Graphical Models for the sampling processes. Left: standard sampling. Center: hierarchical sampling. Right: hierarchical sampling with internal structure.

Here, q is a guided distribution utilizing the grounding model g, which provides specialized feedback for vision-language alignment. This feedback mechanism is particularly effective for improving spatial relationships and object attributes, where grounding helps correct the base model's initial predictions. The discrepancy between base model predictions and grounded outputs serves as a valuable signal for enhancing vision-language alignment, especially in cases where grounding information conflicts with initial model predictions.

Figure 6: Visualization of prior and guided distribution for token t over vocabulary $V = \{\texttt{above}, \texttt{below}, \texttt{circle}, \texttt{rhomboid}\}$. The base model p_θ incorrectly predicts "$\texttt{below}$" for the circle-rhomboid spatial relationship. With grounding feedback, q correctly assigns higher likelihood to "$\texttt{above}$". Using log-ratio and re-weighting with $w(\mathbf{z}_t) \propto q(\mathbf{z}_t | \mathbf{z}_{<t}, \mathbf{c}, \mathbf{g})$ emphasizes grounding-relevant tokens while down-weighting tokens with similar likelihoods in both distributions.

Sampling We implement a guided three-step sampling process to generate improved visual projections: *(i.1)* Prior Sampling, where we generate initial projections $\mathbf{z}_p \sim p_\theta(\mathbf{z}_p | \mathbf{c})$ from the base model. $\mathbf{z}_p$ acts as a draft used solely to obtain feedback. *(i.2)* Grounding, where we apply the grounding model to obtain feedback $\mathbf{g} \leftarrow g(\mathbf{z}_p, \mathbf{c})$; and *(i.3)* Guided Sampling, where we generate guided visual projections $\mathbf{z} \sim q(\mathbf{z} | g(\mathbf{z}_p, \mathbf{c}), \mathbf{c})$. This process repeats K times for each visual input $\mathbf{c}$.

For each guided sample, we evaluate the guided distribution $q(\mathbf{z} | \mathbf{c}, \mathbf{g})$ with grounding feedback $\mathbf{g}$ and the prior distribution $p_\theta(\mathbf{z} | \mathbf{c})$ using the base model. This computation allows us to quantify grounding effects by comparing guided and prior distributions token-wise over the vocabulary, revealing how visual context influences model predictions. For practical implementation, we convert visual grounding to textual form and include it in the prompt as context, rather than using direct visual representation. The complete prompt structure and examples are detailed in Appx G.

Scoring We evaluate sample quality by viewing alignment as a feedback-driven process inspired by policy optimization (Rafailov et al., 2024; Peters & Schaal, 2007; Go et al., 2023). We define a scoring function[1] that measures the *alignment gap* between the guided and prior distributions:

$$S(\mathbf{z}) \propto \log q(\mathbf{z} | \mathbf{c}, \mathbf{g}) - \log p_\theta(\mathbf{z} | \mathbf{c}), \quad \mathbf{z} \sim q(\mathbf{z} | \mathbf{c}, \mathbf{g}). \qquad (4)$$

This score quantifies the effect of grounded visual projection on the model. When grounding provides no additional information, $q(\mathbf{z} | \mathbf{g}, \mathbf{c}) \approx p(\mathbf{z} | \mathbf{z}_p, \mathbf{c})$, and Eq. 3 reduces to Eq. 1. The score approximates the one

---

[1] if we assume that q is the optimal alignment policy, we can write $q(\mathbf{z} | \mathbf{c}, \mathbf{g}) \propto p_\theta(\mathbf{z} | \mathbf{c}) \exp(S(\mathbf{z})/w)$

sample $\mathbb{KL}$ divergence between q and p_θ. Low values indicate token trajectories well-known to the base model[2], while high values reveal *surprising trajectories* that offer learning opportunities. As shown in Fig. 6, the guided distribution q helps correct misaligned predictions of the base model. We implement two scoring approaches. First, a log-ratio scoring:

$$S(q, p)_{\mathbf{z}} = \sum_{t=1}^{T} \sum_{v=1}^{V} w_{v,t} \left[\log q_{v,t} - \log p_{\theta\,v,t} \right] \tag{5}$$

where $w_{v,t} \propto q(\mathbf{z}_t|\mathbf{z}_{<t}, \mathbf{c}, \mathbf{g})$ over-emphasizes grounding-relevant tokens. Second, a weighted-difference scoring:

$$\Delta(q, p)_{\mathbf{z}} = \sum_{t=1}^{T} \sum_{v=1}^{V} w_{v,t}^q \log q_{v,t} - \sum_{t=1}^{T} \sum_{v=1}^{V} w_{v,t}^p \log p_{\theta\,v,t}. \tag{6}$$

The weighted-difference score (Settles, 2009) is inspired by the fact that grounding should reduces prediction uncertainty: $\mathbb{H}[\mathbf{z}|\mathbf{c}, \mathbf{g}] < \mathbb{H}[\mathbf{z}|\mathbf{c}]$. In practice, we find both log-ratio and weighted-difference scoring provide similar ranking signals (correlation analysis in Appx E.11). Crucially, generic surprise alone - in the form of pure exploration - does not improve vision-language alignment. Rather, we hypothesize that grounding conditioning provides informative context that makes surprising instances statistically valuable for learning and alignment.

Adaptation   Inspired by re-weighted regression (Peng et al., 2019) and off-policy policy optimization (Roux et al., 2025; Ahmadian et al., 2024; Gulcehre et al., 2023), we propose an iterative optimization where $q(\mathbf{z}|\mathbf{g}, \mathbf{c})$ serves as a behavioral policy providing high-quality demonstrations, while $p_\theta(\mathbf{z}|\mathbf{c})$ is our target model. We maximize:

$$\tilde{\mathcal{F}}(\mathbf{c}; \theta) = |k(\mathbf{c})|^{-1} \sum_{i=1}^{K} \left[\mathbb{1}\{\mathbf{z}^i : S(q(\mathbf{z}^i|\mathbf{c}, \mathbf{g}), p_\theta(\mathbf{z}^i|\mathbf{c})) \geq S_{k(\mathbf{c})}\} \right]_{\mathbf{sg}} \log p_\theta(\mathbf{z}^i|\mathbf{c}) \tag{7}$$

where $S_{k(\mathbf{c})}$ is the k-th highest score among K samples generated for image $\mathbf{c}$ from the guided distribution, $\{\mathbf{z}^i\}_{i=1}^K \sim q(\mathbf{z}|\mathbf{c}, \mathbf{g})$. Gradients are stopped ($\mathbf{sg}$) over the scores in the indicator function. This objective can be interpreted as both re-weighted maximum likelihood and greedy off-policy optimization (Appx F). While not necessarily optimal for likelihood or policy trajectories, this approach prioritizes vision-language alignment by selectively optimizing better-aligned samples. The final training loss averages this objective over a batch of visual inputs $\mathbf{c}$.

Iterative Loop   Our approach uses a nested structure with two distinct loops. The *inner loop* is a data generation process: for each seed image, we sample, guide, and score multiple candidate captions to create a high-quality dataset of well-aligned image-text pairs. The *outer loop* is a model adaptation process: we use this curated dataset to fine-tune the base VLM's parameters. This two-stage design allows the model to first generate its own feedback-driven training data and then learn from it, creating a virtuous cycle of feedback-driven iterative refinement (Fig. 8, 19). This design creates a natural balance between exploration, achieved through guided sampling, and exploitation, driven by model adaptation on the best aligned samples.

4   Experiments

4.1   Experimental Design

Base Model Selection We selected the LLaVA model family (Liu et al., 2024c) to rigorously validate our method, SVP. LLaVA's straightforward architecture exhibits well-defined capability gaps (Table 4), providing a clear baseline to demonstrate SVP's effectiveness in building foundational visual-language skills. Moreover, its transparent and incrementally expanding open-source datasets [3] allow for a controlled analysis of performance gains, free from evaluation set overlaps or confounding variables like proprietary data or extensive reinforcement fine-tuning. To contextualize our results, we provide comprehensive comparisons against existing methods, with a focus on hallucination reduction (Tables 2 and 3).

---

[2]Since low scores can result from an already grounded projection or a lack of spatial dependency, SVP treats the score as a selection tool for informative samples rather than a metric for groundedness.

[3]https://github.com/haotian-liu/LLaVA/blob/main/docs/Data.md

Table 2: Hallucination Mitigation - F1 scores on POPE benchmark comparing LLaVA variants across adversarial, popular, random, and overall splits. Hallucination avoidance is influenced by model size, fine-tuning approach, encoder selection, and SVP adaptation. See E.9 for analysis of model scaling effects.

Model	Size	v_θ	t_θ	POPE ($F1$ score ↑)			
				adv	pop	random	all
LLaVA (Liu et al., 2024c)	7b	CLIP	Vicuna	72.0	75.3	80.7	76.0
LLaVA-SFT$^+$ (Sun et al., 2023)	7b	CLIP	Vicuna	80.1	82.4	85.5	82.7
LLaVA-RLHF (Sun et al., 2023)	7b	CLIP	Vicuna	79.5	81.8	83.3	81.5
LLaVA (Liu et al., 2024c)	13b	CLIP	Vicuna	74.4	78.2	78.8	77.1
LLaVA-SFT$^+$ (Sun et al., 2023)	13b	CLIP	Vicuna	81.1	82.6	84.8	82.8
LLaVA-RLHF (Sun et al., 2023)	13b	CLIP	Vicuna	80.5	81.8	83.5	81.9
LLaVA-NeXT-DPO (Liu et al., 2024b)	7b	CLIP	Qwen2	83.43	83.78	84.73	83.98
LLaVA-OV-DPO (Li et al., 2024)	7b	SigLIP	Qwen2	85.12	86.24	87.37	86.24
LLaVA-HA-DPO (Zhao et al., 2023)	7b	CLIP	Vicuna	82.54	87.89	90.25	86.90
LLaVA-1.5 (Liu et al., 2024a)	13b	CLIP	Vicuna	84.53	86.31	87.17	86.00
LLaVA-1.5 w/ SVP	13b	CLIP	Vicuna	84.66	86.84	87.44	86.31
LLaVA-1.6 (Liu et al., 2024b)	7b	CLIP	Mistral	85.43	86.87	88.05	86.73
LLaVA-1.6 w/ SVP	7b	CLIP	Mistral	85.93	89.04	90.02	88.33
LLaVA-1.6 (Liu et al., 2024b)	13b	CLIP	Vicuna	85.17	86.36	87.20	86.24
LLaVA-1.6 w/ SVP	13b	CLIP	Vicuna	85.15	87.50	89.23	87.30
LLaVA-OV (Li et al., 2024)	0.5b	SigLIP	Qwen2	82.28	83.19	83.89	83.12
LLaVA-OV w/ SVP	0.5b	SigLIP	Qwen2	83.45	84.70	85.46	84.53
Bigger VLMs							
LLaVA-1.6 (Liu et al., 2024b)	34b	CLIP	Yi-2	-	-	-	87.7
InternVL (Chen et al., 2024b)	19b	IViT	Vicuna	-	-	-	87.6
InternVL-1.2 (Chen et al., 2024b)	40b	IViT	Yi-2	-	-	-	88.0
InternVL-1.2$^+$ (Chen et al., 2024b)	40b	IViT	Yi-2	-	-	-	88.7
VILA-1.5 (Lin et al., 2024)	8b	SigLIP	LLaMA3	-	-	-	85.6
VILA-1.5 (Lin et al., 2024)	8b	SigLIP	Vicuna	-	-	-	86.3
VILA-1.5 (Lin et al., 2024)	40b	IViT	Yi2	-	-	-	87.3
VILA-1.5-AWQ (Lin et al., 2024)	40b	IViT	Yi2	-	-	-	88.2

Table 3: Hallucination Mitigation - Accuracy across VLMs using fine-tuning, train-time, and test-time adaptation approaches. Size (Eff) indicates total parameters for multi-phase inference, e.g., Woodpecker (Wp) (Yin et al., 2023) requires multiple models for response processing. Higher is better.

Model	Size (Eff)	v_θ	t_θ	POPE (Acc score ↑)		
				adv	pop	random
Fine-tuning						
InstructBLIP (Dai et al., 2023)	7b	ViT	FlanT5	72.1	82.7	88.6
LLaVA-SFT$^+$ (Sun et al., 2023)	7b	CLIP	Vicuna	80.2	82.9	86.1
mPLUG-Owl2 (Ye et al., 2024)	8b	ViT	LLaMA2	84.1	86.2	88.3
InstructBLIP (Dai et al., 2023)	13b	ViT	Vicuna	74.5	81.4	88.7
LLaVA-SFT$^+$ (Sun et al., 2023)	13b	CLIP	Vicuna	82.3	83.9	85.2
Test-time adaptation						
QwenVL w/ VCD (Leng et al., 2024)	7b (14b)	CLIP	Vicuna	84.3	87.1	88.6
LLaVA w/ M3ID (Favero et al., 2024)	7b (14b)	CLIP	Vicuna	65.8	69.3	76.0
Otter w/ Wp (Yin et al., 2023)	7b (14b+)	CLIP	LLaMA	83.0	84.3	86.7
mPLUG-Owl w/ Wp (Yin et al., 2023)	7b (14b+)	ViT	LLaMA	81.0	84.1	86.3
LLaVA w/ M3ID (Favero et al., 2024)	13b (26b)	CLIP	Vicuna	71.3	77.0	84.3
Train-time adaptation						
LLaVA-M3ID-DPO (Favero et al., 2024)	7b	CLIP	Vicuna	68.2	73.9	81.2
LLaVA-RLHF (Sun et al., 2023)	7b	CLIP	Vicuna	80.7	83.3	84.8
LLaVA-NeXT-DPO (Rafailov et al., 2024)	7b	CLIP	Qwen2	85.2	85.6	86.6
LLaVA-OV-DPO (Rafailov et al., 2024)	7b	SigLIP	Qwen2	86.3	87.5	88.7
LLaVA-HA-DPO (Zhao et al., 2023)	7b	CLIP	Vicuna	81.5	87.9	90.5
SeVa (Zhu et al., 2024)	7b	CLIP	Vicuna	83.6	87.4	89.4
LLaVA-M3ID-DPO (Favero et al., 2024)	13b	CLIP	Vicuna	73.2	79.1	85.2
LLaVA-RLHF (Sun et al., 2023)	13b	CLIP	Vicuna	82.3	83.9	85.2
InstructBLIP-HA-DPO (Zhao et al., 2023)	13b	ViT	Vicuna	80.7	85.8	89.8
LLaVA-1.6 (Liu et al., 2024b)	7b	CLIP	Mistral	86.4	87.9	89.2
LLaVA-1.6 w/ SVP	7b	CLIP	Mistral	86.2	89.6	90.6
LLaVA-1.6 (Liu et al., 2024b)	13b	CLIP	Vicuna	86.4	87.7	88.5
LLaVA-1.6 w/ SVP	13b	CLIP	Vicuna	86.7	88.4	89.2
LLaVA-OV	0.5b	SigLIP	Qwen2	84.3	85.2	86.0
LLaVA-OV w/ SVP	0.5b	SigLIP	Qwen2	85.0	86.3	87.2

Seed Images We utilize a pretrained GroundingDINO-tiny (GDINO-T) (Liu et al., 2023) as our expert guide for feedback. Our adaptation set consists of $C = 1000$ images randomly sampled from the COCO2014 training set (Lin et al., 2014). We selected the GDINO-T as it was not trained on the COCO dataset. *This design ensures the feedback stems from the guide's generalizable ability to ground the VLM-generated description within the visual context, rather than from memorized annotations.* Furthermore, as these COCO images were part of base LLaVA tuning data, our method isolates the grounding feedback as the sole source of new information for the model, removing confounding factors.

Baselines We conduct a comprehensive comparison against various baselines, including models fine-tuned with self-captioning without grounding and preference-based adaptation methods. Our evaluation encompasses a wide range of model scales (.5B, 7B, 8B, 13B, 19B, 40B parameters), architectures (LLaVA-1.5 (Liu et al., 2024a), LLaVA-1.6 (Liu et al., 2024b), LLaVA-OV (Li et al., 2024), VILA (Lin et al., 2024), InternVL (Chen et al., 2024b)), visual encoders (CLIP (Radford et al., 2021), SigLIP (Zhai et al., 2023), ViT (Dosovitskiy et al., 2020)), language encoders (Vicuna (Chiang et al., 2023), Mistral (Jiang et al., 2023), Qwen2 (Yang et al., 2024), Yi-2 (Young et al., 2024)), and scoring mechanisms $S(q, p)$ and $\Delta(q, p)$.

Implementation Details Here we detail the core setup for the experiments with LLaVA-1.5/1.6. We implement two SVP variants: SVP (C), using self-generated descriptions, and SVP (CVQ), which adds visual queries (already seen by the base models) to prevent over-specialization. For the sampling loop, we generate $K = 20$ samples for each of $C = 1000$ images, selecting the top-20% with our scoring mechanisms (Eq. 5, 6) to yield 4000/8000 training pairs, a size shown to be effective for adaptation (Sun et al., 2023; Zhu et al., 2024). For the adaptation loop, we fine-tune for one epoch on 8-A100 GPUs ($B = 20$) using LoRA (Hu et al., 2021), with α and r scaled to model size ($\alpha = 16, r = 64$ for ≤7b; $\alpha = 256, r = 128$ for 13b). Following prior work (Li et al., 2024; Liu et al., 2024b), we run up to 3 SVP iterations. We use normalized *xyxy* boxes and filter degenerate samples ($< 0.5\%$) We feed the output of the grounding model to the VLM as context *without* any post-processing or filtering. Our evaluation uses sample-wise, zero-shot testing without prompt engineering or batching to ensure fair comparison across model variants. More details in Appendix K.

Metrics We use the CIDEr score (Vedantam et al., 2015) for captioning and referring tasks; accuracy for VQA and multitasking. F1, Accuracy and Recall for hallucination and object recall. We also consider

standard metrics for language translation like BLEU (Papineni et al., 2002), METEOR (Banerjee & Lavie, 2005), and ROUGE (Lin, 2004) scores. We re-compute metrics for LLaVA baselines and variants (1.5, 1.6, OV) up to 13b parameters.

4.2 Vision-Language Benchmarks

Table 4: Benchmark Performance across LLaVA variants (7B/13B) with same visual encoder (CLIP) and varying the text encoders (Mistral and Vicuna) evaluated using `lmms-eval` (`lite` split, full MMMU, POPE, and ScienceQA). Results show `SVP` (C) and `SVP` (CVQ) improve captioning, referring tasks, and object recall while reducing hallucinations, maintaining strong performance on multitask benchmarks. Higher is better.

Model	v_θ	t_θ	VQA ScienceQA test	GQA test	NoCaps val	Captioning COCO2017 val	Flickr30k test	Referring RefCOCO val	Multitasking MMBench en_dev	MMMU val	Hallucinations POPE (F1) all	POPE (R) all
LLaVA-1.6-7b	CLIP	Mistral	**78.54**	**75.80**	92.60	109.68	78.74	6.70	**80.30**	34.11	86.73	79.60
w/ SVP (C)	CLIP	Mistral	77.24	73.80	100.93	112.95	83.49	18.15	77.27	36.44	**88.33**	**84.20**
w/ SVP (CVQ)	CLIP	Mistral	78.40	75.10	**103.95**	**115.02**	**85.31**	24.74	78.03	**37.44**	88.25	84.41
			↓ 0.54 %			↑ 8.48 %		↑ 18.04	↑ 3.43 %		↑ 3.94 %	
LLaVA-1.6-13b	CLIP	Vicuna	70.30	**74.60**	83.89	104.21	69.86	**29.71**	**83.33**	35.22	86.24	78.13
w/ SVP (C)	CLIP	Vicuna	**74.34**	74.40	87.09	111.09	71.43	28.93	81.06	**36.33**	87.44	81.20
w/ SVP (CVQ)	CLIP	Vicuna	68.49	73.20	**100.26**	**122.03**	**85.32**	27.20	78.03	35.66	87.68	82.53
			↑ 2.65 %			↑ 19.58 %		↓ 0.78	↑ 0.12 %		↑ 3.65 %	

Datasets We evaluate SVP across six tasks using ten standard VLM benchmarks: COCO2017 (Lin et al., 2014), NoCaps (Agrawal et al., 2019), and Flickr30k (Plummer et al., 2015) for captioning; RefCOCO variants (Kazemzadeh et al., 2014) for referring expression generation; ScienceQA (Saikh et al., 2022) and GQA (Hudson & Manning, 2019) for VQA; MMBench (Liu et al., 2025) and MMMU (Yue et al., 2024) for multitasking; and POPE (Li et al., 2023b) for hallucination assessment. Following lmms-eval (Zhang et al., 2024b), we use both full and lite evaluation sets for captioning and VQA tasks to demonstrate result stability across sample sizes. For MMMU, POPE, and all RefCOCO variants, we use the complete evaluation sets.

General Results Across the 10 datasets and 6 tasks evaluated (Fig. 2 and Table 4), our method demonstrates significant improvements in captioning, referring expression generation, hallucination control, and object recall. We maintain comparable or improved performance on multitasking benchmarks and VQA tasks. The most substantial gains appear in captioning, with nearly 20% improvement, while performance remains stable even in challenging tasks like visual question answering.

The impact of `SVP` is especially dramatic for models with initial weaknesses in specific tasks. For instance, when applied to LLaVA with Mistral, which originally shows poor referring capabilities, SVP improves referring expression generation performance by a factor of three (Fig. 2a). The preservation of VQA performance is particularly significant, as it indicates that our method *enhances vision-language alignment without compromising existing capabilities* or requiring task-specific knowledge injection. This balanced improvement highlights SVP's ability to strengthen fundamental cross-modal understanding while maintaining the model's broader base capabilities.

Captioning Tasks We conducted extensive captioning experiments using both 7B and 13B model architectures across three standard datasets: COCO2017, Flickr30k, and NoCaps (Fig. 2b). Our comprehensive evaluation, detailed in Tables 11 and 12, spans four datasets and employs four widely-accepted metrics for assessing language generation and alignment quality. The evaluation encompasses over 80,000 samples, providing robust statistical evidence for our findings.

SVP demonstrates consistent superior performance across all datasets and metrics compared to existing methods. This comprehensive improvement underscores the effectiveness of our integrated sampling and feedback approach in enhancing image captioning capabilities. More fundamentally, these results validate our core hypothesis: strengthening vision-language alignment serves as a foundational principle for advancing VLM capabilities.

Referring Tasks We evaluate model performance on referring expression tasks, which require the VLM to generate descriptions for specific image regions (Fig. 7 and Appx 16). Since our adaptation targets are purely textual (containing no bounding boxes), the model learns to generate improved referring expressions solely through the distilled alignment of the linguistic features.

Our analysis compares four model variants: a baseline model, a model tuned without grounding (w/o **g**), a model incorporating visual grounding (w/ SVP (C)), and our full model with both grounding and visual queries (w/ SVP (CVQ)). The results demonstrate that SVP substantially improves performance across all datasets and tasks. Most notably, SVP significantly enhances the base model's ability to understand and describe spatial relationships, particularly in cases where initial performance is poor. In fact, our enhanced models achieve performance levels approaching those of much larger 13B parameter models (Table 4).

Figure 7: Referring Expression Generation on RefCOCO comparing base LLaVA-1.6-7b versus SVP (C) and SVP (CVQ) variants. CIDEr scores shown for detection (`bbox`) and segmentation (`seg`) on test/validation sets. SVP models outperform baseline without using bounding boxes. Appx 16 for RefCOCO+ and RefCOCOg results.

A key insight emerges from these results: these improvements occur without direct access to grounding information (bounding boxes) during the adaptation phase. The grounding conditioning **g** is utilized only during the inner-loop sampling to construct $q(\mathbf{z}|\mathbf{c}, \mathbf{g})$ (Fig. 4.(*iii*)), after which we adapt model parameters θ using only the refined visual projections **z**. This success in improving referring abilities without explicit grounding supervision suggests that enhanced modality alignment naturally leads to better spatial understanding in VLMs.

Table 5: Component Ablation. Performance comparison of LLaVA-1.6-7b variants after one adaptation iteration: base model, fine-tuning without feedback, sampling with grounding (no scoring), grounding with scoring, and full SVP (grounding, scoring, visual queries). Results provide evidence of the importance of the SVP's components for model performance.

Model	Grounding	Scoring	VQ	RefCOCO	Flickr30k	MMMU	POPE
LLaVA	-	-	-	6.70	78.74	34.11	86.73
w/o SVP	✗	✗	✗	3.01	79.03	35.55	87.21
w/ SVP	✓	✗	✗	9.98	78.67	35.77	86.92
w/ SVP	✓	✓	✗	18.15	83.49	36.44	**88.33**
w/ SVP	✓	✓	✓	**24.74**	**85.31**	**37.44**	88.25

Table 6: Preference Ablation. Comparison between SVP and DPO (Rafailov et al., 2024) for LLaVA-7b-OV with Qwen2 language model (higher is better). While DPO requires a learned reward model or human preference pairs, SVP uses only a small grounding model for feedback ($C = 2000$, $K = 10$, top-10%). Results show that DPO, while effective for general preference alignment, does not achieve the visual-language alignment gains of SVP.

Model	Samples	SciQA	NoCaps	RefCOCO	MMBench	POPE
w/ DPO	$\geq 9.4k$	79.25	112.51	13.60	85.60	**86.24**
w/ SVP (C)	$\approx 2k$	**83.89**	**120.23**	**15.75**	**86.36**	85.78

Hallucination and Object Recall We evaluate our model's hallucination rate (Tables 2 and 3) and object recall (Figs. 2c and 8), where object recall measures the model's ability to capture visual elements in its textual output. Our comparison includes HA-DPO (Zhao et al., 2023), the leading DPO (Rafailov et al., 2024) variant for hallucination reduction, and CSR (Zhou et al., 2024b), an iterative self-rewarding VLM mechanism. For CSR, we evaluate both single-iteration performance and the best result across iterations $I \in [1 : 5]$. SVP demonstrates substantial improvements across most model variants on the POPE dataset. With the 7B model, SVP raises the F1 score from 86.7% to 88.3%, achieving performance comparable to models five times larger (E.9).

Similarly, the 13B model shows improvement from 86.2% to 87.5%. Most impressively, when running SVP for three iterations with our scoring mechanism (Eq. 5), object recall improves dramatically from 79% to over 87% (Fig. 8). These results provide strong evidence that enhancing modality alignment through self-captioning and grounding feedback effectively reduces hallucinations without requiring specialized fine-tuning. This

Figure 8: Iterations. Halluci-nations (F1) and object recall (R) results with $C = 1000$ for $I = 3$ iterations with $\Delta(q, p)$ and $S(q, p)$ scores.

Figure 9: Sample Size. Hal-lucinations (F1) and object recall (R) results with $I = 1$ a single it-eration increasing the sample size $C \in (0.1, 0.2, 0.5, 1, 5, 10)k$.

Figure 10: Distribution of ground-able objects in captions from base model $p_\theta(\mathbf{z}|\mathbf{c})$ and grounded model $q(\mathbf{z}|\mathbf{c}, \mathbf{g})$. SVP guided models gener-ate fewer hallucinated objects.

validates our core hypothesis while demonstrating SVP's ability to significantly improve the model's factual accuracy and reliability. Notice that naively finetuning a strong VLM on a larger multimodal dataset does not improve hallucination or recall, as shown in Table 13, providing evidence that methods like SVP are necessary to align vision and language.

Ablations We conduct comprehensive ablation studies to analyze SVP's components and behavior. First, we examine the individual contributions of grounding, scoring, and visual queries (Table 5). We then investigate the impact of key hyperparameters: the number of iterations I (Fig. 8, Appx 19) and sample size C (Fig. 9). For scoring mechanisms, we evaluate both $\Delta(q, p)$ and $S(q, p)$ on the full captioning benchmark (Tables 11 and 12). We also compare SVP against DPO using Qwen2 (Yang et al., 2024) as the language model on a subset of our benchmark (Table 6). Additionally, we explore iSVP, a variant designed for inference-time adaptation without parameter tuning (Table 9, Fig. 13, Fig. 14). Finally, we quantify the set of groundable objects for captions generated by guided versus prior distributions (Fig. 10).

Comparison with Qwen-VL Table 7 compares Qwen2-VL and Qwen2.5-VL with LLaVA-1.6-7b w/ SVP on POPE. Despite using roughly two orders of magnitude fewer multimodal samples (800K vs. 100M+), LLaVA-1.6-7b w/ SVP achieves the best hallucination performance, with the highest F1 and recall across all subsets. This indicates that simply scaling multimodal finetuning data is insufficient to fix vision-language misalignment in strong VLMs, whereas targeted adaptation such as SVP is more effective. As shown in Table 8,

Table 7: Hallucination (F1) and Recall (R) using Qwen2-VL7b and Qwen2.5-VL-7b on the POPE dataset. Naively scaling the multimodal finetuning dataset does not solve visual-language alignment in powerful VLMs.

Name	Multimodal Samples	F1 (all - 9k)	F1 (adv - 3k)	F1 (pop - 3k)	F1 (random - 3k)	Recall (all - 9k)
Qwen2-VL-7b	100M	87.8	**85.8**	87.9	89.8	83.4
Qwen2.5-VL-7b	100M+	86.2	85.1	86.1	87.1	77.9
LLaVA-1.6-7b w/ SVP	800K	**88.3**	**85.9**	**89.1**	**90.1**	**84.4**

applying SVP to Qwen2.5-VL-7b similarly yields substantial gains in both F1 and recall without additional large-scale pretraining, providing evidence that SVP is a general mechanism to improve vision-language alignment.

5 Related Work

Improving Vision-Language Models Enhancing vision-language alignment in VLMs is an active research area. Explicit grounding in generative VLMs (Li et al., 2024; 2022a; Chen et al., 2024a) has primarily addressed hallucinations (Wan et al., 2024; Favero et al., 2024). Common strategies include incorporating grounding annotations into training data (Peng et al., 2024) for vision-centric VLMs (Beyer et al., 2024; Yuan et al., 2021; You et al., 2023; Zhang et al., 2025), though this process is costly and error-prone. Explicit supervision during fine-tuning can enhance alignment (Liu et al., 2024a; Sun et al., 2023) but requires extensive high-quality data. Techniques like

Table 8: Hallucination (F1) and Recall (R) using Qwen2.5-VL-7b w/o and w/ SVP adaptation. SVP can improve vision-language alignment in powerful VLM models.

Name	F1	Recall
Qwen2.5-VL-7b	86.2	77.9
Qwen2.5-VL-7b w/ SVP	**89.1**	**83.7**

RLHF (Ouyang et al., 2022) and DPO (Rafailov et al., 2024), originally for LLMs, have been adapted to align VLM outputs with visual inputs (Zhou et al., 2024a; Sun et al., 2023; Zhu et al., 2024). These post-training approaches incorporate feedback (Sun et al., 2023; Favero et al., 2024) but are limited by the need for reward signals and curated preference pairs. Test-time methods (Wan et al., 2024), such as Visual Contrastive Decoding (Leng et al., 2024) and Multi-Modal Mutual-Information Decoding (Favero et al., 2024), aim to improve grounding at inference without altering model architecture or training. Woodpecker (Yin et al., 2023) proposes a five-step inference procedure to mitigate hallucination. While effective, these methods often require memory-intensive computation and model-specific heuristics, limiting their usage.

Grounding Models Visual grounding, the dual of text-image alignment, organizes information within VLMs, aligning visual and textual modalities in both representation and generation. The concept of grounding has deep roots in cognitive sciences (Kiefer & Barsalou, 2013; Barsalou, 2008; Anderson, 2010; Glenberg & Kaschak, 2002). In the context of computer vision, visual grounding can be seen as an extension of the classic closed-set detection problem (Girshick et al., 2014; Carion et al., 2020; Redmon, 2016; Zhang et al., 2022). Traditional object detection, using curated datasets (Lin et al., 2014), has improved precision and speed but struggles with scaling to larger class sets and varying detection granularity's (Gupta et al., 2019; Dave et al., 2021). Visual grounding inverts this approach, using class sets as input to assign bounding boxes, generalizing to accommodate various textual inputs. Contrastive models like GLIP (Li et al., 2022b) and GroundingDINO (Liu et al., 2023) offer flexible, generalized detection models, enhancing spatial understanding (Yin et al., 2023) and supporting diverse tasks. Auto-regressive VLMs have further expanded capabilities in grounding and referring tasks (Yuan et al., 2021; You et al., 2023; Peng et al., 2024; Tong et al., 2024), bridging visual and linguistic information more effectively.

See Appendix A for extended related work.

6 Conclusion and Limitations

We present `SVP`, a novel method that leverages self-captioning and grounding feedback to enhance VLMs without requiring additional annotations. Our approach significantly improves captioning quality, referring expression generation, hallucination control, and object recall while maintaining strong performance on VQA and multitasking benchmarks. These results demonstrate `SVP`'s potential to unlock latent VLM capabilities, advancing toward more robust real-world applications, like 3D designs and video generation.

Limitations However, `SVP` has limitations: it requires VLMs capable of in-context learning, relies multiple samples per input, and feedback depends on the availability of a pre-trained grounding model. The method may not benefit tasks without spatial components or those requiring specialized knowledge, such as VQA. Additionally, without injecting new information, its applicability to knowledge-intensive tasks remains uncertain without external data.

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.

Harsh Agrawal, Karan Desai, Yufei Wang, Xinlei Chen, Rishabh Jain, Mark Johnson, Dhruv Batra, Devi Parikh, Stefan Lee, and Peter Anderson. Nocaps: Novel object captioning at scale. In *Proceedings of the IEEE/CVF international conference on computer vision*, pp. 8948–8957, 2019.

Arash Ahmadian, Chris Cremer, Matthias Gallé, Marzieh Fadaee, Julia Kreutzer, Olivier Pietquin, Ahmet Üstün, and Sara Hooker. Back to basics: Revisiting reinforce style optimization for learning from human feedback in llms. *arXiv preprint arXiv:2402.14740*, 2024.

Ekin Akyürek, Dale Schuurmans, Jacob Andreas, Tengyu Ma, and Denny Zhou. What learning algorithm is in-context learning? investigations with linear models. *arXiv preprint arXiv:2211.15661*, 2022.

Michael L Anderson. Neural reuse: A fundamental organizational principle of the brain. *Behavioral and brain sciences*, 33(4):245–266, 2010.

Thomas Anthony, Zheng Tian, and David Barber. Thinking fast and slow with deep learning and tree search. *Advances in neural information processing systems*, 30, 2017.

Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, et al. Constitutional ai: Harmlessness from ai feedback. *arXiv preprint arXiv:2212.08073*, 2022.

Zechen Bai, Pichao Wang, Tianjun Xiao, Tong He, Zongbo Han, Zheng Zhang, and Mike Zheng Shou. Hallucination of multimodal large language models: A survey. *arXiv preprint arXiv:2404.18930*, 2024.

Satanjeev Banerjee and Alon Lavie. Meteor: An automatic metric for mt evaluation with improved correlation with human judgments. In *Proceedings of the acl workshop on intrinsic and extrinsic evaluation measures for machine translation and/or summarization*, pp. 65–72, 2005.

Lawrence W Barsalou. Grounded cognition. *Annu. Rev. Psychol.*, 59(1):617–645, 2008.

Lucas Beyer, Andreas Steiner, André Susano Pinto, Alexander Kolesnikov, Xiao Wang, Daniel Salz, Maxim Neumann, Ibrahim Alabdulmohsin, Michael Tschannen, Emanuele Bugliarello, et al. Paligemma: A versatile 3b vlm for transfer. *arXiv preprint arXiv:2407.07726*, 2024.

Florian Bordes, Richard Yuanzhe Pang, Anurag Ajay, Alexander C Li, Adrien Bardes, Suzanne Petryk, Oscar Mañas, Zhiqiu Lin, Anas Mahmoud, Bargav Jayaraman, et al. An introduction to vision-language modeling. *arXiv preprint arXiv:2405.17247*, 2024.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. 2020. URL https://proceedings.neurips.cc/paper/2020/hash/1457c0d6bfcb4967418bfb8ac142f64a-Abstract.html.

Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *European conference on computer vision*, pp. 213–229. Springer, 2020.

Zhe Chen, Weiyun Wang, Hao Tian, Shenglong Ye, Zhangwei Gao, Erfei Cui, Wenwen Tong, Kongzhi Hu, Jiapeng Luo, Zheng Ma, et al. How far are we to gpt-4v? closing the gap to commercial multimodal models with open-source suites. *arXiv preprint arXiv:2404.16821*, 2024a.

Zhe Chen, Jiannan Wu, Wenhai Wang, Weijie Su, Guo Chen, Sen Xing, Muyan Zhong, Qinglong Zhang, Xizhou Zhu, Lewei Lu, et al. Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 24185–24198, 2024b.

Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E Gonzalez, et al. Vicuna: An open-source chatbot impressing gpt-4 with 90%* chatgpt quality. *See https://vicuna. lmsys. org (accessed 14 April 2023)*, 2(3):6, 2023.

Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. *Advances in neural information processing systems*, 30, 2017.

Daniel Collerton, James Barnes, Nico J Diederich, Rob Dudley, Karl Friston, Christopher G Goetz, Jennifer G Goldman, Renaud Jardri, Jaime Kulisevsky, Simon JG Lewis, et al. Understanding visual hallucinations: A new synthesis. *Neuroscience & Biobehavioral Reviews*, 150:105208, 2023.

Wenliang Dai, Junnan Li, Dongxu Li, Anthony Meng Huat Tiong, Junqi Zhao, Weisheng Wang, Boyang Li, Pascale Fung, and Steven Hoi. Instructblip: Towards general-purpose vision-language models with instruction tuning, 2023. URL https://arxiv.org/abs/2305.06500.

Achal Dave, Piotr Dollár, Deva Ramanan, Alexander Kirillov, and Ross Girshick. Evaluating large-vocabulary object detectors: The devil is in the details. *arXiv preprint arXiv:2102.01066*, 2021.

Hanze Dong, Wei Xiong, Deepanshu Goyal, Yihan Zhang, Winnie Chow, Rui Pan, Shizhe Diao, Jipeng Zhang, Kashun Shum, and Tong Zhang. Raft: Reward ranked finetuning for generative foundation model alignment. *arXiv preprint arXiv:2304.06767*, 2023.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

Alessandro Favero, Luca Zancato, Matthew Trager, Siddharth Choudhary, Pramuditha Perera, Alessandro Achille, Ashwin Swaminathan, and Stefano Soatto. Multi-modal hallucination control by visual information grounding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14303–14312, 2024.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. 70:1126–1135, 2017. URL http://proceedings.mlr.press/v70/finn17a.html.

Ross Girshick, Jeff Donahue, Trevor Darrell, and Jitendra Malik. Rich feature hierarchies for accurate object detection and semantic segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 580–587, 2014.

Arthur M Glenberg and Michael P Kaschak. Grounding language in action. *Psychonomic bulletin & review*, 9(3):558–565, 2002.

Dongyoung Go, Tomasz Korbak, Germán Kruszewski, Jos Rozen, Nahyeon Ryu, and Marc Dymetman. Aligning language models with preferences through f-divergence minimization. *arXiv preprint arXiv:2302.08215*, 2023.

Caglar Gulcehre, Tom Le Paine, Srivatsan Srinivasan, Ksenia Konyushkova, Lotte Weerts, Abhishek Sharma, Aditya Siddhant, Alex Ahern, Miaosen Wang, Chenjie Gu, et al. Reinforced self-training (rest) for language modeling. *arXiv preprint arXiv:2308.08998*, 2023.

Agrim Gupta, Piotr Dollar, and Ross Girshick. Lvis: A dataset for large vocabulary instance segmentation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 5356–5364, 2019.

John Hattie and Helen Timperley. The power of feedback. *Review of educational research*, 77(1):81–112, 2007.

Yuting He, Fuxiang Huang, Xinrui Jiang, Yuxiang Nie, Minghao Wang, Jiguang Wang, and Hao Chen. Foundation model for advancing healthcare: Challenges, opportunities, and future directions. *arXiv preprint arXiv:2404.03264*, 2024.

Matthew Douglas Hoffman, Du Phan, David Dohan, Sholto Douglas, Tuan Anh Le, Aaron Parisi, Pavel Sountsov, Charles Sutton, Sharad Vikram, and Rif A Saurous. Training chain-of-thought via latent-variable inference. *Advances in Neural Information Processing Systems*, 36, 2024.

Timothy Hospedales, Antreas Antoniou, Paul Micaelli, and Amos Storkey. Meta-learning in neural networks: A survey. *ArXiv preprint*, abs/2004.05439, 2020. URL https://arxiv.org/abs/2004.05439.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021.

Drew A Hudson and Christopher D Manning. Gqa: A new dataset for real-world visual reasoning and compositional question answering. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 6700–6709, 2019.

Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. Mistral 7b. *arXiv preprint arXiv:2310.06825*, 2023.

Michael I Jordan, Zoubin Ghahramani, Tommi S Jaakkola, and Lawrence K Saul. An introduction to variational methods for graphical models. *Machine learning*, 37(2):183–233, 1999.

Junmo Kang, Leonid Karlinsky, Hongyin Luo, Zhen Wang, Jacob Hansen, James Glass, David Cox, Rameswar Panda, Rogerio Feris, and Alan Ritter. Self-moe: Towards compositional large language models with self-specialized experts. *arXiv preprint arXiv:2406.12034*, 2024a.

Junmo Kang, Hongyin Luo, Yada Zhu, Jacob Hansen, James Glass, David Cox, Alan Ritter, Rogerio Feris, and Leonid Karlinsky. Self-specialization: Uncovering latent expertise within large language models. In *Findings of the Association for Computational Linguistics ACL 2024*, pp. 2681–2706, 2024b.

Sahar Kazemzadeh, Vicente Ordonez, Mark Matten, and Tamara Berg. Referitgame: Referring to objects in photographs of natural scenes. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pp. 787–798, 2014.

Markus Kiefer and Lawrence W Barsalou. Grounding the human conceptual system in perception, action, and internal states. 2013.

Black Forest Labs. Flux. https://github.com/black-forest-labs/flux, 2024.

Sicong Leng, Hang Zhang, Guanzheng Chen, Xin Li, Shijian Lu, Chunyan Miao, and Lidong Bing. Mitigating object hallucinations in large vision-language models through visual contrastive decoding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13872–13882, 2024.

Bo Li, Yuanhan Zhang, Dong Guo, Renrui Zhang, Feng Li, Hao Zhang, Kaichen Zhang, Yanwei Li, Ziwei Liu, and Chunyuan Li. Llava-onevision: Easy visual task transfer. *arXiv preprint arXiv:2408.03326*, 2024.

Junnan Li, Dongxu Li, Caiming Xiong, and Steven Hoi. Blip: Bootstrapping language-image pre-training for unified vision-language understanding and generation. In *ICML*, 2022a.

Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. In *International conference on machine learning*, pp. 19730–19742. PMLR, 2023a.

Liunian Harold Li, Pengchuan Zhang, Haotian Zhang, Jianwei Yang, Chunyuan Li, Yiwu Zhong, Lijuan Wang, Lu Yuan, Lei Zhang, Jenq-Neng Hwang, et al. Grounded language-image pre-training. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10965–10975, 2022b.

Yifan Li, Yifan Du, Kun Zhou, Jinpeng Wang, Wayne Xin Zhao, and Ji-Rong Wen. Evaluating object hallucination in large vision-language models. *arXiv preprint arXiv:2305.10355*, 2023b.

Chin-Yew Lin. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*, pp. 74–81, 2004.

Ji Lin, Hongxu Yin, Wei Ping, Pavlo Molchanov, Mohammad Shoeybi, and Song Han. Vila: On pre-training for visual language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 26689–26699, 2024.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *Computer Vision–ECCV 2014: 13th European Conference, Zurich, Switzerland, September 6-12, 2014, Proceedings, Part V 13*, pp. 740–755. Springer, 2014.

Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. Improved baselines with visual instruction tuning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 26296–26306, 2024a.

Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. Llava-next: Improved reasoning, ocr, and world knowledge, 2024b.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *Advances in neural information processing systems*, 36, 2024c.

Shilong Liu, Zhaoyang Zeng, Tianhe Ren, Feng Li, Hao Zhang, Jie Yang, Chunyuan Li, Jianwei Yang, Hang Su, Jun Zhu, et al. Grounding dino: Marrying dino with grounded pre-training for open-set object detection. *arXiv preprint arXiv:2303.05499*, 2023.

Yuan Liu, Haodong Duan, Yuanhan Zhang, Bo Li, Songyang Zhang, Wangbo Zhao, Yike Yuan, Jiaqi Wang, Conghui He, Ziwei Liu, et al. Mmbench: Is your multi-modal model an all-around player? In *European Conference on Computer Vision*, pp. 216–233. Springer, 2025.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, et al. Self-refine: Iterative refinement with self-feedback. *Advances in Neural Information Processing Systems*, 36, 2024.

Maxime Oquab, Leon Bottou, Ivan Laptev, and Josef Sivic. Learning and transferring mid-level image representations using convolutional neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1717–1724, 2014.

Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *arXiv preprint arXiv:2203.02155*, 2022.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association for Computational Linguistics*, pp. 311–318, 2002.

Jonathan W Peirce. Understanding mid-level representations in visual processing. *Journal of Vision*, 15(7): 5–5, 2015.

Xue Bin Peng, Aviral Kumar, Grace Zhang, and Sergey Levine. Advantage-weighted regression: Simple and scalable off-policy reinforcement learning. *arXiv preprint arXiv:1910.00177*, 2019.

Zhiliang Peng, Wenhui Wang, Li Dong, Yaru Hao, Shaohan Huang, Shuming Ma, Qixiang Ye, and Furu Wei. Grounding multimodal large language models to the world. In *The Twelfth International Conference on Learning Representations*, 2024.

Jan Peters and Stefan Schaal. Reinforcement learning by reward-weighted regression for operational space control. In *Proceedings of the 24th international conference on Machine learning*, pp. 745–750, 2007.

Renjie Pi, Jianshu Zhang, Jipeng Zhang, Rui Pan, Zhekai Chen, and Tong Zhang. Image textualization: An automatic framework for creating accurate and detailed image descriptions. *arXiv preprint arXiv:2406.07502*, 2024.

Cyril Picard, Kristen M Edwards, Anna C Doris, Brandon Man, Giorgio Giannone, Md Ferdous Alam, and Faez Ahmed. From concept to manufacturing: Evaluating vision-language models for engineering design. *arXiv preprint arXiv:2311.12668*, 2023.

Bryan A Plummer, Liwei Wang, Chris M Cervantes, Juan C Caicedo, Julia Hockenmaier, and Svetlana Lazebnik. Flickr30k entities: Collecting region-to-phrase correspondences for richer image-to-sentence models. In *Proceedings of the IEEE international conference on computer vision*, pp. 2641–2649, 2015.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pp. 8748–8763. PMLR, 2021.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. *Advances in Neural Information Processing Systems*, 36, 2024.

Pooyan Rahmanzadehgervi, Logan Bolton, Mohammad Reza Taesiri, and Anh Totti Nguyen. Vision language models are blind. *arXiv preprint arXiv:2407.06581*, 2024.

J Redmon. You only look once: Unified, real-time object detection. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2016.

Nicolas Le Roux, Marc G Bellemare, Jonathan Lebensold, Arnaud Bergeron, Joshua Greaves, Alex Fréchette, Carolyne Pelletier, Eric Thibodeau-Laufer, Sándor Toth, and Sam Work. Tapered off-policy reinforce: Stable and efficient reinforcement learning for llms. *arXiv preprint arXiv:2503.14286*, 2025.

Tanik Saikh, Tirthankar Ghosal, Amish Mittal, Asif Ekbal, and Pushpak Bhattacharyya. Scienceqa: A novel resource for question answering on scholarly articles. *International Journal on Digital Libraries*, 23(3): 289–301, 2022.

Kuleen Sasse, Shan Chen, Jackson Pond, Danielle Bitterman, and John Osborne. Mapping bias in vision language models: Signposts, pitfalls, and the road ahead. *arXiv preprint arXiv:2410.13146*, 2024.

Tom Schaul and Jürgen Schmidhuber. Metalearning. *Scholarpedia*, 5(6):4650, 2010.

Juergen Schmidhuber. A general method for incremental self-improvement and multi-agent learning. In *Evolutionary Computation: Theory and Applications*, pp. 81–123. World Scientific, 1999.

Jürgen Schmidhuber. *Evolutionary principles in self-referential learning, or on learning how to learn: the meta-meta-... hook.* PhD thesis, Technische Universität München, 1987.

Burr Settles. Active learning literature survey. 2009.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. *Advances in Neural Information Processing Systems*, 36, 2024.

David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of go with deep neural networks and tree search. *nature*, 529(7587):484–489, 2016.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *nature*, 550(7676):354–359, 2017.

Binyang Song, Rui Zhou, and Faez Ahmed. Multi-modal machine learning in engineering design: A review and future directions. *Journal of Computing and Information Science in Engineering*, 24(1):010801, 2024.

Shivchander Sudalairaj, Abhishek Bhandwaldar, Aldo Pareja, Kai Xu, David D Cox, and Akash Srivastava. Lab: Large-scale alignment for chatbots. *arXiv preprint arXiv:2403.01081*, 2024.

Zhiqing Sun, Sheng Shen, Shengcao Cao, Haotian Liu, Chunyuan Li, Yikang Shen, Chuang Gan, Liang-Yan Gui, Yu-Xiong Wang, Yiming Yang, et al. Aligning large multimodal models with factually augmented rlhf. *arXiv preprint arXiv:2309.14525*, 2023.

Zhiqing Sun, Yikang Shen, Qinhong Zhou, Hongxin Zhang, Zhenfang Chen, David Cox, Yiming Yang, and Chuang Gan. Principle-driven self-alignment of language models from scratch with minimal human supervision. *Advances in Neural Information Processing Systems*, 36, 2024.

Gershon Tenenbaum and Ellen Goldring. A meta-analysis of the effect of enhanced instruction: cues, participation, reinforcement and feedback and correctives on motor skill learning. *Journal of Research & Development in Education*, 1989.

Joshua B Tenenbaum, Charles Kemp, Thomas L Griffiths, and Noah D Goodman. How to grow a mind: Statistics, structure, and abstraction. *science*, 331(6022):1279–1285, 2011.

Shengbang Tong, Ellis Brown, Penghao Wu, Sanghyun Woo, Manoj Middepogu, Sai Charitha Akula, Jihan Yang, Shusheng Yang, Adithya Iyer, Xichen Pan, et al. Cambrian-1: A fully open, vision-centric exploration of multimodal llms. *arXiv preprint arXiv:2406.16860*, 2024.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023.

Giuseppe Vallar. Spatial neglect, balint-homes' and gerstmann's syndrome, and other spatial disorders. *Cns Spectrums*, 12(7):527–536, 2007.

Ramakrishna Vedantam, C Lawrence Zitnick, and Devi Parikh. Cider: Consensus-based image description evaluation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4566–4575, 2015.

David Wan, Jaemin Cho, Elias Stengel-Eskin, and Mohit Bansal. Contrastive region guidance: Improving grounding in vision-language models without training. *arXiv preprint arXiv:2403.02325*, 2024.

Xiyao Wang, Jiuhai Chen, Zhaoyang Wang, Yuhang Zhou, Yiyang Zhou, Huaxiu Yao, Tianyi Zhou, Tom Goldstein, Parminder Bhatia, Furong Huang, et al. Enhancing visual-language modality alignment in large vision language models via self-improvement. *arXiv preprint arXiv:2405.15973*, 2024.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*, 2022.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Ed Chi, Quoc Le, and Denny Zhou. Chain of thought prompting elicits reasoning in large language models. *arXiv preprint arXiv:2201.11903*, 2022.

Sang Michael Xie, Aditi Raghunathan, Percy Liang, and Tengyu Ma. An explanation of in-context learning as implicit bayesian inference. *arXiv preprint arXiv:2111.02080*, 2021.

Jiazheng Xu, Xiao Liu, Yuchen Wu, Yuxuan Tong, Qinkai Li, Ming Ding, Jie Tang, and Yuxiao Dong. Imagereward: Learning and evaluating human preferences for text-to-image generation. *Advances in Neural Information Processing Systems*, 36, 2024.

An Yang, Baosong Yang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Zhou, Chengpeng Li, Chengyuan Li, Dayiheng Liu, Fei Huang, et al. Qwen2 technical report. *arXiv preprint arXiv:2407.10671*, 2024.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. React: Synergizing reasoning and acting in language models. *arXiv preprint arXiv:2210.03629*, 2022.

Qinghao Ye, Haiyang Xu, Jiabo Ye, Ming Yan, Anwen Hu, Haowei Liu, Qi Qian, Ji Zhang, and Fei Huang. mplug-owl2: Revolutionizing multi-modal large language model with modality collaboration. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13040–13051, 2024.

Shukang Yin, Chaoyou Fu, Sirui Zhao, Tong Xu, Hao Wang, Dianbo Sui, Yunhang Shen, Ke Li, Xing Sun, and Enhong Chen. Woodpecker: Hallucination correction for multimodal large language models. *arXiv preprint arXiv:2310.16045*, 2023.

Haoxuan You, Haotian Zhang, Zhe Gan, Xianzhi Du, Bowen Zhang, Zirui Wang, Liangliang Cao, Shih-Fu Chang, and Yinfei Yang. Ferret: Refer and ground anything anywhere at any granularity. *arXiv preprint arXiv:2310.07704*, 2023.

Alex Young, Bei Chen, Chao Li, Chengen Huang, Ge Zhang, Guanwei Zhang, Heng Li, Jiangcheng Zhu, Jianqun Chen, Jing Chang, et al. Yi: Open foundation models by 01. ai. *arXiv preprint arXiv:2403.04652*, 2024.

Lu Yuan, Dongdong Chen, Yi-Ling Chen, Noel Codella, Xiyang Dai, Jianfeng Gao, Houdong Hu, Xuedong Huang, Boxin Li, Chunyuan Li, et al. Florence: A new foundation model for computer vision. *arXiv preprint arXiv:2111.11432*, 2021.

Xiang Yue, Yuansheng Ni, Kai Zhang, Tianyu Zheng, Ruoqi Liu, Ge Zhang, Samuel Stevens, Dongfu Jiang, Weiming Ren, Yuxuan Sun, et al. Mmmu: A massive multi-discipline multimodal understanding and reasoning benchmark for expert agi. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9556–9567, 2024.

Eric Zelikman, Yuhuai Wu, Jesse Mu, and Noah Goodman. Star: Bootstrapping reasoning with reasoning. *Advances in Neural Information Processing Systems*, 35:15476–15488, 2022.

Eric Zelikman, Georges Harik, Yijia Shao, Varuna Jayasiri, Nick Haber, and Noah D Goodman. Quiet-star: Language models can teach themselves to think before speaking. *arXiv preprint arXiv:2403.09629*, 2024.

Xiaohua Zhai, Basil Mustafa, Alexander Kolesnikov, and Lucas Beyer. Sigmoid loss for language image pre-training. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 11975–11986, 2023.

Duzhen Zhang, Yahan Yu, Jiahua Dong, Chenxing Li, Dan Su, Chenhui Chu, and Dong Yu. Mm-llms: Recent advances in multimodal large language models. *arXiv preprint arXiv:2401.13601*, 2024a.

Hao Zhang, Feng Li, Shilong Liu, Lei Zhang, Hang Su, Jun Zhu, Lionel M Ni, and Heung-Yeung Shum. Dino: Detr with improved denoising anchor boxes for end-to-end object detection. *arXiv preprint arXiv:2203.03605*, 2022.

Hao Zhang, Hongyang Li, Feng Li, Tianhe Ren, Xueyan Zou, Shilong Liu, Shijia Huang, Jianfeng Gao, Chunyuan Li, Jainwei Yang, et al. Llava-grounding: Grounded visual chat with large multimodal models. In *European Conference on Computer Vision*, pp. 19–35. Springer, 2025.

Kaichen Zhang, Bo Li, Peiyuan Zhang, Fanyi Pu, Joshua Adrian Cahyono, Kairui Hu, Shuai Liu, Yuanhan Zhang, Jingkang Yang, Chunyuan Li, et al. Lmms-eval: Reality check on the evaluation of large multimodal models. *arXiv preprint arXiv:2407.12772*, 2024b.

Zhiyuan Zhao, Bin Wang, Linke Ouyang, Xiaoyi Dong, Jiaqi Wang, and Conghui He. Beyond hallucinations: Enhancing lvlms through hallucination-aware direct preference optimization. *arXiv preprint arXiv:2311.16839*, 2023.

Yiyang Zhou, Chenhang Cui, Rafael Rafailov, Chelsea Finn, and Huaxiu Yao. Aligning modalities in vision large language models via preference fine-tuning. *arXiv preprint arXiv:2402.11411*, 2024a.

Yiyang Zhou, Zhiyuan Fan, Dongjie Cheng, Sihan Yang, Zhaorun Chen, Chenhang Cui, Xiyao Wang, Yun Li, Linjun Zhang, and Huaxiu Yao. Calibrated self-rewarding vision language models. *arXiv preprint arXiv:2405.14622*, 2024b.

Deyao Zhu, Jun Chen, Xiaoqian Shen, Xiang Li, and Mohamed Elhoseiny. Minigpt-4: Enhancing vision-language understanding with advanced large language models. *arXiv preprint arXiv:2304.10592*, 2023.

Ke Zhu, Liang Zhao, Zheng Ge, and Xiangyu Zhang. Self-supervised visual preference alignment. In *Proceedings of the 32nd ACM International Conference on Multimedia*, pp. 291–300, 2024.

Reproducibility

The core SVP framework is described in the Method Section, with explicit pseudo-code for our algorithm and its scoring variants available in Appendix D. Our complete experimental design, including the selection of base models, datasets, and metrics, is detailed in the Experiments Section and Appendix K. Datasets details are in Table 17. A comprehensive table of all hyperparameters used for sampling and training is provided in Table 18. The exact prompts used to generate our data are included in Appendix G. The baselines and experiments are implemented on top of the `LLaVA` [4] and `LLaVA-NeXT` [5] codebases. We use `lmms-eval` [6] for evaluation.

Broader Impact Statement

Our Sampling-based Visual Projection (SVP) framework offers significant positive societal impacts by enabling resource-efficient, annotation-free alignment of Vision-Language Models (VLMs), reducing hallucinations, and improving reliability for high-stakes applications like scientific discovery and engineering. However, this approach carries potential risks; because SVP relies on a pre-trained external grounding model for spatial feedback, any systemic biases or misclassifications inherent in that expert could be inadvertently distilled into the generalist VLM. To mitigate these risks, practitioners must rigorously audit both the base VLM and the external grounding expert for biases prior to data generation, and deploy standard safety guardrails such as toxicity filters and continuous monitoring when deploying these adapted models.

---

[4] `https://github.com/haotian-liu/LLaVA`
[5] `https://github.com/LLaVA-VL/LLaVA-NeXT`
[6] `https://github.com/EvolvingLMMs-Lab/lmms-eval`

Contents

A   Extended Related Work

Improving Vision-Language Models   Researchers have investigated explicit grounding in VLMs, primarily to address hallucinations (Wan et al., 2024; Favero et al., 2024), with less focus on developing general paradigms for improving vision-language alignment. A common strategy involves incorporating grounding annotations into training data (Peng et al., 2024) for vision-centric VLMs (Beyer et al., 2024; Yuan et al., 2021; You et al., 2023; Zhang et al., 2025).

However, this annotation process is costly, time-consuming, and prone to errors. For instance, directly generating coordinate tokens as output is sample-inefficient, requiring billions of annotations even for small VLMs to develop a competitive detector (Yuan et al., 2021). While explicit supervision during fine-tuning can enhance alignment between visual and linguistic representations (Liu et al., 2024a; Sun et al., 2023), these train-time methods necessitate large amounts of high-quality visual-text data and are resource-intensive to scale with human annotations.

Train-time techniques like Reinforcement Learning from Human Feedback (RLHF (Christiano et al., 2017; Ouyang et al., 2022)) and Direct Preference Optimization (DPO (Rafailov et al., 2024)), primarily used for aligning LLMs with human preferences, can be adapted to align VLM text outputs with visual inputs (Zhou et al., 2024a; Sun et al., 2023; Wang et al., 2024). These approaches incorporate feedback and preferences during post-training but are limited by the need for reward signals (Sun et al., 2023), curated preference pairs (Zhu et al., 2024; Zhou et al., 2024a), and AI feedback (Wang et al., 2024).

Test-time methods (Wan et al., 2024), such as Visual Contrastive Decoding (Leng et al., 2024) and Multi-Modal Mutual-Information Decoding (Favero et al., 2024), aim to improve grounding at inference by leveraging differences between vision-conditional and unconditional models, without altering the model architecture or training. Woodpecker (Yin et al., 2023) proposes a five-step inference procedure to mitigate hallucination. While somewhat effective, these methods often require memory-intensive and computationally expensive inference, as well as model-specific heuristics, which limits their generalization and usability.

Grounding in Vision-Language Models   Visual grounding can be conceptualized as the dual of text-image alignment. When viewed as a mechanism to elicit and organize information within Vision-Language Models (VLMs), it represents a form of alignment between visual and textual modalities, encompassing both representation and generation aspects.

The concept of grounding has deep roots in cognitive sciences (Kiefer & Barsalou, 2013; Barsalou, 2008; Anderson, 2010; Glenberg & Kaschak, 2002). In the context of computer vision, visual grounding can be seen as an extension of the classic closed-set detection problem (Girshick et al., 2014; Carion et al., 2020; Redmon, 2016; Zhang et al., 2022).

Traditional object detection tasks involve regressing bounding box coordinates and assigning class labels to regions within an input image. While leveraging curated benchmark datasets (Lin et al., 2014) has led to rapid improvements in precision and speed, this approach has been constrained by predefined class sets. Scaling to a larger number of classes and adapting to varying detection granularities have proven challenging (Gupta et al., 2019; Dave et al., 2021).

Visual grounding inverts this paradigm by using the set of classes as input and employing a vision-language model to assign bounding boxes to each element in the input. This concept can be further generalized to accommodate captions, descriptions, and various forms of textual input. Contrastive models such as GLIP (Li et al., 2022b) and GroundingDINO (Liu et al., 2023) offer flexible, generalized detection models that enhance spatial understanding (Yin et al., 2023) and serve as foundations for a wide range of tasks. Moreover, auto-regressive VLMs have been developed to perform grounding and referring tasks (Yuan et al., 2021; You et al., 2023; Peng et al., 2024; Tong et al., 2024), further expanding the capabilities of these models in bridging visual and linguistic information.

Self-Training in Vision and Language Models   Self-training and self-play autonomous learners have been a long standing goal of the AI field (Schmidhuber, 1987; 1999). In the context of Vision-Language Models (VLMs), self-training can be conceptualized as a form of self-play (Silver et al., 2016; 2017), where the

model enhances its performance through sampling and external feedback mechanisms (Anthony et al., 2017). The advent of Large Language Models (LLMs) (Brown et al., 2020; Achiam et al., 2023) has necessitated novel approaches to self-training, given the challenges in defining explicit feedback for natural language trajectories.

Reinforcement Learning from Human Feedback (RLHF) (Ouyang et al., 2022) and Reinforcement Learning from AI Feedback (RLAIF) (Bai et al., 2022) have emerged as prominent mechanisms. These methods score samples from the base model and select preferred outputs based on specific criteria, such as human preferences in chat interactions. Both approaches learn preference or reward models from human or AI feedback, and these concepts have been successfully adapted to VLMs (Sun et al., 2023; Favero et al., 2024).

Further developments in this field include using rewards for ranking (Dong et al., 2023) and implicitly specifying preferences through positive and negative pairs (Rafailov et al., 2024). Alignment can also be achieved through AI distillation (Sudalairaj et al., 2024; Chiang et al., 2023) and self-refinement techniques (Kang et al., 2024b;a; Wang et al., 2022; Sun et al., 2024).

A recent class of algorithms for self-training involves iterative processes (Zelikman et al., 2022; 2024; Anthony et al., 2017; Gulcehre et al., 2023) that leverage feedback to enhance downstream tasks and reasoning chains (Wei et al., 2022) in LLMs. Moreover, feedback can be incorporated at inference time (Madaan et al., 2024) and even utilize the model's own capabilities as evaluator (Yao et al., 2022; Shinn et al., 2024). These methods can be seen as instantiating meta-learning algorithms.

Meta-learning (Schaul & Schmidhuber, 2010; Hospedales et al., 2020; Finn et al., 2017), often described as learning to learn, plays a crucial role in the development of self-improving AI systems. This approach aims to create models that can adapt quickly to new tasks by leveraging knowledge from previously learned tasks (Schmidhuber, 1987; 1999). In the context of VLMs and LLMs, meta-learning techniques have been explored to enhance model adaptability and generalization across diverse domains. For instance, few-shot in-context learning methods (Brown et al., 2020; Xie et al., 2021; Akyürek et al., 2022) demonstrate how large models can rapidly adapt to new tasks with minimal task-specific examples.

B   Sampling-based Visual Projection Workflow

Instruction: Please describe the content of this image as detailed as possible.

VLM response:
The image depicts a modern home office setup. At the center of the scene is a wooden desk with a sleek, minimalist design. The desk features a flat surface with a built-in drawer and a small shelf on the left side. On the right side of the desk, there is a laptop open and ready for use.
Above the desk, mounted on the wall, is a framed artwork of a ballerina in a dynamic pose, adding a touch of elegance and movement to the space. The artwork is encased in a black frame that contrasts with the wall's dark gray color.
To the left of the desk, there is a floor lamp with a modern design, providing additional lighting. The lamp has a tall, slender base and a curved arm with a white shade.
On the desk, there is a small plant in a white pot, adding a touch of greenery and life to the space. The plant is placed on the left side of the desk, near the laptop. Underneath the desk, there is a black wire basket, which is likely used for cable management and storage.

Note: missing chair, missing background.

Grounded Objects: desk (0.82). laptop (0.93). artwork (0.64). frame (0.74). lamp (0.87). plant (0.83). pot (0.68). basket (0.83).

Instruction: Please describe the content of this image as detailed as possible.
Context: Use the following context. The list of numbers are bounding boxes for the objects. Check if object and bounding boxes connections are correct. Check if there are additional objects in the image and describe them.
format: cxcywh.
boxes: lamp [0.33,0.47,0.16,0.23], laptop [0.48,0.54,0.16,0.09], desk [0.49,0.75,0.61,0.33], plant [0.36,0.56,0.04,0.06], frame [0.64,0.22,0.24,0.24], basket [0.80,0.80,0.15,0.15].

VLM response:
The image depicts a modern workspace setup against a dark gray wall with horizontal wood paneling. On the wall, there is a framed artwork featuring a figure in a red dress with a blue background, possibly a painting or a print. Below the artwork, there is a desk with a light wood finish. The desk has a rectangular shape with a flat top and is supported by four black metal legs.
On the desk, there is a laptop with a black screen and a silver body, positioned towards the center. To the left of the laptop, there is a white desk lamp with a curved neck and a silver base, turned off. Next to the lamp, there is a small white potted plant with green leaves.
In front of the desk, there is a white office chair with a modern design, featuring a curved backrest and armrests. The chair is positioned facing the desk, with the seat slightly pulled out.
To the right of the desk, there is a black wire basket with a handle, placed on the floor. The flooring appears to be a light-colored wooden plank. The overall lighting in the room is soft and ambient, suggesting a calm and focused work environment.
Grounded Objects: artwork (0.83). desk (0.85). laptop (0.94). desk lamp (0.84). potted plant (0.83). office chair (0.90). wire basket (0.94). flooring (0.64).

Figure 11: Sampling VLMs with and without Grounding Feedback. Incorporating grounding feedback helps VLMs to focus on factual information and better describe the details in the input image. We use GroundingDINO (Liu et al., 2023), an open-set grounding model, to obtain the conditioning information. When the predicted bounding boxes overlap above a certain threshold, we select the box with the highest score, following a standard non-maximum-suppression approach. By leveraging this grounding feedback, the model is better able to specify the entities and relationships between the objects in the image, leading to an improved parsing of the visual information. This results in more accurate and detailed descriptions, such as identifying a `desk lamp` instead of a `floor lamp`, mentioning an `office chair`, describing the `flooring` in the background, and differentiating between an `artwork` and a simple `frame`, or a `potted plant` and a generic `plant`. More visualizations in J.

C In-Context Visual Projection and Text-to-Image Alignment

Table 9: Text-to-Image alignment scores computed using base VLMs and VLMs with in-context grounding (w/ `iSVP`). Image Text Matching (ITM (Li et al., 2023a)) and ImageReward (Xu et al., 2024) are traditionally used to evaluate AI-generated images from real text prompts. Here we apply these scores to assess AI-generated captions for real images. Although Text-to-Image alignment is not fully indicative of Image-to-Text alignment in this context, these scores provide an additional qualitative measure of caption-image correspondence. Higher is better.

Model	Size	ITMScore (BLIP2) ↑	ImageReward ↑
LLaVA-1.6	7b	0.83	0.47
LLaVA-1.6 w/ `iSVP`	7b	**0.89**	**0.49**
LLaVA-1.6	13b	0.82	0.44
LLaVA-1.6 w/ `iSVP`	13b	**0.87**	**0.46**

A central question in vision-language modeling is how the alignment between visual and textual data impacts text-to-image generation. Visual grounding serves as a key mechanism for structuring this cross-modal information, creating a unified representational space that enables effective multi-modal reasoning.

To explore this relationship, we evaluated text-to-image alignment using `iSVP`, a technique for inference-time adaptation that requires no parameter tuning. In our experiment, we provided a pre-trained grounding model as an inference-time tool to a base model (LLaVA-1.6). We then prompted both the base model and the grounded version (LLaVA-1.6 w/ `iSVP`) to generate captions for 1000 images on the fly, without any fine-tuning. We sample one caption per image, i.e. $K = 1$.

As shown in Table 9, Fig. 13, and Fig. 14, the captions generated by the `iSVP`-enhanced model were significantly better aligned with the images, according to standard metrics for Text-to-Image alignment like ITS and ImageReward. These results provide strong evidence that the `SVP` framework is also an effective and general mechanism for improving vision-language alignment at inference time.

(a) Input image

(b) Text-to-Image generation using base VLM response - $\mathbf{z} \sim p_\theta(\mathbf{z}|\mathbf{c})$. See left side 11.

(c) Text-to-Image generation using grounded VLM response - $\mathbf{z} \sim q(\mathbf{z}|\mathbf{c}, \mathbf{g})$. See right side 11.

Figure 12: FLUX-schnell (Labs, 2024) text to image generation using the original VLM response (left) and the response leveraging grounding (right) as input. We generated a single image without multiple attempts or selective filtering. The comparison clearly illustrates that the grounding-enhanced response produces more accurate and reliable generation outcomes.

(a) Input image from `coco2017_cap_val_lite`. Image id: `000000466567`. Target Captions (provided as ground truth): ["A tree with a donut as an ornament", "A plastic tree with a doughnut hanging by a strip of red ribbon.", "A Christmas ornament is a donut with a squirrel on it.", "A doughnut hanging from a Christmas tree as a decoration.", "a donut being used as an ornament for a chistmas tree"]

(b) Text-to-Image generation using base VLM response - $\mathbf{z} \sim p_\theta(\mathbf{z}|\mathbf{c})$: `"A donut with a red ribbon and a small toy animal on it"` for image (a).

(c) Text-to-Image generation using grounded VLM response - $\mathbf{z} \sim q(\mathbf{z}|\mathbf{c}, \mathbf{g})$: `"A donut with a red ribbon and a small toy animal on a Christmas tree"` for image (a).

Figure 13: FLUX-schnell (Labs, 2024) text to image generation using the base VLM response (left) and the response using `iSVP` (right) as input. We generated a single image without multiple attempts or selective filtering.

(a) Input image from `coco2017_cap_val_lite`. Image id: `000000253742`. Target Captions (provided as ground truth): ["A woman standing next to a herd of animals.", "a woman holding an umbrella at the park", "A woman standing in the rain with an umbrella with a herd of deer behind her.", "On a rainy day at the zoo umbrellas are frequently seen.", "Several people holding umbrellas and standing next to deer."]

(b) Text-to-Image generation using base VLM response - $\mathbf{z} \sim p_\theta(\mathbf{z}|\mathbf{c})$: `"A group of people holding umbrellas and standing in the rain"` for image (a).

(c) Text-to-Image generation using grounded VLM response - $\mathbf{z} \sim q(\mathbf{z}|\mathbf{c}, \mathbf{g})$: `"A woman holding an umbrella stands among a group of people and deer"` for image (a).

Figure 14: FLUX-schnell (Labs, 2024) text to image generation using the base VLM response (left) and the response using `iSVP` (right) as input. We generated a single image without multiple attempts or selective filtering.

D SVP Algorithms

Algorithm 1 Sampling-based Visual Projection (SVP) w/ log-ratio scoring $S(q,p)$

Require:
1: Base VLM $p_\theta(\mathbf{z}_p|\mathbf{c})$
2: Grounding model $g(\mathbf{z}, \mathbf{c})$
3: Scoring function $S(q, p)$
4: Seed images $\mathcal{C} = \{\mathbf{c}_c\}_{c=1}^C$
5: Samples per image K, top-k ratio k
6: Learning rate α, iterations I, vocabulary size V, grounded sequence length T
Ensure: Updated model parameters $\theta_1 \leftarrow \theta$
7: **for** iteration $i = 1$ to I **do**
8:    $\mathcal{D} \leftarrow \{\}$ ▷ Initialize dataset
9:    **for** each image $\mathbf{c} \in \mathcal{C}$ **do**
10:       $\mathbf{Z}_q \leftarrow \{\}$ ▷ Sample buffer
11:       **for** $j = 1$ to K **do**
12:          $\mathbf{z}_p^j \sim p_{\theta_i}(\mathbf{z}|\mathbf{c})$ ▷ Sample from prior
13:          $\mathbf{g}_j \leftarrow g(\mathbf{z}_p^j, \mathbf{c}_v)$ ▷ Grounding feedback
14:          $\mathbf{z}_q^j \sim q(\mathbf{z}|\mathbf{c}, \mathbf{g}_j)$ ▷ Sample with grounding
15:          $\mathbf{Z}_q \leftarrow \mathbf{Z}_q \cup \{\mathbf{z}_q^j\}$
16:       **end for**
17:       **for** $\mathbf{z}_q \in \mathbf{Z}_q$ **do**
18:          $S(q,p)_{\mathbf{z}_q} \leftarrow \sum_{t=1}^T \sum_{v=1}^V w_{v,t}[\log q_{v,t} - \log p_{v,t}]$
19:          $s_q \leftarrow S(q, p_{\theta_i})_{\mathbf{z}_q}$ ▷ Score samples
20:       **end for**
21:       $S_k \leftarrow k$-th highest score in $\{s_q\}$
22:       $\mathbf{Z}^* \leftarrow \{\mathbf{z}_q : s_q \geq S_k\}$ ▷ Select top-k
23:       $\mathcal{D} \leftarrow \mathcal{D} \cup \{(\mathbf{c}, \mathbf{z}) : \mathbf{z} \in \mathbf{Z}^*\}$
24:    **end for**
25:    **for** minibatch $B \subset \mathcal{D}$ **do**
26:       $\mathcal{L}(\theta) \leftarrow -\frac{1}{|B|} \frac{1}{|k(\mathbf{c})|} \sum_{(\mathbf{c},\mathbf{z}) \in B} \log p_\theta(\mathbf{z}|\mathbf{c})$
27:       $\theta_i \leftarrow \theta - \alpha \nabla_\theta \mathcal{L}$ ▷ Update parameters
28:    **end for**
29:    $\theta_{i+1} = \theta_i$
30: **end for**
         return $p_{\theta_I}(\mathbf{z}|\mathbf{c})$

Algorithm 2 Sampling-based Visual Projection (SVP) w/ weighted difference scoring $\Delta(q,p)$

Require:
 1: Base VLM $p_\theta(\mathbf{z}_p|\mathbf{c})$
 2: Grounding model $g(\mathbf{z}, \mathbf{c})$
 3: Scoring function $\Delta(q, p)$
 4: Seed images $\mathcal{C} = \{\mathbf{c}_c\}_{c=1}^C$
 5: Samples per image K, top-k ratio k
 6: Learning rate α, iterations I, vocabulary size V, grounded sequence length T
Ensure: Updated model parameters $\theta_1 \leftarrow \theta$
 7: **for** iteration $i = 1$ to I **do**
 8:     $\mathcal{D} \leftarrow \{\}$ $\triangleright$ Initialize dataset
 9:     **for** each image $\mathbf{c} \in \mathcal{C}$ **do**
10:         $\mathbf{Z}_q \leftarrow \{\}$ $\triangleright$ Sample buffer
11:         **for** $j = 1$ to K **do**
12:             $\mathbf{z}_p^j \sim p_{\theta_i}(\mathbf{z}|\mathbf{c})$ $\triangleright$ Sample from prior
13:             $\mathbf{g}_j \leftarrow g(\mathbf{z}_p^j, \mathbf{c}_v)$ $\triangleright$ Grounding feedback
14:             $\mathbf{z}_q^j \sim q(\mathbf{z}|\mathbf{c}, \mathbf{g}_j)$ $\triangleright$ Sample with grounding
15:             $\mathbf{Z}_q \leftarrow \mathbf{Z}_q \cup \{\mathbf{z}_q^j\}$
16:         **end for**
17:         **for** $z_q \in Z_q$ **do**
18:             $\Delta(q,p)_{\mathbf{z}_q} = \sum_{t=1}^T \sum_{v=1}^V w_{v,t}^q \log q_{v,t} - \sum_{t=1}^T \sum_{v=1}^V w_{v,t}^p \log p_{\theta\,v,t}$
19:             $s_q \leftarrow \Delta(q,p)_{\mathbf{z}_q}$ $\triangleright$ Score samples
20:         **end for**
21:         $S_k \leftarrow k$-th highest score in $\{s_q\}$
22:         $\mathbf{Z}^* \leftarrow \{\mathbf{z}_q : s_q \geq S_k\}$ $\triangleright$ Select top-k
23:         $\mathcal{D} \leftarrow \mathcal{D} \cup \{(\mathbf{c}, \mathbf{z}) : \mathbf{z} \in \mathbf{Z}^*\}$
24:     **end for**
25:     **for** minibatch $B \subset \mathcal{D}$ **do**
26:         $\mathcal{L} \leftarrow -\frac{1}{|B|}\frac{1}{|k(\mathbf{c})|} \sum_{(\mathbf{c},\mathbf{z}) \in B} \log p_\theta(\mathbf{z}|\mathbf{c})$
27:         $\theta \leftarrow \theta - \alpha\nabla_\theta \mathcal{L}$ $\triangleright$ Update parameters
28:     **end for**
29:     $\theta_{i+1} = \theta_i$
30: **end for**
        return $p_{\theta_I}(\mathbf{z}|\mathbf{c})$

E   Additional Experiments

E.1   Image Textualization Ablation

Table 10: Accuracy comparison for SVP and Image-Textualization (IT) on the POPE dataset splits. SVP is competitive with IT and more data efficient, requiring less feedback.

Name	Samples	All	Adversarial	Popular	Random
LLaVA w/ SVP	4k	**88.3**	**85.9**	89.1	**90.1**
LLaVA w/ IT (Pi et al., 2024)	10k	86.4	81.3	90.6	87.4
GPT4-V w/ IT (Pi et al., 2024)	50k	87.4	83.3	**90.8**	88.2

Table 10 compares our SVP approach with Image Textualization (IT) on the POPE benchmark, which evaluates object hallucination via yes/no existence queries across multiple splits (All, Adversarial, Popular, Random).

LLaVA trained with SVP achieves the highest overall accuracy of 88.3% using only 4k preference samples, outperforming LLaVA with IT (86.4% with 10k samples) and GPT-4V with IT (87.4% with 50k samples). SVP also attains the best performance on the more challenging Adversarial and Random splits (85.9% and 90.1%), while remaining competitive on the Popular split despite using substantially less feedback than IT-based baselines.

These results indicate that supervision-free preferences derived directly from the base MLLM can replace large-scale IT-generated descriptions, yielding strong robustness to hallucination with markedly improved data efficiency.

E.2 IoU Ablation

In this work we have seen how SVP can be leveraged to improve vision-language alignment without relying on additional human annotation. However, because our analysis is focused on the textual output in a VLM, it is unclear if and how the geometric alignment in the grounding model is amortized in the VLM using SVP.

Her we provide an experiment on a subset of RefCOCO (`val_lite`) with 500 samples. We sample a base LLaVA-1.6-7B model and the same model adapted with w/ SVP using $k = 5$ to better evaluate the robustness of our method to the number of images/sample. Then we use the grounding model to ground generated caption from both models, and compute the IoU@0.5 with the RefCOCO ground truth bounding box.

Figure 15 shows performance metrics for LLaVA (blue bars) and LLaVA w/ SVP (brown bars) on RefCOCO referring tasks. The x-axis displays three key metrics: IoU@0.5 (intersection over union at 50%), IoU<0.05 (a failure rate metric, not grounded object), and CIDEr (a consensus-based image description metric). The

Figure 15: Performance comparison of the baseline LLaVA model against LLaVA with Sampling-based Visual Projection (SVP) across RefCOCO referring tasks, demonstrating significant improvements in grounding accuracy (IoU@0.5) and captioning quality (CIDEr), alongside a reduction in failure cases (IoU<0.05)

results highlights the positive impact of SVP, showing a 30% increase in IoU@0.5 scores (rising from 0.37 to 0.48) and a substantial 130% increase in CIDEr scores (rising from 0.06 to 0.14). Furthermore, the failure rate IoU<0.05) drops significantly by 58.82% (from 0.17 to 0.07), indicating that the SVP integration effectively reduces instances where the model fails to ground the target object. These results clearly show that the feedback-driven self-training mechanism driving SVP not only improves visual-language alignment, but effectively extract geometric knowledge from the grounding model. See Figure 16 for visualizations.

(a) Grounding output using LLaVA captions.

(b) Grounding output using LLaVA w/ SVP captions.

Figure 16: Qualitative comparison of grounding performance using different captioning strategies. (a) Baseline LLaVA generates captions that often lack groundable details or fail to trigger detections entirely (missing detections in 3/9 examples). (b) LLaVA w/ SVP produces more descriptive, groundable captions, resulting in successful detections across all examples and improved downstream IoU performance. The green bounding boxes illustrate the grounding model's ability to localize the caption's content.

E.3 Grounding Model Ablation

To assess the impact of visual grounding quality on model performance, we conducted an ablation study using the RefCOCO (`val_lite`) dataset comprising 500 images. We evaluated four configurations: a baseline without grounding (w/o GDINO), a noisy variant where 30% of GDINO-tiny predictions are randomly dropped (GDINO-noisy), our standard setup (GDINO-tiny), and a high-capacity version (GDINO-base). Performance was measured across three difficulty levels defined by Intersection over Union (IoU) thresholds: easy (IoU@0.5), medium (IoU@0.75), and hard (IoU@0.95). As shown in the results, increasing the capacity of the grounding model yields consistent performance gains across all strictness levels. The GDINO-base model achieved the highest accuracy in every category, peaking at over 0.50 for IoU@0.5 and maintaining a lead even at the strictest IoU@0.95 threshold. Notably, providing even noisy grounding signals (GDINO-noisy) offered a tangible improvement over the ungrounded baseline, confirming that explicit visual localization cues are critical for this task.

Figure 17: Performance ablation of different grounding models on RefCOCO validation tasks. We compare four setups: w/o GDINO (no grounding), GDINO-noisy (GDINO-tiny predictions with 30% random dropout), GDINO-tiny (standard setup), and GDINO-base (high capacity). Bar charts display IoU accuracy across three difficulty thresholds: (a) Easy (IoU@0.5), (b) Medium (IoU@0.75), and (c) Hard (IoU@0.95). Higher capacity models consistently improve performance across all strictness levels, demonstrating the importance of robust visual grounding signals.

E.4 Number of generated samples per image K Ablation

To assess the impact of the sampling strategy on model performance, we conducted an ablation study on the number of samples per image, denoted as K, generated during the sampling loop. We evaluated the LLaVA-1.6-7B model across a diverse set of benchmarks, including RefCOCO (`val_lite`) and Flickr30k (`test_lite`) for captioning capabilities, the MMMU val set for multitasking performance, and POPE for hallucination control. We varied K across the set $0, 1, 5, 10, 20$, where $K = 0$ represents a baseline with no grounding and $K = 1$ introduces grounding without scoring. As shown in Figure 18, performance metrics exhibit a consistent upward trend as the number of samples increases. We observed a sharp improvement in generation quality as K rose to 10, beyond which the performance gains saturated, plateauing around $K = 20$. Based on these results, we selected $K = 20$ for the majority of our subsequent experiments to maximize performance while maintaining computational feasibility.

Figure 18: Ablation study on the effect of sample count K during the sampling loop. $K = 0$ represents the baseline without grounding, while $K = 1$ utilizes grounding without scoring. We report CIDEr scores for captioning tasks (RefCOCO, Flickr30k), Accuracy for multitasking (MMMU), and F1 scores for hallucination evaluation (POPE). Results indicate that increasing K yields significant gains up to $K = 10$, with performance saturating near $K = 20$. Consequently, $K = 20$ is adopted for subsequent experiments.

E.5 Captioning

Table 11: Captioning Performance on COCO2014, NoCaps, COCO2017, and Flickr30k datasets (80k samples) using `lmms-eval`. Results compare LLaVA-1.6-7B/13B models with weighted-difference ($\Delta(q,p)$) and log-ratio ($S(q,p)$) scoring mechanisms. Performance measured by METEOR (M), ROUGE-L (R), and CIDEr (C); higher scores better. See K for dataset details.

Model	Score	COCO2014_val			COCO2017_val			NoCaps_test			Flickr30k_test		
		M	R	C	M	R	C	M	R	C	M	R	C
LLaVA-1.6-7b	-	26.14	54.25	107.65	26.00	54.12	109.32	27.03	56.98	96.08	23.63	51.61	73.17
w/ SVP (C)	$\Delta(q,p)$	28.74	56.69	111.98	28.74	56.69	**114.77**	29.37	59.52	**104.79**	25.62	53.25	75.98
w/ SVP (CVQ)	$\Delta(q,p)$	**29.26**	56.62	111.38	29.24	56.67	114.72	30.07	**59.69**	104.58	**26.34**	**53.58**	**77.68**
w/ SVP (C)	$S(q,p)$	28.64	**56.74**	**112.45**	28.57	**56.71**	114.69	29.29	59.62	104.75	25.54	53.40	76.53
w/ SVP (CVQ)	$S(q,p)$	29.22	56.25	109.57	**29.25**	56.34	113.08	**30.08**	59.55	104.01	26.26	53.23	76.73
LLaVA-1.6-13b	-	24.67	52.03	99.39	24.72	52.23	102.04	25.44	54.93	88.13	22.21	48.78	66.68
w/ SVP (C)	$\Delta(q,p)$	25.31	54.28	104.83	25.30	54.40	107.20	26.16	57.21	93.11	22.54	50.82	67.77
w/ SVP (CVQ)	$\Delta(q,p)$	28.38	**56.71**	**113.30**	**28.49**	**57.03**	**117.23**	28.94	**59.19**	**102.32**	**25.69**	**53.61**	**78.11**
w/ SVP (C)	$S(q,p)$	25.32	54.22	104.84	25.37	54.37	107.52	26.14	57.14	93.11	22.71	51.00	68.56
w/ SVP (CVQ)	$S(q,p)$	**28.39**	56.54	112.65	28.35	56.67	116.09	**28.96**	59.14	101.93	25.59	53.25	77.00

Table 12: Captioning Performance on COCO2014, NoCaps, COCO2017, and Flickr30k datasets (80k samples) using `lmms-eval`. Comparing LLaVA-1.6-7B/13B models with weighted-difference ($\Delta(q,p)$) and log-ratio ($S(q,p)$) scoring. Evaluated using BLEU-1 to BLEU-4 (B1-B4); higher scores better.

Model	Score	COCO2014_val				COCO2017_val				NoCaps_test				Flickr30k_test			
		B4	B3	B2	B1	B4	B3	B2	B1	B4	B3	B2	B1	B4	B3	B2	B1
LLaVA-1.6-7b	-	31.04	41.51	54.40	68.81	30.82	41.24	54.14	68.54	38.43	50.03	62.89	75.43	28.57	39.90	54.54	71.41
w/ SVP (C)	$\Delta(q,p)$	32.29	44.25	59.33	76.16	32.61	44.50	59.44	76.09	41.05	54.12	**68.82**	83.18	28.94	40.62	55.85	73.53
w/ SVP (CVQ)	$\Delta(q,p)$	31.69	43.50	58.46	75.52	32.01	43.72	58.53	75.53	40.88	53.78	68.49	**83.42**	29.22	40.71	55.63	73.27
w/ SVP (C)	$S(q,p)$	**32.75**	**44.76**	**59.86**	76.71	**32.82**	**44.74**	**59.78**	**76.54**	**41.15**	**54.17**	68.77	82.93	**29.59**	**41.38**	**56.68**	**74.36**
w/ SVP (CVQ)	$S(q,p)$	30.95	42.67	57.60	74.76	31.46	43.02	57.78	74.86	40.29	53.27	68.16	83.17	28.76	40.09	54.90	72.56
LLaVA-1.6-13b	-	27.33	36.76	48.51	61.98	27.64	37.06	48.84	62.33	34.06	44.86	56.93	68.78	24.28	34.50	48.31	65.26
w/ SVP (C)	$\Delta(q,p)$	29.97	39.65	51.34	63.79	29.96	39.65	51.37	63.76	37.28	48.33	59.97	70.31	27.15	37.88	51.83	67.78
w/ SVP (CVQ)	$\Delta(q,p)$	**33.65**	**45.40**	**59.99**	76.45	**34.28**	**45.90**	**60.43**	**76.71**	**40.77**	**53.66**	**68.09**	82.25	**29.91**	**41.92**	**57.53**	**75.55**
w/ SVP (C)	$S(q,p)$	29.97	39.78	51.67	64.45	30.25	39.97	51.83	64.56	37.54	48.61	60.40	71.12	27.60	38.64	52.60	68.83
w/ SVP (CVQ)	$S(q,p)$	33.45	45.26	59.90	**76.47**	34.00	45.59	60.10	76.50	40.35	53.24	67.81	82.17	29.40	41.39	57.03	75.18

E.6 Hallucination Rate

Table 13: Hallucination (F1) and Recall (R) using Qwen2-VL7b and Qwen2.5-VL-7b. Naively scaling the multimodal finetuning dataset does not solve visual-language alignment in more powerful VLMs, and can even be detrimental.

Name	Multimodal Samples	F1 (all - 9k)	F1 (adv - 3k)	F1 (pop - 3k)	F1 (random - 3k)	Recall (all - 9k)
Qwen2-VL-7b (Yang et al., 2024)	100M	87.8	**85.8**	87.9	89.8	83.4
Qwen2.5-VL-7b (Yang et al., 2024)	100M	86.2	85.1	86.1	87.1	77.9
LLaVA-1.6-7b w/ SVP	800K	**88.3**	**85.9**	**89.1**	**90.1**	**84.4**

Table 14: Hallucination Mitigation performance on POPE benchmark. Comparison of LLaVA model variants' F1 scores across adversarial, popular, random, and overall splits. Results demonstrate impacts of model size, fine-tuning strategy, encoder choices, and SVP adaptation on hallucination avoidance.

Model	Size	v_θ	t_θ	POPE ($F1$ score ↑)			
				adv	pop	random	all
LLaVA (Liu et al., 2024c)	7b	CLIP	Vicuna	72.0	75.3	80.7	76.0
LLaVA-SFT$^+$ (Sun et al., 2023)	7b	CLIP	Vicuna	80.1	82.4	85.5	82.7
LLaVA-RLHF (Sun et al., 2023)	7b	CLIP	Vicuna	79.5	81.8	83.3	81.5
LLaVA (Liu et al., 2024c)	13b	CLIP	Vicuna	74.4	78.2	78.8	77.1
LLaVA-SFT$^+$ (Sun et al., 2023)	13b	CLIP	Vicuna	81.1	82.6	84.8	82.8
LLaVA-RLHF (Sun et al., 2023)	13b	CLIP	Vicuna	80.5	81.8	83.5	81.9
LLaVA-NeXT-DPO (Liu et al., 2024b)	7b	CLIP	Qwen2	83.43	83.78	84.73	83.98
LLaVA-OV-DPO (Li et al., 2024)	7b	SigLIP	Qwen2	85.12	86.24	87.37	86.24
LLaVA-HA-DPO (Zhao et al., 2023)	7b	CLIP	Vicuna	82.54	87.89	**90.25**	86.90
LLaVA-1.5 (Liu et al., 2024a)	13b	CLIP	Vicuna	84.53	86.31	87.17	86.00
LLaVA-1.5 w/ SVP	13b	CLIP	Vicuna	84.66	86.84	87.44	86.31
LLaVA-1.6 (Liu et al., 2024b)	7b	CLIP	Mistral	85.43	86.87	88.05	86.73
LLaVA-1.6 w/ SVP	7b	CLIP	Mistral	**85.93**	**89.04**	90.02	**88.33**
LLaVA-1.6 (Liu et al., 2024b)	13b	CLIP	Vicuna	85.17	86.36	87.20	86.24
LLaVA-1.6 w/ SVP	13b	CLIP	Vicuna	85.15	87.50	89.23	87.30
LLaVA-OV (Li et al., 2024)	0.5b	SigLIP	Qwen2	82.28	83.19	83.89	83.12
LLaVA-OV w/ SVP	0.5b	SigLIP	Qwen2	83.45	84.70	85.46	84.53
LLaVA-1.6 (Liu et al., 2024b)	34b	CLIP	Yi-2	-	-	-	87.7
InternVL (Chen et al., 2024b)	19b	IViT	Vicuna	-	-	-	87.6
InternVL-1.2 (Chen et al., 2024b)	40b	IViT	Yi-2	-	-	-	88.0
InternVL-1.2$^+$ (Chen et al., 2024b)	40b	IViT	Yi-2	-	-	-	88.7
VILA-1.5 (Lin et al., 2024)	8b	SigLIP	LLaMA3	-	-	-	85.6
VILA-1.5 (Lin et al., 2024)	8b	SigLIP	Vicuna	-	-	-	86.3
VILA-1.5 (Lin et al., 2024)	40b	IViT	Yi2	-	-	-	87.3
VILA-1.5-AWQ (Lin et al., 2024)	40b	IViT	Yi2	-	-	-	88.2

Table 15: Evaluating hallucination rates in different VLMs adapted with fine-tuning, train-time adaptation, and test-time adaptation. Higher is better. Eff-Size: effective model size for multi-phase inference pipelines. Woodpecker (Yin et al., 2023) requires multiple models to process the response.

Model	Size	Eff-Size	v_θ	t_θ	POPE (*Acc* score ↑) adv	pop	random
Fine-tuning							
InstructBLIP (Dai et al., 2023)	7b	7b	ViT	FlanT5	72.1	82.7	88.6
LLaVA-SFT$^+$ (Sun et al., 2023)	7b	7b	CLIP	Vicuna	80.2	82.9	86.1
mPLUG-Owl2 (Ye et al., 2024)	8b	8b	ViT	LLaMA2	84.1	86.2	88.3
InstructBLIP (Dai et al., 2023)	13b	13b	ViT	Vicuna	74.5	81.4	88.7
LLaVA-SFT$^+$ (Sun et al., 2023)	13b	13b	CLIP	Vicuna	82.3	83.9	85.2
Test-time adaptation							
QwenVL w/ VCD (Leng et al., 2024)	7b	14b	CLIP	Vicuna	84.3	87.1	88.6
LLaVA w/ M3ID (Favero et al., 2024)	7b	14b	CLIP	Vicuna	65.8	69.3	76.0
Otter w/ Woodpecker (Yin et al., 2023)	7b	≥ 14b	CLIP	LLaMA	83.0	84.3	86.7
mPLUG-Owl w/ Woodpecker (Yin et al., 2023)	7b	≥ 14b	ViT	LLaMA	81.0	84.1	86.3
LLaVA w/ M3ID (Favero et al., 2024)	13b	26b	CLIP	Vicuna	71.3	77.0	84.3
Train-time adaptation							
LLaVA-M3ID-DPO (Favero et al., 2024)	7b	7b	CLIP	Vicuna	68.2	73.9	81.2
LLaVA-RLHF (Sun et al., 2023)	7b	7b	CLIP	Vicuna	80.7	83.3	84.8
LLaVA-NeXT-DPO (Rafailov et al., 2024)	7b	7b	CLIP	Qwen2	85.2	85.6	86.6
LLaVA-OV-DPO (Rafailov et al., 2024)	7b	7b	SigLIP	Qwen2	86.3	87.5	88.7
LLaVA-HA-DPO (Zhao et al., 2023)	7b	7b	CLIP	Vicuna	81.5	87.9	**90.5**
SeVa (Zhu et al., 2024)	7b	7b	CLIP	Vicuna	83.6	87.4	89.4
LLaVA-M3ID-DPO (Favero et al., 2024)	13b	13b	CLIP	Vicuna	73.2	79.1	85.2
LLaVA-RLHF (Sun et al., 2023)	13b	13b	CLIP	Vicuna	82.3	83.9	85.2
InstructBLIP-HA-DPO (Zhao et al., 2023)	13b	13b	ViT	Vicuna	80.7	85.8	89.8
LLaVA-1.6 (Liu et al., 2024b)	7b	7b	CLIP	Mistral	86.4	87.9	89.2
LLaVA-1.6 w/ SVP	7b	7b	CLIP	Mistral	86.2	**89.6**	**90.6**
LLaVA-1.6 (Liu et al., 2024b)	13b	13b	CLIP	Vicuna	86.4	87.7	88.5
LLaVA-1.6 w/ SVP	13b	13b	CLIP	Vicuna	**86.7**	88.4	89.2
LLaVA-OV	0.5b	0.5b	SigLIP	Qwen2	84.3	85.2	86.0
LLaVA-OV w/ SVP	0.5b	0.5b	SigLIP	Qwen2	85.0	86.3	87.2

E.7 Referring Tasks

Table 16: Evaluation of referring expression generation on various `RefCOCO`, `RefCOCO+`, and `RefCOCOg` datasets using LLaVA-1.6-7b. The experiment compares the performance of different models, including a base model, a model without visual grounding (w/o **g**), a model with Visual Projections (w/ `SVP` (C)), and a model with `SVP` and Visual Query (w/ `SVP` (CVQ)). The performance is measured using the CIDEr score on bounding box (`bbox`) and segmentation (`seg`) referring task on the test and validation sets for each dataset. The results show that `SVP` models significantly outperform the base and w/o **g** models, indicating the importance of visual grounding for referring tasks. Notice that the adapted models do not have access to the bounding boxes during fine-tuning.

	base	w/o **g**	$\Delta(q,p)$ w/ `SVP` (C)	w/ `SVP` (CVQ)	$S(q,p)$ w/ `SVP` (C)	w/ `SVP` (CVQ)
RefCOCO						
`bbox-test`	9.53	3.57	18.99	26.96	20.74	25.52
`bbox-testA`	5.91	1.59	11.14	14.37	12.33	14.00
`bbox-testB`	12.35	6.27	25.13	36.65	27.64	34.71
`bbox-val`	9.93	3.95	18.84	27.01	21.07	25.76
`seg-test`	9.46	3.70	18.27	25.02	19.68	23.89
`seg-testA`	5.32	1.37	9.48	12.67	10.95	11.70
`seg-testB`	12.92	6.44	25.49	35.08	26.61	33.28
`seg-val`	9.44	4.02	18.35	25.15	19.60	23.95
RefCOCO+						
`bbox-testA`	6.68	2.16	12.25	16.93	14.05	16.44
`bbox-testB`	10.98	6.21	23.31	33.02	25.46	30.98
`bbox-val`	9.57	3.68	18.00	26.67	20.70	25.35
`seg-testA`	5.98	1.86	10.74	13.97	12.30	13.56
`seg-testB`	11.75	6.45	23.67	31.25	24.59	29.70
`seg-val`	9.19	3.90	17.15	24.31	19.13	23.81
RefCOCOg						
`bbox-test`	20.27	13.68	47.74	59.74	50.89	56.79
`bbox-val`	19.70	12.16	47.69	59.65	50.73	56.81
`seg-test`	18.76	12.90	45.23	54.39	47.51	51.18
`seg-val`	18.77	12.55	45.45	54.01	46.93	50.77

E.8 Iteration Ablation

Figure 19: `SVP` effectively boosts captioning performance and reduces hallucinations on benchmark tasks using LLaVA-1.6-7b as base model. The second iteration of `SVP` adaptation leads to significant improvements compared to the initial round, underscoring the value of this technique for enhancing visual-language model capabilities. However, the gains tend to plateau after the second iteration, suggesting diminishing returns from further fine-tuning.

E.9 Model Size Ablation

Figure 20: Model size comparison using the F1 metric on the POPE dataset. `SVP` improves the base model and achieves better or comparable performance with models five times larger.

E.10 Object Grounding Ablation

(a) LLaVA-1.5-7b.

(b) LLaVA-1.5-13b.

(a) LLaVA-1.6-7b.

(b) LLaVA-1.6-13b.

(a) LLaVA-1.6-7b iteration 1.

(b) LLaVA-1.6-7b iteration 2.

(c) LLaVA-1.6-7b iteration 3.

Figure 23: Distribution of groundable objects in generated caption sampling the base model $p_\theta(\mathbf{z}|\mathbf{c})$ and the grounded model $q(\mathbf{z}|\mathbf{c}, \mathbf{g})$. Models adapted with `SVP` generate less groundable objects and have better object recall.

E.11 Score Ablation

(a) Top1 Ranking Correlation for weighted-difference $\Delta(q,p)$ and log-ratio $S(q,p)$ score using LLaVA-1.6-7b as base model.

(b) Empirical Distribution of sequence scores. Log-space representation of $S(q, p_\theta)$ for sequence scoring. We see the scoring mechanism's effectiveness to differentiate between posterior samples $\mathbf{z}_q$ (with grounding) and prior samples $\mathbf{z}_p$ (without grounding).

F   Training Objective Derivation

We derive our visual-language alignment objective following two approaches: re-weighted maximum likelihood and greedy off-policy optimization. Assuming a deterministic output distribution $p(\mathbf{x}|\mathbf{z},\mathbf{c}) = d(\mathbf{z},\mathbf{c})$, we start with re-weighted maximum likelihood as a negated KL maximization:

$$\mathcal{F}_{\text{MLE}}(\mathbf{c};\theta) = -\mathbb{KL}\left[q(\mathbf{z}|\mathbf{c},\mathbf{g}), p_\theta(\mathbf{z}|\mathbf{c})\right] = \int q(\mathbf{z}|\mathbf{c},\mathbf{g})\log p_\theta(\mathbf{z}|\mathbf{c})d\mathbf{z} - \int q(\mathbf{z}|\mathbf{c},\mathbf{g})\log q(\mathbf{z}|\mathbf{c},\mathbf{g})d\mathbf{z} \tag{8}$$

Taking the gradient with respect to θ:

$$\nabla_\theta \mathcal{F}_{\text{MLE}}(\mathbf{c};\theta) = \nabla_\theta \int q(\mathbf{z}|\mathbf{c},\mathbf{g})\log p_\theta(\mathbf{z}|\mathbf{c})d\mathbf{z} = \int q(\mathbf{z}|\mathbf{c},\mathbf{g})\nabla_\theta \log p_\theta(\mathbf{z}|\mathbf{c})d\mathbf{z} \tag{9}$$

Approximating the expectation with K samples from $\mathbf{z} \sim q(\mathbf{z}|\mathbf{c},\mathbf{g})$ and filtering using our scoring mechanism:

$$\nabla_\theta \mathcal{F}_{\text{MLE}}^{k(\mathbf{c})}(\mathbf{c};\theta) \approx \frac{1}{|k(\mathbf{c})|}\sum_{i=1}^{K}\left[\mathbb{1}\{\mathbf{z}^i : S(q(\mathbf{z}^i|\mathbf{c},\mathbf{g}), p_\theta(\mathbf{z}^i|\mathbf{c})) \geq S_{k(\mathbf{c})}\}\right]_{\text{sg}}\nabla_\theta \log p_\theta(\mathbf{z}^i|\mathbf{c}) \tag{10}$$

For the policy optimization approach, we begin with the standard on-policy REINFORCE estimator using our scoring mechanism $f(\mathbf{z})$ as reward:

$$\mathcal{F}_{\text{RL-ON}}(\mathbf{c};\theta) = \mathbb{E}_{p_\theta(\mathbf{z}|\mathbf{c})}\left[f(\mathbf{z})\right] = \int p_\theta(\mathbf{z}|\mathbf{c})f(\mathbf{z})d\mathbf{z} \tag{11}$$

The gradient for θ yields:

$$\nabla_\theta \mathcal{F}_{\text{RL-ON}}(\mathbf{c};\theta) = \nabla_\theta \int p_\theta(\mathbf{z}|\mathbf{c})f(\mathbf{z})d\mathbf{z} = \int \nabla_\theta p_\theta(\mathbf{z}|\mathbf{c})f(\mathbf{z})d\mathbf{z} = \int p_\theta(\mathbf{z}|\mathbf{c})\nabla_\theta \log p_\theta(\mathbf{z}|\mathbf{c})f(\mathbf{z})d\mathbf{z}. \tag{12}$$

To incorporate our guiding distribution q, we use importance sampling:

$$\nabla_\theta \mathcal{F}_{\text{RL-ON}}^q(\mathbf{c};\theta) = \int q(\mathbf{z}|\mathbf{c},\mathbf{g})\frac{p_\theta(\mathbf{z}|\mathbf{c})}{q(\mathbf{z}|\mathbf{c},\mathbf{g})}\nabla_\theta \log p_\theta(\mathbf{z}|\mathbf{c})f(\mathbf{z})d\mathbf{z} \tag{13}$$

This is an unbiased estimator for the on-policy gradient leveraging the "off-policy" or behavioral/guiding distribution q. If now we approximate the expectation for q with K samples and filter using the score contained in $f(\mathbf{z})$, we can write:

$$\nabla_\theta \mathcal{F}_{\text{RL-OFF}}^{k(\mathbf{c})}(\mathbf{c};\theta) \approx \frac{1}{|k(\mathbf{c})|}\sum_{i=1}^{K}\left[\mathbb{1}\{\mathbf{z}^i : S(q(\mathbf{z}^i|\mathbf{c},\mathbf{g}), p_\theta(\mathbf{z}^i|\mathbf{c})) \geq S_{k(\mathbf{c})}\}\right]_{\text{sg}}\frac{p_\theta(\mathbf{z}^i|\mathbf{c})}{q(\mathbf{z}^i|\mathbf{c},\mathbf{g})}\nabla_\theta \log p_\theta(\mathbf{z}^i|\mathbf{c}), \tag{14}$$

where we leverage the fact that $f(\mathbf{z}^i) = \mathbb{1}\{\mathbf{z}^i : S(q(\mathbf{z}^i|\mathbf{c},\mathbf{g}), p_\theta(\mathbf{z}^i|\mathbf{c})) \geq S_{k(\mathbf{c})}\}$. Gradients are stopped over the scores in the indicator function.

By construction we are only retaining samples with low importance ratio p_θ/q. We are introducing bias focusing on samples that will improve vision-language alignment, and reducing the importance sampling estimator variance. Simplifying the previous gradient considering the importance ratio constant, we obtain the objective we maximize:

$$\nabla_\theta \tilde{\mathcal{F}}_{\text{RL-OFF}}^{k(\mathbf{c})}(\mathbf{c};\theta) \approx \frac{1}{|k(\mathbf{c})|}\sum_{i=1}^{K}\left[\mathbb{1}\{\mathbf{z}^i : S(q(\mathbf{z}^i|\mathbf{c},\mathbf{g}), p_\theta(\mathbf{z}^i|\mathbf{c})) \geq S_{k(\mathbf{c})}\}\right]_{\text{sg}}\nabla_\theta \log p_\theta(\mathbf{z}^i|\mathbf{c}) \tag{15}$$

Both approaches yield equivalent gradients after approximations: $\nabla_\theta \mathcal{F}_{\text{MLE}}^{k(\mathbf{c})}(\mathbf{c};\theta) = \nabla_\theta \tilde{\mathcal{F}}_{\text{RL-OFF}}^{k(\mathbf{c})}(\mathbf{c};\theta)$. This equivalence provides a strong theoretical foundation for our method. We optimize this objective at each SVP iteration by averaging over a batch of visual inputs: $\mathcal{L}(\theta) = -1/|B|\sum_{c=1}^{C}\mathcal{F}(\mathbf{c};\theta)$.

G Prompting

System Prompt - Sampling

You are an AI visual-language assistant that can analyze images and helps writing detailed descriptions of images.
`<instruction>`
Describe the scene and the objects in the image in details. Describe the object attributes and positions. Output only the descriptions of objects that are in the image. Use separate sentence for each object. Include details like object counts, position of the objects, relative position between the objects.
Start your description with "In the image, ".
`</instruction>`

System Prompt - Grounded Sampling

You are an AI visual-language assistant that can analyze images and helps writing detailed descriptions of images.
In addition, specific objects and object locations within the image are given, along with detailed coordinates inside `<context></context>`. These coordinates are in the form of bounding boxes, represented as `(x1, y1, x2, y2)` with floating numbers ranging from 0 to 1. These values correspond to the top left `x`, top left `y`, bottom right `x`, and bottom right `y`.
`<instruction>`
Using the provided objects and bounding boxes inside `<context></context>`, describe the image.
Describe the scene and the objects in the image in details. Describe the object attributes and positions. Output only the descriptions of objects that are in the image. Use separate sentence for each object. Include details like object counts, position of the objects, relative position between the objects.
Do not mention the bounding box coordinates. Utilize this data to explain the scene using natural language.
Start your description with "In the image, ".
`</instruction>`

Base Prompt

Please generate a detailed and comprehensive description for the content of this image. Be precise.

Grounded Prompt

`<context>`
`{grounding}`
`</context>`
Please generate a detailed and comprehensive description for the content of this image. Be precise.

H   Iterative Self-Training in Generative Models

Our method is inspired by recent advances in self-training in language modelling (Zelikman et al., 2022; Dong et al., 2023; Gulcehre et al., 2023), where the focus has been in improving chain-of-though reasoning leveraging feedback. The Self-Taught Reasoner (STaR (Zelikman et al., 2022)) uses ground truth labels and rationalization as feedback (Zelikman et al., 2022) and fine-tunes the model on reasoning steps that generate the correct answer (Hoffman et al., 2024). In 25 we provide a comparison between SVP and rationalization in STaR, where the model tries to find the correct reasoning path given external feedback in the form or a ground truth response.

```
P: Where do you put your
grapes just before
checking out?
Answer Choices:
(a) mouth
(b) grocery cart
(c) super market
(d) fruit basket
(e) fruit market
C: grocery cart (CORRECT)
R: The answer should be
the place where grocery
items are placed before
checking out.
Grocery cart makes the most
sense for holding grocery
items.
```

```
P: <IMAGE> Please describe
the content of this image.
C:
lamp   [0.33,0.47,0.16,0.23],
laptop [0.48,0.54,0.16,0.09],
desk   [0.49,0.75,0.61,0.33],
plant  [0.36,0.56,0.04,0.06],
frame  [0.64,0.22,0.24,0.24],
basket [0.80,0.80,0.15,0.15].
R: The image depicts
a modern work setup.
On the wall,
there is a framed artwork.
Below the frame,
there is a desk.
On the desk,
there is a laptop.
```

(a) Rationalization in STaR. We sample from $q(\mathbf{z}|\mathbf{c}, \mathbf{y})$, where $\mathbf{y}$ is the ground truth label provided as context C. The response $\mathbf{z}$ is then leveraged to build $p(\mathbf{y}|\mathbf{c}, \mathbf{z})$ or a deterministic decoding $d(\mathbf{c}, \mathbf{z})$.

(b) Grounded sampling in SVP. We sample from $q(\mathbf{z}|\mathbf{c}, \mathbf{g})$, where $\mathbf{g}$ is the grounding information provided as context C. The response $\mathbf{z}$ is then leveraged to build $p(\mathbf{x}|\mathbf{c}, \mathbf{z})$ or a deterministic decoding $d(\mathbf{c}, \mathbf{z})$.

Figure 25: Comparison between rationalization in STaR (Zelikman et al., 2022) and posterior sampling in SVP.

I   DPO Derivation

The DPO loss comparing policy π_θ to reference π_{ref} is:

$$\mathcal{L}_{\mathrm{DPO}}(\pi_\theta, \pi_{\mathrm{ref}}) = -\mathbb{E}_{(\mathbf{x}, \mathbf{y}_w, \mathbf{y}_l) \sim \mathcal{D}}[\log \sigma(\beta \, \delta r_\theta)], \tag{16}$$

where $\mathbf{x}$ is the input prompt, $\mathbf{y}_w$ and $\mathbf{y}_l$ are preferred and dis-preferred responses, $\sigma(z)$ is the sigmoid function, and $\beta = 1$ for simplicity. δr_θ represents the log-probability ratio difference between winning and losing samples:

$$\delta r_\theta = \log \frac{\pi_\theta(\mathbf{y}_w|\mathbf{x})}{\pi_\theta(\mathbf{y}_l|\mathbf{x})} = \log \frac{\pi_\theta(\mathbf{y}_w|\mathbf{x})}{\pi_{\mathrm{ref}}(\mathbf{y}_w|\mathbf{x})} - \log \frac{\pi_\theta(\mathbf{y}_l|\mathbf{x})}{\pi_{\mathrm{ref}}(\mathbf{y}_l|\mathbf{x})} = r_w(\theta) - r_l(\theta) \tag{17}$$

Preference Feedback and Optimal Policy   In determining the shape of DPO's implicit reward $r_w(\theta)$, we can draw insights from the standard PPO formulation used in RLHF. The RLHF framework integrates reinforcement learning with human preferences through three key components: (i) a reward model s_ψ (typically parametric) that encodes human preference labels; (ii) a generative policy model π_θ that can be sampled and improved through reward feedback; (iii) a reference model $\pi_{\mathtt{ref}}$ that provides stability during learning. This framework is expressed mathematically as:

$$\mathcal{F}_{\mathtt{PPO}} = \mathbb{E}_{\pi_\theta(\mathbf{z}|\mathbf{c})} \left[s_{\bar{\psi}}(\mathbf{z}, \mathbf{c}) - \gamma \log \frac{\pi_\theta(\mathbf{z}|\mathbf{c})}{\pi_{\mathtt{ref}}(\mathbf{z}|\mathbf{c})} \right], \tag{18}$$

where $\mathbf{z}$ represents a textual continuation for a given prompt $\mathbf{c}$ (either visual or textual). For this regularized policy optimization problem, it can be demonstrated that the optimal policy takes the form:

$$\pi_\theta^*(\mathbf{z}|\mathbf{c}) \propto \pi_{\mathtt{ref}}(\mathbf{z}|\mathbf{c}) \exp \left(\frac{s_{\bar{\psi}}(\mathbf{z}, \mathbf{c})}{\gamma} \right). \tag{19}$$

When we isolate the reward term $s_{\bar{\psi}}$, we find that this formulation aligns with the DPO framework, differing only by constant terms.

Gradient Derivation   Applying the chain rule to find $\nabla_\theta \mathcal{L}_{\mathrm{DPO}}$:

$$-\nabla_\theta \mathcal{L}_{\mathrm{DPO}} = \mathbb{E} \left[\frac{\sigma'(\delta r_\theta)}{\sigma(\delta r_\theta)} \, \nabla_\theta \delta r_\theta \right] \tag{20}$$

Using $\sigma'(z) = \sigma(z)(1 - \sigma(z))$:

$$\nabla_\theta \mathcal{L}_{\mathrm{DPO}} = -\mathbb{E} \left[(1 - \sigma(\delta r_\theta)) \cdot \nabla_\theta \delta r_\theta \right] \tag{21}$$

The gradient of δr_θ simplifies to:

$$\nabla_\theta \delta r_\theta = \nabla_\theta \log \pi_\theta(\mathbf{y}_w|\mathbf{x}) - \nabla_\theta \log \pi_\theta(\mathbf{y}_l|\mathbf{x}) \tag{22}$$

The final DPO gradient is:

$$\nabla_\theta \mathcal{L}_{\mathrm{DPO}} = -\beta \, \mathbb{E} \left[(1 - \sigma(\delta r_\theta))[\nabla_\theta \log \pi_\theta(\mathbf{y}_w|\mathbf{x}) - \nabla_\theta \log \pi_\theta(\mathbf{y}_l|\mathbf{x})] \right] \tag{23}$$

This formulation optimizes preferences using a re-weighted maximum likelihood without requiring a separate reward model or RL training.

Preference Optimization and Vision-Language Alignment   The application of SVP for vision-language alignment shares conceptual similarities with DPO, though with notable distinctions. A key difference lies in our scoring mechanisms' approach to negative samples. While our scores can effectively guide ranking and top-K selection, a small difference between guided and prior distributions doesn't necessarily indicate an undesirable sample. Low scores may simply reflect cases where grounding information offers minimal improvement, such as when the base model's response is already grounded in the visual input, or the response does not require the visual information. Consequently, in SVP, the gradient information from negative samples provides limited value.

DPO employs a gradient re-weighting scheme based on how much a model's preference predictions deviate from ground truth. This acts as a soft sample selection mechanism, giving greater weight to more informative training examples. Our approach parallels this concept, though we implement a hard sample selection strategy that emphasizes examples offering greater vision-language alignment information.

J Qualitative Examples

Here we provide additional visualizations and examples to illustrate our method. The images used for captioning and visual queries were selected from the COCO2014 training set (Lin et al., 2014), while referring examples were sourced from the RefCOCO dataset (Kazemzadeh et al., 2014), specifically the val_lite set (Zhang et al., 2024b). The examples are presented with minimal post-processing, limited to the removal of special characters and correction of obvious grammatical errors. Both models were prompted using the protocols outlined in G. All hyper-parameters remained consistent across both models. The examples compare output of LLaVA-1.6 models sampling from the base model (w/o SVP) and sampling from the adapted model (w/ SVP). These comparisons provide qualitative insights into the performance differences between the base and adapted models.

J.1 Captioning Tasks

Instruction: Describe the content of this image as detailed as possible.

VLM response w/o SVP:
In the image, there are four pizzas in an oven. The oven is filled with racks, each holding a pizza. The pizzas are of different types, with various toppings visible. The oven is illuminated, casting a warm glow on the pizzas. The pizzas are arranged in two rows, with two pizzas in each row. The pizzas are cooking, as indicated by their position in the oven. The oven is a standard kitchen appliance, with a door that is open to reveal the pizzas inside. The pizzas are the main focus of the image, with their colors and textures contrasting against the dark interior of the oven. The image captures a moment of culinary preparation, with the pizzas in various stages of cooking.

VLM response w/ SVP:
In the image, there is a well-lit oven with a black interior. Inside the oven, there are three pizzas on the top rack and two pizzas on the bottom rack. On the top rack, the first pizza is on the left side of the oven. It has a golden brown crust and is topped with green peppers and mushrooms. The second pizza is on the right side of the oven. It also has a golden brown crust and is topped with green peppers and black olives. On the bottom rack, the first pizza is on the left side of the oven. It has a golden brown crust and is topped with mushrooms. The second pizza is on the right side of the oven.
The light inside the oven illuminates the pizzas, highlighting their toppings and crusts. The pizzas appear to be freshly baked, as their crusts are golden brown and their toppings are evenly distributed. The overall scene suggests a home or restaurant kitchen where pizzas are being prepared.

Instruction: Describe the content of this image as detailed as possible.

VLM response w/o SVP:
In the image, there is a large clock mounted on a building. The clock face is white with black numbers and hands. The building itself is adorned with intricate carvings and statues. There are three statues visible in the image. One statue is of a woman holding a shield, another is of a man holding a spear, and the third is of a man holding a scroll. The carvings and statues are detailed and appear to be made of stone. The building has a gray roof, and the clock is positioned in the center of the image. The statues are positioned on either side of the clock, with the woman on the left, the man with the spear in the middle, and the man with the scroll on the right. The overall scene is a blend of architectural and artistic elements.

VLM response w/ SVP:
In the image, there is a grand clock tower that is ornate and intricate. The tower is made of stone and is topped with a statue of a woman holding a sword. This statue is located at the top of the tower, near the center. The tower also features a large clock face on the front, which is situated below the statue. The clock face is white with black numbers and hands. Below the clock face, there are two smaller statues of people. These statues are positioned on either side of the clock face, with the one on the left being slightly larger than the one on the right. The tower is set against a gray brick background, which contrasts with the white stone of the tower. The overall scene suggests a sense of grandeur and history.

Instruction: Describe the content of this image as detailed as possible.

VLM response w/o SVP:
In the image, there are three objects: a pink frisbee, a pair of red sneakers, and a beer bottle. The pink frisbee is located in the foreground, with its star-shaped design prominently displayed. The red sneakers are positioned in the background, with one shoe slightly in front of the other. The beer bottle is also in the background, standing upright and slightly to the right of the sneakers. The objects are arranged in a way that suggests a casual, outdoor setting, possibly a park or a beach. The frisbee and sneakers are the main focus of the image, while the beer bottle adds a touch of leisure to the scene.

VLM response w/ SVP:
In the image, there is a casual outdoor setting with a pair of red and white Adidas shoes. The shoes are placed on a grassy area, with one shoe closer to the camera and the other slightly behind it. The Adidas logo is prominently displayed on both pairs of shoes. A pink frisbee with a blue star design is also present in the scene. It is positioned in the foreground, with the shoes in the background. The frisbee appears to be resting on the grass, and its bright color stands out against the natural backdrop.The overall scene suggests a leisurely outdoor activity, possibly a game of frisbee, with the Adidas shoes indicating a sporty or active lifestyle. The grassy area and the casual arrangement of the shoes and frisbee give the image a relaxed and informal vibe.

Instruction: Describe the content of this image as detailed as possible.

VLM response w/o SVP:
In the image, there is a large yellow bus parked on the side of a street. The bus is positioned on the right side of the image and is the most prominent object in the scene. It is a double-decker bus, which is characterized by its two levels of seating. The bus is parked next to a sidewalk, which is visible on the right side of the image. There are several people in the image, some of whom are standing near the bus. One person is standing on the sidewalk, while others are standing on the street. There is also a car parked on the left side of the image, which is partially visible. The bus is parked in front of a building, which is located on the left side of the image. The building is partially visible, with only the top part of it visible in the image. The bus is also parked near a tree, which is located on the left side of the image. The tree is partially visible, with only the top part of it visible in the image. The overall scene suggests a typical day in a city, with people going about their daily routines and public transportation being a common sight.

VLM response w/ SVP:
In the image, a large yellow bus dominates the scene, traveling down a city street. The bus is vibrant and appears to be in motion, heading towards the right side of the frame. Its size and bright color make it the main focus of the image. In the background, another bus can be seen, albeit much smaller and less prominent. It's positioned on the left side of the image, providing a sense of depth and perspective to the scene. On the right side of the image, there's a large advertisement. It's not clear what the advertisement is for, but its size and placement suggest it's a significant feature of the urban landscape. The setting appears to be a typical city street. Trees can be seen in the background, adding a touch of nature to the urban environment. There are also several people scattered throughout the image, going about their day, which contributes to the everyday, relaxed atmosphere of the scene. The overall composition of the image suggests a bustling city life, with public transportation playing a significant role. The buses, people, and advertisement all come together to paint a picture of a vibrant, active cityscape.

Instruction: Describe the content of this image as detailed as possible.

VLM response w/o SVP:
In the image, there are three horses standing in a dirt enclosure. The horse on the left is brown with a white blaze on its face. It is standing with its head turned to the side, looking towards the camera. The horse in the middle is white with a brown spot on its head. It is standing with its head turned to the side, looking towards the camera. The horse on the right is brown with a white blaze on its face. It is standing with its head turned to the side, looking towards the camera. The enclosure is made of metal fencing and there is a mountain visible in the background.

VLM response w/ SVP:
In the image, there are three horses standing in a dirt enclosure. The horse on the left is brown with a white stripe running down its nose. Its head is slightly turned to the left. The horse in the middle is white and stands with its head facing forward. The horse on the right is black and its head is turned to the right. The three horses are standing next to each other, separated by a metal fence. In the background, there is a clear blue sky and a mountain range. The overall scene is a serene outdoor setting.

Instruction: Describe the content of this image as detailed as possible.

VLM response w/o SVP:
In the image, there is a young boy standing on the shore of a body of water. The boy is wearing a striped shirt and has blonde hair. He is looking out towards the water, which is calm and reflects the light. In the distance, there is a boat on the water, and the horizon is visible. The boy is standing in front of a tree with green leaves, which is located on the shore. The overall scene suggests a peaceful day by the water.

VLM response w/ SVP:
In the image, a young boy is standing by a body of water. He is wearing a black striped shirt. His back is turned to the camera, and he is looking out at the water. The boy appears to be standing on a grassy area near the water's edge. The water in the image is calm and appears to be a lake or a large river. It is a clear day, and the sky is visible in the background. There are no other people or objects in the image. The boy is the only person present. The relative position of the boy to the water is such that he is standing on the right side of the image. He is standing closer to the foreground than the water, which is further back in the image. The boy is also standing to the right of the water.

Instruction: Describe the content of this image as detailed as possible.

Instruction: Describe the content of this image as detailed as possible.

VLM response w/o SVP:
In the image, there are three giraffes standing in a field. The giraffe on the left is bending its neck down towards the ground, possibly to reach for food or water. The giraffe in the middle is standing upright, with its neck extended upwards. The giraffe on the right is also standing upright, but its neck is bent down towards the ground. All three giraffes are facing the same direction, suggesting they might be looking at something in the distance. The field they are standing in appears to be dry and dusty, with no visible vegetation. There are no other objects or animals in the image.

VLM response w/ SVP:
In the image, there are three giraffes standing in a field. The giraffes are tall and majestic, with their long necks reaching upwards. The giraffe on the left is slightly bending its neck, possibly to reach for something. The giraffe in the middle is standing upright, and the giraffe on the right is also bending its neck. In the center of the image, there is a tall pole. The pole has a feeder attached to it, which is likely providing food for the giraffes. The pole is surrounded by the field, which appears to be dry and brown. The giraffes are spread out across the image, with the giraffe on the left being closer to the pole than the other two. The giraffe on the right is the furthest away from the pole. The giraffes are the main focus of the image, with their long necks and distinctive patterns standing out against the backdrop of the field.

VLM response w/o SVP:
In the image, there is a bathroom setting. The main object is a white toilet, which is positioned in the lower right corner of the image. The toilet is situated on a beige tiled floor. Above the toilet, there is a metal rack mounted on the wall. The rack holds a single magazine, which is titled "Architectural Digest". The magazine is displayed prominently on the rack, indicating that it is the main focus of the rack's purpose. The overall scene suggests a well-organized and aesthetically pleasing bathroom space, with the magazine rack providing a functional and decorative element. The white toilet contrasts with the beige tiles, creating a clean and modern look. The magazine on the rack adds a touch of sophistication and suggests an interest in architecture or design.

VLM response w/ SVP:
In the image, there is a bathroom setting with a white toilet located towards the right side of the frame. Above the toilet, there is a magazine rack mounted on the wall. The rack holds two magazines, one titled "ARCHITECTURAL DIGEST" and the other "EXOTIC HOMES". The "ARCHITECTURAL DIGEST" magazine is positioned slightly higher than the "EXOTIC HOMES" magazine, and both are centrally located within the rack. The "EXOTIC HOMES" magazine is situated directly below the "ARCHITECTURAL DIGEST" magazine. The bathroom walls are beige, and the overall scene suggests a quiet and relaxed atmosphere.

J.2 Referring Tasks

Instruction: Provide a short description for this region.

VLM response w/o *SVP*:
The image shows a man sitting in the foreground, looking to the side with a serious expression. Behind him, there is another man standing on a boat, gesturing with his hands. The boat has a lifebuoy with the word "UNDER" on it, and the man standing is wearing a white cap and sunglasses. The background features a clear blue sky and calm water, with a few boats visible in the distance. The overall setting suggests a leisurely day out on the water.

VLM response w/ *SVP*:
A man wearing a white hat and sunglasses.

Instruction: Provide a short description for this region.

VLM response w/o *SVP*:
The image shows a bag of donuts with the brand name "NATAS" printed on it. The donuts are visible through the clear plastic packaging, and there are three donuts in total. The donuts appear to be of a similar type, possibly a ring donut, and they are placed on a white surface. The background is blurred, but there is a hint of a beige or light brown object to the right of the bag. The text on the bag is in Japanese, and the donuts have a hole in the center, which is typical for ring donuts.

VLM response w/ *SVP*:
A donut in a bag.

Instruction: Provide a short description for this region.

VLM response w/o SVP:
The image shows a person holding a mug with a flamingo design. The mug features two flamingos, one pink and one white, surrounded by green foliage and blue flowers. The design is colorful and playful, with the flamingos depicted in a stylized manner. The mug has a white handle and is placed in front of a computer keyboard, suggesting that the person might be using the computer while enjoying their drink. The background is blurred, but it appears to be an indoor setting with a desk or table.

VLM response w/ SVP:
A white coffee mug with a flamingo design.

Instruction: Provide a short description for this region.

AUG   12

VLM response w/o SVP:
The image is a black and white photograph capturing a moment on a tennis court. In the foreground, there are two men standing on the court. The man on the left is holding a tennis racket and appears to be speaking into a microphone, suggesting he might be a commentator or announcer. He is wearing a white shirt and shorts, which is typical attire for a tennis player or official. The man on the right is seated on the edge of the court, holding a tennis racket and smiling, possibly a player or a coach. He is wearing a white shirt and black shorts. In the background, there is a fence separating the court from the spectator area, and beyond the fence, there are trees and buildings, indicating that the court is part of a larger sports complex or club. The sky is clear, suggesting it might be a sunny day. The image has a vintage or retro feel due to the black and white filter and the style of the clothing and the court's design. The text "THE FIRST ANNUAL WEST SIDE TENNIS CLUB" and "EVIAN RACQUET CUP 2012" are visible, indicating that this is an event sponsored by Evian, a brand known for its water products. The date "AUG 12" is also visible, which is likely the date of the event. The overall atmosphere of the image is casual and relaxed, with the focus on the tennis court and the people involved in the event.

VLM response w/ SVP:
A man holding a tennis racket.

Instruction: Provide a short description for this region.

VLM response w/o *SVP:*
The pizza is in a box.

VLM response w/ *SVP:*
A slice of pizza.

Instruction: Provide a short description for this region.

VLM response w/o *SVP:*
This is a photo of a man riding a motorcycle with a dog sitting on the back. The man is wearing a black helmet and a black vest, and the dog appears to be a golden retriever. The man is also wearing a black tank top and blue jeans. The motorcycle is black and has a large engine. The setting appears to be an outdoor event or gathering, as there are other motorcycles parked in the background and a yellow police tape is visible in the foreground. The man is taking a photo of the scene with his cell phone.

VLM response w/ *SVP:*
A man taking a picture of a dog sitting on a motorcycle.

J.3 Visual Queries

Instruction: What activity could potentially be enjoyed near the area shown in the image?

VLM response:
The image shows a wooden bench situated near a body of water, possibly a lake or a river. Given the serene and peaceful setting, one could potentially enjoy various activities such as: Sitting on the bench to relax, read a book, or simply enjoy the view of the water and the surrounding landscape. Taking a leisurely walk or jog along the water's edge, enjoying the tranquility and the natural beauty of the area. Engaging in photography, capturing the picturesque scenery and the reflections on the water's surface. Bird watching, as the area might be home to various bird species. Fishing, if the water body is a lake or a river with fish populations. Picnicking with friends or family, enjoying a meal outdoors in the fresh air and the calming presence of the water. These activities are suitable for the setting depicted in the image, offering a chance to unwind and connect with nature.

Instruction: What are some factors contributing to the difficulty of this activity?

VLM response:
The image shows a person skiing on a steep, snow-covered slope. The difficulty of this activity can be attributed to several factors: Terrain: The steepness of the slope increases the challenge of maintaining balance and control while skiing. Steeper slopes require more advanced skiing techniques and greater physical strength. Snow Conditions: The type of snow can greatly affect the difficulty of skiing. In the image, the snow appears to be well-packed, which can make it harder to carve turns and maintain speed. Visibility: The image shows a cloudy day, which can reduce visibility and make it more difficult to navigate the slope. Equipment: The skier is wearing a backpack, which can add extra weight and affect balance and maneuverability. Weather: The cloudy day suggests that the weather conditions might be challenging, with the possibility of poor visibility, cold temperatures, or even snowfall. Skill Level: The skier's skill level plays a significant role in the difficulty of the activity. More advanced skiers are better equipped to handle steep slopes and challenging

K   Details

K.1   Baselines

We conduct a comprehensive comparison against various baselines, including models fine-tuned with self-captioning without grounding and preference-based adaptation methods. Our evaluation encompasses a wide range of model scales (.5B, 7B, 8B, 13B, 19B, 40B parameters), architectures (LLaVA-1.5 (Liu et al., 2024a), LLaVA-1.6 (Liu et al., 2024b), LLaVA-OV (Li et al., 2024), VILA (Lin et al., 2024), InternVL (Chen et al., 2024b)), visual encoders (CLIP (Radford et al., 2021), SigLIP (Zhai et al., 2023), ViT (Dosovitskiy et al., 2020)), language encoders (Vicuna (Chiang et al., 2023), Mistral (Jiang et al., 2023), Qwen2 (Yang et al., 2024), Yi-2 (Young et al., 2024)), and scoring mechanisms $S(q, p)$ and $\Delta(q, p)$.

K.2   Implementation Details

We implement two SVP variants: SVP (C) using only grounded self-generated captions, and SVP (CVQ) which additionally incorporates visual queries from the model's training set to prevent over-specialization on descriptive tasks. For the sampling loop, we generate K (20 for LLaVA-1.5 and LLaVA-1.6, 10 for LLaVA-OV) samples per image from both base and grounded VLMs, selecting the `top-k` (20% for LLaVA-1.5 and LLaVA-1.6, and 10% for LLaVA-OV) using our scoring mechanisms (Eq. 5, 6).

For example, with LLaVA-1.6 and $C = 1000$ images, we collect ~4000 samples for SVP (C) and double this for SVP (CVQ) by including visual queries, yielding ~8000 total training pairs. While smaller than typical supervised datasets, this proves sufficient for effective model adaptation (Sun et al., 2023; Zhu et al., 2024). We use normalized `xyxy` bounding boxes and filter out degenerate samples ($< 0.5\%$ for LLaVA-1.5/1.6, 5% for LLaVA-OV), with $w_{v,t} = q_{v,t}$.

For the adaptation loop, we fine-tune using LoRA (Hu et al., 2021) ($\alpha = 16$, $r = 64$ for $\leq$ 7b models; $\alpha = 256$, $r = 128$ for 13b models) for one epoch on 8-A100 GPUs with batch size $B = 20$. Following (Li et al., 2024; Liu et al., 2024b), we run up to 3 iterations of SVP. Our evaluation uses sample-wise, zero-shot testing without prompt engineering or batching to ensure fair comparison across model variants.

K.3   Metrics

We use the CIDEr score (Vedantam et al., 2015) for captioning and referring tasks; accuracy for VQA and multitasking. F1, Accuracy and Recall for hallucination and object recall. We also consider standard metrics for language translation like BLEU (Papineni et al., 2002), METEOR (Banerjee & Lavie, 2005), and ROUGE (Lin, 2004) scores. We re-compute metrics for LLaVA baselines and variants (1.5, 1.6, OV) up to 13b parameters.

K.4 Datasets

Table 17: Datasets utilized in `SVP`. We use COCO2014 images as conditioning for building visual projections, using self-captioning and grounding feedback. VP: visual projection. VQA: visual question answering. REG: referring expression generation. We use `lmms-eval` (Zhang et al., 2024b) for all the evaluations. The `lite` splits as proposed in (Zhang et al., 2024b).

Dataset	Task	Split	N
Sampling			
COCO2014 (Lin et al., 2014)	VP	train	100:10000
Evaluation			
ScienceQA (Saikh et al., 2022)	VQA	test	4241
GQA (Hudson & Manning, 2019)	VQA	lite	500
COCO2017 (Lin et al., 2014)	Captioning	val_lite	500
Flickr30k (Plummer et al., 2015)	Captioning	test_lite	500
NoCaps (Agrawal et al., 2019)	Captioning	val_lite	500
COCO2014 (Lin et al., 2014)	Captioning	val	40504
COCO2017 (Lin et al., 2014)	Captioning	val	5000
Flickr30k (Plummer et al., 2015)	Captioning	test	31783
NoCaps (Agrawal et al., 2019)	Captioning	val	4500
RefCOCO (Kazemzadeh et al., 2014)	REG	val_lite	500
RefCOCO (Kazemzadeh et al., 2014)	REG	val	8811
RefCOCO (Kazemzadeh et al., 2014)	REG	test	5000
RefCOCO (Kazemzadeh et al., 2014)	REG	testA	1975
RefCOCO (Kazemzadeh et al., 2014)	REG	testB	1810
RefCOCO+ (Kazemzadeh et al., 2014)	REG	val	3805
RefCOCO+ (Kazemzadeh et al., 2014)	REG	testA	1975
RefCOCO+ (Kazemzadeh et al., 2014)	REG	testB	1798
RefCOCOg (Kazemzadeh et al., 2014)	REG	val	7573
RefCOCOg (Kazemzadeh et al., 2014)	REG	test	5023
MMBench (Liu et al., 2025)	Multitasking	en_dev_lite	500
MMMU (Yue et al., 2024)	Multitasking	val	900
POPE (Li et al., 2023b)	Hallucinations	adv	3000
POPE (Li et al., 2023b)	Hallucinations	pop	3000
POPE (Li et al., 2023b)	Hallucinations	random	3000

K.5 Hyperparameters

Table 18: Hyper-parameters for the main experiments.

	LLaVA-1.5-13b	LLaVA-1.6-7b	LLaVA-1.6-13b	LLaVA-OV-0.5b	LLaVA-OV-7b
Sampling					
images	1000	1000	1000	2000	2000
iterations	1	1	1	1	1
prompt-version	llava_v1	mistral_instruct	llava_v1	qwen_1_5	qwen_1_5
sample-batch	20	20	20	10	10
samples/image	20	20	20	10	10
top k	0.2	0.2	0.2	0.1	0.1
Training					
accelerators	A100	A100	A100	A100	A100
deepspeed	w/ ZeRO-2	w/ ZeRO-3	w/ ZeRO-3	w/ ZeRO-3	w/ ZeRO-3
epochs	1	1	1	3	3
grad-acc	1	1	1	2	2
learning-rate	$2e^{-4}$	$2e^{-4}$	$2e^{-4}$	$1e^{-5}$	$1e^{-5}$
lora	w/	w/	w/	w/ and w/o	w/ and w/o
lora-α	256	16	256	16	16
lora-r	128	64	128	64	64
lr-schedule	cos	cos	cos	cos	cos
max-tokens	2048	2048	2048	1024	1024
mix-precision	w/	w/	w/	w/	w/
optimizer	AdamW	AdamW	AdamW	AdamW	AdamW
samples	4000:8000	4000:8000	4000:8000	2000	2000
text-encoder	Vicuna-13b-v1.5	Mistral-7b-Instruct-v0.2	Vicuna-13b-v1.5	Qwen2-0.5b	Qwen2-7b
train-batch	16	16	16	4	4
vision-encoder	CLIP-L/14	CLIP-L/14	CLIP-L/14	SigLIP-SO/14	SigLIP-SO/14
warm-up-rate	0.03	0.03	0.03	0.03	0.03