Let Your Light Shine: Foreground Portrait Matting via Deep Flash Priors

Abstract

In this paper, we delve into a new perspective to solve image matting by revealing the foreground with flash priors. Previous Background Matting frameworks require a clean background as input, and although demonstrated powerfully, they are not practical to handle real-world scenarios with dynamic camera or background movement. We introduce the flash/no-flash image pair to portray the foreground object while eliminating the influence of dynamic background. The rationale behind this is that the foreground object is closer to the camera and thus received more light than the background. We propose a cascaded end-to-end network to integrate flash prior knowledge into the alpha matte estimation process. Particularly, a transformer-based Foreground Correlation Module is presented to connect foregrounds exposed in different lightings, which can effectively filter out the perturbation from the dynamic background and also robust to foreground motion. The initial prediction is concatenated with a Boundary Matting Network to polish the details of previous predictions. To supplement the training and evaluation of our flash/no-flash framework, we construct the first flash/no-flash portrait image matting dataset with 3,025 well-annotated alpha mattes. Experimental evaluations show that our proposed model significantly outperforms existing trimap-free matting methods on scenes with dynamic backgrounds. Moreover, we detailedly discuss and analyze the effects of different prior knowledge on static and dynamic backgrounds. In contrast to the restricted scenarios of Background Matting, we demonstrate a flexible and reliable solution in real-world cases with the camera or background movements.

1 Introduction

Image matting has been a core and fundamental problem in computer vision that extensively applied in film production, social media, video conferencing, and many other fields. Nowadays, video conferencing has become the status quo in business and educational contexts, and image matting can be used to prevent privacy leakage by replacing a virtual background. Mathematically, the image matting problem can be formulated as

$$I = \alpha F + (1 - \alpha)B, \tag{1}$$

where the foreground F, background B, and the pixel-wise opacity α are unknowns. Given an input image I in RGB representation, estimating seven unknown factors are obviously an ill-posed problem.

To resolve this problem, traditional matting methods (Ruzon & Tomasi, 2000; Chuang et al., 2001; Wang & Cohen, 2007; Gastal & Oliveira, 2010; He et al., 2011; Feng et al., 2016) usually rely on a trimap as a prior to limit the solution space. However, generating a high-quality trimap is time-consuming and impractical in real-time applications. Recently, some trimap-free methods are proposed to replace the trimap with other prior knowledge. Such of methods adopt the clean background (Sengupta et al., 2020; Lin et al., 2021), semantic mask (Chen et al., 2018; Yu et al., 2021b; Park et al., 2023; Jiang et al., 2025), or temporal features in videos (Sun et al., 2021b; Lin et al., 2022; Li et al., 2023a; 2024a;b; Lin et al., 2023), as auxiliaries to predict the alpha matte.

Among these methods, Background Matting series (*i.e.*, BGMv1 (Sengupta et al., 2020) and BGMv2 (Lin et al., 2021)) achieves robust performances by taking a clean background as an additional input (see Fig. 1a).

(a) Inputs of BGMv2   (b) Inputs of our model

Figure 1: We consider the portrait matting problem in the dynamic scene. BGMv2 (Lin et al., 2021) requires two images (a) as inputs. However, their assumption of a clean and static background image does not hold in a dynamic scene, in which it produces a poor alpha matte. We propose a new setting to use an additional flash image to shed light on the foreground object. Our setting is robust to misalignments like background objects and camera movements.

This clean and static background provides a very strong prior knowledge that objects that have not appeared in the background image must belong to the foreground. With great assumption comes great restriction, background matting cannot handle any types of movements that make the source image not aligned with the background image.

In this paper, we resolve this problem from an opposite perspective. Instead of providing background hints, we shed light on the foreground regions with flash photography. The rationale behind is that foreground objects are typically closer to the camera and thus received more lights than the background. Taking an additional flash input can not only provide strong foreground clues, it also enables a more flexible and practical setting: 1) users are not required to take the additional reference image in advance (*e.g.*, background image in BGM), and the matting process can start together with filming; 2) main objects can move around, and we can take a new flash image anytime during filming to adapt to the new scene.

To fully exploit flash priors, we devise the Flash and No-flash Net (FNFNet), which uses flash/no-flash image pair to produce high-resolution portrait alpha matte and the foreground of the no-flash image. The estimation is insensitive to moving foreground, background misalignment, and camera shaking. Our FNFNet consists of two cascaded stages. The first stage aims to explore the interaction between flash and no-flash images, and provides coarse estimations of trimap and initial alpha matte. Concretely, we propose a transformer-based Foreground Correlation Module (FCM) to jointly identify illumination-irrelevant foreground appearances across two inputs in a reciprocal manner. Moreover, we calculate a flash ratio map between flash/no-flash images as a coarse indicator of foreground regions to supplement the alpha matte estimation. In the second stage, the trimap and initial alpha matte are fed to the Boundary Matting Network, which has a unique emphasis on producing fine boundary details of the mattes.

In order to train and evaluate our method and promote research on flash photography, we construct the first flash/no-flash portrait matting dataset. It consists of more than 100 diverse videos captured using the green screen, in total containing 3,025 well-annotated alpha mattes. We also collect dynamic videos of various real-world scenes to compose dynamic background image pairs. Therefore our benchmark can be used to evaluate

matting methods with static and dynamic backgrounds. Several trimap-free matting methods are compared on this benchmark. Extensive experiments show that our proposed method achieves superior performances on the scenarios with dynamic backgrounds, and our flash prior demonstrates comparable performance to the background prior in static scenes.

In summary, our contribution is fourfold:

- We construct the first flash/no-flash portrait matting dataset. It consists of more than 100 diverse videos with 3,025 well-annotated alpha mattes. We collect additional dynamic background videos, together with static backgrounds, to form a benchmark for evaluating the matting performance on both scenarios.

- Rather than relying on a clean background, we propose a deep flash prior, which enables a more flexible and practical solution for real-time or live-streaming matting.

- We propose FNFNet to integrate flash photography into a deep neural network. It explores the interaction between two differently illuminated foregrounds to extract high-quality alpha matte.

- Experiment results show that our model achieves state-of-the-art performance among other trimap-free matting methods. More importantly, our method is insensitive to the dynamic background and not restricted to well-aligned foreground or background between source and reference images.

2 Related work

2.1 Trimap-based Matting

Traditional methods often require a manually annotated trimap as additional information for solving the matting problem, which can be classified into sampling-based methods and propagation-based methods. Sampling-based methods (Ruzon & Tomasi, 2000; Chuang et al., 2001; Wang & Cohen, 2007; Gastal & Oliveira, 2010; He et al., 2011; Feng et al., 2016; Johnson et al., 2016) sample pixels from the labelled foreground and background regions to get the color information, and then estimate the alpha matte of the unknown region. Propagation-based methods (Sun et al., 2004; Levin et al., 2007; 2008; Chen et al., 2013; Aksoy et al., 2017) build the similarity of neighboring pixels, trying to propagate alpha value from known to unknown regions. Since the above methods only utilize low-level features, they seldom achieve good performance in complex scenes. With the rapid development of deep learning, many methods (Yao et al., 2024; Cai et al., 2022; Park et al., 2022; Lutz et al., 2018; Tang et al., 2019; Liu et al., 2021c) based on neural network have been explored and have made unprecedented progress in image matting, which have been comprehensively reviewed in Li et al. (2023b); Lepcha et al. (2023). Xu *et al.* (Xu et al., 2017) proposes a two-stage neural network structure named Deep Image Matting (DIM) to obtain the coarse alpha and refined alpha matte, respectively. They also collects the first large-scale matting dataset, which empowers the development of many following works. Hou *et al.* (Hou & Liu, 2019) employs two encoders to extract local features and the global context information respectively, and estimates foreground and alpha simultaneously. Lu *et al.* (Lu et al., 2019) presents IndexNet, which can dynamically generates indices as conditions to guide the matting context modelling and operating. GCAMatting (Li & Lu, 2020) designs a Guided Contextual Attention module to propagate global high-level features based on the learned low-level affinity. Cai *et al.* (Cai et al., 2019) disentangles image matting into two sub-tasks: trimap adaptation and alpha estimation, with a disentangled framework proposed named AdaMatting to solve them. Yu *et al.* (Yu et al., 2021a) extend the matting problem to high-resolution images relying on a patch-based method with several modules to capture long-range matting contextual and handle information propagation. Zhang *et al.* (Zhang et al., 2021) suggest propagating the trimap via temporal dimension to achieve video object matting using a temporal aggregation module. In Sun et al. (2021a) and Liu et al. (2021a), semantic classification of matting regions is incorporated into the matting framework. Recently, some methods leverage diffusion algorithm (Ho et al., 2020) to facilitate image matting, including diffusing in pixel space by diffusing a disturbed trimap (Xu et al., 2023) or pure noise (Hu et al., 2024) until a clean alpha matte is produced, or diffusing in latent space (Li et al., 2024d). However, as trimap-based methods rely on a well-annotated trimap as the input for generating plausible results, they often fail to be applied in real-time scenarios.

2.2 Trimap-free Matting

Many recent works (Zhang et al., 2019; Dai et al., 2022; Zhu et al., 2017; Shen et al., 2016; Chen et al., 2018; Liu et al., 2020; Yu et al., 2021b; Qiao et al., 2020; Park et al., 2023; Jiang et al., 2025) try to relax trimap input by adding a segmentation process before acquiring the final alpha matte, while matting performance overly depends on the results of segmentation. HAttMatting (Qiao et al., 2020) introduces a blended attention mechanism to integrate features. Self-guidance provided by Progressive Refinement Network (PRN) module in Yu et al. (2021b) can deal with versatile guidance masks. LFPNet (Liu et al., 2021b) learns long-range context features outside the reception field and propagates learned surrounding features to help matting prediction inside the reception field. Sun *et al.* (Sun et al., 2022) introduce flaw detection as a sub-task to achieve automatic error-correcting in trimap-free portrait matting problems. Lin et al. (2022); Li et al. (2023a); Sun et al. (2023); Li et al. (2024a); Gu et al. (2023); Li et al. (2024b); Lin et al. (2023) adopt temporal information in the video as guidance to do the video objects or portrait matting. However, the temporal priors relied on by these video matting methods may face challenges in various dynamic backgrounds. Recently, some trimap-free matting methods (Ke et al., 2022; Chen et al., 2022b;a; Li et al., 2022; Ma et al., 2023) follow the idea of decomposing the matting problem into semantic prediction and detail prediction and then considering fusion or collaboration between these two sub-objectives. However, these methods usually perform worse than trimap-based methods in matting quality. Some methods take advantage of the text-image correspondence prior (*e.g.*, CLIP (Radford et al., 2021)) to achieve referring image matting (Xu et al., 2024; Li et al., 2023c). Some methods also try to directly solve the alpha via in-context prior (Guo et al., 2024), latent diffusion prior (Wang et al., 2024), or vision foundation model (Ye et al., 2024; Li et al., 2024c). Sengupta *et al.* (Sengupta et al., 2020) proposes Background Matting (BGM) which only requires a pre-captured background image without foreground objects as auxiliary cues to help determine the position of the foreground. This method achieves high-quality results. Based on Sengupta et al. (2020), Lin *et al.* (Lin et al., 2021) further uses a two-stage network to realize real-time high-resolution matting. However, background matting cannot handle dynamic backgrounds and large camera movements.

2.3 Flash Photography Applications

The advantages of exploiting flash photography have been explored in many computer vision tasks. For adopting flash and no-flash image pairs, specially, Sun *et al.* (Sun et al., 2006) tries to recover the matte based on the simple observation that the most noticeable difference between the flash and no-flash images is the foreground object if the background scene is far enough away. Additional information given by flash/no-flash image pairs is also explored in He & Lau (2014) for saliency detection. However, they strictly require perfect alignment for the foregrounds in flash and no-flash images, making it unsuitable for scenarios involving dynamic foregrounds. Sun *et al.* (Sun et al., 2007) suggests adopting a Markov Random Field to combine flash, motion, and color cues and model the flash effect using the histograms of the flash/no-flash images. However, it strongly relies on several strict low-level feature assumptions like the background consistency (*i.e.*, near-bijective relationship for the background region) and obvious contrast due to flash in foreground regions in flash/no-flash image pairs, making it fail when the foreground undergoes significant pose variations, or when the background exhibits dynamic changes (*e.g.*, new objects appearing), or the flash contrast for the foreground is not obvious.

In our work, we explore the previously unaddressed connection between flash cues and high-level instance-level representations. By modeling instance-level matching representations, our method effectively tackles the challenges of dynamic flash matting, including variations in foreground pose and position, as well as interference from dynamic backgrounds.

3 FNF Matting Dataset

To the best of our knowledge, there does not exist an available large-scale dataset containing flash and no-flash image pairs that can be used for portrait matting. Therefore, we construct the first flash and no-flash portrait matting dataset by combing foreground portraits (Fig. 2a) and dynamic background scenes (Fig. 2b) together.

Flash frames   Flash GT   No-flash frames   No-flash GT

(a) Examples of selected flash/no-flash portrait frames and corresponding GT alpha matte in our dataset.

(b) Examples of dynamic backgrounds in our dataset.

Figure 2: Examples from our dataset: (a) flash/no-flash portrait frames with ground truth alpha mattes, and (b) dynamic backgrounds.

3.1 Data Collection and Processing

Foreground Portrait. To collect the foreground portrait videos, we take the green screen as the background and use the two latest smartphones for shooting. We invited 133 participants (66 males and 67 females) for taking the videos. Each video is in a resolution of 1080P and lasts around 20 seconds. Participants were asked to act on some common actions that happened during the online meeting for simulating the real scenarios, such as turning around, talking, and playing with their hair. A hand-held lamp is used for generating the flash and no-flash effects. We ensure the lighting conditions and camera settings are consistent across all videos, to minimize individual bias and improve annotation convenience. For each video, we use the Super Key function in Adobe Premiere to extract the foregrounds and alpha mattes automatically. In practical, process a single video only takes less than 10 minutes, and the entire annotation process for the dataset was completed in several days with 3 skilled workers. As shown in Fig. 2a, our dataset covers diverse foreground portraits under common matting cases, such as long and spread hair (*e.g.*, 4[th] row of Fig. 2a) and transparent area (*e.g.*, eyeglasses in 2[nd] row of Fig. 2a). The portraits are also in different clothes and poses to enhance the robustness of the model. In total, we obtain 1,322 flash and 1,703 no-flash portraits with their well-annotated alpha mattes.

Dynamic Background. For background, we collect 714 videos under diverse real-world scenes from the Internet. We sample frames from each video with an interval of 15, and we only select 20 frames at most from each video. Several examples have been shown in Fig. 2b.

We split the dataset for training and testing in the video-level and show the statistics in Tab. 1.

3.2 Dataset Statistics Analysis

To gain more knowledge from our dataset, we conduct some statistic analysis in this subsection and show the results in Fig. 3.

3.2.1 Flash/no-flash Frames

The number of selected flash/no-flash frames of each person (*i.e.*, video) is shown in Fig. 3a. We can see that majority of video has no less than 20 flash and no-flash frames in total. Some video has more than 20

(a) The number of flash/no-flash frames per person, sorted in decreasing order of the total number of frames selected for each person.

(b) The distributions of resolution (left, height×width) and frame rate (right, fps) of dynamic backgrounds.

(c) The number of background videos under different scenes.

Figure 3: The statistics of the proposed FNF Matting dataset. We show that the dataset has a rational distribution of flash/no-flash foregrounds for each green-screen portrait video. We also illustrate some basic properties (resolution and frame rate) of collected dynamic background videos and distribution in various scenes.

selected frames, indicating they contain more various poses or complexity in the edge area of the portrait (*e.g.*, hair, eyeglasses, etc.) relatively. Videos with 20 selected frames are common in portrait variety and normal quality, while videos with poor recording quality have less than 20 selected frames.

Table 1: Statistics of our proposed dataset.

	Training Set	Test Set	Total
Protrait Videos	111	22	133
Flash Frames	1,102	220	1,322
No-flash Frames	1,408	295	1,703
Dynamic Background Videos	625	89	714
Dynamic Background Frames	11,806	1,712	13,518

3.2.2   Resolution and Frame Rate of Dynamic Backgrounds

The left chart of Fig. 3b shows the resolution distribution of dynamic background videos. It can be seen that more than 80 percent of the videos have a resolution of 1080×1920, and almost all videos are high resolution. And the vast majority of videos are horizontal, and a few videos are vertical. The right chart of Fig. 3b shows the frame rate (fps) distribution of our dataset. In this chart, we approximate some videos with standard frame rates to the nearest integer frame rates when counting statistics (*e.g.*, video in 29.97 fps is counted as 30 fps). Nearly half of the videos have a frame rate of 30 fps, and most of the videos are recorded at a common frame speed. About 10 percent of the videos have a higher frame rate (*e.g.*, 50 fps, 60 fps, etc.), which means that the difference between two adjacent frames of these videos may be smaller in general.

3.2.3   Scenes of Background Videos

Our dataset consists of background videos across 29 categories, and the specific statistics are shown in Fig. 3c. As can be seen, the category "city" is the most common one in our dataset, as most of our background videos come from urban street views. There are also many videos shot in places such as building interiors and natural landscapes. Almost all of them record dynamic changing due to camera shaking or movement, pedestrian or vehicle movement, water flowing, or other dynamic changes. Examples of such changes can also be found in Fig. 2b.

3.3   Mitigating Synthetic Data Discrepancy

In light of the disparities between composite data used for training and natural data, such as differences in resolution, noise distribution, and composite artifacts between the foreground and background, we have adopted techniques from Li et al. (2022) to address these discrepancies. To tackle resolution differences, we have meticulously selected background videos with high resolutions that align with those of the foreground videos, as elaborated in Sec. 3.2.2. In addressing differences in noise distribution, we initiate the process by applying BM3D (Dabov et al., 2009) for denoising both the foreground and background. Subsequently, we introduce Gaussian noise with the same deviation to further refine the composition. To further mitigate composite artifacts, we incorporate the re-JPEG (Hou & Liu, 2019) operation into our data augmentation strategy for training samples.

4   Method

Considering the person in front of the camera cannot remain completely still and the background may also undergo some dynamic changes in real-world video conference scenes, we need to take full advantage of the assumption that flash has a significant enhancement of foreground color intensity. This leads us to establish a non-local relationship between foreground person in flash and no-flash images, providing foreground location cues to guide the matting of no-flash image.

To this end, we propose the Foreground Correlation Module (FCM), a dual-branch and Transformer-based component to integrate implicit foreground information extracted from flash image to no-flash image features.

Figure 4: Overview of our FNFNet structure. Given a pair of flash/no-flash images $\{I^f, I^{nf}\}$ as input, we first down-sample them with a scale factor $c'(c' \leq 0.1)$ to $\{I^f_{c'}, I^{nf}_{c'}\}$, and calculate the smoothed flash ratio map (r^f_p) of the flash image according to the interior transfer of pixels affected by flash in the image histograms. Then we randomly select q points from the truncated ratio map as flash cues, and adopt a pretrained segmentation model to extract the trimap t^f_c of the flash image I^f_c with down-sample scale $c(c \leq 0.5)$. The Coarse Matting Network (CMN) takes $\{I^f_c, I^{nf}_c, t^f_c\}$ as inputs and predicts low-resolution matting results of the no-flash image: trimap t^{nf}_c, detail map d^{nf}_c, foreground color F^{nf}_c with context hidden feature F^{nf}_c. The Boundary Matting Network (BMN) is further introduced to enhance the fine details and up-sample d^{nf}_c and F^{nf}_c to the original resolution (d^{nf}, F^{nf}).

Moreover, inspired by Sun et al. (2007); He & Lau (2014), we introduce the flash ratio map as another flash cue, imprecisely labelling pixels in both flash and no-flash images with significant intensity changes as foreground based on the image histogram. We furthermore embed FCM to the Flash and No-flash matting network (FNFNet) to obtain robust and high-quality alpha matte of the no-flash image in the dynamic background scene.

4.1   Model Overview

Fig. 4 demonstrates the pipeline of our proposed FNFNet. FNFNet includes a Coarse Matting Network (CMN) and a Boundary Matting Network (BMN). The CMN has two inputs, one is the down-sampled no-flash image I^{nf}_c, the other is the concatenation of flash image I^f_c with its trimap t^f_c (which is obtained by flash cues guided trimap prediction), two inputs are extracted to their high-level features respectively. Then these two features are fed into the Foreground Correlation Module (FCM) for feature aggregation, following three separate decoders to predict the trimap t^{nf}_c, detail map d^{nf}_c, and foreground prediction F^{nf}_c of the no-flash image. In BMN, we take the original no-flash image and reuse the first three layers of the encoder in CMN to extract low-level textual features, enabling BMN to recover details and up-sample the low-resolution outputs from CMN to produce the high-resolution detail map d^{nf} and foreground prediction F^{nf} of the no-flash image. Then the alpha matte α^{nf} of the no-flash image can be obtained by compositing the up-sampled trimap t^{nf} and detail map d^{nf}.

Figure 5: Demonstration of our flash ratio map. Foreground pixels are normally transferred from low intensity to high intensity due to the flash. Takes the i-th bin in the histograms of no-flash and flash image (h_i^{nf} and h_i^f respectively) as an example. If $h_i^{nf} > h_i^f$, it means that the number of pixels transferred to other bins is more than the newly added pixels. Therefore, pixels in the i-th bin of the no-flash image are more likely to be foreground. Similar conclusion can be found in the j-th bin of the flash image if $h_j^{nf} < h_j^f$.

(a) Original flash/no-flash pair with down-sample scale c'.

(b) Flash ratio maps calculated using Eq. (2) directly.

(c) Truncated ratio maps with $\delta = 0.7$.

(d) Smoothed ratio maps using medium filter with $r = 5$.

Figure 6: Examples of flash ratio maps. For pairs of down-sampled flash/no-flash images in (a), (b) shows the flash ratio maps computed by the differences between histogram distributions. We furthermore refine (b) by increasing truncate threshold δ (c) and applying medium filtering to get a smoother result (d).

4.2 Flash Guided Flash-Trimap Prediction

The additional flash provides strong cues on revealing foreground objects. Before getting into the network, we first derive an extra input of our framework, the trimap of flash image predicted using flash ratio map.

4.2.1 Flash ratio map

The flash ratio map is obtained by analyzing the differences between flash and no-flash histograms. The reason for utilizing the image histogram is that it gives the distribution of the color intensity of each pixel from the overall statistical level, making the produced flash ratio map insensitive to small background changes and foreground movements.

We denote the RGB color histogram of the flash images as $H^f = \{h_k^f\}$, and no-flash image histogram as $H^{nf} = \{h_k^{nf}\}$, where h_k indicates the corresponding number of pixel in the k-th bin. Here, both H^f and H^{nf} are computed in the entire RGB space, which ensures that the same index value (*i.e.*, "global" index) refers to the same color bin in both histograms, ensuring consistency across both images. We observe that the flash will modify and transfer some pixels in the low-intensity bins of the no-flash image histogram to the high-intensity bins of the flash image histogram (illustrated in Fig. 5), we have the following analysis with h_k^f and h_k^{nf}.

For $h_k^f > h_k^{nf}$, we can infer that some pixels in low-intensity bins of no-flash histogram have been transferred to the k-th bin of flash image histogram due to the flash effect. Thus, pixels in the k-th bin of the flash image histogram are more likely to be the foreground. While $h_k^f < h_k^{nf}$ indicates that some pixels in the k-th bin of the no-flash image histogram have been transferred to high-intensity bins of the flash image histogram. Similarly, pixels in the k-th bin of the flash image histogram have a higher probability of being the foreground.

Based on the above analysis, given a pair of flash/no-flash image, their corresponding flash ratio maps r_p^f and r_p^{nf} at pixel p can be quantified as:

$$r_p^f = \frac{h_{k_p}^f - h_{k_p}^{nf}}{h_{k_p}^f}, \quad r_p^{nf} = \frac{h_{k_p}^{nf} - h_{k_p}^f}{h_{k_p}^{nf}}, \tag{2}$$

where k_p is the bin index which contains p.

4.2.2 Flash-Trimap Processing

In order to get a flash ratio map that can provide a more accurate flash hint for further trimap prediction, we extract the confident points as flash cues by following steps. We first calculate the flash ratio map r^f of the down-sampled flash image $I_{c'}^f$ with the scale factor $\frac{1}{c'}$ using Eq. (2). Particularly, c' is usually set to be less than 0.1 to eliminate interference from irrelevant pixels as much as possible. Here we do not calculate r^{nf} because r^{nf} is often inaccurate while r^f has a more accurate estimate of the foreground in the flash image. In order to retain more reliable regions in r^f, we first perform truncation on r^f using following equation:

$$r^f := \begin{cases} r^f, & r^f \geq \delta \\ 0, & otherwise \end{cases} \tag{3}$$

where δ is a threshold to control the truncation level considering the flash ratio map may not be completely correct. r^f is further smoothed by applying the medium filter with kernel size r for further refinement.

We showcase intermediate results before and after smoothing in Fig. 6. To ensure that selected points are distributed evenly and do not accumulate in local areas, we randomly choose q points from r^f as flash cues and then map these points to the resolution of I_c^f. We employ a pretrained segmentation model to extract the segmentation mask of the foreground, using I_c^f and the flash cues as input. Subsequently, we derive the trimap t_c^f for I_c^f from the segmentation mask using an erosion-dilation operation. During training, to enhance the training process for the subsequent end-to-end network, we directly apply the erosion-dilation operation to the ground truth alpha α_c^f of I_c^f to obtain t_c^f.

4.3 Coarse Matting Network

Inspired by DeeplabV3 (Chen et al., 2017), our CMN has the encoder-decoder architecture, which includes two separate encoders with ResNet-50 (He et al., 2016) structures, the Atrous Spatial Pyramid Pooling (ASPP) modules, a Foreground Correlation Module (FCM), and three decoder networks for different types of output.

4.3.1 Backbone Network

Given a pair of flash and no-flash images $I^f, I^{nf} \in \mathbb{R}^{H \times W \times 3}$, we first down-sample them with a scale factor $\frac{1}{c}$ to $I_c^f, I_c^{nf} \in \mathbb{R}^{\frac{H}{c} \times \frac{W}{c} \times 3}$, and obtain one-hot trimap $t_c^f \in \{0,1\}^{\frac{H}{c} \times \frac{W}{c} \times 3}$ of I_c^f. As discussed in Sec. 4.1,

Figure 7: Overview of the Foreground Correlation Module (FCM). FCM consists of two branches: T^f and T^{nf}, each of which contains L_f and L_{nf} transformer layers respectively. Each layer in T^f only have Multi-head Self-Attention (MHSA), while in T^{nf}, each layer have the Multi-head Cross-Attention (MHCA). The Convolutional Block Attention Module (CBAM) (Woo et al., 2018) is applied for the reshaped feature outputted by T^{nf} for feature re-attention.

I_c^{nf}, and the concatenation between I_c^f and t_c^f are fed into the two non-shared encoders following the ASPP module separately to extract their respective feature maps, denoted as $x^f, x^{nf} \in \mathbb{R}^{h \times w \times C}$ respectively. Here, the ASPP module consists of three dilated convolution layers with dilation rates of 3, 6, and 9 to summarize the contextual information.

4.3.2 Foreground Correlation Module

As depicted in Fig. 7, we feed x^f and x^{nf} into the FCM. Our objective is to establish an association between the flash image and the no-flash information using a cross-attention mechanism. The leftmost branch, T^{nf}, comprises L_{nf} identical cross-attention layers, which are designed to facilitate the connection and fusion of the no-flash information with the foreground in the flash image. On the other hand, the rightmost branch, T^f, consists of L_f identical self-attention layers, focusing solely on extracting features from the flash image. Both of these branches take input sequences with a length of $h \times w$. To create these sequences, we apply a linear projection followed by a flatten operation to the input features x^f, x^{nf}, resulting in corresponding

input sequences denoted as $Z^f, Z^{nf} \in \mathbb{R}^{hw \times C'}$, where C' represents the dimension of the embedding space. Additionally, we incorporate learnable positional embeddings into these sequences.

Computation of $\mathbf{T^f}$: The embedded sequences Z^f is fed into T^f. At each layer l^f in T^f, we first calculate the triplet $(Q_{l-1}^f, K_{l-1}^f, V_{l-1}^f)$ of Z_{l-1}^f, the input of current layer. Then the self-attention SA_{l-1}^f is given as:

$$SA_{l-1}^f = \texttt{softmax}(\frac{Q_{l-1}^f(K_{l-1}^f)^T)}{\sqrt{d}})(V_{l-1}^f). \tag{4}$$

We further calculate the multi-head self-attention MSA_{l-1}^f with the residual connection by concatenating m independent self-attention operation following a linear projection. Then, a feed-forward network (FFN) with the residual connection is used to transform MSA_{l-1}^f and obtain the output $Z_l^f \in \mathbb{R}^{hw \times C'}$ of current layer:

$$Z_l^f = FFN_{l-1}^f(MSA_{l-1}^f) + MSA_{l-1}^f. \tag{5}$$

We denote $Z_{L_f}^f$ as the output of the last layer of T^f. Recall that L_f represents the layer number of T_f.

Computation of $\mathbf{T^{nf}}$: At each layer l^{nf} in T^{nf}, we utilize the multi-head cross-attention to fuse flash image features extracted from T^f with the input Z_{l-1}^{nf}. For multi-head cross-attention, denoted as MCA_{l-1}^{nf}, we first calculate the query(Q_{l-1}^{nf}) from MSA_{l-1}^{nf}, and the key (K_{l-1}^{nf}) and value(V_{l-1}^{nf}) from $Z_{L_f}^f$. Then MCA_{l-1}^{nf} can be similarly carried out based on Eq. (4). An FFN with the residual connection is applied for feature refinement to produce the output sequence Z_{l-1}^{nf} of current layer:

$$Z_{l-1}^{nf} = FFN_{l-1}^{nf}(MCA_{l-1}^{nf}) + MCA_{l-1}^{nf}. \tag{6}$$

We denote $Z_{L_{nf}}^{nf}$ as the output of the last layer of T^{nf}. Finally, $Z_{L_{nf}}^{nf} \in \mathbb{R}^{hw \times C'}$ is reshaped to shape of $\mathbb{R}^{h \times w \times C}$ and passed to the Convolutional Block Attention Module (CBAM) (Woo et al., 2018) for feature re-attention both in spatial and channel-wise and obtain $\widetilde{x}^{nf}$ for further decoding.

4.3.3 Decoders

Considering the distinct appearance of semantic and detail features, we adopt three non-shared decoders $(D_{trimap}, D_{detail}, D_{foreground})$ to predict the low-resolution trimap, detail of alpha prediction, and foreground color. Each of these decoders includes different number of Conv-BN-ReLU groups. In each group, the input feature is bilinear-upsampled with a scale factor 2, and then concatenated with the shortcut feature following a 3×3 convolution, batch normalization (Ioffe & Szegedy, 2015), and ReLU activation (Nair & Hinton, 2010).

The trimap decoder D_{trimap} only contains 2 groups of Conv-BN-ReLU considering D_{trimap} only responsible for coarse trimap estimation. It takes $\widetilde{x}^{nf}$ as input and outputs the classification probabilities with 3 classes (foreground, background, and unknown region) of all pixel of I_{4c}^{nf} at $\frac{1}{4}$ resolution of I_c^{nf}, denoted as $s_{4c}^{nf} \in [0,1]^{\frac{H}{4c} \times \frac{W}{4c} \times 3}$. Then we directly up-sample s_{4c}^{nf} to original resolution of I_c^{nf}, denoted as $s_c^{nf} \in [0,1]^{\frac{H}{c} \times \frac{W}{c} \times 3}$. By taking the Argmax operation, s_c^{nf} can be easily converted to the trimap prediction, denoted as $t_c^{nf} \in \{0,1,2\}^{\frac{H}{c} \times \frac{W}{c}}$.

The detail decoder D_{detail} is responsible for predicting fine alpha matte in the unknown region. For preserving rich low-level contextual features, D_{detail} consists of 3 groups of Conv-BN-ReLU, and takes shortcut feature of no-flash image encoder at 1/8 resolution of I_c^{nf} as input. It also receives the Argmax operation applied s_{4c}^{nf} from D_{trimap} and concatenate it with midden features before going into the second group, fusing semantic information in to better estimate detail alpha. D_{detail} finally outputs the detail alpha matte $d_c^{nf} \in [0,1]^{\frac{H}{c} \times \frac{W}{c} \times 1}$, which is only meaningful in the unknown region.

The foreground decoder $D_{foreground}$ consists of 4 groups of Conv-BN-ReLU and also takes $\widetilde{x}^{nf}$ as input. Following Lin et al. (2021), $D_{foreground}$ predicts the foreground residual R_c^{nf} and we then add the original image with clamping into $[0,1]$ to obtain the foreground color prediction of the no-flash image, denoted as $F_c^{nf} \in \mathbb{R}^{\frac{H}{c} \times \frac{W}{c} \times 3}$. $D_{foreground}$ also produces the hidden features $H_c^{nf} \in \mathbb{R}^{\frac{H}{c} \times \frac{W}{c} \times 32}$, which contains the contextual information of foreground. In addition, both D_{detail} and $D_{foreground}$ have skip connections with the no-flash image encoder (see in Fig. 4).

4.4 Boundary Matting Network

To obtain the matting result of the no-flash image with the original resolution, we design the boundary matting network to improve the matting result boundaries to high-resolution by incorporating low-level features. For the trimap t_c^{nf}, we directly take a bi-linear interpolation operation to up-sample it to the original resolution, denoted as t^{nf}. And for the detail map d_c^{nf} and foreground residual R_c^{nf}, we treat them differently for enhancement. We first adopt a bi-linear interpolation to up-sample the detail map feature (or foreground feature) to $\frac{1}{2}$ of the original resolution. Then, we reuse the first three layers from the backbone network in CMN, including a 7×7 convolutional layers, a batch-normalization layer, and a ReLU operation, to extract the low-level feature. We also apply several shallow convolutional layers with a small number of channels to process detailed low-level information. In detail, the low-level feature is concatenated with the detail map feature and passed into two groups of 3x3Conv-BN-ReLU to help restore the matting details. Furthermore, the output feature that has been interpolated to the original resolution, is concatenated with the original no-flash image and passed to another two groups of 3x3Conv-BN-ReLU (with the last ReLU removed) to obtain the final enhanced and high-resolution detail map (or foreground residual), denoted as d^{nf} (or R^{nf}).

4.5 Loss Function

4.5.1 Trimap Loss

To learn the trimap of the foreground, we adopt the cross entropy loss on the semantic classification probabilities s:

$$\mathcal{L}_{sem}(s) = -\sum_{c=1}^{3} s_{GT}^c \log s^c, \tag{7}$$

where $s^c \in [0,1]$ is the classification probability of c-th class in s and $s_{GT}^c \in \{0,1\}$ is the corresponding label. s_{GT}^c is generated by the dilation and erosion operation on the ground-truth alpha.

4.5.2 Alpha Loss

Before calculating the alpha loss, we convert the trimap prediction t to the corresponding binary class masks of the foreground, background, and unknown region, denoted as $\{t^{fg}, t^{bg}, t^{un}\}$. Then, the two alpha losses, calculated on both unknown region ($\mathcal{L}_{detail}$) and the whole image ($\mathcal{L}_{alpha}$), are given by the following equations.

$$\mathcal{L}_{detail}(d, t^{un}) = t^{un}\{\|d - \alpha_{GT}\|_1 + \|\nabla d - \nabla \alpha_{GT}\|_1 + \sum_{k=1}^{5} \|Lap^k(d) - Lap^k(\alpha_{GT})\|_1\}, \tag{8}$$

$$\mathcal{L}_{alpha}(\alpha) = \|\alpha - \alpha_{GT}\|_1 + \|\nabla \alpha - \nabla \alpha_{GT}\|_1 + \sum_{k=1}^{5} \|Lap^k(\alpha) - Lap^k(\alpha_{GT})\|_1, \tag{9}$$

where d is the predicted detail map, α_{GT} is the ground-truth alpha, and α is the alpha prediction given by $\alpha = d \cdot t^{un} + t^{fg}$. In addition to directly use the L1 loss, we also use the Sobel gradient operator (∇) and Laplacian pyramid ($Lap^k(\cdot)$) loss (Hou & Liu, 2019) to get better results.

4.5.3 Foreground Loss and Re-construction Loss

To learn the foreground color prediction, we adopt L1 loss on the foreground prediction F where $\alpha_{GT} > 0$:

$$\mathcal{L}_{fg}(F) = \|(\alpha_{GT} > 0) \odot (F - F_{GT})\|_1, \tag{10}$$

where $\odot$ is the Hadamard product.

We also use alpha prediction to re-construct the image using Eq. (1) and take the L1 loss when training with the synthetic data:

$$\mathcal{L}_{recons}(\alpha) = \|\alpha \cdot F_{GT} + (1 - \alpha) \cdot B - I\|_1, \tag{11}$$

Pseudo flash image	No-flash image	GT alpha

Figure 8: Example of generated pseudo real-world flash/no-flash samples from PM-10K (Li et al., 2022).

where B is the background for compositing to the training data, and I is the original image.

4.5.4 Overall Loss

We first train the Coarse Matting Network using following loss:

$$\mathcal{L}_{CMN} = \mathcal{L}_{sem}(s_c^{nf}) + \mathcal{L}_{detail}(d_c^{nf}, t_c^{nf(un)}) + \mathcal{L}_{alpha}(\alpha_c^{nf}) + \mathcal{L}_{fg}(F_c^{nf}) + \mathcal{L}_{recons}(\alpha_c^{nf}), \tag{12}$$

where c is the down-sampling scale in CMN.

Once the training of CMN converges, we attach BMN to the CMN and train the entire model jointly using:

$$\mathcal{L}_{BMN} = \mathcal{L}_{CMN} + \mathcal{L}_{detail}(d^{nf}, t^{nf(un)}) + \mathcal{L}_{alpha}(\alpha^{nf}) + \mathcal{L}_{fg}(F^{nf}). \tag{13}$$

5 Experiment evaluation

5.1 Data Preparation

5.1.1 Data Synthesis

Foreground Acquirement. In addition to training with our own constructed dataset, we also adopt foreground samples in VideoMatte240K (Lin et al., 2021) dataset for training. For a foreground video in this dataset, we select 10 frames with a large and uniform time interval and adjust their V channel in the YUV space to enhance the brightness. It forms flash/no-flash image pairs with the remaining frames of the video. For implementation, we use the `adjust_gamma` function in `skimage.exposure` to adjust the V channel, where the gamma value is randomly selected in $[0.2, 0.5]$. Although the pseudo flash image generated in this way is far from the real flash image, our model has no selectivity for the enhancement of foreground object color intensity, these images can effectively prevent the model from over-fitting with a small amount of data. Our model is trained on the mixed dataset of our real flash/no-flash image samples and pseudo flash/no-flash image samples from VideoMatte240K.

Composite with Backgrounds. Following Eq. (1), we can build flash/no-flash image pairs by compositing flash/no-flash foregrounds and their corresponding alpha matte onto dynamic background pairs under the same scene. During training, we first pair flash/no-flash foregrounds of the same person one by one. Then we select two background images of the same scene with a random interval from all the background images as a dynamic background pair. To enhance the robustness of our model to static backgrounds, we replace a certain dynamic background pair (B_i, B_j) with a static background pair (B_i, B_i) with a probability of 0.4, where (B_i, B_j) represents two different background images but from the same scene and (B_i, B_i) represents two identical background images. The background pair is composited with the previous foreground pair to obtain flash/no-flash image pairs for training.

Test Set Building. To build the test set, we composite pairs of flash/no-flash foreground with pairs of pre-randomly scrambled dynamic background images alternatively. A flash/no-flash foreground pair is composited with five different dynamic background pairs to form the test set.

Adapt to Real-world Domain. The model trained only on the synthetic data often suffers from the domain shift problem, *i.e.*, the model has a poor performance on real-world data. This is mainly due to the compositional artifacts and invariable texture of these samples, leading to over-fitting of the model. To

Table 2: Quantitative results on the synthetic data on our dataset (testing set). Best results under dynamic background are marked in blue, while those in green are the best under static backgrounds. A '†' indicates the model is retrained using our mixed training dataset. (BG=Background, FG=Foreground)

BG Type	Input Image Type		Method	Evaluation Metrics			
				MSE↓	SAD↓	Grad↓	Conn↓
-	Single FG image		MODNet† (Ke et al., 2022)	1.751	4744.656	4188.432	3491.866
			SHM† (Chen et al., 2018)	3.289	5931.676	5462.052	5287.020
			LF† (Zhang et al., 2019)	3.504	6582.503	5911.190	5445.151
			HATT† (Qiao et al., 2020)	3.651	6892.154	6529.803	5792.352
			RVM† (Lin et al., 2022)	1.981	4270.903	7097.109	4133.624
			SGHM† (Chen et al., 2022b)	1.830	3859.964	4160.247	3837.194
			PPM† (Chen et al., 2022a)	2.891	5726.036	4793.306	4907.765
			GFM† (Li et al., 2022)	2.265	5415.296	4674.963	4321.387
			MAM† (Li et al., 2024c)	2.374	4480.037	3959.617	2202.677
			SmartMat† (Ye et al., 2024)	1.034	2450.608	4019.710	1753.940
			P3M-Net† (Ma et al., 2023)	1.733	3034.637	5130.156	2828.504
Static	FG	BG	BGMv2 (Lin et al., 2021)	0.396	1112.788	1851.081	992.213
	Flash	No-flash	Ours	0.634	1767.632	3697.195	1589.147
Dynamic	FG	BG	BGMv2 (Lin et al., 2021)	115.7	116675.8	32762.20	116327.7
	FG	BG	BGMv2† (Lin et al., 2021)	1.212	2744.400	5314.358	2615.139
	FG	Other FG		2.547	4415.687	7394.905	4352.937
	Flash	No-flash		1.989	3768.433	6802.648	3701.530
	Flash	No-flash	Ours	0.652	1804.741	3742.230	1626.339

Figure 9: Qualitative results on the synthetic data with static backgrounds.

eliminate such a domain gap, in addition to introducing some data augmentation methods, we directly use PM-10K, a real-world portrait matting dataset proposed by Li et al. (2022) to transfer our model to the real-world domain. We use the same manner discussed above to generate the corresponding pseudo flash image for every real-world training sample in PM-10K dataset. Examples of generated training samples are shown in Fig. 8. However, we only brighten the foreground part of each sample by taking the weighted average of brightened image and the original image. The weight mask is obtained by applying erosion operation and averaging filter of the GT alpha matte.

5.1.2 Data Augmentation for Training

Moreover, we do the following augmentation operations for each pair of composited flash/no-flash image pairs. The operations include affine transformations, horizontal flipping, brightness, hue, and saturation adjustments on both foreground and background. We also apply blur, sharpening on the foreground randomly. The foreground is resized randomly and also placed to a random position to accommodate the perturbations caused by the movement of characters in the real world. After generating the training samples, each batch of images is cropped to a random height and width between 960 and 1600 to adapt the model to inputs of different resolutions.

Figure 10: Qualitative results on the synthetic data with dynamic backgrounds.

5.2 Implementation Details

We use DeeplabV3 (Chen et al., 2017) weights pre-trained on Pascal VOC 2012 (Everingham et al., 2010) for semantic segmentation to initialize the backbone network and ASPP module, and adopt Adam as the optimizer. In the initial training of CMN, we set the down-sampling rate c and batch size to 0.25 and 8 respectively. To learn the trimap prediction, the kernel size of erosion-dilation operation in generating GT trimap and t_c^f is set to be 25×25. In FCM, we set $L_{nf} = L_f = 2$. And the learning rates are set to 5e-5 for the backbone, and 1e-4 for ASPP, FCM, and three decoders. In the joint training of CMN and BMN, the batch size is 4 and the learning rates of the backbone, ASPP, FCM, decoders, and BMN are set to 1e-5, 1e-5, 1e-5, 2e-5, 3e-5, 3e-4 respectively. In CMN training, we use a single Nvidia GeForce RTX 3090 to accelerate training. In the joint training, two Nvidia GeForce RTX 3090 cards are used for distributed training. For inference and following evaluation experiments, we set $c' = 20$, $r = 5$, $\delta = 0.7$, and $q = 5$ in the flash guided trimap prediction process. We also use Segment Anything Model (SAM) (Kirillov et al., 2023) as the pretrained segmentation model.

5.3 Evaluation Metrics

We use four common metrics proposed in Rhemann et al. (2009) to measure the quality of the alpha matte prediction with ground-truth alpha matte, including mean square error (MSE), the sum of absolute difference (SAD), the gradient difference (Grad) and the connectivity difference (Conn). All MSE values are scaled by 10^{-3}.

5.4 Comparisons on Synthetic Data

We composite testing foreground videos and testing dynamic background videos of our dataset introduced in Sec. 3 to build the test set, and perform both quantitative and qualitative comparisons on it.

5.4.1 Quantitative Comparison

For quantitative comparison, we benchmark one background-based matting method (BGMv2 (Lin et al., 2021)), and several trimap-free matting methods including MODNet (Ke et al., 2022), SHM (Chen et al., 2018), LF (Zhang et al., 2019), HATT (Qiao et al., 2020), RVM (Lin et al., 2022), SGHM (Chen et al.,

Table 3: Ablation study on the proposed FNF test set with dynamic backgrounds.

Methods	Evaluate metrics			
	MSE↓	SAD↓	Grad↓	Conn↓
Basic	1.874	5153.745	9239.828	5783.462
+SepDecoder	1.729	4426.630	7239.828	4330.583
+BMN	1.212	2744.400	5314.357	2615.139
+T^{nf}	1.197	2617.628	5035.997	2380.563
+T^f	0.836	2005.576	4257.153	1885.972
+CBAM	0.652	1804.741	3742.230	1626.339

(a) **Each component.** Progressively attaching each component can significant improve the performance, demonstrating importance of each module.

δ	Evaluate metrics			
	MSE↓	SAD↓	Grad↓	Conn↓
0.4	2.384	5769.857	6834.817	4743.609
0.5	1.214	2996.780	4970.955	2498.168
0.6	0.794	2257.089	4275.529	1841.292
0.7	0.652	1804.741	3742.230	1626.339
0.8	0.701	1932.605	3861.104	1801.177
0.9	0.893	2160.262	4342.540	2389.265

(b) **Flash ratio map truncation threshold δ.** Using lower or higher δ will result in inaccurate t_c^f, thus degrade the performance.

Kernel Size	Evaluate metrics			
	MSE↓	SAD↓	Grad↓	Conn↓
15×15	0.649	1799.543	3767.761	1617.709
25×25	0.652	1804.741	3742.230	1626.339
35×35	0.698	2071.123	3868.911	1729.099
45×45	0.791	2105.520	4132.484	1966.840
55×55	0.878	2437.644	4519.305	2352.018

(c) **Kernel size of erosion-dilation for generating GT trimaps.** Larger kernel size of erosion-dilation will make the performance worse.

Medium Filter Kernel Size	Evaluate metrics			
	MSE↓	SAD↓	Grad↓	Conn↓
3	0.652	1804.810	3741.978	1626.490
5	0.652	1804.741	3742.230	1626.339
7	0.652	1804.740	3742.230	1626.338
9	0.652	1804.741	3742.231	1626.339

(d) **Kernel size of medium filter for generating flash trimap.** The effect of adopting different medium filter kernel on the performance is negligible.

q	Evaluate metrics			
	MSE↓	SAD↓	Grad↓	Conn↓
3	1.199	2641.574	5496.697	2682.519
4	0.686	1819.145	3797.614	1655.620
5	0.652	1804.741	3742.230	1626.339
6	0.652	1804.742	3742.230	1626.340

(e) **Number of confidence points q for generating flash trimap.** Smaller q results in worse performance.

Segmentation model	Evaluate metrics			
	MSE↓	SAD↓	Grad↓	Conn↓
SAM	0.652	1804.741	3742.230	1626.339
InterFormer	0.684	1815.367	3801.018	1652.824

(f) **Pre-trained segmentation model for generating flash trimap.** Our method is not selective for different segmentation models.

2022b), PPM (Chen et al., 2022a), GFM (Li et al., 2022), and P3M-Net (Ma et al., 2023). We also include two interactive matting methods, including SmartMat (Ye et al., 2024) and MAM (Li et al., 2024c). Since SmartMat supports automatic matting originally, we apply it in such mode directly. For MAM, since it requires user interaction as input, we utilize one of the state-of-the-art detection models (GDINO (Liu et al., 2025)) to obtain the bounding box of the foreground in the no-flash image (with the text input for GDINO set as "foreground person") as prompt for MAM for further alpha prediction. For a fair comparison, all methods are retrained on the same mixed dataset. For MAM, we follow its original training settings, which only train the matting components and let the SAM (Kirillov et al., 2023) backbone frozen. In addition, we retrain the BGMv2 with three types of input and evaluate them respectively, including with/without subject image pairs, different image pairs of the same subject, and flash/no-flash image pairs. The comparison with the BGMv2 is performed with both static and dynamic backgrounds. For static background, the input image pair has the same background. For dynamic background, the backgrounds of the input image pair are under the same scene but are different caused by dynamic changes. All the test samples for testing are resized to a resolution of 1280×720.

The quantitative comparison result is shown in Tab. 2. According to the results, we found our model shows superior performance on dynamic scenes while slightly falling behind BGMv2 on static scenes. This is mainly because modeling static and dynamic scenes involves contradictory objectives: static scenes prioritize the detection of foreground inconsistency solely, while dynamic scenes require modeling high-level foreground correspondences under motion and pose variations in both foreground and background. It is also worth knowing that dynamic scenes are a generalization of static ones, and training for broader generalization often reduces overfitting to simpler tasks, leading to slightly lower performance on static cases. This phenomenon aligns with the bias-variance dilemma (Zou & Hastie, 2005; Kohavi et al., 1996; Geman et al., 1992), showing that improving generalization may sacrifice some task-specific accuracy. Despite this, our model demonstrates strong generalization, excelling in dynamic backgrounds and effectively handling both static and dynamic scenarios. This versatility is a key strength, even if it comes at a small cost in static performance compared to static-specific methods like BGMv2.

Moreover, when training with flash/no-flash image pairs using the architecture of BGMv2, it performs much worse than our model. This also justifies the rationality of our model architecture for predicting alpha matte under dynamically changing backgrounds using flash/no-flash pairs. Also, since the input of trimap-free based methods is only one single image and does not contain any priors, they do not perform well in some diverse backgrounds. The corresponding quantitative results also show their performance is weaker than our model in the test set. It is worth noting that our proposed method still outperforms MAM (Li et al., 2024c)

on the dynamic scenes although it adopts SAM (Kirillov et al., 2023) as backbone. However, in addition to generating t_c^f, our model does not directly use any external segmentation model to solve the alpha matte of the no-flash image.

5.4.2 Qualitative Comparison

We also select several latest state-of-the-art trimap-free methods (MODNet (Ke et al., 2022), RVM (Lin et al., 2022), SGHM (Chen et al., 2022b), P3M-Net (Ma et al., 2023), SmartMat (Ye et al., 2024), MAM (Li et al., 2024c)) and BGMv2 (Lin et al., 2021) for qualitative comparison. When dealing with static background, as shown in Fig. 9, we can see the performance gap between BGMv2 and our model is only reflected in the details of the edges in static backgrounds. However, BGMv2 performs poorly when the background is not aligned due to objects moving or camera shaking, which is shown in Fig. 10. Most of trimap-free methods also suffer from interference from background salient objects, but our model is robust to dynamic backgrounds and also have well performance.

5.5 Ablation Study

5.5.1 Component Analysis

To demonstrate the effect of the proposed Foreground Correlation Module and Boundary Matting Network, we first define the baseline as a network that only includes the encoder, ASPP module, and a single decoder without down-sampling. This baseline takes I^{nf} as input only, and we denote it as **Basic**. We further replace the single decoder with three separate decoders, denoted as **SepDecoder**. Then we progressively attach BMN with down-sampling before the encoder, and each branch of FCM to build the corresponding combinations. These combinations are all retrained on the mixed dataset, and quantitative evaluation tests are carried out on the test set under dynamic background. The quantitative results are shown in Tab. 4a. We can see that decomposing the matting problem into semantic and detail predictions separately can effectively improve the matting performance. The BMN can recover fine details to predict alpha matte with higher-quality in the original resolution. However, attaching T^{nf} with only self-attention blocks has a minor performance improvement, since a single no-flash image does not contain any foreground cues in various dynamic scenes. We further start to utilize the guidance information from I^f by taking (I^{nf}, I^f, t_c^f) as input, and introduce T^f and add cross-attention blocks in T^{nf} for modeling the foreground correspondence, resulting in a significant improvement. On this basis, the model with CBAM module adopted before T^{nf} can achieve better performance, showing the effectiveness of feature re-attention operation.

5.5.2 Hyper-Parameter Analysis

We also conduct ablation studies on various hyper-parameter aspects, including the truncation threshold δ of the flash ratio map (presented in Tab. 4b), and the kernel size of erosion-dilation for generating the ground truth trimap (shown in Tab. 4c).

For the truncation threshold δ, we observed that using a smaller threshold value degrades performance, as it results in a ratio map containing more inaccurate regions with low confidence scores. Conversely, a larger δ overly truncates regions with higher confidence, leading to inaccuracies in mask prediction for the flash image and a deterioration in model performance.

For the kernel size for erosion-dilation, we observed that employing a kernel size smaller than 25×25 can lead to slight improvements in model performance. Conversely, using a larger kernel size introduces more unknown regions in the ground truth trimap, potentially covering the entire portrait area. This forces the detailed branch to learn semantic information, ultimately resulting in a decrease in model performance.

We also explore the effect of adopting different kernel size of the medium filter and different number of confidence points q when generating the flash trimap t_c^f. The corresponding quantative ablation results are presented in Tab. 4d and Tab. 4e, respectively. We found that using smaller or larger filter kernels has minimal impact on performance. However, larger kernels increase computational cost due to higher sorting complexity, leading us to adopt a median filter kernel size of 5 in this study. Regarding the number of points q, smaller values may result in obvious performance degradation, as insufficient confident points may fail to

fully represent the foreground in the flash image, leading to incomplete or inaccurate flash cues. Conversely, larger q values have almost no impact on performance.

5.5.3 Pre-trained Segmentation Model

The flexible design of our method allows the pretrained segmentation model for generating flash trimap can be replaced with any other more lightweight model to generate accurate flash cues. Such a substitution would not impact the overall performance of our approach, ensuring robustness and adaptability across different model choices. To further verify this, we conducted an ablation study by replacing current SAM (Kirillov et al., 2023) with InterFormer (Huang et al., 2023), a lightweight, real-time interactive image segmentation method that supports point-prompt inputs to generate segmentation masks, similar to SAM. The experimental results (showed in Tab. 4f) demonstrate that our model's performance remains largely unaffected by this substitution. Moreover, the use of InterFormer (Huang et al., 2023) accelerates the pre-processing stage, further enhancing the practicality of our approach.

5.6 Model Complexity Comparison

We conduct a model complexity comparison, which encompasses the number of parameters (M), computational complexity (GMac), and inference time (ms), as detailed in Tab. 4. For the backbones, we use MobileNetV2(Sandler et al., 2018) for MODNet (Ke et al., 2022), ViTAE-S (Xu et al., 2021) for P3M-Net (Ma et al., 2023), DINOv2-ViTS14 (Oquab et al., 2024; Dosovitskiy et al., 2021) for SmartMat (Ye et al., 2024), SAM-B (Kirillov et al., 2023) for MAM (Li et al., 2024c), and ResNet-50 (He et al., 2016) for the remaining models. To assess inference time, we resized the input image to 1280×720, and the reported inference times were obtained using an NVIDIA RTX A5000.

While it is true that our model boasts a larger number of parameters compared to other models, this is primarily attributed to our use of two separate ResNet-50 encoders that do not share weights, as well as the inclusion of the FCM module. Our ablation experiments, as detailed in Sec. 5.5 of the main paper, demonstrated the essential roles played by these two modules in establishing the connection between the flash image and the no-flash image foreground. These modules contributed significantly to the overall performance improvement of our model. In future work, we will explore the development of more lightweight modules for flash image encoding and foreground correction.

We report the computational complexity and inference time for our model in two distinct cases. The first case, denoted as **1$^{\text{st}}$ frame**, involves the model taking $I_c^f, I_c^{nf}, t_c^f, I^{nf}$ as input and working end-to-end. In the second case, denoted as **other frames**, the computation result of the flash image until T^f is given, and only new no-flash frames are forwarded, significantly reducing computational costs. Comparatively, BGMv2 (Lin et al., 2021) and RVM (Lin et al., 2022) exhibit lower computational complexity and inference time. This can be attributed to several factors, such as BGMv2 using a single decoder for direct alpha matte and foreground color prediction and RVM operating at lower resolutions and performing up-sampling through DGF (Wu et al., 2018) directly at the end of processing. Furthermore, SGHM (Chen et al., 2022b) only predicts alpha matte without foreground color, resulting in a lower computational complexity compared to our model. For MAM (Li et al., 2024c) and SmartMat (Ye et al., 2024), they have relatively higher GMac since they adopt ViT (Dosovitskiy et al., 2021) as backbone. Even if we choose the lightest version of SAM (SAM-B), MAM still suffers from high computational complexity and inference time. Regarding our model, we observed a significant reduction in computational complexity and inference time when forwarding only new no-flash frames, while still maintaining competitive performance. This optimization is especially noticeable in the 'only-no-flash forwarding' scenario, where our model's inference time closely aligns with that of MODNet (Ke et al., 2022) and SGHM (Chen et al., 2022b), despite our model's larger size.

5.7 Limitations

While our model performs admirably in most environments with normal light conditions, it is not immune to the limitations inherent in flash/no-flash photography. For instance, when the foreground is outdoors in very strong sunlight (see Fig. 11), the flash difference between the flash image and the no-flash image

Table 4: Comparison of number of model parameters (M), computational complexity (GMac), and inference time (ms). For ours, (1st frame) and (other frames) represent forwarding the first no-flash frame and the flash image initially and forwarding other no-flash frames with given flash image features, respectively.

Method	#Params (M)	Comp. (GMac)	Infer. (ms)
BGMv2 (Lin et al., 2021)	40.25	17.47	13.27
MODNet (Ke et al., 2022)	6.49	64.95	27.90
RVM (Lin et al., 2022)	26.89	11.49	8.89
SGHM (Chen et al., 2022b)	40.25	25.81	25.96
P3M-Net (Ma et al., 2023)	39.48	300.39	36.79
MAM (Li et al., 2024c)	96.45	383.02	533.2
SmartMat (Ye et al., 2024)	26.89	228.73	38.96
Ours (1st frame)	70.09	60.29	34.06
Ours (other frames)		44.85	28.69

Flash image   No-flash image   Alpha prediction of no-flash image

Figure 11: Example of challenging cases. Our method may encounter failures when the flash photography assumption is not met in such scenes with extreme light conditions, *e.g.* no enough flash contrast on the foreground in the environment with very strong sunlight.

becomes so minimal that no flash cues can be reliably detected, thus violating the flash/no-flash photography assumption. A potential solution to address this issue is the use of infrared light to illuminate the foreground, which will be explored in our future research. However, it is important to note that such light-related challenging scenarios are infrequent in typical environments, particularly indoors. These limitations do not compromise the performance of our model in applications such as video conferencing, live boardcasting, and virtual/augmented reality. Since modern imaging devices, including smartphones and webcams, are commonly equipped with built-in flash modules or external lighting aids, which are routinely used in professional and semi-professional setups to enhance visual quality. Our approach does not impose restrictive requirements such as continuous flash triggering or user calibration. Capturing a flash image is a one-time, automatic process that does not interfere with user experience. Compared to BGMv2 (Lin et al., 2021), which requires user intervention prior to each capture, our method offers improved usability and flexibility, making it more suitable for practical deployment.

6 Conclusion

To solve the matting problem with dynamic backgrounds, this paper proposes a portrait matting model based on flash and no-flash images, which provides additional foreground priors to reveal the foreground objects. Our model is insensitive to dynamically changing backgrounds, and does not require that the movements of the foreground characters are exactly the same in the two images. Therefore, taking a flash image can map out multiple no-flash images, which is very practical. This paper also presents the first high-quality matting dataset of flash and no-flash single-person images, which provides an effective resource for subsequent research work on flash and no-flash matting work. Experiments show that our proposed method outperforms existing matting methods that do not require a tripartite map as a prior in dynamic backgrounds, showing the effectiveness of the model.

Future Works. Although our method shows strong generalization on both static and dynamic backgrounds, it still has slightly weaker performance in static scenes comparing with BGMv2 (Lin et al., 2021). Here we

provide two possible future directions to improve this. First, we can further integrate some pixel-flow estimation techniques, such as optical flow, into our foreground correlation modeling based on current flash cues, which can better capture subtle spatial and temporal relationships in static scenes. Optical flow can provide precise motion cues, enabling the model to distinguish static background elements from foreground objects more effectively. Another direction is to explicitly model static background information by introducing a background restoration subtask that uses a generative inpainting prior, taking the flash cues as guidance. By training the model to reconstruct background regions, it can learn a robust representation of static scene features, thereby reducing artifacts and improving consistency in static matting tasks. Furthermore, considering the privacy-sensitive scenarios, we can also adapt the method to operate with infrared illumination, which is invisible to the human eye. We leave this promising direction for future research.

References

Yagiz Aksoy, Tunc Ozan Aydin, and Marc Pollefeys. Designing effective inter-pixel information flow for natural image matting. In *CVPR*, 2017.

Huanqia Cai, Fanglei Xue, Lele Xu, and Lili Guo. Transmatting: Enhancing transparent objects matting with transformers. In *ECCV*, 2022.

Shaofan Cai, Xiaoshuai Zhang, Haoqiang Fan, Haibin Huang, Jiangyu Liu, Jiaming Liu, Jiaying Liu, Jue Wang, and Jian Sun. Disentangled image matting. In *ICCV*, 2019.

Guowei Chen, Yi Liu, Jian Wang, Juncai Peng, Yuying Hao, Lutao Chu, Shiyu Tang, Zewu Wu, Zeyu Chen, Zhiliang Yu, et al. Pp-matting: High-accuracy natural image matting. *arXiv preprint arXiv:2204.09433*, 2022a.

Liang-Chieh Chen, George Papandreou, Florian Schroff, and Hartwig Adam. Rethinking atrous convolution for semantic image segmentation. *arXiv preprint arXiv:1706.05587*, 2017.

Qifeng Chen, Dingzeyu Li, and Chi-Keung Tang. Knn matting. *IEEE TPAMI*, 2013.

Quan Chen, Tiezheng Ge, Yanyu Xu, Zhiqiang Zhang, Xinxin Yang, and Kun Gai. Semantic human matting. In *ACM Multimedia*, 2018.

Xiangguang Chen, Ye Zhu, Yu Li, Bingtao Fu, Lei Sun, Ying Shan, and Shan Liu. Robust human matting via semantic guidance. In *ACCV*, 2022b.

Yung-Yu Chuang, Brian Curless, David H Salesin, and Richard Szeliski. A bayesian approach to digital matting. In *CVPR*, 2001.

Kostadin Dabov, Alessandro Foi, Vladimir Katkovnik, and Karen Egiazarian. Bm3d image denoising with shape-adaptive principal component analysis. In *Signal Processing with Adaptive Sparse Structured Representations*, 2009.

Linhui Dai, Xiang Song, Xiaohong Liu, Chengqi Li, Zhihao Shi, Jun Chen, and Martin Brooks. Enabling trimap-free image matting with a frequency-guided saliency-aware network via joint learning. *IEEE TMM*, 25:4868–4879, 2022.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *ICLR*, 2021.

Mark Everingham, Luc Van Gool, Christopher KI Williams, John Winn, and Andrew Zisserman. The pascal visual object classes (voc) challenge. 2010.

Xiaoxue Feng, Xiaohui Liang, and Zili Zhang. A cluster sampling method for image matting via sparse coding. In *ECCV*, 2016.

Eduardo SL Gastal and Manuel M Oliveira. Shared sampling for real-time alpha matting. In *Computer Graphics Forum*, 2010.

Stuart Geman, Elie Bienenstock, and René Doursat. Neural networks and the bias/variance dilemma. *Neural computation*, 1992.

Zeqi Gu, Wenqi Xian, Noah Snavely, and Abe Davis. Factormatte: Redefining video matting for re-composition tasks. *ACM TOG*, 2023.

He Guo, Zixuan Ye, Zhiguo Cao, and Hao Lu. In-context matting. In *CVPR*, 2024.

Kaiming He, Christoph Rhemann, Carsten Rother, Xiaoou Tang, and Jian Sun. A global sampling method for alpha matting. In *CVPR*, 2011.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

Shengfeng He and Rynson WH Lau. Saliency detection with flash and no-flash image pairs. In *ECCV*, 2014.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *NeurIPS*, 2020.

Qiqi Hou and Feng Liu. Context-aware image matting for simultaneous foreground and alpha estimation. In *ICCV*, 2019.

Yihan Hu, Yiheng Lin, Wei Wang, Yao Zhao, Yunchao Wei, and Humphrey Shi. Diffusion for natural image matting. In *ECCV*, 2024.

You Huang, Hao Yang, Ke Sun, Shengchuan Zhang, Liujuan Cao, Guannan Jiang, and Rongrong Ji. Inter-former: Real-time interactive image segmentation. In *ICCV*, pp. 22301–22311, 2023.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *ICML*, 2015.

Weihao Jiang, Zhaozhi Xie, Yuxiang Lu, Longjie Qi, Jingyong Cai, Hiroyuki Uchiyama, Bin Chen, Yue Ding, and Hongtao Lu. Learning auxiliary representations with inconsistency-guided detail regularization for mask-guided matting. *IEEE TMM*, 2025.

Jubin Johnson, Ehsan Shahrian Varnousfaderani, Hisham Cholakkal, and Deepu Rajan. Sparse coding for alpha matting. *IEEE TIP*, 2016.

Zhanghan Ke, Jiayu Sun, Kaican Li, Qiong Yan, and Rynson WH Lau. Modnet: real-time trimap-free portrait matting via objective decomposition. In *AAAI*, 2022.

Alexander Kirillov, Eric Mintun, Nikhila Ravi, Hanzi Mao, Chloe Rolland, Laura Gustafson, Tete Xiao, Spencer Whitehead, Alexander C Berg, Wan-Yen Lo, et al. Segment anything. In *ICCV*, 2023.

Ron Kohavi, David H Wolpert, et al. Bias plus variance decomposition for zero-one loss functions. In *ICML*, 1996.

Dawa Chyophel Lepcha, Bhawna Goyal, and Ayush Dogra. Image matting: a comprehensive survey on techniques, comparative analysis, applications and future scope. *International Journal of Image and Graphics*, 2023.

Anat Levin, Dani Lischinski, and Yair Weiss. A closed-form solution to natural image matting. *IEEE TPAMI*, 2007.

Anat Levin, Alex Rav-Acha, and Dani Lischinski. Spectral matting. *IEEE TPAMI*, 2008.

Jiachen Li, Marianna Ohanyan, Vidit Goel, Shant Navasardyan, Yunchao Wei, and Humphrey Shi. Video-matt: A simple baseline for accessible real-time video matting. In *CVPR*, 2023a.

Jiachen Li, Vidit Goel, Marianna Ohanyan, Shant Navasardyan, Yunchao Wei, and Humphrey Shi. Vm-former: End-to-end video matting with transformer. In *WACV*, 2024a.

Jiachen Li, Roberto Henschel, Vidit Goel, Marianna Ohanyan, Shant Navasardyan, and Humphrey Shi. Video instance matting. In *WACV*, 2024b.

Jiachen Li, Jitesh Jain, and Humphrey Shi. Matting anything. In *CVPR Workshop*, 2024c.

Jizhizi Li, Jing Zhang, Stephen J Maybank, and Dacheng Tao. Bridging composite and real: towards end-to-end deep image matting. 2022.

Jizhizi Li, Jing Zhang, and Dacheng Tao. Deep image matting: A comprehensive survey. *arXiv preprint arXiv:2304.04672*, 2023b.

Jizhizi Li, Jing Zhang, and Dacheng Tao. Referring image matting. In *CVPR*, 2023c.

Xiaodi Li, Zongxin Yang, Ruijie Quan, and Yi Yang. DRIP: Unleashing diffusion priors for joint foreground and alpha prediction in image matting. In *NeurIPS*, 2024d.

Yaoyi Li and Hongtao Lu. Natural image matting via guided contextual attention. In *AAAI*, 2020.

Chung-Ching Lin, Jiang Wang, Kun Luo, Kevin Lin, Linjie Li, Lijuan Wang, and Zicheng Liu. Adaptive human matting for dynamic videos. In *CVPR*, 2023.

Shanchuan Lin, Andrey Ryabtsev, Soumyadip Sengupta, Brian L Curless, Steven M Seitz, and Ira Kemelmacher-Shlizerman. Real-time high-resolution background matting. In *CVPR*, 2021.

Shanchuan Lin, Linjie Yang, Imran Saleemi, and Soumyadip Sengupta. Robust high-resolution video matting with temporal guidance. In *WACV*, 2022.

Chang Liu, Henghui Ding, and Xudong Jiang. Towards enhancing fine-grained details for image matting. In *WACV*, 2021a.

Jinlin Liu, Yuan Yao, Wendi Hou, Miaomiao Cui, Xuansong Xie, Changshui Zhang, and Xian-sheng Hua. Boosting semantic human matting with coarse annotations. In *CVPR*, 2020.

Qinglin Liu, Haozhe Xie, Shengping Zhang, Bineng Zhong, and Rongrong Ji. Long-range feature propagating for natural image matting. In *ACM Multimedia*, 2021b.

Shilong Liu, Zhaoyang Zeng, Tianhe Ren, Feng Li, Hao Zhang, Jie Yang, Qing Jiang, Chunyuan Li, Jianwei Yang, Hang Su, et al. Grounding dino: Marrying dino with grounded pre-training for open-set object detection. In *ECCV*, 2025.

Yuhao Liu, Jiake Xie, Yu Qiao, Yong Tang, and Xin Yang. Prior-induced information alignment for image matting. *IEEE TMM*, 24:2727–2738, 2021c.

Hao Lu, Yutong Dai, Chunhua Shen, and Songcen Xu. Indices matter: Learning to index for deep image matting. In *ICCV*, 2019.

Sebastian Lutz, Konstantinos Amplianitis, and Aljosa Smolic. Alphagan: Generative adversarial networks for natural image matting. *arXiv preprint arXiv:1807.10088*, 2018.

Sihan Ma, Jizhizi Li, Jing Zhang, He Zhang, and Dacheng Tao. Rethinking portrait matting with privacy preserving. *IJCV*, 2023.

Vinod Nair and Geoffrey E Hinton. Rectified linear units improve restricted boltzmann machines. In *ICML*, 2010.

Maxime Oquab, Timothée Darcet, Théo Moutakanni, Huy V. Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel HAZIZA, Francisco Massa, Alaaeldin El-Nouby, Mido Assran, Nicolas Ballas, Wojciech Galuba, Russell Howes, Po-Yao Huang, Shang-Wen Li, Ishan Misra, Michael Rabbat, Vasu Sharma, Gabriel Synnaeve, Hu Xu, Herve Jegou, Julien Mairal, Patrick Labatut, Armand Joulin, and Piotr Bojanowski. DINOv2: Learning robust visual features without supervision. *Transactions on Machine Learning Research*, 2024.

GyuTae Park, SungJoon Son, JaeYoung Yoo, SeHo Kim, and Nojun Kwak. Matteformer: Transformer-based image matting via prior-tokens. In *CVPR*, 2022.

Kwanyong Park, Sanghyun Woo, Seoung Wug Oh, In So Kweon, and Joon-Young Lee. Mask-guided matting in the wild. In *CVPR*, 2023.

Yu Qiao, Yuhao Liu, Xin Yang, Dongsheng Zhou, Mingliang Xu, Qiang Zhang, and Xiaopeng Wei. Attention-guided hierarchical structure aggregation for image matting. In *CVPR*, 2020.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *ICML*, 2021.

Christoph Rhemann, Carsten Rother, Jue Wang, Margrit Gelautz, Pushmeet Kohli, and Pamela Rott. A perceptually motivated online benchmark for image matting. In *CVPR*, 2009.

Mark A Ruzon and Carlo Tomasi. Alpha estimation in natural images. In *CVPR*, 2000.

Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *CVPR*, 2018.

Soumyadip Sengupta, Vivek Jayaram, Brian Curless, Steven M Seitz, and Ira Kemelmacher-Shlizerman. Background matting: The world is your green screen. In *CVPR*, 2020.

Xiaoyong Shen, Xin Tao, Hongyun Gao, Chao Zhou, and Jiaya Jia. Deep automatic portrait matting. In *ECCV*, 2016.

Jian Sun, Jiaya Jia, Chi-Keung Tang, and Heung-Yeung Shum. Poisson matting. In *SIGGRAPH*. 2004.

Jian Sun, Yin Li, Sing Bing Kang, and Heung-Yeung Shum. Flash matting. In *SIGGRAPH*. 2006.

Jian Sun, Sing Bing Kang, Zong-Ben Xu, Xiaoou Tang, and Heung-Yeung Shum. Flash cut: Foreground extraction with flash and no-flash image pairs. In *CVPR*, 2007.

Jiayu Sun, Zhanghan Ke, Ke Xu, Fan Shao, Lihe Zhang, Huchuan Lu, and Rynson WH Lau. Semantics-adding flaw-erasing network for semantic human matting. In *BMVC*, 2022.

Yanan Sun, Chi-Keung Tang, and Yu-Wing Tai. Semantic image matting. In *CVPR*, 2021a.

Yanan Sun, Guanzhi Wang, Qiao Gu, Chi-Keung Tang, and Yu-Wing Tai. Deep video matting via spatio-temporal alignment and aggregation. In *CVPR*, 2021b.

Yanan Sun, Chi-Keung Tang, and Yu-Wing Tai. Ultrahigh resolution image/video matting with spatio-temporal sparsity. In *CVPR*, 2023.

Jingwei Tang, Yagiz Aksoy, Cengiz Oztireli, Markus Gross, and Tunc Ozan Aydin. Learning-based sampling for natural image matting. In *CVPR*, 2019.

Jue Wang and Michael F Cohen. Optimized color sampling for robust matting. In *CVPR*, 2007.

Zhixiang Wang, Baiang Li, Jian Wang, Yu-Lun Liu, Jinwei Gu, Yung-Yu Chuang, and Shin'ichi Satoh. Matting by generation. In *SIGGRAPH*, 2024.

Sanghyun Woo, Jongchan Park, Joon-Young Lee, and In So Kweon. Cbam: Convolutional block attention module. In *ECCV*, 2018.

Huikai Wu, Shuai Zheng, Junge Zhang, and Kaiqi Huang. Fast end-to-end trainable guided filter. In *CVPR*, 2018.

Ning Xu, Brian Price, Scott Cohen, and Thomas Huang. Deep image matting. In *CVPR*, 2017.

Yangyang Xu, Shengfeng He, Wenqi Shao, Kwan-Yee K Wong, Yu Qiao, and Ping Luo. Diffusionmat: Alpha matting as sequential refinement learning. *arXiv preprint arXiv:2311.13535*, 2023.

Yong Xu, Xin Yao, Baoling Liu, Yuhui Quan, and Hui Ji. Text-guided portrait image matting. *IEEE Transactions on Artificial Intelligence*, 2024.

Yufei Xu, Qiming Zhang, Jing Zhang, and Dacheng Tao. Vitae: Vision transformer advanced by exploring intrinsic inductive bias. *NeurIPS*, 2021.

Jingfeng Yao, Xinggang Wang, Shusheng Yang, and Baoyuan Wang. Vitmatte: Boosting image matting with pre-trained plain vision transformers. *Information Fusion*, 2024.

Zixuan Ye, Wenze Liu, He Guo, Yujia Liang, Chaoyi Hong, Hao Lu, and Zhiguo Cao. Unifying automatic and interactive matting with pretrained vits. In *CVPR*, 2024.

Haichao Yu, Ning Xu, Zilong Huang, Yuqian Zhou, and Humphrey Shi. High-resolution deep image matting. In *AAAI*, 2021a.

Qihang Yu, Jianming Zhang, He Zhang, Yilin Wang, Zhe Lin, Ning Xu, Yutong Bai, and Alan Yuille. Mask guided matting via progressive refinement network. In *CVPR*, 2021b.

Yunke Zhang, Lixue Gong, Lubin Fan, Peiran Ren, Qixing Huang, Hujun Bao, and Weiwei Xu. A late fusion cnn for digital matting. In *CVPR*, 2019.

Yunke Zhang, Chi Wang, Miaomiao Cui, Peiran Ren, Xuansong Xie, Xian-Sheng Hua, Hujun Bao, Qixing Huang, and Weiwei Xu. Attention-guided temporally coherent video object matting. In *ACM Multimedia*, 2021.

Bingke Zhu, Yingying Chen, Jinqiao Wang, Si Liu, Bo Zhang, and Ming Tang. Fast deep matting for portrait animation on mobile phone. In *ACM Multimedia*, 2017.

Hui Zou and Trevor Hastie. Regularization and variable selection via the elastic net. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, 2005.