Word2Fun: Modelling Words as Functions for Diachronic Word Representation

Abstract

Diachronic word representation is of great interest for NLP, lexicography, and linguistics. Existing approaches for diachronic word representation train the embeddings separately for each pre-grouped times-tamped corpus and align these embeddings, e.g., by orthogonal projections, vector initialization, and temporal referencing. These methods 1) involve more parameters with space complexity of $\mathcal{O}(TVD)$ [1], since word vectors for all timestamps are saved; and 2) do not consider word meaning evolution in a longer timespan but only aligning two adjoining times-tamps. To avoid both these issues, we propose a new paradigm that models words as functions, such that word meaning in a different time would be correlated and evolves gradually within a continuous process, which also reduces the space complexity from $\mathcal{O}(TVD)$ to $\mathcal{O}(kVD)$ and k is a small constant ($k \ll T$). Inspired by the Weierstrass Approximation Theorem, we adopt various functions, especially sinusoidal functions, to approximate the word meaning evolution in the context of distributed representations, since it can approximate any continuous process with a given negligible error. Experimental results show that the proposed approach is effective in diverse tasks including time-aware word clustering, temporal analogy, and semantic change detection.

1 Introduction

Word meaning changes over time as a reflection of the changes of human society. Not only does word meaning change in a short time, word meaning may also be subject to evolution over long timespans. The causes of the change of word meaning may be cultural, societal, or technological [20]; for example, the word `gay` shifted from the meaning '`cheerful`' in the 1900s to the meaning '`frolicsome`' in the 1950s and finally to the meaning '`homosexuality`' since the 1990s [8]. A word may even disappear because of the replacement with another word or a new word may come up because of new technology, situation, or phenomenon. The change of word meaning, which is also known as lexical semantic change, has been investigated for some decades [3, 20].

Modeling the change of word meaning recently relies on distributed representations of words [2, 13] and adopting time-specific word vectors as diachronic word representation. The training is based on diachronic text corpora, which are obtained by partitioning some text corpora into bins of textual documents labeled by time. A popular training paradigm within such an approach is known as *train-and-align*: first, the embeddings are trained separately for each pre-grouped time-stamped corpus; then, the embeddings are aligned by computing, e.g. orthogonal projections [9, 11], vector initialization [10], temporal referencing [7], parameter regularizers [22, 17], aligned compass [6], or latent diffusion [1]. The methods above do not model word meaning evolution as a continuous

---

[1] V is the size of vocabulary, D is the dimension size of word vectors, and T is the number of timestamps.

process, but consider one-hop transformation between two pairwise adjacent timestamps as a Markov process. However, the meaning of some words may smoothly evolve across a long-range span, according to a mixture of short and long timespans or in general according to unknown patterns which cannot straightforwardly be represented by Markov processes.

This paper proposes to model the change of word meaning as functions of diachronic word representation, which consider word meaning evolution as a continuous process. Trigonometric functions have considerable expressive power, in a sense that they can universally approximate any function describing word meaning evolution, since the trigonometric polynomial used in this paper can approximate any continuous process with a given negligible error thanks to the Weierstrass Theorem.

We experimentally show that modelling each word as a finite number of sinusoidal functions combined together in trigonometric polynomials is an effective approach to modeling the change of word meaning. Our experimental investigation also shows that the proposed method, even using fewer parameters, achieves better performance than SOTA diachronic word representation in time-aware word clustering, temporal analogy, and semantic change detection tasks, showing its potential for the research in diachronic word meaning representation and processing.

2 Background

2.1 Problem Definition

Representing words in vector space, i.e., a static word embedding [13] $h : \mathbb{N} \to \mathbb{N}^D$, is a common practice. However, it [13] cannot model word dynamics over time when considering time-dependent corpora (e.g., studying the evolution of cultural aspects). Diachronic word embedding [9] (sometimes called dynamic word embedding [1]) assumes that each word has a meaning which may vary with time. One word w_i with index i has its meaning represented as a D-dimensional vector $\mathbf{U}_{i,t} \in \mathbb{R}^D$ at a given time t. Therefore, diachronic word embedding can be formalized as a mapping from $\mathbb{N} \times \mathbb{N}$ to $\mathbb{R}^D$, i.e. from the pair (i, t) to a D-dimensional vector defined over the real field.

Existing methods for diachronic word embedding separately train embeddings for each time $t \in \mathbb{N}$. Note that even if we assume $t \in \mathbb{N}$, all formalization can be extended to $t \in \mathbb{R}$; in practice, the granularity between two consecutive times is fixed, e.g., one year, thus representing t in $\mathbb{N}$ is enough.

The vectors that represent V words in time t are defined as $\mathbf{U}_{.,t} \overset{def}{=} [\mathbf{U}_{1,t}, \mathbf{U}_{2,t} \cdots, \mathbf{U}_{V,t}] \in \mathbb{R}^{VD}$.

2.2 Alignment Issues for Rotation-invariant Embeddings

There are typically two ways to obtain word vectors: one method is matrix factorization, the other method is predication-based neural methods. However, the former method is related to the latter; for example, Skip-gram with negative sampling can be described as factorizing an implicit matrix [12].

Consider matrix factorization. A common approach [22] is to approximate a given Positive Pointwise Mutual Information (PPMI) matrix $M_t \in \mathbb{R}^{V \times V}$ by means of the V word vectors $\mathbf{U}_{.,t}$ such that $\mathbf{U}_{.,t}\mathbf{U}_{.,t}^T \approx M_t$. The entries of M_t are measures of a relationship between words; for example, the entry at row i and column j may measure the degree of co-occurrence of the i-th word with the j-word within fixed-size textual windows. The word embeddings can be found by either using an eigenvalue method or a matrix factorization method which finds

$$\mathbf{U}_{.,t} = \underset{\mathbf{V}}{\arg\min} |\mathbf{V}\mathbf{V}^T - M_t|_F \tag{1}$$

However, we have that $\mathbf{U}'_{.,t} = \mathbf{U}_{.,t}\mathbf{R}$ can be an alternative solution of Eq. 1 for any orthogonal rotation matrix $\mathbf{R} \in \mathbb{R}^{D \times D}$. Indeed, $\mathbf{U}_{.,t}\mathbf{R}(\mathbf{U}_{.,t}\mathbf{R})^T = \mathbf{U}_{.,t}\mathbf{R}\mathbf{R}^T(\mathbf{U}_{.,t})^T = \mathbf{U}_{.,t}(\mathbf{U}_{.,t})^T$, since $\mathbf{R}\mathbf{R}^T = \mathbf{I}$. Therefore, training word embeddings according to Eq. 1 is non-convex [1] and as a consequence a global minimum might not exist.

Moreover, if diachronic word embeddings are trained twice on the same time-specific corpus yet with different random seeds, different solutions may result. It is also possible that two word vectors corresponding to different times, i.e., $\mathbf{U}_{.,t_1}$ and $\mathbf{U}_{.,t_2}$ cannot be compared because they might be arbitrarily rotated. One has to align these time-specific word embeddings. Because of the equivalence between prediction-based word embedding and matrix factorization[12], this rotation-invariant issue holds in prediction-based word embedding, e.g., Word2Vec, as well.

Table 1: Comparison of existing diachronic word representation and Word2Fun. i refers to a word index; j refers to a dimension index. The target embedding $\boldsymbol{C} \in \mathbb{R}^{VD}$ is not considered in this table.

	Diachronic word vectors		Param.
Word2Vec	standard word embeddings, e.g., [13]	$\boldsymbol{W}_i$	VD
Aligned Diachronic Word2Vec	linear projection [11, 9] vector initialization [10] discrepancy penalty [17, 22] latent diffusion [1] temporal referencing [7] aligned compass [6]	$\mathbf{B}_{i,t}$; $\mathbf{B}_{i,t} \in \mathbb{R}^D$	TVD
Word2Fun	linear function ('fun.' in short)	$\boldsymbol{W}_i + \boldsymbol{K}_i t$	$2VD$
	sinusoidal fun. I (Time2Fun)	$\boldsymbol{B}_i + \sin(\boldsymbol{\Omega} t)$	$VD + D$
	sinusoidal fun. II (w/ fixed freqs)	$\boldsymbol{B}_i + \boldsymbol{R}_i[\sin(\boldsymbol{\Omega} t; \cos(\boldsymbol{\Omega} t)], \boldsymbol{\Omega}_j = \frac{1}{10000}^{j/\frac{D}{2}}$	$2VD$
	sinusoidal fun. III (w/ trainable freqs)	$\boldsymbol{B}_i + \boldsymbol{R}_i[\sin(\boldsymbol{\Omega}_{\boldsymbol{i}}^{(1)} t); \cos(\boldsymbol{\Omega}_{\boldsymbol{i}}^{(2)} t)]$	$3VD$
	sinusoidal fun. IV(w/ trainable phases)	$\boldsymbol{B}_i + \boldsymbol{R}_i[\sin(\boldsymbol{\Omega}_{\boldsymbol{i}}^{(1)} t + \boldsymbol{\Theta}_{\boldsymbol{i}}^{(1)}); \cos(\boldsymbol{\Omega}_{\boldsymbol{i}}^{(2)} t + \boldsymbol{\Theta}_{\boldsymbol{i}}^{(2)})]$	$4VD$

2.3 Existing Work of Diachronic Word Embedding

Existing dynamic word embedding approaches, e.g., [1, 9], solve the issue as a Markov process where word dynamics is considered only in two consecutive time-specific corpora (e.g., t_1 and t_2), instead of a whole continuous process. The parameters of a Markov process are estimated on the assumption that the event occurring at t only depends on the event at $t-1$. Dynamic word embedding approaches based on the Markovian assumption train word vectors for each time-specific corpus and then *align* them using orthogonal projections [9, 11], vector initialization [10], temporal referencing [7], parameter regularizers [22, 17], aligned compass [6], latent diffusion [1]. The number of parameters of the alignment-based dynamic word embeddings is proportional to the number T of time bins, resulting in a parameter space of $O(TVD)$. Tab. 1 summarizes these approaches.

Limitations. There are three limitations of the above train-and-align approaches. First, transformations between any two consecutive time bins are independent, namely, $\mathbf{U}_{i,t_1}$, $\mathbf{U}_{i,t_2}$ may be totally independent of the one between $\mathbf{U}_{i,t_2}$, $\mathbf{U}_{i,t_3}$ even if they are nearby in the time scale. Note that the word vectors might lose some power to model such sequential evolution with more than two time bins in the event of word meaning that gradually evolves during a longer timespan, e.g., many decades. Second, dividing a corpus into separate time bins may lead to many smaller training sets. Suppose we have T time bins, word vectors in a time bin are trained with roughly $\frac{1}{T}$ training examples. This is unfriendly to time-unbalanced dynamic corpora. e.g., there are much fewer documents in a specific year t than others; the word-specific word vectors in that year may be distorted because of underfitting and, therefore, negatively affect the long-range transformation of word meaning change.

Finally, much storage space is needed since the train-and-align approaches store word vectors for each time. For example, in COHA that spans 200 years, these approaches require 200 copies of full-vocabulary word vectors to investigate yearly evolution, which is space-costly.

Contribution of our work. We argue that a method to unify all time-specific corpora chronologically in a single dynamic process would be expected. This paper addresses the limitations above through a method called 'Word2Fun', which models words as functions to capture word meaning change over time. The Contribution of Word2Fun are:

1. Word2Fun is a novel paradigm to model smooth transformations of word meaning change over long timespans; empirical results evidences its effectiveness.

2. Space complexity of diachronic word representation is reduced from $O(TVD)$ to $O(kVD)$, k is a small constant term; thus space complexity is constant with respect to long timespans.

3 Methodology: Modelling Words as Functions

3.1 Formulation

To smoothly model word meaning change over time we represent each word as a continuous function: a specific word vector at time t is represented as the values of the function when the variable equals t. More formally, our approach aims to learn a mapping that maps each word w_i to functions over time:

$$f : \mathbb{N} \to (g : \mathbb{N} \to \mathbb{R}^D)$$

where f maps a word, e.g., w_i with index i, to a function g, which is a function over a variable $t \in \mathbb{N}$. Note that the output of g is a D-dimensional vector, $g(t) \in \mathbb{R}^D$. Let us denote $f(i)$ as g_i. A word w_i at time t is represented as a D-dimensional vector $\mathbf{U}_{i,t} = f(i)(t) = g_i(t)$.

Examples of g are linear functions $g(t) = \boldsymbol{b} + \boldsymbol{k}t$ with parameters $\boldsymbol{b}, \boldsymbol{k} \in \mathbb{R}^D$ or a sinusoidal functions $g(t) = \boldsymbol{b} + \boldsymbol{r}\sin(\boldsymbol{\omega}t + \boldsymbol{\theta})$ with parameters $\boldsymbol{b}, \boldsymbol{r}, \boldsymbol{\omega}, \boldsymbol{\theta} \in \mathbb{R}^D$. Section 4 reports some remarks on the considered instantiations of g and how they are linked to previously proposed approaches.

3.2 A Skip-gram Implementation with a Compass

The Skip-gram model architecture tries to predict the source context words (surrounding words) given a target word (the center word), which was considered to achieve the reverse of what the CBOW model does. Let us denote u as the target word and v as the source word, and negatively-sampled target words $\hat{\mathbb{V}} = \{\hat{v}_i\}$. It learns a diachronic word representation method $f : \mathbb{N} \times \mathbb{R} \to \mathbb{R}^D$ and a static word mapping $h : \mathbb{N} \to \mathbb{R}^D$; $f(u, t)$ denotes the diachronic word vector of w_u in time t.

The static word embedding $h(u)$ is introduced to align the diachronic word vectors in different time; it is called a *compass* in [6]. Our implementation of the *compass* differs from [6], since we jointly train the static compass and diachronic word vectors simultaneously, thus avoiding a two-stage training and the compass can be non-fixed in the second stage.

The loss function is defined as:

$$\mathcal{L} = -\sum_{(u,v,\hat{\mathbb{V}},t) \in \mathbb{D}_{\text{train}}} \left(\log(\delta(f(u,t)h(v)^T)) + \frac{1}{|\hat{\mathbb{V}}|}\sum_{\hat{v}_i \in \hat{\mathbb{V}}} \log(\delta(-f(u,t)h(\hat{v}_i)^T)) \right) \tag{2}$$

The algorithm is explained in Algo. 1, and details on the parameterization are reported in Tab. 1.

ALGORITHM 1: Training algorithm for Word2Fun.

Require: time-stamped corpora $\{\mathcal{C}_t\}$;
            a diachronic word mapping $f : (\mathbb{N}, \mathbb{R}) \to \mathbb{N}^D$
            a static word mapping $h : \mathbb{N} \to \mathbb{R}^D$
1: shuffling time-stamped corpora
2: **for** epoch $t = 1$ to L **do**
3:     **for each** t-time-stamped skip-gram (u, v) in $\{\mathcal{C}_t\}$ **do**
4:        calculating the loss for the positive sample $\mathcal{L}_{\text{pos}} = \log(\delta(f(u,t)h(v)^T))$
5:        generating negatively-sampled target words $\hat{\mathbb{V}}$
6:        calculating the loss for negative samples $\mathcal{L}_{\text{neg}} = -\sum_{\hat{v}_i \in \hat{\mathbb{V}}} \log(\delta(-f(u,t)h(\hat{v}_i)^T))$
7:        back-propagating using the loss $\mathcal{L} = \mathcal{L}_{\text{pos}} + \mathcal{L}_{\text{neg}}$
8:     **end for**
9: **end for**

---

4 Which Functions?

4.1 Function Approximation using Polynomials

For a skip-gram pair (w_i, w_j),[2] the similarity degree between a context word w_i and a target word w_j in time t is calculated as a dot product between the time-specific context embedding $f(i, t)$ and

---

[2]If w_i and w_j appear together in a h-size window, we call (w_i, w_j) as a skip-gram pair in this paper, w_i is the context word and w_j is the target word, and vice versa.

138 the static target embedding $h(j)$ — the latter is the 'compass'.

$$y_{i,j}(t) = f(i,t)h(j)^T \tag{3}$$

139 By treating $y_{i,j}(t)$ as a function over time, it measures the *similarity between w_i and w_j over evolving*
140 *time*;[3] we argue that semantic change detection can be captured by approximating arbitrary between-
141 word similarity over time. The problem becomes how to approximate a real function over time t, i.e.,
142 $y_{i,j}(t)$, by selecting appropriated parameterization of f and h.

143 Let us recall the Weierstrass's theorem that states that every continuous real function defined on $[a,b]$
144 can be approximated by a real polynomial. Note Theorem 1 also holds for trigonometric polynomial
145 defined in Definition 1, see Corollary 1.

146 **Theorem 1.** *Weierstrass Approximation Theorem. Let F be a continuous real-valued function*
147 *defined on the real interval $[a,b]$. For any $\epsilon > 0$, there exists a polynomial P such that for all*
148 $x \in [a,b]$, *we have* $|F(x) - P(x)|_\infty < \epsilon$.

149 **Definition 1.** A **trigonometric polynomial** of degree D is an expression of the form $\Delta +$
150 $\sum_{k=1}^{D} \alpha_k \cos(kx) + \beta_k \sin(kx)$, where $\Delta, \alpha_1, \ldots, \alpha_D, \beta_1, \ldots, \beta_D \in \mathbb{R}$.

151 **Corollary 1.** *Approximation by trigonometric polynomials For every continuous function $F : \mathbb{R} \to$*
152 $\mathbb{R}$ *defined on the real interval $[0, 2\pi]$, and for any $\epsilon > 0$, there exists a trigonometric polynomial P*
153 *such that for all $x \in [0, 2\pi]$, we have* $|F(x) - P(x)|_\infty < \epsilon$.

154 **Corollary 2.** *The trigonometric polynomials* $span\{1, \sin x, \cos x, \cdots, \sin(Dx), \cos(Dx)\}$ *is dense*
155 *in* $\mathcal{C}[0, 2\pi]$ *iff* $span\{1, \sin\frac{2\pi x}{a-b}, \cos\frac{2\pi x}{a-b}, \cdots, \sin\frac{2\pi Dx}{a-b}, \cos\frac{2\pi Dx}{a-b}\}$ *is dense in* $\mathcal{C}[a,b]$.

156 From Corollary 1 [14, 23], we know that a trigonometric polynomial
157 $\{0, \sin x, \cos x, \cdots, \sin(Dx), \cos(Dx)\}$ spans a subspace that can approximate any continu-
158 ous functions defined on $[0, 2\pi]$ (i.e., it is dense in $\mathcal{C}[0, 2\pi]$). By Corollary 2, one can conclude that
159 a weighted sum of sinusoidal functions with appropriate periods can approximate any continuous
160 functions defined in an arbitrary closed interval [14].

161 ## 4.2 Sinusoidal Parameterization in Word2Fun

162 Since the static embedding $h(j)$ is not related to time t, we consider $f(i,t)$ with sinusoidal paramer-
163 ization (a mixture of cosine and sine functions plus a bias term). Then Eq. 3 will result in [4]:
164

$$
y_{i,j}(t) = f(i,t)h(j)^T = \sum \left(\begin{bmatrix} \boldsymbol{B}_{i,1} + \boldsymbol{R}_{i,1}\sin(\Omega_1 t) \\ \boldsymbol{B}_{i,2} + \boldsymbol{R}_{i,2}\cos(\Omega_1 t) \\ \cdots \\ \boldsymbol{B}_{i,D-1} + \boldsymbol{R}_{i,D-1}\sin(\Omega_{\frac{D}{2}} t) \\ \boldsymbol{B}_{i,D} + \boldsymbol{R}_{i,D}\cos(\Omega_{\frac{D}{2}} t) \end{bmatrix} \odot \begin{bmatrix} \boldsymbol{C}_{j,1} \\ \boldsymbol{C}_{j,2} \\ \cdots \\ \boldsymbol{C}_{j,D-1} \\ \boldsymbol{C}_{j,D} \end{bmatrix} \right)
$$
$$
= \underbrace{\sum_{k=1}^{D} \boldsymbol{B}_{i,k}\boldsymbol{C}_{j,k}}_{\Delta} + \sum_{k=1}^{\frac{D}{2}} \underbrace{\boldsymbol{R}_{i,2k-1}\boldsymbol{C}_{j,2k-1}}_{\alpha_{i,j,k}}\sin(\Omega_k t) + \underbrace{\boldsymbol{R}_{i,2k}\boldsymbol{C}_{j,2k}}_{\beta_{i,j,k}}\cos(\Omega_k t)
\tag{4}
$$

165 Therefore, $y_{i,j}(t)$ is a weighted sum of sinusoidal functions plus a constant term $\Delta = \sum_{k=1}^{D} \boldsymbol{B}_{i,k}\boldsymbol{C}_{j,k}$.
166 By replacing the coefficients with $\alpha_{i,j,k}$ and $\beta_{i,j,k}$, we can rewrite Eq. 4 as $y(t) = \Delta +$
167 $\sum_{k=1}^{\frac{D}{2}} \alpha_{i,j,k}\sin(\Omega_k t) + \beta_{i,j,k}\cos(\Omega_k t)$; $\{\alpha_{i,j,k}\}_{k=1}^{\frac{D}{2}}$ and $\{\beta_{i,j,k}\}_{k=1}^{\frac{D}{2}}$ are the coefficients and
168 $\{\Omega_k\}_{k=1}^{\frac{D}{2}}$ are the corresponding frequencies. Following the argument in [4] when discussing approxi-
169 mation properties of sine and cosine activation functions, since linear combinations of sine and cosine
170 generate all finite trigonometric polynomials that have approximation properties described in Section
171 4.1, the dot product between the diachronic embedding $f(i,t)$ and the static target embedding $h(i)$,
172 denoted as $y_{i,j}(t)$, can capture any evolving relations between arbitrary skip-gram pairs.

173 By iteratively training all skip-gram pairs, Word2Fun can model complicated semantic change
174 across time. Intuitively, long frequencies would reflect some long-range evolution, while some

---

[3]For PPMI factorization to obtain word vectors, $y_{i,j}(t)$ is the changing PPMI between w_i and w_j over time.
[4]$\odot$ is the element-wise multiplication

Table 2: Statistics of Diachronic corpora.

corpus	num. of tokens	time range	time granularity	T	Vocab
COHA [5]	472M	1810 - 2009	every decade	20	43, 734
New York Times [22]	105M	1990 - 2016	yearly	27	20, 314

low frequencies would capture short-range evolution. Such periodical property would allow such functions to capture long enough evolution without considering constraint issues. Note that the function would not necessarily be periodical with an extremely long period in a limited timespan.

4.3 Investigated Function Parameterizations

Linear functions. A real polynomial naturally induce: $\mathbf{U}_{i,t} = g_i(t) = \boldsymbol{b}_i + \boldsymbol{k}_i \odot [1, t, t^2, \cdots t^D]^T$. Since t^D is computationally expensive and sometimes meets the overflow issue, we choose a simpler case with a linear function parameterization of Word2fun: $\mathbf{U}_{i,t} = g_i(t) = \boldsymbol{b}_i + \boldsymbol{k}_i t$.

Sinusoidal functions. In this work, we investigate the sinusoidal parameterization. We use a combination of sine and cosine functions; i.e., half of dimensions are parameterized by sine functions and half of them are parameterized by cosine functions. Considering the domain of time $t \in \mathbb{N}$ and its range in this paper, we adopt a set of frequencies $\{\boldsymbol{\omega}_i\}$ [21] that is different from standard trigonometric polynomial. The *Word2Fun* II is defined as below:

$$g_i(t) = \boldsymbol{b}_i + \boldsymbol{r}_i[\cos(\boldsymbol{\Omega}t); \sin(\boldsymbol{\Omega}t)], \quad \boldsymbol{\Omega}_j = \frac{1}{10000}^{j/\frac{D}{2}}, \; j \in [1, \cdots, \frac{D}{2}] \tag{5}$$

Note we add a static component $\mathbf{b}_i$ that is independent from time. In *Word2Fun* III we also learn word-specific frequencies: $\mathbf{U}_{i,t} = g_i(t) = \boldsymbol{b}_i + \boldsymbol{r}_i[\sin(\boldsymbol{\omega}_i^{(1)}t); \cos(\boldsymbol{\omega}_i^{(2)}t)]$. *Word2Fun* IV adds trainable word-specific phases: $\mathbf{U}_{i,t} = g_i(t) = \boldsymbol{b}_i + \boldsymbol{r}_i[\sin(\boldsymbol{\omega}_i^{(1)}t + \boldsymbol{\theta}_i^{(1)}); \cos(\boldsymbol{\omega}_i^{(2)}t + \boldsymbol{\theta}_i^{(2)})]$, see Tab. 1. $\boldsymbol{\omega}_i^{(1)} \in \mathbb{R}^{\frac{D}{2}}$ is different from $\boldsymbol{\omega}_i^{(2)} \in \mathbb{R}^{\frac{D}{2}}$. $\boldsymbol{\theta}_i^{(1)} \in \mathbb{R}^{\frac{D}{2}}$ is different from $\boldsymbol{\theta}_i^{(2)} \in \mathbb{R}^{\frac{D}{2}}$.

Standard static word vectors, e.g., [13], can be considered as constant functions, a special case of Word2fun since $\boldsymbol{b}_i$ is a time-agnostic word vector. For instance, (1) in the case of the linear function, $\boldsymbol{k}_i = \boldsymbol{0}$; (2) in the case of sinusoidal function, $\boldsymbol{r}_i = \boldsymbol{0}$ or $\boldsymbol{\omega}_i$ is small enough. Both these cases results in $g_i = \boldsymbol{b}_i$. The additional parameters $\boldsymbol{\omega_i}$ and $\boldsymbol{r}_i$ are expected to capture the word meaning evolution.

Time2Fun: purely encoding time as functions. We can separately learn a word mapping and a time mapping:

$$f_{\text{word}} : \mathbb{N} \longrightarrow \mathbb{R}^D, \quad f_{\text{time}} : \mathbb{N} \longrightarrow \mathbb{R}^D \tag{6}$$

Then w_i at time t can be represented as $\mathbf{U}_{i,t} = f_{\text{word}}(i) + f_{\text{time}}(t)$, where f_{time} can be a function over time, e.g., $f_{\text{time}} = \boldsymbol{K}t$ or $f_{\text{time}} = \sin(\boldsymbol{\Omega}t)$ — the latter corresponds to Word2Fun I in Tab. 1.

5 Experiments

5.1 Data and Experimental Settings

Corpora. The diachronic corpora used in this paper are reported in Tab. 2. The Corpus of Historical American English (**COHA**) [5] is the largest structured corpus of historical English (the 1820s-2010s), contains more than 475 million words and is balanced by genre decade by decade. The **New York Times** (NYT) [22] contains 99,872 articles published between January 1990 and July 2016; besides the article text, metadata including title, author, release date, and section label were also collected.

Baselines. We choose the baselines from [22]. *Static Word2Vec*: the standard word2vec embeddings [13], trained on the entire corpus and ignoring time information. *Transformed Word2Vec* [11]: the embeddings are first trained separately by factorizing PPMI matrix for each year, and then transformed by optimizing a linear transformation matrix which minimizes the distance between two consequent time-stamped trained embeddings for the k nearest words' embeddings to the querying words. *Aligned Word2Vec* [9] : the embeddings are first trained by factorizing the PPMI matrix for each year t, and

Table 3: Experimental results of Time-aware word clustering.

Method	10 Clusters		15 Clusters		20 Clusters	
	NMI	F_β	NMI	F_β	NMI	F_β
Global/static word vector [13]	0.6736	0.6163	0.6867	0.7147	0.6713	0.7214
Transformed Word2Vec [11]	0.5175	0.4584	0.5221	0.5072	0.5130	0.5373
Aligned Word2Vec [9]	0.6580	0.6530	0.6618	0.7115	0.6386	0.7187
Dynamic Word2Vec [22]	0.7175	0.6949	0.7162	0.7515	0.6906	0.7585
Compass aligned Word2Vec [6]	0.5191	0.3750	0.5062	0.4051	0.5077	0.4331
Word2Fun linear	0.1676	0.1813	0.2826	0.3035	0.2473	0.2932
Word2Fun I (Time2Fun)	0.1703	0.1783	0.2691	0.2680	0.2842	0.2649
Word2Fun II	**0.7281**	**0.7147**	**0.7181**	0.7645	**0.7012**	0.7616
Word2Fun III	0.7233	0.7080	0.7086	**0.7701**	0.6980	**0.7630**
Word2Fun IV	0.7111	0.6913	0.7023	0.7451	0.6823	0.7602

then aligned by searching for the best orthonormal transformation between two consequent time-stamped trained embeddings. *Dynamic word embedding* [22] learn word embedding by factorizing PPMI matrix in individual time; plus, it imposes a regularizer to encourage two subsequent word embedding being similar for alignment. We only implement dynamic word embeddings in [22], since it is a generalized version of many train-and-align paradigm based dynamic word embeddings, e.g., [9, 11]. In addition to the baselines in [22], we considered also *Compass aligned word embedding* [6] that proposes a identical fixed target embeddings to align time-specific context embeddings.

Experimental settings. We removed words that appear less than 200 times, as [22] did. We used the Adam optimizer with a learning rate of 0.0025. The batch size can be as big as it achieves the upper bound of memory of GPU. The model converged in less than 20 epochs with no drop in terms of loss. We computed the average performance on the last three saved checkpoints. For sinusoidal functions, we used a mixture of cosine functions and sine functions. The dimension was 100; we preliminary found that models with bigger dimensions (e.g. 200 or 300) can slightly improve performance. Word2Fun with all settings was slightly slower than the standard Word2Vec due to additional computation for obtaining word vectors. However, all methods include Word2Vec and Word2Fun took 10-15 minutes for one epoch in a single Nvidia V100 32G GPU for NYT dataset.

5.2 Quantitative Evaluations

The quantitative evaluation is performed using the quantitative methods by [22] – time-aware word clustering and temporal analogy – and the Semantic Change Detection task [18].

5.2.1 Time-aware Word Clustering

If one word is extremely frequent in a particular section, it was labeled as most-used in that section.[5] Such section annotation was used to evaluate the clustering results, which were firstly reported by [22]. Across 11 sections, there were 1,888 triplets denoted as (w_i, t_i, s_i) to indicate that word w_i in year t_i was associated with section s_i.

We apply spherical K-means on learned time-specific word vectors using cosine distance, with K = 10, 15, and 20 clusters. As in [22], we used *Normalized Mutual Information* (NMI) and F_β-*measure* to measure the consistency between section label and clustering results. **NMI** was defined as $\text{NMI}(\mathcal{C}, \mathcal{S}) = 2\text{MI}(\mathcal{C}, \mathcal{S})/(\text{E}(\mathcal{C}) + \text{E}(\mathcal{S}))$, where $\mathcal{S}$ denotes section labels ($\{s_i\}$) for word-year pairs $\{(w_i, t_i)\}$ and $\mathcal{C}$ denotes clustering categories ($\{c_i\}$) for these word-year pairs $\{(w_i, t_i)\}$. $\text{MI}(\cdot, \cdot)$ and $\text{E}(\cdot)$ are the functions to compute Mutual Information and Entropy respectively. $F_\beta = \frac{(\beta^2+1)PR}{\beta^2 P + R}$ measures the effectiveness as a β-weighted harmonic mean of precision and recall. As in [22], we set $\beta = 5$ to emphasise recall to penalizing false negative more.

---

[5]News articles in NYT dataset are tagged with their 'sections' such as 'Business', 'Sports', 'World', and 'Technology'. For example, we see that *amazon* occurs 41% of the time in *World* in 1995, associating strongly with the rainforest, and 50% of the time in *Technology* in 2012, associating strongly with *e-commerce*.

Table 4: Experimental results of temporal analogy in *test1*

Method	MRR	P@1	P@3	P@5	P@10
Global/static Word2Vec [13]	0.3560	0.2664	0.4210	0.4774	0.5612
Transformed Word2Vec [11]	0.0920	0.0500	0.1168	0.1482	0.1910
Aligned Word2Vec [9]	0.1582	0.1066	0.1814	0.2241	0.2953
Dynamic Word2Vec [22]	0.4222	0.3306	0.4854	0.5488	0.6191
Compass aligned Word2Vec [6]	**0.481**	**0.404**	**0.534**	0.582	0.636
Word2Fun linear	0.3016	0.2649	0.3255	0.3426	0.3630
Word2Fun I (Time2Fun)	0.3735	0.2646	0.4300	0.4955	0.5874
Word2Fun II	0.4061	0.2756	0.4916	0.5614	0.6434
Word2Fun III	0.4354	0.3076	0.5330	**0.5837**	**0.6647**
Word2Fun IV	0.4208	0.2954	0.5076	0.5715	0.6470

Table 5: Experimental results of temporal analogy in *test2*

Method	MRR	P@1	P@3	P@5	P@10
Global/static Word2Vec [13]	0.0472	0.0000	0.0787	0.0787	0.2022
Transformed Word2Vec [11]	0.0664	0.0404	0.0764	0.0989	0.1438
Aligned Word2Vec [9]	0.0500	0.0225	0.0517	0.0787	0.1416
Dynamic Word2Vec [22]	0.1444	0.0764	0.1596	0.2202	0.3820
Compass Aligned Word Embedding [6]	0.1361	0.0749	0.1918	0.2904	0.3918
Word2Fun linear	0.0425	0.0137	0.0384	0.0630	0.1014
Word2Fun I (Time2Fun)	0.0992	0.0000	0.1315	0.1726	0.2849
Word2Fun II	0.1194	0.0358	0.1075	0.2219	0.3863
Word2Fun III	**0.1824**	**0.0795**	**0.1973**	**0.2932**	**0.4164**
Word2Fun IV	0.1536	0.0548	0.1562	0.2411	0.3918

Experimental results. As shown in Tab. 3, the proposed Word2fun II, III and IV outperformed all the baseline methods. Word2Fun with linear parameterization and Word2fun I performed nearly the worst, since they could not learn word-dependent evolution. Word2fun IV achieved better performance than III, thus showing that adding phase was not beneficial to Word2Fun.

5.2.2 Temporal Analogy

Temporal Analogy [19] is task which utilizes quadruples $(w^{(1)}, t^{(1)}, w^{(2)}, t^{(2)})$ to say that "$w^{(1)}$ in year $t^{(1)}$" is like "$w^{(2)}$ in year $t^{(2)}$". To examine the quality of temporal analogy, [22] created a task to investigate equivalences across years. For example, given *obama* in *2012*, we aim to find its equivalent word in 2002. As we know *obama* was the U.S. president in 2012, its equivalent word in 2002 is *bush*, who was the U.S. president in 2002. In this way, there are two test sets. The first set (test1) is based on publicly recorded knowledge that lists different names for a particular role, such as U.S. president for each year. Human experts generated the second test (test2) to explore emerging technologies, brands, and significant events (e.g., disease outbreaks and financial crisis) , etc. Reciprocal Rank (MRR) and Precision@K (P@K) are used for the evaluation.

Experimental results. As shown in Tab. 4 and Tab. 5,Word2Fun III outperformed all baselines in *test2* and some metrics (including P@5, P@10) in *test1*. In *test1*, Word2Fun performed worse than Compass-aligned Word2Vec [6] in terms of MRR and P@1; this might be explained by 1) Word2Fun has fewer parameters than [6] and 2) [6] relies on the Word2Vec implementation [13] and therefore may have benefited from some of the implemented strategies, e.g., negative sampling and word sub-sampling strategies.

5.2.3 Semantic Change Detection

Effectiveness in Semantic Change Detection was investigated by the protocol of the Semeval-2020 task titled 'Unsupervised lexical semantic change detection' [18] that annotates the semantically-shift degree of some English words from 1810-1860 timespan to another timespan 1960-2010. We split

Table 6: Semantic change detection. Baselines in the first group are implemented by this work.

models	Pearson	Spearman
Global/static Word2Vec [13]	nan	nan
Transformed Word2Vec [11]	0.0727	0.0865
Aligned Word2Vec [9]	0.3333	0.3083
Dynamic Word2Vec [22]	0.2727	0.2877
Compass aligned word embedding [6]	0.3199	0.2567
Word2Fun linear	-0.1200	-0.0790
Word2Fun I (Time2Fun)	0.3925	0.4550
Word2Fun II	0.4478	**0.5038**
Word2Fun III	**0.5355**	0.4057
Word2Fun IV	0.4483	0.3578
multilingual BERT [16] (SemEval-2020 1st)	-	0.436
ensemble between aligned Word2Vec and BERT [15] (SemEval-2020 2nd)	-	0.422

Table 7: Most similar words for *apple*, *european*, *phone*, and *browser* from the year 1990 (denoted as 90) to 2016 (denoted as 16). All words are lower cased.

year	90	91	92	93	94	95	96	97	98	99	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
apple			sorbet				|		chutney							|						android					|
browser						netscape										|						android					
phone				telephone				|								911					|		password				|
european		republics		|	euro		|	republics		|	euro			|	hollande		|	republics		|	euro						|

268 data of every decade into time bins. We used Word2Fun trained on COHA dataset. For each word,
269 we take the cosine distance between its first five decade-specific word vectors and last five decade-
270 specific word vectors as the semantic change degree. Thirty seven English words were annotated with
271 semantic shift degree by human experts. In this paper, we use the Pearson and Spearman correlation.

272 **Experimental Results.** As shown in Tab. 6, Word2Fun outperformed the five mentioned baselines
273 and the most effective approaches in the Semeval-2020 'Unsupervised lexical semantic change
274 detection' task. Note that the Semeval-2020 participants [16, 15] did not train on the same text
275 collection; they used a subset of COHA and we use a complete one.

5.3 Qualitative Analysis

277 In Tab. 7, we report some results from the trained word representation in the NYT dataset that ranges
278 from 1990 to 2009. From the the case of '*apple*', we can see that '*apple*' were more about a fruit used
279 to prepare *sorbet* or *chutney*. Since the invention of Android in the early 2000s, '*apple*' has become
280 more related to *Android*. The same trend can be seen in the case of 'browser': it was used in personal
281 computer (e.g., *netscape* browser) in PC era, and then became more popular in mobile devices (e.g.,
282 in *Android* system) in the mobile Internet era. As for '*phone*', it typically referred to a traditional
283 *telephone* in 1990s, and it has become related to *911* (an universal emergency number) since 9/11
284 attacks. In the mobile internet era, *phone* is highly related to password since intelligent phones need
285 password while the fixed-line *phone* does not need. These cases suggest that the proposed Word2Fun
286 can model such semantic change to some extent.

6 Conclusion and Future Work

288 To smoothly model word meaning evolution in a single process, this paper proposes to model the
289 change of word meaning as a function. With a specific type of function like sinusoidal functions,
290 our approach consists of a sum of many sinusoids to approximate the change of word meaning. The
291 proposed method performs comparably with SOTA dynamic word embedding in temporal analogy
292 and achieves better performance than SOTA dynamic word embedding in time-aware word clustering
293 and semantic change detection. This work is a preliminary step to develop sinusoidal function
294 approximation in diachronic word representation. However, we argue this paradigm can inspire more
295 work on a general time-series or sequential modeling research.

References

[1] Robert Bamler and Stephan Mandt. Dynamic word embeddings. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pages 380–389. JMLR. org, 2017.

[2] Yoshua Bengio, Réjean Ducharme, Pascal Vincent, and Christian Janvin. A neural probabilistic language model. *The journal of machine learning research*, 3:1137–1155, 2003.

[3] Ronnie Cann, Ruth Kempson, and Eleni Gregoromichelaki. Semantics: An introduction to meaning in language. 2009.

[4] George Cybenko. Approximation by superpositions of a sigmoidal function. *Mathematics of control, signals and systems*, 2(4):303–314, 1989.

[5] Mark Davies. Expanding horizons in historical linguistics with the 400-million word corpus of historical american english. *Corpora*, 7(2):121–157, 2012.

[6] Valerio Di Carlo, Federico Bianchi, and Matteo Palmonari. Training temporal word embeddings with a compass. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33(01):6326–6334, 2019.

[7] Haim Dubossarsky, Simon Hengchen, Nina Tahmasebi, and Dominik Schlechtweg. Time-out: Temporal referencing for robust modeling of lexical semantic change. *ACL*, 2019.

[8] William L. Hamilton, Kevin Clark, Jure Leskovec, and Dan Jurafsky. Inducing domain-specific sentiment lexicons from unlabeled corpora. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 595–605, Austin, Texas, November 2016. Association for Computational Linguistics.

[9] William L. Hamilton, Jure Leskovec, and Dan Jurafsky. Diachronic word embeddings reveal statistical laws of semantic change. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1489–1501, Berlin, Germany, August 2016. Association for Computational Linguistics.

[10] Yoon Kim, Yi-I Chiu, Kentaro Hanaki, Darshan Hegde, and Slav Petrov. Temporal analysis of language through neural language models. *ACL*, page 61, 2014.

[11] Vivek Kulkarni, Rami Al-Rfou, Bryan Perozzi, and Steven Skiena. Statistically significant detection of linguistic change. In *Proceedings of the 24th International Conference on World Wide Web*, pages 625–635, 2015.

[12] Omer Levy and Yoav Goldberg. Neural word embedding as implicit matrix factorization. In *Proceedings of the 27th International Conference on Neural Information Processing Systems - Volume 2*, NIPS'14, page 2177–2185, Cambridge, MA, USA, 2014. MIT Press.

[13] Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. *ICLR*, 2013.

[14] Allan Pinkus. Weierstrass and approximation theory. *Journal of Approximation Theory*, 107(1):1–66, 2000.

[15] Martin Pömsl and Roman Lyapin. Circe at semeval-2020 task 1: Ensembling context-free and context-dependent word representations. *ACL*, 2020.

[16] David Rother, Thomas Haider, and Steffen Eger. Cmce at semeval-2020 task 1: Clustering on manifolds of contextualized embeddings to detect historical meaning shifts. In *Proceedings of the Fourteenth Workshop on Semantic Evaluation*, pages 187–193, 2020.

[17] Maja Rudolph and David Blei. Dynamic embeddings for language evolution. In *Proceedings of the 2018 World Wide Web Conference*, pages 1003–1011, 2018.

[18] Dominik Schlechtweg, Barbara McGillivray, Simon Hengchen, Haim Dubossarsky, and Nina Tahmasebi. Semeval-2020 task 1: Unsupervised lexical semantic change detection. *SemEval*, 2020.

[19] Terrence Szymanski. Temporal word analogies: Identifying lexical replacement with diachronic word embeddings. In *Proceedings of the 55th annual meeting of the association for computational linguistics (volume 2: short papers)*, pages 448–453, 2017.

[20] Nina Tahmasebi, Lars Borin, and Adam Jatowt. Survey of computational approaches to lexical semantic change. *arXiv preprint arXiv:1811.06278*, 2018.

[21] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. *NIPS 2017*, 2017.

[22] Zijun Yao, Yifan Sun, Weicong Ding, Nikhil Rao, and Hui Xiong. Dynamic word embeddings for evolving semantic discovery. In *Proceedings of the eleventh acm international conference on web search and data mining*, pages 673–681, 2018.

[23] Matt Young. The stone-weierstrass theorem. In *MATH 328 Notes*. Queen's University at Kingston, 2006.