MVEB: Massive Video Embedding Benchmark

Abstract

We introduce the **M**assive **V**ideo **E**mbedding **B**enchmark (MVEB), a 23-task benchmark for video embeddings spanning classification, zero-shot classification, clustering, pair classification, retrieval, and video-centric question answering. We evaluate 33 models and find that no single model dominates: MLLM-based embeddings lead on classification, clustering, pair classification, and QA; multimodal binding leads on retrieval and zero-shot classification; generative MLLMs without contrastive adaptation collapse on cross-modal tasks. Paired video-only vs. audio+video evaluations show that audio's contribution depends on dataset annotation provenance: audio helps when labels were produced from both modalities and hurts when they were produced from visuals alone, a six-point gap consistent across model families. MVEB is derived from MVEB+, a 184-task pool, and is designed to maintain task diversity while reducing evaluation cost. It integrates into the MTEB ecosystem for unified evaluation across text, image, audio, and video. We release MVEB and all 184 tasks along with code and a leaderboard at https://anonymous.4open.science/r/mteb-2FEB/.

1 Introduction

Video representations support a wide range of downstream tasks such as action recognition, text-video retrieval, and question answering. Most existing video benchmarks evaluate models on only one such capability, making it difficult to tell whether a high score reflects general-purpose video representation quality or a model that overfits to one task. The result is a fragmented landscape in which models with strong action-recognition scores routinely under-perform on retrieval, and vice versa, with no standard protocol for measuring this gap.

We introduce the **M**assive **V**ideo **E**mbedding **B**enchmark (MVEB), the video sibling in the MTEB (Muennighoff et al., 2023) family of em-bedding benchmarks alongside its multilingual extension MMTEB (Enevoldsen et al., 2025), MIEB (Xiao et al., 2025b) for image, and MAEB (Assadi et al., 2026) for audio. Like its predecessors, MVEB measures general-purpose embedding quality zero-shot, with no per-task fine-tuning. MVEB systematically pairs every audio-bearing dataset with both video-only and video+audio variants, enabling direct measurement of when audio improves video understanding, a setting prior video benchmarks (see §2) do not support.

MVEB itself is a curated 23-task subset of MVEB+ (a 184-task pool) selected by correlation-based redundancy pruning. MVEB groups tasks into six families: classification, zero-shot classification, clustering, pair classification, retrieval (over eight modality directions), and video-centric question answering. Models that cannot accept the full audio+video+text input surface are evaluated on modality-restricted leaderboards drawn from the same pool: MVEB(text, video) (19 tasks) for text-video encoders without an audio encoder, and MVEB(video) (9 tasks) for video-only encoders.

Evaluating 33 models across six embedding paradigms, we find that no single model dominates: MLLM-based embedding leads on classification, clustering, pair classification, and QA; multimodal binding leads on retrieval and zero-shot classification; and generative MLLMs used as embedders without contrastive adaptation collapse on cross-modal tasks. Two findings stand out: (i) The audio track of a video is a distinct signal whose contribution depends on the dataset's annotation provenance. Audio helps on AV-grounded datasets (labels produced from both modalities) and hurts on V-grounded ones (labels produced from visuals alone), a six-point gap consistent across task types and model families (§5.1); (ii) The modality-restricted MVEB(text, video) leaderboard reorders the top of the field: a text-video embedder without

Figure 1: Overview of task types and example subtypes in MVEB+.

an audio path (Qwen3-VL-Embedding-8B) takes rank 1 ahead of every audio+video+text model in our roster, so the two leaderboards reward distinct model families.

To summarize, MVEB makes the following key contributions:

1. A 23-task benchmark (MVEB) for video embedding models, curated from a 184-task pool (MVEB+) that combines video with text and audio modalities, with evaluations of 33 models across six embedding paradigms. We also expose MVEB(text, video) for models without an audio encoder and MVEB(video) for video-only encoders, drawn from the same pool.

2. Actionable findings for general-purpose video embedder development: a contrastive embedding stage is a near-prerequisite for cross-modal performance, and training-data alignment matters more than backbone scale for cross-modal tasks.

3. Integration into the MTEB ecosystem with task and model versioning, enabling community-driven contribution and long-term maintenance.

2 Related Work

Embedding Benchmarks MTEB (Muennighoff et al., 2023) and its multilingual, image, and audio extensions MMTEB (Enevoldsen et al., 2025), MIEB (Xiao et al., 2025b), and MAEB (Assadi et al., 2026) have driven progress in representation learning by providing broad, regularly-maintained leaderboards with consistent protocols; MVEB completes the family for video.

Video Representation Benchmarks Prior video benchmarks each cover only a slice of the surface MVEB exercises: VideoEval (Li et al., 2024) (20 models, 12 tasks) is visual-only; UVRB (Guo et al., 2025) (16 datasets) is retrieval-only; LoVR (Cai et al., 2026) (467 videos) is a single long-video retrieval task; VidVec (Tzachor et al., 2026) is a method paper that evaluates on 5 retrieval benchmarks. Most closely related, MMEB-V2 (Meng et al., 2025) extends MMEB (Jiang et al., 2024) to video across four categories (Video Retrieval, Moment Retrieval, Video Classification, and Video QA), and MMEB-V3 (Huang et al., 2026) adds audio as a separate modality with 11 audio tasks across three categories (classification, retrieval, temporal grounding) and cross-modal retrieval directions between audio and each of text, image, and video. MVEB differs in three concrete ways: (i) scale on video: 184 tasks in MVEB+, roughly an order of magnitude more than the video task counts in the closest prior efforts; (ii) audio-visual coupling: MVEB systematically pairs every audio-bearing dataset with both video-only and video+audio variants on the same task and feeds both streams jointly to the model, whereas MMEB-V3 treats audio strictly as a separate modality with cross-modal retrieval directions and never as joint audio+video input; (iii) maintenance: MVEB inherits MTEB's community-driven contribution and

continuous-update model rather than shipping as a static leaderboard, avoiding the stagnation that has affected most prior video benchmarks.

3 Benchmark Construction

MVEB is built on the MTEB ecosystem (Muennighoff et al., 2023), extending its evaluation framework to video alongside the multilingual (Enevoldsen et al., 2025), image (Xiao et al., 2025b), and audio (Assadi et al., 2026) extensions. We inherit MTEB's standardized metrics, minimal task/model interface, versioned artifacts, and community-driven maintenance (Chung et al., 2025). MVEB evaluates *embedding quality*, not transcription or generation.

Dataset Selection: We curate datasets according to four guiding principles: (1) *domain diversity* across action recognition, social media understanding, emotion recognition, music, scene understanding, and instructional content; (2) *task diversity* across the six families described in §3.4; (3) *modality coverage* across video-only, video+text, and video+audio task variants; and (4) *provenance and accessibility*, prioritizing datasets with established usage, clear licensing, and public availability.

Task Selection: Evaluating models across the full 184-task pool (MVEB+) is prohibitively expensive for most groups. Following MMTEB, MIEB, and MAEB, which demonstrated that principled filtering maintains high rank correlation with exhaustive evaluation, we construct the curated MVEB leaderboard using five selection criteria applied to MVEB+: (1) *Validity*: for directional tasks we prioritize the more semantically valid direction (e.g., text-to-video over video-to-text for retrieval); (2) *Unique coverage*: tasks providing exclusive coverage of a domain or capability are retained regardless of other factors (e.g., the only emotion-clustering task or the only video+audio retrieval direction); (3) *Linguistic breadth*: among comparable tasks, we retain those covering more languages; (4) *Redundancy removal*: we compute pairwise correlation matrices across model rankings and remove tasks with Spearman $\rho > 0.85$ to a retained task, keeping the task with broader coverage or lower runtime; (5) *Runtime efficiency*: among otherwise equivalent tasks, we select those with lower computational cost on video, where frame decoding and per-frame encoding dominate runtime.

Applying these filters produces the 23-task MVEB benchmark. Across representative models

MVEB runs roughly 7–10× faster than MVEB+ (Table 1) while maintaining strong correlation in model scores (Pearson r=0.996) and ranking (Spearman ρ=0.944), so curation preserves relative model performance at a fraction of the runtime.

Model	Params	MVEB+	MVEB	Speedup
LCO-Embedding-Omni-7B	7B	302.7	31.9	9.5×
Qwen2.5-Omni-7B	7B	267.3	29.4	9.1×
pe-av-small	847M	159.7	16.7	9.6×
ebind-audio-vision	764M	122.7	16.8	7.3×

Table 1: GPU runtime (hours) on MVEB vs. MVEB+, measured on a single NVIDIA H100.

Alongside MVEB we expose two leaderboards drawn from the same task pool so that modality-restricted models can also be evaluated: **MVEB(text, video)** (19 tasks) for text-video models without an audio encoder, and **MVEB(video)** (9 tasks) for video-only encoders. Table 2 summarises the four artifacts. The full dataset list is in Appendix A.

Artifact	Tasks	Modalities	Where
MVEB+	184	a, t, v	appdx, Tab. 13
MVEB	23	a, t, v	body, Tab. 3
MVEB(text, video)	19	t, v	appdx, Tab. 11
MVEB(video)	9	v	appdx, Tab. 12

Table 2: **MVEB+** is the 184-task collection. **MVEB** is the 23-task curated benchmark we release. **MVEB(text, video)** and **MVEB(video)** are leaderboards drawn from the same pool that let modality-restricted models also be evaluated. Modalities: a=audio, t=text, v=video.

Data Contamination: We cross-reference each model's declared training data against MVEB tasks; per-model overlap is in Appendix E.

Benchmark Ranking: Following MMTEB (Enevoldsen et al., 2025), we compute model ranks using a Borda count (Colombo et al., 2022) by treating each task as a preference voter over models. Since Borda is not a continuous measure, we report both the Borda rank and the mean in the leaderboard.

Reproducibility and Benchmark Accessibility: Building on prior reproducibility efforts (Enevoldsen et al., 2025, 2024; Chung et al., 2025), we extend MTEB with per-subset versioning, named experiment scoping, and richer model metadata; see Appendix G.

3.1 Models

We evaluate 33 publicly-available checkpoints spanning the major paradigms for video embed-

dings, ranging from ∼200M to 10.7B parameters and covering the modality combinations MVEB exercises. The paradigms below correspond to the Type column in the leaderboard; full per-model details are in Appendix C.

Self-supervised Video Encoders learn from video alone, without paired text or audio. We evaluate the V-JEPA-2 family (Assran et al., 2025); these models contribute only to MVEB(video).

Video-Text Contrastive Encoders learn a joint video-text space through contrastive pretraining over web-scale video-caption pairs. We evaluate the X-CLIP family (Ni et al., 2022).

Audio-Visual Contrastive Encoders jointly align video, audio, and text in a shared embedding space, enabling cross-modal retrieval that involves the audio track of the video. We evaluate the Perception Encoder audio-visual family (Vyas et al., 2025).

Multimodal Binding Models learn a single embedding space across modalities by aligning each to a shared anchor, in the style of ImageBind. We evaluate the eBind family (Broadbent et al., 2025).

MLLM-Based Embedding Models take a multimodal large language model backbone and adapt it into an embedding model through a dedicated contrastive or retrieval-objective training stage. This is the largest family in our roster and reflects the recent shift toward MLLM-backed embeddings observed in MIEB and MMEB-V2 (Xiao et al., 2025b). We evaluate LCO-Embedding-Omni (Xiao et al., 2025a), e5-omni (Chen et al., 2026), Tevatron OmniEmbed (Ma et al., 2025), BidirLM-Omni-Embedding (Boizard et al., 2026), UME-R1 (Lan et al., 2025), OmniEmbed-Nemotron (Xu et al., 2025c), Qwen3-VL-Embedding (Li et al., 2026), VLM2Vec-V2.0 (Meng et al., 2025), and Jina-Embeddings-v5-omni (Akram et al., 2026).

Generative MLLMs used as embedders are multimodal large language models trained for generation rather than embedding; we obtain a representation by pooling the final-layer hidden states using the model's default pooling strategy. Including them lets us measure how far a generation-only training objective gets on embedding tasks, without any embedding-specific adaptation. We evaluate Qwen2.5-Omni (Xu et al., 2025a).

3.2 Evaluation Protocol

Video sampling. Video encoders split into two groups. Variable-length models (the omni MLLM-embedding family and the variable-length Perception Encoder checkpoints) sample at fps=2 with a hard cap of max_frames=64 to bound peak GPU memory on long clips. Fixed-length models (X-CLIP, eBind, V-JEPA-2, fixed-length PE-AV) sample the exact frame count their training pipeline expects; full per-model values are in Table 34. We honor each model's declared configuration on every task rather than forcing a benchmark-wide setting because the latter would push half the roster out of distribution. The effect of *deliberately* varying the budget at test time is studied separately in subsection 5.2.

Audio sampling. Each model also declares its required target_sampling_rate, mono-conversion, and an optional duration cap (per-model values in Table 34). We apply a per-model cap rather than a benchmark-wide one because feature extractors differ: caps range from 30 s (PE-AV, the regime it was trained under) to no explicit cap (LCO-Embedding-Omni, which delegates truncation to its own processor). The shared audio collator resamples, mono-converts, and truncates accordingly.

Other protocol details. All models are evaluated zero-shot: we use each model's default embedding output, without fine-tuning or any layer-specific or pooling-specific tuning. The shared MTEB task evaluator consumes these embeddings and applies the per-task metric defined in subsection 3.4. Some models are instruction-tuned and expect a natural-language instruction prepended to each input (e.g., "Represent this video for retrieval:"); others take raw inputs directly. We pass task-specific instructions only to models trained to use them, so each model sees the input format it was trained under.

3.3 Modalities

For every dataset in MVEB whose source video contains an audio track, we extract that audio and run the task twice: once with video only, and once with both video and audio fed to the model. This gives us paired evaluations on the same underlying clips and lets us measure the contribution of the audio track to video understanding (per-task video vs. audio + video columns in the appendix tables; see Appendix D). We expose both variants rather than scoring models only on va because, as §5.1 shows, on V-grounded datasets the audio channel is a confound rather than a fair test of embedding quality. Datasets whose source has no usable audio (e.g., HMDB51, SSv2, Diving48, Breakfast)

cannot be paired and enter the benchmark in their video-only form only; they are still included in MVEB and MVEB+ where applicable, just without an `audio + video` counterpart. This dual-variant scheme applies to classification, zero-shot classification, clustering, pair classification, and QA; retrieval is handled separately via the eight directions listed in §3.4, since each direction's query and target already carry their own modality.

Each model runs only on the task variants compatible with its declared modalities; audio-bearing variants and audio retrieval directions are skipped for text-video-only models.

3.4 Tasks and Evaluation

We follow the task structure of MTEB, MIEB, and MAEB, adapting each task family to video inputs and adding cross-modal directions specific to the video setting.

Classification A logistic regression is trained on frozen video embeddings to predict labels (Alain and Bengio, 2018; Radford et al., 2021). We use few-shot linear probing (Muennighoff et al., 2023; Cherti et al., 2023) with 8 examples per class, balancing evaluation quality with computational efficiency. Accuracy is the main metric.

Zero-shot Classification Video embeddings are matched against text embeddings of class-label prompts (e.g., "a video of {label}") without training a classifier. Prompt templates are hand-crafted per dataset. We measure accuracy following Radford et al. (2021). This task is restricted to models that declare a joint video-text embedding space.

Clustering We use MiniBatchKMeans (with k set to the number of true labels) over video embeddings and report V-measure (Rosenberg and Hirschberg, 2007) as the main metric, evaluating whether embeddings group meaningfully according to semantic categories without any supervised signal.

Retrieval Retrieval evaluates ranking a corpus by relevance to a query under cosine similarity. We support eight retrieval directions across the modality combinations a video benchmark needs. Writing T for text, A for audio, V for video (combined codes like AT denote joint inputs), the directions are: T→V, A→V, AT→V, V→T, VA→T, V→A, VT→A, and T→VA. Multimodal queries or targets are handled by each model's own pathway: omni models use their native multimodal encoder; others fall back to late fusion of unimodal embeddings (mean or concatenation, as the model declares).

nDCG@10 is the main metric.

Pair Classification Given two video inputs, predict whether they satisfy a binary criterion (e.g., same activity, same speaker). Similarity is computed between embeddings and the maximum average-precision over cosine similarity serves as the main metric.

Video-Centric Question Answering (VCQA) Given a video input (optionally with its audio track) and a textual question, select the most relevant answer from a small set of text options. This is implemented as retrieval over a query-specific candidate pool; accuracy is the main metric.

4 Results

Table 3 reports the MVEB leaderboard for the 16 models that can run all 23 tasks; per-task scores, per-direction retrieval breakdowns, the MVEB+ aggregate over all 184 tasks, and the modality-restricted leaderboards are in Appendix D.

No single model dominates, but general-purpose contenders are emerging. LCO-Embedding-Omni-7B ranks first by Borda count with a mean of 57.6 and is the strongest model on QA and clustering, while losing classification to the newer BidirLM-Omni-2.5B-Embedding (61.2), retrieval and zero-shot classification to eBind, and pair classification to LCO-Embedding-Omni-3B. The category leaders span four model families. We read LCO-Embedding-Omni as the closest current candidate for a general-purpose video embedder: it leads or ties on two categories and stays within a few points of the leader on the rest. The per-category spread is visualized in Figure 2.

Text-video specialists lead MVEB(text, video). The modality-restricted MVEB(text, video) leaderboard (Table 11) evaluates 25 models on the 19 text-video tasks of MVEB. Qwen3-VL-Embedding-8B and -2B (Li et al., 2026), vision-language embedders without an audio path, take ranks 1 and 2 at 60.9 and 58.1 mean, ahead of every omni audio+video+text model in our roster (LCO-Embedding-Omni-7B at 56.8); the Qwen3-VL family wins 5 of 6 task categories, with only QA staying with LCO-Embedding-Omni-3B (32.8). The reordering relative to the headline MVEB leaderboard shows that the text-video scope rewards a different family of models from the full audio+video+text scope, making MVEB(text, video) a useful evaluation surface in its own right rather

Model	Type	Params	Rank (↓) MVEB	ZS %	Average			Average per Category					
					Mean	TV	V	Retr	QA	Cls	Clust	Pair	ZS
Number of tasks			(23)		(19)		(9)	(10)	(1)	(6)	(2)	(2)	(2)
LCO-Embedding-Omni-7B	MLLM-based embedding	8.9B	**1**	100%	**57.6**	**56.8**	**61.7**	58.7	**57.0**	59.2	**27.3**	79.6	55.5
e5-omni-7B	MLLM-based embedding	8.9B	2	100%	55.0	54.1	55.7	59.4	43.8	54.7	21.5	77.3	50.2
ebind-full	Multimodal binding	1.8B	3=	83%	55.5	53.8	55.8	**62.3**	31.4	51.3	20.1	75.4	**61.1**
ebind-audio-vision	Multimodal binding	764M	3=	83%	55.5	53.8	55.8	**62.3**	31.4	51.3	20.1	75.4	**61.1**
LCO-Embedding-Omni-3B	MLLM-based embedding	4.7B	5	100%	54.6	54.8	61.6	54.1	56.4	56.1	27.0	**80.7**	52.7
OmniEmbed-v0.1	MLLM-based embedding	8.9B	6=	100%	52.9	51.3	57.9	52.9	50.2	58.5	20.6	74.7	48.5
pe-av-large	Audio-visual contrastive	2.2B	6=	65%	54.3	52.4	55.2	62.0	29.2	54.8	21.7	75.2	37.9
pe-av-base	Audio-visual contrastive	1.0B	8	65%	53.1	49.7	53.8	59.6	30.6	54.8	22.6	75.7	34.6
BidirLM-Omni-2.5B-Embedding	MLLM-based embedding	2.4B	9	100%	51.2	52.0	58.0	45.5	55.8	**61.2**	17.1	78.7	53.9
pe-av-small	Audio-visual contrastive	847M	10	65%	52.2	50.2	53.3	57.6	27.8	54.8	22.9	75.3	35.4
e5-omni-3B	MLLM-based embedding	4.7B	11	100%	48.5	48.4	55.7	52.2	45.4	48.3	21.4	77.0	30.8
omni-embed-nemotron-3b	MLLM-based embedding	4.7B	12	100%	42.8	35.8	54.7	32.9	46.6	54.6	20.5	77.7	42.5
jina-embeddings-v5-omni-nano	MLLM-based embedding	986M	13	NA	20.8	7.7	24.9	10.3	24.4	28.0	12.6	59.1	20.0
jina-embeddings-v5-omni-small	MLLM-based embedding	1.6B	14	NA	19.4	8.2	24.7	6.2	21.2	28.5	13.7	58.6	23.8
Qwen2.5-Omni-7B	Generative MLLM	10.7B	15	NA	12.8	10.4	30.7	0.5	13.2	20.2	7.5	53.2	16.5
Qwen2.5-Omni-3B	Generative MLLM	5.5B	16	NA	11.4	7.8	30.1	0.6	14.4	19.3	5.9	53.7	3.8

Table 3: Top 16 Models on **MVEB** ranked by Borda count over 23 tasks. **Rank** marked with = shares a Borda count with the row above. **ZS %**: disclosed-zero-shot percentage from Table 32 (NA for models that do not disclose training data). **Mean** is the arithmetic mean over the model's 23 evaluated tasks; **TV** and **V** are the same model's mean on the MVEB(text, video) (19 tasks) and MVEB(video) (9 tasks) subsets respectively, lifted from Table 11 and Table 12. Task categories: Retr (retrieval; per-direction breakdown in appendix), QA, Cls (classification), Clust (clustering), Pair (pair classification), ZS (zero-shot classification). Model types are defined in §3.1. **Bold** = best per column *within the 16 rows shown*; the global MVEB(text, video) and MVEB(video) leaders are Qwen3-VL-Embedding (see Appendix D.1).

than a fallback. Full ranking, per-category breakdown, and an extended discussion are in Appendix K.

Figure 2: Per-category mean scores for five representative models spanning the four paradigms. LCO-Embedding-Omni-7B, eBind-full, PE-AV-large, and BidirLM-Omni-2.5B trace broadly similar but distinct shapes; Qwen2.5-Omni-7B (generative MLLM used as embedder) collapses inward across every category. No single model dominates all six.

Adapted MLLMs beat repurposed generative MLLMs by a wide margin. The MLLM-based embedding family fills five of the top ten ranks on MVEB and dominates the top of the text-video scope (Table 11). Generative MLLMs used as embedders via hidden-state pooling collapse: Qwen2.5-Omni-7B and 3B score 12.8 and 11.4

mean on MVEB, an order of magnitude below their MLLM-embed counterparts at the same scale. Within a single backbone family the gap is even sharper: e5-omni-7B (an MLLM-embed adaptation of Qwen2.5-Omni-7B) scores 55.0 vs. 12.8 for the unadapted generative baseline. A contrastive embedding stage is therefore a near-prerequisite, not a refinement.

Smaller specialized contrastive models punch above their weight. eBind (1.8B / 764M) ties for third place by Borda and wins both retrieval (62.3) and zero-shot classification (61.1) outright, despite being four to ten times smaller than the MLLM-embed leaders (Figure 3). Perception Encoder audio-visual variants (847M–2.2B) similarly outscore the comparable-size MLLM-embed model OmniEmbed-Nemotron-3B (4.7B) on retrieval and clustering. We read this as evidence that training-data alignment matters more than backbone scale for cross-modal video tasks.

Clustering and zero-shot classification show the lowest absolute scores. The strongest model reaches only 27.3 on clustering[1] (LCO-Embedding-Omni-7B) and no model exceeds 61.1 on zero-shot

---

[1]V-measure is bounded by label granularity and dataset noise as well as embedding quality, and its scale is not directly comparable to accuracy-based categories, so we read clustering scores as a relative-comparison signal rather than a direct measure of difficulty.

Figure 3: Mean score vs. parameter count for each of the three leaderboards: MVEB (16 models), MVEB(text, video) (25 models), and MVEB(video) (33 models). Pareto-frontier models are highlighted and labeled per panel; off-frontier dots are colored by paradigm but unlabeled. On MVEB the frontier runs from eBind-AV (764M, 55.5) to LCO-Omni-7B (8.9B, 57.6) (a $12\times$ parameter gap for 2.1 points of score). Removing audio (MVEB(text, video) and MVEB(video)) replaces the frontier with Qwen3-VL-Embedding 2B/8B, consistent with the audio-coverage finding in §5.1.

Dataset type	$\bar{\Delta}$	σ	N
AV-grounded	$+0.016$	0.064	475
V-grounded	-0.046	0.059	195

Table 4: Mean audio delta ($\Delta = \text{score}_{va} - \text{score}_v$) across 48 paired task groups and 14 models, split by annotation provenance (Table 9). N counts model–dataset pairs.

classification, against 74–81 on pair classification for top models. The pattern is consistent across model families.

5 Analyses

5.1 Contribution of the Audio Track to Video Understanding

We compare video-only (v) and video+audio (va) task variants across 48 paired task groups spanning five task types and the 14 audio-capable models in our roster, measuring the audio delta $\Delta = \text{score}_{va} - \text{score}_v$.[2]

Annotation provenance predicts audio's contribution. Table 4 reports mean Δ split by the annotation provenance defined in Table 9: *AV-grounded* datasets had labels produced from both audio and visual content, *V-grounded* datasets had labels produced from visuals alone (even though

the clips often carry audio). Audio helps AV-grounded datasets by $+0.016$ on average and hurts V-grounded ones by -0.046: a six-point gap consistent across task types and model families. The V-grounded penalty is about three times the AV-grounded benefit, so the result reads more as "audio hurts when labels don't reward it" than as "audio is a strong positive signal when they do."

The effect varies more within paradigms than across them. Per-paradigm averages sit near zero ($\bar{\Delta} \in [-0.023, +0.010]$ across the four paradigms), with the within-paradigm range often exceeding the between-paradigm spread; only multimodal binding (eBind-full and eBind-audio-vision) consistently loses from audio (-0.023 each). MLLM-based embedders span almost the full range of observed deltas (-0.039 at e5-omni-3B to $+0.023$ at BidirLM-Omni-2.5B), so audio handling is implementation-specific rather than paradigm-determined (per-model deltas in Table 37, Appendix I).

Per-dataset and per-model breakdowns, including cross-modal retrieval alignment for datasets with paired v2a/a2v variants, are in Appendix I.

5.2 Test-Time Scaling of Temporal Context

We sweep the number of uniformly sampled video frames $N \in \{1, 8, 16, 32, 64\}$ at test time, holding audio sampling and all other inputs at each model's default. The analysis uses a subset of MVEB tasks with average clip duration above 15 s (selection criteria in Appendix F).

---

[2]The jina-embeddings-v5-omni-nano/small models are excluded from this analysis: their video-only scores on the paired tasks sit at near-random levels (<0.01 on Kinetics splits), so the va$-$v delta is dominated by base-line noise rather than by audio's contribution and would distort the per-paradigm summary.

Mean performance scales logarithmically with N (Figure 4). Moving from a single-frame spatial baseline to $N = 8$ yields a 43.7% relative improvement; doubling from 32 to 64 frames adds only 2.2% absolute. For general-purpose evaluation, 32 frames is a reasonable ceiling.

Figure 4: Per-model performance as a function of sampled frame count. The black dotted line is the mean over all models. Most of the gain comes from the first jump to multi-frame sampling; returns plateau beyond 32 frames.

The aggregate trend hides large per-task variance: some tasks (e.g., Breakfast classification, VATEX retrieval) scale steeply with N; others (e.g., OmniVideoBench QA, WorldSense-1min QA) barely move. Per-task and per-model curves are in Appendix F.

5.3 Cross-Modal Retrieval Direction Structure

Pairwise Spearman correlation across the eight retrieval directions (Figure 5) shows the directions cluster into three capability groups rather than measuring eight independent things: text-target ($V \rightarrow T, VA \rightarrow T$ at $\rho = 0.96$), video-target with audio in the query ($A \rightarrow V, AT \rightarrow V, V \rightarrow A$; $\rho \geq 0.87$ among them), and text-as-query ($T \rightarrow V$, $T \rightarrow VA, VT \rightarrow A$; $\rho \geq 0.77$). The most decoupled pair is $T \rightarrow VA$ vs. $A \rightarrow V$ at $\rho = 0.38$, isolating audio-as-target as a distinct axis only because MVEB pairs audio+video as joint retrieval modalities. Full pairwise correlations and discussion are in Appendix J.

6 Conclusion

MVEB provides a unified 23-task benchmark for video embedding models, drawn from a 184-task pool (MVEB+) and accompanied by modality-restricted leaderboards for text-video and video-only encoders. Across 33 models from the major video-embedding paradigms no single approach

Figure 5: Pairwise Spearman correlation across the eight retrieval directions over 16 models. The most distinct pair is $T \rightarrow VA$ vs. $A \rightarrow V$ at $\rho = 0.38$.

dominates. Our paired video-only vs. audio+video analysis shows that audio's contribution depends on dataset annotation provenance (AV-grounded vs. V-grounded), and the MVEB(text, video) leaderboard reorders the top of the field relative to MVEB. We release MVEB inside the MTEB ecosystem with task and model versioning, and a community contribution pipeline, so the benchmark can co-evolve with the field rather than freeze as a snapshot.

Limitations

Model Coverage. Our roster covers 33 publicly-available checkpoints across the major paradigms; the field moves quickly so the list is a snapshot, but new models are added on a rolling basis through the MTEB registry. Notable models we plan to add include ImageBind (Girdhar et al., 2023), LanguageBind (Zhu et al., 2024), InternVideo (Wang et al., 2022), VideoMAE (Tong et al., 2022), and VJEPA-2.1(Mur-Labadia et al., 2026); these have open weights but no clean inference API or versioned checkpoints yet.

Frame and Audio Budgets. Each model uses its declared sampling configuration (§3.2), so absolute scores can partly reflect the frame and audio budgets each model was trained under; the frame-scaling analysis (subsection 5.2) explores how scores move when this budget is varied at test time.

Dataset Coverage. While MVEB+ covers 184 tasks across multiple domains, some areas remain thin: low-resource languages are underrepresented, long-form video content (lectures, documentaries)

is largely absent due to runtime cost, and several fine-grained domains (sports beyond a few action-recognition datasets, scientific or medical video, sign language) have limited or no coverage. New datasets are added on a rolling basis through community contributions.

Training Data Disclosure and Leakage. Many MVEB tasks draw from web-curated sources (Kinetics, UCF101, MSR-VTT, VATEX, Panda-70M) that are common in large-scale video-caption pre-training, so train-test contamination is a real risk. Appendix E cross-references each model's declared training data against MVEB task names and reports the resulting disclosed-zero-shot percentage per model. The audit is necessarily incomplete for the subset of our roster that does not disclose training data at dataset granularity; rather than assigning these models an optimistic 100% zero-shot, we report their contamination columns as NA in Table 32 and surface the same convention in the headline leaderboard. Their MVEB scores therefore cannot be certified as zero-shot, and per-dataset comparisons involving them should be interpreted with that disclosure gap in mind.

Annotation Quality. A subset of MVEB source datasets inherits label conventions from their original releases that surface as task-level ambiguities, particularly in emotion-recognition tasks. Recurring issues include single-label assignment on utterances that carry multiple sentiments, labels that capture the surface emotion even when the utterance is sarcastic or non-literal, and a fraction of clips that appear plainly mislabeled. We do not silently include these splits: Appendix L flags every affected dataset with concrete failure-mode examples so readers can gate per-dataset interpretation rather than treating scores uniformly across the benchmark. The right long-term fix is to replace affected splits with cleaner sources as the field releases them, and we plan to deprecate flagged splits in subsequent MVEB releases as replacements appear; the MVEB+ contribution pipeline accepts replacement datasets, re-annotation passes against existing splits, and human-model agreement audits in the style of HUME (Assadi et al., 2025), originally developed for MTEB text tasks. We retain the as-released labels in the current release so MVEB scores remain comparable with prior published results.

Ethical Considerations

MVEB aggregates publicly-released video datasets under each source's release license. For datasets where we host evaluation artifacts on HuggingFace (under the `mteb/` namespace), we redistribute decoded frame samples and 16 kHz mono audio extracted from the source clips, paired with the task wrapper (loader, evaluation code, and metric implementation); we do not re-encode or re-host the original full-resolution video files. For datasets where the upstream owner already provides a public mirror, MVEB ships only the task wrapper and links back to that release. The frame/audio packaging is a working-around-bandwidth choice rather than a content choice: the underlying clips, labels, and consent regime are the upstream releases unchanged. Several included datasets (e.g., Kinetics, UCF101, AVMeme, AVE-Dataset, MELD, RAVDESS, VGGSound) contain identifiable individuals; we evaluate models only as embedders on the labels and tasks those datasets already release, and do not introduce new identifying labels or biometric tasks.

The 33 models we evaluate include multimodal large language models capable of free-form generation; we use them only to produce frozen embeddings, never to generate text, audio, or video. We therefore do not amplify generative risks (e.g., deepfake creation, synthetic transcription) beyond what each model's release already permits.

The benchmark inherits the biases of the underlying datasets, including domain skew (most clips are English-language and from web-curated or US-centric sources) and demographic skew in datasets that depict people. We flag these explicitly in the Dataset Coverage limitation and encourage community contributions that broaden coverage to under-represented languages, regions, and domains.

References

Mohammad Kalim Akram, Saba Sturua, Nastia Havriushenko, Quentin Herreros, Michael Günther, Maximilian Werk, and Han Xiao. 2026. jina-embeddings-v5-text: Task-targeted embedding distillation. *Preprint*, arXiv:2602.15547.

Guillaume Alain and Yoshua Bengio. 2018. Understanding intermediate layers using linear classifier probes. *Preprint*, arXiv:1610.01644.

Adnan El Assadi, Isaac Chung, Roman Solomatin, Niklas Muennighoff, and Kenneth Enevoldsen.

2025. Hume: Measuring the human-model performance gap in text embedding tasks. *Preprint*, arXiv:2510.10062.

Adnan El Assadi, Isaac Chung, Chenghao Xiao, Roman Solomatin, Animesh Jha, Rahul Chand, Silky Singh, Kaitlyn Wang, Ali Sartaz Khan, Marc Moussa Nasser, Sufen Fong, Pengfei He, Alan Xiao, Ayush Sunil Munot, Aditya Shrivastava, Artem Gazizov, Niklas Muennighoff, and Kenneth Enevoldsen. 2026. Maeb: Massive audio embedding benchmark. *Preprint*, arXiv:2602.16008.

Mido Assran, Adrien Bardes, David Fan, Quentin Garrido, Russell Howes, Mojtaba Komeili, Matthew Muckley, Ammar Rizvi, Claire Roberts, Koustuv Sinha, Artem Zholus, Sergio Arnaud, Abha Gejji, Ada Martin, Francois Robert Hogan, Daniel Dugas, Piotr Bojanowski, Vasil Khalidov, Patrick Labatut, and 10 others. 2025. V-jepa 2: Self-supervised video models enable understanding, prediction and planning. *Preprint*, arXiv:2506.09985.

Hritik Bansal, Yonatan Bitton, Idan Szpektor, Kai-Wei Chang, and Aditya Grover. 2023. Videocon: Robust video-language alignment via contrast captions. *arXiv preprint arXiv:2311.10111*.

Nicolas Boizard, Théo Deschamps-Berger, Hippolyte Gisserot-Boukhlef, Céline Hudelot, and Pierre Colombo. 2026. Bidirlm: From text to omnimodal bidirectional encoders by adapting and composing causal llms. *Preprint*, arXiv:2604.02045.

Jim Broadbent, Felix Cohen, Frederik Hvilshøj, Eric Landau, and Eren Sasoglu. 2025. EBind: a practical approach to space binding. *Preprint*, arXiv:2511.14229.

Qifeng Cai, Hao Liang, Zhaoyang Han, Hejun Dong, Meiyi Qiang, Ruichuan An, Quanqing Xu, Bin Cui, and Wentao Zhang. 2026. Lovr: A benchmark for long video retrieval in multimodal contexts. *Preprint*, arXiv:2505.13928.

Joao Carreira, Eric Noland, Andras Banki-Horvath, Chloe Hillier, and Andrew Zisserman. 2018. A short note about kinetics-600. *arXiv preprint arXiv:1808.01340*.

David Chen and William Dolan. 2011. Collecting highly parallel data for paraphrase evaluation. In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 190–200.

Haonan Chen, Sicheng Gao, Timofte Radu, Sakai Tetsuya, and Zhicheng Dou. 2026. e5-omni: Explicit cross-modal alignment for omni-modal embeddings. *arXiv preprint arXiv:2601.03666*.

Honglie Chen, Weidi Xie, Andrea Vedaldi, and Andrew Zisserman. 2020. Vggsound: A large-scale audio-visual dataset. In *ICASSP 2020 - 2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 721–725. IEEE.

Sihan Chen, Xingjian He, Longteng Guo, Xinxin Zhu, Weining Wang, Jinhui Tang, and Jing Liu. 2023. Valor: Vision-audio-language omni-perception pre-training model and dataset. *arXiv preprint arXiv:2304.08345*.

Tsai-Shien Chen, Aliaksandr Siarohin, Willi Menapace, Ekaterina Deyneka, Hsiang-wei Chao, Byung Eun Jeon, Yuwei Fang, Hsin-Ying Lee, Jian Ren, Ming-Hsuan Yang, and Sergey Tulyakov. 2024. Panda-70m: Captioning 70m videos with multiple cross-modality teachers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

Mehdi Cherti, Romain Beaumont, Ross Wightman, Mitchell Wortsman, Gabriel Ilharco, Cade Gordon, Christoph Schuhmann, Ludwig Schmidt, and Jenia Jitsev. 2023. Reproducible scaling laws for contrastive language-image learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2818–2829.

Isaac Chung, Imene Kerboua, Marton Kardos, Roman Solomatin, and Kenneth Enevoldsen. 2025. Maintaining mteb: Towards long term usability and reproducibility of embedding benchmarks. *Preprint*, arXiv:2506.21182.

Pierre Colombo, Nathan Noiry, Ekhine Irurozki, and Stephan Clémençon. 2022. What are the best systems? new perspectives on nlp benchmarking. In *Advances in Neural Information Processing Systems*, volume 35, pages 26915–26932. Curran Associates, Inc.

Hao Dong, Ismail Nejjar, Han Sun, Eleni Chatzi, and Olga Fink. 2023. SimMMDG: A simple and effective framework for multi-modal domain generalization. In *Advances in Neural Information Processing Systems*.

Kenneth Enevoldsen, Isaac Chung, Imene Kerboua, Márton Kardos, Ashwin Mathur, David Stap, Jay Gala, Wissam Siblini, Dominik Krzemiński, Genta Indra Winata, Saba Sturua, Saiteja Utpala, Mathieu Ciancone, Marion Schaeffer, Gabriel Sequeira, Diganta Misra, Shreeya Dhakal, Jonathan Rystrøm, Roman Solomatin, and 67 others. 2025. Mmteb: Massive multilingual text embedding benchmark. *Preprint*, arXiv:2502.13595.

Kenneth Enevoldsen, Márton Kardos, Niklas Muennighoff, and Kristoffer Laigaard Nielbo. 2024. The scandinavian embedding benchmarks: Comprehensive assessment of multilingual and monolingual text embedding. *Preprint*, arXiv:2406.02396.

Chaoyou Fu, Yuhan Dai, Yondong Luo, Lei Li, Shuhuai Ren, Renrui Zhang, Zihan Wang, Chenyu Zhou, Yunhang Shen, Mengdan Zhang, and 1 others. 2024. Video-mme: The first-ever comprehensive evaluation benchmark of multi-modal llms in video analysis. *arXiv preprint arXiv:2405.21075*.

Rohit Girdhar, Alaaeldin El-Nouby, Zhuang Liu, Mannat Singh, Kalyan Vasudev Alwala, Armand Joulin, and Ishan Misra. 2023. Imagebind: One embedding space to bind them all. *Preprint*, arXiv:2305.05665.

Raghav Goyal, Samira Ebrahimi Kahou, Vincent Michalski, Joanna Materzynska, Susanne Westphal, Heuna Kim, Valentin Haenel, Ingo Fruend, Peter Yianilos, Moritz Mueller-Freitag, Florian Hoppe, Christian Thurau, Ingo Bax, and Roland Memisevic. 2017. The "something something" video database for learning and evaluating visual common sense. pages 5843–5851.

Zhuoning Guo, Mingxin Li, Yanzhao Zhang, Dingkun Long, Pengjun Xie, and Xiaowen Chu. 2025. Towards universal video retrieval: Generalizing video embedding via synthesized multimodal pyramid curriculum. *Preprint*, arXiv:2510.27571.

Mingfei Han, Linjie Yang, Xiaojun Chang, Lina Yao, and Heng Wang. 2023. Shot2story: A new benchmark for comprehensive understanding of multi-shot videos. *arXiv preprint arXiv:2312.10300*.

Lisa Anne Hendricks, Oliver Wang, Eli Shechtman, Josef Sivic, Trevor Darrell, and Bryan Russell. 2017. Localizing moments in video with natural language. In *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*.

Jack Hong, Shilin Yan, Jiayin Cai, Xiaolong Jiang, Yao Hu, and Weidi Xie. 2025. Worldsense: Evaluating real-world omnimodal understanding for multimodal llms.

Haohang Huang, Xuan Lu, Mingyi Su, Xuan Zhang, Ziyan Jiang, Ping Nie, Kai Zou, Tomas Pfister, Wenhu Chen, Wei Zhang, Xiaoyu Shen, and Rui Meng. 2026. Mmeb-v3: Measuring the performance gaps of omni-modality embedding models. *Preprint*, arXiv:2604.23321.

Xilin Jiang, Qiaolin Wang, Junkai Wu, Xiaomin He, Zhongweiyang Xu, Yinghao Ma, Minshuo Piao, Kaiyi Yang, Xiuwen Zheng, Riki Shimizu, Yicong Chen, Arsalan Firoozi, Gavin Mischler, Sukru Samet Dindar, Richard Antonello, Linyang He, Tsun-An Hsieh, Xulin Fan, Yulun Wu, and 14 others. 2026a. Avmeme exam: A multimodal multilingual multicultural benchmark for llms' contextual and cultural knowledge and thinking.

Xilin Jiang, Qiaolin Wang, Junkai Wu, Xiaomin He, Zhongweiyang Xu, Yinghao Ma, Minshuo Piao, Kaiyi Yang, Xiuwen Zheng, Riki Shimizu, and 1 others. 2026b. Avmeme exam: A multimodal multilingual multicultural benchmark for llms' contextual and cultural knowledge and thinking.

Ziyan Jiang, Rui Meng, Xinyi Yang, Semih Yavuz, Yingbo Zhou, and Wenhu Chen. 2024. Vlm2vec: Training vision-language models for massive multimodal embedding tasks. *arXiv preprint arXiv:2410.05160*.

Will Kay, Joao Carreira, Karen Simonyan, Brian Zhang, Chloe Hillier, Sudheendra Vijayanarasimhan, Fabio Viola, Tim Green, Trevor Back, Paul Natsev, Mustafa Suleyman, and Andrew Zisserman. 2017. The kinetics human action video dataset. *Preprint*, arXiv:1705.06950.

Chris Dongjoo Kim, Byeongchang Kim, Hyunmin Lee, and Gunhee Kim. 2019. Audiocaps: Generating captions for audios in the wild. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 119–132.

Fanheng Kong, Jingyuan Zhang, Hongzhi Zhang, Shi Feng, Daling Wang, Linhao Yu, Xingguang Ji, Yu Tian, Victoria W., and Fuzheng Zhang. 2025. Tuna: Comprehensive fine-grained temporal understanding evaluation on dense dynamic videos. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (ACL)*. ArXiv:2505.20124.

Ranjay Krishna, Kenji Hata, Frederic Ren, Li Fei-Fei, and Juan Carlos Niebles. 2017. Dense-captioning events in videos. In *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*.

H. Kuehne, H. Jhuang, E. Garrote, T. Poggio, and T. Serre. 2011a. Hmdb: A large video database for human motion recognition. In *2011 International Conference on Computer Vision*, pages 2556–2563.

Hilde Kuehne, Ali Arslan, and Thomas Serre. 2014. The language of actions: Recovering the syntax and semantics of goal-directed human activities. In *2014 IEEE Conference on Computer Vision and Pattern Recognition*, pages 3325–3332.

Hildegard Kuehne, Hueihan Jhuang, Estíbaliz Garrote, Tomaso Poggio, and Thomas Serre. 2011b. Hmdb: a large video database for human motion recognition. In *2011 International Conference on Computer Vision*, pages 2556–2563. IEEE.

Zhibin Lan, Liqiang Niu, Fandong Meng, Jie Zhou, and Jinsong Su. 2025. Ume-r1: Exploring reasoning-driven generative multimodal embeddings. *arXiv preprint arXiv:2511.00405*.

Caorui Li, Yu Chen, Yiyan Ji, Jin Xu, Zhenyu Cui, Shihao Li, Yuanxing Zhang, Wentao Wang, Zhenghao Song, Dingling Zhang, and 1 others. 2025. Omnivideobench: Towards audio-visual understanding evaluation for omni mllms. *arXiv preprint arXiv:2510.10689*.

Guangyao Li, Yake Wei, Yapeng Tian, Chenliang Xu, Ji-Rong Wen, and Di Hu. 2022. Learning to answer questions in dynamic audio-visual scenarios. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 19108–19118.

Mingxin Li, Yanzhao Zhang, Dingkun Long, Keqin Chen, Sibo Song, Shuai Bai, Zhibo Yang, Pengjun

Xie, An Yang, Dayiheng Liu, Jingren Zhou, and Junyang Lin. 2026. Qwen3-vl-embedding and qwen3-vl-reranker: A unified framework for state-of-the-art multimodal retrieval and ranking. *arXiv preprint arXiv:2601.04720*.

Xinhao Li, Zhenpeng Huang, Jing Wang, Kunchang Li, and Limin Wang. 2024. Videoeval: Comprehensive benchmark suite for low-cost evaluation of video foundation model. *Preprint*, arXiv:2407.06491.

Yingwei Li, Yi Li, and Nuno Vasconcelos. 2018. Resound: Towards action recognition without representation bias. In *Proceedings of the European Conference on Computer Vision (ECCV)*.

Steven R. Livingstone and Frank A. Russo. 2018. The ryerson audio-visual database of emotional speech and song (ravdess): A dynamic, multimodal set of facial and vocal expressions in north american english. *PLOS ONE*, 13(5):1–35.

Xueguang Ma, Luyu Gao, Shengyao Zhuang, Jiaqi Samantha Zhan, Jamie Callan, and Jimmy Lin. 2025. Tevatron 2.0: Unified document retrieval toolkit across scale, language, and modality. *arXiv preprint arXiv:2505.02466*.

Karttikeya Mangalam, Raiymbek Akshulakov, and Jitendra Malik. 2023. Egoschema: A diagnostic benchmark for very long-form video language understanding. *Advances in Neural Information Processing Systems*.

Rui Meng, Ziyan Jiang, Ye Liu, Mingyi Su, Xinyi Yang, Yuepeng Fu, Can Qin, Zeyuan Chen, Ran Xu, Caiming Xiong, Yingbo Zhou, Wenhu Chen, and Semih Yavuz. 2025. Vlm2vec-v2: Advancing multimodal embedding for videos, images, and visual documents. *arXiv preprint arXiv:2507.04590*.

Niklas Muennighoff, Nouamane Tazi, Loïc Magne, and Nils Reimers. 2023. Mteb: Massive text embedding benchmark. *Preprint*, arXiv:2210.07316.

Lorenzo Mur-Labadia, Matthew Muckley, Amir Bar, Mido Assran, Koustuv Sinha, Mike Rabbat, Yann LeCun, Nicolas Ballas, and Adrien Bardes. 2026. V-jepa 2.1: Unlocking dense features in video self-supervised learning. *Preprint*, arXiv:2603.14482.

Le Thien Phuc Nguyen, Zhuoran Yu, Samuel Low Yu Hang, Subin An, Jeongik Lee, Yohan Ban, SeungEun Chung, Thanh-Huy Nguyen, JuWan Maeng, Soochahn Lee, and Yong Jae Lee. 2024. See, hear, and understand: Benchmarking audiovisual human speech understanding in multimodal large language models. *arXiv preprint arXiv:2512.02231*.

Le Thien Phuc Nguyen, Zhuoran Yu, Samuel Low Yu Hang, Subin An, Jeongik Lee, Yohan Ban, SeungEun Chung, Thanh-Huy Nguyen, and 1 others. 2025. See, hear, and understand: Benchmarking audiovisual human speech understanding in multimodal large language models. *arXiv preprint arXiv:2512.02231*.

Bolin Ni, Houwen Peng, Minghao Chen, Songyang Zhang, Gaofeng Meng, Jianlong Fu, Shiming Xiang, and Haibin Ling. 2022. Expanding language-image pretrained models for general video recognition. *arXiv preprint arXiv:2208.02816*.

Viorica Patraucean, Lucas Smaira, Ankush Gupta, Adria Recasens, Larisa Markeeva, Dylan Banarse, Skanda Koppula, Mateusz Malinowski, Yi Yang, Carl Doersch, and 1 others. 2023. Perception test: A diagnostic benchmark for multimodal video models. In *Advances in Neural Information Processing Systems (Datasets and Benchmarks Track)*.

Soujanya Poria, Devamanyu Hazarika, Navonil Majumder, Gautam Naik, Erik Cambria, and Rada Mihalcea. 2019. Meld: A multimodal multi-party dataset for emotion recognition in conversations. In *Proceedings of the 57th annual meeting of the association for computational linguistics*, pages 527–536.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. 2021. Learning transferable visual models from natural language supervision. *Preprint*, arXiv:2103.00020.

Andrew Rosenberg and Julia Hirschberg. 2007. V-measure: A conditional entropy-based external cluster evaluation measure. In *Proceedings of the 2007 Joint Conference on Empirical Methods in Natural Language Processing and Computational Natural Language Learning (EMNLP-CoNLL)*, pages 410–420, Prague, Czech Republic. Association for Computational Linguistics.

Lucas Smaira, Joao Carreira, Eric Noland, Ellen Clancy, Amy Wu, and Andrew Zisserman. 2020. A short note on the kinetics-700-2020 human action dataset. *arXiv preprint arXiv:2010.10864*.

Khurram Soomro, Amir Roshan Zamir, and Mubarak Shah. 2012. Ucf101: A dataset of 101 human actions classes from videos in the wild. *Preprint*, arXiv:1212.0402.

Yapeng Tian, Jing Shi, Bochen Li, Zhiyao Duan, and Chenliang Xu. 2018a. Audio-visual event localization in unconstrained videos. In *Proceedings of the European conference on computer vision (ECCV)*, pages 247–263.

Yapeng Tian, Jing Shi, Bochen Li, Zhiyao Duan, and Chenliang Xu. 2018b. Audio-visual event localization in unconstrained videos. In *The European Conference on Computer Vision (ECCV)*.

Zhan Tong, Yibing Song, Jue Wang, and Limin Wang. 2022. Videomae: Masked autoencoders are data-efficient learners for self-supervised video pretraining. *Preprint*, arXiv:2203.12602. NeurIPS 2022.

Issar Tzachor, Dvir Samuel, and Rami Ben-Ari. 2026. Vidvec: Unlocking video mllm embeddings for video-text retrieval. *Preprint*, arXiv:2602.08099.

Apoorv Vyas, Heng-Jui Chang, Cheng-Fu Yang, Po-Yao Huang, Luya Gao, Julius Richter, Sanyuan Chen, Matt Le, Piotr Dollár, Christoph Feichtenhofer, Ann Lee, and Wei-Ning Hsu. 2025. Pushing the frontier of audiovisual perception with large-scale multimodal correspondence learning. *Preprint*, arXiv:2512.19687.

Xin Wang, Jiawei Wu, Junkun Chen, Lei Li, Yuan-Fang Wang, and William Yang Wang. 2019. Vatex: A large-scale, high-quality multilingual dataset for video-and-language research. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*.

Yi Wang, Kunchang Li, Yizhuo Li, Yinan He, Bingkun Huang, Zhiyu Zhao, Hongjie Zhang, Jilan Xu, Yi Liu, Zun Wang, Sen Xing, Guo Chen, Junting Pan, Jiashuo Yu, Yali Wang, Limin Wang, and Yu Qiao. 2022. Internvideo: General video foundation models via generative and discriminative learning. *Preprint*, arXiv:2212.03191.

Chenghao Xiao, Hou Pong Chan, Hao Zhang, Weiwen Xu, Mahani Aljunied, and Yu Rong. 2025a. Scaling language-centric omnimodal representation learning. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*.

Chenghao Xiao, Isaac Chung, Imene Kerboua, Jamie Stirling, Xin Zhang, Márton Kardos, Roman Solomatin, Noura Al Moubayed, Kenneth Enevoldsen, and Niklas Muennighoff. 2025b. Mieb: Massive image embedding benchmark. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 22187–22198.

Junbin Xiao, Xindi Shang, Angela Yao, and Tat-Seng Chua. 2021. Next-qa: Next phase of question-answering to explaining temporal actions. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9777–9786.

Jin Xu, Zhifang Guo, Jinzheng He, Hangrui Hu, Ting He, Shuai Bai, Keqin Chen, Jialin Wang, Yang Fan, Kai Dang, Bin Zhang, Xiong Wang, Yunfei Chu, and Junyang Lin. 2025a. Qwen2.5-omni technical report. *Preprint*, arXiv:2503.20215.

Jin Xu, Zhifang Guo, Hangrui Hu, Yunfei Chu, Xiong Wang, Jinzheng He, Yuxuan Wang, Xian Shi, Ting He, Xinfa Zhu, Yuanjun Lv, Yongqi Wang, Dake Guo, He Wang, Linhan Ma, Pei Zhang, Xinyu Zhang, Hongkun Hao, Zishan Guo, and 19 others. 2025b. Qwen3-omni technical report. *Preprint*, arXiv:2509.17765.

Jun Xu, Tao Mei, Ting Yao, and Yong Rui. 2016. Msr-vtt: A large video description dataset for bridging video and language. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

Mengyao Xu, Wenfei Zhou, Yauhen Babakhin, Gabriel Moreira, Ronay Ak, Radek Osmulski, Bo Liu, Even

Oldridge, and Benedikt Schifferer. 2025c. Omni-embed-nemotron: A unified multimodal retrieval model for text, image, audio, and video. *arXiv preprint arXiv:2510.03458*.

Pinci Yang, Xin Wang, Xuguang Duan, Hong Chen, Runze Hou, Cong Jin, and Wenwu Zhu. 2022. Avqa: A dataset for audio-visual question answering on videos. In *Proceedings of the 30th ACM International Conference on Multimedia*.

Hanrong Ye, Chao-Han Huck Yang, Arushi Goel, Wei Huang, Ligeng Zhu, Yuanhang Su, Sean Lin, An-Chieh Cheng, Zhen Wan, Jinchuan Tian, and 1 others. 2025. Omnivinci: Enhancing architecture and data for omni-modal understanding llm. *arXiv preprint arXiv:2510.15870*.

Jianrui Zhang, Mu Cai, and Yong Jae Lee. 2024a. Vinoground: Scrutinizing lmms over dense temporal reasoning with short videos. *arXiv preprint arXiv:2410.02763*.

Yuanhan Zhang, Kaichen Zhang, Bo Li, Fanyi Pu, Christopher Arif Setiadharma, Jingkang Yang, and Ziwei Liu. 2024b. Worldqa: Multimodal world knowledge in videos through long-chain reasoning. *arXiv preprint arXiv:2405.03272*.

Luowei Zhou, Chenliang Xu, and Jason J. Corso. 2018. Towards automatic learning of procedures from web instructional videos. In *Proceedings of the AAAI Conference on Artificial Intelligence*.

Ziwei Zhou, Rui Wang, Zuxuan Wu, and Yu-Gang Jiang. 2025. Daily-omni: Towards audio-visual reasoning with temporal alignment across modalities. *arXiv preprint arXiv:2505.17862*.

Bin Zhu, Bin Lin, Munan Ning, Yang Yan, Jiaxi Cui, HongFa Wang, Yatian Pang, Wenhao Jiang, Junwu Zhang, Zongwei Li, Wancai Zhang, Zhifeng Li, Wei Liu, and Li Yuan. 2024. Languagebind: Extending video-language pretraining to n-modality by language-based semantic alignment. *Preprint*, arXiv:2310.01852. ICLR 2024.

A Tasks overview

This appendix provides detailed information on all tasks within MVEB, including size, language, metrics, and other relevant details in Table 5, Table 6, Table 7, and Table 8.

A.1 Audio–video annotation provenance

When a source video carries an audio track, MVEB pairs it into both a video-only (v) and a video+audio (va) task variant; §5.1 measures the per-task audio delta $\Delta = \text{score}_{va} - \text{score}_v$ from those paired evaluations. To interpret that Δ, we classify each source dataset by what modalities its annotators worked from. **AV-grounded**

Dataset	Citation	MVEB	TV	V	N.samples	Total Duration(s)	N.Langs	Domains	Main metric
Video Classification									
AVEDatasetVideoClassification	(Tian et al., 2018a)				402	1h (4,026s)	1	Web, AudioScene	accuracy
AVMemeVideoClassification	(Jiang et al., 2026b)		✓	✓	900	3h (11,010s)	16	Web, Entertainment, Music	accuracy
BreakfastClassification	(Kuehne et al., 2014)	✓	✓	✓	433	17h (62,706s)	1	Scene	accuracy
Diving48Classification.V2	(Li et al., 2018)				1,970	2h (8,621s)	1	Sport	accuracy
HMDB51Classification	(Kuehne et al., 2011a)			✓	1,530	1h (4,833s)	1	Scene	accuracy
HumanAnimalCartoonV	(Dong et al., 2023)				644	1h (5,118s)	1	Web, Scene	accuracy
Kinetics400V	(Kay et al., 2017)				3,995	10h (38,195s)	1	Web, Scene	accuracy
Kinetics600V	(Carreira et al., 2018)			✓	9,576	1d (92,401s)	1	Web, Scene	accuracy
Kinetics700V	(Smaira et al., 2020)		✓		11,190	1d (108,857s)	1	Web, Scene	accuracy
MELDVideoClassification	(Poria et al., 2019)			✓	2,048	1h (7,134s)	1	Entertainment	accuracy
MusicAVQACLSVideoClassification	(Li et al., 2022)				1,706	1d (101,285s)	1	Music	accuracy
RAVDESSVClassification	(Livingstone and Russo, 2018)				1,440	1h (5,312s)	1	Spoken	accuracy
SomethingSomethingV2Classification	(Goyal et al., 2017)				5,444	6h (22,173s)	1	Scene	accuracy
UCF101VideoClassification	(Soomro et al., 2012)				1,944	3h (13,304s)	1	Web, Scene	accuracy
VGGSoundV	(Chen et al., 2020)		✓		9,888	1d (98,459s)	1	Web	accuracy
WorldSenseVideoClassification	(Hong et al., 2025)			✓	1,047	13h (50,231s)	1	Scene, AudioScene, Music, Entertainment	accuracy
Video Clustering									
AVEDatasetVideoClustering	(Tian et al., 2018b)				402	1h (4,026s)	1	Spoken, Scene, Music	v_measure
HMDB51Clustering	(Kuehne et al., 2011b)				1,530	1h (4,833s)	1	Scene	v_measure
MELDEmotionVideoClustering	(Poria et al., 2019)				1,354	1h (4,980s)	1	Entertainment	v_measure
MELDSpeakerVideoClustering	(Poria et al., 2019)				2,610	2h (8,844s)	1	Entertainment	v_measure
MusicAVQACLSVideoClustering	(Li et al., 2022)				1,706	1d (101,285s)	1	Music	v_measure
RAVDESSVideoClustering	(Livingstone and Russo, 2018)		✓		1,440	1h (5,312s)	1	Spoken	v_measure
UCF101VideoClustering	(Soomro et al., 2012)				1,944	3h (13,304s)	1	Web, Scene	v_measure
WorldSense1MinDomainVideoClustering	(Hong et al., 2025)				568	7h (27,808s)	1	Scene, Web, Entertainment	v_measure
Video Pair Classification									
AVEDatasetVPairClassification	(Tian et al., 2018a)				804	4h (16,104s)	1	Web, AudioScene	max_ap
AVSpeakerBenchPairClassification	(Nguyen et al., 2025)				2,048	15h (56,521s)	1	Spoken	max_ap
HumanAnimalCartoonVPairClassification	(Dong et al., 2023)		✓	✓	1,288	5h (20,445s)	1	Web, Scene	max_ap
MELDVPairClassification	(Poria et al., 2019)				2,048	3h (14,093s)	1	Entertainment	max_ap
MusicAVQAVPairClassification	(Li et al., 2022)			✓	2,048	2d (243,133s)	1	Music	max_ap
RAVDESSAVVPairClassification	(Livingstone and Russo, 2018)			✓	2,048	4h (15,096s)	1	Spoken	max_ap
VinogroundPairClassification	(Zhang et al., 2024a)				2,000	9h (33,330s)	1	Scene	max_ap

Table 5: Video-only tasks in MVEB. All tasks use video modality exclusively.

datasets had labels produced from both audio and visual content (audio-visual event labels, dialogue-emotion labels, music QA, multimodal exam-style questions, audio-visual captions). **V-grounded** datasets had labels produced from visuals alone, even though the source clips may carry audio (action-recognition splits, frame-conditioned captioning). In both cases the source clips still have audio that we feed to the model in the va variant; the provenance distinction is about the labels, not the clips. Table 9 lists the families in each group, and §5.1 reports that the provenance predicts whether audio helps a model on a dataset: it helps on AV-grounded and hurts on V-grounded.

B Dataset Construction

This appendix provides a brief description of each dataset contributed to MVEB by this work, including the source data, the sampling and filtering applied for our benchmark, and the upstream release used to obtain the raw clips. Datasets are grouped by primary task type; a single dataset may be used in multiple task formats (e.g. classification, zero-shot classification, and clustering all draw on the same underlying clips). The processed datasets described here are publicly released to support reproducible evaluation.

B.1 Video Classification

AVE-Dataset (Tian et al., 2018a) is an audio-visual event localization dataset of approximately 4K YouTube clips spanning 28 audio-visual event categories, with each clip approximately 10 seconds long. Used the official train and test splits across 28 audio-visual event classes (∼3,312 train / ∼402 test). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the AVE official release.

AVMeme Exam (Jiang et al., 2026b) is a multilingual, multicultural multi-modal benchmark of internet memes whose questions probe cultural and contextual reasoning. Used the full/test split (∼900 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the upstream HF mirror.

Breakfast (Kuehne et al., 2014) is a cooking activity dataset of approximately 1.9K crowdsourced videos covering 10 breakfast preparation activities, filmed from multiple camera viewpoints. Used only camera-01 clips, capped at 50 per class across 10 meal classes (∼433 test). The raw video data are retrieved from the Breakfast Actions official release.

Human-Animal-Cartoon (HAC) (Dong et al., 2023) is a domain-generalization dataset spanning human, animal, and cartoon clips of 7 shared action

Dataset	Citation	MVEB	TV	N.samples	Total Duration(s)	N.Langs	Domains	Main metric
Video Zero-shot Classification								
AVEDatasetVideoZeroShot	(Tian et al., 2018a)			402	1h (4,026s)	1	Web, AudioScene	accuracy
AVMemeVideoZeroShot	(Jiang et al., 2026b)			900	3h (11,010s)	16	Web, Entertainment, Music	accuracy
BreakfastZeroShot	(Kuehne et al., 2014)			433	17h (62,710s)	1	Scene	accuracy
HMDB51ZeroShot	(Kuehne et al., 2011a)	✓		1,530	1h (4,833s)	1	Scene	accuracy
HumanAnimalCartoonZeroShot	(Dong et al., 2023)			644	1h (5,118s)	1	Web, Scene	accuracy
Kinetics400ZeroShot	(Kay et al., 2017)		✓	3,995	10h (38,195s)	1	Web, Scene	accuracy
Kinetics600VZeroShot	(Carreira et al., 2018)			9,576	1d (92,401s)	1	Web, Scene	accuracy
Kinetics700VZeroShot	(Smaira et al., 2020)			11,190	1d (108,857s)	1	Web, Scene	accuracy
MELDVideoZeroShot	(Poria et al., 2019)		✓	2,048	1h (7,134s)	1	Entertainment	accuracy
MusicAVQACLSVideoZeroShot	(Li et al., 2022)			1,706	1d (101,285s)	1	Music	accuracy
RAVDESSVZeroShot	(Livingstone and Russo, 2018)			1,440	1h (5,312s)	1	Spoken	accuracy
UCF101VideoZeroShotClassification	(Soomro et al., 2012)		✓	1,944	3h (13,304s)	1	Web, Scene	accuracy
VGGSoundVideoZeroshot	(Chen et al., 2020)			9,888	1d (98,459s)	1	Web	accuracy
WorldSenseVideoZeroShot	(Hong et al., 2025)		✓	1,047	13h (50,231s)	1	Scene, AudioScene, Music, Entertainment	accuracy
Video Pair Classification								
VideoConPairClassification	(Bansal et al., 2023)			1,138	11h (42,348s)	1	Scene	max_ap
Video-Centric QA								
AVMemeExamVideoCentricQA	(Jiang et al., 2026b)			4,612	3h (11,010s)	1	Web	accuracy
AVQAVideoCentricQA	(Yang et al., 2022)			4,605	2h (9,184s)	1	Web	accuracy
AVSpeakerBenchVideoCentricQA	(Nguyen et al., 2024)			16,060	12h (46,068s)	1	Web	accuracy
DailyOmniVideoCentricQA	(Zhou et al., 2025)			5,980	14h (51,726s)	1	Web	accuracy
EgoSchemaVideoCentricQA	(Mangalam et al., 2023)	✓		3,000	1d (90,000s)	1	Web	accuracy
NExTQAVideoCentricQA	(Xiao et al., 2021)			5,958	10h (39,190s)	1	Web	accuracy
OmniVideoBenchVideoCentricQA	(Li et al., 2025)		✓	2,545	18h (66,152s)	1	Web	accuracy
PerceptionTestVideoCentricQA	(Patraucean et al., 2023)			3,752	5h (19,843s)	1	Web	accuracy
VideoMMEShortVideoCentricQA	(Fu et al., 2024)			4,500	20h (72,599s)	1	Web	accuracy
WorldQAVideoCentricQA	(Zhang et al., 2024b)			16,372	3d (313,887s)	1	Web	accuracy
WorldSense1MinVideoCentricQA	(Hong et al., 2025)			5,165	13h (50,231s)	1	Web	accuracy
Video Retrieval								
AVMemeExamT2VRetrieval	(Jiang et al., 2026a)		✓	1,800	3h (11,010s)	1	Web, Social	ndcg_at_10
AVMemeExamV2TRetrieval	(Jiang et al., 2026a)			1,800	3h (11,010s)	1	Web, Social	ndcg_at_10
ActivityNetCaptionsT2VRetrieval	(Krishna et al., 2017)	✓	✓	9,768	6d (579,288s)	1	Web, Spoken	ndcg_at_10
ActivityNetCaptionsV2TRetrieval	(Krishna et al., 2017)			9,768	6d (579,288s)	1	Web, Spoken	ndcg_at_10
AudioCapsAVT2VRetrieval	(Kim et al., 2019)		✓	1,330	1h (6,541s)	1	Encyclopaedic, Web	ndcg_at_10
AudioCapsAVV2TRetrieval	(Kim et al., 2019)			1,330	1h (6,541s)	1	Encyclopaedic, Web	ndcg_at_10
DiDeMoT2VRetrieval	(Hendricks et al., 2017)			1,998	13h (50,032s)	1	Web, Spoken	ndcg_at_10
DiDeMoV2TRetrieval	(Hendricks et al., 2017)		✓	1,998	13h (50,032s)	1	Web, Spoken	ndcg_at_10
MSRVTTT2V	(Xu et al., 2016)			1,758	3h (13,369s)	1	Unknown	ndcg_at_10
MSRVTTV2T	(Xu et al., 2016)			1,758	3h (13,369s)	1	Unknown	ndcg_at_10
MSVDT2VRetrieval	(Chen and Dolan, 2011)	✓		1,320	1h (6,642s)	1	Web, Spoken	ndcg_at_10
MSVDV2TRetrieval	(Chen and Dolan, 2011)		✓	1,320	1h (6,642s)	1	Web, Spoken	ndcg_at_10
Panda70MT2VRetrieval	(Chen et al., 2024)		✓	6,790	10h (37,488s)	1	Web, Spoken	ndcg_at_10
Panda70MV2TRetrieval	(Chen et al., 2024)			6,790	10h (37,488s)	1	Web, Spoken	ndcg_at_10
Shot2Story20KT2VRetrieval	(Han et al., 2023)			8,046	18h (67,101s)	1	Web, Spoken	ndcg_at_10
Shot2Story20KV2TRetrieval	(Han et al., 2023)			8,046	18h (67,101s)	1	Web, Spoken	ndcg_at_10
TUNABenchT2VRetrieval	(Kong et al., 2025)			2,000	3h (14,248s)	1	Web, Spoken	ndcg_at_10
TUNABenchV2TRetrieval	(Kong et al., 2025)			2,000	3h (14,248s)	1	Web, Spoken	ndcg_at_10
VALOR32KT2VRetrieval	(Chen et al., 2023)		✓	6,982	9h (34,636s)	1	Web, Spoken	ndcg_at_10
VALOR32KV2TRetrieval	(Chen et al., 2023)			6,982	9h (34,636s)	1	Web, Spoken	ndcg_at_10
VATEXT2VRetrieval	(Wang et al., 2019)		✓	2,000	1d (157,615s)	1	Web, Spoken	ndcg_at_10
VATEXV2TRetrieval	(Wang et al., 2019)			2,000	1d (157,615s)	1	Web, Spoken	ndcg_at_10
VGGSoundAVT2VRetrieval	(Chen et al., 2020)			1,392	1h (6,952s)	1	Web, Spoken	ndcg_at_10
VGGSoundAVV2TRetrieval	(Chen et al., 2020)			1,392	1h (6,952s)	1	Web, Spoken	ndcg_at_10
YouCook2T2VRetrieval	(Zhou et al., 2018)			6,208	17h (61,878s)	1	Web, Spoken	ndcg_at_10
YouCook2V2TRetrieval	(Zhou et al., 2018)			6,208	17h (61,878s)	1	Web, Spoken	ndcg_at_10

Table 6: Video-text multimodal tasks in MVEB. Tasks use both video and text modalities.

categories. Concatenated the three HAC test-only domain CSVs, capped at 32 per class across 7 action classes (∼644 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the HAC official release.

HMDB51 (Kuehne et al., 2011a) is a video dataset for human motion recognition containing approximately 6K clips from movies and online sources, organized into 51 action categories such as catch, drink, kick, and walk. We used the official train/test split 1 across all 51 action classes, yielding ∼3,570 train and ∼1,530 test clips. The raw video data are retrieved from the Brown serre-lab official release.

Kinetics-400 (Kay et al., 2017) is a large-scale action recognition dataset of approximately 300K YouTube clips spanning 400 human action classes such as cooking, sports, and dance. Each clip is approximately 10 seconds long. We sampled 25 random shard files from each of the official train and test path lists and capped at 10 examples per class per split, yielding ∼3,970 train and ∼4,000 test clips. We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the CVD Foundation Kinetics downloader.

Kinetics-600 (Carreira et al., 2018) extends Kinetics-400 to 600 action classes with an expanded YouTube video pool. We sampled the official test split capped at approximately 16 examples per class, yielding ∼9,576 clips. We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the CVD Foundation Kinetics downloader.

Dataset	Citation	MVEB	N.samples	Total Duration(s)	N.Langs	Domains	Main metric
Video Classification							
AVEDatasetClassification	(Tian et al., 2018a)	✓	402	1h (4,026s)	1	Web, AudioScene	accuracy
AVMemeAudioVideoClassification	(Jiang et al., 2026b)	✓	900	3h (11,010s)	16	Web, Entertainment, Music	accuracy
HumanAnimalCartoonVA	(Dong et al., 2023)		644	1h (5,118s)	1	Web, Scene	accuracy
Kinetics400VA	(Kay et al., 2017)		3,995	10h (38,195s)	1	Web, Scene	accuracy
Kinetics600VA	(Carreira et al., 2018)		9,576	1d (92,401s)	1	Web, Scene	accuracy
Kinetics700VA	(Smaira et al., 2020)	✓	11,190	1d (108,857s)	1	Web, Scene	accuracy
MELDAudioVideoClassification	(Poria et al., 2019)		2,048	1h (7,134s)	1	Entertainment	accuracy
MusicAVQACLSAudioVideoClassification	(Li et al., 2022)		1,706	1d (101,285s)	1	Music	accuracy
RAVDESSAVClassification	(Livingstone and Russo, 2018)	✓	1,440	1h (5,312s)	1	Spoken	accuracy
UCF101VideoAudioClassification	(Soomro et al., 2012)	✓	1,944	3h (13,304s)	1	Web, Scene	accuracy
VGGSoundVA	(Chen et al., 2020)		9,888	1d (98,459s)	1	Web	accuracy
WorldSenseAudioVideoClassification	(Hong et al., 2025)		1,047	13h (50,231s)	1	Scene, AudioScene, Music, Entertainment	accuracy
Video Clustering							
AVEDatasetAudioVideoClustering	(Tian et al., 2018b)		402	1h (4,026s)	1	Spoken, Scene, Music	v_measure
MELDEmotionAudioVideoClustering	(Poria et al., 2019)	✓	1,354	1h (4,980s)	1	Entertainment	v_measure
MELDSpeakerAudioVideoClustering	(Poria et al., 2019)		2,610	2h (8,844s)	1	Entertainment	v_measure
MusicAVQACLSAudioVideoClustering	(Li et al., 2022)	✓	1,706	1d (101,285s)	1	Music	v_measure
RAVDESSAVClustering	(Livingstone and Russo, 2018)		1,440	1h (5,312s)	1	Spoken	v_measure
UCF101AudioVideoClustering	(Soomro et al., 2012)		1,944	3h (13,304s)	1	Web, Scene	v_measure
WorldSense1MinDomainAudioVideoClustering	(Hong et al., 2025)		568	7h (27,808s)	1	Scene, Web, Entertainment	v_measure
Video Zero-shot Classification							
AVEDatasetZeroShot	(Tian et al., 2018a)		402	1h (4,026s)	1	Web, AudioScene	accuracy
AVMemeAudioVideoZeroShot	(Jiang et al., 2026b)		900	3h (11,010s)	16	Web, Entertainment, Music	accuracy
HumanAnimalCartoonVAZeroShot	(Dong et al., 2023)		644	1h (5,118s)	1	Web, Scene	accuracy
Kinetics400VAZeroShot	(Kay et al., 2017)		3,995	10h (38,195s)	1	Web, Scene	accuracy
Kinetics600VAZeroShot	(Carreira et al., 2018)		9,576	1d (92,401s)	1	Web, Scene	accuracy
Kinetics700VAZeroShot	(Smaira et al., 2020)		11,190	1d (108,857s)	1	Web, Scene	accuracy
MELDAudioVideoZeroShot	(Poria et al., 2019)		2,048	1h (7,134s)	1	Entertainment	accuracy
MusicAVQACLSAudioVideoZeroShot	(Li et al., 2022)		1,706	1d (101,285s)	1	Music	accuracy
RAVDESSAVZeroShot	(Livingstone and Russo, 2018)		1,440	1h (5,312s)	1	Spoken	accuracy
UCF101VideoAudioZeroShotClassification	(Soomro et al., 2012)		1,944	3h (13,304s)	1	Web, Scene	accuracy
VGGSoundVideoAudioZeroshot	(Chen et al., 2020)		9,888	1d (98,459s)	1	Web	accuracy
WorldSenseAudioVideoZeroShot	(Hong et al., 2025)	✓	1,047	13h (50,231s)	1	Scene, AudioScene, Music, Entertainment	accuracy
Video Pair Classification							
AVEDatasetVAPairClassification	(Tian et al., 2018a)		804	4h (16,104s)	1	Web, AudioScene	max_ap
HumanAnimalCartoonVAPairClassification	(Dong et al., 2023)	✓	1,288	5h (20,445s)	1	Web, Scene	max_ap
MELDVAPairClassification	(Poria et al., 2019)		2,048	3h (14,093s)	1	Entertainment	max_ap
MusicAVQAVAPairClassification	(Li et al., 2022)	✓	2,048	2d (243,133s)	1	Music	max_ap
RAVDESSAVVAPairClassification	(Livingstone and Russo, 2018)		2,048	4h (15,096s)	1	Spoken	max_ap
Video-Centric QA							
AVMemeExamVideoAudioCentricQA	(Jiang et al., 2026b)		4,612	3h (11,010s)	1	Web	accuracy
AVQAVideoAudioCentricQA	(Yang et al., 2022)		4,605	2h (9,184s)	1	Web	accuracy
AVSpeakerBenchVideoAudioCentricQA	(Nguyen et al., 2024)		16,060	12h (46,068s)	1	Web	accuracy
DailyOmniVideoAudioCentricQA	(Zhou et al., 2025)		5,980	14h (51,726s)	1	Web	accuracy
OmniVideoBenchVideoAudioCentricQA	(Li et al., 2025)		2,545	18h (66,152s)	1	Web	accuracy
PerceptionTestVideoAudioCentricQA	(Patraucean et al., 2023)		3,752	5h (19,843s)	1	Web	accuracy
VideoMMEShortVideoAudioCentricQA	(Fu et al., 2024)		4,500	20h (72,599s)	1	Web	accuracy
WorldQAVideoAudioCentricQA	(Zhang et al., 2024b)		16,372	3d (313,887s)	1	Web	accuracy
WorldSense1MinVideoAudioCentricQA	(Hong et al., 2025)		5,165	13h (50,231s)	1	Web	accuracy

Table 7: Video-audio(-text) multimodal tasks in MVEB (non-retrieval). Tasks use video with audio and optionally text.

Kinetics-700-2020 (Smaira et al., 2020) is the 2020 release of Kinetics-700 with 700 action classes and refreshed annotations. We sampled the official test split capped at approximately 16 examples per class, yielding ∼11,190 clips. We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the CVD Foundation Kinetics downloader.

MELD (Poria et al., 2019) is a multi-party conversation dataset drawn from the TV show *Friends*, with utterances annotated with emotion and sentiment labels. Sampled the test split (∼2,610 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the MELD official release.

MUSIC-AVQA (Li et al., 2022) is an audio-visual question-answering dataset over musical instrument performances. Filtered the test split to rows whose answer is one of the 22 instrument-vocabulary labels (∼1,706 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the MUSIC-AVQA official release.

RAVDESS (Livingstone and Russo, 2018) is a dataset of emotional acted speech and song recordings by 24 professional actors; we use the 1,440-clip speech audio-visual subset covering 8 emotion categories. Used the metadata train split (the only split RAVDESS exposes) remapped to its audio-visual "01-" filenames (∼1,440 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the RAVDESS Zenodo release.

Something-Something v2 (Goyal et al., 2017) is a dataset of approximately 220K crowdsourced clips showing fine-grained physical interactions be-

tween humans and objects, with 174 action classes. Used the official validation as test, capped at 32 per class across 174 classes (~5,444 examples). The raw video data are retrieved from the Qualcomm SSv2 release.

UCF101-51VA (Soomro et al., 2012) is an action recognition dataset of approximately 13K YouTube videos across 101 action categories. We restricted to a 51-class audio-bearing subset (the "51VA" partition) and used the official train/test split 1, yielding ~4,890 train and ~1,944 test clips. We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the CRCV UCF official release.

VGGSound (Chen et al., 2020) is a large-scale audio-visual dataset of approximately 200K YouTube clips with sound-event class labels. Filtered the test split, capped at 32 per class across 309 classes (~9,888 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the VGGSound official release.

WorldSense (Hong et al., 2025) is a multi-modal video understanding benchmark spanning multiple domains and durations, with a short-clip subset used here. Filtered the test split to short (<1 min) clips (~1,047 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the WorldSense official release.

B.2 Video-Centric QA

AVMeme Exam (Jiang et al., 2026b) is a multilingual, multicultural multi-modal benchmark of internet memes whose questions probe cultural and contextual reasoning. Same data as the classification variant (~900 examples), evaluated as multiple-choice retrieval over the candidate set. We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the upstream HF mirror.

AVQA (Yang et al., 2022) is an audio-visual multiple-choice question answering benchmark. Used the test QA split keyed by (video, question) since one clip can carry multiple questions (~921 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the upstream AVQA HF mirror.

Daily-Omni (Zhou et al., 2025) is a multi-modal

QA benchmark over everyday-life videos. Used the upstream evaluation split keyed by (video, question) (~1,200 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the Daily-Omni HF mirror.

EgoSchema (Mangalam et al., 2023) is an ego-centric (first-person) long-form video question-answering benchmark. Used the Subset config test split (500 examples). The raw video data are retrieved from the EgoSchema official release.

NExT-QA (Xiao et al., 2021) is a video question answering benchmark focused on causal and temporal reasoning over untrimmed daily-activity videos, supporting both multiple-choice and open-ended QA. We use the multiple-choice portion: we sampled the test split, yielding ~993 examples. We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the upstream HF mirror.

OmniVideoBench (Li et al., 2025) is a video QA benchmark spanning a range of clip durations and content types. Filtered the test split to clips under 5 minutes (~509 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the OmniVideoBench HF mirror.

Perception Test (Patraucean et al., 2023) is a multi-modal benchmark probing perception and reasoning over diverse video clips. Used the mc_question_val validation split (~938 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the Perception Test HF mirror.

Video-MME (short) (Fu et al., 2024) is a comprehensive video-MLLM benchmark with multi-domain clips at three duration buckets. Filtered the test split to duration == "short" clips, deterministically shuffled (seed=42), capped at 2,000 (~900 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the Video-MME HF mirror.

WorldQA (Zhang et al., 2024b) is a long-horizon video QA benchmark drawn from real-world activities. Used the MC config test split keyed by (video, question_idx) (~3,284 examples). We extracted 16 kHz mono audio via ffmpeg from

each clip, dropping clips where extraction failed. The raw video data are retrieved from the WorldQA HF mirror.

WorldSense (VCQA) (Hong et al., 2025) is a multi-modal video understanding benchmark spanning multiple domains and durations. Same data as the WorldSense classification variant, evaluated as multiple-choice retrieval (∼1,047 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the WorldSense official release.

B.3 Video Retrieval

ActivityNet Captions (Krishna et al., 2017) is a dense video captioning dataset of approximately 20K untrimmed videos with temporally-localized natural-language captions. Used the upstream `val2` split as the test split (∼4,884 examples). The raw video data are retrieved from the ActivityNet Captions official release.

AudioCaps-AV (Kim et al., 2019) is a dataset of approximately 46K 10-second YouTube clips with human-written audio captions, derived from AudioSet. Sampled the test split (∼665 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the upstream HF AudioCaps mirror joined with a Kaggle video archive.

DiDeMo (Hendricks et al., 2017) is a video moment localization dataset with natural-language descriptions of short temporally-grounded events. Used the test split (∼999 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the DiDeMo official release.

MSR-VTT (Xu et al., 2016) is a video description dataset containing 10K video clips and 200K human-written captions covering 20 categories. We used the standard 1,000-clip retrieval test split (`msrvtt_ret_test1k`), yielding 879 final clips after filtering. We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from a Kaggle mirror of the official MSR-VTT test partition.

MSVD (Chen and Dolan, 2011) is a dataset of approximately 2K short YouTube clips with multiple paraphrased English captions per clip. Used the test split with the first caption per clip (∼660

examples). The raw video data are retrieved from the UT Austin YouTubeClips release.

PANDA-70M (Chen et al., 2024) is a large-scale collection of YouTube clips paired with dense automatic captions. Sampled the test split (∼3,395 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the PANDA-70M official release.

Shot2Story-20K (Han et al., 2023) is a dataset of approximately 20K multi-shot videos paired with shot-level captions, narration captions, and multi-shot video summaries. Used the test split (∼4,023 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the Shot2Story-20K official release.

TUNA-Bench (Kong et al., 2025) is a dense fine-grained temporal video captioning benchmark. Used the `TUNA-1K` config test split (∼1,000 examples). The raw video data are retrieved from the TUNA-Bench HF mirror.

VALOR-32K (Chen et al., 2023) is a dataset of 32K paired audio-visual-language samples for cross-modal alignment. Used the official `desc_test.json` test split (∼3,491 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the VALOR-32K official release.

VATEX (Wang et al., 2019) is a multilingual video captioning dataset of approximately 41K video clips drawn from Kinetics, paired with 10 captions each in English and Chinese. Used the `vatex_test` config with the first English caption per clip, capped at 1,000 (∼1,000 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the VATEX official release.

VGGSound-AV Retrieval (Chen et al., 2020) is a text-annotated extension of VGGSound that pairs each clip with separate visual and audio captions, repurposed here for audio-visual retrieval evaluation. Used the VGGSound-T2AV test split (∼696 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the VGGSound official release.

YouCook2 (Zhou et al., 2018) is a dataset of approximately 2K untrimmed instructional cooking videos with temporally-localized step-level annota-

tions. Used the official validation annotations cut into recipe-step segments (3,104 examples). We extracted 16 kHz mono audio via ffmpeg from each clip, dropping clips where extraction failed. The raw video data are retrieved from the YouCook2 official release.

C Overview of Models

All models used in the evaluations are listed in Table 10.

D Per-Task Results

This appendix reports raw per-task scores for every model on every MVEB task. Each cell is the `main_score` as defined by the upstream `mteb` task (nDCG@10 for retrieval, accuracy for classification and zero-shot, v-measure for clustering, max-AP for pair classification, accuracy for question answering), scaled to 0–100. **Bold** = best per column within a table. A – cell means the task variant is incompatible with the model's input modalities (for example, an `audio + video` variant on a model without an audio encoder such as X-CLIP or V-JEPA-2, or any retrieval direction with audio in the query/target for a text-video model). Models with no scores at all on a given task family are hidden from that family's table; the full roster is in Table 10. Tables are auto-generated from `results/results/<model>/<rev>/*.json`; do not edit by hand.

D.1 Modality-restricted leaderboards

Two modality-restricted leaderboards accompany MVEB for models that cannot accept the full input surface: `MVEB(text, video)` for models without an audio encoder and `MVEB(video)` for video-only encoders. Each table lists only the models compatible with that input surface, ranked among themselves; these are not parallel benchmarks to MVEB but accommodations for restricted modality coverage.

D.2 MVEB+ aggregate

Table 13 reports the aggregate over the full MVEB+ pool (all 184 tasks). MVEB is a correlation-preserving subset of MVEB+ (Pearson r=0.996, Spearman ρ=0.944 between the two; section 3). This aggregate is included as a transparency artifact, showing that the 23-task MVEB does not distort relative model performance versus running every task in the pool; it is not framed as a separate leaderboard.

D.3 Retrieval

One table per query/target direction. Two patterns are consistent across the eight directions. (1) On purely text↔video directions (T→V, V→T), Qwen3-VL-Embedding-8B leads at 75.8 and 72.6 nDCG@10 respectively, ahead of eBind, the Perception Encoder audio-visual family, and the omni MLLM-embed models; the smaller Qwen3-VL-Embedding-2B comes in second on T→V. (2) On audio-conditioned directions (A→V, AT→V, V→A, VT→A, VA→T, T→VA), Qwen3-VL is unable to participate (no audio path) and the audio-capable families share the lead: LCO-Embedding-Omni-7B wins V→A (44.5), VT→A (53.8), VA→T (64.5), and T→VA (64.7); pe-av-large wins A→V (52.8); eBind wins AT→V (74.8). Generative MLLMs (Qwen2.5-Omni) score near zero on every retrieval direction, including text→video; embedding-specific training is essential for retrieval.

D.4 Classification

LCO-Embedding-Omni-7B leads on the classification family average (57.4), with BidirLM-Omni-2.5B (56.9) and Qwen3-VL-Embedding-8B (56.8) close behind; BidirLM wins many individual audio+video columns despite ranking ninth on the headline MVEB leaderboard, and Qwen3-VL-Embedding-8B is the strongest text-video classifier (top on HumAnimCartoon-video, Breakfast, HMDB51). X-CLIP-large-patch14 remains the strongest video-only-input model on the Kinetics family and UCF101 (e.g. 83.3 on Kinetics-400, 76.6 on Kinetics-600, 96.1 on UCF101), reflecting Kinetics-supervised pretraining transferring cleanly to evaluation on the same dataset family (which we audit as in-distribution in Appendix E). For audio+video variants the MLLM-embed family is uniformly stronger because the X-CLIP, V-JEPA-2, and Qwen3-VL models cannot consume the audio channel; the audio+video columns are blank for those families. Audio rarely degrades performance for omni models: on Kinetics-700, MELD, and RAVDESS the audio+video score is within a few points of the video-only score for most models.

D.5 Zero-Shot Classification

On the MVEB-curated zero-shot tasks (Table 3) eBind leads at 61.1, but on the full 26-task appendix average Qwen3-VL-Embedding-8B (59.8) edges ahead of LCO-Embedding-Omni-7B (58.3) and eBind (58.1) on the strength of Breakfast, HMDB51, HumAnimCartoon-video, MusicAVQA-video, and UCF101-video, where it tops every audio-capable model; per-column leadership on Kinetics, RAVDESS, VGGSound, and WorldSense still goes to audio-capable models (eBind, pe-av-large, BidirLM-Omni-2.5B), so Qwen3-VL-8B's lead is an across-column average rather than a clean sweep. The Qwen2.5-Omni generative-MLLM-as-embedder rows again collapse (3.8–16.5), confirming that hidden-state pooling without a text↔video contrastive stage cannot align video to label-text prompts.

D.6 Clustering

Clustering remains universally hard on the curated MVEB pair. The strongest MVEB-curated clustering average is 27.3 (v-measure) by LCO-Embedding-Omni-7B, with runners-up in the 20–27 range; the bottleneck is the emotion-clustering task (MELDEmotion AV) where no model exceeds 8.8, while music-clustering (MusicAVQA AV) is comparatively easier (top scores in the 38–47 range). Across the wider 15-task appendix pool the picture changes: Qwen3-VL-Embedding-8B leads at 51.3 driven by strong UCF101 and HMDB51 splits where models reach 75–95. Adding the audio channel changes clustering scores very little on the curated pair, suggesting the headline-clustering bottleneck is the embedding geometry on fine-grained emotion labels rather than a missing modality.

D.7 Pair Classification

Pair classification is the easiest category for top models, with the leader (LCO-Embedding-Omni-3B at 80.7 max-AP) just above LCO-Embedding-Omni-7B (79.6) and Perception Encoder large (75.2). The MLLM-embed and audio-visual contrastive families cluster within four points of each other. On the 12-task appendix average, Qwen3-VL-Embedding-2B/8B lead at 75.0/74.5 because they consistently score high on the video-only pair-classification splits where audio is unavailable. Smaller multimodal-binding (eBind) and audio-visual contrastive checkpoints (PE-AV-small/base) are noticeably behind the MLLM-embed leaders

on this category.

D.8 Question Answering

LCO-Embedding-Omni-7B leads QA at 57.0, with the smaller LCO-Embedding-Omni-3B close behind at 56.4 and e5-omni-3B at 45.4. Qwen3-VL-Embedding-8B and BidirLM-Omni-2.5B are next strongest among the newer MLLM-embed entrants. The Perception Encoder audio-visual family scores 27.8–30.6 here, well behind the MLLM-embed leaders. This is a paradigm gap rather than a scale gap, since PE-AV-large (2.2B) loses to LCO-Embedding-Omni-3B (4.7B) by more than 25 points. Video-centric QA benefits more from large language-model context than from larger video-only feature extractors.

E Data Contamination Analysis

We follow Chung et al. (2025) and report disclosed train-evaluation overlap per model in Table 32. Each model's declared training datasets (in its MTEB ModelMeta) are cross-referenced against MVEB task names. Of the 33 evaluated models, 18 report no overlap with MVEB tasks and 15 have disclosed overlap on at least one task; the worst case is 65%. Qwen2.5-Omni, Qwen3-VL-Embedding, Jina-Embeddings-v5-omni, and VLM2Vec-V2.0 do not disclose their training data at dataset granularity, so we cannot certify their MVEB results as zero-shot; their rows in Table 32 carry NA in the Zero-shot % and # Overlap columns rather than the optimistic 100% / 0 that would otherwise appear by default.

F Extended Analyses on Temporal Context Scaling (# Frames)

subsection 5.2 discusses the aggregate effects of test-time frame scaling. This appendix details the experimental setup (task and model subsets, what varies, what is held fixed) and provides the task- and model-level breakdowns that the main-text plot aggregates over.

F.1 Experimental Setup

What varies. We sweep the number of uniformly sampled video frames $N \in \{1, 8, 16, 32, 64\}$ at test time, for each (task, model) pair in the subsets below.

What is held fixed. Every other input the model sees is unchanged from its default MVEB run: the audio track (when the model accepts audio)

is passed at the model's declared sampling rate and duration cap, instructions are passed only for models that declare `use_instructions=True`, embeddings are taken from each model's default output layer, and the per-task metric is the same one used in the main leaderboard (nDCG@10 for retrieval, accuracy for classification and QA, v-measure for clustering). No fine-tuning or pooling-strategy changes are introduced.

Task subset. We restrict the analysis to MVEB tasks whose average source clip is longer than 15 seconds, where multi-frame sampling has room to matter. Table 33 lists the seven tasks (top block) and the five models (bottom block) used.

Model subset. The five models span the major embedding paradigms in our roster and bracket the parameter range (847M to 7B), covering both architectures that integrate frames via temporal attention and those that pool frame embeddings post-hoc. Models with fixed clip-length training (X-CLIP, the 16-frame PE-AV variants) are excluded because their positional embeddings are tied to a single budget.

Entry	Identifier	Category / family
Task	Breakfast	Classification
Task	MusicAVQACLS	Clustering
Task	OmniVideoBench	QA
Task	WorldSense1Min	QA
Task	MSRVTT T2V	Retrieval
Task	VATEX T2VA	Retrieval
Task	VATEX V2A	Retrieval
Model	LCO-Embedding-Omni-3B	MLLM Embed
Model	e5-omni-3B	MLLM Embed
Model	omni-embed-nemotron-3b	MLLM Embed
Model	ebind-full	Multi-Bind
Model	pe-av-small	Aud-Vis Contr

Table 33: Frame-scaling experimental subsets. The seven tasks are MVEB entries with average source-clip duration > 15 s; the five models span the MLLM-based, multimodal-binding, and audio-visual contrastive paradigms.

F.2 Task-Level Performance Scaling

The benefit of frame scaling depends sharply on the task. Tasks with temporally rich content show steep gains: Breakfast improves from 15.88 (N=1) to 45.35 (N=64), and VATEX T2VA scales from 38.24 to 76.03. Other tasks barely move: OmniVideoBench QA shifts from 25.85 (N=1) to 26.68 (N=64), and WorldSense1Min QA from 28.42 to 30.60. The flat tasks share two properties:

they either carry complementary audio/text context that already saturates the model, or they admit a strong single-frame solution (e.g., scene-level QA that can be answered from a representative still). Per-task curves are in Figure 6.

Figure 6: Per-task mean performance as a function of sampled frame count.

F.3 Model-Level Performance Scaling

Scaling trajectories differ across architectures (Figure 4, main text). `ebind-full` plateaus early: it reaches 45.62 at N=8 and only 46.68 at N=64, suggesting its frame-pooling integrator extracts most of its signal from a small budget. The MLLM-based and audio-visual contrastive models scale more smoothly through N=64; `omni-embed-nemotron-3b` reaches 44.67 and `pe-av-small` reaches 44.32 at the top of the sweep.

G Accessibility and Reproducibility

While previous works (Enevoldsen et al., 2025, 2024; Chung et al., 2025) drastically improve transparency, reproducibility and submission protocols for MTEB, we here describe further improvements to MTEB that support reproducibility and long-term usability of the benchmark:

Experiment tracking: MTEB now records the full set of evaluation run settings (model configuration and task parameters) alongside each result file. Package version is tracked at the granularity of individual dataset subsets rather than per result file, enabling reliable merging of results obtained across different MTEB versions. Thus reducing the need to rerun the full results when expanding existing evaluations to include new splits or languages, while maintain a full reproducible traceback. Results can

be submitted to the community repository directly from the local cache via a standardised API. Submissions can additionally be scoped to a named experiment, keeping ablations and non-standard runs separate from canonical model results, thus allow for experiments on embedding compression, reduced vector size and similar.

Runtime tracking and evaluation efficiency: Results are now written incrementally per dataset subset rather than once per completed task, so that only the interrupted subset must be re-run following a crash or preemption. Runtime is also recorded per evaluation phase, supporting transparency into wall-clock costs alongside quality metrics.

Model metadata extensions: MODELMETA has been extended with an `active_parameters` field, recording the number of parameters engaged during inference rather than the total parameter count, which is more relevant for efficiency comparisons especially for smaller models where the vocabulary can drastically influence the parameters count in the embeddings whithout influencing the runtime cost. A `required_dependencies` field allows model authors to declare additional package requirements at registration time, reducing friction and ensuring reproducibility when running third-party models.

Leaderboard transparency: A performance-over-time visualization traces the progression of state-of-the-art scores across benchmarks over the history of model submissions, enabling researchers to contextualize new results against the trajectory of the field.

G.1 Per-model sampling configuration

Table 34 lists each model's declared video and audio sampling configuration. We honor these declared settings on every task rather than forcing a benchmark-wide budget; the rationale is in §3.2.

H Task correlation

I Audio Contribution: Per-Dataset and Per-Model Breakdowns

This appendix expands the audio-contribution analysis from §5.1. Table 35 reports the per-dataset audio delta sorted within each annotation group; Table 36 reports cross-modal retrieval alignment for the datasets that have both v2a and a2v task variants; Table 37 reports the per-model mean audio delta across all 48 paired task groups.

J Cross-Modal Retrieval Direction Structure: Extended Analysis

This appendix expands the cross-modal retrieval correlation analysis in §5.3. Table 38 reports every pairwise Spearman correlation across the eight retrieval directions, computed over the 16 audio-capable models in our roster.

Three latent capability axes. The 28 pairwise correlations resolve into three latent capability groups:

Text-as-query $T \to V$, $T \to VA$, $VT \to A$. Internal $\rho \in [0.77, 0.92]$. These directions all start from a textual query and retrieve into some non-text modality; the strongest pair is $T \to V$ vs. $T \to VA$ ($\rho = 0.92$), which differ only in whether the target includes audio.

Audio-as-conditioning-into-video $A \to V$, $AT \to V$, $V \to A$. Internal $\rho \in [0.87, 0.94]$. The directions that involve audio paired with video as either query or target; $V \to A$ correlates as tightly with $AT \to V$ ($\rho = 0.94$) as it does with $A \to V$ ($\rho = 0.87$), suggesting these three measure essentially the same capability of an audio-video joint encoder.

Text-as-target $V \to T$, $VA \to T$. A tight pair at $\rho = 0.96$; whether the query includes audio or not, the model's text-target ranking is nearly invariant.

What this means for benchmarking. The directions that *cross* group boundaries are the most decoupled: $T \to VA$ vs. $A \to V$ ($\rho = 0.38$) and $T \to VA$ vs. $AT \to V$ ($\rho = 0.39$) are the lowest pairs in the table. Both contrasts involve audio: in one case $T \to VA$ has audio as part of the *target* (joined with video), while $A \to V$/$AT \to V$ have audio as part of the *query*. Models that handle one of these well are not guaranteed to handle the other; this is consistent with the audio-track analysis in §5.1 that audio contributes a genuinely distinct signal whose encoding is implementation-specific.

This decoupling is the contrast that MMEB-V3 (Huang et al., 2026) cannot expose: by treating audio strictly as a separate retrieval modality with only $A \to V$ and $V \to A$ directions and never paired audio+video inputs, it does not include $T \to VA$ at all, and so the third capability group (audio as part of a joint retrieval target) is invisible.

Figure 7: Overview of task correlations.

Implication for the headline leaderboard. The within-group correlations above 0.85 mean a reader could collapse the eight directions into three target-grouped scores (text-target, video-target, audio-target) without losing rank information. We keep all eight in the per-direction appendix tables (subsection D.3) for transparency, but the MVEB **Retr** column already mean-pools them into a single score that aligns with the dominant capability axis.

K MVEB(text, video): Extended Analysis

This appendix expands the discussion of MVEB(text, video) from §4. The full 25-model leaderboard is in Table 11 (Appendix D.1); we report three observations here.

Breadth of the Qwen3-VL family's lead. Qwen3-VL-Embedding-8B and -2B (Li et al., 2026) take ranks 1 and 2 on MVEB(text, video) (60.9 and 58.1 mean). On the per-category breakdown, Qwen3-VL-Embedding-8B leads retrieval (69.2), classification (57.5), and zero-shot classification (59.2); Qwen3-VL-Embedding-2B leads clustering (24.9) and pair classification (88.3). LCO-Embedding-Omni-3B retains QA (32.8). Qwen3-VL-Embedding-2B at 58.1 mean already exceeds LCO-Embedding-Omni-7B (56.8) at roughly one-quarter the parameter count. We report these numbers; we do not attempt to attribute the gap to a specific cause, since the Qwen3-VL checkpoints differ from the omni embedders in training recipe, training-data composition, and declared input modalities simultaneously.

Figure 8: Overview of model size vs their performance.

What MVEB(text, video) is not. MVEB(text, video) excludes the audio-conditioned retrieval directions ($A \rightarrow V$, $V \rightarrow A$, $AT \rightarrow V$, $VT \rightarrow A$, $T \rightarrow VA$, $VA \rightarrow T$) and the `audio+video` task variants by construction; a high rank here is not evidence that a model would generalize to audio-bearing tasks, and the headline MVEB leaderboard remains the appropriate surface for audio-capable models. We expose MVEB(text, video) so that models that do not accept the full audio+video+text input surface can still be evaluated on a principled subset of the same task pool.

Relation to MMEB-V2. MMEB-V2 (Meng et al., 2025) is the closest existing text-video evaluation surface: 18 video tasks across retrieval, classification, VQA, grounding, and instance retrieval, evaluating text-video models in isolation. The structural difference with MVEB(text, video) is that the latter is the text-video projection of the same task pool we use for the headline MVEB and the audio-only-encoder variant, so the same model can be compared on the same tasks with and without an audio path. We do not claim a head-to-head comparison of model rankings between MMEB-V2 and MVEB(text, video) here, since the two benchmarks draw their tasks from different pools.

Caveat: non-uniform frame budgets. The Qwen3-VL checkpoints declare `[image, text]` modalities in their `ModelMeta` and rely on the Qwen3-VL processor's internal vision sampler rather than the `fps/max_frames` budget we apply to the omni models (see Table 34). We have not modified this; it is the model's intended inference path. It does mean the per-model frame budget across the MVEB(text, video) leaderboard is not strictly uniform, which a reader should keep in mind when interpreting absolute score differences.

L Annotation Quality Notes

We expand on the annotation-quality limitation introduced in the Limitations section. The most affected MVEB source datasets are the emotion-recognition splits; similar issues likely apply elsewhere but emotion datasets surface them most visibly.

MELD. MELD assigns a single discrete emotion to short utterance clips drawn from a sitcom. Two annotation patterns recur: (i) multi-sentiment utterances are squashed to one label, since a single clip can carry a surprise reaction, a brief rebuke, and a laugh track all in a few seconds, yet only one emotion tag is assigned; (ii) sitcom-specific context cues (laugh tracks, sarcastic delivery, the listener's reaction shot) can pull the gold label away from the literal text content. As an illustrative example of the first pattern, an utterance that contains an initial exclamation followed by a mild verbal complaint may carry an *anger* label even though a reasonable reader would split the same clip into several distinct affect segments. The single-label formulation is a property of the dataset, not the MVEB task wrapper, and we have not re-annotated for this paper.

RAVDESS. RAVDESS uses scripted emotion-acting performed by 24 professional actors at two intensity levels. Compound or transition states (e.g., a clip whose first half is neutral and second half is angry) are not captured by the single-emotion label, and intensity is a separate axis rather than a per-clip secondary label.

AVE-Dataset. AVE-Dataset annotates audio-visual events with class labels and bounding times. Some events co-occur within a clip but only the dominant event is annotated, which introduces unavoidable noise in clip-level classification tasks that operate on the whole clip rather than on the bounded event spans.

Figure 9: Per-task mean score across the model roster, sorted ascending. Low scores reflect a mix of intrinsic task difficulty and dataset label-quality issues; the emotion-recognition splits (MELD, RAVDESS) sit low primarily because of known label noise rather than embedding-quality limits (see Appendix L).

Why we keep the as-released labels. (a) These datasets are widely used and re-annotating them would break score comparability with the substantial body of prior published results. (b) MVEB's goal is to measure embedding quality on the field's standard evaluation surfaces, including their imperfections; an embedding model that perfectly fits a noisy single-label gold standard may be over-fitting to the annotation noise itself.

Mitigation paths for the community. Three directions are tractable: (i) soft-label or multi-label re-releases that publish per-clip distributions over labels rather than a single argmax, with evaluation tasks that consume the distribution; (ii) human-model agreement audits in the style of HUME (Assadi et al., 2025) that sample clips where current models disagree with the as-released label and check which side a fresh human annotator takes; (iii) targeted re-annotation on the most affected splits, with the as-released labels retained under a versioned task so prior results remain reproducible.

Dataset	Citation	MVEB	N.samples	Total Duration(s)	N.Langs	Domains	Main metric
Video Retrieval							
AVMemeExamA2VRetrieval	(Jiang et al., 2026a)		1,800	3h (11,010s)	1	Web, Social	ndcg_at_10
AVMemeExamAT2VRetrieval	(Jiang et al., 2026a)	✓	1,800	3h (11,010s)	1	Web, Social	ndcg_at_10
AVMemeExamT2VARetrieval	(Jiang et al., 2026a)		1,800	3h (11,010s)	1	Web, Social	ndcg_at_10
AVMemeExamV2ARetrieval	(Jiang et al., 2026a)		1,800	3h (11,010s)	1	Web, Social	ndcg_at_10
AVMemeExamVA2TRetrieval	(Jiang et al., 2026a)		1,800	3h (11,010s)	1	Web, Social	ndcg_at_10
AVMemeExamVT2ARetrieval	(Jiang et al., 2026a)		1,800	3h (11,010s)	1	Web, Social	ndcg_at_10
AudioCapsAVA2VRetrieval	(Kim et al., 2019)		1,330	1h (6,541s)	1	Encyclopaedic, Web	ndcg_at_10
AudioCapsAVAT2VRetrieval	(Kim et al., 2019)		1,330	1h (6,541s)	1	Encyclopaedic, Web	ndcg_at_10
AudioCapsAVT2VARetrieval	(Kim et al., 2019)		1,330	1h (6,541s)	1	Encyclopaedic, Web	ndcg_at_10
AudioCapsAVV2ARetrieval	(Kim et al., 2019)		1,330	1h (6,541s)	1	Encyclopaedic, Web	ndcg_at_10
AudioCapsAVVA2TRetrieval	(Kim et al., 2019)	✓	1,330	1h (6,541s)	1	Encyclopaedic, Web	ndcg_at_10
AudioCapsAVVT2ARetrieval	(Kim et al., 2019)	✓	1,330	1h (6,541s)	1	Encyclopaedic, Web	ndcg_at_10
DiDeMoA2VRetrieval	(Hendricks et al., 2017)		1,998	13h (50,032s)	1	Web, Spoken	ndcg_at_10
DiDeMoAT2VRetrieval	(Hendricks et al., 2017)		1,998	13h (50,032s)	1	Web, Spoken	ndcg_at_10
DiDeMoT2VARetrieval	(Hendricks et al., 2017)		1,998	13h (50,032s)	1	Web, Spoken	ndcg_at_10
DiDeMoV2ARetrieval	(Hendricks et al., 2017)		1,998	13h (50,032s)	1	Web, Spoken	ndcg_at_10
DiDeMoVA2TRetrieval	(Hendricks et al., 2017)		1,998	13h (50,032s)	1	Web, Spoken	ndcg_at_10
DiDeMoVT2ARetrieval	(Hendricks et al., 2017)		1,998	13h (50,032s)	1	Web, Spoken	ndcg_at_10
MSRVTTA2V	(Xu et al., 2016)		1,758	3h (13,369s)	1	Unknown	ndcg_at_10
MSRVTTAT2V	(Xu et al., 2016)		1,758	3h (13,369s)	1	Unknown	ndcg_at_10
MSRVTTT2VA	(Xu et al., 2016)		1,758	3h (13,369s)	1	Unknown	ndcg_at_10
MSRVTTV2A	(Xu et al., 2016)		1,758	3h (13,369s)	1	Unknown	ndcg_at_10
MSRVTTVA2T	(Xu et al., 2016)		1,758	3h (13,369s)	1	Unknown	ndcg_at_10
MSRVTTVT2A	(Xu et al., 2016)		1,758	3h (13,369s)	1	Unknown	ndcg_at_10
Panda70MT2VARetrieval	(Chen et al., 2024)		6,790	10h (37,488s)	1	Web, Spoken	ndcg_at_10
Panda70MVA2TRetrieval	(Chen et al., 2024)		6,790	10h (37,488s)	1	Web, Spoken	ndcg_at_10
Shot2Story20KA2VRetrieval	(Han et al., 2023)		8,046	18h (67,101s)	1	Web, Spoken	ndcg_at_10
Shot2Story20KAT2VRetrieval	(Han et al., 2023)		8,046	18h (67,101s)	1	Web, Spoken	ndcg_at_10
Shot2Story20KT2VARetrieval	(Han et al., 2023)		8,046	18h (67,101s)	1	Web, Spoken	ndcg_at_10
Shot2Story20KV2ARetrieval	(Han et al., 2023)		8,046	18h (67,101s)	1	Web, Spoken	ndcg_at_10
Shot2Story20KVA2TRetrieval	(Han et al., 2023)		8,046	18h (67,101s)	1	Web, Spoken	ndcg_at_10
Shot2Story20KVT2ARetrieval	(Han et al., 2023)		8,046	18h (67,101s)	1	Web, Spoken	ndcg_at_10
VALOR32KA2VRetrieval	(Chen et al., 2023)		6,982	9h (34,636s)	1	Web, Spoken	ndcg_at_10
VALOR32KAT2VRetrieval	(Chen et al., 2023)		6,982	9h (34,636s)	1	Web, Spoken	ndcg_at_10
VALOR32KT2VARetrieval	(Chen et al., 2023)	✓	6,982	9h (34,636s)	1	Web, Spoken	ndcg_at_10
VALOR32KV2ARetrieval	(Chen et al., 2023)		6,982	9h (34,636s)	1	Web, Spoken	ndcg_at_10
VALOR32KVA2TRetrieval	(Chen et al., 2023)		6,982	9h (34,636s)	1	Web, Spoken	ndcg_at_10
VALOR32KVT2ARetrieval	(Chen et al., 2023)		6,982	9h (34,636s)	1	Web, Spoken	ndcg_at_10
VATEXA2VRetrieval	(Wang et al., 2019)		2,000	1d (157,615s)	1	Web, Spoken	ndcg_at_10
VATEXAT2VRetrieval	(Wang et al., 2019)		2,000	1d (157,615s)	1	Web, Spoken	ndcg_at_10
VATEXT2VARetrieval	(Wang et al., 2019)		2,000	1d (157,615s)	1	Web, Spoken	ndcg_at_10
VATEXV2ARetrieval	(Wang et al., 2019)	✓	2,000	1d (157,615s)	1	Web, Spoken	ndcg_at_10
VATEXVA2TRetrieval	(Wang et al., 2019)	✓	2,000	1d (157,615s)	1	Web, Spoken	ndcg_at_10
VATEXVT2ARetrieval	(Wang et al., 2019)		2,000	1d (157,615s)	1	Web, Spoken	ndcg_at_10
VGGSoundAVA2VRetrieval	(Chen et al., 2020)	✓	1,392	1h (6,952s)	1	Web, Spoken	ndcg_at_10
VGGSoundAVAT2VRetrieval	(Chen et al., 2020)		1,392	1h (6,952s)	1	Web, Spoken	ndcg_at_10
VGGSoundAVT2VARetrieval	(Chen et al., 2020)		1,392	1h (6,952s)	1	Web, Spoken	ndcg_at_10
VGGSoundAVV2ARetrieval	(Chen et al., 2020)		1,392	1h (6,952s)	1	Web, Spoken	ndcg_at_10
VGGSoundAVVA2TRetrieval	(Chen et al., 2020)		1,392	1h (6,952s)	1	Web, Spoken	ndcg_at_10
VGGSoundAVVT2ARetrieval	(Chen et al., 2020)		1,392	1h (6,952s)	1	Web, Spoken	ndcg_at_10
YouCook2A2VRetrieval	(Zhou et al., 2018)		6,208	17h (61,878s)	1	Web, Spoken	ndcg_at_10
YouCook2AT2VRetrieval	(Zhou et al., 2018)		6,208	17h (61,878s)	1	Web, Spoken	ndcg_at_10
YouCook2T2VARetrieval	(Zhou et al., 2018)	✓	6,208	17h (61,878s)	1	Web, Spoken	ndcg_at_10
YouCook2V2ARetrieval	(Zhou et al., 2018)		6,208	17h (61,878s)	1	Web, Spoken	ndcg_at_10
YouCook2VA2TRetrieval	(Zhou et al., 2018)		6,208	17h (61,878s)	1	Web, Spoken	ndcg_at_10
YouCook2VT2ARetrieval	(Zhou et al., 2018)		6,208	17h (61,878s)	1	Web, Spoken	ndcg_at_10

Table 8: Video-audio(-text) retrieval tasks in MVEB. Tasks use video with audio and optionally text for retrieval.

Provenance	Dataset families
AV-grounded	AudioCaps_AV, AVEDataset, AVMeme, AVMemeExam, AVQA, AVSpeakerBench, Daily-Omni, MELD, MusicAVQA, MusicAVQACLS, OmniVideoBench, PerceptionTest, RAVDESS, Shot2Story20K, VALOR-32K, VGGSoundAV, VideoMME, VideoMMEShort, WorldQA, World-Sense, WorldSense1Min, YouCook2
V-grounded	ActivityNetCaptions, Breakfast, Charades-STA, DiDeMo, Diving48, EgoSchema, HMDB51, Hu-manAnimalCartoon, Kinetics-400, Kinetics-600, Kinetics-700, MSR-VTT, MSVD, NExT-QA, Panda70M, SomethingSomethingV2, TUNA-Bench, UCF101, VATEX, VideoCon, Vinoground

Table 9: Annotation provenance of MVEB source datasets. AV-grounded families had labels produced from both audio and visual content; V-grounded families had labels produced from visuals alone, even though the source clips often carry audio. Both groups are paired into video-only and video+audio task variants in MVEB; the distinction matters for interpreting the per-task audio delta in §5.1.

Model	Parameters (M)	Modalities
BidirLM/BidirLM-Omni-2.5B-Embedding	2445.0	a, i, t, v
Haon-Chen/e5-omni-3B (Chen et al., 2026)	4703.5	a, i, t, v
Haon-Chen/e5-omni-7B (Chen et al., 2026)	8931.8	a, i, t, v
LCO-Embedding/LCO-Embedding-Omni-3B (Xiao et al., 2025a)	4703.5	a, i, t, v
LCO-Embedding/LCO-Embedding-Omni-7B (Xiao et al., 2025a)	8931.8	a, i, t, v
Qwen/Qwen2.5-Omni-3B (Xu et al., 2025a)	5537.1	a, i, t, v
Qwen/Qwen2.5-Omni-7B (Xu et al., 2025a)	10732.2	a, i, t, v
Qwen/Qwen3-VL-Embedding-2B	2127.5	i, t, v
Qwen/Qwen3-VL-Embedding-8B	8144.8	i, t, v
Qwen/Qwen3-Omni-30B-A3B-Captioner[†] (Xu et al., 2025b)	31719.2	a, i, t, v
Qwen/Qwen3-Omni-30B-A3B-Instruct[†] (Xu et al., 2025b)	35259.8	a, i, t, v
Qwen/Qwen3-Omni-30B-A3B-Thinking[†] (Xu et al., 2025b)	31719.2	a, i, t, v
Tevatron/OmniEmbed-v0.1 (Ma et al., 2025)	8931.8	a, i, t, v
encord-team/ebind-audio-vision (Broadbent et al., 2025)	764.2	a, i, t, v
encord-team/ebind-full (Broadbent et al., 2025)	1790.0	a, i, t, v
encord-team/ebind-points-vision (Broadbent et al., 2025)	1694.2	i, t, v
facebook/pe-av-base (Vyas et al., 2025)	1033.7	a, t, v
facebook/pe-av-base-16-frame[†] (Vyas et al., 2025)	1033.7	a, t, v
facebook/pe-av-large (Vyas et al., 2025)	2234.7	a, t, v
facebook/pe-av-large-16-frame[†] (Vyas et al., 2025)	2234.7	a, t, v
facebook/pe-av-small (Vyas et al., 2025)	847.0	a, t, v
facebook/pe-av-small-16-frame[†] (Vyas et al., 2025)	847.0	a, t, v
facebook/vjepa2-vitg-fpc32-384-diving48	1127.9	v
facebook/vjepa2-vitg-fpc64-256	1034.6	v
facebook/vjepa2-vitg-fpc64-384	1034.6	v
facebook/vjepa2-vitg-fpc64-384-ssv2	1128.0	v
facebook/vjepa2-vith-fpc64-256	653.9	v
facebook/vjepa2-vitl-fpc16-256-ssv2	375.5	v
facebook/vjepa2-vitl-fpc32-256-diving48	375.4	v
facebook/vjepa2-vitl-fpc64-256	326.0	v
jinaai/jina-embeddings-v5-omni-nano	986.0	a, i, t, v
jinaai/jina-embeddings-v5-omni-small	1626.3	a, i, t, v
microsoft/xclip-base-patch16 (Ni et al., 2022)	194.9	t, v
microsoft/xclip-base-patch32 (Ni et al., 2022)	196.6	t, v
microsoft/xclip-large-patch14 (Ni et al., 2022)	575.7	t, v
VLM2Vec/VLM2Vec-V2.0 (Meng et al., 2025)	2209.0	i, t, v
nvidia/omni-embed-nemotron-3b (Xu et al., 2025c)	4703.5	a, i, t, v
nvidia/omnivinci[†] (Ye et al., 2025)	8742.9	a, i, t, v
zhibinlan/UME-R1-2B (Lan et al., 2025)	2209.0	i, t, v
zhibinlan/UME-R1-7B (Lan et al., 2025)	8291.4	i, t, v

Table 10: Models registered in MVEB. Model sizes are in millions of parameters. [†]Registered in the MTEB model registry but not yet evaluated on MVEB.

Model	Type	Params	Rank (↓) MVEB(text, video)	Average Mean	Macro	Retr	QA	Cls	Clust	Pair	ZS
Number of tasks						(8)	(1)	(4)	(1)	(1)	(4)
Qwen3-VL-Embedding-8B	MLLM-based embedding	8.1B	**1**	**60.9**	**53.7**	**69.2**	27.3	**57.5**	22.2	86.7	**59.2**
Qwen3-VL-Embedding-2B	MLLM-based embedding	2.1B	2	58.1	52.6	65.7	26.7	54.8	**24.9**	**88.3**	55.0
LCO-Embedding-Omni-7B	MLLM-based embedding	8.9B	3	56.8	51.8	62.3	30.8	54.3	20.8	85.9	56.4
LCO-Embedding-Omni-3B	MLLM-based embedding	4.7B	4	54.8	50.8	59.1	**32.8**	54.0	17.6	87.7	53.7
ebind-points-vision	Multimodal binding	1.7B	5	53.8	44.8	62.9	22.2	46.2	1.4	78.2	57.9
UME-R1-7B	MLLM-based embedding	8.3B	6	53.3	46.7	62.5	26.7	48.1	8.8	84.0	50.0
ebind-audio-vision	Multimodal binding	764M	7	53.8	44.8	62.9	22.2	46.2	1.4	78.2	57.9
ebind-full	Multimodal binding	1.8B	7	53.8	44.8	62.9	22.2	46.2	1.4	78.2	57.9
e5-omni-7B	MLLM-based embedding	8.9B	9	54.1	46.5	63.6	26.5	45.3	3.5	84.3	55.8
pe-av-large	Audio-visual contrastive	2.2B	10	52.4	46.1	60.3	26.3	45.3	11.5	79.2	53.6
BidirLM-Omni-2.5B-Embedding	MLLM-based embedding	2.4B	11	52.0	48.7	56.3	26.9	48.5	21.6	85.7	53.4
UME-R1-2B	MLLM-based embedding	2.2B	12	51.5	46.4	57.6	25.1	48.0	14.9	82.1	50.9
OmniEmbed-v0.1	MLLM-based embedding	8.9B	13	51.3	45.8	57.6	25.9	49.0	10.6	81.8	50.1
pe-av-base	Audio-visual contrastive	1.0B	14	49.7	43.7	57.0	25.1	45.4	10.7	75.2	49.0
pe-av-small	Audio-visual contrastive	847M	15	50.2	44.1	56.1	23.6	45.0	9.0	76.5	54.2
e5-omni-3B	MLLM-based embedding	4.7B	16	48.4	43.5	57.9	28.3	45.1	8.0	82.1	39.5
xclip-large-patch14	Video-text contrastive	576M	17	42.9	41.5	37.0	24.2	48.2	8.2	77.3	54.1
VLM2Vec-V2.0	MLLM-based embedding	2.2B	18	44.9	41.0	50.0	29.1	40.6	0.2	81.3	45.0
omni-embed-nemotron-3b	MLLM-based embedding	4.7B	19	35.8	38.4	29.3	25.1	43.7	10.9	82.9	38.3
xclip-base-patch16	Video-text contrastive	195M	20	38.4	38.8	30.6	22.4	41.9	10.6	74.9	52.3
xclip-base-patch32	Video-text contrastive	197M	21	35.9	38.0	26.9	26.5	37.2	11.1	74.7	51.6
Qwen2.5-Omni-7B	Generative MLLM	10.7B	22	10.4	18.9	0.4	25.1	11.8	7.4	53.1	15.5
jina-embeddings-v5-omni-nano	MLLM-based embedding	986M	23	7.7	15.8	0.4	26.3	8.9	1.0	51.5	6.9
Qwen2.5-Omni-3B	Generative MLLM	5.5B	24	7.8	17.0	0.4	24.4	10.6	7.9	54.5	4.1
jina-embeddings-v5-omni-small	MLLM-based embedding	1.6B	25	8.2	16.2	0.4	24.4	8.4	1.2	52.4	10.2

Table 11: Models on **MVEB(text, video)** ranked by Borda count over 19 tasks. **Mean** is the arithmetic mean over the model's evaluated tasks; **Macro** is the macro-average across task categories (each category weighted equally regardless of task count). Task categories: Retr (retrieval; per-direction breakdown in appendix), QA, Cls (classification), Clust (clustering), Pair (pair classification), ZS (zero-shot classification). Model types are defined in §3.1. **Bold** = best per column.

Model	Type	Params	Rank (↓) MVEB(video)	Average Mean	Macro	Average per Category Cls	Pair
Number of tasks						(6)	(3)
LCO-Embedding-Omni-3B	MLLM-based embedding	4.7B	**1**	61.6	65.1	54.4	**75.9**
LCO-Embedding-Omni-7B	MLLM-based embedding	8.9B	2	61.7	65.0	55.1	74.9
Qwen3-VL-Embedding-2B	MLLM-based embedding	2.1B	2	62.3	65.6	55.6	75.7
Qwen3-VL-Embedding-8B	MLLM-based embedding	8.1B	4	**63.5**	**66.3**	**58.0**	74.6
xclip-large-patch14	Video-text contrastive	576M	5	58.6	62.3	51.0	73.7
UME-R1-2B	MLLM-based embedding	2.2B	6	57.4	61.2	49.9	72.4
UME-R1-7B	MLLM-based embedding	8.3B	7	57.5	61.2	50.0	72.4
BidirLM-Omni-2.5B-Embedding	MLLM-based embedding	2.4B	7	58.0	62.0	50.1	73.8
ebind-full	Multimodal binding	1.8B	9	55.8	59.4	48.6	70.3
ebind-audio-vision	Multimodal binding	764M	9	55.8	59.4	48.6	70.3
ebind-points-vision	Multimodal binding	1.7B	11	55.8	59.4	48.6	70.3
OmniEmbed-v0.1	MLLM-based embedding	8.9B	12	57.9	61.3	51.2	71.4
xclip-base-patch16	Video-text contrastive	195M	13	55.6	59.8	47.3	72.2
e5-omni-3B	MLLM-based embedding	4.7B	14	55.7	59.3	48.3	70.4
e5-omni-7B	MLLM-based embedding	8.9B	15	55.7	59.4	48.2	70.7
pe-av-large	Audio-visual contrastive	2.2B	16	55.2	59.2	47.2	71.2
omni-embed-nemotron-3b	MLLM-based embedding	4.7B	16	54.7	58.8	46.3	71.3
VLM2Vec-V2.0	MLLM-based embedding	2.2B	18	52.9	56.8	45.0	68.5
pe-av-base	Audio-visual contrastive	1.0B	19	53.8	58.2	45.0	71.3
xclip-base-patch32	Video-text contrastive	197M	20	53.0	57.6	43.8	71.5
pe-av-small	Audio-visual contrastive	847M	21	53.3	57.6	44.8	70.4
vjepa2-vitg-fpc32-384-diving48	Self-supervised video	1.1B	22	46.2	50.3	38.0	62.5
vjepa2-vitl-fpc16-256-ssv2	Self-supervised video	375M	23	44.6	49.1	35.7	62.5
vjepa2-vitl-fpc64-256	Self-supervised video	326M	24	45.2	49.8	36.0	63.5
vjepa2-vitg-fpc64-256	Self-supervised video	1.0B	25	45.9	49.8	38.0	61.7
vjepa2-vitg-fpc64-384	Self-supervised video	1.0B	26	45.6	49.5	37.9	61.0
vjepa2-vitg-fpc64-384-ssv2	Self-supervised video	1.1B	26	45.6	49.5	37.9	61.0
vjepa2-vitl-fpc32-256-diving48	Self-supervised video	375M	28	44.8	49.4	35.5	63.2
vjepa2-vith-fpc64-256	Self-supervised video	654M	29	42.5	46.8	34.0	59.5
Qwen2.5-Omni-3B	Generative MLLM	5.5B	30	30.1	36.4	17.5	55.3
Qwen2.5-Omni-7B	Generative MLLM	10.7B	31	30.7	36.6	18.9	54.3
jina-embeddings-v5-omni-nano	MLLM-based embedding	986M	32	24.9	31.3	12.0	50.6
jina-embeddings-v5-omni-small	MLLM-based embedding	1.6B	33	24.7	31.2	11.6	50.8

Table 12: Models on **MVEB(video)** ranked by Borda count over 9 tasks. **Mean** is the arithmetic mean over the model's evaluated tasks; **Macro** is the macro-average across task categories (each category weighted equally regardless of task count). Task categories: Cls (classification), Pair (pair classification). Model types are defined in §3.1. **Bold** = best per column.

Model	Type	Params	Rank (↓) MVEB+	Average Mean	Macro	Retr	QA	Cls	Clust	Pair	ZS
Number of tasks						(82)	(20)	(28)	(15)	(13)	(26)
LCO-Embedding-Omni-7B	MLLM-based embedding	8.9B	1	**58.7**	**58.1**	**61.0**	**51.8**	**57.4**	46.5	73.9	**58.3**
LCO-Embedding-Omni-3B	MLLM-based embedding	4.7B	2	56.3	56.6	57.3	49.8	55.9	**46.7**	**74.3**	55.6
e5-omni-7B	MLLM-based embedding	8.9B	3	56.2	54.7	60.8	46.2	52.2	43.2	72.4	53.4
ebind-audio-vision	Multimodal binding	764M	4	54.1	53.3	57.3	36.4	50.8	45.3	71.9	58.1
ebind-full	Multimodal binding	1.8B	5	54.1	53.3	57.2	36.4	50.8	45.3	71.9	58.1
BidirLM-Omni-2.5B-Embedding	MLLM-based embedding	2.4B	6	51.6	53.3	49.4	40.4	56.9	45.2	73.9	54.1
pe-av-large	Audio-visual contrastive	2.2B	7	52.7	51.1	57.7	30.7	50.7	42.8	72.0	52.6
pe-av-base	Audio-visual contrastive	1.0B	8	51.3	50.4	55.0	30.5	50.1	41.9	72.1	52.7
OmniEmbed-v0.1	MLLM-based embedding	8.9B	9	49.7	50.4	50.6	37.5	53.3	43.9	72.3	44.8
pe-av-small	Audio-visual contrastive	847M	10	50.8	50.2	53.7	30.0	50.2	41.5	72.0	53.5
e5-omni-3B	MLLM-based embedding	4.7B	11	49.2	50.1	50.6	42.7	48.6	43.6	72.0	43.2
omni-embed-nemotron-3b	MLLM-based embedding	4.7B	12	43.7	47.4	39.7	38.2	51.8	43.9	72.5	38.5
jina-embeddings-v5-omni-nano	MLLM-based embedding	986M	13	16.6	24.4	7.2	29.7	16.9	20.7	57.3	14.7
jina-embeddings-v5-omni-small	MLLM-based embedding	1.6B	14	15.8	24.4	5.0	28.3	17.2	22.3	57.9	15.5
Qwen2.5-Omni-7B	Generative MLLM	10.7B	15	11.6	20.7	0.4	23.9	14.2	20.9	56.5	8.4
Qwen2.5-Omni-3B	Generative MLLM	5.5B	16	11.3	20.5	0.5	25.2	14.2	20.6	58.0	4.8

Table 13: Models on **MVEB+** ranked by Borda count over 184 tasks. **Mean** is the arithmetic mean over the model's evaluated tasks; **Macro** is the macro-average across task categories (each category weighted equally regardless of task count). Task categories: Retr (retrieval; per-direction breakdown in appendix), QA, Cls (classification), Clust (clustering), Pair (pair classification), ZS (zero-shot classification). Model types are defined in §3.1. **Bold** = best per column.

Model	AVMemeExam T→V	ActivityNet T→V	AudioCapsAV T→V	DiDeMo T→V	MSRVTT T→V	MSVD T→V	Panda70M T→V	Shot2Story20K T→V	TUNABench T→V	VALOR32K T→V	VATEX T→V	VGGSoundAV T→V	YouCook2 T→V	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	33.70	65.02	28.39	56.73	59.22	82.43	–	95.44	96.39	56.24	75.86	97.72	26.13	64.44
Haon-Chen/e5-omni-3B	39.20	71.48	24.56	63.24	66.66	81.74	78.12	97.88	95.20	60.77	79.47	97.65	32.10	68.31
Haon-Chen/e5-omni-7B	42.32	74.17	21.13	65.55	68.05	82.62	83.33	99.07	98.58	64.88	81.06	98.75	37.95	70.57
LCO-Embedding/LCO-Embedding-Omni-3B	44.16	63.28	26.93	61.61	62.06	79.00	70.15	95.51	95.55	55.23	76.45	94.74	34.37	66.08
LCO-Embedding/LCO-Embedding-Omni-7B	48.26	70.65	27.77	65.87	64.35	79.82	70.58	96.64	97.02	59.40	80.16	96.48	41.31	69.10
Qwen/Qwen2.5-Omni-3B	0.45	0.08	0.65	0.41	0.49	1.00	0.18	0.13	0.64	0.12	0.40	0.60	0.18	0.41
Qwen/Qwen2.5-Omni-7B	0.50	0.10	0.77	0.33	0.63	1.11	0.21	0.11	0.55	0.15	0.36	0.74	0.17	0.44
Qwen/Qwen3-VL-Embedding-2B	43.83	73.85	25.79	69.92	70.94	86.87	81.66	98.84	99.06	67.47	82.53	99.12	46.98	72.84
Qwen/Qwen3-VL-Embedding-8B	**50.00**	**78.82**	27.60	**74.81**	**74.01**	**87.56**	83.38	**99.45**	**99.45**	71.20	**85.30**	**99.40**	**53.87**	**75.76**
Tevatron/OmniEmbed-v0.1	40.59	71.46	18.03	61.53	68.47	80.75	75.85	98.61	96.57	58.21	77.81	96.00	40.16	68.00
encord-team/ebind-audio-vision	42.28	61.18	25.84	58.31	66.60	85.46	84.18	59.49	67.50	61.91	83.05	94.56	39.15	63.81
encord-team/ebind-full	42.28	61.18	25.84	58.31	66.60	85.46	**84.18**	59.49	67.50	61.91	83.05	94.56	39.15	63.81
encord-team/ebind-points-vision	42.28	61.19	25.84	58.35	66.55	85.46	84.18	59.50	67.50	61.92	83.12	94.56	39.15	63.81
facebook/pe-av-base	21.95	69.41	30.86	52.14	56.90	75.63	61.18	94.78	95.99	68.99	80.54	97.42	16.47	63.25
facebook/pe-av-large	26.32	69.48	**35.63**	55.05	59.79	78.56	64.12	96.94		**72.00**	81.69	98.33	18.96	65.60
facebook/pe-av-small	20.39	68.60	27.25	51.76	55.81	74.60	62.64	94.88	96.71	68.23	79.04	97.91	15.17	62.54
jinaai/jina-embeddings-v5-omni-nano	0.40	0.09	0.86	0.61	0.52	0.55	0.21	0.18	0.52	0.19	0.45	0.70	0.09	0.41
jinaai/jina-embeddings-v5-omni-small	1.03	0.05	0.53	0.47	0.33	0.55	0.15	0.05	0.52	0.23	0.53	0.73	0.11	0.41
microsoft/xclip-base-patch16	17.72	24.02	12.56	24.48	26.91	47.93	34.30	26.80	37.18	17.17	45.21	65.07	8.01	29.80
microsoft/xclip-base-patch32	11.69	21.22	11.02	19.60	19.33	39.93	27.96	25.81	33.21	13.42	39.51	64.14	6.63	25.65
microsoft/xclip-large-patch14	26.58	30.47	17.15	32.49	40.39	59.19	44.41	40.52	46.57	22.36	56.88	72.60	11.23	38.53
VLM2Vec/VLM2Vec-V2.0	33.40	52.66	19.94	51.46	50.23	69.76	67.92	95.02	96.17	42.19	69.19	95.37	22.37	58.90
nvidia/omni-embed-nemotron-3b	14.63	48.61	12.41	39.71	31.99	29.09	27.30	89.64	89.40	33.28	27.27	95.09	1.15	41.51
zhibinlan/UME-R1-2B	38.37	61.63	25.10	58.63	59.83	78.01	70.42	94.51	94.42	52.48	74.05	95.94	34.60	64.46
zhibinlan/UME-R1-7B	45.20	69.53	26.30	62.34	63.10	81.69	75.45	97.88	97.47	58.01	79.18	98.58	39.16	68.76

Table 14: **Retrieval: Text → Video** (13 tasks, nDCG@10).

Model	AVMemeExam A→V	AudioCapsAV A→V	DiDeMo A→V	MSRVTT A→V	Shot2Story20K A→V	VALOR32K A→V	VATEX A→V	VGGSoundAV A→V	YouCook2 A→V	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	25.31	13.96	10.23	34.86	60.39	8.73	22.88	14.17	17.34	23.10
Haon-Chen/e5-omni-3B	29.87	22.94	16.09	36.19	69.70	12.45	35.55	24.91	16.79	29.39
Haon-Chen/e5-omni-7B	31.95	19.53	20.16	45.52	86.12	12.71	43.02	27.16	31.65	35.31
LCO-Embedding/LCO-Embedding-Omni-3B	40.60	31.30	27.86	45.89	82.83	20.87	46.71	34.82	31.81	40.30
LCO-Embedding/LCO-Embedding-Omni-7B	**43.60**	35.86	29.36	49.47	**89.08**	23.21	49.05	40.25	**41.94**	44.65
Qwen/Qwen2.5-Omni-3B	1.10	0.91	0.61	0.57	0.14	0.13	0.70	0.92	0.15	0.58
Qwen/Qwen2.5-Omni-7B	0.69	0.71	0.41	0.30	0.26	0.14	0.53	0.43	0.12	0.40
Tevatron/OmniEmbed-v0.1	21.09	13.68	13.53	25.26	68.54	6.40	35.13	15.69	14.97	23.81
encord-team/ebind-audio-vision	36.51	78.13	39.74	41.19	17.48	47.71	45.32	67.98	7.89	42.44
encord-team/ebind-full	36.51	78.13	39.74	41.19	17.48	47.71	45.32	67.98	7.89	42.44
facebook/pe-av-base	23.86	69.35	59.99	43.36	21.85	48.24	62.20	74.58	10.55	46.00
facebook/pe-av-large	24.52	**79.01**	**65.81**	**49.92**	27.80	**58.44**	**68.77**	**84.27**	16.28	**52.76**
facebook/pe-av-small	16.84	65.60	55.74	39.83	20.52	42.09	61.33	69.13	9.29	42.26
jinaai/jina-embeddings-v5-omni-nano	0.50	1.21	0.53	0.63	0.05	0.17	0.47	0.64	0.21	0.49
jinaai/jina-embeddings-v5-omni-small	0.60	1.02	0.53	0.25	0.11	0.11	0.40	0.53	0.04	0.40
nvidia/omni-embed-nemotron-3b	29.77	24.88	20.38	37.10	66.64	16.09	35.24	30.03	20.39	31.17

Table 15: **Retrieval: Audio → Video** (9 tasks, nDCG@10).

Model	AVMemeExam AT→V	AudioCapsAV AT→V	DiDeMo AT→V	MSRVTT AT→V	Shot2Story20K AT→V	VALOR32K AT→V	VATEX AT→V	VGGSoundAV AT→V	YouCook2 AT→V	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	39.93	30.50	45.65	58.57	90.50	48.28	72.95	95.04	29.38	56.76
Haon-Chen/e5-omni-3B	47.70	29.51	55.31	65.26	98.44	50.20	75.73	95.68	32.33	61.13
Haon-Chen/e5-omni-7B	42.52	24.46	59.54	73.12	**99.39**	48.97	77.71	95.98	43.58	62.81
LCO-Embedding/LCO-Embedding-Omni-3B	53.32	35.24	68.96	77.39	97.81	61.89	83.36	94.04	41.46	68.16
LCO-Embedding/LCO-Embedding-Omni-7B	55.95	38.31	72.52	**79.19**	98.68	65.97	88.22	94.45	52.93	71.80
Qwen/Qwen2.5-Omni-3B	0.55	0.82	0.42	0.50	0.15	0.12	0.60	0.67	0.16	0.45
Qwen/Qwen2.5-Omni-7B	0.77	0.65	0.59	0.31	0.18	0.15	0.42	1.04	0.23	0.48
Tevatron/OmniEmbed-v0.1	31.23	16.08	34.36	47.97	98.79	21.70	58.48	76.04	22.10	45.19
encord-team/ebind-audio-vision	**58.98**	**69.89**	74.88	76.81	68.44	79.00	92.20	96.56	**56.83**	**74.84**
encord-team/ebind-full	58.98	69.89	74.88	76.78	68.44	79.00	92.20	96.56	56.83	74.84
facebook/pe-av-base	28.77	57.58	72.58	69.01	94.22	79.62	90.36	98.29	26.18	68.51
facebook/pe-av-large	31.50	68.54	**76.07**	73.43	95.71	**84.69**	**93.08**	**98.74**	29.68	72.38
facebook/pe-av-small	25.85	50.60	71.46	67.08	94.32	77.39	89.51	98.10	23.02	66.37
jinaai/jina-embeddings-v5-omni-nano	0.48	1.21	0.54	0.83	0.09	0.18	0.47	0.59	0.18	0.51
jinaai/jina-embeddings-v5-omni-small	0.75	1.06	0.56	0.25	0.09	0.14	0.47	0.59	0.03	0.44
nvidia/omni-embed-nemotron-3b	33.34	24.53	21.35	38.31	85.84	17.56	36.00	63.41	20.86	37.91

Table 16: **Retrieval: Audio+Text → Video** (9 tasks, nDCG@10).

Model	AVMemeExam V→T	ActivityNet V→T	AudioCapsAV V→T	DiDeMo V→T	MSRVTT V→T	MSVD V→T	Panda70M V→T	Shot2Story20K V→T	TUNABench V→T	VALOR32K V→T	VATEX V→T	VGGSoundAV V→T	YouCook2 V→T	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	28.36	60.26	30.32	54.14	56.35	81.05	–	93.15	94.42	57.63	74.72	97.14	20.20	62.31
Haon-Chen/e5-omni-3B	23.94	48.05	20.28	36.12	49.28	73.29	68.87	79.29	80.78	48.56	66.85	88.88	18.86	54.08
Haon-Chen/e5-omni-7B	37.60	67.86	27.88	64.77	63.06	77.03	79.10	98.55	98.27	59.71	79.37	**98.87**	31.11	67.94
LCO-Embedding/LCO-Embedding-Omni-3B	37.77	58.95	29.85	57.14	58.07	79.46	69.62	93.22	95.12	53.12	76.71	94.46	35.51	64.54
LCO-Embedding/LCO-Embedding-Omni-7B	40.43	65.67	31.10	60.62	61.15	81.32	71.75	95.52	96.33	58.08	80.07	96.86	39.20	67.55
Qwen/Qwen2.5-Omni-3B	0.53	0.12	0.74	0.44	0.53	0.54	0.16	0.14	0.37	0.16	0.31	0.79	0.12	0.38
Qwen/Qwen2.5-Omni-7B	0.57	0.11	0.62	0.46	0.50	0.60	0.11	0.16	0.54	0.13	0.42	0.64	0.13	0.38
Qwen/Qwen3-VL-Embedding-2B	40.46	57.32	29.16	68.72	58.01	81.95	78.74	96.89	98.36	63.76	80.51	98.11	43.94	68.92
Qwen/Qwen3-VL-Embedding-8B	45.29	69.84	29.29	72.87	62.80	84.16	80.70	98.75	98.70	66.42	83.43	98.80	52.45	**72.58**
Tevatron/OmniEmbed-v0.1	18.32	56.52	26.82	48.50	54.06	70.23	58.70	96.75	93.91	43.32	64.05	94.62	18.44	57.25
encord-team/ebind-audio-vision	44.85	59.33	32.03	58.92	67.41	86.07	**85.63**	60.06	67.09	65.10	82.92	93.61	41.60	64.97
encord-team/ebind-full	44.85	59.33	32.03	58.92	67.41	86.07	**85.63**	60.06	67.09	65.12	82.92	93.61	41.60	64.97
encord-team/ebind-points-vision	44.85	59.31	32.03	58.92	**67.47**	86.07	**85.63**	60.06	67.09	65.10	82.92	93.61	41.61	64.97
facebook/pe-av-base	21.83	54.84	31.19	50.32	56.36	72.38	57.19	93.35	93.97	56.89	78.27	94.84	18.70	60.01
facebook/pe-av-large	26.22	56.31	**34.96**	54.17	60.03	79.34	65.65	95.47	96.23	64.99	80.08	96.25	22.54	64.02
facebook/pe-av-small	22.91	53.86	29.77	49.14	56.44	73.33	62.02	92.89	94.91	57.25	77.91	95.12	17.80	60.26
jinaai/jina-embeddings-v5-omni-nano	0.50	0.10	0.57	0.61	0.50	0.72	0.15	0.14	0.44	0.14	0.48	0.53	0.15	0.39
jinaai/jina-embeddings-v5-omni-small	0.55	0.07	0.74	0.40	0.50	0.56	0.12	0.12	0.40	0.17	0.62	0.65	0.17	0.39
microsoft/xclip-base-patch16	23.48	28.85	18.02	33.69	39.72	60.27	42.60	39.35	48.92	25.86	56.92	70.64	6.52	38.06
microsoft/xclip-base-patch32	22.23	28.98	19.27	34.89	38.83	55.59	41.12	38.96	45.76	25.09	55.56	70.58	6.94	37.21
microsoft/xclip-large-patch14	27.74	29.22	18.27	34.57	42.24	63.53	46.62	46.06	52.66	24.59	59.22	74.57	9.89	40.71
VLM2Vec/VLM2Vec-V2.0	31.92	57.77	21.56	44.49	48.52	69.86	72.58	95.62	96.36	50.44	65.55	96.59	24.91	59.71
nvidia/omni-embed-nemotron-3b	25.72	39.81	18.47	36.44	28.29	34.45	49.87	90.13	93.13	31.85	46.80	94.20	10.91	46.16
zhibinlan/UME-R1-2B	34.51	59.88	29.95	59.35	57.25	79.51	71.39	92.62	93.15	56.19	74.47	96.20	37.04	64.73
zhibinlan/UME-R1-7B	44.68	69.13	31.67	63.81	62.39	82.34	77.51	97.17	96.89	62.39	80.23	98.57	42.66	69.96

Table 17: **Retrieval: Video → Text** (13 tasks, nDCG@10).

Model	AVMemeExam VA→T	AudioCapsAV VA→T	DiDeMo VA→T	MSRVTT VA→T	Panda70M VA→T	Shot2Story20K VA→T	VALOR32K VA→T	VATEX VA→T	VGGSoundAV VA→T	YouCook2 VA→T	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	47.49	35.38	53.01	61.97	–	96.82	59.75	76.61	96.92	31.20	62.13
Haon-Chen/e5-omni-3B	30.29	39.80	19.26	32.49	46.20	78.98	30.97	50.96	55.79	24.89	40.96
Haon-Chen/e5-omni-7B	51.23	47.48	**58.85**	**63.32**	77.32	**98.95**	60.87	**79.15**	**98.73**	50.74	**68.66**
LCO-Embedding/LCO-Embedding-Omni-3B	**59.26**	46.52	48.17	51.84	48.58	93.78	53.69	72.21	92.14	59.21	62.54
LCO-Embedding/LCO-Embedding-Omni-7B	58.13	49.29	47.32	54.74	50.77	96.01	55.81	75.49	94.66	**63.00**	64.52
Qwen/Qwen2.5-Omni-3B	0.78	0.59	0.49	0.61	0.15	0.15	0.16	0.41	0.48	0.12	0.39
Qwen/Qwen2.5-Omni-7B	0.63	0.60	0.44	0.38	0.12	0.18	0.11	0.46	0.77	0.15	0.39
Tevatron/OmniEmbed-v0.1	21.86	52.79	37.58	48.13	42.66	98.60	29.40	59.52	89.99	22.92	50.35
encord-team/ebind-audio-vision	42.51	45.59	51.59	62.30	**79.45**	52.46	64.62	78.48	90.96	35.35	60.33
encord-team/ebind-full	42.51	45.59	51.59	62.30	**79.45**	52.46	64.62	78.48	90.96	35.35	60.33
facebook/pe-av-base	22.00	55.23	44.52	55.16	50.35	90.79	**66.51**	76.41	95.99	16.43	57.34
facebook/pe-av-large	22.27	**59.58**	43.12	53.13	44.47	87.53	65.87	74.89	93.90	17.25	56.20
facebook/pe-av-small	23.24	55.30	42.43	56.61	54.48	91.00	63.82	76.94	95.44	16.34	57.56
jinaai/jina-embeddings-v5-omni-nano	22.99	32.19	5.71	16.00	5.64	46.51	8.00	9.20	29.00	9.86	18.51
jinaai/jina-embeddings-v5-omni-small	21.61	28.30	2.92	13.87	5.78	45.60	5.57	9.46	25.32	4.90	16.33
nvidia/omni-embed-nemotron-3b	39.41	23.41	30.52	33.32	47.90	94.54	34.88	46.98	94.30	21.71	46.70

Table 18: **Retrieval: Video+Audio → Text** (10 tasks, nDCG@10).

Model	AVMemeExam V→A	AudioCapsAV V→A	DiDeMo V→A	MSRVTT V→A	Shot2Story20K V→A	VALOR32K V→A	VATEX V→A	VGGSoundAV V→A	YouCook2 V→A	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	23.81	17.10	12.72	30.76	53.04	10.31	23.11	15.57	15.25	22.41
Haon-Chen/e5-omni-3B	28.58	26.08	22.06	28.64	56.15	14.64	34.72	29.69	13.40	28.22
Haon-Chen/e5-omni-7B	39.77	35.63	30.79	**50.78**	**83.98**	24.31	46.54	38.95	30.56	42.37
LCO-Embedding/LCO-Embedding-Omni-3B	40.58	35.05	28.08	41.72	75.14	23.29	43.80	38.02	29.31	39.44
LCO-Embedding/LCO-Embedding-Omni-7B	**45.32**	39.20	30.17	48.41	83.13	27.33	47.98	43.42	**35.59**	**44.51**
Qwen/Qwen2.5-Omni-3B	0.51	0.74	0.63	0.63	0.15	0.17	0.50	0.63	0.21	0.46
Qwen/Qwen2.5-Omni-7B	0.65	0.81	0.46	0.76	0.11	0.12	0.53	0.66	0.21	0.48
Tevatron/OmniEmbed-v0.1	29.58	32.90	26.98	40.81	57.37	20.27	38.47	35.12	12.06	32.62
encord-team/ebind-audio-vision	34.05	**81.40**	40.92	43.34	20.41	**50.98**	46.67	70.13	7.80	43.97
encord-team/ebind-full	34.05	**81.40**	40.92	43.34	20.41	**50.98**	46.67	70.13	7.80	43.97
facebook/pe-av-base	10.94	65.58	57.69	32.61	19.56	38.02	43.13	65.90	4.91	37.59
facebook/pe-av-large	12.17	71.60	**61.90**	37.98	24.64	41.94	**49.97**	**77.07**	7.02	42.70
facebook/pe-av-small	11.73	59.61	51.32	34.14	19.33	31.95	35.70	61.23	4.59	34.40
jinaai/jina-embeddings-v5-omni-nano	0.57	0.78	0.33	0.50	0.14	0.16	0.44	0.90	0.12	0.44
jinaai/jina-embeddings-v5-omni-small	0.51	0.68	0.53	0.40	0.15	0.17	0.56	0.74	0.13	0.43
nvidia/omni-embed-nemotron-3b	36.67	26.24	20.46	31.29	52.15	16.10	33.93	32.21	17.50	29.62

Table 19: **Retrieval: Video → Audio** (9 tasks, nDCG@10).

Model	AVMemeExam VT→A	AudioCapsAV VT→A	DiDeMo VT→A	MSRVTT VT→A	Shot2Story20K VT→A	VALOR32K VT→A	VATEX VT→A	VGGSoundAV VT→A	YouCook2 VT→A	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	44.79	21.77	12.64	36.19	78.07	11.70	25.44	21.59	25.31	30.83
Haon-Chen/e5-omni-3B	46.78	63.82	20.81	36.10	80.20	25.13	40.76	55.24	25.87	43.86
Haon-Chen/e5-omni-7B	59.34	66.39	30.33	**52.99**	**93.33**	33.40	**49.83**	63.13	44.64	**54.82**
LCO-Embedding/LCO-Embedding-Omni-3B	62.08	48.87	21.33	41.72	90.58	24.68	42.93	56.41	42.61	47.91
LCO-Embedding/LCO-Embedding-Omni-7B	**67.05**	55.86	25.89	48.54	93.11	30.79	48.88	61.81	51.81	53.75
Qwen/Qwen2.5-Omni-3B	1.11	1.13	0.77	0.59	0.21	0.13	1.19	0.34	0.51	0.66
Qwen/Qwen2.5-Omni-7B	1.40	0.71	0.58	0.50	0.18	0.17	0.76	1.04	0.33	0.63
Tevatron/OmniEmbed-v0.1	44.61	61.49	26.53	42.95	77.89	27.32	42.33	62.65	16.36	44.68
encord-team/ebind-audio-vision	34.87	**86.51**	35.78	41.65	17.78	50.34	40.15	63.30	5.29	41.74
encord-team/ebind-full	34.87	**86.51**	35.78	41.66	17.78	50.34	40.15	63.30	5.29	41.74
facebook/pe-av-base	16.53	80.49	39.34	25.89	22.85	48.12	36.93	81.94	2.08	39.35
facebook/pe-av-large	18.54	83.12	**49.84**	27.96	26.35	**52.42**	41.92	**87.55**	2.75	43.38
facebook/pe-av-small	16.87	78.72	37.94	24.49	21.67	44.04	29.11	81.58	1.76	37.35
jinaai/jina-embeddings-v5-omni-nano	26.04	41.42	5.66	16.85	48.32	9.57	11.90	34.62	8.93	22.59
jinaai/jina-embeddings-v5-omni-small	3.75	7.79	1.17	3.39	7.34	1.59	3.72	6.73	0.59	4.01
nvidia/omni-embed-nemotron-3b	53.19	38.01	20.57	35.97	81.36	20.12	37.68	45.35	35.98	40.91

Table 20: **Retrieval: Video+Text → Audio** (9 tasks, nDCG@10).

Model	AVMemeExam T→VA	AudioCapsAV T→VA	DiDeMo T→VA	MSRVTT T→VA	Panda70M T→VA	Shot2Story20K T→VA	VALOR32K T→VA	VATEX T→VA	VGGSoundAV T→VA	YouCook2 T→VA	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	53.22	30.86	57.43	64.16	–	98.16	59.48	77.93	96.87	36.89	63.89
Haon-Chen/e5-omni-3B	56.74	59.25	54.28	62.53	72.40	98.69	64.32	77.20	95.93	42.52	68.39
Haon-Chen/e5-omni-7B	64.51	52.92	**63.30**	**71.76**	**79.49**	**99.47**	72.08	**83.61**	**99.06**	**56.31**	**74.25**
LCO-Embedding/LCO-Embedding-Omni-3B	64.13	39.85	50.16	58.32	46.59	94.70	55.34	69.47	92.66	43.65	61.49
LCO-Embedding/LCO-Embedding-Omni-7B	**66.97**	43.67	51.19	61.55	48.62	95.38	59.09	73.85	94.21	52.71	64.72
Qwen/Qwen2.5-Omni-3B	1.21	0.54	0.46	0.66	0.12	0.18	0.19	0.47	0.62	0.15	0.46
Qwen/Qwen2.5-Omni-7B	0.54	0.54	0.46	0.33	0.16	0.15	0.17	0.31	0.78	0.14	0.36
Tevatron/OmniEmbed-v0.1	60.41	57.33	56.05	66.82	72.41	99.39	65.96	75.20	97.23	51.41	70.22
encord-team/ebind-audio-vision	44.34	44.12	50.97	62.76	76.03	53.00	63.25	76.08	90.76	28.94	59.03
encord-team/ebind-full	44.34	44.12	50.97	62.66	76.03	53.00	63.25	76.08	90.76	28.94	59.02
facebook/pe-av-base	25.52	60.92	45.50	58.41	58.01	93.36	**76.72**	78.35	97.17	15.40	60.94
facebook/pe-av-large	22.50	**61.62**	42.25	54.16	51.13	92.02	75.55	74.80	96.12	13.04	58.32
facebook/pe-av-small	26.04	59.89	45.55	55.35	62.04	93.52	76.39	78.08	96.68	15.18	60.87
jinaai/jina-embeddings-v5-omni-nano	23.26	32.76	5.36	15.76	6.34	42.46	8.87	10.34	25.67	8.70	17.95
jinaai/jina-embeddings-v5-omni-small	22.89	31.31	5.29	17.10	7.81	51.28	8.14	12.01	28.90	6.12	19.08
nvidia/omni-embed-nemotron-3b	29.05	23.25	31.13	31.81	24.38	94.80	39.95	17.04	94.47	5.47	39.13

Table 21: **Retrieval: Text → Video+Audio** (10 tasks, nDCG@10).

Model	AVEDataset audio + video	AVEDataset video	AVMeme audio + video	AVMeme video	Breakfast video	Diving48 video	HMDB51 video	HumAnimCartoon video	HumAnimCartoon audio + video	Kinetics400 video	Kinetics400 audio + video	Kinetics600 video	Kinetics600 audio + video	Kinetics700 video	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	**61.09**	**60.05**	54.33	46.33	43.14	5.91	63.22	93.33	**92.24**	66.57	**67.56**	68.23	**69.60**	57.02	56.89
Haon-Chen/e5-omni-3B	56.84	56.29	62.22	**52.56**	42.71	3.35	56.41	86.81	79.66	56.12	46.54	56.37	48.62	45.30	48.60
Haon-Chen/e5-omni-7B	58.66	57.11	59.67	48.67	40.63	3.72	59.03	87.43	86.19	59.90	58.43	60.35	59.66	49.33	52.23
LCO-Embedding/LCO-Embedding-Omni-3B	58.43	58.76	59.00	49.56	58.65	3.97	64.73	92.40	90.53	68.73	63.25	69.14	63.83	59.30	55.90
LCO-Embedding/LCO-Embedding-Omni-7B	60.00	58.38	**62.44**	49.56	59.33	4.56	66.26	93.33	89.91	70.01	65.03	70.75	67.26	60.36	**57.43**
Qwen/Qwen2.5-Omni-3B	22.39	14.05	43.89	28.78	12.69	2.43	13.02	26.25	19.10	0.25	0.25	0.93	0.65	0.44	14.19
Qwen/Qwen2.5-Omni-7B	23.61	9.85	37.78	30.56	15.01	2.15	10.49	22.22	24.54	0.25	0.25	0.38	0.81	0.20	14.17
Qwen/Qwen3-VL-Embedding-2B	–	58.83	–	49.22	62.78	4.61	67.09	93.32	–	69.38	–	70.04	–	60.14	54.98
Qwen/Qwen3-VL-Embedding-8B	–	58.71	–	49.89	**70.90**	4.02	**70.75**	**94.41**	–	71.40	–	71.63	–	60.87	56.81
Tevatron/OmniEmbed-v0.1	56.84	56.22	61.89	51.33	50.34	4.06	62.85	88.36	82.61	61.74	56.15	62.73	58.46	51.41	53.33
encord-team/ebind-audio-vision	59.20	58.53	60.67	44.78	38.09	5.07	61.92	88.36	79.97	64.27	43.59	63.83	43.20	54.44	50.83
encord-team/ebind-full	59.20	58.53	60.67	44.78	38.09	5.07	61.92	88.36	79.97	64.27	43.59	63.83	43.20	54.44	50.83
encord-team/ebind-points-vision	–	58.53	–	44.78	38.09	5.07	61.92	88.36	–	64.27	–	63.83	–	54.44	50.05
facebook/pe-av-base	59.75	57.59	57.56	36.44	49.43	2.95	43.19	76.39	80.60	59.60	53.70	61.03	55.15	51.02	50.13
facebook/pe-av-large	59.15	57.59	57.11	42.22	50.56	4.36	52.39	83.85	83.69	62.72	53.20	63.47	53.91	42.85	50.73
facebook/pe-av-small	58.78	57.11	56.00	39.44	46.19	4.12	42.93	80.44	84.01	60.02	53.08	60.21	54.17	50.70	50.21
facebook/vjepa2-vitg-fpc32-384-diving48	–	42.96	–	41.78	30.47	5.86	51.98	69.10	–	33.32	–	32.93	–	22.98	38.13
facebook/vjepa2-vitg-fpc64-256	–	42.14	–	39.11	28.17	6.74	49.70	67.08	–	32.11	–	31.95	–	21.92	37.70
facebook/vjepa2-vitg-fpc64-384	–	42.29	–	41.33	35.99	5.86	49.65	66.92	–	31.87	–	31.50	–	22.03	37.46
facebook/vjepa2-vitg-fpc64-384-ssv2	–	42.29	–	41.33	35.99	5.86	49.65	66.92	–	31.87	–	31.50	–	22.03	37.46
facebook/vjepa2-vith-fpc64-256	–	39.35	–	40.56	28.17	6.49	42.16	68.02	–	25.55	–	26.25	–	17.86	33.29
facebook/vjepa2-vitl-fpc16-256-ssv2	–	45.32	–	40.33	24.06	6.48	69.89		–	32.46	–	33.38	–	22.93	36.12
facebook/vjepa2-vitl-fpc32-256-diving48	–	44.68	–	39.89	25.63	6.82	47.37	68.65	–	32.32	–	32.63	–	22.52	35.98
facebook/vjepa2-vitl-fpc64-256	–	44.38	–	40.33	30.95	6.50	45.61	70.04	–	31.74	–	32.06	–	22.36	35.89
jinaai/jina-embeddings-v5-omni-nano	47.46	5.10	57.67	25.89	8.78	1.96	5.65	19.88	38.52	0.54	7.87	0.22	6.98	0.20	16.95
jinaai/jina-embeddings-v5-omni-small	48.66	5.17	57.00	26.67	8.54	1.75	5.15	22.20	37.11	0.25	7.92	0.30	6.89	0.21	17.20
microsoft/xclip-base-patch16	–	55.65	–	41.00	30.02	6.88	66.76	85.56	–	76.44	–	69.80	–	55.22	50.61
microsoft/xclip-base-patch32	–	54.38	–	39.00	22.15	6.88	62.70	82.62	–	70.89	–	63.80	–	48.81	47.44
microsoft/xclip-large-patch14	–	58.53	–	42.56	40.64	**7.37**	67.82	85.87	–	**83.31**	–	**76.59**	–	**63.62**	53.97
VLM2Vec/VLM2Vec-V2.0	–			46.22	30.48	3.27	17.49	88.52	–	56.28	–	55.47	–	44.40	45.98
nvidia/omni-embed-nemotron-3b	59.60	56.89	59.44	50.67	34.64	3.09	57.21	88.67	85.57	57.71	56.49	58.11	57.82	46.45	51.81
zhibinlan/UME-R1-2B	–	56.87	–	48.78	46.65	3.62	58.35	88.36	–	61.87	–	62.07	–	51.69	50.26
zhibinlan/UME-R1-7B	–	57.61	–	50.22	43.41	3.73	59.29	92.55	–	63.00	–	63.75	–	52.89	50.74

Table 22: **Classification** (28 tasks, accuracy), part 1 of 2.

Model	Kinetics700 audio + video	MELD audio + video	MELD video	MusicAVQA audio + video	MusicAVQA video	RAVDESS audio + video	RAVDESS video	SSv2 video	UCF101 audio + video	UCF101 video	VGGSound audio + video	VGGSound video	WorldSense audio + video	WorldSense video	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	58.10	18.21	15.09	56.97	56.09	56.88	51.53	13.37	93.89	94.19	47.36	49.85	67.92	64.76	56.89
Haon-Chen/e5-omni-3B	15.10	16.89	15.13	51.35	49.47	29.44	31.60	10.32	83.34	88.62	39.94	47.07	66.09	66.76	48.60
Haon-Chen/e5-omni-7B	48.67	17.58	15.33	53.40	51.81	29.65	32.92	13.06	91.13	91.91	42.58	52.84	67.62	65.04	52.23
LCO-Embedding/LCO-Embedding-Omni-3B	53.13	23.29	16.41	59.61	61.61	19.17	38.33	13.02	88.38	92.99	48.39	54.64	67.72	68.10	55.90
LCO-Embedding/LCO-Embedding-Omni-7B	56.07	25.10	15.77	59.15	58.73	28.75	43.19	17.23	88.80	94.27	48.14	56.80	68.96	69.34	57.43
Qwen/Qwen2.5-Omni-3B	0.52	19.68	14.25	12.90	7.56	21.81	23.33	0.59	14.31	14.26	0.32	4.75	42.70	35.24	14.19
Qwen/Qwen2.5-Omni-7B	0.58	14.50	15.06	8.91		28.61	24.38	0.59	15.74	15.87	0.32	0.32	37.25	43.27	14.17
Qwen/Qwen3-VL-Embedding-2B	–	–	15.33	–	60.61	–	45.28	13.46	–	93.45	47.00	–	–	69.15	54.98
Qwen/Qwen3-VL-Embedding-8B	–	–	14.40	–	62.37	–	48.96	17.49	–	94.46	48.30	–	–	70.49	56.81
Tevatron/OmniEmbed-v0.1	46.80	19.68	14.50	50.41	52.05	44.72	36.46	14.68	90.11	92.17	42.88	50.74	67.43	65.52	53.33
encord-team/ebind-audio-vision	33.69	16.21	15.48	54.45	57.62	32.29	28.47	11.37	84.10	93.53	47.38	50.33	64.65	67.62	50.83
encord-team/ebind-full	33.69	16.21	15.48	54.45	57.62	32.29	28.47	11.37	84.10	93.52	47.38	50.33	64.65	67.62	50.83
encord-team/ebind-points-vision	–	–	15.48	–	57.62	–	28.47	11.37	–	93.52	47.38	–	–	67.62	50.05
facebook/pe-av-base	45.25	15.23	13.77	55.04	55.92	35.90	36.53	6.91	81.13	84.54	44.69	53.53	64.46	66.38	50.13
facebook/pe-av-large	44.02	16.16	10.79	53.28	54.28	33.06	32.85	8.49	85.04	90.73	45.47	52.68	62.55	63.99	50.73
facebook/pe-av-small	44.41	15.04	13.87	53.46	54.75	38.47	32.99	6.69	84.81	88.17	43.85	52.21	64.18	65.90	50.21
facebook/vjepa2-vitg-fpc32-384-diving48	–	–	15.72	–	41.85	–	39.31	14.86	–	84.57	27.08	–	–	55.30	38.13
facebook/vjepa2-vitg-fpc64-256	–	–	15.48	–	41.97	–	38.26	15.65	–	83.29	26.31	–	–	53.39	37.70
facebook/vjepa2-vitg-fpc64-384	–	–	15.33	–	41.74	–	36.11	15.63	–	83.35	26.08	–	–	53.68	37.46
facebook/vjepa2-vitg-fpc64-384-ssv2	–	–	15.33	–	41.74	–	36.11	15.63	–	83.35	26.08	–	–	53.68	37.46
facebook/vjepa2-vith-fpc64-256	–	–	14.85	–	21.92	–	34.72	13.98	–	78.03	22.52	–	–	52.14	33.29
facebook/vjepa2-vitl-fpc16-256-ssv2	–	–	16.16	–	31.54	–	33.89	14.29	–	80.68	26.14	–	–	53.10	36.12
facebook/vjepa2-vitl-fpc32-256-diving48	–	–	15.24	–	32.59	–	33.75	14.00	–	81.28	25.76	–	–	52.52	35.98
facebook/vjepa2-vitl-fpc32-256	–	–	16.02	–	32.47	–	29.72	13.76	–	81.38	25.90	–	–	51.96	35.89
jinaai/jina-embeddings-v5-omni-nano	5.62	16.99	13.04	38.28	4.45	21.04	14.79	1.29	27.54	3.38	0.82	27.00	55.01	18.53	16.95
jinaai/jina-embeddings-v5-omni-small	3.29	17.58	10.79	38.98	5.04	22.43	15.49	0.72	31.38	3.07	0.32	26.95	59.40	20.43	17.20
microsoft/xclip-base-patch16	–	–	15.19	–	56.27	–	45.49	8.60	–	94.50	41.45	–	–	60.93	50.61
microsoft/xclip-base-patch32	–	–	13.96	–	49.35	–	45.56	7.26	–	91.97	38.64	–	–	61.13	47.44
microsoft/xclip-large-patch14	–	–	16.89	–	59.32	–	47.78	9.53	–	96.11	45.95	–	–	61.61	53.97
VLM2Vec/VLM2Vec-V2.0	–	–	16.50	–	49.53	–	26.04	13.59	–	88.65	41.17	–	–	64.08	45.98
nvidia/omni-embed-nemotron-3b	45.05	18.50	13.91	53.34	56.97	42.01	36.81	10.03	87.11	88.81	42.90	51.62	67.81	63.51	51.81
zhibinlan/UME-R1-2B	–	–	16.41	–	51.06	–	43.96	11.33	–	91.08	44.71	–	–	67.43	50.26
zhibinlan/UME-R1-7B	–	–	14.99	–	50.18	–	40.83	13.67	–	91.27	45.95	–	–	68.58	50.74

Table 23: **Classification** (28 tasks, accuracy), part 2 of 2.

Model	AVEDataset video	AVEDataset audio + video	AVMeme audio + video	AVMeme video	Breakfast video	HMDB51 video	HumAnimCartoon audio + video	HumAnimCartoon video	Kinetics400 audio + video	Kinetics400 video	Kinetics600 audio + video	Kinetics600 video	Kinetics700 audio + video	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	84.33	85.57	27.78	21.56	27.71	48.30	92.39	91.93	59.17	58.02	58.81	57.06	50.23	54.09
Haon-Chen/e5-omni-3B	76.87	64.93	19.78	12.78	31.64	40.78	85.40	89.75	46.31	55.84	43.16	54.30	33.43	43.18
Haon-Chen/e5-omni-7B	84.33	78.36	19.78	16.00	26.79	47.25	88.04	88.20	61.33	61.33	60.47	51.62	35.89	53.36
LCO-Embedding/LCO-Embedding-Omni-3B	88.81	91.29	27.78	21.89	43.19	52.94	90.99	91.61	65.43	69.31	63.90	67.65	55.70	55.56
LCO-Embedding/LCO-Embedding-Omni-7B	88.81	90.80	28.78	21.78	45.03	57.71	92.70	93.32	67.86	71.19	68.47	71.41	60.17	58.26
Qwen/Qwen2.5-Omni-3B	1.49	3.48	8.44	5.00	11.32	1.96	12.89	13.04	0.35	0.25	0.17	0.16	0.13	4.82
Qwen/Qwen2.5-Omni-7B	1.49	0.50	14.89	14.89	10.39	1.96	13.82	13.82	0.25	0.25	0.18	0.20	0.16	8.39
Qwen/Qwen3-VL-Embedding-2B	91.04	–	–	20.78	50.81	60.26	–	94.41	–	66.96	–	66.53	–	56.91
Qwen/Qwen3-VL-Embedding-8B	89.55	–	–	17.44	52.42	64.31	–	95.19	–	71.09	–	70.92	–	59.82
Tevatron/OmniEmbed-v0.1	75.62	57.71	15.22	15.33	26.56	43.20	86.96	85.09	50.24	57.75	47.92	56.91	39.40	44.85
encord-team/ebind-audio-vision	92.54	94.03	26.00	21.67	34.41	56.60	90.37	93.79	66.83	72.59	65.52	72.43	58.11	58.11
encord-team/ebind-full	92.54	94.03	26.00	21.67	34.41	56.60	90.37	93.79	66.83	72.59	65.52	72.43	58.11	58.11
encord-team/ebind-points-vision	92.54	–	–	21.67	34.41	56.60	–	93.79	–	72.59	–	72.43	–	57.95
facebook/pe-av-base	90.80	91.54	25.33	19.89	27.48	39.22	89.75	90.53	69.89	71.76	69.89	72.48	59.31	52.73
facebook/pe-av-large	88.81	87.06	19.33	18.67	30.25	45.03	88.51	93.63	64.96	75.72	65.17	75.86	53.86	52.56
facebook/pe-av-small	85.57	90.55	20.11	15.22	32.10	38.95	87.58	89.60	70.51	72.49	70.86	72.78	58.91	53.51
jinaai/jina-embeddings-v5-omni-nano	3.98	60.95	22.56	13.89	10.16	2.48	39.60	16.30	6.48	0.33	5.30	0.16	4.33	14.73
jinaai/jina-embeddings-v5-omni-small	3.73	62.19	23.78	14.89	11.55	1.83	37.42	14.60	5.98	0.25	4.74	0.18	3.58	15.54
microsoft/xclip-base-patch16	69.65	–	–	20.78	26.56	46.54	–	84.63	–	78.62	–	60.56	–	48.88
microsoft/xclip-base-patch32	71.64	–	–	15.22	22.86	44.05	–	85.09	–	73.74	–	58.03	–	46.92
microsoft/xclip-large-patch14	73.38	–	–	17.78	32.33	47.39	–	86.34	–	83.20	–	65.51	–	51.17
VLM2Vec/VLM2Vec-V2.0	76.87	–	–	20.33	32.79	42.42	–	84.94	–	52.79	–	50.39	–	44.88
nvidia/omni-embed-nemotron-3b	59.45	62.44	17.78	14.78	31.41	35.03	87.58	83.85	36.80	35.89	33.89	31.12	28.40	38.52
zhibinlan/UME-R1-2B	83.08	–	–	18.78	36.95	51.11	–	92.70	–	62.75	–	60.62	–	52.21
zhibinlan/UME-R1-7B	85.82	–	–	22.00	39.26	50.39	–	94.72	–	65.96	–	65.63	–	53.99

Table 24: **Zero-shot classification** (26 tasks, accuracy), part 1 of 2.

Model	Kinetics700 video	MELD audio + video	MELD video	MusicAVQA audio + video	MusicAVQA video	RAVDESS audio + video	RAVDESS video	UCF101 audio + video	UCF101 video	VGGSound audio + video	VGGSound video	WorldSense audio + video	WorldSense video	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	48.91	25.59	19.68	55.63	57.09	42.29	40.49	78.40	78.09	40.72	39.21	59.60	57.78	54.09
Haon-Chen/e5-omni-3B	45.31	11.77	7.86	52.99	57.21	28.68	22.01	66.98	70.37	28.28	31.48	20.82	24.07	43.18
Haon-Chen/e5-omni-7B	52.05	30.27	31.40	59.09	60.26	25.35	25.97	83.80	83.49	45.18	41.91	53.10	47.09	53.36
LCO-Embedding/LCO-Embedding-Omni-3B	59.79	21.29	15.28	60.49	62.66	21.53	20.83	78.19	81.12	46.50	44.84	52.53	49.00	55.56
LCO-Embedding/LCO-Embedding-Omni-7B	63.07	16.94	11.23	63.66	64.89	28.12	32.78	83.95	84.26	50.02	45.53	53.20	53.20	58.26
Qwen/Qwen2.5-Omni-3B	0.13	10.06	1.90	3.17	1.76	13.33	13.33	2.47	2.21	0.28	0.32	5.64	12.13	4.82
Qwen/Qwen2.5-Omni-7B	0.16	12.65	46.04	5.16	5.16	13.33	13.33	3.03	2.16	0.22	0.37	31.04	12.80	8.39
Qwen/Qwen3-VL-Embedding-2B	58.44	–	38.62	–	63.48	–	26.46	–	85.24	–	44.60	–	29.13	56.91
Qwen/Qwen3-VL-Embedding-8B	62.04	–	24.80	–	66.24	–	35.35	–	91.51	–	47.39	–	49.28	59.82
Tevatron/OmniEmbed-v0.1	47.44	14.31	11.67	52.64	57.97	15.21	20.07	60.19	71.50	13.97	30.06	53.77	50.72	44.85
encord-team/ebind-audio-vision	65.52	12.35	17.53	63.31	65.47	29.79	27.64	75.41	79.37	52.29	49.58	65.52	62.18	58.11
encord-team/ebind-full	65.52	12.35	17.53	63.31	65.47	29.79	27.64	75.41	79.37	52.29	49.58	65.52	62.18	58.11
encord-team/ebind-points-vision	65.52	–	17.53	63.31	65.47	–	27.64	–	79.37	–	49.58	–	62.18	57.95
facebook/pe-av-base	61.46	18.90	17.48	56.68	57.27	25.35	29.17	70.83	77.21	41.72	37.61	29.89	29.61	52.73
facebook/pe-av-large	64.83	13.18	12.65	58.44	59.09	16.18	18.33	77.21	86.27	40.64	42.35	30.75	39.83	52.56
facebook/pe-av-small	61.60	19.09	26.22	59.14	58.79	36.18	19.24	80.25	79.89	39.17	36.48	31.90	38.20	53.51
jinaai/jina-embeddings-v5-omni-nano	0.20	28.76	17.53	39.10	8.03	18.06	6.67	15.48	1.59	15.15	0.25	37.44	8.31	14.73
jinaai/jina-embeddings-v5-omni-small	0.16	22.80	10.89	39.39	8.79	25.07	6.60	14.97	1.75	14.93	0.30	45.85	27.79	15.54
microsoft/xclip-base-patch16	48.07	–	16.16	–	53.93	–	34.38	–	75.15	–	29.95	–	39.35	48.88
microsoft/xclip-base-patch32	44.91	–	10.74	–	52.64	–	28.06	–	74.28	–	27.95	–	47.66	46.92
microsoft/xclip-large-patch14	54.19	–	21.00	–	55.98	–	34.03	–	80.61	–	33.09	–	31.52	51.17
VLM2Vec/VLM2Vec-V2.0	42.88	–	7.96	–	58.21	–	7.22	–	66.72	–	32.29	–	52.53	44.88
nvidia/omni-embed-nemotron-3b	26.58	10.60	9.91	31.13	26.44	46.04	32.92	59.88	56.64	22.86	19.27	50.05	50.72	38.52
zhibinlan/UME-R1-2B	52.44	–	25.34	–	61.31	–	28.75	–	76.23	–	41.56	–	39.26	52.21
zhibinlan/UME-R1-7B	56.99	–	16.65	–	62.43	–	34.17	–	83.02	–	44.44	–	34.38	53.99

Table 25: **Zero-shot classification** (26 tasks, accuracy), part 2 of 2.

Model	AVEDataset audio + video	AVEDataset video	HMDB51 video	MELDEmotion audio + video	MELDEmotion video	MELDSpeaker audio + video	MELDSpeaker video	MusicAVQA audio + video	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	80.77	79.54	69.89	0.84	0.81	31.51	31.58	33.39	45.17
Haon-Chen/e5-omni-3B	82.66	79.43	69.56	1.66	1.01	27.04	30.05	41.17	43.63
Haon-Chen/e5-omni-7B	80.59	75.96	68.70	1.85	0.80	30.91	32.58	41.22	43.25
LCO-Embedding/LCO-Embedding-Omni-3B	**87.38**	**85.49**	72.83	7.30	0.96	20.03	31.06	**46.73**	46.65
LCO-Embedding/LCO-Embedding-Omni-7B	87.31	83.77	73.82	**8.75**	1.21	21.60	32.67	45.95	46.49
Qwen/Qwen2.5-Omni-3B	44.07	37.29	39.89	2.26	**1.96**	16.17	17.67	9.62	20.58
Qwen/Qwen2.5-Omni-7B	41.08	37.65	38.06	2.06	1.87	15.95	17.12	12.86	20.91
Qwen/Qwen3-VL-Embedding-2B	–	83.18	72.58	–	1.01	–	28.78	–	50.07
Qwen/Qwen3-VL-Embedding-8B	–	84.02	**75.47**	–	1.46	–	31.33	–	**51.30**
Tevatron/OmniEmbed-v0.1	81.23	75.80	71.14	1.96	1.26	27.89	29.55	39.31	43.94
encord-team/ebind-audio-vision	83.68	83.73	72.04	1.78	1.15	**36.72**	**41.51**	38.42	45.34
encord-team/ebind-full	83.68	83.73	72.04	1.78	1.15	**36.72**	**41.51**	38.42	45.34
encord-team/ebind-points-vision	–	83.73	72.04	–	1.15	–	**41.51**	–	47.82
facebook/pe-av-base	82.48	80.79	58.41	2.11	1.85	28.27	22.48	43.04	41.91
facebook/pe-av-large	80.51	81.04	64.07	2.11	1.81	29.31	24.18	41.30	42.83
facebook/pe-av-small	81.18	77.13	57.09	2.07	1.76	28.49	22.71	43.74	41.52
facebook/vjepa2-vitg-fpc32-384-diving48	–	51.68	55.68	–	1.34	–	22.39	–	32.66
facebook/vjepa2-vitg-fpc64-256	–	51.38	55.02	–	1.39	–	23.01	–	32.54
facebook/vjepa2-vitg-fpc64-384	–	49.88	54.76	–	1.07	–	22.68	–	31.80
facebook/vjepa2-vitg-fpc64-384-ssv2	–	49.88	54.76	–	1.07	–	22.68	–	31.80
facebook/vjepa2-vith-fpc64-256	–	46.63	51.88	–	1.07	–	22.69	–	29.12
facebook/vjepa2-vitl-fpc16-256-ssv2	–	57.77	58.07	–	1.13	–	23.61	–	34.52
facebook/vjepa2-vitl-fpc32-256-diving48	–	57.90	56.53	–	1.17	–	23.73	–	34.35
facebook/vjepa2-vitl-fpc64-256	–	57.01	55.76	–	1.22	–	24.00	–	34.28
jinaai/jina-embeddings-v5-omni-nano	56.22	27.41	34.21	2.17	1.84	16.59	17.11	22.95	20.66
jinaai/jina-embeddings-v5-omni-small	60.81	28.58	33.63	1.63	1.48	16.53	17.14	25.81	22.28
microsoft/xclip-base-patch16	–	75.87	72.76	–	1.07	–	29.35	–	45.62
microsoft/xclip-base-patch32	–	73.71	70.88	–	1.09	–	26.34	–	43.89
microsoft/xclip-large-patch14	–	79.20	73.29	–	1.25	–	31.85	–	46.20
VLM2Vec/VLM2Vec-V2.0	–	73.02	67.71	–	0.95	–	32.05	–	42.19
nvidia/omni-embed-nemotron-3b	85.14	79.40	68.54	1.52	1.02	27.27	30.21	39.40	43.89
zhibinlan/UME-R1-2B	–	78.02	69.47	–	0.96	–	32.40	–	44.74
zhibinlan/UME-R1-7B	–	78.19	68.90	–	1.21	–	33.61	–	44.71

Table 26: **Clustering** (15 tasks, v-measure), part 1 of 2.

Model	MusicAVQA video	RAVDESS audio + video	RAVDESS video	UCF101 audio + video	UCF101 video	WS-1m-Domain audio + video	WS-1m-Domain video	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	32.75	18.95	21.57	**93.09**	94.05	**46.67**	42.09	45.17
Haon-Chen/e5-omni-3B	34.66	7.27	7.96	87.53	91.33	44.45	48.70	43.63
Haon-Chen/e5-omni-7B	36.86	3.71	3.45	90.55	91.58	45.26	44.69	43.25
LCO-Embedding/LCO-Embedding-Omni-3B	48.44	7.41	17.60	88.44	93.75	46.02	46.32	46.65
LCO-Embedding/LCO-Embedding-Omni-7B	39.93	7.90	20.80	88.37	94.14	44.96	46.19	46.49
Qwen/Qwen2.5-Omni-3B	8.63	6.62	7.92	38.92	38.54	27.56	11.60	20.58
Qwen/Qwen2.5-Omni-7B	9.72	9.18	7.35	37.81	36.58	27.26	19.06	20.91
Qwen/Qwen3-VL-Embedding-2B	44.15	–	**24.89**	–	93.81	–	**52.14**	50.07
Qwen/Qwen3-VL-Embedding-8B	**48.95**	–	22.16	–	**95.14**	–	51.90	**51.30**
Tevatron/OmniEmbed-v0.1	35.88	10.97	10.65	90.23	92.39	45.45	45.34	43.94
encord-team/ebind-audio-vision	44.33	11.20	1.37	82.86	93.06	42.89	45.39	45.34
encord-team/ebind-full	44.33	11.20	1.37	82.86	93.06	42.89	45.39	45.34
encord-team/ebind-points-vision	44.33	–	1.37	–	93.06	–	45.39	47.82
facebook/pe-av-base	43.58	7.09	10.67	79.72	80.74	42.75	44.66	41.91
facebook/pe-av-large	42.52	6.03	11.53	85.88	87.70	41.13	43.33	42.83
facebook/pe-av-small	41.32	6.81	8.99	82.00	84.64	41.76	43.07	41.52
facebook/vjepa2-vitg-fpc32-384-diving48	21.44	–	5.42	–	76.47	–	26.87	32.66
facebook/vjepa2-vitg-fpc64-256	21.93	–	6.24	–	75.72	–	25.66	32.54
facebook/vjepa2-vitg-fpc64-384	20.83	–	5.04	–	74.60	–	25.53	31.80
facebook/vjepa2-vitg-fpc64-384-ssv2	20.83	–	5.04	–	74.60	–	25.53	31.80
facebook/vjepa2-vith-fpc64-256	9.84	–	5.95	–	71.42	–	23.48	29.12
facebook/vjepa2-vitl-fpc16-256-ssv2	25.43	–	6.86	–	78.72	–	24.57	34.52
facebook/vjepa2-vitl-fpc32-256-diving48	25.69	–	7.25	–	78.54	–	23.98	34.35
facebook/vjepa2-vitl-fpc64-256	25.70	–	6.95	–	78.01	–	25.58	34.28
jinaai/jina-embeddings-v5-omni-nano	5.74	15.59	0.96	46.53	29.80	27.14	5.61	20.66
jinaai/jina-embeddings-v5-omni-small	5.37	**22.32**	1.16	52.60	31.22	30.10	5.82	22.28
microsoft/xclip-base-patch16	44.89	–	10.62	–	93.84	–	36.57	45.62
microsoft/xclip-base-patch32	40.62	–	11.14	–	92.38	–	34.96	43.89
microsoft/xclip-large-patch14	48.60	–	8.17	–	94.64	–	32.63	46.20
VLM2Vec/VLM2Vec-V2.0	32.41	–	0.17	–	88.91	–	42.31	42.19
nvidia/omni-embed-nemotron-3b	40.96	8.19	10.92	88.66	90.87	45.53	40.70	43.89
zhibinlan/UME-R1-2B	29.62	–	14.93	–	90.27	–	42.26	44.74
zhibinlan/UME-R1-7B	30.15	–	8.79	–	91.27	–	45.54	44.71

Table 27: **Clustering** (15 tasks, v-measure), part 2 of 2.

Model	AVEDataset audio + video	AVEDataset video	AVSpeakerBench video	HumAnimCartoon audio + video	HumAnimCartoon video	MELD audio + video	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	96.11	95.80	95.89	**84.93**	85.70	53.44	73.85
Haon-Chen/e5-omni-3B	96.14	94.52	97.09	77.29	82.14	51.19	72.03
Haon-Chen/e5-omni-7B	94.70	93.90	98.01	80.71	84.29	**54.34**	72.38
LCO-Embedding/LCO-Embedding-Omni-3B	95.60	**97.03**	97.46	82.75	87.74	53.40	74.31
LCO-Embedding/LCO-Embedding-Omni-7B	95.21	96.11	97.43	81.39	85.91	53.69	73.91
Qwen/Qwen2.5-Omni-3B	68.69	61.45	78.62	52.44	54.49	53.69	57.99
Qwen/Qwen2.5-Omni-7B	61.64	57.79	75.73	51.50	53.11	51.57	56.47
Qwen/Qwen3-VL-Embedding-2B	–	96.16	96.65	–	**88.35**	–	**75.02**
Qwen/Qwen3-VL-Embedding-8B	–	95.32	97.07	–	86.75	–	74.45
Tevatron/OmniEmbed-v0.1	94.45	93.39	98.04	75.94	81.81	52.82	72.32
encord-team/ebind-audio-vision	**96.25**	95.67	**99.15**	73.35	78.18	49.27	71.93
encord-team/ebind-full	**96.25**	95.67	**99.15**	73.35	78.18	49.27	71.93
encord-team/ebind-points-vision	–	95.67	**99.15**	–	78.18	–	72.51
facebook/pe-av-base	90.83	92.82	98.01	76.32	75.24	52.59	72.12
facebook/pe-av-large	90.69	92.67	98.23	76.45	79.24	54.24	72.01
facebook/pe-av-small	91.56	93.24	98.23	76.02	76.54	53.10	71.99
facebook/vjepa2-vitg-fpc32-384-diving48	–	78.76	94.08	–	68.60	–	66.27
facebook/vjepa2-vitg-fpc64-256	–	77.60	93.38	–	68.08	–	66.16
facebook/vjepa2-vitg-fpc64-384	–	75.42	92.84	–	67.56	–	65.28
facebook/vjepa2-vitg-fpc64-384-ssv2	–	75.42	92.84	–	67.56	–	65.28
facebook/vjepa2-vith-fpc64-256	–	73.52	94.14	–	68.76	–	64.52
facebook/vjepa2-vitl-fpc16-256-ssv2	–	81.53	93.36	–	70.05	–	66.25
facebook/vjepa2-vitl-fpc32-256-diving48	–	81.82	93.49	–	71.38	–	66.61
facebook/vjepa2-vitl-fpc64-256	–	82.84	93.80	–	72.85	–	67.19
jinaai/jina-embeddings-v5-omni-nano	80.88	53.25	71.96	55.29	51.47	49.88	57.35
jinaai/jina-embeddings-v5-omni-small	76.29	54.96	80.49	54.09	52.38	50.43	57.87
microsoft/xclip-base-patch16	–	91.61	96.94	–	74.86	–	72.80
microsoft/xclip-base-patch32	–	90.92	96.36	–	74.74	–	72.27
microsoft/xclip-large-patch14	–	90.64	97.31	–	77.33	–	73.07
VLM2Vec/VLM2Vec-V2.0	–	91.96	97.06	–	81.30	–	71.48
nvidia/omni-embed-nemotron-3b	94.54	92.91	97.56	79.28	82.86	53.16	72.49
zhibinlan/UME-R1-2B	–	95.16	97.37	–	82.12	–	73.51
zhibinlan/UME-R1-7B	–	96.04	98.29	–	84.05	–	73.75

Table 28: **Pair classification** (12 tasks, max-AP), part 1 of 2.

Model	MELD video	MusicAVQA audio + video	MusicAVQ video	RAVDESSAV audio + video	RAVDESSAV video	Vinoground video	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	51.74	72.57	72.23	**62.39**	63.59	51.83	73.85
Haon-Chen/e5-omni-3B	51.13	76.73	72.14	56.78	56.83	52.36	72.03
Haon-Chen/e5-omni-7B	52.82	73.92	71.15	55.11	56.67	52.92	72.38
LCO-Embedding/LCO-Embedding-Omni-3B	50.61	**78.64**	79.98	55.55	59.83	53.10	74.31
LCO-Embedding/LCO-Embedding-Omni-7B	50.69	77.87	76.18	56.30	62.57	53.52	73.91
Qwen/Qwen2.5-Omni-3B	52.66	54.91	55.05	56.50	56.30	51.06	57.99
Qwen/Qwen2.5-Omni-7B	53.03	54.98	55.09	57.71	54.70	50.77	56.47
Qwen/Qwen3-VL-Embedding-2B	52.19	–	78.55	–	60.18	53.02	**75.02**
Qwen/Qwen3-VL-Embedding-8B	52.79	–	77.18	–	59.77	52.27	74.45
Tevatron/OmniEmbed-v0.1	51.00	73.41	72.84	61.38	59.57	53.14	72.32
encord-team/ebind-audio-vision	50.54	77.43	77.20	59.34	55.45	51.36	71.93
encord-team/ebind-full	50.54	77.43	77.20	59.34	55.45	51.36	71.93
encord-team/ebind-points-vision	50.54	–	77.20	–	55.45	51.36	72.51
facebook/pe-av-base	**54.62**	75.17	76.26	58.11	62.45	52.99	72.12
facebook/pe-av-large	54.20	74.04	76.77	57.56	57.52	52.55	72.01
facebook/pe-av-small	52.72	74.61	75.62	59.52	58.89	53.87	71.99
facebook/vjepa2-vitg-fpc32-384-diving48	52.75	–	62.81	–	56.22	50.68	66.27
facebook/vjepa2-vitg-fpc64-256	51.91	–	62.88	–	54.15	**55.09**	66.16
facebook/vjepa2-vitg-fpc64-384	51.76	–	61.80	–	53.78	53.82	65.28
facebook/vjepa2-vitg-fpc64-384-ssv2	51.76	–	61.80	–	53.78	53.82	65.28
facebook/vjepa2-vith-fpc64-256	52.35	–	55.33	–	54.35	53.21	64.52
facebook/vjepa2-vitl-fpc16-256-ssv2	51.73	–	62.83	–	54.52	49.72	66.25
facebook/vjepa2-vitl-fpc32-256-diving48	51.70	–	63.26	–	54.91	49.72	66.61
facebook/vjepa2-vitl-fpc64-256	51.51	–	63.52	–	54.20	51.60	67.19
jinaai/jina-embeddings-v5-omni-nano	51.23	62.85	49.63	60.66	50.67	50.38	57.35
jinaai/jina-embeddings-v5-omni-small	51.05	63.17	49.51	60.02	50.52	51.49	57.87
microsoft/xclip-base-patch16	49.98	–	78.18	–	**63.66**	54.37	72.80
microsoft/xclip-base-patch32	50.35	–	76.46	–	63.29	53.80	72.27
microsoft/xclip-large-patch14	49.42	–	**81.33**	–	62.31	53.11	73.07
VLM2Vec/VLM2Vec-V2.0	51.49	–	69.64	–	54.46	54.48	71.48
nvidia/omni-embed-nemotron-3b	52.21	76.04	73.26	58.96	57.69	51.38	72.49
zhibinlan/UME-R1-2B	51.41	–	72.60	–	62.56	53.37	73.51
zhibinlan/UME-R1-7B	51.30	–	72.33	–	60.85	53.39	73.75

Table 29: **Pair classification** (12 tasks, max-AP), part 2 of 2.

Model	AVMemeExam audio + video	AVMemeExam video	AVQA audio + video	AVQA video	AVSpeakerBench audio + video	AVSpeakerBench video	DailyOmni audio + video	DailyOmni video	EgoSchema video	NExTQA video	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	36.44	31.89	79.15	77.96	29.17	28.58	27.84	27.43	55.80	46.32	40.36
Haon-Chen/e5-omni-3B	37.44	35.67	72.64	75.46	29.61	29.67	32.86	31.86	45.40	51.76	42.65
Haon-Chen/e5-omni-7B	41.67	38.00	79.59	77.96	32.16	31.35	34.87	32.94	43.80	58.31	46.22
LCO-Embedding/LCO-Embedding-Omni-3B	40.00	38.56	83.50	82.30	**34.00**	33.41	42.89	**36.96**	56.40	66.47	49.77
LCO-Embedding/LCO-Embedding-Omni-7B	**42.22**	**40.11**	**85.67**	83.17	33.84	34.34	**43.90**	36.71	57.00	70.80	**51.81**
Qwen/Qwen2.5-Omni-3B	26.67	27.33	24.86	24.32	26.99	25.96	24.08	23.33	14.40	21.15	25.19
Qwen/Qwen2.5-Omni-7B	23.78	23.00	24.00	26.06	24.66	25.28	23.49	23.58	13.20	19.13	23.91
Qwen/Qwen3-VL-Embedding-2B	–	38.11	–	81.98	–	32.04	–	29.43	**63.40**	55.29	44.76
Qwen/Qwen3-VL-Embedding-8B	–	37.44	–	**83.50**	–	32.56	–	31.02	56.80	58.61	46.09
Tevatron/OmniEmbed-v0.1	32.56	33.44	67.32	68.73	28.71	29.14	28.85	27.59	50.20	41.99	37.53
encord-team/ebind-audio-vision	32.44	30.67	80.02	73.18	29.08	29.76	26.92	26.67	31.40	43.30	36.37
encord-team/ebind-full	32.44	30.67	80.02	73.18	29.08	29.76	26.92	26.67	31.40	43.30	36.37
encord-team/ebind-points-vision	–	30.67	–	73.18	–	29.76	–	26.67	31.40	43.30	35.91
facebook/pe-av-base	27.22	27.67	49.29	49.19	26.21	26.68	28.76	28.34	30.60	34.04	30.48
facebook/pe-av-large	29.78	28.89	41.04	42.56	26.25	26.40	28.18	27.01	29.20	33.84	30.74
facebook/pe-av-small	27.78	27.44	45.71	46.80	26.56	26.87	27.34	26.92	27.80	35.45	30.01
jinaai/jina-embeddings-v5-omni-nano	32.78	28.78	50.38	26.28	26.81	24.44	25.50	27.51	24.40	32.63	29.72
jinaai/jina-embeddings-v5-omni-small	38.11	22.67	47.77	28.77	26.43	21.51	25.92	25.17	21.20	25.18	28.30
microsoft/xclip-base-patch16	–	31.22	–	65.91	–	27.40	–	26.42	28.40	42.60	33.85
microsoft/xclip-base-patch32	–	29.67	–	64.71	–	25.47	–	26.76	30.80	41.49	34.69
microsoft/xclip-large-patch14	–	31.44	–	70.79	–	25.16	–	25.75	29.20	43.20	34.83
VLM2Vec/VLM2Vec-V2.0	–	33.89	–	72.31	–	31.10	–	27.26	55.80	44.91	41.72
nvidia/omni-embed-nemotron-3b	32.89	29.89	62.54	65.91	29.61	29.05	30.60	29.10	46.60	37.36	38.25
zhibinlan/UME-R1-2B	–	36.89	–	81.65	–	29.05	–	27.76	57.60	54.48	43.47
zhibinlan/UME-R1-7B	–	37.56	–	80.35	–	30.70	–	30.69	60.80	58.71	46.97

Table 30: **Question answering** (20 tasks, accuracy), part 1 of 2.

Model	OmniVideoBench audio + video	OmniVideoBench video	PerceptionTest audio + video	PerceptionTest video	VideoMME-Short audio + video	VideoMME-Short video	WorldQA audio + video	WorldQA video	WS-1m audio + video	WS-1m video	Avg.
BidirLM/BidirLM-Omni-2.5B-Embedding	26.92	26.92	44.46	44.67	40.89	41.11	–	38.37	32.00	30.95	40.36
Haon-Chen/e5-omni-3B	27.31	28.29	42.54	47.76	48.89	53.78	48.30	50.21	32.86	30.75	42.65
Haon-Chen/e5-omni-7B	27.11	26.52	54.48	53.30	54.22	55.44	53.87	54.17	38.01	36.68	46.22
LCO-Embedding/LCO-Embedding-Omni-3B	**32.81**	**32.81**	54.80	55.76	61.33	59.22	56.33	55.66	36.68	35.44	49.77
LCO-Embedding/LCO-Embedding-Omni-7B	31.63	30.84	**59.91**	**61.51**	**64.67**	**62.22**	**59.93**	**57.77**	**41.07**	**38.97**	**51.81**
Qwen/Qwen2.5-Omni-3B	23.58	24.36	34.54	35.50	22.78	23.33	25.67	27.89	23.21	23.88	25.19
Qwen/Qwen2.5-Omni-7B	25.74	25.15	36.57	33.58	22.11	21.11	18.12	18.36	26.27	24.93	23.91
Qwen/Qwen3-VL-Embedding-2B	–	26.72	–	46.05	–	46.56	–	43.12	–	29.70	44.76
Qwen/Qwen3-VL-Embedding-8B	–	27.31	–	51.60	–	52.22	–	44.37	–	31.52	46.09
Tevatron/OmniEmbed-v0.1	26.52	25.93	42.00	40.41	40.22	40.11	34.23	37.85	27.98	26.74	37.53
encord-team/ebind-audio-vision	23.77	22.20	45.42	43.82	34.11	34.00	35.11	34.04	25.41	25.98	36.37
encord-team/ebind-full	23.77	22.20	45.42	43.82	34.11	34.00	35.11	34.04	25.41	25.98	36.37
encord-team/ebind-points-vision	–	22.20	–	43.82	–	34.00	–	34.04	–	25.98	35.91
facebook/pe-av-base	24.95	25.15	36.67	36.35	28.44	28.00	25.94	28.17	24.07	23.78	30.48
facebook/pe-av-large	24.56	26.33	42.32	43.50	28.78	29.00	26.40	27.44	25.79	27.51	30.74
facebook/pe-av-small	23.77	23.58	33.79	33.69	29.11	30.11	27.38	28.81	25.41	25.98	30.01
jinaai/jina-embeddings-v5-omni-nano	23.97	26.33	41.58	41.05	27.89	26.56	27.47	30.79	26.46	22.92	29.72
jinaai/jina-embeddings-v5-omni-small	25.34	24.36	41.90	36.89	27.67	22.56	29.66	24.76	27.89	22.16	28.30
microsoft/xclip-base-patch16	–	22.40	–	39.87	–	30.33	–	31.03	–	26.74	33.85
microsoft/xclip-base-patch32	–	26.52	–	42.11	–	29.89	–	34.65	–	29.51	34.69
microsoft/xclip-large-patch14	–	24.16	–	42.43	–	31.33	–	34.90	–	24.74	34.83
VLM2Vec/VLM2Vec-V2.0	–	29.08	–	42.75	–	47.78	–	40.07	–	34.00	41.72
nvidia/omni-embed-nemotron-3b	26.13	25.15	40.73	41.26	40.33	40.22	48.20	48.33	29.51	31.52	38.25
zhibinlan/UME-R1-2B	–	25.15	–	43.60	–	45.11	–	44.40	–	32.47	43.47
zhibinlan/UME-R1-7B	–	26.72	–	54.16	–	56.22	–	47.20	–	33.62	46.97

Table 31: **Question answering** (20 tasks, accuracy), part 2 of 2.

Model	Zero-shot %	# Overlap	Overlapping tasks
BidirLM-Omni-2.5B-Embedding	100%	0	—
e5-omni-3B	100%	0	—
e5-omni-7B	100%	0	—
LCO-Embedding-Omni-3B	100%	0	—
LCO-Embedding-Omni-7B	100%	0	—
Qwen2.5-Omni-3B[†]	NA	NA	—
Qwen2.5-Omni-7B[†]	NA	NA	—
Qwen3-VL-Embedding-2B[†]	NA	NA	—
Qwen3-VL-Embedding-8B[†]	NA	NA	—
Tevatron OmniEmbed-v0.1	100%	0	—
VLM2Vec-V2.0[†]	NA	NA	—
ebind-audio-vision	83%	4	AudioCapsAVVA2T, AudioCapsAVVT2A, VALOR32KT2VA, VGGSoundAVA2V
ebind-full	83%	4	AudioCapsAVVA2T, AudioCapsAVVT2A, VALOR32KT2VA, VGGSoundAVA2V
ebind-points-vision	100%	0	—
pe-av-base	65%	8	ActivityNetCaptionsT2V, AudioCapsAVVA2T, AudioCapsAVVT2A, HMDB51ZeroShot, Kinetics700VA, MSVDT2V, VALOR32KT2VA, VGGSoundAVA2V
pe-av-large	65%	8	ActivityNetCaptionsT2V, AudioCapsAVVA2T, AudioCapsAVVT2A, HMDB51ZeroShot, Kinetics700VA, MSVDT2V, VALOR32KT2VA, VGGSoundAVA2V
pe-av-small	65%	8	ActivityNetCaptionsT2V, AudioCapsAVVA2T, AudioCapsAVVT2A, HMDB51ZeroShot, Kinetics700VA, MSVDT2V, VALOR32KT2VA, VGGSoundAVA2V
vjepa2-vitg-fpc32-384-diving48	96%	1	Kinetics700VA
vjepa2-vitg-fpc64-256	96%	1	Kinetics700VA
vjepa2-vitg-fpc64-384	96%	1	Kinetics700VA
vjepa2-vitg-fpc64-384-ssv2	96%	1	Kinetics700VA
vjepa2-vith-fpc64-256	96%	1	Kinetics700VA
vjepa2-vitl-fpc16-256-ssv2	96%	1	Kinetics700VA
vjepa2-vitl-fpc32-256-diving48	96%	1	Kinetics700VA
vjepa2-vitl-fpc64-256	96%	1	Kinetics700VA
jina-embeddings-v5-omni-nano[†]	NA	NA	—
jina-embeddings-v5-omni-small[†]	NA	NA	—
xclip-base-patch16	100%	0	—
xclip-base-patch32	100%	0	—
xclip-large-patch14	100%	0	—
omni-embed-nemotron-3b	100%	0	—
UME-R1-2B	65%	8	BreakfastClassification, HMDB51ZeroShot, Kinetics700VA, MSVDT2V, UCF101VideoAudioClassification, VATEXV2A, VATEXVA2T, YouCook2T2VA
UME-R1-7B	65%	8	BreakfastClassification, HMDB51ZeroShot, Kinetics700VA, MSVDT2V, UCF101VideoAudioClassification, VATEXV2A, VATEXVA2T, YouCook2T2VA

Table 32: Disclosed train-evaluation overlap on MVEB. [†]Training data not disclosed at dataset granularity; we cannot certify zero-shot status for these models, so the Zero-shot % and # Overlap columns are reported as NA rather than 100% / 0.

Model family	Video	Audio cap
Variable-length: fps=2, max_frames=64		
LCO-Embedding-Omni 3B/7B	fps=2, max=64	uncapped[†]
e5-omni 3B/7B	fps=2, max=64	uncapped[†]
BidirLM-Omni-2.5B	fps=2, max=64	30 s
OmniEmbed-v0.1 (Tevatron)	fps=2, max=64	uncapped[†]
OmniEmbed-Nemotron-3B	fps=2, max=64	~128 s
Qwen2.5-Omni 3B/7B	fps=2, max=64	300 s
Jina-Embeddings-v5-omni nano/small	fps=2, max=64	30 s
UME-R1 2B/7B	fps=2, max=64	— (no audio)
VLM2Vec-V2.0	fps=2, max=64	— (no audio)
PE-AV (variable-length)	fps=2, max=64	30 s
Fixed-length: uniform sampling		
X-CLIP base-patch16/32, large-patch14	8 frames	— (no audio)
PE-AV (fixed-length, 16-frame)	16 frames	30 s
eBind (full / audio-vision / points)	8 frames	uncapped[†]
V-JEPA-2 (fpc16/32/64 variants)	16/32/64 frames	— (no audio)
Processor-managed: model's own sampler		
Qwen3-VL-Embedding 2B/8B	processor-managed	— (no audio)

Table 34: Per-model video and audio sampling configuration. "Variable-length" models sample at fps=2 with a hard cap of max_frames=64 to bound peak GPU memory; "fixed-length" models sample the exact number of frames their training pipeline expects; Qwen3-VL-Embedding uses the Qwen processor's internal vision sampler (controlled by pixel budgets rather than frame count). [†]Uncapped models delegate audio truncation to the model's own processor.

Table 35: Per-dataset audio delta ($\Delta = \text{score}_{\text{va}} - \text{score}_{\text{v}}$), sorted by mean delta within each annotation group. AV-grounded datasets had labels produced from both audio and visual content; V-grounded datasets had labels produced from visuals alone, even though the source clips often carry audio (see Table 9). N counts model–dataset pairs with results for both task variants.

Dataset	Task type	$\bar{\Delta}$	σ	N
AV-grounded datasets				
AudioCaps-AV	Retrieval	+0.151	0.093	14
AVMeme-Exam	Classification	+0.126	0.041	14
AVMeme-Exam	Retrieval	+0.063	0.090	14
VGGSound	Classification	+0.062	0.031	14
YouCook2	Retrieval	+0.056	0.107	14
AVMeme-Exam	ZS Classification	+0.040	0.024	14
MELD	Classification	+0.036	0.026	14
RAVDESS-AV	ZS Classification	+0.030	0.061	14
AVE-Dataset	Clustering	+0.029	0.023	14
AVE-Dataset	Classification	+0.025	0.038	14
Daily-Omni	QA	+0.016	0.022	14
AVMeme-Exam	QA	+0.014	0.016	14
WorldSense	Clustering	+0.013	0.054	14
MUSIC-AVQA	Clustering	+0.008	0.039	14
AVQA	QA	+0.006	0.032	14
VGGSound	ZS Classification	+0.004	0.052	14
WorldSense	QA	+0.003	0.013	14
OmniVideoBench	QA	+0.002	0.009	14
WorldSense	Classification	+0.001	0.035	14
AV-SpeakerBench	QA	−0.000	0.006	14
MUSIC-AVQA	Classification	−0.000	0.030	14
PerceptionTest	QA	−0.001	0.020	14
WorldSense	ZS Classification	−0.001	0.071	14
Video-MME	QA	−0.001	0.017	14
RAVDESS-AV	Classification	−0.003	0.078	14
WorldQA	QA	−0.006	0.016	13
VALOR-32K	Retrieval	−0.008	0.071	14
MUSIC-AVQA	ZS Classification	−0.011	0.024	14
Shot2Story20K	Retrieval	−0.012	0.040	14
MELD	ZS Classification	−0.012	0.104	14
AVE-Dataset	ZS Classification	−0.014	0.064	14
RAVDESS-AV	Clustering	−0.014	0.062	14
MELD	Clustering	−0.019	0.053	14
VGGSound-AV-Ret.	Retrieval	−0.035	0.087	14
V-grounded datasets				
Human-Animal-Cartoon	ZS Classification	−0.010	0.024	14
Human-Animal-Cartoon	Classification	−0.027	0.043	14
MSR-VTT	Retrieval	−0.030	0.057	14
VATEX	Retrieval	−0.032	0.044	14
UCF101-51VA	Clustering	−0.033	0.035	14
Kinetics-400	ZS Classification	−0.034	0.039	14
UCF101-51VA	Classification	−0.037	0.032	14
Kinetics-600	ZS Classification	−0.037	0.045	14
Kinetics-700-2020	ZS Classification	−0.039	0.045	14
Kinetics-600	Classification	−0.059	0.070	14
Kinetics-400	Classification	−0.065	0.069	14
Kinetics-700-2020	Classification	−0.070	0.098	14
DiDeMo	Retrieval	−0.072	0.049	14
Panda-70M	Retrieval	−0.102	0.089	13

Table 36: Cross-modal retrieval scores ($\bar{s}$) averaged across 14 models, for datasets that have v2a (video-to-audio) and a2v (audio-to-video) retrieval task variants. High scores indicate that video and audio embeddings are well-aligned, making explicit audio information more likely redundant. *YouCook2* has the lowest cross-modal alignment and gains $\Delta = +0.056$ in the paired v/va comparison, consistent with spoken narration providing information not recoverable from visual frames alone. By contrast, *VGGSound-AV-Ret.* has high alignment yet yields $\Delta = -0.035$, indicating the video embedding already captures the acoustic structure of these clips.

Dataset	Dir.	$\bar{s}$	σ	N
AVMeme-Exam	a2v	0.259	0.130	14
AVMeme-Exam	v2a	0.249	0.150	14
AudioCaps-AV	a2v	0.381	0.296	14
AudioCaps-AV	v2a	0.410	0.271	14
DiDeMo	a2v	0.285	0.211	14
DiDeMo	v2a	0.304	0.190	14
MSR-VTT	a2v	0.350	0.160	14
MSR-VTT	v2a	0.332	0.153	14
Shot2Story20K	a2v	0.449	0.327	14
Shot2Story20K	v2a	0.404	0.290	14
VALOR-32K	a2v	0.246	0.201	14
VALOR-32K	v2a	0.250	0.165	14
VATEX	a2v	0.394	0.204	14
VATEX	v2a	0.351	0.164	14
VGGSound-AV-Ret.	a2v	0.395	0.283	14
VGGSound-AV-Ret.	v2a	0.413	0.251	14
YouCook2	a2v	0.162	0.121	14
YouCook2	v2a	0.133	0.113	14

Table 37: Per-model mean audio delta ($\bar{\Delta}$) across 48 paired task groups for the 14 audio-capable models in our roster. A positive $\bar{\Delta}$ indicates the model benefits on average from the audio track; a negative value indicates the audio channel hurts performance. N counts dataset–task pairs evaluated.

Model	$\bar{\Delta}$	σ	N
BidirLM-Omni-2.5B-Embedding	+0.023	0.036	46
omni-embed-nemotron-3b	+0.020	0.042	48
e5-omni-7B	+0.019	0.052	48
Qwen2.5-Omni-3B	+0.013	0.042	48
pe-av-small	+0.008	0.062	48
Qwen2.5-Omni-7B	+0.007	0.063	48
pe-av-base	+0.006	0.058	48
LCO-Embedding-Omni-7B	+0.002	0.082	48
LCO-Embedding-Omni-3B	−0.002	0.080	48
OmniEmbed-v0.1	−0.016	0.074	48
pe-av-large	−0.021	0.069	48
ebind-audio-vision	−0.023	0.072	48
ebind-full	−0.023	0.072	48
e5-omni-3B	−0.039	0.099	48

Table 38: Pairwise Spearman correlation ρ across the eight retrieval directions, computed across the audio-capable models in our roster. Each cell reports ρ over the models that have results in both directions. Higher ρ means models that rank well on one direction also rank well on the other (the two directions measure overlapping capabilities). Bold cells: $|\rho| > 0.85$.

	$T{\to}V$	$V{\to}T$	$A{\to}V$	$V{\to}A$	$AT{\to}V$	$VA{\to}T$	$VT{\to}A$	$T{\to}VA$
$T{\to}V$	1.00	0.74	0.50	0.59	0.53	0.70	0.88	0.92
$V{\to}T$		1.00	0.71	0.86	0.81	0.96	0.82	0.66
$A{\to}V$			1.00	0.87	0.90	0.63	0.65	0.38
$V{\to}A$				1.00	0.94	0.75	0.74	0.43
$AT{\to}V$					1.00	0.72	0.64	0.39
$VA{\to}T$						1.00	0.73	0.68
$VT{\to}A$							1.00	0.77
$T{\to}VA$								1.00