Advancing Radiograph Representation Learning with Masked Record Modeling

Abstract

Modern studies in radiograph representation learning (R^2L) rely on either self-supervision to encode invariant semantics or associated radiology reports to incorporate medical expertise, while the complementarity between them is barely noticed. To explore this, we formulate the self- and report-completion as two complementary objectives and present a unified framework based on masked record modeling (MRM). In practice, MRM reconstructs masked image patches and masked report tokens following a multi-task scheme to learn knowledge-enhanced semantic representations. With MRM pre-training, we obtain pre-trained models that can be well transferred to various radiography tasks. Specifically, we find that MRM offers superior performance in label-efficient fine-tuning. For instance, MRM achieves 88.5% mean AUC on CheXpert using 1% labeled data, outperforming previous R^2L methods with 100% labels. On NIH ChestX-ray, MRM outperforms the best performing counterpart by about 3% under small labeling ratios. Besides, MRM surpasses self- and report-supervised pre-training in identifying the pneumonia type and the pneumothorax area, sometimes by large margins.

1 Introduction

Radiograph representation learning (R^2L) has been among the core problems of medical image analysis. Previously, downstream radiograph analysis tasks counts on pre-trained models on ImageNet (Deng et al., 2009) or large X-ray datasets (Wang et al., 2017; Irvin et al., 2019; Johnson et al., 2019; Bustos et al., 2020) to alleviate the shortage of expert labeling. The emergence of self-supervised representation learning (Doersch et al., 2015; Agrawal et al., 2015; Wang & Gupta, 2015) provides a choice to conduct pre-training with negligible human intervention by exploiting self-supervision. However, the self-supervised paradigm ignores the introduction of medical expertise (e.g., anatomy), reducing its transferability to downstream tasks with limited label information.

Figure 1: Illustration. MRM learns transferable radiograph representations via reconstructing masked records, i.e., masked radiograph patches and masked reports tokens.

On the other hand, free-text radiology reports written by experienced radiologists often contain rich domain knowledge. To leverage this, researchers developed automated rule-based labelers (Wang et al., 2017; Irvin et al., 2019) to extract structured labels from unstructured texts. Nevertheless, these labelers have several practical limitations. First, some procedures of the label extraction workflow, such as rulemaking and natural language processing, still require the intensive involvement of experts and engineers. Besides, the developed labelers can hardly adapt to new scenarios due to the fixed rules and lexicons.

Against this background, report-supervised R^2L was proposed (Zhang et al., 2020) to acquire supervision from radiology reports. In practice, this paradigm leverages words and sentences in free-text reports as supervision to guide deep neural networks to learn radiograph representations, outper-

forming the archetypical label- and self-supervised pre-training by observable margins in various downstream tasks (Zhang et al., 2020; Zhou et al., 2022). The report-supervised R^2L highlights the importance of the incorporation of domain knowledge. This differs from the self-supervised paradigm, which focuses on learning invariant semantic representations. Nonetheless, current studies view the self- and report-supervised R^2L as separate, discrete choices, preventing their combinations.

Driven by this analysis, we present a unified framework base on masked record modeling (MRM), where the self- and report-completion tasks are modeled as two complementary objectives. Specifically, masked image reconstruction integrates semantics into pre-trained models, while masked report restoration facilitates the incorporation of medical expertise. As a result, MRM learns knowledge-enhanced semantic representations that generalize well. In practice, MRM masks random patches and tokens from the input radiograph and associated radiology report with high masking ratios. Following a multi-task scheme, MRM asks the radiography pre-trained model to learn visual representations that can not only reconstruct the missing patches but also restore the missing tokens from the non-masked token embeddings along with mask tokens.

With MRM pre-training, we can train radiography models on MIMIC-CXR (Johnson et al., 2019) with improved generalization performance. With a pre-trained ViT-B/16 model, we achieve 88.5% mean AUC when fine-tuned on CheXpert (Irvin et al., 2019) with only 1% labels. This outperforms all previous counterparts with 100% labeled data. On NIH ChestX-ray (Wang & Gupta, 2015), MRM surpasses the report-supervised paradigm by about 3% when the labeling ratios are 1% and 10%. On pneumonia identification tasks, MRM outperforms self- and report-supervised baselines, sometimes by substantial margins. These observations help verify the effectiveness of MRM in learning more transferable radiograph representations.

2 RELATED WORK

2.1 REPORT-SUPERVISED RADIOGRAPH REPRESENTATION LEARNING

Recently, report-supervised learning (Zhang et al., 2020; Liao et al., 2021; Huang et al., 2021; Zhou et al., 2022; Boecking et al., 2022) emerges as a new R^2L paradigm that automatically acquires supervision from free-text radiology reports. Zhang et al. (2020) proposed ConVIRT to contrast the radiograph features with latent embeddings of sentences in radiology reports. Liao et al. (2021) and Huang et al. (2021) explored the alignment between local patches and words in the report. Zhou et al. (2022) presented a Transformer-based R^2L framework that conducts autoregressive report modeling and study-report matching. Report-supervised R^2L takes the advantage of label-supervised learning, which is the incorporation of domain knowledge. Compared to the self-supervised paradigm, report-supervised R^2L lays no emphasis on learning semantically invariant representations. To address the discrepancy between them, we formalize self- and report-completion as two complementary objectives, based on which we propose to encode both semantics and medical expertise into latent representations following a multi-task scheme.

2.2 VISUAL REPRESENTATION LEARNING VIA IMAGE-LANGUAGE PRE-TRAINING

Learning visual representations from image-language pairs has achieved tremendous success in natural image tasks (Sariyildiz et al., 2020; Desai & Johnson, 2021; Radford et al., 2021; Mu et al., 2021; Li et al., 2021; Geng et al., 2022; Wang et al., 2022; Chen et al., 2022; Singh et al., 2022; Yu et al., 2022; Dou et al., 2022). Similar to ConVIRT (Zhang et al., 2020), image-language contrast has been widely adopted to conduct pre-training (Radford et al., 2021; Mu et al., 2021; Li et al., 2021; Yu et al., 2022; Dou et al., 2022; Gao et al., 2022). Nowadays, efforts have been made to train a unified encoder for vision and language data (Geng et al., 2022; Wang et al., 2022; Chen et al., 2022; Geng et al., 2022). Akin to our approach, SLIP (Mu et al., 2021) combines SimCLR (Chen et al., 2020) and CLIP (Radford et al., 2021) to train a vision encoder using image-language pairs. However, SLIP only slightly outperforms SimCLR in fine-tuning, while requiring large batch sizes and tens of millions of image-language pairs for pre-training. In contrast, our MRM surpasses various self-supervised methodologies by large margins and can be pre-trained using only hundreds of thousands of radiograph-report pairs, enabling effective medical visual representation learning with limited annotations and computing resources.

Figure 2: OVERVIEW. During the pre-training stage, MRM requires the image encoder to provide radiograph representations to simultaneously support the restoration of masked radiograph patches and masked associated radiology report tokens. The masked language and image modeling losses are only calculated on image and report tokens highlighted in pink . **Embed.**, **LR**, and **HR** stand for embeddings, low-resolution, and high-resolution, respectively.

3 MASKED RECORD MODELING

We propose MRM (i.e., Masked Record Modeling) to learns radiograph representations using record-level supervision. As the name implies, MRM acquires supervision signals from both radiographs and associated radiology reports. The motivation behind is to learn knowledge-enhanced semantic latent representations by reconstructing masked radiograph patches and masked radiology report tokens in medical records.

Fig. 2 presents an overview of MRM. We first apply random masking to each low-resolution radiograph and its associated radiology report (with different high masking ratios). Then, we forward the obtained non-masked image patches to the image encoder to acquire non-masked image patch embeddings. These embeddings serve two purposes: (**i**) assist non-masked report tokens to restore the masked report tokens; (**ii**) restore the high-resolution masked radiograph patches. To achieve the first goal, we add the globally averaged radiograph representation to each non-masked report token embedding and pass the resulting hybrid representations to the report decoder for masked report restoration. As for the second purpose, we conduct a novel patch restoration task to explicitly encode more local details into radiograph representations by reconstructing high-resolution patches from low-resolution inputs.

3.1 REPORT COMPREHENSION

Masked report generation. In our scenario, each radiology report is associated with a radiograph. To convert the free-text report into tokens, we use WordPiece (Wu et al., 2016) as the default tokenizer, whose vocabulary has approximately 30k tokens. After tokenization, we randomly mask a number of report tokens with [MASK]. Compared to BERT (Devlin et al., 2018) that randomly masks 15% tokens, we use a 50% probability of masking each token in the report. The insight behind the use of a higher masking ratio is that we want the model to lean more upon the image embeddings to finish the report-completion task.

Hybrid representations for storing multi-modal information. We then transform non-masked report tokens into token embeddings using a simple lookup table, which stores randomly initialized embeddings of a fixed dictionary and size. In practice, we retrieve embeddings using indices. Then,

the global embedding of the associated radiograph is added to each non-masked token embedding. The resulting non-masked hybrid embeddings are supposed to include the multi-modal information from the radiograph and associated radiology report, which ought to be helpful for restoring the masked tokens.

Masked report restoration. To reconstruct the masked tokens, we forward latent embeddings of both hybrid tokens and mask tokens to the report decoder (a light-weight transformer model), where fixed (i.e., unlearnable) positional embeddings are added to encode the position information. We train the report decoder using the masked language modeling objective.

3.2 RADIOGRAPH UNDERSTANDING

Masked image generation with low resolution. We propose to learn radiograph representations by reconstructing high-resolution radiograph patches from low-resolution inputs. The motivation behind is to encode more local information into latent embeddings via super-resolution imaging. As shown in Fig. 2, we sub-sample each high-resolution radiograph by a factor of two to generate a low-resolution input. Following He et al. (2022), we split low-resolution radiograph into non-overlapping image patches, where 75% patches are randomly masked.

Radiograph representations. We add fixed unlearnable positional embeddings to linearly transformed non-masked image patches. Next, we forward the resulting patch embeddings to the transformer-based image encoder, which produces non-masked image patch embeddings. Then, the global average pooling (GAP) is applied to all non-masked embeddings, whereby a global feature is obtained. Here, we hypothesize that the image-level information brought by the global feature is helpful to the restoration of masked report tokens. Based on this hypothesis, we duplicate and add the global feature to each non-masked report token embedding, producing the hybrid token embeddings that encode the multi-modal information.

Masked image restoration with high resolution. Non-masked image and mask token representations with added positional embeddings are passed to the image decoder for the restoration of masked radiograph patches. Specifically, the image decoder is required to restore a high-resolution ($2\times$ the input resolution) patch from each input token via a shared fully-connected (FC) layer (across all tokens). In practice, the proposed restoration procedure explicitly requires the learned image representations to include more local details that often matter a lot in medical diagnosis.

3.3 MULTI-TASK MODELING

Suppose each input radiograph consists of two set $\mathcal{I}_\mathcal{M}$ and $\mathcal{I}_\mathcal{N}$. The masked set $\mathcal{I}_\mathcal{M}=\{\mathbf{x}_1,\ldots,\mathbf{x}_h\}$ (ground truths) contains h high-resolution image patches that serve as reconstruction targets. The non-masked set $\mathcal{I}_\mathcal{N}=\{\mathbf{s}_1,\ldots,\mathbf{s}_k\}$ comprises k low-resolution patches that are treated as model inputs. Likewise, we denote the associated radiology report using the masked set $\mathcal{R}_\mathcal{M}=\{\mathbf{u}_1,\ldots,\mathbf{u}_p\}$ (ground truths) and the non-masked set $\mathcal{R}_\mathcal{N}=\{\mathbf{v}_1,\ldots,\mathbf{v}_q\}$ (inputs). Here, $\mathbf{x}$, $\mathbf{s}$, $\mathbf{u}$, and $\mathbf{v}$ stand for the masked image patch, non-masked image patch, masked report token, and non-masked report token, respectively. For model parameters, we use Θ_E, Θ_D, and Θ_R to denote the parameters of the image encoder, image decoder, and report decoder, respectively.

For the restoration of masked report tokens, we forward hybrid representations to the report decoder and minimize the negative log-likelihood function. During the training stage, the objective function $\mathcal{L}_\mathrm{R}$ (i.e., the MLM loss in Fig. 2) of the above optimization procedure can be summarized as follows:

$$\mathcal{L}_\mathrm{R}(\mathcal{R}_\mathcal{M},\mathcal{R}_\mathcal{N},\mathcal{I}_\mathcal{N}) = -\sum_{i=1}^{p} \log P\left(\mathbf{u}_i \mid \mathbf{v}_{1:q}, \mathbf{s}_{1:k};\ \Theta_E,\Theta_R\right), \qquad (1)$$

where P stands for the conditional probability. We ignore the mask tokens for simplicity.

Similarly, we can formalize the objective function of the high-resolution masked radiograph restoration (cf. the MIM loss in Fig. 2) as follows:

$$\mathcal{L}_\mathrm{I}(\mathcal{I}_\mathcal{M},\mathcal{I}_\mathcal{N}) = \mathrm{MSE}\left(f_{\Theta_D}(f_{\Theta_E}(\mathbf{s}_{1:k})), \mathbf{x}_{1:h}\right). \qquad (2)$$

In practice, we adopt the mean squared error (MSE) to measure the differences between the predicted and ground-truth image patches with high resolution, where all pixel values are normalized to [0, 1].

The total multi-task training objective function (to be minimized) of the multi-modal restoration is as follows:

$$\mathcal{L}(\mathcal{R}_{\mathcal{M}}, \mathcal{R}_{\mathcal{N}}, \mathcal{I}_{\mathcal{M}}, \mathcal{I}_{\mathcal{N}}) = \mathcal{L}_{\mathrm{R}}(\mathcal{R}_{\mathcal{M}}, \mathcal{R}_{\mathcal{N}}, \mathcal{I}_{\mathcal{N}}) + \lambda \mathcal{L}_{\mathrm{I}}(\mathcal{I}_{\mathcal{M}}, \mathcal{I}_{\mathcal{N}}) \tag{3}$$

where λ is a hyper-parameter that controls the relative impacts of two objective functions. After pre-training, we can transfer the weight parameters of the image encoder (i.e., Θ_E) to various downstream tasks for fine-tuning.

4 EXPERIMENTS

In this section, we mainly compare MRM against report- and self-supervised R^2L methodologies on 5 well-established public datasets. The pre-trained models are evaluated on several types of downstream applications, including chest pathology identification, pneumothorax segmentation, and pneumonia type classification. Besides MRM, we also report the experimental results of 9 baseline approaches. Results of ablation experiments are presented to investigate and demonstrate the impacts of different modules in MRM. Average results are reported over three training runs.

4.1 MIMIC-CXR FOR PRE-TRAINING

We conduct pre-training on MIMIC-CXR (Johnson et al., 2019), one of the largest X-ray datasets, that contains more than 370,000 radiograph images from over 220,000 patient studies. Each radiograph is paired with one associated radiology report, and they will be passed to the MRM as a pair of inputs. As a result, there are over 370,000 radiograph-report pairs available in MIMIC-CXR. Note that we scale down the short side of all radiographs to 512 while keeping their aspect radios unchanged in pre-processing.

4.2 DATASETS FOR FINE-TUNING

We validate the transferability of learned radiograph representations on X-ray based classification and segmentation tasks via end-to-end fine-tuning. Specifically, we evaluate the pre-trained model on 4 X-ray datasets in the classification tasks, which are NIH ChestX-ray (Wang et al., 2017), CheXpert (Irvin et al., 2019), RSNA Pneumonia (Shih et al., 2019), and COVID-19 Image Data Collection (Cohen et al., 2020). For the segmentation task, we fine-tune the pre-trained model on SIIM-ACR Pneumothorax Segmentation.[1]

CheXpert introduces a multi-label classification problem on chest X-rays. We follow the official guideline (Irvin et al., 2019) and report the model performance on 5 selected pathologies, i.e., atelectasis, cardiomegaly, consolidation, edema, and pleural effusion. Considering the official test set of CheXpert is not available to the public, we follow ConVIRT (Zhang et al., 2020) to regard the official validation set as the test set. Meanwhile, we randomly sample 5,000 images from the official training set to build the validation set. The training/validation/test split each constitutes 218,414/5,000/234 images of the whole dataset.

RSNA Pneumonia defines a binary classification problem, where each chest radiograph is categorized as either pneumonia or normal. We adopt the official data split, where the training/validation/test set comprises 25,184/1,500/3,000 images, respectively.

NIH ChestX-ray consists of about 112,120 frontal-view chest radiograph images, where a multi-label classification problem on 14 chest pathologies is introduced. The training/validation/test split each constitutes 70%/10%/20% of the whole dataset.

COVID-19 Image Data Collection is a relatively small dataset, which involves 900 chest radiographs. We follow Zhou et al. (2022) to conduct fine-tuning on this small-scale dataset to investigate the effectiveness of various pre-training methodologies when the amount of annotations is limited. There are two tasks included. The first task requires the model to distinguish COVID-19 cases from non-COVID-19 pneumonia cases, where the training/validation/test set comprises 356/54/99 radiographs, respectively. The second task is to distinguish viral pneumonia cases from bacterial pneumonia ones, where the training/validation/test set contains 297/43/86 cases, respectively.

---

[1]https://www.kaggle.com/c/siim-acr-pneumothorax-segmentation.

Methods	Input Size	Pre-train. Data	CheXpert			RSNA Pneumonia			SIIM	
			1%	10%	100%	1%	10%	100%	10%	100%
Our MRM	224	MI-CXR	**88.5**	**88.5**	**88.7**	**91.3**	**92.7**	**93.3**	**73.2**	**91.4**
CNN-based										
ConVIRT	224	CheXpert	85.9	86.8	87.3	77.4	80.1	81.3	43.2	59.9
GLoRIA	224	CheXpert	86.6	87.8	88.1	86.1	88.0	88.6	46.9	63.4
ConVIRT	224	MI-CXR	87.0	88.1	88.1	88.8	91.5	92.7	-	-
BioViL	480	PubMed + MI-III/CXR	-	-	-	88.1	88.4	89.1	-	-
Transformer-based										
GLoRIA*	224	MI-CXR	86.5	87.5	87.8	89.7	91.2	92.1	71.8	90.9
REFERS	224	MI-CXR	87.2	88.1	88.2	89.4	91.6	92.7	72.1	89.7

Table 1: COMPARISONS ON CHEXPERT, RSNA PNEUMONIA, AND SIIM. We report AUC scores of different labeling ratios when fine-tuning on CheXpert and RSNA Pneumonia. In comparison, dice scores are presented on SIIM. The best results are bolded. Note that ResNet-50 and ViT-B/16 are treated as the default backbones for CNN- and Transformer-based methods, respectively. * denotes our implementation of GLoRIA using ViT-B/16. **MI-** stands for the MIMIC dataset series.

Labeling Ratios	Methods	Average	Atelectasis	Cardiomegaly	Consolidation	Edema	Effusion	Emphysema	Fibrosis	Hernia	Infiltration	Mass	Nodule	Pleural Thickening	Pneumonia	Pneumothorax
1%	Our MRM	**79.4**	**78.8**	**90.3**	**80.0**	**86.5**	**86.9**	**82.0**	71.9	**90.0**	67.2	**82.3**	69.6	**72.3**	69.6	**84.0**
	REFERS	76.7	77.5	85.6	78.6	84.9	85.4	79.5	**72.3**	77.1	**67.5**	76.2	66.5	71.6	69.3	81.7
	Model Genesis	70.3	72.1	67.1	75.8	76.1	80.6	72.6	64.8	73.5	65.7	65.2	62.2	67.6	64.8	76.2
	C2L	71.1	75.1	67.1	77.6	75.1	83.4	71.5	66.8	70.0	63.8	70.1	66.2	68.1	65.7	74.4
	Context Restoration	67.8	69.1	64.4	73.2	73.8	78.1	70.0	62.1	70.2	65.2	62.4	59.1	65.0	62.2	73.8
	TransVW	71.3	74.5	68.9	76.7	79.8	81.1	67.9	68.7	68.2	66.8	66.5	66.2	68.5	68.8	75.0
	ImageNet Pre-training	69.8	73.3	69.6	76.0	81.7	80.5	67.1	64.9	64.8	65.8	67.0	62.3	65.7	65.0	74.0
10%	Our MRM	**84.0**	**82.3**	**90.9**	**81.1**	**89.0**	**88.8**	**92.2**	84.8	**94.0**	70.1	**86.6**	**75.1**	**78.6**	74.3	**88.4**
	REFERS	80.9	80.1	89.8	79.5	87.8	87.5	88.2	77.2	86.1	69.6	82.0	72.8	74.2	72.2	85.6
	Model Genesis	76.0	77.2	72.8	77.5	85.7	85.2	81.0	75.3	78.0	68.4	73.1	69.5	72.2	67.7	80.4
	C2L	76.6	78.0	75.5	77.5	84.1	85.7	81.2	73.7	79.5	67.4	77.5	71.7	72.0	67.3	81.9
	Context Restoration	73.8	75.5	70.6	77.1	84.5	84.2	79.4	73.1	67.5	68.1	70.9	66.9	71.7	65.2	79.1
	TransVW	74.4	76.5	70.8	77.6	83.0	84.8	79.7	69.9	74.7	68.5	72.1	68.3	72.4	63.2	79.6
	ImageNet Pre-training	74.4	74.2	79.8	75.9	85.7	83.2	80.4	72.1	74.0	64.1	71.7	65.6	69.6	66.2	79.7
100%	Our MRM	**85.9**	**84.2**	**93.0**	**82.2**	**91.0**	**89.6**	**94.3**	86.7	**94.4**	71.8	**88.2**	**78.5**	**81.4**	77.3	**90.2**
	REFERS	84.7	83.0	92.3	82.1	90.2	88.7	91.4	83.9	93.3	**74.1**	85.5	76.7	78.5	77.0	89.1
	Model Genesis	81.0	78.8	84.5	79.2	87.8	86.6	89.7	81.0	85.2	71.1	81.9	73.2	75.8	73.0	85.6
	C2L	82.2	81.1	90.2	81.0	88.1	88.0	88.3	80.8	86.8	72.0	82.7	74.1	76.2	75.3	85.9
	Context Restoration	78.7	75.8	82.9	76.4	86.6	84.8	88.2	78.6	83.0	70.0	79.6	69.5	73.2	69.4	84.0
	TransVW	81.7	79.8	85.0	80.0	88.2	87.1	90.1	81.8	85.9	72.3	82.6	74.4	76.6	74.0	86.1
	ImageNet Pre-training	80.0	78.3	89.3	77.6	87.9	85.9	87.4	78.5	88.8	65.9	79.9	70.7	74.5	71.0	84.7

Table 2: COMPARISONS ON NIH CHESTX-RAY. Besides self-supervised and transfer learning baselines, we also present the performance of REFERS (with competitive performance on CheXpert, RSNA Pneumonia, and SIIM) as a reference. AUC scores are displayed. The highest AUC scores in each labeling ratio are bolded.

SIIM-ACR Pneumothorax Segmentation (SIIM) aims to facilitate the development of segmentation models to identify pneumothorax disease in chest radiographs. SIIM contains over 120,000 frontal-view chest X-rays with precise manual segmentation of pneumothorax. We follow Huang et al. (2021) to construct the training/validation/test split, where each constitutes 70%/15%/15% of the whole dataset.

4.3 BASELINES

4.3.1 REPORT-SUPERVISED METHODOLOGIES

We first compare MRM against a range of pre-training approaches, which use radiology reports as supervision to learn radiograph representations. There are 4 report-supervised approaches involved in the baseline comparisons, which are ConVIRT (Zhang et al., 2020), GLoRIA (Huang et al., 2021), BioViL (Boecking et al., 2022), and REFERS (Zhou et al., 2022). Specifically, *Con-*

VIRT (Zhang et al., 2020) proposed to learn medical visual representations by contrasting paired radiographs and sentences from radiology reports. *GLoRIA* (Huang et al., 2021) improved ConVIRT by contrasting radiograph sub-regions and words in the reports. *BioViL* (Boecking et al., 2022) and *REFERS* (Zhou et al., 2022) incorporated masked language modeling loss into contrastive learning. Moreover, REFERS introduced a multi-view fusion attention to better align the representations of each radiograph and its associated report. In experiments, we fine-tune pre-trained models of MRM and other report-supervised methods on CheXpert (classification), RSNA Pneumonia (classification), and SIIM (segmentation).

4.3.2 SELF-SUPERVISED AND TRANSFER LEARNING METHODS

Besides report-supervised approaches, we also include self-supervised and transfer learning approaches in our comparisons. Specifically, Context Restoration (Chen et al., 2019), Model Genesis (Zhou et al., 2021), and TransVW (Haghighi et al., 2021) are based on predictive SSL, while C2L (Zhou et al., 2020) was developed on top of contrastive learning. In addition, MRM is also compared to ImageNet pre-training (Wang et al., 2017). In practice, we conduct the comparisons with self-supervised and transfer learning approaches on NIH ChestX-ray and COVID-19 Image Data Collection.

Methods	COVID-19 vs. Others	Viral vs. Bacterial
Our MRM	**85.8**	**91.5**
REFERS	82.1	80.4
Model Genesis	76.0	71.8
C2L	77.8	73.0
Context Restoration	74.6	69.8
TransVW	76.1	71.5
ImageNet Pre-training	74.1	70.3

Methods	1%	10%	100%
Our MRM	**79.4**	**84.0**	**85.9**
- Masked report modeling ($\mathcal{L}_R$)	74.7	81.3	85.1
- Masked radiograph modeling ($\mathcal{L}_I$)	76.7	82.2	84.7
- Super-resolution restoration	78.8	83.7	85.7
+ Hybrid features for image restoration	78.9	83.6	85.7

Table 3: COMPARISONS ON COVID-19 IMAGE DATA COLLECTION. The best results are bolded.

Table 4: ABLATIONS ON NIH CHESTX-RAY. AUC scores of three different labeling ratios are reported. The best results are bolded.

4.4 IMPLEMENTATION DETAILS.

Our code is implemented using PyTorch 1.8.2 (Paszke et al., 2019). The pre-training experiments were conducted on 4 GeForce RTX 3080Ti GPUs, and the training time is about 2 days for 200 epochs, requiring 12GB memory from each GPU. The training batch size is 256. We use AdamW (Loshchilov & Hutter, 2017) as the default optimizer, where the initial learning rate is $1.5\mathrm{e}^{-4}$, weight decay is 0.05, β_1 is 0.9, and β_2 is 0.95. The cross-entropy and MSE losses are used for masked image and language modeling, respectively. In practice, we set λ in Eq. 3 to 1.

For fine-tuning on SIIM, we train the segmentation network on 4 GeForce RTX 3080Ti GPUs. AdamW is the default optimizer, where the initial learning rate is $2\mathrm{e}^{-5}$, weight decay is 0.05, β_1 is 0.9, and β_2 is 0.999. For fine-tuning on other datasets, we train the classification network on a single GeForce RTX 3080Ti GPU, where the default optimizer is SGD with momentum 0.9. The training cost is a mix of focal and dice losses.

For fine-tuning on CheXpert, RSNA Pneumonia, NIH ChestX-ray, and COVID-19 Image Data Collection, we adopt the cross-entropy loss. We search the best initial learning rate from 3e-2, 3e-3, and 5e-4 to get the best performance on validation set.

For both the pre-training and the fine-tuning of image classification task, the network is "warmed up" by increasing the learning rate linearly to the set value, and then learning rate is decreased using the cosine decay schedule.

4.5 RESULTS

4.5.1 COMPARISONS WITH REPORT-SUPERVISED BASELINES

In Table 1, we present the comparative results with report-supervised methodologies on CheXpert, RSNA Pneumonia, and SIIM (segmentation). Specifically, we investigate the performance when fine-tuning with limited and full supervision. We provide segmentation results in the appendix.

From Table 1, we observe no obvious performance gap between CNN- and Transformer-based report-supervised pre-training methods. For instance, after implementing GLoRIA on MIMIC-CXR

with ViT-B/16, we observe performance drops and improvements on CheXpert and RSNA Pneumonia, respectively. This contrast demonstrates that replacing CNN with Transformer may not bring performance gains to report-supervised pre-training. Among all baselines, REFERS is the best performing approach.

Nonetheless, MRM consistently outperforms various baselines on all three datasets under different labeling ratios. Specifically, MRM maintains more advantages over previous pre-training methodologies when fine-tuning with limited annotations, which is quite meaningful for medical image analysis as large amounts of specialist annotations (from radiologists or clinicians) are usually hard to access. *It is worth noting that MRM achieves 88.5% when using only 1% labeled data on CheXpert, better than previous counterparts with 100% annotations.*

4.5.2 COMPARISONS WITH SELF-SUPERVISED AND TRANSFER LEARNING BASELINES

Table 2 presents the average and per-class classification results on NIH ChestX-ray. Compared to self-supervised learning baselines, MRM achieves large improvements in almost every chest pathology. On average, MRM outperforms C2L (Zhou et al., 2020) and TransVW (Haghighi et al., 2021), the best two self-supervised pre-training methodologies, by about 8% when the amount of available labeled data is extremely limited (i.e., the labeling ratio is 1%). Similarly, we also observe remarkable improvements when comparing MRM to ImageNet Pre-training (Wang et al., 2017). These phenomena demonstrate that the radiograph representations learned by MRM are more transferable than those from previous self-supervised and transfer learning methods.

Compared to REFERS (i.e., the best performing report-supervised baseline in Table 1), MRM still provides notable improvements in most chest pathologies. Specifically, MRM is more advantageous when the amount of labeled data is limited. For instance, MRM surpasses REFERS by 2.7% and 3.1% on average when the labeling ratios are 1% and 10%, respectively. These comparisons again verify the effectiveness of MRM over previous report-supervised pre-training counterparts.

We also investigate the impacts of pre-training on the real-world scenario with extremely limited specialist supervision. In Table 3, we compare the performance of a range of pre-training methodologies on two binary classification tasks, which are distinguishing COVID-19 from non-COVID-19 pneumonia, and differentiating between viral pneumonia and bacterial pneumonia. Again, MRM outperforms self-supervised, transfer learning, and report-supervised pre-training methodologies by substantial margins. Compared to REFERS, MRM brings nearly 4% and 11% improvements to two tasks, respectively, further enhancing the practicability of the diagnosis system trained with extremely limited supervision.

4.6 ABLATION ANALYSIS.

We present ablations to given an intuition of MRM's behaviors and performance. Specifically, we study the impacts of the masked report modeling (cf. $\mathcal{L}_R$ in Eq. 1), the masked radiograph modeling (cf. $\mathcal{L}_I$ in Eq. 2), and the super-resolution restoration process, respectively. Besides, we also investigate employing a different form of hybrid representations, whose goal is to use radiology reports to assist the restoration of associated radiographs. Ablation results are presented in Table 4.

Advantages over single-task pre-training paradigm. After removing the masked report modeling objective, MRM only acquires supervision signals from self-supervision. Thus, the whole framework degenerates into a self-supervised pre-training methodology. From Table 4, we observe that removing $\mathcal{L}_R$ leads to dramatic performance degradation in different labeling ratios. Moreover, we find that introducing the masked report modeling is greatly helpful to the fine-tuning performance with limited labeling resources (1% and 10%). For instance, adding $\mathcal{L}_R$ brings about 5-percent improvements to MRM. Similarly, removing the masked radiograph modeling also leads to notable performance drops in all labeling ratios. These results demonstrate the necessity of introducing multi-task objectives in masked modeling pre-training.

Is super-resolution restoration helpful? As Table 4 shows, the proposed super-resolution restoration provides consistent performance gains in different labeling ratios. The underlying reason may be that the low to high resolution restoration process helps preserve more local information into latent representations, which enhances the transferable ability to downstream tasks.

Figure 3: Example results on MIMIC-CXR. For each triplet, we show the masked radiograph and report (Inputs), our MRM reconstruction (Recons.), and the ground truth (GT). The masking ratios are 75% (radiograph) and 50% (report). Predicted and corresponding ground truth words are highlighted in pink and green , respectively. More examples are in the appendix.

Would it be beneficial to introduce multi-modal information to image restoration? We investigate this question by adding non-masked report token embeddings to image patch embeddings and passing the resulting hybrid features to the image decoder. As Table 4 shows, introducing multi-modal information to masked image restoration does not improve the fine-tuning performance. We leave the exploration of the reason behind to future work.

4.7 RECONSTRUCTION ANALYSIS

Fig. 3 presents example results on MIMIC-CXR. We find that even with high masking ratios, MRM can still produce satisfactory reconstructions, though some details are missing. Specifically, the reconstructed reports are surprisingly close to the ground truths, which we attribute to the introduction of hybrid multi-modal representations. For instance, MRM can tell the position of rib fractures based on the radiograph input. Besides, we obtain some interesting mistakes. In the first example, MRM recognizes the clips over the left lung as calcifications (potentially in nipple shadow). This observation again shows that the report reconstructions rely on the image input as the clips are masked in the input radiograph.

5 CONCLUSION

We present a unified yet simple framework based on masked record modeling (MRM) for radiograph representation learning. MRM formalizes the radiograph understanding and radiology report comprehension as two complementary masked modeling objectives. In practice, MRM learns pre-trained models that generalize well. With MRM pre-training, we achieve better results on well-established datasets. Specifically, MRM outperforms previous self- and report-supervised counterparts by large margins when the labeled data is extremely limited. These observations verify the effectiveness of MRM, and we hope they will enable our field to explore the use of multi-task supervision for learning more transferable visual representations.

REFERENCES

Pulkit Agrawal, Joao Carreira, and Jitendra Malik. Learning to see by moving. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 37–45, 2015.

Benedikt Boecking, Naoto Usuyama, Shruthi Bannur, Daniel C Castro, Anton Schwaighofer, Stephanie Hyland, Maria Wetscherek, Tristan Naumann, Aditya Nori, Javier Alvarez-Valle, et al. Making the most of text semantics to improve biomedical vision–language processing. *arXiv preprint arXiv:2204.09817*, 2022.

Aurelia Bustos, Antonio Pertusa, Jose-Maria Salinas, and Maria de la Iglesia-Vayá. Padchest: A large chest x-ray image dataset with multi-label annotated reports. *Medical Image Analysis*, 66: 101797, 2020.

Liang Chen, Paul Bentley, Kensaku Mori, Kazunari Misawa, Michitaka Fujiwara, and Daniel Rueckert. Self-supervised learning for medical image analysis using image context restoration. *Medical Image Analysis*, 58:101539, 2019.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International Conference on Machine Learning*, pp. 1597–1607. PMLR, 2020.

Xi Chen, Xiao Wang, Soravit Changpinyo, AJ Piergiovanni, Piotr Padlewski, Daniel Salz, Sebastian Goodman, Adam Grycner, Basil Mustafa, Lucas Beyer, et al. Pali: A jointly-scaled multilingual language-image model. *arXiv preprint arXiv:2209.06794*, 2022.

Joseph Paul Cohen, Paul Morrison, Lan Dao, Karsten Roth, Tim Q Duong, and Marzyeh Ghassemi. Covid-19 image data collection: Prospective predictions are the future. *arXiv preprint arXiv:2006.11988*, 2020.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. ImageNet: A large-scale hierarchical image database. In *Proceedings of the IEEE/CVF conference on Computer Vision and Pattern Recognition*, pp. 248–255. Ieee, 2009.

Karan Desai and Justin Johnson. Virtex: Learning visual representations from textual annotations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 11162–11173, 2021.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *North American Chapter of the Association for Computational Linguistics*, 2018.

Carl Doersch, Abhinav Gupta, and Alexei A Efros. Unsupervised visual representation learning by context prediction. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 1422–1430, 2015.

Zi-Yi Dou, Aishwarya Kamath, Zhe Gan, Pengchuan Zhang, Jianfeng Wang, Linjie Li, Zicheng Liu, Ce Liu, Yann LeCun, Nanyun Peng, et al. Coarse-to-fine vision-language pre-training with fusion in the backbone. *arXiv preprint arXiv:2206.07643*, 2022.

Yuting Gao, Jinfeng Liu, Zihan Xu, Jun Zhang, Ke Li, and Chunhua Shen. Pyramidclip: Hierarchical feature alignment for vision-language model pretraining. *arXiv preprint arXiv:2204.14095*, 2022.

Xinyang Geng, Hao Liu, Lisa Lee, Dale Schuurams, Sergey Levine, and Pieter Abbeel. Multimodal masked autoencoders learn transferable representations. *arXiv preprint arXiv:2205.14204*, 2022.

Fatemeh Haghighi, Mohammad Reza Hosseinzadeh Taher, Zongwei Zhou, Michael B Gotway, and Jianming Liang. Transferable visual words: Exploiting the semantics of anatomical patterns for self-supervised learning. *IEEE Transactions on Medical Imaging*, 40(10):2857–2868, 2021.

Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16000–16009, 2022.

Shih-Cheng Huang, Liyue Shen, Matthew P Lungren, and Serena Yeung. Gloria: A multimodal global-local representation learning framework for label-efficient medical image recognition. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 3942–3951, 2021.

Jeremy Irvin, Pranav Rajpurkar, Michael Ko, Yifan Yu, Silviana Ciurea-Ilcus, Chris Chute, Henrik Marklund, Behzad Haghgoo, Robyn Ball, Katie Shpanskaya, et al. Chexpert: A large chest radiograph dataset with uncertainty labels and expert comparison. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 590–597, 2019.

Alistair EW Johnson, Tom J Pollard, Nathaniel R Greenbaum, Matthew P Lungren, Chih-ying Deng, Yifan Peng, Zhiyong Lu, Roger G Mark, Seth J Berkowitz, and Steven Horng. Mimic-cxr-jpg, a large publicly available database of labeled chest radiographs. *arXiv preprint arXiv:1901.07042*, 2019.

Yangguang Li, Feng Liang, Lichen Zhao, Yufeng Cui, Wanli Ouyang, Jing Shao, Fengwei Yu, and Junjie Yan. Supervision exists everywhere: A data efficient contrastive language-image pre-training paradigm. In *International Conference on Learning Representations*, 2021.

Ruizhi Liao, Daniel Moyer, Miriam Cha, Keegan Quigley, Seth Berkowitz, Steven Horng, Polina Golland, and William M Wells. Multimodal representation learning via maximization of local mutual information. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pp. 273–283. Springer, 2021.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*, 2017.

Norman Mu, Alexander Kirillov, David Wagner, and Saining Xie. Slip: Self-supervision meets language-image pre-training. *arXiv preprint arXiv:2112.12750*, 2021.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in Neural Information Processing Systems*, 32: 8026–8037, 2019.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International Conference on Machine Learning*, pp. 8748–8763. PMLR, 2021.

Mert Bulent Sariyildiz, Julien Perez, and Diane Larlus. Learning visual representations with caption annotations. In *European Conference on Computer Vision*, pp. 153–170. Springer, 2020.

George Shih, Carol C Wu, Safwan S Halabi, Marc D Kohli, Luciano M Prevedello, Tessa S Cook, Arjun Sharma, Judith K Amorosa, Veronica Arteaga, Maya Galperin-Aizenberg, et al. Augmenting the national institutes of health chest radiograph dataset with expert annotations of possible pneumonia. *Radiology. Artificial intelligence*, 1(1), 2019.

Amanpreet Singh, Ronghang Hu, Vedanuj Goswami, Guillaume Couairon, Wojciech Galuba, Marcus Rohrbach, and Douwe Kiela. Flava: A foundational language and vision alignment model. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 15638–15650, 2022.

Wenhui Wang, Hangbo Bao, Li Dong, Johan Bjorck, Zhiliang Peng, Qiang Liu, Kriti Aggarwal, Owais Khan Mohammed, Saksham Singhal, Subhojit Som, et al. Image as a foreign language: Beit pretraining for all vision and vision-language tasks. *arXiv preprint arXiv:2208.10442*, 2022.

Xiaolong Wang and Abhinav Gupta. Unsupervised learning of visual representations using videos. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 2794–2802, 2015.

Xiaosong Wang, Yifan Peng, Le Lu, Zhiyong Lu, Mohammadhadi Bagheri, and Ronald M Summers. Chestx-ray8: Hospital-scale chest x-ray database and benchmarks on weakly-supervised classification and localization of common thorax diseases. In *Proceedings of the IEEE/CVF conference on Computer Vision and Pattern Recognition*, pp. 2097–2106, 2017.

Yonghui Wu, Mike Schuster, Zhifeng Chen, Quoc V Le, Mohammad Norouzi, Wolfgang Macherey, Maxim Krikun, Yuan Cao, Qin Gao, Klaus Macherey, et al. Google's neural machine translation system: Bridging the gap between human and machine translation. *arXiv preprint arXiv:1609.08144*, 2016.

Jiahui Yu, Zirui Wang, Vijay Vasudevan, Legg Yeung, Mojtaba Seyedhosseini, and Yonghui Wu. Coca: Contrastive captioners are image-text foundation models. *arXiv preprint arXiv:2205.01917*, 2022.

Yuhao Zhang, Hang Jiang, Yasuhide Miura, Christopher D Manning, and Curtis P Langlotz. Contrastive learning of medical visual representations from paired images and text. *arXiv preprint arXiv:2010.00747*, 2020.

Hong-Yu Zhou, Shuang Yu, Cheng Bian, Yifan Hu, Kai Ma, and Yefeng Zheng. Comparing to learn: Surpassing imagenet pretraining on radiographs by comparing image representations. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pp. 398–407. Springer, 2020.

Hong-Yu Zhou, Xiaoyu Chen, Yinghao Zhang, Ruibang Luo, Liansheng Wang, and Yizhou Yu. Generalized radiograph representation learning via cross-supervision between images and free-text radiology reports. *Nature Machine Intelligence*, 4(1):32–40, 2022.

Zongwei Zhou, Vatsal Sodha, Jiaxuan Pang, Michael B Gotway, and Jianming Liang. Models genesis. *Medical Image Analysis*, 67:101840, 2021.