# Learning with Algorithmic Supervision
# via Continuous Relaxations

## Abstract

The integration of algorithmic components into neural architectures has gained an increased attention recently, as it allows training neural networks with new forms of supervision such as ordering constraints or silhouettes instead of using ground truth labels. Many approaches in the field focus on the continuous relaxation of a specific task and show promising results in this context. But the focus on single tasks also limits the applicability of the proposed concepts to a narrow range of applications. In this work, we build on those ideas to propose an approach that allows to integrate algorithms into end-to-end trainable neural network architectures based on a general approximation of discrete conditions. To this end, we relax these conditions in control structures such as conditional statements, loops, and indexing, so that resulting algorithms are smoothly differentiable. To obtain meaningful gradients, each relevant variable is perturbed via logistic distributions and the expectation value under this perturbation is approximated. We evaluate the proposed continuous relaxation model on four challenging tasks and show that it can keep up with relaxations specifically designed for each individual task.

## 1 Introduction

Artificial Neural Networks have shown their ability to solve various problems, ranging from classical tasks in computer science such as machine translation [1] and object detection [2] to many other topics in sciences such as, e.g., protein folding [3]. Simultaneously, classical algorithms exist, which typically solve predefined tasks based on a given input and a predefined control structure such as, e.g., sorting, shortest-path computation and many more. Recently, research has started to combine both elements by integrating algorithmic concepts into neural network architectures. Those approaches allow training neural networks with alternative supervision strategies. Examples for such algorithmic supervision are, e.g., learning 3D representations via a differentiable renderer [4], [5] or training neural networks with ordering information [6], [7]. In general, to allow for end-to-end training of neural architectures with integrated algorithms, the challenge is to estimate the gradients of a respective algorithm, e.g., by a differentiable approximation. Here, most solutions are tailored to specific problems like, e.g., differentiable sorting or rendering. But also more general frameworks have recently been proposed, which estimate gradients for combinatorial optimizers. Examples for such approaches are, e.g, proposed by Vlastelica *et al.* [8] focusing on the differentiation of black box combinatorial solvers and Berthet *et al.* [9], who differentiate optimizers by stochastically perturbing the input. Both approaches focus on the problem that it is necessary to estimate the gradients of an algorithm to allow for an end-to-end training of neural architectures including it. To address this issue, Vlastelica *et al.* [8] estimate the gradients of an optimizer by a one-step linearization method that takes the gradients with respect to the optimizer's output into account, which allows to integrate any off-the-shelf combinatorial optimizer. Berthet *et al.* [9] estimate the gradients by perturbing the input to a discrete solver by random noise.

In this context, we propose an approach that allows to make algorithms differentiable and estimate their gradients by perturbing those variables wrt. which we want to differentiate in a discrete algorithm by a logistic distribution. Specifically, we propose continuous relaxations of different algorithmic concepts such as comparators, conditional statements, bounded and unbounded loops, and indexing. This allows us to estimate the expected value of an algorithm sampling-free and in closed form, e.g. compared to methods approximating the distributions via Monte-Carlo sampling methods (e.g. [9]). To keep the computation feasible, we approximate the expectation value by merging computation paths after each conditional block in sequences of conditional blocks. For nested conditional blocks, we compute the exact expectation value without merging conditional cases. This trade-off allows merging paths in regular intervals and thus alleviates the need to keep track of all possible path combinations. As we model perturbations of variables when they are accessed, all distributions are independent, which contrasts the case of modeling input perturbations, where all computation paths would have to be handled separately.

To demonstrate the practical aspects, we apply the proposed approach in the context of four tasks, that make use of algorithmic supervision to train a neural network, namely sorting supervision [6], [7], [10], shortest-path supervision [8], [9], silhouette supervision (differentiable rendering) [4], [5], [11], and finally Levenshtein distance supervision. While the first three setups are based on existing benchmarks in the field, we introduce the fourth experiment to show the application of this idea to a new algorithmic task in the field of differentiable dynamic programming. In the latter, the Levenshtein distance between two concatenated character sequences from the EMNIST data set [12] is supervised while the individual letters remain unsupervised. We show that the proposed system is able to outperform current state-of-the-art systems on sorting supervision, while it performs comparable on shortest path supervision and silhouette supervision.

The implementation of this work as well as its experiments will be made publicly available in the form of a high-level library for continuously relaxing algorithms.

## 2  Related Work

We cover the field of training networks with algorithmic supervision. While some of these works cover single algorithmic concepts, e.g., sorting [6], [7], [13] or rendering [4], [5], [14], others have covered wider areas such as dynamic programming [15] or gradient estimation for general optimizers [8], [9], [16], [17]. Paulus *et al.* [18] employ the Gumbel-Softmax [19] distribution to estimate gradients for concepts such as subset selection. Xie *et al.* [20] and Blondel *et al.* [13] employ differentiable sorting methods for top-$k$ classification. Cuturi *et al.* [21] and Blondel *et al.* [22] present approaches for differentiable dynamic time warping. In machine translation, Bahdanau *et al.* [23] investigate soft alignments, while Collobert *et al.* [24] present a fully differentiable beam sorting algorithm. In speech recognition, Bahdanau *et al.* [25] propose differentiable surrogate task losses for sequence prediction tasks. Dasgupta *et al.* [26] model box parameters with Gumbel distributions to obtain soft differentiable box embeddings.

In the following, we focus on those works that provide relaxations for tasks considered in this work. We close the overview with a review of some early works on smooth program interpretation.

**Sorting Supervision**   The task of training neural networks with sorting supervision has been first proposed by Grover *et al.* [6]. In this case, a set four-digit numbers based on concatenated MNIST digits [27] is given, and the task is to find an order-preserving mapping from the images to scalars. Here, a CNN should predict a scalar for each of $n$ four-digit numbers such that their order is preserved among the predicted scalars. For training, only sorting supervision in the form of the ground truth order of input images is given, while their absolute values remain unsupervised. Grover *et al.* [6] address this task by relaxing the permutation matrices to double stochastic matrices. Cuturi *et al.* [7] pick up this on benchmark and propose a differentiable proxy by approximating the sorting problem with a regularizing optimal transport algorithm.

**Silhouette Supervision**   A line of work in computer vision is differentiable renderers for 3D-unsupervised 3D-reconstruction. Here, recent approaches have proposed differentiable renderers for 3D mesh reconstruction with only 2D silhouette supervision [4], [5] on 13 classes of the ShapeNet data set [28]. Kato *et al.* [5] propose a renderer where surrogate gradients of rasterization are approximated to perform 3D mesh reconstruction via silhouette supervision as well as 3D style

transfer. Liu *et al.* [4] propose a differentiable renderer without surrogate gradients by using a differentiable aggregating process and apply it to 3D mesh reconstruction as well as pose / shape optimization.

**Shortest-Path Supervision** Two works, proposed by Vlastelica *et al.* [8] and Berthet *et al.* [9] presented methods for estimating gradients for general off-the-shelf optimizers. In this context, Vlastelica *et al.* [8] proposed an experiment of shortest-path supervision, where an image of a terrain is given with different costs for each type of train, and the task is to predict the shortest path from the top-left to the opposite corner. Integrating a shortest-path algorithm into a neural architecture lets the neural network produce a cost embedding of the terrain which the shortest-path algorithm uses for predicting the shortest path. Vlastelica *et al.* [8] tackle this task by finding a linearization of the Dijkstra algorithm [29], which they can differentiate. Berthet *et al.* [9] take up this problem and produce gradient estimates for the Dijkstra algorithm by stochastically perturbing the inputs to the algorithm.

**Smooth Interpretation** In another line of work. in the field of computer aided verification. Chaudhuri *et al.* [30], [31] propose a program smoothing method based on randomly perturbing the inputs of a program by a Gaussian distribution. Here, an initial Gaussian perturbation is propagated through program transformations, and a final distribution over perturbed outputs is approximated via a mixture of Gaussians. The smooth function is then optimized using the gradient-free Nelder-Mead optimization method. The main differences to our method are that we perturb all relevant variables (and not the inputs) with logistic distributions and use this for gradient based optimization.

# 3 Method

To continuously relax algorithms and, thus, make them differentiable, we relax all values with respect to which we want to differentiate into logistic distributions. We choose the logistic distribution as it provides two distinctive properties that make it especially suited for the task at hand: (1) logistic distributions have heavier tails than normal distribution, which allows for larger probability mass and thus larger gradients when two compared values are further away from each other. (2) the cumulative density function (CDF) of the logistic distribution is the logistic sigmoid function, which can be computed analytically, and its gradient is easily computable. This contrasts the CDF of the normal distribution, which has no closed form and is commonly approximated via a polynomial [32].

Specifically, we relax any value $x$, for which we want to compute gradients, by perturbing it into a logistic random variable $\tilde{x} \sim \text{Logistic}(x, \beta)$, where $\beta$ is a temperature parameter such that for $\beta \to 0 : \tilde{x} = x$. Based on this, we can relax a discrete conditional statement, e.g., based on the condition $x < c$ with constant $c \in \mathbb{R}$, as follows:

$$\big[y \ \texttt{if} \ \tilde{x} < c \ \texttt{else} \ z\big] \equiv \int_{-\infty}^{c} f_{\log}(t; x, \beta) \cdot y \, \mathrm{d}t + \int_{c}^{\infty} f_{\log}(t; x, \beta) \cdot z \, \mathrm{d}t \tag{1}$$

$$= \quad F_{\log}(c; x, \beta) \cdot y \quad + \quad (1 - F_{\log}(c; x, \beta)) \cdot z \tag{2}$$

$$= \quad \sigma(c - x) \cdot y \quad + \quad (1 - \sigma(c - x)) \quad \cdot z \tag{3}$$

where $\sigma$ is the logistic (sigmoid) function $\sigma(x) = \frac{1}{1+e^{-x/\beta}}$. In this example, as $x$ increases, the result smoothly transitions from $y$ to $z$. Thus, the derivative of the result wrt. $x$ is defined as

$$\frac{\partial}{\partial x}\big[y \ \texttt{if} \ \tilde{x} < c \ \texttt{else} \ z\big] = \frac{\partial}{\partial x}\left(y \cdot \sigma(c - x) + z \cdot (1 - \sigma(c - x))\right) \tag{4}$$

$$= (z - y) \cdot \sigma(c - x) \cdot (1 - \sigma(c - x)) \tag{5}$$

Hence, the gradient descent method can influence the condition ($\tilde{x} < c$) to hold if the `if` case reduces the loss, or influence the condition to fail if the `else` case reduces the loss function.

In this example, $y$ and $z$ may not only be scalar values but also results of algorithms or parts of an algorithm themselves. This introduces a recursive formalism of relaxed program flow, where parts of an algorithm are combined via a convex combination:

$$\big[f(s) \ \texttt{if} \ a < b \ \texttt{else} \ g(s)\big] \equiv \sigma(b - a) \cdot f(s) + (1 - \sigma(b - a)) \cdot g(s) \tag{6}$$

131 where $f$ and $g$ denote functions, algorithms, or sequences of statements that operate on the set of
132 all variables $s$ via call-by-value and return the set of all variables $s$. The result of this may either
133 overwrite the set of all variables ($s := [...]$) or be used in a nested conditional statement.

134 After introducing `if-else` statements above, we extend the idea to loops, which extends the formal-
135 ism of relaxed program flow to Turing-completeness. In fixed loops, i.e., loops with a predefined
136 number of iterations, since there is only a single computation path, no relaxation is necessary, and,
137 thus, fixed loops can be handled by unrolling.

138 The more complex case is conditional unbounded loops, i.e., `While` loops, which are executed as
139 long as a condition holds. For that, let $(s_i)_{i \in \mathbb{N}}$ be the sequence of all variables after applying $i$ times
140 the content of a loop. That is, $s_0 = s$ for initial set of all variables $s$, and $s_i = f(s_{i-1})$, where $f$
141 is the content of a loop, i.e., a function, an algorithm, or sequence of statements. Let $a, b$ denote
142 accessing variables of $s$, i.e., $s[a], s[b]$, respectively. By recursively applying the rule for `if-else`
143 statements, we obtain the following rule for unbounded loops:

$$\left[\texttt{while } a < b \texttt{ do } s := f(s)\right] \equiv \sum_{i=0}^{\infty} \underbrace{\prod_{j=0}^{i} \left(\sigma(b_j - a_j)\right)}_{(a)} \cdot \underbrace{\left(1 - \sigma(b_{i+1} - a_{i+1})\right)}_{(b)} \cdot s_i \quad (7)$$

144 Here, (a) is the probability that the $i$th iteration is reached and (b) is the probability that there are
145 no more than $i$ iterations. Together, (a) and (b) is the probability that there are exactly $i$ iterations
146 weighing the state of all variables after applying $i$ times $f$, which is $s_i$. Computationally, we evaluate
147 the infinite series until the probability of execution (a) becomes numerically negligible. Again, the
148 result may either overwrite the set of all variables ($s := [...]$) or be used in a nested conditional
149 statement.

150 **Complexity and Merging of Paths** To compute the exact expectation value of an algorithm under
151 logistic perturbation of its variables, all computation paths would have to be evaluated separately
152 to account for dependencies. However, this would result in an exponential complexity. Therefore,
153 we compute the exact expectation value for nested conditional blocks, but for sequential conditional
154 blocks we merge the computation paths at the end of each block. This allows for a linear complexity
155 in the number of sequential conditional blocks and only an exponential complexity in the largest
156 depth of nested conditional blocks. Note that the number of sequential conditional blocks is usually
157 much larger than the depth of conditional blocks, e.g., hundreds or thousands of sequential blocks and
158 a maximum depth of just $2 - 5$ in our experiments. For example, the expression $\big[a := (f(x) \texttt{ if } i <$
159 $0 \texttt{ else } g(x)); \; b := (0 \texttt{ if } a < 0 \texttt{ else } a^2)\big]$ contains a dependence between the two sequential
160 conditional blocks, which introduces the error in our approximation. In general, our formalism
161 also supports modeling dependencies between sequential conditional blocks, however practically, it
162 might become intractable for entire algorithms. Also, it is possible to consider relevant dependencies
163 explicitly if an algorithm relies on specific dependencies.

164 Note that modeling the perturbation of variables is different from modeling the perturbation of the
165 inputs. A condition, where the difference becomes clear, is, e.g., $(x < x)$. When modeling input
166 perturbations, the condition would have a strong implicit conditional dependency and evaluate to
167 a $0\%$ probability. However, in this work, we do *not* model perturbations of the inputs, but instead
168 model perturbations of variables each time they are accessed such that accessing a variable twice is
169 independently identically distributed (iid). Therefore, $(x < x)$ evaluates to a $50\%$ probability. To
170 minimize the approximation error of the relaxation, only those variables wrt. which a gradient is
171 required should be relaxed.

172 In terms of runtime, one has to note that runtime optimized algorithms (e.g., Dijkstra) usually do not
173 improve the runtime for the relaxation, because for the proposed continuous relaxations all cases in an
174 algorithm have to be executed. Thus, an additional condition to reduce the computational cost does not
175 improve runtime because both cases are executed. Instead, it becomes beneficial if an algorithm solves
176 a problem in a rather fixed execution order. On the other hand, optimizing an algorithm with respect
177 to runtime leads to interpolations between the fastest execution paths. This optimization cannot
178 improve the gradients but rather degrades them as it is an additional approximation and produces
179 gradients with respect to runtime optimization. Further, algorithms with rather strict execution can
180 often be executed in parallel on GPUs such that they can be often be faster than runtime-optimized
181 sequential algorithms on CPUs.

Figure 1: Left: Hard decision boundary (cyan) and probability under logistic perturbation (magenta). Right: Hard equality (cyan), relaxed equality (magenta), and relaxed inequality (light magenta).

## 3.1 Relaxed Comparators

So far, we have only considered the comparator $<$. $>$ follows by swapping the arguments:

$$\mathbb{P}\left[a < b\right] \equiv \sigma(b - a) \qquad \mathbb{P}\left[a > b\right] \equiv \sigma(a - b) \qquad (8)$$

For the equality operator $=$, we consider two distributions $\tilde{a} \sim \mathrm{Logistic}(a, \beta)$ and $\tilde{b} \sim \mathrm{Logistic}(b, \beta)$, which we want to check for similarity / equality. Given value $a$, we compute the likelihood that $a$ is a sample from $\tilde{b}$ rather than $\tilde{a}$. If $a$ is equally likely to be drawn from $\tilde{a}$ and $\tilde{b}$, $\tilde{a}$ and $\tilde{b}$ are equal. If $a$ is unlikely to be drawn from $\tilde{b}$, $\tilde{a}$ and $\tilde{b}$ are unequal. To compute whether it is equally likely for $a$ to be drawn from $\tilde{a}$ and $\tilde{b}$, we take the ratio between the probability that $a$ is from $\tilde{b}$ ($f_{\log}(a; b, \beta)$) and the probability that $a$ is from $\tilde{a}$ ($f_{\log}(a; a, \beta)$):

$$\mathbb{P}\left[a = b\right] \equiv \frac{f_{\log}(a; b, \beta)}{f_{\log}(a; a, \beta)} = \frac{f_{\log}(b; a, \beta)}{f_{\log}(b; b, \beta)} = \mathrm{sech}^2\left(\frac{b - a}{2\beta}\right) \qquad (9)$$

These relaxed comparators are displayed in Fig. 1. To compute probabilities of conjunction (i.e., and) or of disjunction (i.e., or), we use the product or probabilistic sum, respectively. This corresponds to an intersection / union of independent events.

To compare more than two elements and relax the $\arg\max$ function, we use the multinomial logistic distribution which is also known as the softmax distribution.

$$\mathbb{P}(i = \arg\max_j X_j) = \frac{e^{X_i/\beta}}{\sum_j e^{X_j/\beta}} \qquad (10)$$

To relax the $\max$ operation, we use the product of $\arg\max$ / softmax and the respective vector.

To compare a categorical probability distribution $X \in [0, 1]^n$ with a categorical probability distribution $Y$, we consider two scenarios: If $Y \in \{0, 1\}^n$, i.e., $Y$ is one-hot, we can use the inner product of $X$ and $Y$ to obtain their joint probability. However, if $Y \notin \{0, 1\}^n$, i.e., $Y$ is not one-hot, even if $X = Y$ the inner product can not be 1, but a probability of 1 would be desirable if $X = Y$. Therefore, we ($L_2$) normalize $X$ and $Y$ before taking the inner product, which corresponds to the cosine similarity.

## 3.2 Relaxed Indexing

As vectors, arrays, and tensors are essential for algorithms and machine learning, we also formalize relaxed indexing. For this, we introduce real-valued indexing and marginal indexing.

In a relaxed algorithm, indices may be drawn from the set of real number as they may be a convex combination of computations or a real-valued input. This poses a challenge since it requires interpolating between multiple values. The direct approach would be grid sampling with bilinear or bicubic interpolation to interpolate values. However, this leads to a smoothness of only up to $C^1$. This means relationships exceeding the direct (or next) neighbors in the array are not modeled with such interpolation. Thus,

Figure 2: Real-valued indexing: the gray-value represents the extent to which each value is used for indexing. Left: 1D integer-valued hard indexing compared to real-valued indexing. Right: 2D real-valued indexing.

to index an $n$-dimensional tensor **A** with values $i \in \mathbb{R}^n$ we apply a convolution with a Logistic filter $g$ and obtain the result as $(g * \mathbf{A})(i)$. We normalize the weights used to interpolate the respective indexed values such that they sum up to one: we divide the weights by their sum in the forward pass but ignore this during the backward pass (computation of the gradient). This trick allows proper values but avoids optimization algorithms to exploit aliasing effects. Real-valued indexing is displayed in Fig. 2, which compares it to hard indexing.

If a marginal distribution over indices is given, e.g., computed by $\mathrm{argmax}$ or its relaxation $\mathrm{softmax}$, marginal indexing can be used. Here, the marginal distribution is used as weights for indexing a tensor.

Note that real-valued indexing is only meaningful iff the indexed array follows a semantic order such as time series, an image, or the position in a grid. If, on the other hand, the array contains categorical information such as the nodes of graphs, values should be indexed with marginal indexing as their neighborhood is arbitrary.

# 4 Experiments

We evaluate the proposed approach on various algorithmic supervision experiments. For each algorithmic supervision experiment, we first briefly described the task and the respective input data as well as the relaxed algorithm that is used. To allow an application to various tasks, we need to find a suitable temperature $\beta$ for each algorithm. As a heuristic, we start with $\beta = 1/\sqrt{k}$ where $k$ is the number of occurrences of relaxed variables in the algorithm, which is a balance between a good approximation and sufficient relaxation for good gradient estimates. For each task, we tune this parameter on a validation set. Pseudo-code for all algorithms as well as additional information on the relaxation and the temperature parameter can be found in the supplementary material.

## 4.1 Sorting Supervision

In the sorting supervision experiment, a set of four-digit numbers based on concatenated MNIST digits [27] is given, and the task is to find an order-preserving mapping from the images to scalars. A CNN learns to predict a scalar for each of $n$ four-digit numbers such that their order is preserved among the predicted scalars. For this, only sorting supervision in form of the ground truth order of input images is given, while their absolute values remain unsupervised. This follows the protocol of Grover *et al.* [6] and Cuturi *et al.* [7]. An example for a concatenated MNIST image is  .

Using our method, we relax the well established stable sorting algorithm Bubble sort [33], which works by iteratively going through a list and swapping any two adjacent elements if they are not in the correct order until there are no more swap operations in one iteration. We include a variable that keeps track of whether the input sequence is in correct order by setting it to true if a swap operation occurs. Due to the relaxation, the expectation value of this variable is a floating point number between $0$ and $1$. Therefore, we can use this variable as the loss function. By that, the training objective becomes for the input sequence to be sorted and, thus, that the scores predicted by the neural network correspond to the supervised partial order. In fact, the number of swaps in bubble sort corresponds to the Kendall's $\tau$ coefficient, which indicates to which degree a sequence is sorted. Note that, e.g., QuickSort does not have this property as it performs swaps even if the sequence is already sorted.

We emphasize that the task of the trained neural network is *not* to sort a sequence but instead to predict a score for each element such that the ordering / ranking corresponds to the supervised ordering / ranking. While the relaxed algorithm can sort the inputs correctly, at evaluation time, following the setup of [6] and [7] we use an $\mathrm{argsort}$ method to test whether the outputs produced by the neural network are in accordance with the ground truth partial order. We use the same network architecture as [6] and [7]. Here, we only optimize the temperature for $n = 5$, resulting in $\beta = 1/8$, and fix this for all other $n$. For training, we use the Adam optimizer [34] with a learning rate of $10^{-4}$ for between $1.5 \cdot 10^5$ and $1.5 \cdot 10^6$ iterations.

We evaluate our method against state-of-the-art hand-crafted relaxations of the sorting operation using the same network architecture and evaluation metrics as Grover *et al.* [6] and Cuturi *et al.* [7]. As displayed in Tab. 1, our method outperforms state-of-the-art. This demonstrates that our general formulation can compete with and even outperform state-of-the-art hand-crafted relaxations of the sorting operation for sorting supervision.

Table 1: Results for the 4-digit MNIST sorting task, averaged over 10 runs. Baselines as reported by Cuturi *et al.* [7]. Trained and evaluated on sets of $n$ elements, the displayed metrics are exact matches (and element-wise correct ranks).

Table 2: Results for the Warcraft shortest-path task using shortest-path supervision, averaged over 10 runs. Reported are exact matches (EM) as well as cost ratio of the predicted to the optimal shortest path.

| Method | $n = 3$ | $n = 5$ | $n = 7$ |
|---|---|---|---|
| Stoch. NeuralSort [6] | 0.920 (0.946) | 0.790 (0.907) | 0.636 (0.873) |
| Det. NeuralSort [6] | 0.919 (0.945) | 0.777 (0.901) | 0.610 (0.862) |
| Optimal Transport [7] | 0.928 (0.950) | 0.811 (0.917) | 0.656 (0.882) |
| Relaxed Bubble Sort | **0.944 (0.961)** | **0.842 (0.930)** | **0.707 (0.898)** |

| Method | EM | cost ratio |
|---|---|---|
| ResNet Baseline [8] | 40.2% | 1.01530 |
| Black-Box Loss [8] | 86.6% | 1.00026 |
| Perturbed Opt. [9] | **91.7%** | 1.00042 |
| Relaxed Shortest-Path | 88.4% | **1.00014** |

Figure 3: (From left to right.) Example input image of the Warcraft terrain data set with the hidden cost matrix and the resulting shortest path. Shortest paths relaxed with the proposed method for $\beta \in \{0.67, 4\}$, which correspond to the perturbed paths by Berthet *et al.* [9] with $\epsilon \in \{0.5, 2.0\}$.

### 4.2 Shortest-Path Supervision

For shortest-path supervision on 2D terrains, we follow the setup by Vlastelica *et al.* [8] and Berthet *et al.* [9] and use the data set of $10\,000$ patches of Warcraft terrains of size $96 \times 96$ representing terrain grids of size $12 \times 12$. Given an image of a terrain (e.g., Fig. 3 first), the goal is to predict the shortest path (e.g., Fig. 3 third) according to a hidden cost matrix (e.g., Fig. 3 second). For this, $12 \times 12$ binary matrices of the shortest-path are supervised, while the hidden cost matrix is used only to determine the shortest path. In their works, Vlastelica *et al.* [8] and Berthet *et al.* [9] show that integrating and differentiating a shortest-path algorithm can improve the results by allowing the neural network to predict a cost matrix from which the shortest path can be computed via the algorithm. This performs significantly better than a ResNet baseline where the shortest paths have to be predicted by the neural network alone (see Tab. 2).

For this task, we relax the Bellman-Ford algorithm [35] with 8-neighborhood, node weights, and path reconstruction, details on which are given in the supplementary material. For the loss between the supervised shortest paths and the paths produced by the relaxed Bellman-Ford algorithm we use the $\ell^2$ loss. To illustrate the shortest paths created by our method and to compare them to those created through the Perturbed Optimizers by Berthet *et al.* [9], we display examples of back traced shortest paths for two temperatures in Fig. 3 (center to right).

We use the same network architecture as Vlastelica *et al.* [8] and Berthet *et al.* [9] and also train for 50 epochs with a batch size of 70. We use a temperature of $\beta = 1/25$.

As shown in Tab. 2, our relaxation outperforms all baselines on the cost ratio of the predicted to the optimal shortest path and achieves the second-best result on the shortest path exact match accuracy after the perturbed optimizers [9].

### 4.3 Silhouette Supervision

Reconstructing a 3D model from a single 2D image is an important task in computer vision. Recent works [4], [5] have employed differentiable renderers to train a 3D reconstruction network by giving feedback on whether the silhouettes of a reconstruction match the input image. Specifically, on a data set of 13 object classes from ShapeNet [28] that have been rendered from 24 azimuths at a resolution of $64 \times 64$ [5], recent works have been benchmarked [4], [5], [11]. For learning with silhouette supervision, a single image is processed by a neural network, which returns a 3D mesh. The silhouette of this mesh is rendered from two view-points by a differentiable renderer and the intersection-over-union between the rendered and predicted meshes is used as a training objective to

Table 3: Single-view 3D reconstruction results using silhouette supervision. Reported is the 3D IoU.

| Method | Airplane | Bench | Dresser | Car | Chair | Display | Lamp | Speaker | Rifle | Sofa | Table | Phone | Vessel | *Mean* |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **With a batch size of 64** | | | | | | | | | | | | | | |
| Yan *et al.* [11] (retrieval) | 0.5564 | 0.4875 | 0.5713 | 0.6519 | 0.3512 | 0.3958 | 0.2905 | 0.4600 | 0.5133 | 0.5314 | 0.3097 | 0.6696 | 0.4078 | 0.4766 |
| Yan *et al.* [11] (voxel) | 0.5556 | 0.4924 | 0.6823 | 0.7123 | 0.4494 | 0.5395 | 0.4223 | 0.5868 | 0.5987 | 0.6221 | 0.4938 | 0.7504 | 0.5507 | 0.5736 |
| Kato *et al.* [5] (NMR) | 0.6172 | 0.4998 | 0.7143 | 0.7095 | 0.4990 | 0.5831 | 0.4126 | 0.6536 | 0.6322 | 0.6735 | 0.4829 | 0.7777 | 0.5645 | 0.6015 |
| Liu *et al.* [4] (SoftRas) | 0.6419 | 0.5080 | 0.7116 | 0.7697 | 0.5270 | 0.6156 | 0.4628 | 0.6654 | 0.6811 | 0.6878 | 0.4487 | 0.7895 | 0.5953 | 0.6234 |
| **With a batch size of 2** | | | | | | | | | | | | | | |
| Liu *et al.* [4] (SoftRas) | **0.5741** | **0.3746** | 0.6373 | **0.6939** | **0.4220** | 0.5168 | 0.4001 | 0.6068 | **0.6026** | **0.5922** | 0.3712 | **0.7464** | **0.5534** | **0.5455** |
| Relaxed Sil. via Three Edges | 0.5418 | 0.3667 | **0.6626** | 0.6546 | 0.3899 | 0.5229 | 0.4105 | **0.6232** | 0.5497 | 0.5639 | 0.3580 | 0.6609 | 0.5279 | 0.5256 |
| Relaxed Sil. via Euclid. Dist | 0.5399 | 0.3698 | 0.6503 | 0.6524 | 0.4044 | **0.5261** | **0.4247** | 0.6225 | 0.5723 | 0.5643 | **0.3829** | 0.7265 | 0.5180 | 0.5349 |

Figure 5: Levenshtein distance matrix. Left: hard matrix and alignment path. Right: relaxed matrix with $\beta = 1.5$.

Table 4: EMNIST classification results with Levenshtein editing distance supervision averaged over 10 runs. We report the Top-1 accuracy (top) and the F1-score (bottom) for different character pairs as well as for character quadrouples.

| Method | AB | BC | CD | DE | EF | IL | OX | ACGT | OSXL |
|---|---|---|---|---|---|---|---|---|---|
| Baseline | .616 | .651 | .768 | .739 | .701 | .550 | .893 | .403 | .448 |
| | .581 | .629 | .759 | .711 | .674 | .490 | .890 | .336 | .384 |
| Relaxed LD | **.671** | **.807** | **.816** | **.833** | **.847** | **.570** | **.960** | **.437** | **.487** |
| | **.666** | **.805** | **.815** | **.831** | **.845** | **.539** | **.960** | **.367** | **.404** |

update the neural network [4], [5]. For training, we also use the same neural network architecture as Kato *et al.* [5] as well as Liu *et al.* [4]. Note that, while renderers can be able to render a full RGB image, in these experiments, only the silhouette is used for supervision of the 3D geometry reconstruction. Specifically, public implementations of [4], [5] only use silhouette supervision.

For this task, we relax two silhouette rendering algorithms. The algorithms rasterize a 3D mesh as follows: For each pixel and for each triangle of the mesh, if a pixel lies inside a triangle, the value of the pixel in the output image is set to $1$. The condition of whether a pixel lies inside a triangle is checked in two alternative fashions: (1) by three nested `if` conditions that check on which side of each edge the pixel lies. (2) by checking whether the directed euclidean distance between a pixel and a triangle is positive. Examples of relaxed silhouette renderings and an example image from the data set are displayed in Fig. 4.

As the simple silhouette renderer does not have any optimizations, such as discarding pixels that are far away from a triangle or triangles that are occluded by others, it is not very efficient. Thus, due to limited resources, we are only able to train with a maximum batch size of 2 while previous works used a batch size of $64$. Therefore, we reproduce the recent best performing work by Liu *et al.* [4] on a batch size of only 2 to allow for a fair comparison. For directed Euclidean distance, we use a steepness of $\beta = 1/2\,000$; for three edges, $\beta = 1/10\,000$.

Figure 4: An input image from the data set (left). Silhouette of a prediction rendered with directed Euclidean distance approach (center) and three edge comparison (right).

We report the average as well as class-wise 3D IoU results in Tab. 3. Our relaxations outperform the retrieval baseline by Yan *et al.* [11] even though we use a batch size of only 2. In direct comparison to the SoftRas renderer at a batch size of 2, our relaxations achieve the best accuracy for 5 out of 13 object classes. However, on average, our methods, although they do not outperform SoftRas, show a comparable performance with a drop of only 1%. It is notable that the directed Euclidean distance approach performs better than the three edges approach. The three edges approach is faster by a factor of 3 because computing the directed Euclidean distance is more expensive than three nested `if` clauses (even in the relaxed case).

### 4.4 Levenshtein Distance Supervision

In the Levenshtein distance supervision experiment, we supervise a classifier for handwritten EMNIST letters [12] by supervising the editing distance between two handwritten strings of length 32 only. As editing distance, we use the Levenshtein distance LD which is defined as $\mathrm{LD}(a,b) = \mathrm{LD}_{|a|,|b|}(a,b)$ with

$$\mathrm{LD}_{i,j}(a,b) = \begin{cases} j & i = 0 \\ i & j = 0 \\ \min \begin{cases} \mathrm{LD}_{i-1,j}(a,b) + 1 \\ \mathrm{LD}_{i,j-1}(a,b) + 1 \\ \mathrm{LD}_{i-1,j-1}(a,b) + \mathbb{1}_{(a_{i-1} \neq b_{j-1})} \end{cases} & \text{else.} \end{cases} \tag{11}$$

We relax the Levenshtein distance using its classic dynamic programming algorithm. An example Levenshtein distance matrix and its relaxation are displayed in Fig. 5.

For learning, pairs of strings of images of 32 handwritten characters $a, b$ as well as the ground truth Levenshtein distance $\mathrm{LD}(\mathbf{y}_a, \mathbf{y}_b)$ are given. We sample strings $a, b$ from an alphabet of 2 or 4 characters. For sampling the second string given the first one, we uniformly choose two to four insertion and deletion operations. Thus, the mean editing distance for strings, which use two different characters, is $4.25$ and for four characters is $5$. An example for two of such strings is  and .

For each letter, the CNN returns a categorical distributions over letters, which is then fed to the algorithm. Our training objective is minimizing the $\ell^2$ loss between the predicted distance and the ground truth distance:

$$\mathcal{L} = \left\| \mathrm{LD}\left( (\mathrm{CNN}(a_i))_{i \in \{1..32\}}, (\mathrm{CNN}(b_i))_{i \in \{1..32\}} \right) - \mathrm{LD}(\mathbf{y}_a, \mathbf{y}_b) \right\|_2. \tag{12}$$

For training, we use a temperature of $\beta = 1/9$ and Adam ($\eta = 10^{-4}$) for $128 - 512$ iterations.

For evaluation, we use Hungarian matching with Top-1 accuracy as well as the F1-score. We compare it against a baseline, which uses the $\ell_1$ distance between encodings instead of the editing distance:

$$\mathcal{L} = \left\| \left\| (\mathrm{CNN}(a_i))_{i \in \{1..32\}} - (\mathrm{CNN}(b_i))_{i \in \{1..32\}} \right\|_1 - \mathrm{LD}(\mathbf{y}_a, \mathbf{y}_b) \right\|_2. \tag{13}$$

Tab. 4 shows that our method consistently outperforms the baseline on both metrics in all cases. The character combinations `AB`, `BC`, `CD`, `DE`, and `EF` are a canonical choice for random combinations. The characters `IL` represent are the hardest combination of two letters as they even get frequently confused by supervised neural networks [12] and can also be indistinguishable for humans. The characters `OX` represent the easiest case as supervised classifiers can perfectly distinguish them on the test dataset [12]. For two letter combinations, we achieve Top-1 accuracies between $57\%$ (`IL`) and $96\%$ (`OX`). Even for four letter combinations (`ACGT` and `OSXL`), we achieve Top-1 accuracies of up to $48.7\%$.

## 5 Conclusion

We proposed an approach for continuous relaxations of algorithms that allows their integration into end-to-end trainable neural network architectures. For that, we use convex combinations of execution paths of algorithms that are parameterized by smooth functions. We show that our proposed general framework can compete with SOTA continuous relaxations of specific algorithms as well as gradient estimation methods on a variety of algorithmic supervision tasks. Moreover, we show that our formulation successfully relaxes even complex algorithms such as a shortest-path algorithm or a renderer. We hope to inspire the research community to build on our framework to further explore the potential of algorithmic supervision and algorithmically enhanced neural network architectures.

# References

[1] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin, "Attention is all you need," in *Proc. Neural Information Processing Systems (NIPS)*, 2017.

[2] J. Redmon, S. Divvala, R. Girshick, and A. Farhadi, "You only look once: Unified, real-time object detection," in *Proc. International Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016.

[3] A. W. Senior, R. Evans, J. Jumper, J. Kirkpatrick, L. Sifre, T. Green, C. Qin, A. Žídek, A. W. R. Nelson, A. Bridgland, H. Penedones, S. Petersen, K. Simonyan, S. Crossan, P. Kohli, D. T. Jones, D. Silver, K. Kavukcuoglu, and D. Hassabis, "Improved protein structure prediction using potentials from deep learning," *Nature*, vol. 577, no. 7792, pp. 706–710, Jan. 2020.

[4] S. Liu, T. Li, W. Chen, and H. Li, "Soft Rasterizer: A Differentiable Renderer for Image-based 3D Reasoning," in *Proc. International Conference on Computer Vision (ICCV)*, 2019.

[5] H. Kato, Y. Ushiku, and T. Harada, "Neural 3D mesh renderer," in *Proc. International Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018.

[6] A. Grover, E. Wang, A. Zweig, and S. Ermon, "Stochastic Optimization of Sorting Networks via Continuous Relaxations," in *International Conference on Learning Representations (ICLR)*, 2019.

[7] M. Cuturi, O. Teboul, and J.-P. Vert, "Differentiable ranking and sorting using optimal transport," in *Proc. Neural Information Processing Systems (NIPS)*, 2019.

[8] M. Vlastelica, A. Paulus, V. Musil, G. Martius, and M. Rolinek, "Differentiation of blackbox combinatorial solvers," in *International Conference on Learning Representations (ICLR)*, 2020.

[9] Q. Berthet, M. Blondel, O. Teboul, M. Cuturi, J.-P. Vert, and F. Bach, "Learning with Differentiable Perturbed Optimizers," in *Proc. Neural Information Processing Systems (NIPS)*, 2020.

[10] G. Mena, D. Belanger, S. Linderman, and J. Snoek, "Learning latent permutations with gumbel-sinkhorn networks," in *International Conference on Learning Representations (ICLR)*, 2018.

[11] X. Yan, J. Yang, E. Yumer, Y. Guo, and H. Lee, "Perspective transformer nets: Learning single-view 3D object reconstruction without 3D supervision," in *Proc. Neural Information Processing Systems (NIPS)*, 2016.

[12] G. Cohen, S. Afshar, J. Tapson, and A. van Schaik, "EMNIST: an extension of MNIST to handwritten letters," *arXiv preprint arXiv:1702.05373*, 2017.

[13] M. Blondel, O. Teboul, Q. Berthet, and J. Djolonga, "Fast Differentiable Sorting and Ranking," in *International Conference on Machine Learning (ICML)*, 2020.

[14] W. Chen, J. Gao, H. Ling, E. J. Smith, J. Lehtinen, A. Jacobson, and S. Fidler, "Learning to predict 3D objects with an interpolation-based differentiable renderer," in *Proc. Neural Information Processing Systems (NIPS)*, 2019.

[15] A. Mensch and M. Blondel, "Differentiable Dynamic Programming for Structured Prediction and Attention," in *International Conference on Machine Learning (ICML)*, Jul. 2018.

[16] M. Rolinek, V. Musil, A. Paulus, M. Vlastelica, C. Michaelis, and G. Martius, "Optimizing rank-based metrics with blackbox differentiation," in *Proc. International Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

[17] S. Shirobokov, V. Belavin, M. Kagan, A. Ustyuzhanin, and A. G. Baydin, "Black-box optimization with local generative surrogates," in *Workshop on Real World Experiment Design and Active Learning at International Conference on Machine Learning (ICML)*, 2020.

[18] M. B. Paulus, D. Choi, D. Tarlow, A. Krause, and C. J. Maddison, "Gradient estimation with stochastic softmax tricks," in *Proc. Neural Information Processing Systems (NIPS)*, 2020.

[19] E. Jang, S. Gu, and B. Poole, "Categorical reparameterization with gumbel-softmax," in *International Conference on Learning Representations (ICLR)*, 2016.

[20] Y. Xie, H. Dai, M. Chen, B. Dai, T. Zhao, H. Zha, W. Wei, and T. Pfister, "Differentiable top-k with optimal transport," in *Proc. Neural Information Processing Systems (NIPS)*, 2020.

[21] M. Cuturi and M. Blondel, "Soft-DTW: A Differentiable Loss Function for Time-Series," in *International Conference on Machine Learning (ICML)*, 2017.

[22] M. Blondel, A. Mensch, and J.-P. Vert, "Differentiable divergences between time series," *arXiv preprint arXiv:2010.08354*, 2020.

[23] D. Bahdanau, K. Cho, and Y. Bengio, "Neural machine translation by jointly learning to align and translate," in *International Conference on Learning Representations (ICLR)*, 2015.

[24] R. Collobert, A. Hannun, and G. Synnaeve, "A fully differentiable beam search decoder," in *International Conference on Machine Learning (ICML)*, Jul. 2019.

[25] D. Bahdanau, D. Serdyuk, P. Brakel, N. R. Ke, J. Chorowski, A. Courville, and Y. Bengio, "Task loss estimation for sequence prediction," *ICLR Workshop track*, 2016.

[26] S. S. Dasgupta, M. Boratko, D. Zhang, L. Vilnis, X. L. Li, and A. McCallum, "Improving local identifiability in probabilistic box embeddings," in *Proc. Neural Information Processing Systems (NIPS)*, 2020.

[27] Y. LeCun, C. Cortes, and C. Burges, "Mnist handwritten digit database," *ATT Labs*, vol. 2, 2010. [Online]. Available: http://yann.lecun.com/exdb/mnist.

[28] A. X. Chang, T. Funkhouser, L. Guibas, P. Hanrahan, Q. Huang, Z. Li, S. Savarese, M. Savva, S. Song, H. Su, J. Xiao, L. Yi, and F. Yu, "ShapeNet: An information-rich 3D model repository," *arXiv preprint arXiv:1512.03012*, 2015.

[29] E. W. Dijkstra *et al.*, "A note on two problems in connexion with graphs," *Numerische mathematik*, vol. 1, no. 1, pp. 269–271, 1959.

[30] S. Chaudhuri and A. Solar-Lezama, "Smooth interpretation," in *Proceedings of the 31st ACM SIGPLAN Conference on Programming Language Design and Implementation*, ser. PLDI '10, Association for Computing Machinery, 2010.

[31] ——, "Smoothing a program soundly and robustly," in *Proceedings of the 23rd International Conference on Computer Aided Verification*, ser. CAV'11, Springer-Verlag, 2011.

[32] W. J. Cody, "Rational Chebyshev approximations for the error function," *Mathematics of Computation*, vol. 23, no. 107, pp. 631–637, 1969.

[33] O. Astrachan, "Bubble sort: An archaeological algorithmic analysis," *ACM Sigcse Bulletin*, vol. 35, no. 1, pp. 1–5, 2003.

[34] D. Kingma and J. Ba, "Adam: A method for stochastic optimization," in *International Conference on Learning Representations (ICLR)*, 2015.

[35] R. Bellman, "On a routing problem," *Quarterly of applied mathematics*, vol. 16, no. 1, pp. 87–90, 1958.

[36] V. I. Levenshtein, "Binary codes capable of correcting deletions, insertions, and reversals," in *Soviet physics doklady*, vol. 10, 1966, pp. 707–710.