BREAKING THE DETECTION-GENERALIZATION PARADOX ON OUT-OF-DISTRIBUTION DATA

ABSTRACT

The detection and generalization of out-of-distribution (OOD) data are critical in numerous real-world applications. While OOD detection enhances model reliability against outliers, generalization enables adaptability to unforeseen variations. Despite their importance, the intrinsic relationship between OOD detection and generalization remains underexplored, posing risks in practical deployments. This study identifies the *Detection-Generalization Paradox* on OOD data, where optimizing one objective can degrade the other. We investigate this paradox by analyzing the behaviors of models trained under different paradigms, focusing on representation, logits, and loss across in-distribution, covariate-shift, and semantic-shift data. Based on our findings, we propose Distribution-Robust Sharpness-Aware Minimization (DR-SAM), an optimization framework that balances OOD detection and generalization. DR-SAM employs both in-distribution and semantic-shift data during training, using data augmentation on in-distribution data to simulate potential covariate-shift scenarios and computing perturbations on model parameters to enhance OOD generalization. By determining the worst-case gradient direction, the model's decision boundary is adjusted to better encompass covariate-shift samples. Empirical evaluations demonstrate that DR-SAM improves the detection of semantic-shift samples and enhances generalization for covariate-shift samples.

1 INTRODUCTION

The detection and generalization of out-of-distribution (OOD) data are pivotal in real-world applications across various domains (Arjovsky, 2020; Salehi et al., 2021; Yang et al., 2022; 2024). Typical examples can be found in autonomous systems, medical diagnosis, and financial fraud detection (Sinha et al., 2022; Hilal et al., 2022; Hong et al., 2024). These aspects underscore the reliability and adaptability of machine learning models when exposed to multifarious data distributions.

In general, detecting OOD instances ensures reliability, while generalization empowers models to adapt to unforeseen OOD variations, as illustrated in Fig. 1. Methods of OOD detection utilize the model's probabilities or representations to identify OOD samples (Hendrycks et al., 2018; Lee et al., 2018; Liu et al., 2020; Zhang et al., 2023a). On the other side, the OOD generalization techniques, *e.g.*, regularization (Arjovsky et al., 2019; Krueger et al., 2021) and data augmentation (Kim et al., 2021; Hendrycks et al., 2021), facilitate the acquisition towards invariant representations. Notably, despite the real-world application *simultaneously* demanding both capabilities of detection and generalization, *the inherent relationship* between these two lines of research has yet to be elucidated comprehensively (Katz-Samuels et al., 2022; Bai et al., 2023). Such a knowledge gap entails hidden risks in the context of real-world applications.

Figure 1: Data samples with semantic shift (D_{SS}) and covariate shift (D_{CS}) *w.r.t.* the in-distribution samples (D_{ID}).

In this study, we discover the underlying detection-generalization trade-off in OOD data arising from the prevailing detection (OOD-D) and generalization (OOD-G) methods, as shown in Fig. 2. We termed this trade-off as *Detection-Generalization Paradox*, namely, solely optimizing one objective with the corresponding method will degenerate the other. Nonetheless, optimizing the trade-off between these two essential targets remains under-explored and challenging (Bai et al., 2023; Katz-Samuels et al., 2022). Thus, we raise an open problem: *how to break the detection-generalization paradox to attain advanced abilities in both OOD detection and generalization simultaneously?*

(a) CIFAR-10 dataset   (b) CIFAR-100 dataset

Figure 2: A performance comparison on both tasks of OOD detection and generalization. The ID-pre-trained models are finetuned with various OOD-D/OOD-G methods. The *variations* in OOD-D/OOD-G performance are calculated with metrics FPR@95/accuracy compared to the MSP baseline, where a *lower* ΔFPR@95 indicates *improved* OOD-D and a *higher* ΔAcc denotes *improved* OOD-G. As can be seen, OOD-D methods improve OOD-D but deteriorate OOD-G, while OOD-G methods enhance OOD-G but degenerate OOD-D. In contrast, DR-SAM improves both OOD-D and OOD-G.

To figure out the reason behind the paradox, we delve into the distinct behaviors when model training with different paradigms that induce the generalization-detection paradox. We start from the model's inference pipeline: $\forall (x, y) \sim D, \; x \xmapsto{f_{\boldsymbol{\theta}}^{\text{EMB}}(\cdot)} \boldsymbol{h}_x \xmapsto{f_{\boldsymbol{\theta}}^{\text{CLS}}(\cdot)} \hat{\boldsymbol{y}} \xmapsto{\mathcal{L}(\cdot,\cdot)} \mathcal{L}(\hat{\boldsymbol{y}}, y)$, in which we conduct an in-depth analysis of the three informative variables - representation $\boldsymbol{h}_x$, logits $\hat{\boldsymbol{y}}$, and loss $\mathcal{L}(\hat{\boldsymbol{y}}, y)$ with in-distribution data D_{ID}, covariate shift data D_{CS}, and semantic shift data D_{SS}. Specifically,

Analysis on the representation space $\boldsymbol{h}_x$. The OOD-D method enlarges the semantic gap between D_{ID} and D_{SS} but also enlarges the gap between D_{ID} and D_{CS}. This explains its improvement in OOD-D and degeneration in OOD-G. On the other hand, the OOD-G method reduces the gap between D_{ID} and D_{CS} but also reduces the gap between D_{ID} and D_{SS}. This explains its improvement in OOD-G and degeneration in OOD-D. Namely, neither line of the method can obtain the ideal representations.

Analysis on the logit space $\hat{\boldsymbol{y}}$. The OOD-D method enlarges the gap of prediction confidence between D_{ID} and D_{SS} (better OOD-D) and decreases the model's prediction on D_{CS} (worse OOD-G). On the other side, the OOD-G method increases the confidence on both D_{CS} (better OOD-G) and D_{SS} (over-confident, worse OOD-D). These discoveries are aligned with those in representation space.

Analysis on the loss space $\mathcal{L}(\hat{\boldsymbol{y}}, y)$. We adopt the loss landscape and sharpness to investigate the flatness around the model's convergent point. Notably, the OOD-D method leads to a relatively flat landscape on $D_{\text{ID}}^{\text{test}}$ but with a sharper landscape on $D_{\text{CS}}^{\text{test}}$, indicating its degeneration in OOD generalization. Conversely, OOD-G method induces a flat landscapes on $D_{\text{ID}}^{\text{train}}$ and $D_{\text{CS}}^{\text{test}}$ but with a high sharpness on $D_{\text{ID}}^{\text{test}}$. An ideal model should possess low sharpness on both in-distribution and covariate-shift data. However, this cannot be achieved by the current OOD-D or OOD-G method.

To break the paradox based on the above discoveries, one solution is to actively seek local flatness during training to enhance OOD generalization ability under the constraint of the OOD detection objective. Considering both detection and generalization objectives, we propose a novel optimization framework, Distribution-Robust Sharpness-Aware Minimization (DR-SAM).

Specifically, DR-SAM utilizes both in-distribution data and semantic-shift data in model training. The adoption of auxiliary semantic-shift outliers is to guarantee better OOD detection capability on test-time outliers encountered. Notably, in computing the perturbation on model parameters, we apply data augmentation on in-distribution data, aiming to simulate the potential covariate-shift data and thereby guarantee the model's OOD generalization capacity during the optimization procedure. Then, by applying an optimizer like the stochastic gradient descent (SGD), we obtain the gradient direction that indicates the worst-case from the current point. We can then extrapolate the decision boundary by shifting the current point towards this gradient direction to cover more covariate-shift samples.

Empirically, we evaluate DR-SAM on a series of OOD-D benchmarks with auxiliary OOD-G metrics. Extensive evaluations demonstrate that our method can achieve better OOD detection capability for semantic-shift samples by lowering FPR@95 and improving generalization by increasing the classification accuracy on covariate-shift samples. It achieves up to a 9.82% improvement in OOD-D and 7.02% in OOD-G compared to the best baseline approaches. Further, we discuss the proposed method from different perspectives and provide a broad range of ablation studies and visualizations.

We summarize our main contributions as follows:

- We identify the detection-generalization paradox on out-of-distribution data among the prevailing OOD detection/generalization methods. Furthermore, we conduct an in-depth analysis to provide several insights into the paradox's intuitive manifestation and the underlying cause (Sec. 3).

- We propose a new optimization framework, Distribution-Robust Sharpness-Aware Minimization (DR-SAM), to break the detection-generalization paradox. By balancing OOD detection and generalization objectives, DR-SAM actively seeks local flatness to enhance OOD generalization ability under the constraint of OOD detection objective to guarantee dual capabilities (Sec. 4).

- Empirically, we conduct extensive experiments and justify that DR-SAM achieves leading performance in both measurements of OOD detection and generalization. We conduct several ablation studies and visualizations to provide further insights into the effectiveness of DR-SAM (Sec. 5).

2 PRELIMINARIES

Notations. We denote D_{ID} as the $\underline{\text{i}}$n-$\underline{\text{d}}$istribution data, D_{CS} as the $\underline{\text{c}}$ovariate $\underline{\text{s}}$hift data for OOD generalization, and D_{SS} as the $\underline{\text{s}}$emantic $\underline{\text{s}}$hift data for OOD detection. A sample $(x, y) \sim D$ contains image x and label y. Besides, $f_{\boldsymbol{\theta}}(\cdot)$ denotes a classification model parameterized by $\boldsymbol{\theta}$. Here, $f_{\boldsymbol{\theta}}(\cdot) = f_{\boldsymbol{\theta}}^{\text{EMB}}(\cdot) \circ f_{\boldsymbol{\theta}}^{\text{CLS}}(\cdot)$, wherein the embedding module $f_{\boldsymbol{\theta}}^{\text{EMB}}(\cdot)$ encodes input x to representation $\boldsymbol{h}_x$, and the following classification module $f_{\boldsymbol{\theta}}^{\text{CLS}}(\cdot)$ projects $\boldsymbol{h}_x$ to the classification logits $\hat{\boldsymbol{y}}$.

OOD Detection (OOD-D) aims to *identify* the semantic shift data D_{SS} from in-distribution D_{ID}. Existing methods can be generally divided into two categories, *i.e.*, post-hoc approaches and finetuning approaches. Specifically, based on a pre-trained model, the post-hoc methods (Hendrycks & Gimpel, 2016; Lee et al., 2018; Liu et al., 2020; Zhou et al., 2021) adopt a score function $s(\cdot)$, *e.g.*, maximum softmax probability (MSP) or Mahalanobis distance, to project an input instance x to a real value $s(x) \in \mathbb{R}$. The post-hoc score function $s(\cdot)$ is expected to maximize the gap between D_{ID} and D_{SS}:

$$\max \mathbb{E}_{(x,y) \sim D_{\text{ID}}} \mathbb{E}_{(x',y') \sim D_{\text{SS}}} \left| s(x) - s(x') \right|. \tag{1}$$

Besides, fine-tuning approaches (Hendrycks et al., 2018; Du et al., 2022; Wang et al., 2023; Zhang et al., 2023a) further tune the trainable parameters to enhance the pre-trained model's OOD-D capability. Among these, the epidemic method of Outlier Exposure (OE) (Hendrycks et al., 2018) leverages *extra, exposures* OOD samples $D_{\text{SS}}^{\text{train}}$ during training, namely, learning with the objective:

$$\boldsymbol{\theta}^* = \min_{\boldsymbol{\theta}} \mathbb{E}_{(x,y) \sim D_{\text{ID}}^{\text{train}}} \mathcal{L}_{\text{CE}}(f_{\boldsymbol{\theta}}(x), y) + \lambda_{\text{OE}} \cdot \mathbb{E}_{(x',y') \sim D_{\text{SS}}^{\text{train}}} \mathcal{L}_{\text{OE}}(f_{\boldsymbol{\theta}}(x')), \tag{2}$$

where the $\mathcal{L}_{\text{OE}}$ forces the outlier's logits $f(x')$ to be close to a uniform distribution. OE helps the model to recognize characteristics that are specific to the training data $D_{\text{ID}}^{\text{train}}$ and generalize to the outliers during testing ($D_{\text{SS}}^{\text{test}}$). Empirically, OE is proven effective in enlarging the gap in Eqn. 1.

OOD Generalization (OOD-G) aims to *generalize* to the covariate shift data D_{CS}, which is achieved by optimizing models that have consistent performance across domains with different covariate shifts. Following (Gulrajani & Lopez-Paz, 2021), we consider the dataset $D_e := \{(x_i^e, y_i^e)\}_{i=1}^{n_e}$ collected under multiple environment $e \in \mathcal{E}$. $D_{CS} = \{D_e : e \in \mathcal{E}\}$ denotes the collection of datasets from multiple environments with potential covariant shifts. The objective is given as:

$$\boldsymbol{\theta}^* = \min_{\boldsymbol{\theta}} \mathbb{E}_{e \in \mathcal{E}} \mathbb{E}_{(x,y) \sim D_e} \mathcal{L}_{\text{CE}}(f_{\boldsymbol{\theta}}(x), y) \text{ s.t. } \boldsymbol{\theta} \in \arg\min_{\boldsymbol{\theta}} \mathbb{E}_{(x',y') \sim D_e} \mathcal{L}_{\text{CE}}(f_{\boldsymbol{\theta}}(x'), y'), \tag{3}$$

To achieve the objective, IRM (Arjovsky et al., 2019) penalizes the model on domains with sub-optimal performance, while VREx (Krueger et al., 2021) optimizes the loss variance across domains.

Sharpness-Aware Minimization (SAM) (Foret et al., 2021) In general, optimizing neural networks minimizes target loss $\mathcal{L}$ by gradient descent. However, such an approach often causes the model to fall into a sharp local minimum. This leads the model to be sensitive to distribution shift (Chaudhari et al., 2019) and thus fails to generalize. To solve this, SAM is proposed to find a flat landscape within radius ρ center at parameter $\boldsymbol{\theta}$ with the following objective:

$$\boldsymbol{\theta}^* = \min_{\boldsymbol{\theta}} \max_{\|\epsilon\|_2 \leq \rho} \mathbb{E}_{(x,y) \sim D_{\text{ID}}} \mathcal{L}_{\text{CE}}(f_{\boldsymbol{\theta}+\epsilon}(x), y), \tag{4}$$

where ϵ is the perturbation on $\boldsymbol{\theta}$. Through the min-max optimization, SAM can induce a less-sharp convergence point $\boldsymbol{\theta}^*$ and thus improve the model's generalizability.

(a) Fine-tuning effects of OOD-D/OOD-G methods

(b) The ID-pre-trained model without fine-tuning

(c) Model fine-tuned with OOD-D method (Eqn. 2)

(d) Model fine-tuned with OOD-G method (Eqn. 3)

Figure 3: A comparison in the representation space. The effects of different training paradigms are illustrated in **(a)**. Specifically, compared to the pretrained model **(b)**, OOD-D method **(c)** enlarges the gap between D_{ID} and D_{SS}, while OOD-G method **(d)** reduces the gap between D_{ID} and D_{CS}.

(a) The ID-pre-trained model without fine-tuning

(b) Model fine-tuned with OOD-D method (Eqn. 2)

(c) Model fine-tuned with OOD-G method (Eqn. 3)

Figure 4: A comparison of energy-based score (Liu et al., 2020) in the logit space. The gap in the embedding space is also reflected in the model's prediction. Specifically, OOD-D method **(b)** lowers the confidence of D_{CS} and D_{SS}, while OOD-G method **(c)** increases the confidence of D_{CS} and D_{SS}.

3   AN IN-DEPTH ANALYSIS OF THE DETECTION-GENERALIZATION PARADOX

In this section, we delve into the distinct behaviors when model training with different paradigms that induce the generalization-detection paradox. We start from the model's inference pipeline:

$$D \in \{D_{\text{ID}}, D_{\text{CS}}, D_{\text{SS}}\}, \forall (x,y) \sim D, \ x \xmapsto{f_{\boldsymbol{\theta}}^{\text{EMB}}(\cdot)} \boldsymbol{h}_x \xmapsto{f_{\boldsymbol{\theta}}^{\text{CLS}}(\cdot)} \hat{\boldsymbol{y}} \xmapsto{\mathcal{L}(\cdot,\cdot)} \mathcal{L}(\hat{\boldsymbol{y}}, y). \quad (5)$$

In particular, we investigate the three informative variables, *i.e.*, representation $\boldsymbol{h}_x$, logits $\hat{\boldsymbol{y}}$, and loss $\mathcal{L}(\hat{\boldsymbol{y}}, y)$. Specifically, we conduct 1) a data-perspective analysis via the $\boldsymbol{h}_x$ and $\hat{\boldsymbol{y}}$ in Sec. 3.1, and 2) a model-perspective analysis via the landscape and sharpness on $\mathcal{L}(\hat{\boldsymbol{y}}, y)$ in Sec. 3.2. These two perspectives provide insights into the paradox's intuitive manifestation and underlying cause.

3.1   DATA-PERSPECTIVE ANALYSIS VIA REPRESENTATIONS AND LOGITS

Analysis on the representation space. An ideal model should possess (1) a small representation gap between D_{ID} and D_{CS}, in order to successfully generalize to D_{CS} samples, and (2) a large gap between D_{ID} and D_{SS} to clearly discriminate the D_{SS} samples. However, this *cannot* be achieved by adopting the current OOD-D / OOD-G methods. As shown in Fig. 3, OOD-D method enlarges the gap between D_{ID} and D_{SS} (enhance the OOD-D) but also enlarges the gap between D_{ID} and D_{CS} (degenerate the OOD-G). On the other hand, OOD-G method reduces the gap between D_{ID} and D_{CS} (enhance the OOD-G) but also reduces the gap between D_{ID} and D_{SS} (degenerate the OOD-D).

Analysis on the logit space. We employ the energy-based score in Eqn. 1 to indicate the model prediction confidence. As shown in Fig. 4, the OOD-D method enlarges the gap between D_{ID} and D_{CS} would decrease the model's prediction on D_{CS} (degenerate the OOD-G). On the other side, the OOD-G would increase the confidence on both D_{SS} and D_{CS} (degenerate the OOD-D).

3.2   MODEL-PERSPECTIVE ANALYSIS VIA LOSS SHARPNESS AND LANDSCAPE

Next, we investigate from the lens of landscape (Li et al., 2018a) and sharpness (Keskar et al., 2016). **Landscape** indicates the flatness of local minima $\boldsymbol{\theta}$. Specifically, with a chosen center point $\boldsymbol{\theta}$ and

(a) Loss landscape of ID-pre-trained model
(b) Loss landscape of OOD-D fine-tuned model
(c) Loss landscape of OOD-G fine-tuned model
(d) Impact of fine-tuning on model's loss sharpness

Figure 5: A comparison in the loss space. We show the loss landscape and sharpness comparison across different training strategies. **(a)-(c)**: the loss landscapes of model training with different approaches on $D_{\text{ID}}^{\text{train}}$ using cross-entropy loss. **(d)**: sharpness comparison across different approaches.

(a) ID-pre-trained   (b) OOD-D fine-tuned   (c) OOD-G fine-tuned   (d) loss sharpness

Figure 6: A comparison of loss landscape and sharpness across different training strategies on $D_{\text{ID}}^{\text{test}}$.

(a) ID-pre-trained   (b) OOD-D fine-tuned   (c) OOD-G fine-tuned   (d) loss sharpness

Figure 7: A comparison of loss landscape and sharpness across different training strategies on $D_{\text{CS}}^{\text{test}}$.

two direction vectors, $\boldsymbol{\delta}$ and $\boldsymbol{\eta}$, we plot the 2D surface landscape using the following function:

$$\text{landscape}(\boldsymbol{\theta}, D, \alpha, \beta) = \mathbb{E}_{(x,y)\sim D}\mathcal{L}(f_{\boldsymbol{\theta}+\alpha\boldsymbol{\delta}+\beta\boldsymbol{\eta}}(x), y). \tag{6}$$

Shaprness also indicates the flatness of the converging area around parameters $\boldsymbol{\theta}$. Given a model $f_{\boldsymbol{\theta}}$ on a dataset D and loss function $\mathcal{L}$, the sharpness of the region at radii ρ center at $\boldsymbol{\theta}$ is given as:

$$\text{sharpness}(\boldsymbol{\theta}, D) \triangleq \max_{\|\epsilon\|_2 \le \rho} \mathbb{E}_{(x,y)\sim D}\big[\mathcal{L}(f_{\boldsymbol{\theta}+\epsilon}(x), y) - \mathcal{L}(f_{\boldsymbol{\theta}}(x), y)\big], \tag{7}$$

where ϵ is small perturbation imposing on $\boldsymbol{\theta}$. A lower sharpness value indicates less loss variance within radii ρ and, thereby, a flatter neighborhood around the converging area of $\boldsymbol{\theta}$. A flatter region around $\boldsymbol{\theta}$ generally leads the model to have a better generalization ability (Foret et al., 2021).

Here, we visualize the model's loss landscape and sharpness in Figs. 5, 6 and 7, wherein the model witnesses different landscapes when various distributions and training methods. Overall, the qualitative landscapes (Figs. 5(a-c)) are aligned with the quantitative sharpness curves (Fig. 5(d)).

Notably, OOD-D method leads to a relatively flat landscape on the $D_{\text{ID}}^{\text{test}}$ but experiences large sharpness in the $D_{\text{CS}}^{\text{test}}$, indicating its degeneration in generalization ability. Conversely, the OOD-G fine-tuned model has flat landscapes (low sharpness) on $D_{\text{ID}}^{\text{train}}$ and $D_{\text{CS}}^{\text{test}}$ but with a high sharpness on $D_{\text{ID}}^{\text{test}}$. Namely, this model generalizes well on $D_{\text{CS}}^{\text{test}}$ at the cost of worse performance on $D_{\text{ID}}^{\text{test}}$.

Therefore, an ideal model should have low sharpness on both in-distribution and covariate-shift data. However, this cannot be achieved by solely adopting the current OOD-D or OOD-G method. Besides, it is discovered that a lower sharpness on $D_{\text{ID}}^{\text{train}}$ might ensure a lower sharpness on $D_{\text{ID}}^{\text{test}}$ or $D_{\text{CS}}^{\text{test}}$. To handle the paradox, one conceptual idea is to actively seek flatness within radii ρ to enhance generalization ability under the constraint of OOD-D objective to guarantee the detection capability.

4 DR-SAM: DISTRIBUTION-ROBUST SHARPNESS-AWARE MINIMIZATION

Recall that the generalization ability is bounded by the neighborhood-wise training loss (Foret et al., 2021), which is indicated by the sharpness. Taking both objectives of OOD detection and generalization into consideration, we propose a novel optimization framework, Distribution-Robust Sharpness-Aware Minimization (DR-SAM). The overall pipeline of the proposed method is elaborated in Algorithm 1. Specifically, DR-SAM obtains the optimal parameters $\boldsymbol{\theta}^*$ as follows:

$$\boldsymbol{\theta}^* = \min_{\boldsymbol{\theta}} \max_{\|\epsilon\|_2 \le \rho} \underbrace{\mathbb{E}_{x \sim D_{\text{ID}}^{\text{train}}} \mathcal{L}_{\text{CE}}(f_{\boldsymbol{\theta}+\epsilon}(x), y) + \lambda \cdot \mathbb{E}_{x' \sim D_{\text{SS}}^{\text{train}}} \mathcal{L}_{\text{OE}}(f_{\boldsymbol{\theta}+\epsilon}(x'))}_{\mathcal{L}_{\text{DR-SAM}}(f_{\boldsymbol{\theta}+\epsilon}, D_{\text{ID}}^{\text{train}}, D_{\text{SS}}^{\text{train}})}, \qquad (8)$$

where ϵ denotes the perturbation on model parameters. Notably, the ϵ here is calculated as:

$$\epsilon = \frac{\rho \cdot \nabla_{\boldsymbol{\theta}} \mathcal{L}_{\text{DR-SAM}}(f_{\boldsymbol{\theta}+\epsilon}, \texttt{aug}(D_{\text{ID}}^{\text{train}}), D_{\text{SS}}^{\text{train}})}{||\nabla_{\boldsymbol{\theta}} \mathcal{L}_{\text{DR-SAM}}(f_{\boldsymbol{\theta}+\epsilon}, \texttt{aug}(D_{\text{ID}}^{\text{train}}), D_{\text{SS}}^{\text{train}})||}, \qquad (9)$$

where the augmentation $\texttt{aug}(\cdot)$ on in-distribution data aims to simulate the covariate-shift data and guarantee the model's OOD generalization capacity during optimization. Then, by applying an optimizer, *e.g.*, the stochastic gradient descent (SGD), we obtain the gradient direction of Eqn. 9 that indicates the *worst-case* from the current point. By shifting $\boldsymbol{\theta}$ towards this gradient direction, we can extrapolate the decision boundary with ratio ρ to cover more covariate-shift samples. Besides, the adoption of auxiliary outliers $D_{\text{SS}}^{\text{train}}$ is to guarantee better OOD detection capability on test-time outliers encountered. Then, the parameters are iteratively updated with learning rate η as:

$$\boldsymbol{\theta}' = \boldsymbol{\theta} - \eta \nabla_{\boldsymbol{\theta}+\epsilon} \mathcal{L}_{\text{DR-SAM}}(f_{\boldsymbol{\theta}+\epsilon}, D_{\text{ID}}^{\text{train}}, D_{\text{SS}}^{\text{train}}). \qquad (10)$$

Algorithm 1 DR-SAM: Distribution-Robust Sharpness-Aware Minimization

Require: In-distribution data $D_{\text{ID}}^{\text{train}}$, auxiliary semantic-shift data $D_{\text{SS}}^{\text{train}}$, data augmentation operator $\texttt{aug}$, an ID-pre-trained model $f_{\boldsymbol{\theta}}$, number of iterations T.
1: **for** $t = 1 \ldots T$ **do**
2:     Sample mini-batch data $B_{\text{ID}} \subset D_{\text{ID}}^{\text{train}}$ and $B_{\text{SS}} \subset D_{\text{SS}}^{\text{train}}$.
3:     Compute the loss $\mathcal{L}_{\epsilon} \leftarrow \mathcal{L}_{\text{DR-SAM}}(f_{\theta}, \texttt{aug}(B_{\text{ID}}^{\text{train}}), B_{\text{SS}}^{\text{train}})$.
4:     Compute the perturbation $\epsilon \leftarrow \frac{\rho \cdot \nabla_{\boldsymbol{\theta}} \mathcal{L}_{\epsilon}}{||\nabla_{\boldsymbol{\theta}} \mathcal{L}_{\epsilon}||}$.
5:     Compute the loss $\mathcal{L}_{\theta+\epsilon} \leftarrow \mathcal{L}_{\text{DR-SAM}}(f_{\boldsymbol{\theta}+\epsilon}, B_{\text{ID}}^{\text{train}}, B_{\text{SS}}^{\text{train}})$.
6:     Update the parameters $\boldsymbol{\theta} \leftarrow \boldsymbol{\theta} - \eta \nabla_{\boldsymbol{\theta}+\epsilon} \mathcal{L}_{\theta+\epsilon}$.
7: **end for**
8: **return** The fine-tuned model $f_{\boldsymbol{\theta}}$.

It is noteworthy that the most distinct point in DR-SAM compared with the vanilla SAM is the $\texttt{aug}(\cdot)$, which is applied solely during the perturbation generation stage. The intuition here is to create a challenging perturbation aware of the worst case for generalization under covariate shift, rather than only exploring the separation between in-distribution data and out-of-distribution data. The reason that we go back to the training without $\texttt{aug}(\cdot)$ at the parameter optimization stage (see Lines 5 and 6 in Algorithm 1) is to preserve the benefits of the training trajectory for OOD-D, enabling us to simultaneously improve the generalization and detection in a more harmonious manner. As will be shown later, such a novel design brings us a significant gain compared with the vanilla SAM in the following experiments, which helps to break the generalization-detection paradox for OOD data.

4.1 COMPARING DR-SAM WITH THE MOST-RELATED WORKS

Several previous works also study the model's detection-generalization problem. The pioneer work SCONE (Bai et al., 2023) proposes to enhance the model's OOD-D and OOD-G ability simultaneously when training the model with wild data. In contrast, DR-SAM follows the common practice in OOD-D. Unlike SCONE, DR-SAM employs training distribution containing only labeled in-distribution samples and unlabeled auxiliary outliers. In addition, DR-SAM focuses on alleviating the generalization trade-off due to the employment of auxiliary outliers. Whereas SCONE (Bai et al., 2023) pays more attention to handling samples from mixing types of distributions. Averly & Chao (2023) proposes a novel evaluation framework that focuses on detecting and rejecting samples beyond the model's classification capability, which aims to evaluate the existing model's robustness with

Method	Near-OOD		Far-OOD		Average		Accuracy	
	FPR@95↓	AUROC↑	FPR@95↓	AUROC↑	FPR@95↓	AUROC↑	ID↑	OOD↑
Post-hoc								
MSP	$48.14_{\pm4.02}$	$88.04_{\pm0.26}$	$31.68_{\pm1.77}$	$90.75_{\pm0.43}$	39.91	89.39	$95.06_{\pm0.30}$	$79.24_{\pm0.45}$
EBO	$61.63_{\pm4.91}$	$87.61_{\pm0.47}$	$41.47_{\pm5.09}$	$91.25_{\pm0.90}$	51.55	89.43	$95.06_{\pm0.30}$	$79.24_{\pm0.45}$
Gen	$53.85_{\pm3.10}$	$88.22_{\pm0.30}$	$34.60_{\pm1.42}$	$91.38_{\pm0.68}$	44.23	89.80	$95.06_{\pm0.30}$	$79.24_{\pm0.45}$
KNN	$33.91_{\pm0.38}$	$90.67_{\pm0.20}$	$24.21_{\pm0.45}$	$92.99_{\pm0.14}$	29.06	91.83	$95.06_{\pm0.30}$	$79.24_{\pm0.45}$
RMDS	$38.78_{\pm2.52}$	$89.83_{\pm0.28}$	$25.25_{\pm0.70}$	$92.23_{\pm0.21}$	32.02	91.03	$95.06_{\pm0.30}$	$79.24_{\pm0.45}$
VIM	$44.76_{\pm2.18}$	$88.73_{\pm0.28}$	$24.97_{\pm0.49}$	$93.50_{\pm0.23}$	34.87	91.12	$95.06_{\pm0.30}$	$79.24_{\pm0.45}$
Training Methods (w/o Outlier Data)								
ConfBranch	$36.96_{\pm0.52}$	$87.37_{\pm0.33}$	$30.70_{\pm0.56}$	$88.78_{\pm0.33}$	33.83	88.08	$93.66_{\pm0.27}$	$77.19_{\pm0.39}$
G-ODIN	$63.32_{\pm5.43}$	$84.35_{\pm1.38}$	$49.54_{\pm6.31}$	$88.54_{\pm1.37}$	56.43	86.45	$93.33_{\pm0.25}$	$77.56_{\pm0.24}$
LogitNorm	$28.32_{\pm0.85}$	$92.40_{\pm0.24}$	$15.17_{\pm1.04}$	$96.05_{\pm0.19}$	21.75	94.23	$94.89_{\pm0.19}$	$79.09_{\pm0.66}$
Training Methods (w/ Outlier Data)								
OE	$17.42_{\pm0.75}$	$95.51_{\pm0.26}$	$10.70_{\pm0.58}$	$97.33_{\pm0.23}$	14.06	96.42	$95.02_{\pm0.08}$	$78.77_{\pm0.38}$
MCD	$38.48_{\pm0.38}$	$87.94_{\pm0.07}$	$33.20_{\pm0.46}$	$89.27_{\pm0.18}$	35.84	88.61	$93.92_{\pm0.11}$	$78.01_{\pm0.23}$
MixOE	$87.53_{\pm6.17}$	$85.19_{\pm1.78}$	$66.63_{\pm12.85}$	$89.11_{\pm1.89}$	77.08	87.15	$96.13_{\pm0.18}$	$79.94_{\pm0.58}$
OOD-G Methods (w/ covariate shift samples)								
ERM	$43.51_{\pm4.66}$	$88.67_{\pm0.36}$	$27.44_{\pm1.75}$	$91.26_{\pm0.26}$	35.48	89.97	$93.94_{\pm0.23}$	$89.52_{\pm0.24}$
VRE-x	$43.96_{\pm5.32}$	$88.68_{\pm0.40}$	$28.69_{\pm5.20}$	$91.10_{\pm0.66}$	36.33	89.89	$93.86_{\pm0.00}$	$89.48_{\pm0.10}$
GroupDRO	$42.37_{\pm4.79}$	$88.75_{\pm0.31}$	$27.92_{\pm4.24}$	$91.31_{\pm0.56}$	35.15	90.03	$93.84_{\pm0.20}$	$89.30_{\pm0.21}$
Sharpness-based Methods								
SAM	$28.86_{\pm0.50}$	$91.09_{\pm0.10}$	$21.45_{\pm1.03}$	$93.08_{\pm0.39}$	25.15	92.08	$95.69_{\pm0.21}$	$80.69_{\pm0.65}$
DR-SAM	$18.81_{\pm1.07}$	$95.41_{\pm0.20}$	$5.90_{\pm1.39}$	$98.67_{\pm0.40}$	12.36	97.04	$95.13_{\pm0.19}$	$80.50_{\pm0.55}$

Table 1: Performance comparison on the CIFAR-10 benchmark. All methods are trained on the same backbone. ↑ indicates larger values are preferred, and ↓indicates smaller values are better. All performances are reported by percentage and are averaged by multiple trials.

samples from mixing distribution types. Conversely, DR-SAM simultaneously enhances the model's generalization and detection ability.

The most related work DUL (Zhang et al., 2024) propose a novel and theoretical guarantee optimization framework to enhance the model's OOD-D ability while maintaining the original OOD-G capability. DUL incorporates distributional uncertainty in the Bayesian framework to bridge the detection and generalization learning target. Specifically, DUL encourages the exposed outlier to have high uncertainty while maintaining a non-increased overall uncertainty to ensure generalization capability. Instead of focusing on decoupling the uncertainty under the Bayesian framework, we propose DR-SAM to minimize the model's loss of sharpness under the framework of SAM. We provide a detailed discussion in Appendix F.3.

5 EXPERIMENTS

In this section, we present the comprehensive experiments of the proposed method. To begin with, we provide the experimental setups in detail in Sec. 5.1. Next, we compare the proposed method's performance with a series of post-hoc scoring functions and the OE-based approaches with different strategies on the adopted auxiliary outliers in Sec. 5.2. Then, we conduct various ablation studies in Sec. 5.3 and visualizations in Sec. 5.4 to provide further insights into the proposed method.

5.1 SETUPS

To evaluate the proposed method under complex real-world scenarios, we employ a wide range of datasets that cover different levels of distribution shift $w.r.t.$ the in-distribution data D_{ID}, which are listed as follows. All experiments are conducted on ResNet-18 that pre-trained on respecting D_{ID}.

CIFAR Benchmark. We empirically evaluate the proposed method on CIFAR-10 and CIFAR-100 benchmarks based on OpenOOD (Zhang et al., 2023b). For the auxiliary outliers, we adopt the TIN-597 (Zhang et al., 2023b) that sampled from ImageNet-1K (Deng et al., 2009) and has no overlap with the test sets. For CIFAR-10/100, we consider TinyImageNet (Le & Yang, 2015) and CIFAR-100/10 as Near-OOD considering their semantic similarity to the D_{ID}. CIFAR-10/100 share the same group of Far-OOD datasets, namely MNIST (Deng, 2012), SVHN (Netzer et al., 2011), Textures (Cimpoi et al., 2014), and Places365 (Zhou et al., 2018). To assess the model's generalization ability, we employ the covariate-shifted CIFAR datasets (Hendrycks & Dietterich, 2018), namely CIFAR-10-C and CIFAR-100-C, which adopt various image augmentation with different strengths.

Method	Near-OOD		Far-OOD		Average		Accuracy	
	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	ID↑	OOD↑
Post-hoc								
MSP	54.84±0.58	80.21±0.13	58.52±1.12	77.83±0.45	56.68	79.02	77.26±0.09	36.59±0.04
RMDS	55.43±0.31	80.17±0.09	52.65±0.64	82.97±0.42	54.04	81.57	77.26±0.09	36.59±0.04
Gen	54.23±0.54	81.27±0.10	57.04±1.01	79.59±0.54	55.64	80.43	77.26±0.09	36.59±0.04
EBO	55.77±0.64	80.82±0.09	56.47±1.42	79.83±0.62	56.12	80.33	77.26±0.09	36.59±0.04
VIM	62.61±0.24	75.04±0.14	50.75±1.00	81.64±0.63	56.68	78.34	77.26±0.09	36.59±0.04
KNN	61.18±0.13	80.16±0.16	53.61±0.25	82.43±0.17	57.40	81.30	77.26±0.09	36.59±0.04
Training Methods (w/o Outlier Data)								
ConfBranch	78.04±0.11	67.30±0.08	74.34±2.27	63.99±0.94	76.19	65.65	74.93±0.27	35.49±0.13
G-ODIN	68.07±6.02	74.72±2.93	56.42±2.87	78.80±1.74	62.25	76.76	69.87±4.46	33.10±2.11
LogitNorm	58.99±0.46	79.69±0.31	48.61±1.69	82.91±1.21	53.80	81.30	75.83±0.26	35.92±0.12
Training Methods (w/ Outlier Data)								
OE	33.20±0.59	87.16±0.44	39.03±1.47	88.12±0.39	36.11	87.64	76.51±0.35	36.24±0.16
MCD	58.68±0.30	77.74±0.18	62.02±0.33	75.91±0.13	60.35	76.83	74.66±0.31	35.36±0.15
MixOE	56.89±2.04	80.44±0.69	58.06±4.45	78.70±2.03	57.48	79.57	78.01±0.05	36.95±0.02
OOD-G Methods (w/ Covariate shift samples)								
ERM	59.84±0.15	77.89±0.09	63.67±0.83	73.13±0.14	61.76	75.51	72.10±0.29	34.15±0.14
VRE-x	59.22±0.53	77.99±0.05	63.49±1.29	73.52±0.35	61.35	75.76	72.14±0.49	34.17±0.23
GroupDRO	59.29±0.03	77.87±0.08	62.67±0.33	73.98±0.15	60.98	75.92	72.37±0.33	34.28±0.16
Sharpness-based Methods								
SAM	52.32±0.15	81.32±0.07	55.50±0.19	78.97±0.33	53.91	80.14	78.53±0.27	37.20±0.13
DR-SAM	29.58±0.20	89.13±0.03	46.77±1.54	84.73±0.80	38.18	86.93	77.91±0.28	36.91±0.13

Table 2: Performance comparison on the CIFAR-100 benchmark. All methods are trained on the same backbone. ↑ indicates larger values are preferred, and ↓indicates smaller values are better.

Method	Near-OOD		Far-OOD		Average		Accuracy	
	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	ID↑	OOD↑
Post-hoc								
MSP	54.93±0.36	83.29±0.06	35.39±0.38	90.13±0.09	45.16	86.71	86.38±0.07	43.85±0.09
RMDS	54.09±0.64	82.54±0.26	32.50±0.77	88.06±0.35	43.30	85.30	86.38±0.07	43.85±0.09
Gen	55.16±0.13	83.64±0.04	32.13±0.64	91.35±0.11	43.65	87.50	86.38±0.07	43.85±0.09
EBO	60.31±0.56	82.41±0.07	34.84±1.29	90.84±0.22	47.58	81.63	86.38±0.07	43.85±0.09
VIM	59.36±0.75	78.59±0.24	27.22±0.34	91.26±0.18	43.29	84.93	86.38±0.07	43.85±0.09
KNN	60.32±0.50	81.46±0.18	27.30±0.73	93.15±0.23	43.81	87.31	86.38±0.07	43.85±0.09
Training Methods (w/o Outlier Data)								
ConfBranch	61.56±0.43	79.00±0.14	33.56±0.41	90.64±0.05	47.56	84.82	86.23±0.23	44.34±0.26
G-ODIN	68.92±0.60	77.62±0.07	29.69±1.01	92.25±0.13	49.31	84.94	85.38±0.15	43.19±0.02
LogitNorm	57.36±0.57	82.23±0.15	26.61±0.52	92.92±0.25	41.99	87.58	86.11±0.27	44.32±0.34
Training Methods (w/ Outlier Data)								
OE	52.44±0.67	86.93±0.21	36.75±1.31	87.88±0.31	44.60	87.41	85.67±0.43	43.30±0.40
MCD	59.60±0.63	79.05±0.12	44.48±0.75	86.08±0.21	52.04	82.57	79.33±0.34	35.09±0.16
MixOE	60.50±1.27	82.08±0.43	42.36±1.85	87.66±0.50	51.43	84.87	86.76±0.43	43.49±0.19
Ours								
DR-SAM	52.23±0.60	85.10±0.21	34.01±0.69	89.02±0.19	43.12	87.06	86.63±0.15	46.93±0.12

Table 3: Performance comparison on the ImageNet-200 benchmark. All methods are trained on the same backbone. ↑ indicates larger values are preferred, and ↓indicates smaller values are better.

ImageNet-200 Benchmark. The ImageNet-200 is the subset of the ImageNet-1K (Deng et al., 2009). The rest of the samples act as the auxiliary outliers for training. We employ SSB-hard (Vaze et al., 2021) and NINCO (Bitterwolf et al., 2023) as `Near-OOD`. `Far-OOD` includes iNaturalist (Van Horn et al., 2018), Textures, and OpenImage-O (Wang et al., 2022). To assess the generalization ability, we adopt the ImageNet-R (Hendrycks et al., 2021) with style change from the D_{ID}.

Metrics. To assess the detection ability, we adopt (1) area under the receiver operating characteristic curve (AUROC), which reflects the probability that a positive sample scores higher than a negative one (Fawcett, 2006), and (2) false positive rate at 95% true positive rate (FPR@95) (Liang et al., 2017), which indicates the probability of misclassifying a negative sample as positive when the true positive rate is 95%. We also report the classification accuracy oon D_{ID} and D_{CS} for evaluation.

Baselines. We compare the proposed method with approaches that excel in OOD-D or OOD-G. We employ six post-hoc scoring functions, namely maximum softmax probability (MSP) (Hendrycks & Gimpel, 2016), energy score (EBO) (Liu et al., 2020), relative Mahalanobis distance (RMDS) (Ren et al., 2021), GEN (Liu et al., 2023), VIM (Wang et al., 2022), and KNN (Sun et al., 2022). For methods that do not require outliers, we adopt ConfBranch (DeVries & Taylor, 2018), G-ODIN (Hsu et al., 2020), and LogitNorm (Wei et al., 2022). For methods that require outliers, we employ OE (Hendrycks et al., 2018), MCD (Yu & Aizawa, 2019), and MixOE (Zhang et al., 2023a). For OOD-G, we consider ERM, VRE-x (Krueger et al., 2021), and GroupDRO (Sagawa et al., 2020).

(a) Impact of perturbation strength on OOD-D (b) Impact of perturbation strength on OOD-G (c) Impact of different augmentation on accuracy (d) Impact of different augmentation on AUROC

Figure 8: Ablation study on perturbation factors of DR-SAM.

(a) ID-pre-trained (b) OOD-D (c) OOD-G (d) DR-SAM

Figure 9: A comparison in the representation space for different methods.

Figure 10: Loss landscape visualization for different methods on D_{CS}^{test} of CIFAR-10. From (a) to (d): OE, ERM, SAM, and DR-SAM.

5.2 MAIN RESULTS

In this part, we present the comparison and discussion of different approaches to demonstrate the effectiveness of the proposed method. Since OE-based approaches involve auxiliary outliers during training, the model generally achieves improved empirical performance on detection-related metrics.

For the training methods, G-ODIN and MCD caused a 9.54% and 9.53%, respectively, decrease in OOD-G accuracy compared to the original MSP baseline as shown in Tab. 1 and Tab. 2. G-ODIN decomposes softmax confidence to separate semantic samples from D_{ID}, while MCD ensembles multiple classification heads to promote disagreement between each head's predictions on OOD samples. We attribute this decline to the explicitly promoted disagreement between D_{ID} and D_{SS}, without adequately considering the influence of D_{CS}. LogitNorm, ConfBranch, and OE also suffer from a decrease in the ability to generalize. However, we observe that MixOE helps the model to generalize to covariate shift samples. By constructing mixed samples using D_{ID} and auxiliary outliers for training, which could cover parts of D_{CS} and improve the model's generalization ability.

We observe a positive fine-tuning with OOD-G approaches in Tab. 1. These methods enhance detection and generalization in both realms, though the improvement in detection is negligible compared to generalization. However, on more fine-grand datasets like CIFAR-100 (Tab. 2), the OOD-G methods suffer from up to 8% decrease in the FPR@95 compared to the MSP. Our method can consistently achieve better detection performance across the CIFAR benchmarks and shows scalability in the ImageNet-200 benchmark, as shown in Tab. 3. DR-SAM shows improvement in handling covariate shift samples, which verifies its effectiveness in addressing the trade-off. We provide further experiments and discussions in Appendix B.

5.3 ABLATION STUDIES

The impact of ρ. We aim to understand how radii ρ impact the model's performance on OOD-D/G under different choices of ρ and λ, shown in Fig. 8. Notably, a flat region with small ρ generally

enhances the performance of both OOD-D and OOD-G, as indicated by low FPR@95 in Fig. 8(a) and high accuracy in Fig. 8(b). However, a smaller ρ is preferred for the OOD-D, while OOD-G pursues a larger flatness region around the coverage area. Recall the aforementioned analysis in Sec. 3, which indicates that the model should seek flatness within specific ρ to boost OOD-D/G. We provide further experiments in Appendix A to show the

The impact of $\text{aug}(\cdot)$. In Fig. 8, we demonstrate the impact of different augmentation on the model's OOD-D/G performance. We employ different augmentations that are adopted in Hendrycks & Dietterich (2018). As shown in Fig. 8(c), different augmentations generally affect both in-distribution and covariate-shift samples, wherein Saturate and Brightness have the most positive impact on the model's generalization ability. In Fig. 8(d), we show the augmentation's impact on OOD-D performance. Generally, a proper augmentation can enhance both OOD-D and OOD-G simultaneously by helping the model to enlarge the gap between D_{CS} and $D_{\textbf{SS}}$.

5.4 VISUALIZATION

In this part, we conduct further discussions from the lens of loss landscape and representation visualization. DR-SAM successfully achieves the previously mentioned desired property for the model to handle the detection-generalization paradox. In Fig. 9(d), we demonstrate that DR-SAM can enlarges the gap between D_{ID} and D_{SS} while reduce the gap between D_{ID} and D_{CS}.

In Fig. 10, we demonstrate the loss of landscapes for different methods on $D_{\text{CS}}^{\text{test}}$ of CIFAR-10. OE leads the model to minima with high sharpness, making it sensitive to distribution shift, thus enhancing the model's detection ability while sacrificing the generalization performance. ERM achieves higher sharpness than SAM and DR-SAM, but it does not explicitly optimize the loss's sharpness. DR-SAM, on the other hand, achieves lower sharpness within the specific radii but high at the outer region. This allows the model to be robust to the covariate-shifted samples while sensitive to the semantic-shifted ones.

6 CONCLUSION

In this paper, we identify the Detection-Generalization Paradox on out-of-distribution (OOD) data, where optimizing for detection can degrade generalization and vice versa. We analyze this paradox by examining models trained under various paradigms, focusing on representation, logits, and loss across different data shifts. To address this, we propose Distribution-Robust Sharpness-Aware Minimization (DR-SAM), an optimization framework that balances OOD detection and generalization. DR-SAM uses data augmentation and perturbations on model parameters to simulate covariate-shift scenarios and enhance OOD generalization. Empirical results show that DR-SAM improves the detection of semantic-shift samples and boosts generalization for covariate-shift samples.

ETHIC STATEMENT

The study does not involve human subjects, data set releases, potentially harmful insights, applications, conflicts of interest, sponsorship, discrimination, bias, fairness concerns, privacy or security issues, legal compliance issues, or research integrity issues.

REPRODUCIBILITY STATEMENT

The experimental setups for training and evaluation are described in detail in Appendix E, and the experiments are all conducted using public datasets. We provide the link to our source codes to ensure the reproducibility of our experimental results: https://anonymous.4open.science/r/DR-SAM-9C89/.

REFERENCES

Martin Arjovsky. Out of distribution generalization in machine learning. PhD thesis, New York University, 2020.

Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization. In arXiv, 2019.

Reza Averly and Wei-Lun Chao. Unified out-of-distribution detection: A model-specific perspective. In CVPR, 2023.

Haoyue Bai, Gregory Canal, Xuefeng Du, Jeongyeol Kwon, Robert D Nowak, and Yixuan Li. Feed two birds with one scone: Exploiting wild data for both out-of-distribution generalization and detection. In ICML, 2023.

Julian Bitterwolf, Alexander Meinke, and Matthias Hein. Certifiably adversarially robust detection of out-of-distribution data. In NeurIPS, 2020.

Julian Bitterwolf, Maximilian Mueller, and Matthias Hein. In or out? fixing imagenet out-of-distribution detection evaluation. In arXiv, 2023.

Pratik Chaudhari, Anna Choromanska, Stefano Soatto, Yann LeCun, Carlo Baldassi, Christian Borgs, Jennifer Chayes, Levent Sagun, and Riccardo Zecchina. Entropy-sgd: Biasing gradient descent into wide valleys. Journal of Statistical Mechanics: Theory and Experiment, 2019(12):124018, 2019.

Tianlong Chen, Sijia Liu, Shiyu Chang, Yu Cheng, Lisa Amini, and Zhangyang Wang. Adversarial robustness: From self-supervised pre-training to fine-tuning. In CVPR, 2020.

Mircea Cimpoi, Subhransu Maji, Iasonas Kokkinos, Sammy Mohamed, and Andrea Vedaldi. Describing textures in the wild. In CVPR, 2014.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In CVPR, 2009.

Li Deng. The mnist database of handwritten digit images for machine learning research [best of the web]. IEEE Signal Processing Magazine, 29(6):141–142, 2012. doi: 10.1109/MSP.2012.2211477.

Terrance DeVries and Graham W Taylor. Learning confidence for out-of-distribution detection in neural networks. In arXiv, 2018.

Andrija Djurisic, Nebojsa Bozanic, Arjun Ashok, and Rosanne Liu. Extremely simple activation shaping for out-of-distribution detection. In arXiv, 2022.

Xuefeng Du, Zhaoning Wang, Mu Cai, and Yixuan Li. Vos: Learning what you don't know by virtual outlier synthesis. In ICLR, 2022.

Tom Fawcett. An introduction to roc analysis. Pattern recognition letters, 27(8):861–874, 2006.

Pierre Foret, Ariel Kleiner, Hossein Mobahi, and Behnam Neyshabur. Sharpness-aware minimization for efficiently improving generalization. In ICLR, 2021.

Ishaan Gulrajani and David Lopez-Paz. In search of lost domain generalization. In ICLR, 2021.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. In ICLR, 2019.

Dan Hendrycks and Thomas G Dietterich. Benchmarking neural network robustness to common corruptions and surface variations. In arXiv, 2018.

Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. In ICLR, 2016.

Dan Hendrycks, Mantas Mazeika, and Thomas Dietterich. Deep anomaly detection with outlier exposure. In ICLR, 2018.

Dan Hendrycks, Mantas Mazeika, Saurav Kadavath, and Dawn Song. Using self-supervised learning can improve model robustness and uncertainty. In NeurIPS, 2019.

Dan Hendrycks, Steven Basart, Norman Mu, Saurav Kadavath, Frank Wang, Evan Dorundo, Rahul Desai, Tyler Zhu, Samyak Parajuli, Mike Guo, et al. The many faces of robustness: A critical analysis of out-of-distribution generalization. In ICCV, 2021.

Waleed Hilal, S Andrew Gadsden, and John Yawney. Financial fraud: a review of anomaly detection techniques and recent advances. Expert systems With applications, 2022.

Zesheng Hong, Yubiao Yue, Yubin Chen, Huanjie Lin, Yuanmei Luo, Mini Han Wang, Weidong Wang, Jialong Xu, Xiaoqi Yang, Zhenzhang Li, et al. Out-of-distribution detection in medical image analysis: A survey. In arXiv, 2024.

Yen-Chang Hsu, Yilin Shen, Hongxia Jin, and Zsolt Kira. Generalized odin: Detecting out-of-distribution image without learning from out-of-distribution data. In CVPR, 2020.

Rui Huang and Yixuan Li. Mos: Towards scaling out-of-distribution detection for large semantic space. In CVPR, 2021.

Zeyi Huang, Haohan Wang, Eric P Xing, and Dong Huang. Self-challenging improves cross-domain generalization. In ECCV, 2020.

Zhuo Huang, Xiaobo Xia, Li Shen, Bo Han, Mingming Gong, Chen Gong, and Tongliang Liu. Harnessing out-of-distribution examples via augmenting content and style. In arXiv, 2022.

Ahmadreza Jeddi, Mohammad Javad Shafiee, and Alexander Wong. A simple fine-tuning is all you need: Towards robust deep learning via adversarial fine-tuning. In arXiv, 2020.

Julian Katz-Samuels, Julia B Nakhleh, Robert Nowak, and Yixuan Li. Training ood detectors in their natural habitats. In ICML, 2022.

Nitish Shirish Keskar, Dheevatsa Mudigere, Jorge Nocedal, Mikhail Smelyanskiy, and Ping Tak Peter Tang. On large-batch training for deep learning: Generalization gap and sharp minima. In ICLR, 2016.

Daehee Kim, Youngjun Yoo, Seunghyun Park, Jinkyu Kim, and Jaekoo Lee. Selfreg: Self-supervised contrastive regularization for domain generalization. In CVPR, 2021.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. Technical Report TR-2009, University of Toronto, 2009.

David Krueger, Ethan Caballero, Joern-Henrik Jacobsen, Amy Zhang, Jonathan Binas, Dinghuai Zhang, Remi Le Priol, and Aaron Courville. Out-of-distribution generalization via risk extrapolation (rex). In ICML, 2021.

Ya Le and Xuan Yang. Tiny imagenet visual recognition challenge. CS 231N, 7(7):3, 2015.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In NeurIPS, 2018.

Hao Li, Zheng Xu, Gavin Taylor, Christoph Studer, and Tom Goldstein. Visualizing the loss landscape of neural nets. 2018a.

Haoliang Li, Sinno Jialin Pan, Shiqi Wang, and Alex C Kot. Domain generalization with adversarial feature learning. In CVPR, 2018b.

Shiyu Liang, Yixuan Li, and Rayadurgam Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. In ICLR, 2017.

Weitang Liu, Xiaoyun Wang, John Owens, and Yixuan Li. Energy-based out-of-distribution detection. In NeurIPS, 2020.

Xixi Liu, Yaroslava Lochman, and Christopher Zach. Gen: Pushing the limits of softmax-based out-of-distribution detection. In CVPR, 2023.

Wang Lu, Jindong Wang, Xinwei Sun, Yiqiang Chen, and Xing Xie. Out-of-distribution representation learning for time series classification. In ICLR, 2022.

Yifei Ming, Ying Fan, and Yixuan Li. Poem: Out-of-distribution detection with posterior sampling. In ICML, 2022a.

Yifei Ming, Yiyou Sun, Ousmane Dia, and Yixuan Li. How to exploit hyperspherical embeddings for out-of-distribution detection? In arXiv, 2022b.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y Ng. Reading digits in natural images with unsupervised feature learning. In NeurIPS Workshop on Deep Learning and Unsupervised Feature Learning, 2011.

Hieu Pham, Zihang Dai, Golnaz Ghiasi, Kenji Kawaguchi, Hanxiao Liu, Adams Wei Yu, Jiahui Yu, Yi-Ting Chen, Minh-Thang Luong, Yonghui Wu, et al. Combined scaling for zero-shot transfer learning. Neurocomputing, 555:126658, 2023.

Sudarshan Regmi, Bibek Panthi, Sakar Dotel, Prashnna K Gyawali, Danail Stoynov, and Binod Bhattarai. T2fnorm: Extremely simple scaled train-time feature normalization for ood detection. In arXiv, 2023.

Jie Ren, Stanislav Fort, Jeremiah Liu, Abhijit Guha Roy, Shreyas Padhy, and Balaji Lakshminarayanan. A simple fix to mahalanobis distance for improving near-ood detection. In arXiv, 2021.

Shiori Sagawa, Pang Wei Koh, Tatsunori B Hashimoto, and Percy Liang. Distributionally robust neural networks for group shifts: On the importance of regularization for worst-case generalization. In ICLR, 2020.

Mohammadreza Salehi, Hossein Mirzaei, Dan Hendrycks, Yixuan Li, Mohammad Hossein Rohban, and Mohammad Sabokrou. A unified survey on anomaly, novelty, open-set, and out-of-distribution detection: Solutions and future challenges. In arXiv, 2021.

Rohan Sinha, Apoorva Sharma, Somrita Banerjee, Thomas Lew, Rachel Luo, Spencer M Richards, Yixiao Sun, Edward Schmerling, and Marco Pavone. A system-level view on out-of-distribution data in robotics. In arXiv, 2022.

Baochen Sun and Kate Saenko. Deep coral: Correlation alignment for deep domain adaptation. In Computer Vision–ECCV 2016 Workshops: Amsterdam, The Netherlands, October 8-10 and 15-16, 2016, Proceedings, Part III 14, pp. 443–450. Springer, 2016.

Yiyou Sun, Chuan Guo, and Yixuan Li. React: Out-of-distribution detection with rectified activations. In NeurIPS, 2021.

Yiyou Sun, Yifei Ming, Xiaojin Zhu, and Yixuan Li. Out-of-distribution detection with deep nearest neighbors. In ICML, 2022.

Ilya Sutskever, James Martens, George Dahl, and Geoffrey Hinton. On the importance of initialization and momentum in deep learning. In ICML, 2013.

Junjiao Tian, Yen-Change Hsu, Yilin Shen, Hongxia Jin, and Zsolt Kira. Exploring covariate and concept shift for detection and calibration of out-of-distribution data. In arXiv, 2021.

Grant Van Horn, Oisin Mac Aodha, Yang Song, Yin Cui, Chen Sun, Alex Shepard, Hartwig Adam, Pietro Perona, and Serge Belongie. The inaturalist species classification and detection dataset. In CVPR, 2018.

Vladimir Naumovich Vapnik. Vlamimirvapnik."statistical learning theory", vol. 1, 1998.

Sagar Vaze, Kai Han, Andrea Vedaldi, and Andrew Zisserman. Open-set recognition: A good closed-set classifier is all you need? In ICLR, 2021.

Haoqi Wang, Zhizhong Li, Litong Feng, and Wayne Zhang. Vim: Out-of-distribution with virtual-logit matching. In CVPR, 2022.

Qizhou Wang, Junjie Ye, Feng Liu, Quanyu Dai, Marcus Kalander, Tongliang Liu, Jianye HAO, and Bo Han. Out-of-distribution detection with implicit outlier transformation. In ICLR, 2023.

Hongxin Wei, Renchunzi Xie, Hao Cheng, Lei Feng, Bo An, and Yixuan Li. Mitigating neural network overconfidence with logit normalization. In ICML, 2022.

Mitchell Wortsman, Gabriel Ilharco, Jong Wook Kim, Mike Li, Simon Kornblith, Rebecca Roelofs, Raphael Gontijo Lopes, Hannaneh Hajishirzi, Ali Farhadi, Hongseok Namkoong, et al. Robust fine-tuning of zero-shot models. In CVPR, 2022.

Yilun Xu and Tommi Jaakkola. Learning representations that support robust transfer of predictors. In arXiv, 2021.

Jingkang Yang, Haoqi Wang, Litong Feng, Xiaopeng Yan, Huabin Zheng, Wayne Zhang, and Ziwei Liu. Semantically coherent out-of-distribution detection. In CVPR, 2021.

Jingkang Yang, Pengyun Wang, Dejian Zou, Zitang Zhou, Kunyuan Ding, Wenxuan Peng, Haoqi Wang, Guangyao Chen, Bo Li, Yiyou Sun, Xuefeng Du, Kaiyang Zhou, Wayne Zhang, Dan Hendrycks, Yixuan Li, and Ziwei Liu. Openood: Benchmarking generalized out-of-distribution detection. In arXiv, 2022.

Jingkang Yang, Kaiyang Zhou, Yixuan Li, and Ziwei Liu. Generalized out-of-distribution detection: A survey. In IJCV, 2024.

Qing Yu and Kiyoharu Aizawa. Unsupervised out-of-distribution detection by maximum classifier discrepancy. In ICCV, 2019.

Jingyang Zhang, Nathan Inkawhich, Randolph Linderman, Yiran Chen, and Hai Li. Mixture outlier exposure: Towards out-of-distribution detection in fine-grained environments. In WACV, 2023a.

Jingyang Zhang, Jingkang Yang, Pengyun Wang, Haoqi Wang, Yueqian Lin, Haoran Zhang, Yiyou Sun, Xuefeng Du, Kaiyang Zhou, Wayne Zhang, Yixuan Li, Ziwei Liu, Yiran Chen, and Hai Li. Openood v1.5: Enhanced benchmark for out-of-distribution detection. In arXiv, 2023b.

Marvin Zhang, Henrik Marklund, Nikita Dhawan, Abhishek Gupta, Sergey Levine, and Chelsea Finn. Adaptive risk minimization: Learning to adapt to domain shift. In NeurIPS, 2021.

Qingyang Zhang, Qiuxuan Feng, Joey Tianyi Zhou, Yatao Bian, Qinghua Hu, and Changqing Zhang. The best of both worlds: On the dilemma of out-of-distribution detection. In NeurIPS, 2024.

Bolei Zhou, Àgata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: a 10 million image database for scene recognition. IEEE Transactions on Pattern Analysis and Machine Intelligence, 40(6):1452–1464, 2018.

Zhi Zhou, Lan-Zhe Guo, Zhanzhan Cheng, Yu-Feng Li, and Shiliang Pu. Step: Out-of-distribution detection in the presence of limited in-distribution labeled data. In NeurIPS, 2021.

Jianing Zhu, Yu Geng, Jiangchao Yao, Tongliang Liu, Gang Niu, Masashi Sugiyama, and Bo Han. Diversified outlier exposure for out-of-distribution detection via informative extrapolation. In NeurIPS, 2023.

Yao Zhu, YueFeng Chen, Chuanlong Xie, Xiaodan Li, Rong Zhang, Hui Xue, Xiang Tian, Yaowu Chen, et al. Boosting out-of-distribution detection with typical features. In NeurIPS, 2022.

APPENDIX

A COMPARING DR-SAM WITH SAM

(1) **A key difference between DR-SAM and the standard SAM is employing aug$(\cdot)$ only during the perturbation generation phase.** Analytically, we compare the difference between DR-SAM and standard SAM in Tab. 4 from three: (1) the ultimate optimization target, (2) the data sources for acquiring perturbation, and (3) the parameter optimization stage.

(2) **Simple "SAM+OE" cannot enhance detection and generalization simultaneously.** To further justify the validity of aug$(\cdot)$, we simply cooperate auxiliary outliers to obtain perturbation for SAM optimization, termed "SAM+OE." We compare the SAM+OE with standard SAM and proposed DR-SAM in Tab. 5 and 6.

B FURTHER EXPERIMENTS

In this section, we conduct experiments to show the effect of data augmentation in DR-SAM. We also provide ablation studies on data augmentation to show the capability for OOD-G of DR-SAM is derived from data augmentation.

B.1 THE EFFECT OF DATA AUGMENTATION

We first show that model training with auxiliary outliers would affect the ID performance, even with SAM. We then demonstrate that data augmentation could enhance the model's detection and generalization ability. We conduct experiments on CIFAR-10 and CIFAR-100 with the same setting adopted in Tab. 1 and 2.

As can be seen from Tab. 7 and 8, **model training with auxiliary outliers would sacrifice the model's ID performance but improve its detection capability.** Simply cooperating OE with SAM can improve the model's ID performance, but cannot compete with vanilla SAM. In addition, SAM+OE also fails to achieve competitive performance with vanilla SAM. DR-SAM achieves slightly lower ID accuracy compared to vanilla SAM in CIFAR-10 but exceeds SAM+OE in CIFAR-100. This indicates the necessity of the aug$(\cdot)$ for enhancing both detection and generalization performance.

Table 4: Comparison with SAM

	SAM	**DR-SAM**
Optimization targets	Enhance the model's generalization ability on D_{ID}.	Enhanced model's generalization ability on D_{CS} during optimizing with auxiliary outliers to boost the detection ability on D_{SS}, which effectively handles the detection-generalization paradox.
Acquire perturbation	D_{ID}^{train} (only pursue low sharpness in D_{ID}^{train}. It does not explicitly involve either covariate-shifted or semantic-shifted samples, and cannot guarantee the model's detection performance under fine-grained datasets like CIFAR-100 or ImageNet-200.)	$aug(D_{ID}^{\text{train}})$ with auxiliary outliers (pursue low sharpness in both D_{ID}^{train} and $aug(D_{ID}^{\text{train}})$. DR-SAM obtains perturbation using both simulated covariate-shifted samples and auxiliary semantic-shifted data, to create a challenging perturbation aware of the worst case for generalization under covariate shift, while exploring the separation between D_{ID} and D_{SS}.
Gradient optimization	Perform gradient descent using gradient signal from the perturbed point. This process only guarantees the model's training trajectory for ID classification.	Perform gradient descent using gradient signal from the perturbed point. This process involves samples from D_{ID}^{train} and auxiliary outliers, allowing us to preserve the benefits of the training trajectory for OOD-D. This process enables us to improve generalization and detection simultaneously in a more harmonious manner.

Table 5: CIFAR-10 OOD-D and OOD-G performance.

	FPR@95↓	AUROC↑	ID Accuracy↑	OOD-G Accuracy↑
SAM	25.15	92.08	95.69	80.69
SAM+OE	30.95	90.94	95.27	80.24
DR-SAM	12.36	97.04	95.13	80.50

Table 6: CIFAR-100 OOD-D and OOD-G performance.

	FPR@95↓	AUROC↑	ID Accuracy↑	OOD-G Accuracy↑
SAM	53.91	80.14	78.53	37.20
SAM+OE	55.66	79.56	77.62	36.77
DR-SAM	38.18	86.93	77.91	36.91

In general, despite the slight drawback in ID performance compared to vanilla SAM, DR-SAM effectively resolves the detection-generalization paradox.

B.2 ABLATION STUDIES ON DATA AUGMENTATION

We conduct experiments on CIFAR-10 and fine-grained dataset ImageNet-200 to demonstrate that the capability for OOD-G of DR-SAM is derived from data augmentation.

As can be seen from Tab. 9 and 10, the model fine-tuned with DR-SAM (w/o aug(·)) would generally decrease the performance of detection and generalization. This indicates that the capability for OOD-G is derived from data augmentation rather than SAM.

B.3 ADDITIONAL EXPERIMENTS WITH RECENT BASELINES

We provide a comparison of additional baselines, including POEM, NOPS, and NTOM. We additionally conduct experiments with SCONE and WOODS. We conduct experiments with settings aligned with the original submission. As NPOS trains the CNN backbone without the final linear classifier (Zhang et al., 2023b), we can only provide its OOD-D performance and leave the accuracy as N/A. In addition, DUL has not yet release their source code, we leave the comparsion with it to the future work.

Table 7: CIFAR-10 performance comparison.

	FPR@95↓	ID Accuracy↑
MSP	39.91	95.06
OE	14.06	95.06
SAM	25.15	95.69
SAM+OE	30.95	95.27
DR-SAM	12.36	95.13

Table 8: CIFAR-100 performance comparison.

	FPR@95↓	ID Accuracy↑
MSP	56.68	77.26
OE	33.20	76.51
SAM	53.91	78.53
SAM+OE	55.66	77.62
DR-SAM	38.18	77.91

Table 9: Ablation studies on data augmentation for CIFAR-10.

	FPR@95↓	OOD-G Accuracy↑
MSP	39.91	95.06
SAM	25.15	95.69
DR-SAM	12.36	95.13
DR-SAM (w/o aug($\cdot$))	15.46	80.16

Table 10: Ablation studies on data augmentation for ImageNet-200.

	FPR@95↓	OOD-G Accuracy↑
MSP	56.68	77.26
SAM	53.91	78.53
DR-SAM	38.18	77.91
DR-SAM (w/o aug($\cdot$))	45.10	44.73

We notice that POEM would degenerate the model's classification ability in both in-distribution and covariate-shifted samples, which leads to sub-optimal performance compared to the OE. POEM cannot exceed the OE when using the TIN-597 as auxiliary outliers when training on the CIFAR benchmark, as DUL also has the same report. The WOODS and SCONE, on the other hand, cannot perform well in CIFAR-100 under the traditional OOD-D setting and also scarify the OOD-G performance.

C   DETAILS OF DATASETS

CIFAR-10 (Krizhevsky & Hinton, 2009) is one of the widely used color image datasets in machine learning, containing real objects in the real world. It has a total of 10 classes which are airplane, automobile, bird, cat, deer, dog, frog, horse, ship, and truck. There are 6000 images for each category, of which 5000 images are used for training and 1000 images are used for testing.

CIFAR-100 (Krizhevsky & Hinton, 2009) is similar to the CIFAR-10 data in that it has color images of real objects. It contains a total of 100 categories, divided into 20 superclasses. Each class has 600 images, including 500 for training and 100 for testing.

CIFAR-10/100-C (Hendrycks & Dietterich, 2019) is obtained by corrupting the original CIFAR test set. It has applied a total of 15 corruptions which are Gaussian Noise, Shot Noise, Impulse Noise, Defocus Blur, Frosted Glass Blur, Motion Blur, Zoom Blur, Snow, Frost, Fog, Brightness, Contrast, Elastic, Pixelate, JPEG.

Place365 (Zhou et al., 2018) is a scene recognition dataset with a total of 434 scene categories. There are two versions of the dataset which are Places365-Standard and Places365-Challenge-2016. The Place365 has a total of 10 million images, with between 5,000 and 30,000 training images per class.

MNIST (Deng, 2012) is a dataset of handwritten number images with 10 classes, each representing a number between 0 and 9. The MNIST dataset has a total of 70,000, 28×28 greyscale images, of which 60,000 are in the training set and 10,000 are in the test set.

SVHN (Netzer et al., 2011) is a image datasets with real-world numbers. The numbers in it are captured from various scenes, such as door numbers and historical buildings. It divided into 10 categories and each number in the image is belonged to one class. It contains 73257 digits for training and 26032 digits for testing.

Texture (Cimpoi et al., 2014) a real world surface texture dataset. The images are collected from wood, blankets, cloth, leather, etc. There are 64 categories and a total of 8674 images. The Texture is mainly used to evaluate the capabilities of the model or as a pre-training dataset.

Table 11: CIFAR-10 OOD-D and OOD-G performance.

	FPR@95↓	AUROC↑	ID Accuracy↑	OOD-G Accuracy↑
MSP	39.91	79.24	95.06	79.24
OE	14.06	96.42	95.02	78.77
NOPS	28.05	91.85	N/A	N/A
POEM	33.02	88.00	85.68	66.34
WOODS	20.36	94.39	90.43	71.47
SCONE	19.26	94.71	91.68	73.56
DR-SAM	12.36	97.04	95.13	80.50

Table 12: CIFAR-100 OOD-D and OOD-G performance.

	FPR@95↓	AUROC↑	ID Accuracy↑	OOD-G Accuracy↑
MSP	56.68	79.02	77.26	36.59
OE	36.11	87.64	76.51	36.24
NOPS	57.22	81.06	N/A	N/A
POEM	40.00	82.78	68.58	32.48
WOODS	56.15	80.32	77.01	36.48
SCONE	55.28	81.39	76.58	36.27
DR-SAM	38.18	86.93	77.91	36.91

Method	CIFAR100		TIN		MINIST		SVHN		Textures		Places365	
	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑
Post-hoc												
MSP	$53.09_{\pm4.89}$	$87.19_{\pm0.33}$	$43.18_{\pm3.20}$	$88.89_{\pm0.20}$	$23.64_{\pm5.82}$	$92.63_{\pm1.57}$	$25.43_{\pm1.57}$	$91.56_{\pm0.38}$	$35.20_{\pm4.55}$	$89.89_{\pm0.71}$	$42.47_{\pm3.90}$	$88.92_{\pm0.47}$
RMDS	$43.88_{\pm3.48}$	$88.83_{\pm0.35}$	$33.68_{\pm1.67}$	$90.83_{\pm0.27}$	$21.49_{\pm2.31}$	$93.22_{\pm0.80}$	$23.03_{\pm1.51}$	$91.95_{\pm0.25}$	$25.31_{\pm0.56}$	$92.23_{\pm0.23}$	$31.18_{\pm0.32}$	$91.51_{\pm0.11}$
EBO	$66.58_{\pm4.48}$	$86.36_{\pm0.58}$	$56.68_{\pm5.36}$	$88.85_{\pm0.36}$	$24.98_{\pm12.92}$	$94.32_{\pm2.53}$	$34.21_{\pm5.55}$	$91.98_{\pm0.91}$	$52.00_{\pm6.23}$	$89.47_{\pm0.69}$	$54.68_{\pm6.62}$	$89.25_{\pm0.78}$
VIM	$49.32_{\pm3.10}$	$87.75_{\pm0.28}$	$40.20_{\pm1.38}$	$89.71_{\pm0.32}$	$18.36_{\pm1.42}$	$94.75_{\pm0.38}$	$18.89_{\pm0.58}$	$94.59_{\pm0.47}$	$21.18_{\pm1.62}$	$95.14_{\pm0.32}$	$41.47_{\pm2.22}$	$89.49_{\pm0.38}$
KNN	$37.63_{\pm0.29}$	$89.73_{\pm0.14}$	$30.20_{\pm0.71}$	$91.62_{\pm0.27}$	$20.04_{\pm1.35}$	$94.26_{\pm0.38}$	$22.39_{\pm1.39}$	$92.77_{\pm0.30}$	$24.06_{\pm0.46}$	$93.16_{\pm0.23}$	$30.35_{\pm0.66}$	$91.77_{\pm0.23}$
Training Methods (w/o Outlier Data)												
ConfBranch	$39.03_{\pm0.39}$	$86.67_{\pm0.39}$	$34.90_{\pm0.65}$	$88.06_{\pm0.28}$	$19.81_{\pm1.41}$	$92.89_{\pm1.20}$	$25.09_{\pm1.18}$	$89.49_{\pm0.35}$	$42.42_{\pm1.00}$	$85.30_{\pm0.15}$	$35.49_{\pm1.42}$	$87.43_{\pm0.84}$
G-ODIN	$64.92_{\pm5.16}$	$83.51_{\pm1.52}$	$61.73_{\pm5.74}$	$85.18_{\pm1.25}$	$24.89_{\pm4.87}$	$94.85_{\pm0.95}$	$57.19_{\pm10.20}$	$85.41_{\pm2.56}$	$67.43_{\pm7.80}$	$85.31_{\pm1.66}$	$48.66_{\pm3.23}$	$88.61_{\pm0.46}$
LogitNorm	$32.58_{\pm0.71}$	$91.18_{\pm0.23}$	$24.06_{\pm1.07}$	$93.62_{\pm0.26}$	$2.55_{\pm1.28}$	$99.45_{\pm0.31}$	$11.11_{\pm1.01}$	$97.05_{\pm0.22}$	$24.18_{\pm3.73}$	$93.64_{\pm0.68}$	$22.82_{\pm0.56}$	$94.05_{\pm0.11}$
Training Methods (w/ Outlier Data)												
OE	$32.74_{\pm3.01}$	$91.56_{\pm0.79}$	$2.09_{\pm1.60}$	$99.45_{\pm0.09}$	$17.86_{\pm0.50}$	$94.52_{\pm0.36}$	$0.42_{\pm0.25}$	$99.84_{\pm0.08}$	$10.86_{\pm1.31}$	$98.00_{\pm0.33}$	$13.67_{\pm1.40}$	$96.96_{\pm0.48}$
MCD	$41.10_{\pm0.44}$	$87.19_{\pm0.06}$	$35.86_{\pm0.33}$	$88.68_{\pm0.09}$	$24.45_{\pm2.12}$	$92.42_{\pm0.48}$	$34.94_{\pm3.58}$	$88.02_{\pm1.08}$	$37.08_{\pm2.16}$	$88.04_{\pm0.26}$	$36.34_{\pm0.69}$	$88.60_{\pm0.18}$
MixOE	$90.24_{\pm4.98}$	$83.54_{\pm1.88}$	$84.82_{\pm7.54}$	$86.84_{\pm1.68}$	$65.27_{\pm10.19}$	$90.41_{\pm0.70}$	$32.10_{\pm24.71}$	$93.23_{\pm1.80}$	$84.99_{\pm14.40}$	$85.54_{\pm3.70}$	$84.19_{\pm7.24}$	$87.25_{\pm1.47}$
Ours												
DR-SAM	$31.01_{\pm1.47}$	$92.23_{\pm0.21}$	$6.60_{\pm1.47x}$	$98.59_{\pm0.32}$	$4.59_{\pm3.34}$	$98.80_{\pm0.92}$	$1.59_{\pm0.51}$	$99.55_{\pm0.16}$	$6.49_{\pm1.68}$	$98.73_{\pm0.35}$	$10.95_{\pm1.21}$	$97.58_{\pm0.40}$

Table 13: CIFAR-10 full results

TinyImageNet (Le & Yang, 2015) contains 100000, 64×64 coloured images with 200 classes. Each class has 500 training images, 50 validation images, and 50 test images.

TIN-597 (Zhang et al., 2023b) obtained from ImageNet-1K that is not overlapped with TIN dataset. It has 597 classes and is cleared of CIFAR-10/100 related categories.

ImageNet-200 is the subset from the ImageNet-1K that has same 200 classes as ImageNet-R. In comparison to ImageNet-1K, it contains identical OOD datasets.

SSB-hard (Vaze et al., 2021) is the hard split of SSB dataset which has 980 classes and contains 49K images. It used to explore semantic shift tasks and obtained based on fine-grained datasets.

NINCO (Bitterwolf et al., 2023) contains 5879 noise-free images.

iNaturalist (Van Horn et al., 2018) has 13 super-classes which included Plantae, Insecta, Aves, Mammalia and so on. It has 675170 images for training and validation.

OpenImage-O (Wang et al., 2022) contains images are selected one by one from the OpenImage-V3 test set.

ImageNet-R (Hendrycks et al., 2021) has 200 classed of ImageNet dataset containing 30000 images.

D FULL EXPERIMENT RESULTS

In this part, we report the full training performance for CIFAR-10, CIFAR-100, and ImageNet-200 in Tab. 13, Tab. 14, and Tab. 3.

E CONFIGURATION

We follow the benchmark setting introduced in OpenOOD (Yang et al., 2022).

Model fine-tuning configurations. For both CIFAR-10 and CIFAR-100, we run for 100 epochs with an initial learning rate of 0.01 and the ReduceLROnPlateau learning rate scheduler with the patience parameter of 5. For ImageNet-200, we employ 0.001 fine-tuning learning rate. The batch size is 128

Method	CIFAR10		TIN		MINIST		SVHN		Textures		Places365	
	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑
Post-hoc												
MSP	58.90±0.93	78.47±0.07	50.78±0.57	81.96±0.20	57.24±4.67	76.08±1.86	58.42±2.62	78.68±0.95	61.78±1.30	77.32±0.71	56.64±0.87	79.22±0.29
RMDS	61.37±0.23	77.75±0.19	49.50±0.64	82.58±0.02	52.04±6.27	79.74±2.49	51.06±3.56	85.10±1.06	53.95±0.99	83.65±0.52	53.56±0.37	83.40±0.46
EBO	59.18±0.75	79.05±0.10	52.35±0.58	82.58±0.08	52.61±3.84	79.18±1.36	53.19±3.25	82.28±1.79	62.39±2.07	78.35±0.84	57.70±0.85	79.50±0.23
VIM	70.59±0.42	72.21±0.41	54.63±0.41	77.87±0.13	48.31±1.06	81.88±1.02	46.29±5.47	82.91±3.77	46.84±2.26	85.91±0.78	61.57±0.74	75.86±0.37
KNN	72.81±0.45	77.02±0.25	49.55±0.54	83.31±0.16	48.58±4.68	82.36±1.52	51.48±3.21	84.27±1.10	53.62±2.38	83.66±0.84	60.76±0.90	79.42±0.47
Training Methods (w/o Outlier Data)												
ConfBranch	83.84±0.48	63.58±0.19	72.23±0.69	71.03±0.06	39.36±9.97	86.70±5.83	84.57±2.39	51.46±2.68	96.67±0.84	50.97±0.28	76.77±0.91	66.80±0.42
G-ODIN	74.00±7.25	71.59±3.20	62.15±4.82	77.84±2.66	49.33±4.60	82.66±2.72	54.79±3.93	76.45±2.04	54.52±2.85	80.88±2.01	67.05±4.98	75.22±3.68
LogitNorm	67.91±0.43	76.30±0.32	50.08±0.50	83.07±0.31	27.77±2.56	92.25±0.88	46.71±6.78	82.18±4.22	63.19±2.24	77.56±1.50	56.76±0.62	79.63±0.50
Training Methods (w/ Outlier Data)												
OE	65.47±0.90	74.69±0.74	0.94±0.63	99.63±0.14	44.88±4.53	86.33±3.51	2.06±0.88	99.29±0.02	52.17±4.33	86.09±2.01	57.01±2.23	80.76±1.27
MCD	62.63±0.20	75.95±0.16	54.72±0.42	79.53±0.21	64.69±3.01	73.02±1.82	55.57±3.47	79.43±1.09	68.38±0.49	73.94±0.15	59.42±0.12	77.24±0.17
MixOE	62.33±2.15	78.42±0.64	51.44±1.98	82.46±0.75	60.06±7.82	73.65±4.95	50.21±7.14	82.75±2.55	63.50±2.40	78.76±0.50	58.47±1.53	79.64±0.52
Ours												
DR-SAM	59.05±0.42	78.39±0.10	0.11±0.05	99.88±0.04	54.32±5.65	77.26±3.16	29.17±3.80	94.73±0.95	49.81±0.97	85.42±0.17	53.76±0.51	81.52±0.17

Table 14: CIFAR-100 full results

Method	SBHARD		NINCO		iNATURALIST		Textures		OPENIMAGE_O	
	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑	FPR95↓	AUROC↑
Post-hoc										
MSP	66.09±0.05	80.32±0.04	43.76±0.72	86.27±0.11	26.53±0.69	92.77±0.26	44.43±0.73	88.37±0.13	35.22±0.26	89.24±0.01
RMDS	66.02±0.33	80.16±0.25	42.17±1.12	84.92±0.27	24.74±0.91	90.62±0.47	37.93±1.15	86.76±0.40	34.83±0.40	86.78±0.22
EBO	69.97±0.26	79.72±0.03	50.66±0.94	85.10±0.12	26.41±2.29	92.52±0.51	41.31±1.84	90.80±0.16	36.81±1.15	89.20±0.26
VIM	71.51±0.47	73.90±0.31	47.21±1.15	83.29±0.18	27.37±0.39	90.97±0.36	20.39±0.18	94.61±0.11	33.91±0.72	88.20±0.18
KNN	73.89±0.27	76.88±0.24	46.74±0.78	86.05±0.12	24.43±1.10	93.97±0.36	24.53±0.21	95.30±0.02	32.94±1.11	90.17±0.32
Training Methods (w/o Outlier Data)										
ConfBranch	72.21±0.11	75.06±0.27	50.91±0.83	82.94±0.12	23.80±1.15	93.40±0.26	39.91±0.53	90.03±0.15	36.97±0.38	88.48±0.18
G-ODIN	77.66±0.32	73.33±0.22	60.19±0.95	81.92±0.12	26.86±1.24	92.64±0.22	26.81±1.74	93.96±0.09	35.41±0.44	90.15±0.13
LogitNorm	67.13±0.55	78.45±0.18	47.60±0.62	86.01±0.16	16.21±1.22	96.10±0.34	32.02±1.25	92.00±0.19	31.61±1.06	90.66±0.45
Training Methods (w/ Outlier Data)										
OE	63.44±1.67	82.15±0.36	41.44±0.34	86.93±0.21	29.85±0.28	89.22±0.30	44.71±2.72	86.56±0.79	35.69±1.33	87.86±0.44
MCD	68.03±0.11	76.59±0.06	51.17±1.18	81.52±0.17	35.39±0.40	89.18±0.23	51.77±1.41	84.84±0.26	46.27±0.54	84.23±0.16
MixOE	71.49±0.20	79.53±0.22	49.51±2.68	84.64±0.64	32.43±2.13	89.81±0.61	54.00±2.10	86.02±0.56	40.64±2.02	87.15±0.55
Ours										
DR-SAM	63.08±0.45	82.88±0.23	41.39±0.79	87.33±0.21	26.77±0.30	90.22±0.09	41.20±1.16	88.08±0.37	34.07±0.72	88.75±0.17

Table 15: ImageNet-200 full results

for D_{ID} and 256 for $D_{\text{OOD}}^{\text{train}}$. We adopt SGD optimizer with Nesterov momentum (Sutskever et al., 2013) that is set as 0.9, and the weight decay is set as $5e^{-}4$. We ran our experiment under three seeds, reporting their mean and standard deviation.

DR-SAM configurations. For CIFAR-10, we employ λ and ρ as 0.5, and using brightness as $\text{aug}(\cdot)$. For CIFAR-100, we employ we employ λ and ρ as 0.2, and using brightness as $\text{aug}(\cdot)$. For ImageNet-200, we λ and ρ as 0.5.

Visualization configurations. For Fig. 3 and Fig. 9, we employ CIFAR-10 as ID, CIFAR-10-C as CSID, MNIST as SSID. The same dataset setting for the landscapes is shown in Fig. 10 (a-b). For Fig. 10 (c-d), we employ CIFAR-100 as ID, CIFAR-100-C as CSID, and MNIST as SSID.

F RELATED WORK

F.1 OUT-OF-DISTRIBUTION GENERALIZATION

Empirical Risk Minimization (Vapnik, 1998) methods are insufficient for generalizing novel test distributions because they rely on spurious correlations that only exist in the training data.

Several methods based on representation learning are proposed to generalize the model to new data distribution (Li et al., 2018b; Huang et al., 2020; Xu & Jaakkola, 2021; Lu et al., 2022; Sun & Saenko, 2016; Zhang et al., 2021; Kim et al., 2021). The representative Invariant Risk Minimization (IRM) (Arjovsky et al., 2019) identifies and removes spurious correlations by learning invariant representations of the data. GroupDRO (Sagawa et al., 2020) trains the model to perform well not only on the average data distribution but also on a set of "nearby" distributions defined by a given uncertainty set. VRE-x (Krueger et al., 2021) considers optimizing the affine combinations of training risks instead of the convex combinations of the training risks adopted in GroupDRO.

F.2 OUT-OF-DISTRIBUTION DETECTION

To identify the out-of-distribution samples from in-distribution ones, training-free post-hoc OOD-D methods mainly modify the model's softmax prediction probability to enlarge the gap between in-distribution and out-of-distribution samples (Hendrycks & Gimpel, 2016; Liang et al., 2017; Liu et al., 2020). Another line is to focus on modifying the model's representation to identify the out-of-distribution samples (Zhu et al., 2022; Bitterwolf et al., 2020; Huang et al., 2022; Ming et al., 2022b; Djurisic et al., 2022). In contrast, some researchers focus on modifying the model's activation value to identify the out-of-distribution samples, including ReAct Sun et al. (2021), ASH Djurisic et al. (2022), CONFBRANCH DeVries & Taylor (2018), T2FNorm Regmi et al. (2023), Logitnorm Wei et al. (2022), and Tian et al. (2021).

To further enhance the model's detection ability, Outlier Expose (OE) (Hendrycks et al., 2018) training the model with auxiliary outliers to allow the model to be aware of the semantic-shifted samples. Based on OE, DOE (Wang et al., 2023) uses the implicit transformed data produced by model perturbation to expand distributions for training. MixOE (Zhang et al., 2023a) solves this problem by adopting Mixup or Cutup to combine ID data and surrogate data, which generates a new dataset for training. DivOE (Zhu et al., 2023) provides an adversarial training approach to generate novel and challenging outliers to enhance the detection performance. POEM Ming et al. (2022a) uses an auxiliary outlier dataset to update the posterior distribution's decision boundary between OOD and ID data. By jointly modeling the ID and OOD data, the UDG framework Yang et al. (2021) can enrich the semantic knowledge of the model by exploiting unlabeled data in an unsupervised manner

However, the OE approaches require access to the auxiliary outliers, which might limit their application. G-ODIN Hsu et al. (2020) proposes two corresponding strategies to improve the performance of OOD detection under the setting that no additional OOD data is used for fine-tuning. Hendrycks et al. (2019) found that without using a large model or additional data, the self-supervised models obtained are more robust regarding adversarial robustness, label corruption, common input corruptions, and out-of-distribution detection. Based on this phenomenon, ROTPRED Hendrycks et al. (2019), which is a self-supervised model, learns representations that favor downstream tasks such as OOD detection by predicting the angle of rotation. VOS Du et al. (2022) sampling outliers from the low-likelihood region of the ID data and training the model with the ID. VOS synthetic OOD data to obtain a decision boundary that improves the model's OOD-D performance.

Some existing OOD detection models are trained based on small, low-resolution datasets, such as CIFAR-10, and the models cannot be transferred to large-scale settings. MOS Huang & Li (2021) forms several classes into a new group by taxonomy feature clustering or random grouping to simplify OOD and ID data's decision boundary. The model detects OOD data based on the total confidence values of the input data maps to other classes in all new groups.

The limitations of current OOD detection benchmarks have overcome some challenges that may identify data with the same semantics but different sources as OOD. Yang et al. (2021) proposes a novel Semantically Coherent Out-of-Distribution Detection (SC-OOD) benchmark that evaluates the ability of models to detect OOD samples that are semantically coherent with the ID samples.

F.3 METHODS CONSIDER OOD-D AND OOD-G.

The model would encounter different distributional shifts when deployed in the wild. The pioneering work (Bai et al., 2023) proposes to enhance the model's OOD-D and OOD-G ability when training the model with wild data. [1] proposes SCONE to handle the wild data, assuming that semantic shifts would be encountered less frequently. SCONE forces the model to lower the wild samples' energy while enforcing a sufficient margin between the $D_{\text{ID}}^{\text{train}}$ and a pre-defined energy threshold. Since the model would allocate ID samples with lower energy scores than the semantic-shifted ones, the former objective allows the model to detect the semantic-shifted samples. In contrast, the latter allows the model to predict the covariate-shifted samples correctly.

Averly & Chao (2023) proposes an OOD-D evaluation framework to detect and reject the misclassified covariate-shifted samples while accepting the correctly classified ones. The proposed evaluation framework mainly identifies the sample model cannot predict correctly regardless of their distribution shift types. Averly & Chao (2023) does not explicitly argue the detection-generalization dilemma or propose a new algorithm to enhance both detection and generalization ability.

The concurrent work (Zhang et al., 2024) shares the same setting as DR-SAM but develops a different method to enhance the model's generalization and detection. Zhang et al. (2024) propose a novel and theoretical guarantee optimization framework, Decoupled Uncertainty Learning (DUL), to enhance the model's OOD-D ability while maintaining the original OOD-G capability. DUL incorporates distributional uncertainty in the Bayesian framework to bridge the detection and generalization learning target. Specifically, DUL encourages the exposed outlier to have high uncertainty while maintaining a non-increased overall uncertainty to ensure generalization capability.

F.4   ROBUST FINETUNING

Pham et al. (2023) shows that the model fine-tuned on a dataset with shifted distribution would have lower performance than that of the original zero-shot model. This means that the fine-tuning of the model sacrifices its robustness. WiSE-FT (Wortsman et al., 2022) finds that small variations in the hyperparameters lead to variable model accuracies and that aggressive fine-tuning may lead to reduced accuracy in the distribution shift target dataset. Chen et al. (2020) introduces adversarial training with self-supervised learning to pre-train and fine-tune the model. AFT Jeddi et al. (2020) uses 'Slow Start, Fast Decay' fine-tuning to improve the robustness of the model by controlling the learning rate during the fine-tuning phase, which uses adversarial perturbations.