SPANNING TREE-BASED GRAPH GENERATION FOR MOLECULES

ABSTRACT

In this paper, we explore the problem of generating molecules using deep neural networks, which has recently gained much interest in chemistry. To this end, we propose a spanning tree-based graph generation (STGG) framework based on formulating molecular graph generation as a construction of a spanning tree and the residual edges. Such a formulation exploits the sparsity of molecular graphs and allows using compact tree-constructive operations to define the molecular graph connectivity. Based on the intermediate graph structure of the construction process, our framework can constrain its generation to molecular graphs that satisfy the chemical valence rules. We also newly design a Transformer architecture with tree-based relative positional encodings for realizing the tree construction procedure. Experiments on QM9, ZINC250k, and MOSES benchmarks verify the effectiveness of the proposed framework in metrics such as validity, Fréchet ChemNet distance, and fragment similarity. We also demonstrate the usefulness of STGG in maximizing penalized LogP value of molecules.

1 INTRODUCTION

Researchers have extensively studied graph generative models, dating back to the early works of Erdös Rényi (Erdös et al., 1959). Recently, models based on deep neural networks (DNNs) have gained much attraction due to their expressive power in learning a graph dataset. The molecule-generating DNNs stand out among them for their success in the task of drug discovery.

Recent works have proposed molecule-generating DNNs based on string-based and graph-based representations (Segler et al., 2018; Jin et al., 2018; You et al., 2018; Shi et al., 2020; Jin et al., 2020). For example, Segler et al. (2018) proposed to train language models on the domain-specific linear string representation of molecules, i.e., simplified molecular-input line-entry system (SMILES, Weininger 1988). Since the string-based models ignore the inherent graph structure, recent works explore the graph-based generation that use (a) atom-by-atom (You et al., 2018; Shi et al., 2020; Luo et al., 2021) or (b) substructure-based (Jin et al., 2018; 2019; 2020) operations.

Notably, the substructure-based generative models (Jin et al., 2018; 2019; 2020) successfully exploit the molecular prior knowledge: the graphs are sparsely connected and can be represented as a junction tree with molecular substructure as building blocks. Based on such knowledge, the models use the junction tree construction operators which (a) require a fewer number of steps to generate the whole molecular graph and (b) guarantee generating molecules that satisfy the chemical valence rules. However, despite such advantages, a recent benchmark (Polykovskiy et al., 2020) suggests that they do not outperform the existing methods in terms of learning the data distribution, even when compared with the simple SMILES-based language models. We hypothesize that this is due to the models using a coarse-grained representation of the molecule and they may lack the ability to learn the inner semantics of each substructure-based building block.

Contribution. In this work, we propose a novel framework, coined spanning tree-based graph generation (STGG), for fine-grained generation of molecules while exploiting their sparsity.[1] Mainly inspired from the SMILES representation of molecules, our idea is to generate the molecular graph as a composition of a *spanning tree* and the corresponding *residual edges* with atoms and bonds as building blocks. Such a formulation allows our framework to utilize compact tree-constructive

---

[1]While our framework is designed for general sparse graphs, we focus on the molecular graphs in this paper.

Figure 1: (left) Benzaldehyde, (middle) its spanning tree (blue) and residual edges (red), and the corresponding constructive decisions (right). Open circle represent atoms and bonds in the molecule.

operations to define the molecular graph connectivity. See Figure 1 for an illustration of how we formulate the generation of a molecular graph as a sequence of tree-constructive operations.

Since our framework maintains the molecular graph structure during construction, it can pre-determine decisions that (a) violate the graph construction rule and (b) lead to molecules that violate the chemical valence rule. Such criteria allow control over the generative model to guarantee generating valid molecular graphs by forbidding invalid actions. This is in contrast to prior works (Shi et al., 2020; Luo et al., 2021) that generate the molecular graph atom-by-atom but determines the validity of construction operations through a sample-rejection scheme.

To recognize the spanning tree-based representation used in our STGG framework, we propose a Transformer architecture (Vaswani et al., 2017) with tree-based relative encoding. Inspired by recent works (Villmow et al., 2021; Lukovnikov & Fischer, 2021; Ying et al., 2021) on tree-based and graph-based Transformers, our framework expresses the relative position between two vertices as the number of forward and reverse edges in the shortest path between them. We also introduce an attention-based mechanism for constructing residual edges.

We experiment on popular graph generation benchmarks of QM9, ZINC250K, and MOSES to validate the effectiveness of our algorithm. In the experiments on QM9 and ZINC, our STGG framework outperforms the existing graph-based generative models by a large margin. In the MOSES benchmark, our algorithm achieves superior performance compared to both string-based and graph-based methods for majority of the metrics, e.g., Fréchet ChemNet distance (Preuer et al., 2018) and fragment-based similarity. We also conduct experiments on the offline optimization task for high penalized octanol-water partition coefficient and achieve competitive results.

2 SPANNING TREE-BASED GENERATION OF GRAPHS (STGG)

2.1 OVERVIEW

In this section, we introduce our spanning tree-based graph generation (STGG) framework to sequentially generate a molecule as a composition of a spanning tree and residual edges. To this end, we propose compact tree-constructive operations inspired by the simplified molecular-input line-entry system (SMILES, Weininger, 1988). In contrast to the existing SMILES-based molecular generative methods, our framework (a) allows inferring the intermediate graph structure and (b) is generally applicable to graph types other than molecules. In particular, (a) further enables our framework to control the construction process such that the sequential operations comply with tree-constructive grammar and only generate molecules satisfying the chemical valence rule.

Molecular graph representation. To apply our framework, we represent a molecule as a bipartite graph $\mathcal{G} = (\mathcal{A}, \mathcal{B}, \mathcal{E})$ where $\mathcal{A}$ and $\mathcal{B}$ are the set of vertices associated with atoms and bonds of the molecule, respectively.[2] Each edge $\{a, b\} \in \mathcal{E}$ is assigned for each adjacent pair of atom and bond. We assign attributes $x_a \in \mathcal{X}_{\texttt{atom}}$ and $x_b \in \mathcal{X}_{\texttt{bond}}$ for vertices $a \in \mathcal{A}$ and $b \in \mathcal{B}$ to indicate the corresponding atom type and bond order, respectively. For example, $\{\texttt{"C"}, \texttt{"N"}, \texttt{"O"}\} \subseteq \mathcal{X}_{\texttt{atom}}$ and $\{\texttt{"-"}, \texttt{"="}\} \subseteq \mathcal{X}_{\texttt{bond}}$. See Figure 1 for an example of such a molecular graph representation.

Molecular graph from sequence of decisions. To generate the molecular graph $\mathcal{G} = (\mathcal{A}, \mathcal{B}, \mathcal{E})$, our framework makes a sequence of decisions $d_1, \ldots, d_T$ to generate a spanning tree $\mathcal{T} = (\mathcal{A}_\mathcal{T}, \mathcal{B}_\mathcal{T}, \mathcal{E}_\mathcal{T})$ and a set of residual edges $\mathcal{E}_R = \mathcal{E} \setminus \mathcal{E}_\mathcal{T}$. At each iteration, seven types of decisions are applicable, i.e., $\texttt{attach\_atom}$, $\texttt{attach\_bond}$, $\texttt{branch\_start}$, $\texttt{branch\_end}$, $\texttt{res\_atom}$, $\texttt{res\_bond}$, and $\texttt{terminate}$.

---

[2]Many existing works, e.g., (Shi et al., 2020), use a non-bipartite graph with bonds assigned to edges.

attach_atom	attach_bond	branch_start	branch_end	res_atom	res_bond	terminate
$"C" \in \mathcal{X}_{\text{atom}}$	$"-" \in \mathcal{X}_{\text{bond}}$	"("	")"	"*"	$d \in \mathcal{L}_{\text{res}}$	"[eos]"

Table 1: Operations (top) and example of corresponding decisions (bottom) used in STGG.

Figure 2: Demonstration of executing a sequence of decisions C-C(=O)(-C*-C-C-C-C-2). Here, we use the numbers 1 and 2 to mark vertices for the purpose of illustration. Next, {"C", "O"}, {"-", "="}, "(", ")", "*", and "2" correspond to attach_atom, attach_bond, branch_start, branch_end, res_atom, and res_bond operations, respectively. The decision "2" denotes res_bond operation selecting the vertex marked by "2". Decisions that are not executed at the respective time-step are faded out (gray). Location of the pointer vertex i_{point} is indicated by an arrow (red).

See Table 1 for examples of decisions and the corresponding operations. We provide a detailed description of the graph construction process in Section 2.2.

Generating valid molecular graphs. Without any control, a model may generate decisions that (a) do not comply with the grammar of STGG or (b) leads to a molecule violating the chemical valence rule. To prevent this scenario, we conduct two criteria for determining validity of the given decision for (a) and (b). We further elaborate this in Section 2.3.

2.2 DECISION PROCESS FOR SPANNING TREE-BASED GRAPH GENERATION

We now explain how our STGG framework incorporates the decisions $d_1, \ldots, d_T$ to build the spanning tree $\mathcal{T} = (\mathcal{A}_{\mathcal{T}}, \mathcal{B}_{\mathcal{T}}, \mathcal{E}_{\mathcal{T}})$ and residual edges $\mathcal{E}_R$ from scratch. To this end, our framework introduces the state information of (a) a *pointer vertex* $i_{\text{point}} \in \mathcal{A}_{\mathcal{T}} \cup \mathcal{B}_{\mathcal{T}}$ for specifying the target of the next operation, (b) a *stack* $\mathcal{S}_{\text{branch}}$ that stores vertices to use later as a starting point of a "branch" in the spanning tree, and (c) a *list* $\mathcal{L}_{\text{res}}$ that stores vertices to use later for constructing residual edges.

Algorithm 1 Tree-based generation of molecular graphs

1: **Input:** sequence of decisions $d_1, \ldots, d_T$.
2: **Output:** graph $\mathcal{G} = (\mathcal{A}, \mathcal{B}, \mathcal{E})$, atom attributes $\{x_a\}_{a \in \mathcal{A}}$, and bond attributes $\{x_b\}_{b \in \mathcal{B}}$
3: Set $\mathcal{A}_\mathcal{T} \leftarrow \emptyset$, $\mathcal{B}_\mathcal{T} \leftarrow \emptyset$, $\mathcal{E}_\mathcal{T} \leftarrow \emptyset$, $\mathcal{E}_R \leftarrow \emptyset$, and $\mathcal{T} \leftarrow (\mathcal{A}_\mathcal{T}, \mathcal{B}_\mathcal{T}, \mathcal{E}_\mathcal{T})$.   ▷ *Initialize the empty graph.*
4: Set $\mathcal{L}_{\mathtt{res}}$ as an empty list and $\mathcal{S}_{\mathtt{branch}}$ as an empty stack.
5: **for** $t = 1, \ldots, T$ **do**
6:     **if** $d_t \in \mathcal{X}_{\mathtt{atom}}$ **then**   ▷ *Add a new atom vertex.*
7:        Create a new atom vertex a and set $\mathcal{A} \leftarrow \mathcal{A} \cup \{b\}$ and $x_a \leftarrow d_t$.
8:        If $|\mathcal{B}_\mathcal{T}| > 0$, set $\mathcal{E}_\mathcal{T} \leftarrow \mathcal{E}_\mathcal{T} \cup \{\{a, i_{\mathtt{point}}\}\}$.   ▷ *Edge is added when tree is not empty.*
9:        Set $i_{\mathtt{point}} \leftarrow a$.
10:     **if** $d_t \in \mathcal{X}_{\mathtt{bond}}$ **then**   ▷ *Add a new bond vertex.*
11:        Create a new bond vertex b and set $\mathcal{E}_\mathcal{T} \leftarrow \mathcal{E}_\mathcal{T} \cup \{\{b, i_{\mathtt{point}}\}\}$, $\mathcal{B}_\mathcal{T} \leftarrow \mathcal{B}_\mathcal{T} \cup \{b\}$, and $x_b \leftarrow d_t$.
12:        Set $i_{\mathtt{point}} \leftarrow b$.
13:     **if** $d_t = \texttt{"*"}$ **then** Insert $i_{\mathtt{point}}$ into $\mathcal{L}_{\mathtt{res}}$.   ▷ *Add pointer vertex into the queue.*
14:     **if** $d_t \in \mathcal{L}_{\mathtt{res}}$ **then** Pop d_t from $\mathcal{L}_{\mathtt{res}}$ and update $\mathcal{E}_R \leftarrow \mathcal{E}_R \cup \{\{i_{\mathtt{point}}, d_t\}\}$. ▷ *Add a new residual edge.*
15:     **if** $d_t = \texttt{"("}$ **then** Insert $i_{\mathtt{point}}$ into $\mathcal{S}_{\mathtt{branch}}$.   ▷ *Add pointer vertex into the stack.*
16:     **if** $d_t = \texttt{")"}$ **then** Set $i_{\mathtt{point}} \leftarrow \mathrm{pop}(\mathcal{S}_{\mathtt{branch}})$ ▷ *Update pointer vertex from the stack.*
17: Set $\mathcal{A} \leftarrow \mathcal{A}_\mathcal{T}$, $\mathcal{B} \leftarrow \mathcal{B}_\mathcal{T}$, and $\mathcal{E} \leftarrow \mathcal{E}_\mathcal{T} \cup \mathcal{E}_R$.

In what follows, we describe the seven types of operations, i.e., `attach_atom`, `attach_bond`, `branch_start`, `branch_end`, `res_atom`, `res_bond`, and `terminate`, corresponding to decision values $d \in \mathcal{X}_{\mathtt{atom}} \cup \mathcal{X}_{\mathtt{bond}} \cup \mathcal{L}_{\mathtt{res}} \cup \{\texttt{"("}, \texttt{")"}, \texttt{"*"}, \texttt{"[eos]"}\}$ in detail. See Table 1 for the pairs of operations and the corresponding decisions. We also provide an example of the graph construction process in Figure 2.

Attaching atom and bond vertices to the spanning tree. If the decision d specifies one of the atom or bond attributes, i.e., $d \in \mathcal{X}_{\mathtt{atom}}$ or $d \in \mathcal{X}_{\mathtt{bond}}$, it applies the corresponding `attach_atom` and `attach_bond` operations, respectively. To be specific, the `attach_atom` operation adds a new atom vertex a into the spanning tree $\mathcal{T}$ as a neighbor of the pointer vertex $i_{\mathtt{pointer}}$, i.e., $\mathcal{A}_\mathcal{T} \leftarrow \mathcal{A}_\mathcal{T} \cup \{a\}$, $\mathcal{E}_\mathcal{T} \leftarrow \mathcal{E}_\mathcal{T} \cup \{a, i_{\mathtt{pointer}}\}$. The value d is set as the new atom attribute, i.e., $x_a \leftarrow d$. The newly added vertex is set as the next pointer vertex, i.e., $i_{\mathtt{pointer}} \leftarrow a$. The `attach_bond` operation similarly adds a new bond vertex. For example, a line graph can be expressed as a sequence of `attach_atom` and `attach_bond` operations, e.g., C-C-C where $\texttt{"C"} \in \mathcal{X}_\mathcal{A}$ and $\texttt{"-"} \in \mathcal{X}_\mathcal{B}$.

Branching out the spanning tree. To express graph structures with vertices of degree larger than two, our framework utilizes pairs of the `branch_start` and the `branch_end` operations with decision values of $\texttt{"("}$ and $\texttt{")"}$, respectively. To be specific, the `branch_start` operation inserts the current pointer vertex into a stack $\mathcal{S}_{\mathtt{branch}}$ of vertices. Then the `branch_end` operation pops a vertex from the stack $\mathcal{S}_{\mathtt{branch}}$ and sets it as the new pointer vertex. For an example, a graph with one atom vertex of degree three is constructed from a sequence of decisions C-C(-C)(-C).

Adding residual edges. To construct cyclic molecular graphs, our framework generates residual edges based on pairs of `res_atom` operation and `res_bond` operation, corresponding to decision values of $\texttt{"*"}$ and $d \in \mathcal{L}_{\mathtt{res}}$, respectively. To be specific, the `res_atom` operation inserts the current (atom) pointer vertex into a list $\mathcal{L}_{\mathtt{res}}$. Next, when the decision value $d \in \mathcal{L}_{\mathtt{res}}$ is received for the `res_bond` operation, the corresponding vertex d is popped from the list $\mathcal{L}_{\mathtt{res}}$ and forms a new residual edge with the current (bond) pointer vertex, i.e., $\mathcal{E}_\mathcal{R} \leftarrow \mathcal{E}_\mathcal{R} \cup \{\{d, i_{\mathtt{pointer}}\}\}$. For an example, a cyclic molecular graph is constructed from a sequence of decisions C*-O-O-1, where $\texttt{"1"}$ indicates `res_bond` operation with decision of the first atom vertex with attribute $\texttt{"C"}$.

Termination. The decision $\texttt{"[eos]"}$ applies the `terminate` operation to finish the construction.

We provide the full algorithm in Algorithm 1. We also provide an algorithm to extract a sequence of decisions for constructing a given graph in Appendix A. Such an algorithm is used to obtain sequence of decisions as targets for training the generative model under the STGG framework.

(a) Attention module   (b) Relative positional encoding

Figure 3: Attention module and the relative positional encoding used in our framework.

2.3 MASKING OUT INVALID DECISIONS FOR A VALID MOLECULAR GRAPH

Based on Algorithm 1, we develop two criteria for determining whether if a sequence of decisions leads to (a) valid generation of a molecular graph and (b) generation of a molecule satisfying the valence rule. Such criteria are used to mask out invalid decisions to guarantee generating a valid molecular graph.

Validity of graph generation. To determine whether if a sequence of decisions lead to a valid generation of a molecular graph, we propose an algorithm that outputs a set of valid decisions given the previous decision d, stack of pointer vertices $\mathcal{S}_{\text{branch}}$, and list of atom vertices $\mathcal{L}_{\text{res}}$ during execution of Algorithhm 1. In what follows, we provide a brief description of grammars enforced by the algorithm. We also provide the detailed algorithm in Appendix B.

- The `branch_end` operation only appears when the stack of pointer vertex $\mathcal{S}_{\text{branch}}$ is non-empty.
- The operations `res_atom` and `res_bond` are atom-specific and bond-specific, hence they only appear when the pointer vertex is located at an atom vertex and a bond vertex, respectively.
- All the bond vertices have degree of two, hence `branch_start` and `branch_end` operations only appear when the pointer vertex is located at an atom vertex.
- The stack do not contain duplicates of the a pointer vertex at the same time.
- The `terminate` operation is only allowed when the stack $\mathcal{S}_{\text{branch}}$ and the list $\mathcal{L}_{\text{res}}$ is empty.

Validity of satisfying the valence rule. To consider chemical validity of molecules, our framework offers the ability to constrain the its generation on molecules that satisfy the *valence rule* for each atom. That is, the generated graph $\mathcal{G} = (\mathcal{A}, \mathcal{B}, \mathcal{E})$ satisfies the constraint $v(x_a) \geq \sum_{b \in \mathcal{N}(a)} o(x_b)$ for every atom vertex $a \in \mathcal{A}$ where $v(x_a)$ denotes the valence of an atom type x_a and $o(x_b)$ denotes the bond order. To this end, we keep a record $r(a)$ of available valence for each atom $a \in \mathcal{A}$ and update them for each decision. For example, when a bond vertex b is newly added, record of the neighboring atom vertex a is updated by $r(a) \leftarrow v(a) - o(x_b)$. The main idea is to forbid actions that lead to negative values of $r(a)$. We provide a detailed algorithm in Appendix C.

3 TRANSFORMER ARCHITECTURE FOR TREE-BASED GENERATION

In this section, we describe our deep neural network architecture for generating sequence of decisions $d_1, \ldots, d_T$ under the STGG framework. To accurately recognize the decision process, we employ the tree-based relative positional encodings on the intermediate spanning tree $\mathcal{T}$. We also introduce an attention mechanism to express a probability distribution over $\mathcal{L}_{\text{res}}$ which depends on intermediate state of the algorithm.

3.1 TREE-BASED POSITIONAL ENCODING FOR MULTI-HEAD ATTENTION LAYERS

Each intermediate layer in our model is a combination of a multi-head self-attention module and a position-wise feed-forward neural network similar to that of Vaswani et al. (2017). The main

difference is on how we modify the architecture to incorporate tree-based positional encodings. To be specific, let $H = [h_1^\top, \ldots, h_T^\top] \in \mathbb{R}^{T \times \ell}$ denote the input of a self-attention module where d is the hidden dimension and $h_t \in \mathbb{R}^{1 \times \ell}$ is the hidden representation at position t. The input H is projected by three matrices $W_Q \in \mathbb{R}^{\ell \times \ell_K}, W_K \in \mathbb{R}^{\ell \times \ell_K}$ and $W_V \in \mathbb{R}^{\ell \times \ell_V}$ to the corresponding representations Q, K and V, respectively. A single self-attention head is then calculated as

$$Q = HW_Q, \quad K = HW_K, V = HW_V, \tag{1}$$

$$A = \frac{QK^\top}{\sqrt{\ell_K}} + P, \quad P_{t_1,t_2} = \mathbf{z}^{(1)}_{\phi_{\texttt{forward}}(t_1,t_2)} + \mathbf{z}^{(2)}_{\phi_{\texttt{backward}}(t_1,t_2)} + \mathbf{z}^{(3)}_{\phi_{\texttt{seq}}(t_1,t_2)}, \tag{2}$$

$$\text{Attention}(H) = \text{SoftMax}(M \circ A)V, \tag{3}$$

where $\text{Attention}(H)$ is output of the attention head, M is the triangular mask to forbid the model from accessing future information while making a prediction, and $\circ$ denotes the element-wise multiplication between matrices.

Furthermore, P is the newly introduced relative positional encoding. It is a summation over the trainable embedding vectors $\mathbf{z}^{(1)}, \mathbf{z}^{(2)}, \mathbf{z}^{(3)}$ indexed by relative position values of $\phi_{\texttt{forward}}(t_1,t_2), \phi_{\texttt{backward}}(t_1,t_2)$, and $\phi_{\texttt{seq}}(t_1,t_2)$. To be specific, the *tree-based relative positions* $\phi_{\texttt{forward}}(t_1,t_2)$ and $\phi_{\texttt{backward}}(t_1,t_2)$ denotes the number of forward and backward edges in the spanning tree path between pointer vertices at the t_1-th and t_2-th time step. The direction of edge is decided by order of generation in the STGG framework. Such an encoding was inspired from recent works (Villmow et al., 2021; Lukovnikov & Fischer, 2021; Ying et al., 2021) using Transformers to recognize graphs and trees. Finally, the *sequence-based relative position* $\phi_{\texttt{seq}}(t_1,t_2) = t_1 - t_2$ denotes the relative difference of time-steps for the decisions.

3.2 ATTENTION FOR UPDATING RESIDUAL EDGES.

Our model generates a categorical distribution over the space of $\mathcal{X} = \mathcal{X}_{\texttt{atom}} \cup \mathcal{X}_{\texttt{bond}} \cup \mathcal{L}_{\texttt{res}} \cup \{\texttt{"("},\texttt{")"},\texttt{"*"},\texttt{"[eos]"}\}$. It is relatively straight-forward to output an unnormalized probability over values of $\mathcal{X}_{\texttt{atom}} \cup \mathcal{X}_{\texttt{bond}} \cup \{\texttt{"("},\texttt{")"},\texttt{"*"}\}$ using a linear classifier on top of the Transformer model. However, it is non-trivial to assign probability values for $\texttt{res\_bond}$ operation, i.e., decisions values of $d \in \mathcal{L}_{\texttt{res}}$, since $\mathcal{L}_{\texttt{res}}$ varies between different time-steps. To handle this case, we use an attention-based mechanism for assigning unnormalized probability to decision values in the list $\mathcal{L}_{\texttt{res}}$. To be specific, at the final layer of our model, we obtain the following probability distribution $p(d)$.

$$p(d) \propto \begin{cases} m_g(d) \cdot m_v(d) \cdot \exp(\mathbf{w}_d^\top h) & \forall d \in \mathcal{X}_{\texttt{atom}} \cup \mathcal{X}_{\texttt{bond}} \cup \{\texttt{"("},\texttt{")"},\texttt{"*"}\}, \\ m_g(d) \cdot m_v(d) \cdot \exp(h_d^\top W_1 W_2^\top h) & \forall d \in \mathcal{L}_{\texttt{res}}, \end{cases} \tag{4}$$

where $\mathbf{w}_d \in \mathbb{R}^{1 \times \ell}$ is a decision-specific vector, $W_1, W_2 \in \mathbb{R}^{\ell \times \tilde{\ell}}$ are weight matrices, and h is the decision embedding, i.e., output of the Transformer layer corresponding to the previously made decision. Furthermore, h_d is the embedding corresponding to a past decision $d \in \mathcal{L}_{\texttt{res}}$. Finally, $m_v(d), m_g(d)$ are the mask for excluding invalid decisions that violate the validity of graph generation and valence rule, respectively. The masks are obtained using the criteria explained in Section 2.3. We use the mask during both training and evaluation of the model; this differs from existing graph-generative models which forbid invalid decisions only at evaluation using a sample-rejection scheme.

4 RELATED WORKS

SMILES-based molecular generative models. The sequence of decisions in STGG for molecule generation is largely inspired from how a sequence of SMILES characters define the molecular structure. The main difference lies in how our sequence (a) does not use any abbreviations,[3] and (b) includes the decision of selecting a vertex to perform $\texttt{res\_bond}$ operations.[4] Such modifications allow the STGG framework to interpret the sequence of decisions as sequential graph modification of the spanning tree and residual edges.

Several studies on molecule-generating deep neural networks proposed string-based (Gómez-Bombarelli et al., 2016; Segler et al., 2018; Kim et al., 2021) or grammar-based (Kusner et al., 2017; Dai et al., 2018) generation of the SMILES. However, they do not utilize the underlying graph

---

[3]For example, the SMILES representation ignores the notation of single bonds.
[4]The SMILES representation handle edges outside the spanning tree using "ring markers."

Table 2: Experimental results on ZINC250K and QM9 datasets.

METHOD	CORRECTABLE	ZINC250K			QM9		
		VALID	UNIQUE	NOVEL	VALID	UNIQUE	NOVEL
GCPN (You et al., 2018)	✓	0.20	**1.0000**	**1.0000**	-	-	-
MRNN (Popova et al., 2019)	✓	0.65	0.9989	**1.0000**	-	-	-
GRAPHNVP (Madhawa et al., 2019)		0.426	0.948	**1.0000**	0.831	**0.992**	0.582
GRF (Honda et al., 2019)		0.734	0.537	**1.0000**	0.845	0.66	0.586
GRAPHAF (Shi et al., 2020)	✓	0.680	0.991	**1.0000**	0.67	0.9415	0.8883
MOFLOW (Zang & Wang, 2020)	✓	0.680	0.991	**1.0000**	0.8896	0.9853	0.9604
GRAPHCNF (Lippe & Gavves, 2021)		0.9635	0.9998	0.9998	-	-	-
GRAPHDF (Luo et al., 2021)	✓	0.8903	0.9916	**1.0000**	0.8267	0.9762	**0.9810**
SMILES-TRANSFORMER		0.9558	0.9998	0.9946	0.9908	0.9629	0.6939
STGG (ours)	✓	**0.9950**	0.9999	0.9989	**1.0000**	0.9676	0.7273

structure of the SMILES representation. Given the similarity of our decision process to the SMILES representation, our STGG algorithm could be seen as a modified SMILES-based generative model which is augmented with the information of the molecular graph structure.

Graph-based molecular generative models. Researchers have developed a large variety of molecular graph generation frameworks based on atom-wise and bond-wise operations (You et al., 2018; Popova et al., 2019; Madhawa et al., 2019; Honda et al., 2019; Shi et al., 2020; Zang & Wang, 2020; Lippe & Gavves, 2021; Luo et al., 2021; Chen et al., 2021a). The frameworks mainly differ in the choice of model for generating the full adjacency of the molecular graph, e.g., using recurrent neural network (Popova et al., 2019), continuous normalizing flow model (Shi et al., 2020), and discrete normalizing flow model (Luo et al., 2021). Our STGG framework differs from this line of research since it proposes a new type of graph-based operations for generating the molecular graph. Furthermore, our work is the first to successfully train a Transformer architecture (Vaswani et al., 2017) for molecular graph generation.

In another line of research, several works (Jin et al., 2018; 2019; 2020) proposed generative models based on using the junction-tree representation with molecular substructures as building blocks. Based on such a representation, such works utilize tree-constructive operations to generate the full graph. Since they operate on such a coarse-grained molecular representation, they typically require a fewer number of building blocks to generate the whole molecule. In comparison, our STGG framework utilizes a more fine-grained molecular representation and may additionally learn the inner semantics of substructures that are used as building blocks for the junction tree.

5 EXPERIMENT

In this section, we report the experimental results of the proposed spanning tree-based graph generation (STGG) framework. In Section 5.1 and 5.2, we compare with the existing graph generative models in the ZINC250K (Irwin et al., 2012) and QM9 (Ramakrishnan et al., 2014). We provide ablation studies on each component of our method using the ZINC250K dataset. In Section 5.2, we compare with the existing molecule generative models using the MOSES benchmark (Polykovskiy et al., 2020). Finally, in Section 5.3, we provide our results on the molecular optimization task with respect to the penalized octanol-water partition coefficient function (PLOGP). We provide the implementation details and illustration of the generated molecules in Appendix D and E, respectively.

5.1 MOLECULE GENERATION ON ZINC250K AND QM9 DATASETS

We first compare to the literature standard for the molecular generation task in the ZINC250K and the QM9 datasets. To this end, we train our generative model on the respective datasets and sample 10,000 molecules to measure (a) the ratio of valid molecules (VALID), (b) the ratio of unique molecules (UNIQUE), and (c) the ratio of novel molecules with respect to the training dataset (NOVEL). We compare with the numbers reported by recently proposed graph generative models (Shi et al., 2020; Luo et al., 2021). We also provide an additional baseline of a transformer architecture trained to generate the SMILES representation for the molecule (SMILES-TRANSFORMER).

We mark CORRECTABLE for methods which can optionally use a sample-rejection scheme to forbid decisions that violate the chemical rules at evaluation. Note that our framework can train the

Table 4: First set of experimental results for the MOSES benchmark.

METHOD	VALID	UNIQUE1	UNIQUE2	INTDIV	INTDIV2	FILTERS	NOVEL
TRAINING DATASET	1.0000	1.0000	1.0000	0.8567	0.8508	1.0000	0.0000
HMM (Polykovskiy et al., 2020)	0.0760	0.6230	0.5671	0.8466	0.8104	0.9024	**0.9994**
NGRAM (Polykovskiy et al., 2020)	0.2376	0.9740	0.9217	**0.8738**	**0.8644**	0.9582	0.9694
COMBINATORIAL (Liu et al., 2017)	**1.0000**	0.9983	0.9909	0.8732	0.8666	0.9557	0.9878
CHARRNN (Segler et al., 2018)	0.9748	**1.0000**	0.9994	0.8562	0.8503	0.9943	0.8419
AAE (Polykovskiy et al., 2020)	0.9368	**1.0000**	0.9994	0.8557	0.8499	0.9960	0.7931
VAE (Polykovskiy et al., 2020)	0.9767	**1.0000**	0.9984	0.8558	0.8498	0.9970	0.6949
JT-VAE (Jin et al., 2018)	**1.0000**	**1.0000**	0.9996	0.8551	0.8493	0.9760	0.9143
LATENTGAN (Prykhodko et al., 2019)	0.8966	**1.0000**	0.9968	0.8565	0.8505	0.9735	0.9498
STGG (ours)	**1.0000**	**1.0000**	0.9987	0.8556	0.8496	**0.9976**	0.6727

Table 5: Second set of experimental results for the MOSES benchmark.

	FCD (↓)		SNN (↑)		FRAG (↑)		SCAF (↑)	
METHOD	TEST	TESTSF	TEST	TESTSF	TEST	TESTSF	TEST	TESTSF
TRAINING DATASET	0.0080	0.4755	0.6419	0.5859	1.0000	0.9986	0.9907	0.0000
HMM (Polykovskiy et al., 2020)	24.466	25.431	0.3876	0.3795	0.5754	0.5681	0.2065	0.0490
NGRAM (Polykovskiy et al., 2020)	5.5069	6.2306	0.5209	0.4997	0.9846	0.9815	0.5302	0.0977
COMBINATORIAL (Liu et al., 2017)	4.2375	4.5113	0.4514	0.4388	0.9912	0.9904	0.4445	0.0865
CHARRNN (Segler et al., 2018)	0.0732	0.5204	0.6015	0.5649	**0.9998**	0.9983	0.9242	**0.1101**
AAE (Polykovskiy et al., 2020)	0.5555	1.0572	0.6081	0.5677	0.9910	0.9905	0.9022	0.0789
VAE (Polykovskiy et al., 2020)	0.0990	0.5670	0.6257	0.5783	0.9994	0.9984	0.9386	0.0588
JT-VAE (Jin et al., 2018)	0.3954	0.9382	0.5477	0.5194	0.9965	0.9947	0.8964	0.1009
LATENTGAN (Prykhodko et al., 2019)	0.2968	0.8281	0.5371	0.5132	0.9986	0.9972	0.8867	0.1072
STGG (ours)	**0.0680**	**0.5032**	**0.6359**	**0.5851**	**0.9998**	**0.9984**	**0.9416**	0.0389

generative model under the valence correction mask *during training*, while existing graph generative models use the valence correction *only at evaluation*. However, for comparison, we do not use the valence correction mask during training in this experiment.

We report the experimental results in Table 2. In the table, we observe that our STGG framework outperforms all the existing molecular graph generative models for high VALID at the cost of relatively lower NOVEL. In particular, our generative model can achieve a 100% ratio of valid molecules in the QM9 dataset even without any correction procedure. Such a result highlights the how our model can effectively learn the chemical rules and model the underlying distribution.

Table 3: Ablation on ZINC250K.

Method	VALID	UNIQUE	NOVEL
A	0.9296	0.9995	0.9984
S	0.9814	0.9995	0.9955
S+T	0.9834	0.9997	0.9961
S+T+G	0.9950	**0.9999**	**0.9989**
S+T+G+V	**1.0000**	0.9992	0.9927

Finally, our STGG framework performing better than the SMILES-based transformer implies how the performance of our generative model stems from the STGG framework, rather than using the Transformer architecture.

Ablation studies. We also conduct ablation studies on the ZINC250k dataset to verify the effectiveness of our method. To this end, we report the experimental results of our method without specific components. To be specific, we ablate the effects of using sequential relative positional encoding (S), tree-based relative positional encoding (T), graph-construction mask (G), and valence rule mask (V). We also consider an additional baseline of using the absolute positional encoding (A) as in the original Transformer architecture (Vaswani et al., 2017). In Table 3 and Figure 4, one can observe how each component of

Figure 4: Ablation on ZINC250K.

our algorithm is crucial for achieving high VALID. In particular, the tree encoding is essential for the performance, showing the importance of tree-based representation that we use in our model.

5.2 MOLECULE GENERATION ON THE MOSES BENCHMARK

We also compare our method on the MOSES benchmark with the existing models. The MOSES benchmark offers a large collection of metrics to access the overall quality of generated molecules. To be specific, in addition to VALID, UNIQUE, NOVEL, we consider internal diversity of molecules (INTDIV), ratio of samples being accepted to chemical filters (FILTERS), Frétchet ChemNet Distance

Figure 5: Molecular optimization results with the top-3 property scores denoted by 1ST, 2ND, and 3RD.

Method	OFFLINE	PLOGP		
		1ST	2ND	3RD
GVAE (Kusner et al., 2017)	✓	2.94	2.89	2.80
SD-VAE (Dai et al., 2018)	✓	4.04	3.50	2.96
JT-VAE (Jin et al., 2018)		5.30	4.93	4.49
GRAPHAF (Shi et al., 2020)		12.23	11.29	11.05
GRAPHDF (Luo et al., 2021)		13.70	13.18	13.17
STGG, $\gamma = 4$ (ours)	✓	4.56	4.55	4.53
STGG, $\gamma = 5$ (ours)	✓	5.06	4.89	4.86
STGG, $\gamma = 6$ (ours)	✓	5.72	5.15	4.92
STGG, $\gamma = 7$ (ours)	✓	**23.32**	**18.75**	**16.50**

$4.56, \gamma = 4$ $5.06, \gamma = 5$

$5.72, \gamma = 6$ $23.32, \gamma = 7$

Figure 6: Optimized 1ST molecules

(FCD), nearest neighborhood similarity (SNN), frament similarity (FRAG), and Scaffold similarity (SCAF). The similarity metrics of FCD, SNN, FRAG, SCAF are measured with respect to the test dataset of molecules and the scaffolds extracted from them.

In Table 4 and 5, we provide our experimental result. Here, one can observe how our algorithm outperforms the existing works for 10 out of 15 metrics including FILTERS, FCD-TEST, FCD-TESTSF, SNN-TEST, SNN-TESTSF, FRAG-TEST, FRAG-TESTSF, and SCAF-TEST. This highlights the ability of our STGG framework to successfully learn the training distribution.

5.3 MOLECULAR OPTIMIZATION FOR PENALIZED OCTANOL-WATER PARTITION COEFFICIENT

Finally, we compare with existing graph generative models for the task of molecular optimization. To this end, we consider the literature standard of maximizing the penalized octanol-water partition coefficient (PLOGP). However, several works (Gao & Coley, 2020; Coley, 2020) have noted how the existing algorithms on this benchmark may not be practical, since PLOGP is ill-defined as a scoring function for molecules; this scoring function may assign high values to "unrealistic" molecules that are unstable and hard to synthesize in practice. As a result, any interaction between the scoring function and the generative model may bias the model towards generating unrealistic molecules.

To consider this aspect, we propose an *offline optimization algorithm* which does not require interaction between the scoring function and the generative model, i.e., we train our model only on the dataset of real-world molecules. At a high-level, we train a conditional generative model $p_\theta(m|\gamma)$ under the STGG framework with PLOGP as the condition γ. At the test time, we sample from a high value γ to obtain high-scoring molecules. Such an algorithm is inspired from the recent offline reinforcement learning algorithms (Schmidhuber, 2019; Kumar & Levine, 2020; Chen et al., 2021b; Janner et al., 2021). We fully describe our molecular optimization algorithm in Appendix F.

In Table 5 and Figure 6, we report the result of our molecular optimization experiment. We provide additional illustrations of the generated molecules in Appendix G. One can observe how our STGG model outperforms the existing generative models by a large margin. This demonstrates how our model can extrapolate well outside the training distribution. Intriguingly, in Figure 6 and Appendix G, one can observe how increasing γ gradually changes the optimized molecule from realistic structures to large, chain-like, and unrealistic structures. This observation is in agreement with prior works (Winter et al., 2019; Nigam et al., 2020; Shi et al., 2020; Ahn et al., 2020; Luo et al., 2021) which report molecules with high PLOGP that have chain-like and unrealistic structures. However, our offline optimization algorithm offers an additional freedom of the condition γ to control the trade-off between high PLOGP and realistic-ness of the generated molecules. Investigating the use of our newly proposed optimization algorithm is an interesting future research direction.

6 CONCLUSION

In this paper, we propose STGG which is the first spanning tree-based framework for the generation of molecules using the Transformer architecture. The key idea of using the spanning tree for graph generation applies to any graph type outside the molecules; we believe such an extension of our work to be both promising and interesting. We also propose an offline algorithm for molecular optimization which allows the trade-off between the high score and the realistic-ness of molecules. We leave more investigation of the newly proposed optimization algorithm as future work.

7 REPRODUCIBILITY STATEMENT

We provide explicit description of our algorithm in Algorithm 1, Appendix 2, 3, and 4. We list the hyper-parameters, the hardware used for the experiments, and the data-processing information in Appendix D. We provide illustrations of the molecules generated for the experiments in Figure 6, and Appendix E, G. We submit the full implementation of our STGG framework and the baselines used in our experiments as a supplementary material.

REFERENCES

Sungsoo Ahn, Junsu Kim, Hankook Lee, and Jinwoo Shin. Guiding deep molecular optimization with genetic exploration. *Advances in Neural Information Processing Systems*, 33, 2020.

Binghong Chen, Tianzhe Wang, Chengtao Li, Hanjun Dai, and Le Song. Molecule optimization by explainable evolution. In *International Conference on Learning Representations*, 2021a. URL https://openreview.net/forum?id=jHefDGsorp5.

Lili Chen, Kevin Lu, Aravind Rajeswaran, Kimin Lee, Aditya Grover, Michael Laskin, Pieter Abbeel, Aravind Srinivas, and Igor Mordatch. Decision transformer: Reinforcement learning via sequence modeling. *arXiv preprint arXiv:2106.01345*, 2021b.

Connor W Coley. Defining and exploring chemical spaces. *Trends in Chemistry*, 2020.

Hanjun Dai, Yingtao Tian, Bo Dai, Steven Skiena, and Le Song. Syntax-directed variational autoencoder for structured data. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=SyqShMZRb.

P Erdös, A Rényi, et al. On random graphs. In *Publicationes mathematicae 6*, volume 1, pp. 290–297, 1959.

Wenhao Gao and Connor W Coley. The synthesizability of molecules proposed by generative models. *Journal of Chemical Information and Modeling*, 2020.

Rafael Gómez-Bombarelli, Jorge Aguilera-Iparraguirre, Timothy D Hirzel, David Duvenaud, Dougal Maclaurin, Martin A Blood-Forsythe, Hyun Sik Chae, Markus Einzinger, Dong-Gwang Ha, Tony Wu, et al. Design of efficient molecular organic light-emitting diodes by a high-throughput virtual screening and experimental approach. *Nature materials*, 15(10):1120–1127, 2016.

Shion Honda, Hirotaka Akita, Katsuhiko Ishiguro, Toshiki Nakanishi, and Kenta Oono. Graph residual flow for molecular graph generation. *arXiv preprint arXiv:1909.13521*, 2019.

John J Irwin, Teague Sterling, Michael M Mysinger, Erin S Bolstad, and Ryan G Coleman. Zinc: a free tool to discover chemistry for biology. *Journal of chemical information and modeling*, 52(7): 1757–1768, 2012.

Michael Janner, Qiyang Li, and Sergey Levine. Reinforcement learning as one big sequence modeling problem. *arXiv preprint arXiv:2106.02039*, 2021.

Wengong Jin, Regina Barzilay, and Tommi Jaakkola. Junction tree variational autoencoder for molecular graph generation. In *International Conference on Machine Learning*, pp. 2323–2332, 2018.

Wengong Jin, Kevin Yang, Regina Barzilay, and Tommi Jaakkola. Learning multimodal graph-to-graph translation for molecule optimization. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=B1xJAsA5F7.

Wengong Jin, Regina Barzilay, and Tommi Jaakkola. Hierarchical generation of molecular graphs using structural motifs. In *International Conference on Machine Learning*, pp. to appear, 2020.

Hyunseung Kim, Jonggeol Na, and Won Bo Lee. Generative chemical transformer: attention makes neural machine learn molecular geometric structures via text. *arXiv preprint arXiv:2103.00213*, 2021.

Aviral Kumar and Sergey Levine. Model inversion networks for model-based optimization, 2020. URL https://openreview.net/forum?id=SklsBJHKDS.

Matt J Kusner, Brooks Paige, and José Miguel Hernández-Lobato. Grammar variational autoencoder. In *International Conference on Machine Learning*, pp. 1945–1954, 2017.

Phillip Lippe and Efstratios Gavves. Categorical normalizing flows via continuous transformations. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=-GLNZeVDuik.

Tairan Liu, Misagh Naderi, Chris Alvin, Supratik Mukhopadhyay, and Michal Brylinski. Break down in order to build up: decomposing small molecules for fragment-based drug design with e molfrag. *Journal of chemical information and modeling*, 57(4):627–631, 2017.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=Bkg6RiCqY7.

Denis Lukovnikov and Asja Fischer. Insertion-based tree decoding. In *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pp. 3201–3213, 2021.

Youzhi Luo, Keqiang Yan, and Shuiwang Ji. GraphDF: A discrete flow model for molecular graph generation. In *International Conference on Machine Learning*, 2021.

Kaushalya Madhawa, Katushiko Ishiguro, Kosuke Nakago, and Motoki Abe. Graphnvp: An invertible flow model for generating molecular graphs. *arXiv preprint arXiv:1905.11600*, 2019.

AkshatKumar Nigam, Pascal Friederich, Mario Krenn, and Alan Aspuru-Guzik. Augmenting genetic algorithms with deep neural networks for exploring the chemical space. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=H1lmyRNFvr.

Daniil Polykovskiy, Alexander Zhebrak, Benjamin Sanchez-Lengeling, Sergey Golovanov, Oktai Tatanov, Stanislav Belyaev, Rauf Kurbanov, Aleksey Artamonov, Vladimir Aladinskiy, Mark Veselov, Artur Kadurin, Simon Johansson, Hongming Chen, Sergey Nikolenko, Alan Aspuru-Guzik, and Alex Zhavoronkov. Molecular Sets (MOSES): A Benchmarking Platform for Molecular Generation Models. *Frontiers in Pharmacology*, 2020.

Mariya Popova, Mykhailo Shvets, Junier Oliva, and Olexandr Isayev. MolecularRNN: Generating realistic molecular graphs with optimized properties. *arXiv preprint arXiv:1905.13372*, 2019.

Kristina Preuer, Philipp Renz, Thomas Unterthiner, Sepp Hochreiter, and Günter Klambauer. Fréchet ChemNet distance: a metric for generative models for molecules in drug discovery. *Journal of chemical information and modeling*, 58(9):1736–1741, 2018.

Oleksii Prykhodko, Simon Viet Johansson, Panagiotis-Christos Kotsias, Josep Arús-Pous, Esben Jannik Bjerrum, Ola Engkvist, and Hongming Chen. A de novo molecular generation method using latent vector based generative adversarial network. *Journal of Cheminformatics*, 11(1):1–13, 2019.

Raghunathan Ramakrishnan, Pavlo O Dral, Matthias Rupp, and O Anatole Von Lilienfeld. Quantum chemistry structures and properties of 134 kilo molecules. *Scientific data*, 1(1):1–7, 2014.

Juergen Schmidhuber. Reinforcement learning upside down: Don't predict rewards–just map them to actions. *arXiv preprint arXiv:1912.02875*, 2019.

Marwin HS Segler, Thierry Kogej, Christian Tyrchan, and Mark P Waller. Generating focused molecule libraries for drug discovery with recurrent neural networks. *ACS central science*, 4(1): 120–131, 2018.

Chence Shi, Minkai Xu, Zhaocheng Zhu, Weinan Zhang, Ming Zhang, and Jian Tang. GraphAF: a flow-based autoregressive model for molecular graph generation. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=S1esMkHYPr.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Johannes Villmow, Adrian Ulges, and Ulrich Schwanecke. A structural transformer with relative positions in trees for code-to-sequence tasks. In *2021 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–10. IEEE, 2021.

David Weininger. SMILES, a chemical language and information system. 1. introduction to methodology and encoding rules. *Journal of chemical information and computer sciences*, 28(1):31–36, 1988.

Robin Winter, Floriane Montanari, Andreas Steffen, Hans Briem, Frank Noé, and Djork-Arné Clevert. Efficient multi-objective molecular optimization in a continuous latent space. *Chemical science*, 10(34):8016–8024, 2019.

Chengxuan Ying, Tianle Cai, Shengjie Luo, Shuxin Zheng, Guolin Ke, Di He, Yanming Shen, and Tie-Yan Liu. Do transformers really perform bad for graph representation? *arXiv preprint arXiv:2106.05234*, 2021.

Jiaxuan You, Bowen Liu, Zhitao Ying, Vijay Pande, and Jure Leskovec. Graph convolutional policy network for goal-directed molecular graph generation. In *Advances in Neural Information Processing Systems*, pp. 6410–6421, 2018.

Chengxi Zang and Fei Wang. Moflow: an invertible flow model for generating molecular graphs. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 617–626, 2020.

A EXTRACTING SEQUENCE OF DECISIONS FROM A MOLECULAR GRAPH

In this section, we explain our algorithm for finding a sequence of decisions to construct a given molecular graph $\mathcal{G} = (\mathcal{A}, \mathcal{B}, \mathcal{E})$. The high-level idea is to first perform a depth-first search on $\mathcal{G}$ to find a spanning tree $\mathcal{T} = (\mathcal{A}, \mathcal{B}, \mathcal{E}_{\mathcal{T}})$ and the corresponding set of residual edges $\mathcal{E}_R = \mathcal{E} \backslash \mathcal{E}_T$. Then the algorithm traverses the spanning tree $\mathcal{T}$ according to the depth-first search tree while (a) allocating `branch_start` and `branch_end` for vertices with degree higher than two and (b) adding `res_atom` and `res_bond` operations for any vertex covered by a residual edge $\{a, b\} \in \mathcal{E}_R$.

To this end, we utilize a stack $\mathcal{S}_{\texttt{dfs}}$ that stores the list of vertices in $\mathcal{G}$ and branching tokens $\{"(", ")"\}$ to visit. At each iteration, an element i of the stack $\mathcal{S}_{\texttt{dfs}}$ is popped. If i is a vertex, the algorithm adds the corresponding decision for `attach_atom` and `attach_bond` operations. If the vertex has more than two successors with respect to the spanning tree $\mathcal{T}$, the successors are inserted into the stack $\mathcal{S}_{\texttt{dfs}}$ with surrounding `"("` and `")"` tokens. If the vertex has only one successor, the successor is inserted into the stack without an additional operation. When the branching tokens $\{"(", ")"\}$ are popped from the stack, the algorithm adds the corresponding decision value to the sequence of decisions. We describe the full scheme in Algorithm 2.

Algorithm 2 Generating sequence of decisions for a molecular graphs

---

1: **Input:** graph $\mathcal{G} = (\mathcal{A}, \mathcal{B}, \mathcal{E})$, atom attributes $\{x_a\}_{a \in \mathcal{A}}$, and bond attributes $\{x_b\}_{b \in \mathcal{B}}$
2: Find a spanning tree $\mathcal{T} = (\mathcal{A}, \mathcal{B}, \mathcal{E}_{\mathcal{T}})$ of $\mathcal{G}$ based on depth-first order and set $\mathcal{E}_R \leftarrow \mathcal{E} \setminus \mathcal{E}_{\mathcal{T}}$.
3: Initialize an empty sequence of decisions $\mathcal{D}$.
4: Choose the root $a \in \mathcal{A}$ of $\mathcal{T}$ to insert in an empty stack $\mathcal{S}_{\text{branch}}$.
5: **do**
6:      Pop i from $\mathcal{S}_{\text{branch}}$.
7:      **if** $i \in \mathcal{A} \cup \mathcal{B}$ **then**
8:          Append x_i to $\mathcal{D}$.   ▷ *Decision to attach the atom vertex.*
9:          **for** $j \in \{j | j \in \mathcal{N}(i), \{i, j\} \in \mathcal{E}_{\mathcal{R}}\}$ **do**   ▷ *Decisions for residual edges.*
10:             If $i \in \mathcal{A}$, append `"*"` to $\mathcal{D}$.
11:             If $i \in \mathcal{B}$, append j to $\mathcal{D}$.
12:          Let $\mathcal{V}$ denote $\{j | j \in \mathcal{N}(i), j \notin \mathcal{A}_{\mathcal{T}} \cup \mathcal{B}_{\mathcal{T}}\}$.   ▷ *Successors of i in depth-first order.*
13:          If $|\mathcal{V}| > 1$, insert `"("` to $\mathcal{S}_{\text{branch}}$.   ▷ *Allocate decision to record pointer vertex.*
14:          Insert vertices in $\mathcal{V}$ to $\mathcal{S}_{\text{branch}}$.   ▷ *Allocate successors to visit later.*
15:          If $|\mathcal{V}| > 1$, insert `")"` to $\mathcal{S}_{\text{branch}}$.   ▷ *Allocate decision to return to the pointer vertex.*
16:      **if** $i \in \{"(", ")"\}$ **then**
17:          Append i to $\mathcal{D}$.
18: **while** $|\mathcal{S}_{\text{branch}}| > 0$
19: **Output:** sequence of decisions $\mathcal{D} = d_1, \ldots, d_T$ to reconstruct $\mathcal{G}$.

B   ALGORITHMS FOR GRAPH MASKING

To determine whether if a sequence of decisions lead to a valid generation of a molecular graph, we propose an algorithm that outputs a set of valid decisions given the current decision d, stack of pointer vertices $\mathcal{S}$, and list of atom vertices $\mathcal{L}$ during execution of Algorithhm 1. We provide the full description in Algorithm 3.

Algorithm 3 Determination of grammar violation

1: **Input:** Current decision d, stack $\mathcal{S}_{\text{branch}}$, and list $\mathcal{L}_{\text{res}}$.
2: **Output:** List of candidate decisions $\mathcal{D}$ that are valid.
3: **if** $d \in \mathcal{X}_{\text{atom}}$ **then**
4:      Set $\mathcal{D} \leftarrow \mathcal{X}_{\text{bond}}$.   ▷ *When the atom vertex is followed by bond vertex.*
5:      Set $\mathcal{D} \leftarrow \mathcal{D} \cup \{$"("$\}$ ▷ *When the atom vertex has more than one successors.*
6:      Set $\mathcal{D} \leftarrow \mathcal{D} \cup \{$"*"$\}$ ▷ *When the atom vertex has a neighboring residual edge.*
7:      If $|\mathcal{S}_{\text{branch}}| > 0$, set $\mathcal{D} \leftarrow \mathcal{D} \cup \{$")"$\}$.   ▷ *The ")" decision appears only when $\mathcal{S}_{\text{branch}}$ is non-empty*
8:      If $|\mathcal{L}_{\text{res}}| > 0$ and $|\mathcal{S}_{\text{branch}}| > 0$, set $\mathcal{D} \leftarrow \mathcal{D} \cup \{$"[eos]"$\}$. ▷ *Allow termination when stack and list are empty.*
9: **if** $d \in \mathcal{X}_{\text{bond}}$ **then**
10:      Set $\mathcal{D} \leftarrow \mathcal{X}_{\text{bond}}$.   ▷ *When the bond vertex is followed by atom vertex.*
11:      Set $\mathcal{D} \leftarrow \mathcal{D} \cup \mathcal{L}_{\text{res}}$ ▷ *When the bond vertex has a neighboring residual edge.*
12: **if** $d = $ "*" **then**
13:      Set $\mathcal{D} \leftarrow \mathcal{X}_{\text{bond}}$.   ▷ *When the atom vertex is followed by bond vertex.*
14:      Set $\mathcal{D} \leftarrow \mathcal{D} \cup \{$"("$\}$ ▷ *When the atom vertex has more than one successors.*
15:      Set $\mathcal{D} \leftarrow \mathcal{D} \cup \{$"*"$\}$ ▷ *When the atom vertex has a neighboring residual edge.*
16:      If $|\mathcal{S}_{\text{branch}}| > 0$, set $\mathcal{D} \leftarrow \mathcal{D} \cup \{$")"$\}$.   ▷ *The ")" decision appears only when $\mathcal{S}_{\text{branch}}$ is non-empty*
17: **if** $d \in \mathcal{L}_{\text{res}}$ **then**
18:      Set $\mathcal{D} \leftarrow \{$)$\}$.   ▷ *Residual edge is only constructed at end of each branch.*
19: **if** $d = $ "(" **then**
20:      Set $\mathcal{D} \leftarrow \mathcal{X}_{\text{bond}}$.   ▷ *Branch always starts with a bond vertex.*
21: **if** $d = $ ")" **then**
22:      Set $\mathcal{D} \leftarrow \mathcal{X}_{\text{bond}} \cup \{(,)\}$.   ▷ *Branch is followed by start or end of another branch.*

C ALGORITHM FOR VALENCE MASKING

To consider chemical validity of molecules, our framework offers the ability to constrain its generation on molecules that satisfy the *valence rule* for each atom. That is, the generated graph $\mathcal{G} = (\mathcal{A}, \mathcal{B}, \mathcal{E})$ satisfies the constraint $v(x_a) \geq \sum_{b \in \mathcal{N}(a)} o(x_b)$ for every atom vertex $a \in \mathcal{A}$ where $v(x_a)$ denotes the valence of an atom type x_a and $o(x_b)$ denotes the bond order.

To this end, we propose an algorithm which iteratively updates a record $r(a)$ of available valence for each atom vertex $a \in \mathcal{A}$. The key idea is to (a) update the record accordingly for each addition of atom and bond orders and (b) pre-allocate valence for the `branch_start` and `res_atom` operations by the amount of minimum bond order $\min_{x \in \mathcal{X}_{\text{bond}}} o(x)$. The second part (b) is required since the `branch_start` and `res_atom` operations indicate future bond vertices to be added as a neighbor of the current atom vertex. We provide the full description in Algorithm 4.

Algorithm 4 Determination of valence rule violation

1: **Input:** Intermediate tree $\mathcal{T} = (\mathcal{A}_{\mathcal{T}}, \mathcal{B}_{\mathcal{T}}, \mathcal{E}_{\mathcal{T}})$, current pointer vertex i_{point}, previous pointer vertex $\tilde{i}_{\text{point}}$, current decision d, previous decision $\tilde{d}$, and record $r(\cdot)$ of available valence.

2: **Output:** Newly updated r and the list $\mathcal{D}$ of decisions that violates the valence rule.

3: **if** $d \in \mathcal{X}_{\text{atom}}$ **then**

4:      Set $r(i_{\text{point}}) \leftarrow v(d)$.   ▷ *Initialize record by atom valence.*

5:      Set $r(i_{\text{point}}) \leftarrow r(i_{\text{point}}) - o(\tilde{d})$.   ▷ *Update record using previously added bond vertex.*

6:      Set $\mathcal{D} \leftarrow \{x | x \in \mathcal{X}_{\text{bond}}, o(x) > r(i_{\text{point}})\}$.   ▷ *Reject bond orders higher than the record.*

7:      **if** $r(i_{\text{point}}) < \min_{x \in \mathcal{X}_{\text{bond}}} o(x)$ **then**

8:          Set $\mathcal{D} \leftarrow \mathcal{D} \cup \{\texttt{"("}, \texttt{"*"}\}$.   ▷ *Reject decisions requiring minimal amount of valence.*

9: **if** $d \in \mathcal{X}_{\text{bond}}$ **then**

10:      **if** $\tilde{d} \neq \texttt{"("}$ **then**

11:          Set $r(\tilde{i}_{\text{point}}) \leftarrow r(\tilde{i}_{\text{point}}) - o(d)$.   ▷ *Update record of previously added atom vertex.*

12:      **else**

13:          Set $r(\tilde{i}_{\text{point}}) \leftarrow r(\tilde{i}_{\text{point}}) - o(d) + \min_{x \in \mathcal{X}_{\text{bond}}} o(x)$.

                                    ▷ *Update previously added atom vertex considering pre-allocated valence.*

14:      Set $\mathcal{D} \leftarrow \{x | x \in \mathcal{X}_{\text{atom}}, v(x) < r(i_{\text{point}}))\}$.   ▷ *Reject atom valence lower than bond order.*

15:      Set $\mathcal{D} \leftarrow \mathcal{D} \cup \{x | x \in \mathcal{L}_{\text{res}}, r(x) < o(d) - \min_{x \in \mathcal{X}_{\text{bond}}} o(x)\}$.

                                    ▷ *Reject residual edge candidates with valence lower than bond order.*

16: **if** $d = \texttt{"("}$ **then**

17:      Set $r(i_{\text{point}}) \leftarrow r(i_{\text{point}}) - \min_{x \in \mathcal{X}_{\text{bond}}} o(x)$.   ▷ *Pre-allocate minimum bond order.*

18:      Set $\mathcal{D} \leftarrow \{x | x \in \mathcal{X}_{\text{bond}}, o(x) > r(i_{\text{point}})\}$.   ▷ *Reject bond orders higher than the record.*

19: **if** $d = \texttt{")"}$ **then**

20:      Set $\mathcal{D} \leftarrow \emptyset$

21: **if** $d = \texttt{"*"}$ **then**

22:      Set $r(i_{\text{point}}) \leftarrow r(i_{\text{point}}) - \min_{x \in \mathcal{X}_{\text{bond}}} o(x)$.   ▷ *Pre-allocate minimum bond order.*

23:      Set $\mathcal{D} \leftarrow \{x | x \in \mathcal{X}_{\text{bond}}, o(x) > r(i_{\text{point}})\}$.   ▷ *Reject bond orders higher than the record.*

24: **if** $d \in \mathcal{L}_{\text{res}}$ **then**

25:      Set $r(d) \leftarrow r(d) + \min_{x \in \mathcal{X}_{\text{bond}}} o(x) - o(x_{i_{\text{point}}})$.   ▷ *Update record of previously added atom vertex using current bond order.*

26:      Set $\mathcal{D} \leftarrow \emptyset$.

D   IMPLEMENTATION DETAILS

In this section, we provide specific details on how we implement the STGG framework for our experiments.

Training detail. For all the experiments, we train the Transformer under STGG framework for 100 epochs with batch size of 128 for all the dataset. We use the AdamW (Loshchilov & Hutter, 2019) optimizer with constant learning rate of 10^{-4}. We use three and six Transformer layers for {QM9, ZINC250K} and MOSES, respectively. The rest of Transformer-related configurations follow that of the original work (Vaswani et al., 2017); we use the attention module with embedding size of 1024 with eight heads, MLP with dimension of 2048, and dropout with probability of 0.1. Using a single Quadro RTX 6000 GPU, it takes approximately three, ten, and 96 hours to fully train the models on QM9, ZINC250K, and MOSES datasets, respectively.

Pre-processing. For the whole dataset, we use the following set of atom vocabularies $\mathcal{X}_{\texttt{atom}}$: { `"CH"`, `"CH2"`, `"CH-"`, `"CH2-"`, `"C"`, `"N-"`, `"NH-"`, `"N"`, `"NH"`, `"N+"`, `"NH+"`, `"NH2+"`, `"NH3+"`, `"O-"`, `"O"`, `"O+"`, `"OH+"`, `"F"`, `"P"`, `"PH"`, `"PH2"`, `"P+"`, `"PH+"`, `"S-"`, `"S"`, `"S+"`, `"SH"`, `"SH+"`, `"Cl"`, `"Br"`, `"I"`, }. Note that we assign different features for the same atom numbers with different number of explicit hydrogens and formal charges. This allows our algorithm to properly allocate maximum valence for each atom feature. Next, we use the bond vocabulary $\mathcal{X}_{\texttt{bond}} = \{$`"-"`, `"="`, `"#"`$\}$, corresponding to bond orders of single, double, and triple, respectively. For explicit calculation of the atom valence during molecular construction, we train our models on kekulized molecules, i.e., aromatic bonds are fixed to single or double bonds.

E   EXAMPLE OF GENERATED MOLECULES

Figure 7: Example of molecules generated from the QM9 dataset.

Figure 8: Example of molecules generated from the ZINC250ᴋ dataset.

Figure 9: Example of molecules generated from the MOSES dataset.

F   OFFLINE OPTIMIZATION OF MOLECULES

In this section, we describe our offline molecular optimization algorithm mainly inspired by existing works in offline reinforcement learning (Schmidhuber, 2019; Chen et al., 2021b; Janner et al., 2021) and offline model-based optimization (Kumar & Levine, 2020).

For maximizing a reward function defined on a molecule, our algorithm consists of two simple steps. First, our offline optimization algorithm trains a conditional generative model $p_\theta(m|\gamma)$ where m is the molecule and γ is the reward function evaluated on the offline dataset of molecules. Next, the reward-conditional generative model samples highly-rewarding molecules by generation conditioned on high values of γ. In particular, we set the value of γ to extrapolate outside the training dataset. Based on the highly expressive power of Transformer architecture, our algorithm can successfully generate highly-rewarding molecules.

G   ADDITIONAL EXPERIMENTAL RESULTS ON MOLECULAR OPTIMIZATION

Figure 10: Top-16 molecules generated under condition $\gamma = 4$.

Figure 11: Top-16 molecules generated under condition $\gamma = 5$.

Figure 12: Top-16 molecules generated under condition $\gamma = 6$.

Figure 13: Top-16 molecules generated under condition $\gamma = 7$.